PROGRAM B: INDEXED FILE ALLOCATION

C PROGRAM

```c
#include <stdio.h>

int main()

{

    int n, indexBlock, blocks[20], i;

    printf("Enter Index Block: ");

    scanf("%d", &indexBlock);

    printf("Enter Number of Blocks: ");

    scanf("%d", &n);

    printf("Enter Block Numbers:\n");

    for (i = 0; i < n; i++)

    {

        scanf("%d", &blocks[i]);

    }

    printf("\nIndex Block : %d\n", indexBlock);

    printf("Allocated Blocks : ");

    for (i = 0; i < n; i++)

    {

        printf("%d ", blocks[i]);

    }

    printf("\n");

    return 0;

}
```

SHELL SCRIPT

```
  GNU nano 8.7.1
#!/bin/bash

echo "Enter Index Block:"
read index

echo "Enter Number of Blocks:"
read n

echo "Enter Block Numbers:"

for ((i = 0; i < n; i++))
do
    read block[$i]
done

echo "Index Block : $index"

echo -n "Allocated Blocks : "

for ((i = 0; i < n; i++))
do
    echo -n "${block[$i]} "
done

echo
```

Output :

```
┌──(ganesh㉿LAPTOP-R3RDH9NG)-[~]
└─$ nano indexeds.sh

┌──(ganesh㉿LAPTOP-R3RDH9NG)-[~]
└─$ chmod +x indexeds.sh

┌──(ganesh㉿LAPTOP-R3RDH9NG)-[~]
└─$ bash indexeds.sh
Enter Index Block:
12
Enter Number of Blocks:
7
Enter Block Numbers:
4
3
2
1
5
6
8
Index Block : 12
Allocated Blocks : 4 3 2 1 5 6 8
```