



US007404935B2

(12) **United States Patent**
Lau et al.

(10) **Patent No.:** **US 7,404,935 B2**
(45) **Date of Patent:** ***Jul. 29, 2008**

(54) **AIR TREATMENT APPARATUS HAVING AN ELECTRODE CLEANING ELEMENT**

(75) Inventors: **Shek Fai Lau**, Foster City, CA (US);
Jimmy Luther Lee, Rohnert Park, CA (US); **Andrew J. Parker**, Novato, CA (US)

(73) Assignee: **Sharper Image Corp.**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 801 days.

This patent is subject to a terminal disclaimer.

1,791,338 A	2/1931	Wintermute
1,869,335 A	7/1932	Day
2,247,409 A	7/1941	Roper
2,327,588 A	8/1943	Bennett
2,359,057 A	9/1944	Skinner
2,509,548 A	5/1950	White
2,949,550 A	8/1960	Brown
2,978,066 A	4/1961	Nodolf

(Continued)

FOREIGN PATENT DOCUMENTS

CN 2174002 Y 8/1994

(21) Appl. No.: **10/685,182**

(22) Filed: **Oct. 14, 2003**

(Continued)

(65) **Prior Publication Data**

US 2004/0079233 A1 Apr. 29, 2004

OTHER PUBLICATIONS

U.S. Appl. No. 09/669,253, filed Sep. 25, 2000, Taylor et al.

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 09/924,624, filed on Aug. 8, 2001, now abandoned, which is a continuation of application No. 09/564,960, filed on May 6, 2000, now Pat. No. 6,350,417, which is a continuation-in-part of application No. 09/186,471, filed on Nov. 5, 1998, now Pat. No. 6,176,977.

Primary Examiner—Kishor Mayekar

(74) *Attorney, Agent, or Firm*—Bell, Boyd & Lloyd LLP

(57)

ABSTRACT

An air conditioner device includes a first electrode array and a second electrode array. A mechanism, that cleans the electrode(s) in a first electrode array, includes a length of flexible insulating material that projects from a base of the second electrode array towards the first electrode array. As a user moves the second electrode array up or down within the conditioner housing, the electrode(s) in the first array are frictionally cleaned.

(51) **Int. Cl.**
B01J 19/08 (2006.01)

(52) **U.S. Cl.** **422/186.04**; 96/29; 96/51

(58) **Field of Classification Search** **422/186.04**;
96/29, 51


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,469,275 A * 10/1923 Moller et al. 96/29

31 Claims, 14 Drawing Sheets



US 7,404,935 B2

Page 2

U.S. PATENT DOCUMENTS

3,018,394 A	1/1962	Brown	5,378,978 A	1/1995	Gallo et al.
3,026,964 A	3/1962	Penney	5,437,713 A	8/1995	Chang
3,412,530 A	11/1968	Cardiff	5,484,472 A	1/1996	Weinberg
3,518,462 A	6/1970	Brown	5,535,089 A	7/1996	Ford et al.
3,581,470 A	6/1971	Aitkenhead et al.	5,565,685 A	10/1996	Czako et al.
3,638,058 A	1/1972	Fritzius	5,578,112 A	11/1996	Krause
3,744,216 A	7/1973	Halloran	5,601,636 A	2/1997	Glucksman
3,981,695 A	9/1976	Fuchs	5,656,063 A	8/1997	Hsu
3,984,215 A	10/1976	Zucker	5,667,564 A	9/1997	Weinberg
4,052,177 A	10/1977	Kide	5,667,565 A	9/1997	Gondar
4,092,134 A	5/1978	Kikuchi	5,669,963 A	9/1997	Horton et al.
4,138,233 A	2/1979	Masuda	5,698,164 A	12/1997	Kishioka et al.
4,209,306 A	6/1980	Feldman et al.	5,702,507 A	12/1997	Wang
4,227,894 A	10/1980	Proynoff	5,779,769 A	7/1998	Jiang
4,231,766 A	11/1980	Spurgin	5,785,631 A	7/1998	Heidecke
4,232,355 A	11/1980	Finger et al.	5,814,135 A	9/1998	Weinberg
4,244,710 A	1/1981	Burger	5,879,435 A	3/1999	Satyapal et al.
4,244,712 A	1/1981	Tongret	5,893,977 A	4/1999	Pucci
4,253,852 A	3/1981	Adams	5,911,957 A	6/1999	Khatchatrian et al.
4,259,452 A	3/1981	Yukuta et al.	5,972,076 A	10/1999	Nichols et al.
4,266,948 A	5/1981	Teague et al.	5,975,090 A	11/1999	Taylor et al.
4,282,014 A	8/1981	Winkler et al.	5,993,738 A	11/1999	Goswami
4,284,420 A	8/1981	Borysiak	5,997,619 A	12/1999	Knuth et al.
4,318,718 A	3/1982	Utsumi et al.	6,019,815 A	2/2000	Satyapal et al.
4,342,571 A	8/1982	Hayashi	6,042,637 A	3/2000	Weinberg
4,357,150 A	11/1982	Masuda et al.	6,063,168 A	5/2000	Nichols et al.
4,386,395 A	5/1983	Francis, Jr.	6,086,657 A	7/2000	Freije
4,413,225 A	11/1983	Donig et al.	6,090,189 A	7/2000	Wikström et al.
4,445,911 A	5/1984	Lind	6,118,645 A	9/2000	Partridge
4,477,263 A	10/1984	Shaver et al.	6,126,722 A	10/2000	Mitchell et al.
4,496,375 A	1/1985	Le Vantine	6,126,727 A	10/2000	Lo
4,502,002 A	2/1985	Ando	6,149,717 A	11/2000	Satyapal et al.
4,509,958 A	4/1985	Masuda et al.	6,149,815 A	11/2000	Sauter
4,516,991 A	5/1985	Kawashima	6,152,146 A	11/2000	Taylor et al.
4,536,698 A	8/1985	Shevalenko et al.	6,163,098 A	12/2000	Taylor et al.
4,587,475 A	5/1986	Finney, Jr. et al.	6,176,977 B1	1/2001	Taylor et al.
4,600,411 A	7/1986	Santamaria	6,182,461 B1	2/2001	Washburn et al.
4,601,733 A	7/1986	Ordines et al.	6,182,671 B1	2/2001	Taylor et al.
4,626,261 A	12/1986	Jorgensen	6,187,271 B1	2/2001	Lee et al.
4,643,745 A	2/1987	Sakakibara et al.	6,193,852 B1	2/2001	Caracciolo et al.
4,659,342 A	4/1987	Lind	6,212,883 B1	4/2001	Kang
4,673,416 A	6/1987	Sakakibara et al.	6,228,149 B1	5/2001	Alenichev et al.
4,674,003 A	6/1987	Zylka	6,251,171 B1	6/2001	Marra et al.
4,686,370 A	8/1987	Blach	6,252,012 B1	6/2001	Egitto et al.
4,689,056 A	8/1987	Noguchi et al.	6,270,733 B1	8/2001	Rodden
4,694,376 A	9/1987	Gesslauer	6,277,248 B1	8/2001	Ishioka et al.
4,713,093 A	12/1987	Hansson	6,282,106 B2	8/2001	Grass
4,713,724 A	12/1987	Voelkel	D449,097 S	10/2001	Smith et al.
4,726,812 A	2/1988	Hirth	D449,679 S	10/2001	Smith et al.
4,726,814 A	2/1988	Weitman	6,302,944 B1	10/2001	Hoenig
4,772,297 A	9/1988	Anzai	6,309,514 B1	10/2001	Conrad et al.
4,779,182 A	10/1988	Mickal et al.	6,312,507 B1	11/2001	Taylor et al.
4,781,736 A	11/1988	Cheney et al.	6,315,821 B1	11/2001	Pillion et al.
4,786,844 A	11/1988	Farrell et al.	6,328,791 B1	12/2001	Pillion et al.
4,789,801 A	12/1988	Lee	6,348,103 B1	2/2002	Ahlborn et al.
4,808,200 A	2/1989	Dallhammer et al.	6,350,417 B1 *	2/2002	Lau et al. 422/186.04
4,811,159 A	3/1989	Foster, Jr.	6,362,604 B1	3/2002	Cravey
4,940,470 A	7/1990	Jaisinghani et al.	6,372,097 B1	4/2002	Chen
4,941,068 A	7/1990	Hofmann	6,373,723 B1	4/2002	Wallgren et al.
5,010,869 A	4/1991	Lee	6,379,427 B1	4/2002	Siess
5,024,685 A	6/1991	Torok et al.	6,391,259 B1	5/2002	Malkin et al.
RE33,927 E	5/1992	Fuzimura	D461,002 S	7/2002	Christianson
5,141,529 A	8/1992	Oakley et al.	6,447,587 B1	9/2002	Pillion et al.
5,183,480 A	2/1993	Rateman et al.	6,451,266 B1	9/2002	Lau et al.
5,196,171 A	3/1993	Peltier	6,464,754 B1	10/2002	Ford
5,215,558 A	6/1993	Moon	6,471,753 B1	10/2002	Ahn et al.
5,217,504 A	6/1993	Johansson	6,497,754 B2	12/2002	Joannou
5,296,019 A	3/1994	Oakley et al.	6,504,308 B1	1/2003	Krichtafovitch et al.
5,302,190 A	4/1994	Williams	6,506,238 B1	1/2003	Endo
5,315,838 A	5/1994	Thompson	6,544,485 B1	4/2003	Taylor
5,316,741 A	5/1994	Sewell et al.	6,576,046 B2	6/2003	Pruette et al.
			6,585,935 B1	7/2003	Taylor et al.
			6,588,434 B2	7/2003	Taylor et al.

6,613,277	B1	9/2003	Monagan
6,635,106	B2	10/2003	Katou et al.
6,680,028	B1	1/2004	Harris
D491,654	S	6/2004	Gatchell et al.
6,794,661	B2	9/2004	Tsukihara et al.
6,893,618	B2	5/2005	Kotlyar et al.
6,897,617	B2	5/2005	Lee
6,899,745	B2	5/2005	Gatchell et al.
6,908,501	B2	6/2005	Reeves et al.
6,958,134	B2	10/2005	Taylor et al.
6,974,560	B2	12/2005	Taylor et al.
6,984,987	B2	1/2006	Taylor et al.
7,056,370	B2	6/2006	Reeves et al.
7,097,695	B2	8/2006	Lau et al.
7,220,295	B2	5/2007	Lau et al.
2001/0004046	A1	6/2001	Taylor et al.
2001/0048906	A1	12/2001	Lau et al.
2002/0069760	A1	6/2002	Pruette et al.
2002/0079212	A1	6/2002	Taylor et al.
2002/0098131	A1	7/2002	Taylor et al.
2002/0100488	A1	8/2002	Taylor et al.
2002/0122751	A1	9/2002	Sinaiko et al.
2002/0122752	A1	9/2002	Taylor et al.
2002/0127156	A1	9/2002	Taylor
2002/0134664	A1	9/2002	Taylor et al.
2002/0134665	A1	9/2002	Taylor et al.
2002/0141914	A1	10/2002	Taylor et al.
2002/0144601	A1	10/2002	Palestro et al.
2002/0146356	A1	10/2002	Sinaiko et al.
2002/0150520	A1	10/2002	Taylor et al.
2002/0152890	A1	10/2002	Leiser
2002/0155041	A1	10/2002	McKinney, Jr. et al.
2002/0170435	A1	11/2002	Joannou
2003/0005824	A1	1/2003	Katou et al.
2003/0209420	A1	11/2003	Taylor et al.
2004/0079233	A1	4/2004	Lau et al.
2004/0170542	A1	9/2004	Taylor
2004/0202547	A1	10/2004	Taylor et al.
2005/0095182	A1	5/2005	Lee
2005/0147545	A1	7/2005	Lau et al.
2005/0152818	A1	7/2005	Botvinnik et al.
2005/0158219	A1	7/2005	Taylor et al.
2005/0183576	A1	8/2005	Taylor et al.
2005/0194246	A1	9/2005	Botvinnik et al.
2005/0194583	A1	9/2005	Taylor et al.
2005/0210902	A1	9/2005	Parker et al.
2005/0232831	A1	10/2005	Taylor et al.
2005/0238551	A1	10/2005	Snyder et al.
2006/0016337	A1	1/2006	Taylor et al.
2006/0018076	A1	1/2006	Taylor et al.
2006/0018811	A1	1/2006	Taylor et al.
2006/0018812	A1	1/2006	Taylor et al.
2006/0021509	A1	2/2006	Taylor et al.
2006/0159594	A1	7/2006	Parker et al.
2006/0203416	A1	9/2006	Taylor et al.
2007/0009406	A1	1/2007	Taylor et al.
2007/0148061	A1	6/2007	Lau et al.
2007/0210734	A1	9/2007	Botvinnik et al.

FOREIGN PATENT DOCUMENTS

CN	1232200	C	7/2002
EP	0433152	A1	12/1990
EP	000157581-0001		6/2004
FR	2690509		10/1993
HK	1044365		10/2002
HK	0410006.9		2/2004
HK	0500059.9		2/2005
JP	10137007		5/1998
JP	11104223		4/1999
JP	2000236914		9/2000
KR	0364082		10/2004
WO	WO00/10713	A1	3/2000

WO	WO 01/47803	A1	7/2001
WO	WO 01/48781	A1	7/2001
WO	WO01/64349	A1	9/2001
WO	WO01/85348	A2	11/2001
WO	WO02/20162	A2	3/2002
WO	WO02/20163	A2	3/2002
WO	WO02/30574	A1	4/2002
WO	WO02/32578	A1	4/2002
WO	WO02/42003	A1	5/2002
WO	WO02/066167	A1	8/2002
WO	WO03/009944	A1	2/2003
WO	WO03/013620	A1	2/2003

OTHER PUBLICATIONS

U.S. Appl. No. 09/924,600, filed Aug. 8, 2001, Taylor et al.
U.S. Appl. No. 10/074,096, filed Feb. 12, 2002, Taylor et al.
U.S. Appl. No. 10/074,347, filed Feb. 12, 2002, Taylor et al.
U.S. Appl. No. 10/074,379, filed Feb. 12, 2002, Taylor et al.
U.S. Appl. No. 10/278,193, filed Oct. 21, 2002, Reeves.
U.S. Appl. No. 10/405,193, filed Apr. 1, 2003, Taylor.
“Zenion Elf Device,” drawing, prior art.
Electrical schematic and promotional material available from Zenion Industries, 7 pages, Aug. 1990.
Promotional material available from Zenion Industries for the Plasma-Pure 100/200/300, 2 pages, Aug. 1990.
Promotional material available from Zenion Industries for the Plasma-Tron, 2 pages, Aug. 1990.
Lentek Silā™ Plug-In Air Purifier/Deodorizer product box copy-righted 1999, 13 pages.
Holmes HAP 650/ Bionaire BAP 650, Holmes/ Bionaire, Dec. 2003, or earlier.
Brookstone ESP, Brookstone, Dec. 2003, or earlier.
Air-O-Swiss AOS 2055D Cool Mist Air Washer, Air-O-Swiss, Jan. 2006, or earlier.
Austin Air Allergy Machine Air Filter, Austin Air, Jan. 2006, or earlier.
Sila Plug-In Air Purifier/Deodorizer, Lentek, Dec. 1999, or earlier.
PERMAtech Ionizing Air Cleaner, Bionaire, Mar. 9, 2007, or earlier.
99% HEPA Air Cleaner, Bionaire, Mar. 9, 2007, or earlier.
Air Exchange Delivery System, Bionaire, Mar. 9, 2007, or earlier.
Purif-Ion ICP-250, Purif-Ion, Dec. 2004, or earlier.
Air Cleaner, Electrolux, Mar. 9, 2007, or earlier.
Ionic Tower UV Silent Air Purifier Germicidal Protection, Fresh Air Express, Aug. 2005, or earlier.
Surround Air Ionic Air Purifier, Surround Air, Nov. 2003, or earlier.
LifeWise Ultra Air Purifier, LifeWise, Apr. 29, 2004.
Neo-Tec Air Purifier with Anion Generator, Neo-Tec, Nov. 2003, or earlier.
Eco Quest Living Air Purifier, EcoQuest, Aug. 2002, or earlier.
Anion Cool Fan, Mar. 9, 2007, or earlier.
Moonland Aroma Oxygen Generator, Moonland, Feb. 18, 2006.
Air Innovations Ionic Air Freshener, Air Innovations, Jun. 13, 2003.
Ionic Pet Brush, Mar. 9, 2007, or earlier.
Neo-Tec Air Freshener with Light, Neo-Tec, Jun. 13, 2003.
Enviracaire IFD Air Purifier, Enviracaire, Dec. 2003, or earlier.
Nouveau Enviracaire Air Purifier, Nouveau, Dec. 2003, or earlier.
Ionic Pro Mini Ionic Air Purifier, Ionic Pro, Dec. 2006, or earlier.
Surround Air Air Purifier with Anion Generator, Surround Air, Nov. 2003, or earlier.
Ionic Pro Ionic Air Purifier, Ionic Pro, Dec. 2005, or earlier.
Ionic Pro Ionic Air Purifier, Ionic Pro, Dec. 2006, or earlier.
Neo-Tec Ionic Air Purification System, Neo-Tec, Jun. 13, 2003.
Jenn-Air Air Purifier, Jenn-Air, Dec. 1996, or earlier.
P3 Direct IonizAir, P3 Direct, Mar. 9, 2007, or earlier.
Honeywell Environizer, Honeywell, Dec. 2002, or earlier.
SABA Air Purifier, SABA, Mar. 9, 2007, or earlier.
Brookstone Pure Ion Travel, Brookstone, Dec. 2003, or earlier.
Neo-Tec Professional Ionic Cleaner, Neo-Tec, Jun. 16, 2003.
Lumipure Air Purifier with Permanent Filtration, Lumipure, Mar. 9, 2007, or earlier.
LifeWise Electronic Air Purifier, LifeWise, Dec. 2004, or earlier.
Trion Console 250 Electronic Air Cleaner, Trion, Apr. 28, 2004.

US 7,404,935 B2

Page 4

Brookstone Pure Ion UV Air Purifier, Brookstone, Dec. 2004, or earlier.

Silent Air Purifier, Mar. 9, 2007, or earlier.

Ionic Pro Turbo Ionic Air Purifier, Ionic Pro, Dec. 2006, or earlier.

Oreck XL Professional Air Purifier, Oreck, Dec. 2006, or earlier.

MKS Ion Systems Analog Ceiling Emitter Ionizer, MKS Ion Systems, Dec. 2006, or earlier.

* cited by examiner




FIG. 1A (PRIOR ART)




FIG. 1B (PRIOR ART)




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 4E




FIG. 4F




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 7E

AIR TREATMENT APPARATUS HAVING AN ELECTRODE CLEANING ELEMENT

PRIORITY CLAIM

This application is a continuation of, and claims priority to, U.S. patent application Ser. No. 09/924,624, now abandoned, entitled "Electrode Self-Cleaning Mechanism for Electro-Kinetic Air Transporter Conditioner Devices", filed Aug. 8, 2001, which is a continuation of U.S. patent application Ser. No. 09/564,960 (now U.S. Pat. No. 6,350,417), entitled "Electrode Self-Cleaning Mechanism for Electro-Kinetic Air Transporter Conditioner Devices", filed May 6, 2000, which is a continuation-in-part from U.S. application Ser. No. 09/186,471, entitled "Electro-Kinetic Air Transporter-Conditioner", filed Nov. 5, 1998, each of which is incorporated by reference herein.

CROSS REFERENCE TO RELATED APPLICATIONS

This application is related to the following commonly-owned co-pending patent applications:

U.S. patent application Ser. No.	Filed
90/007,276	Oct. 29, 2004
11/041,926	Jan. 21, 2005
11/091,243	Mar. 28, 2005
11/062,057	Feb. 18, 2005
11/071,779	Mar. 3, 2005
10/994,869	Nov. 22, 2004
11/007,556	Dec. 8, 2004
10/074,209	Feb. 12, 2002
10/685,182	Oct. 14, 2003
10/944,016	Sep. 17, 2004
10/795,934	Mar. 8, 2004
10/435,289	May 9, 2003
11/064,797	Feb. 24, 2005
11/003,671	Dec. 3, 2004
11/003,035	Dec. 3, 2004
11/007,395	Dec. 8, 2004
10/876,495	Jun. 25, 2004
10/809,923	Mar. 25, 2004
11/004,397	Dec. 3, 2004
10/895,799	Jul. 21, 2004
10/642,927	Aug. 18, 2003
11/823,346	Apr. 12, 2004
10/662,591	Sep. 15, 2003
11/061,967	Feb. 18, 2005
11/150,046	Jun. 10, 2005
11/188,448	Jul. 25, 2005
11/188,478	Jul. 25, 2005
11/293,538	Dec. 2, 2005
11/457,396	Jul. 13, 2006
11/464,139	Aug. 11, 2006
11/694,281	Mar. 30, 2007
11/679,606	Feb. 27, 2007
11/781,078	Jul. 20, 2007

FIELD OF THE INVENTION

This invention relates generally to devices that produce ozone and an electro-kinetic flow of air from which particulate matter has been substantially removed, and more particularly to cleaning the electrodes present in such devices.

BACKGROUND OF THE INVENTION

The use of an electric motor to rotate a fan blade to create an airflow has long been known in the art. Unfortunately, such

fans produce substantial noise, and can present a hazard to children who may be tempted to poke a finger or a pencil into the moving fan blade. Although such fans can produce substantial air flow, e.g., 1,000 ft³/minute or more, substantial electrical power is required to operate the motor, and essentially no conditioning of the flowing air occurs.

It is known to provide such fans with a HEPA-compliant filter element to remove particulate matter larger than perhaps 0.3 μ m. Unfortunately, the resistance to airflow presented by the filter element may require doubling the electric motor size to maintain a desired level of airflow. Further, HEPA-compliant filter elements are expensive, and can represent a substantial portion of the sale price of a HEPA-compliant filter-fan unit. While such filter-fan units can condition the air by removing large particles, particulate matter small enough to pass through the filter element is not removed, including bacteria, for example.

It is also known in the art to produce an air flow using electro-kinetic techniques, by which electrical power is directly converted into a flow of air without mechanically moving components. One such system is described in U.S. Pat. No. 4,789,801 to Lee (1988), depicted herein in simplified form as FIGS. 1A and 1B. Lee's system includes an array of small area ("minisectional") electrodes 20 that is spaced-apart symmetrically from an array of larger area ("maxisectional") electrodes 30. The positive terminal of a pulse generator 40 that outputs a train of high voltage pulses (e.g., 0 to perhaps +5 KV) is coupled to the minisectional array, and the negative pulse generator terminal is coupled to the maxisectional array.

The high voltage pulses ionize the air between the arrays, and an airflow 50 from the minisectional array toward the maxisectional array results, without requiring any moving parts. Particulate matter 60 in the air is entrained within the airflow 50 and also moves towards the maxisectional electrodes 30. Much of the particulate matter is electrostatically attracted to the surface of the maxisectional electrode array, where it remains, thus conditioning the flow of air exiting system 10. Further, the high voltage field present between the electrode arrays can release ozone into the ambient environment, which appears to destroy or at least alter whatever is entrained in the airflow, including for example, bacteria.

In the embodiment of FIG. 1A, minisectional electrodes 20 are circular in cross-section, having a diameter of about 0.003" (0.08 mm), whereas the maxisectional electrodes 30 are substantially larger in area and define a "teardrop" shape in cross-section. The ratio of cross-sectional radii of curvature between the maxisectional and minisectional electrodes is not explicitly stated, but from Lee's figures appears to exceed 10:1. As shown in FIG. 1A herein, the bulbous front surfaces of the maxisectional electrodes face the minisectional electrodes, and the somewhat sharp trailing edges face the exit direction of the airflow. The "sharpened" trailing edges on the maxisectional electrodes apparently promote good electrostatic attachment of particular matter entrained in the airflow. Lee does not disclose how the teardrop shaped maxisectional electrodes are fabricated, but presumably they are produced using a relatively expensive mold-casting or an extrusion process.

In another embodiment shown herein as FIG. 1B, Lee's maxisectional sectional electrodes 30 are symmetrical and elongated in cross-section. The elongated trailing edges on the maxisectional electrodes provide increased area upon which particulate matter entrained in the airflow can attach. Lee states that precipitation efficiency and desired reduction of anion release into the environment can result from including a passive third array of electrodes 70. Understandably,

increasing efficiency by adding a third array of electrodes will contribute to the cost of manufacturing and maintaining the resultant system.

While the electrostatic techniques disclosed by Lee are advantageous over conventional electric fan-filter units, Lee's maxisectional electrodes are relatively expensive to fabricate. Further, increased filter efficiency beyond what Lee's embodiments can produce would be advantageous, especially without including a third array of electrodes.

The invention in applicants' parent application provided a first and second electrode array configuration electro-kinetic air transporter-conditioner having improved efficiency over Lee-type systems, without requiring expensive production techniques to fabricate the electrodes. The condition also permitted user-selection of safe amounts of ozone to be generated.

The second array electrodes were intended to collect particulate matter, and to be user-removable from the transporter-conditioner for regular cleaning to remove such matter from the electrode surfaces. The user must take care, however, to ensure that if the second array electrodes were cleaned with water, that the electrodes are thoroughly dried before reinsertion into the transporter-conditioner unit. If the unit were turned on while moisture from newly cleaned electrodes was allowed to pool within the unit, and moisture wicking could result in high voltage arcing from the first to the second electrode arrays, with possible damage to the unit.

The wire or wire-like electrodes in the first electrode array are less robust than the second array electrodes. (The terms "wire" and "wire-like" shall be used interchangeably herein to mean an electrode either made from a wire or, if thicker or stiffer than a wire, having the appearance of a wire.) In embodiments in which the first array electrodes were user-removable from the transporter-conditioner unit, care was required during cleaning to prevent excessive force from simply snapping the wire electrodes. But eventually the first array electrodes can accumulate a deposited layer or coating of fine ash-like material. If this deposit is allowed to accumulate eventually efficiency of the conditioner-transporter will be degraded. Further, for reasons not entirely understood, such deposits can produce an audible oscillation that can be annoying to persons near the conditioner-transporter.

Thus there is a need for a mechanism by a conditioner-transporter unit can be protected against moisture pooling in the unit as a result of user cleaning. Further there is a need for a mechanism by which the wire electrodes in the first electrode array of a conditioner-transporter can be periodically cleaned. Preferably such cleaning mechanism should be straightforward to implement, should not require removal of the first array electrodes from the conditioner-transporter, and should be operable by a user on a periodic basis.

The present invention provides such a method and apparatus.

SUMMARY OF THE PRESENT INVENTION

Applicants' parent application provides an electro-kinetic system for transporting and conditioning air without moving parts. The air is conditioned in the sense that it is ionized and contains safe amounts of ozone. The electro-kinetic air transporter-conditioner disclosed therein includes a louvered or gridded body that houses an ionizer unit. The ionizer unit includes a high voltage DC inverter that boosts common 110 VAC to high voltage, and a generator that receives the high voltage DC and outputs high voltage pulses of perhaps 10 KV peak-to-peak, although an essentially 100% duty cycle (e.g., high voltage DC) output could be used instead of pulses. The

unit also includes an electrode assembly unit comprising first and second spaced-apart arrays of conducting electrodes, the first array and second array being coupled, respectively, preferably to the positive and negative output ports of the high voltage generator.

The electrode assembly preferably is formed using first and second arrays of readily manufacturable electrode configurations. In the embodiments relevant to this present application, the first array included wire (or wire-like) electrodes. The second array comprised "U"-shaped or "L"-shaped electrodes having one or two trailing surfaces and intentionally large outer surface areas upon which to collect particulate matter in the air. In the preferred embodiments, the ratio between effective radii of curvature of the second array electrodes to the first array electrodes was at least about 20:1.

The high voltage pulses create an electric field between the first and second electrode arrays. This field produces an electro-kinetic airflow going from the first array toward the second array, the airflow being rich in preferably a net surplus of negative ions and in ozone. Ambient air including dust particles and other undesired components (germs, perhaps) enter the housing through the grill or louver openings, and ionized clean air (with ozone) exits through openings on the downstream side of the housing.

The dust and other particulate matter attaches electrostatically to the second array (or collector) electrodes, and the output air is substantially clean of such particulate matter. Further, ozone generated by the transporter-conditioner unit can kill certain types of germs and the like, and also eliminates odors in the output air. Preferably the transporter operates in periodic bursts, and a control permits the user to temporarily increase the high voltage pulse generator output, e.g., to more rapidly eliminate odors in the environment.

Applicants' parent application provided second array electrode units that were very robust and user-removable from the transporter-conditioner unit for cleaning. These second array electrode units could simply be slid up and out of the transporter-conditioner unit, and wiped clean with a moist cloth, and returned to the unit. However on occasion, if electrode units are returned to the transporter-conditioner unit while still wet (from cleaning), moisture pooling can reduce resistance between the first and second electrode arrays to where high voltage arcing results.

Another problem is that over time the wire electrodes in the first electrode array become dirty and can accumulate a deposited layer or coating of fine ash-like material. This accumulated material on the first array electrodes can eventually reduce ionization efficiency. Further, this accumulated coating can also result in the transporter-conditioner unit producing 500 Hz to 5 KHz audible oscillations that can annoy people in the same room as the unit.

In a first embodiment, the present invention extends one or more thin flexible sheets of Mylar or Kapton type material from the lower portion of the removable second array electrode unit. This sheet or sheets faces the first array electrodes and is nominally in a plane perpendicular to the longitudinal axis of the first and second array electrodes. Such sheet material has high voltage breakdown, high dielectric constant, can withstand high temperature, and is flexible. A slit is cut in the distal edge of this sheet for each first array electrode such that each wire first array electrode fits into a slit in this sheet. Whenever the user removes the second electrode array from the transporter-conditioner unit, the sheet of material is also removed. However in the removal process, the sheet of material is also pulled upward, and friction between the inner slit edge surrounding each wire tends to scrape off any coating on the first array electrode. When the second array electrode unit

5

is reinserted into the transporter-conditioner unit, the slits in the sheet automatically surround the associated first electrode array electrode. Thus, there is an up and down scraping action on the first electrode array electrodes whenever the second array electrode unit is removed from, or simply moved up and down within, the transporter-conditioner unit.

Optionally, upwardly projecting pillars can be disposed on the inner bottom surface of the transporter-conditioner unit to deflect the distal edge of the sheet material upward, away from the first array electrodes when the second array electrode unit is fully inserted. This feature reduces the likelihood of the sheet itself lowering the resistance between the two electrode arrays.

In a presently preferred embodiment, the lower ends of the second array electrodes are mounted to a retainer that includes pivotable arms to which a strip of Mylar or Kapton type material is attached. The distal edge of each strip includes a slit, and the each strip (and the slit therein) is disposed to self-align with an associated wire electrode. A pedestal extends downward from the base of the retainer, and when fully inserted in the transporter-conditioner unit, the pedestal extends into a pedestal opening in a sub-floor of the unit. The first electrode array-facing walls of the pedestal opening urge the arms and the strip on each arm to pivot upwardly, from a horizontal to a vertical disposition. This configuration can improve resistance between the electrode arrays.

Yet another embodiment provides a cleaning mechanism for the wires in the first electrode array in which one or more bead-like members surrounds each wire, the wire electrode passing through a channel in the bead. When the transporter-conditioner unit is inverted, top-for-bottom and then bottom-for-top, the beads slide the length of the wire they surround, scraping off debris in the process. The beads embodiments may be combined with any or all of the various sheets embodiments to provide mechanisms allowing a user to safely clean the wire electrodes in the first electrode array in a transporter-conditioner unit.

Other features and advantages of the invention will appear from the following description in which the preferred embodiments have been set forth in detail, in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a plan, cross-sectional view, of a first embodiment of a prior art electro-kinetic air transporter-conditioner system, according to the prior art;

FIG. 1B is a plan, cross-sectional view, of a second embodiment of a prior art electro-kinetic air transporter-conditioner system, according to the prior art;

FIG. 2A is a perspective view of a preferred embodiment of the present invention;

FIG. 2B is a perspective view of the embodiment of FIG. 2A, with the second array electrode assembly partially withdrawn depicting a mechanism for self-cleaning the first array electrode assembly, according to the present invention;

FIG. 3 is an electrical block diagram of the present invention;

FIG. 4A is a perspective block diagram showing a first embodiment for an electrode assembly, according to the present invention;

FIG. 4B is a plan block diagram of the embodiment of FIG. 4A;

FIG. 4C is a perspective block diagram showing a second embodiment for an electrode assembly, according to the present invention;

6

FIG. 4D is a plan block diagram of a modified version of the embodiment of FIG. 4C;

FIG. 4E is a perspective block diagram showing a third embodiment for an electrode assembly, according to the present invention;

FIG. 4F is a plan block diagram of the embodiment of FIG. 4E;

FIG. 5A is a perspective view of an electrode assembly depicting a first embodiment of a mechanism to clean first electrode array electrodes, according to the present invention;

FIG. 5B is a side view depicting an electrode cleaning mechanism as shown in FIG. 5A, according to the present invention;

FIG. 5C is a plan view of the electrode cleaning mechanism shown in FIG. 5B, according to the present invention;

FIG. 6A is a perspective view of a pivotable electrode cleaning mechanism, according to the present invention;

FIGS. 6B-6D depict the cleaning mechanism of FIG. 6A in various positions, according to the present invention;

FIGS. 7A-7E depict cross-sectional views of bead-like mechanisms to clean first electrode array electrodes, according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

FIGS. 2A and 2B depict an electro-kinetic air transporter-conditioner system **100** whose housing **102** includes preferably rear-located intake vents or louvers **104** and preferably front and side-located exhaust vents **106**, and a base pedestal **108**. Internal to the transporter housing is an ion generating unit **160**, preferably powered by an AC:DC power supply that is energizable or excitable using switch **S1**. Ion generating unit **160** is self-contained in that other than ambient air, nothing is required from beyond the transporter housing, save external operating potential, for operation of the present invention.

The upper surface of housing **102** includes a user-liftable handle member **112** to which is affixed a second array **240** of electrodes **242** within an electrode assembly **220**. Electrode assembly **220** also comprises a first array of electrodes **230**, shown here as a single wire or wire-like electrode **232**. In the embodiment shown, lifting member **112** upward lifts second array electrodes **240** up and, if desired, out of unit **100**, while the first electrode array **230** remains within unit **100**. In FIG. 2B, the bottom ends of second array electrode **242** are connected to a member **113**, to which is attached a mechanism **500** for cleaning the first electrode array electrodes, here electrode **232**, whenever handle member **112** is moved upward or downward by a user. FIGS. 5A-7E, described later herein, provide further details as to various mechanisms **500** for cleaning wire or wire-like electrodes **232** in the first electrode array **230**, and for maintaining high resistance between the first and second electrode arrays **220**, **230** even if some moisture is allowed to pool within the bottom interior of unit **100**.

The first and second arrays of electrodes are coupled in series between the output terminals of ion generating unit **160**, as best seen in FIG. 3. The ability to lift handle **112** provides ready access to the electrodes comprising the electrode assembly, for purposes of cleaning and, if necessary, replacement. The general shape of the invention shown in FIGS. 2A and 2B is not critical. The top-to-bottom height of the preferred embodiment is perhaps 1 m, with a left-to-right width of perhaps 15 cm, and a front-to-back depth of perhaps 10 cm, although other dimensions and shapes may of course be used. A louvered construction provides ample inlet and

outlet venting in an economical housing configuration. There need be no real distinction between vents **104** and **106**, except their location relative to the second array electrodes, and indeed a common vent could be used. These vents serve to ensure that an adequate flow of ambient air may be drawn into or made available to the unit **100**, and that an adequate flow of ionized air that includes safe amounts of O_3 flows out from unit **130**.

As will be described, when unit **100** is energized with **S1**, high voltage output by ion generator **160** produces ions at the first electrode array, which ions are attracted to the second electrode array. The movement of the ions in an "IN" to "OUT" direction carries with them air molecules, thus electrokinetically producing an outflow of ionized air. The "IN" notation in FIGS. 2A and 2B denote the intake of ambient air with particulate matter **60**. The "OUT" notation in the figures denotes the outflow of cleaned air substantially devoid of the particulate matter, which adheres electrostatically to the surface of the second array electrodes. In the process of generating the ionized air flow, safe amounts of ozone (O_3) are beneficially produced. It may be desired to provide the inner surface of housing **102** with an electrostatic shield to reduce detectable electromagnetic radiation. For example, a metal shield could be disposed within the housing, or portions of the interior of the housing could be coated with a metallic paint to reduce such radiation.

As best seen in FIG. 3, ion generating unit **160** includes a high voltage generator unit **170** and circuitry **180** for converting raw alternating voltage (e.g., 117 VAC) into direct current ("DC") voltage. Circuitry **180** preferably includes circuitry controlling the shape and/or duty cycle of the generator unit output voltage (which control is altered with user switch **S2**). Circuitry **180** preferably also includes a pulse mode component, coupled to switch **S3**, to temporarily provide a burst of increased output ozone. Circuitry **180** can also include a timer circuit and a visual indicator such as a light emitting diode ("LED"). The LED or other indicator (including, if desired, audible indicator) signals when ion generation is occurring. The timer can automatically halt generation of ions and/or ozone after some predetermined time, e.g., 30 minutes. indicator(s), and/or audible indicator(s).

As shown in FIG. 3, high voltage generator unit **170** preferably comprises a low voltage oscillator circuit **190** of perhaps 20 KHz frequency, that outputs low voltage pulses to an electronic switch **200**, e.g., a thyristor or the like. Switch **200** switchably couples the low voltage pulses to the input winding of a step-up transformer **T1**. The secondary winding of **T1** is coupled to a high voltage multiplier circuit **210** that outputs high voltage pulses. Preferably the circuitry and components comprising high voltage pulse generator **170** and circuit **180** are fabricated on a printed circuit board that is mounted within housing **102**. If desired, external audio input (e.g., from a stereo tuner) could be suitably coupled to oscillator **190** to acoustically modulate the kinetic airflow produced by unit **160**. The result would be an electrostatic loudspeaker, whose output airflow is audible to the human ear in accordance with the audio input signal. Further, the output air stream would still include ions and ozone.

Output pulses from high voltage generator **170** preferably are at least 10 KV peak-to-peak with an effective DC offset of perhaps half the peak-to-peak voltage, and have a frequency of perhaps 20 KHz. The pulse train output preferably has a duty cycle of perhaps 10%, which will promote battery lifetime. Of course, different peak-peak amplitudes, DC offsets, pulse train waveshapes, duty cycle, and/or repetition frequencies may instead be used. Indeed, a 100% pulse train (e.g., an essentially DC high voltage) may be used, albeit with shorter

battery lifetime. Thus, generator unit **170** may (but need not) be referred to as a high voltage pulse generator.

Frequency of oscillation is not especially critical but frequency of at least about 20 KHz is preferred as being inaudible to humans. If pets will be in the same room as the unit **100**, it may be desired to utilize an even higher operating frequency, to prevent pet discomfort and/or howling by the pet. As noted with respect to FIGS. 5A-6E, to reduce likelihood of audible oscillations, it is desired to include at least one mechanism to clean the first electrode array **230** elements **232**.

The output from high voltage pulse generator unit **170** is coupled to an electrode assembly **220** that comprises a first electrode array **230** and a second electrode array **240**. Unit **170** functions as a DC:DC high voltage generator, and could be implemented using other circuitry and/or techniques to output high voltage pulses that are input to electrode assembly **220**.

In the embodiment of FIG. 3, the positive output terminal of unit **170** is coupled to first electrode array **230**, and the negative output terminal is coupled to second electrode array **240**. This coupling polarity has been found to work well, including minimizing unwanted audible electrode vibration or hum. An electrostatic flow of air is created, going from the first electrode array towards the second electrode array. (This flow is denoted "OUT" in the figures.) Accordingly electrode assembly **220** is mounted within transporter system **100** such that second electrode array **240** is closer to the OUT vents and first electrode array **230** is closer to the IN vents.

When voltage or pulses from high voltage pulse generator **170** are coupled across first and second electrode arrays **230** and **240**, it is believed that a plasma-like field is created surrounding electrodes **232** in first array **230**. This electric field ionizes the ambient air between the first and second electrode arrays and establishes an "OUT" airflow that moves towards the second array. It is understood that the IN flow enters via vent(s) **104**, and that the OUT flow exits via vent(s) **106**.

It is believed that ozone and ions are generated simultaneously by the first array electrode(s) **232**, essentially as a function of the potential from generator **170** coupled to the first array. Ozone generation may be increased or decreased by increasing or decreasing the potential at the first array. Coupling an opposite polarity potential to the second array electrode(s) **242** essentially accelerates the motion of ions generated at the first array, producing the airflow denoted as "OUT" in the figures. As the ions move toward the second array, it is believed that they push or move air molecules toward the second array. The relative velocity of this motion may be increased by decreasing the potential at the second array relative to the potential at the first array.

For example, if +10 KV were applied to the first array electrode(s), and no potential were applied to the second array electrode(s), a cloud of ions (whose net charge is positive) would form adjacent the first electrode array. Further, the relatively high 10 KV potential would generate substantial ozone. By coupling a relatively negative potential to the second array electrode(s), the velocity of the air mass moved by the net emitted ions increases, as momentum of the moving ions is conserved.

On the other hand, if it were desired to maintain the same effective outflow (OUT) velocity but to generate less ozone, the exemplary 10 KV potential could be divided between the electrode arrays. For example, generator **170** could provide +4 KV (or some other fraction) to the first array electrode(s) and -6 KV (or some other fraction) to the second array electrode(s). In this example, it is understood that the +4 KV

and the -6 KV are measured relative to ground. Understandably it is desired that the unit 100 operate to output safe amounts of ozone. Accordingly, the high voltage is preferably fractionalized with about +4 KV applied to the first array electrode(s) and about -6 KV applied to the second array electrodes.

As noted, outflow (OUT) preferably includes safe amounts of O₃ that can destroy or at least substantially alter bacteria, germs, and other living (or quasi-living) matter subjected to the outflow. Thus, when switch S1 is closed and B1 has sufficient operating potential, pulses from high voltage pulse generator unit 170 create an outflow (OUT) of ionized air and O₃. When S1 is closed, LED will visually signal when ionization is occurring.

Preferably operating parameters of unit 100 are set during manufacture and are not user-adjustable. For example, increasing the peak-to-peak output voltage and/or duty cycle in the high voltage pulses generated by unit 170 can increase air flowrate, ion content, and ozone content. In the preferred embodiment, output flowrate is about 200 feet/minute, ion content is about 2,000,000/cc and ozone content is about 40 ppb (over ambient) to perhaps 2,000 ppb (over ambient). Decreasing the R2/R1 ratio below about 20:1 will decrease flow rate, as will decreasing the peak-to-peak voltage and/or duty cycle of the high voltage pulses coupled between the first and second electrode arrays.

In practice, unit 100 is placed in a room and connected to an appropriate source of operating potential, typically 117 VAC. With S1 energized, ionization unit 160 emits ionized air and preferably some ozone (O₃) via outlet vents 150. The air flow, coupled with the ions and ozone freshens the air in the room, and the ozone can beneficially destroy or at least diminish the undesired effects of certain odors, bacteria, germs, and the like. The air flow is indeed electro-kinetically produced, in that there are no intentionally moving parts within unit 100. (As noted, some mechanical vibration may occur within the electrodes.) As will be described with respect to FIG. 4A, it is desirable that unit 100 actually output a net surplus of negative ions, as these ions are deemed more beneficial to health than are positive ions.

Having described various aspects of the invention in general, preferred embodiments of electrode assembly 220 will now be described. In the various embodiments, electrode assembly 220 will comprise a first array 230 of at least one electrode 232, and will further comprise a second array 240 of preferably at least one electrode 242. Understandably material(s) for electrodes 232 and 242 should conduct electricity, be resilient to corrosive effects from the application of high voltage, yet be strong enough to be cleaned.

In the various electrode assemblies to be described herein, electrode(s) 232 in the first electrode array 230 are preferably fabricated from tungsten. Tungsten is sufficiently robust to withstand cleaning, has a high melting point to retard breakdown due to ionization, and has a rough exterior surface that seems to promote efficient ionization. On the other hand, electrodes 242 preferably will have a highly polished exterior surface to minimize unwanted point-to-point radiation. As such, electrodes 242 preferably are fabricated from stainless steel, brass, among other materials. The polished surface of electrodes 232 also promotes ease of electrode cleaning.

In contrast to the prior art electrodes disclosed by Lee, electrodes 232 and 242, electrodes used in unit 100 are light weight, easy to fabricate, and lend themselves to mass production. Further, electrodes 232 and 242 described herein promote more efficient generation of ionized air, and production of safe amounts of ozone, O₃.

In unit 100, a high voltage pulse generator 170 is coupled between the first electrode array 230 and the second electrode array 240. The high voltage pulses produce a flow of ionized air that travels in the direction from the first array towards the second array (indicated herein by hollow arrows denoted "OUT"). As such, electrode(s) 232 may be referred to as an emitting electrode, and electrodes 242 may be referred to as collector electrodes. This outflow advantageously contains safe amounts of O₃, and exits unit 100 from vent(s) 106.

It is preferred that the positive output terminal or port of the high voltage pulse generator be coupled to electrodes 232, and that the negative output terminal or port be coupled to electrodes 242. It is believed that the net polarity of the emitted ions is positive, e.g., more positive ions than negative ions are emitted. In any event, the preferred electrode assembly electrical coupling minimizes audible hum from electrodes 232 contrasted with reverse polarity (e.g., interchanging the positive and negative output port connections).

However, while generation of positive ions is conducive to a relatively silent airflow, from a health standpoint, it is desired that the output airflow be richer in negative ions, not positive ions. It is noted that in some embodiments, however, one port (preferably the negative port) of the high voltage pulse generator may in fact be the ambient air. Thus, electrodes in the second array need not be connected to the high voltage pulse generator using wire. Nonetheless, there will be an "effective connection" between the second array electrodes and one output port of the high voltage pulse generator, in this instance, via ambient air.

Turning now to the embodiments of FIGS. 4A and 4B, electrode assembly 220 comprises a first array 230 of wire electrodes 232, and a second array 240 of generally "U"-shaped electrodes 242. In preferred embodiments, the number N1 of electrodes comprising the first array will preferably differ by one relative to the number N2 of electrodes comprising the second array. In many of the embodiments shown, N2>N1. However, if desired, in FIG. 4A, addition first electrodes 232 could be added at the out ends of array 230 such that N1>N2, e.g., five electrodes 232 compared to four electrodes 242.

Electrodes 232 are preferably lengths of tungsten wire, whereas electrodes 242 are formed from sheet metal, preferably stainless steel, although brass or other sheet metal could be used. The sheet metal is readily formed to define side regions 244 and bulbous nose region 246 for hollow elongated "U" shaped electrodes 242. While FIG. 4A depicts four electrodes 242 in second array 240 and three electrodes 232 in first array 230, as noted, other numbers of electrodes in each array could be used, preferably retaining a symmetrically staggered configuration as shown. It is seen in FIG. 4A that while particulate matter 60 is present in the incoming (IN) air, the outflow (OUT) air is substantially devoid of particulate matter, which adheres to the preferably large surface area provided by the second array electrodes (see FIG. 4B).

As best seen in FIG. 4B, the spaced-apart configuration between the arrays is staggered such that each first array electrode 232 is substantially equidistant from two second array electrodes 242. This symmetrical staggering has been found to be an especially efficient electrode placement. Preferably the staggering geometry is symmetrical in that adjacent electrodes 232 or adjacent electrodes 242 are spaced-apart a constant distance, Y1 and Y2 respectively. However, a non-symmetrical configuration could also be used, although ion emission and air flow would likely be diminished. Also, it is understood that the number of electrodes 232 and 242 may differ from what is shown.

11

In FIGS. 4A, typically dimensions are as follows: diameter of electrodes 232 is about 0.08 mm, distances Y1 and Y2 are each about 16 mm, distance X1 is about 16 mm, distance L is about 20 mm, and electrode heights Z1 and Z2 are each about 1 m. The width W of electrodes 242 is preferably about 4 mm, and the thickness of the material from which electrodes 242 are formed is about 0.5 mm. Of course other dimensions and shapes could be used. It is preferred that electrodes 232 be small in diameter to help establish a desired high voltage field. On the other hand, it is desired that electrodes 232 (as well as electrodes 242) be sufficiently robust to withstand occasional cleaning.

Electrodes 232 in first array 230 are coupled by a conductor 234 to a first (preferably positive) output port of high voltage pulse generator 170, and electrodes 242 in second array 240 are coupled by a conductor 244 to a second (preferably negative) output port of generator 170. It is relatively unimportant where on the various electrodes electrical connection is made to conductors 234 or 244. Thus, by way of example FIG. 4B depicts conductor 244 making connection with some electrodes 242 internal to bulbous end 246, while other electrodes 242 make electrical connection to conductor 244 elsewhere on the electrode. Electrical connection to the various electrodes 242 could also be made on the electrode external surface providing no substantial impairment of the outflow airstream results.

To facilitate removing the electrode assembly from unit 100 (as shown in FIG. 2B), it is preferred that the lower end of the various electrodes fit against mating portions of wire or other conductors 234 or 244. For example, "cup-like" members can be affixed to wires 234 and 244 into which the free ends of the various electrodes fit when electrode array 220 is inserted completely into housing 102 of unit 100.

The ratio of the effective electric field emanating area of electrode 232 to the nearest effective area of electrodes 242 is at least about 15:1, and preferably is at least 20:1. Thus, in the embodiment of FIG. 4A and FIG. 4B, the ratio $R2/R1 \approx 2 \text{ mm}/0.04 \text{ mm} \approx 50:1$.

In this and the other embodiments to be described herein, ionization appears to occur at the smaller electrode(s) 232 in the first electrode array 230, with ozone production occurring as a function of high voltage arcing. For example, increasing the peak-to-peak voltage amplitude and/or duty cycle of the pulses from the high voltage pulse generator 170 can increase ozone content in the output flow of ionized air. If desired, user-control S2 can be used to somewhat vary ozone content by varying (in a safe manner) amplitude and/or duty cycle. Specific circuitry for achieving such control is known in the art and need not be described in detail herein.

Note the inclusion in FIGS. 4A and 4B of at least one output controlling electrode 243, preferably electrically coupled to the same potential as the second array electrodes. Electrode 243 preferably defines a pointed shape in side profile, e.g., a triangle. The sharp point on electrode(s) 243 causes generation of substantial negative ions (since the electrode is coupled to relatively negative high potential). These negative ions neutralize excess positive ions otherwise present in the output air flow, such that the OUT flow has a net negative charge. Electrode(s) 243 preferably are stainless steel, copper, or other conductor, and are perhaps 20 mm high and about 12 mm wide at the base.

Another advantage of including pointed electrodes 243 is that they may be stationarily mounted within the housing of unit 100, and thus are not readily reached by human hands when cleaning the unit. Were it otherwise, the sharp point on electrode(s) 243 could easily cause cuts. The inclusion of one

12

electrode 243 has been found sufficient to provide a sufficient number of output negative ions, but more such electrodes may be included.

In the embodiment of FIGS. 4A and 4C, each "U"-shaped electrode 242 has two trailing edges that promote efficient kinetic transport of the outflow of ionized air and O_3 . Note the inclusion on at least one portion of a trailing edge of a pointed electrode region 243'. Electrode region 243' helps promote output of negative ions, in the same fashion as was described with respect to FIGS. 4A and 4B. Note, however, the higher likelihood of a user cutting himself or herself when wiping electrodes 242 with a cloth or the like to remove particulate matter deposited thereon. In FIG. 4C and the figures to follow, the particulate matter is omitted for ease of illustration. However, from what was shown in FIGS. 2A-4B, particulate matter will be present in the incoming air, and will be substantially absent from the outgoing air. As has been described, particulate matter 60 typically will be electrostatically precipitated upon the surface area of electrodes 242. As indicated by FIG. 4C, it is relatively unimportant where on an electrode array electrical connection is made. Thus, first array electrodes 232 are shown connected together at their bottom regions, whereas second array electrodes 242 are shown connected together in their middle regions. Both arrays may be connected together in more than one region, e.g., at the top and at the bottom. It is preferred that the wire or strips or other inter-connecting mechanisms be at the top or bottom or periphery of the second array electrodes 242, so as to minimize obstructing stream air movement.

Note that the embodiments of FIGS. 4C and 4D depict somewhat truncated versions of electrodes 242. Whereas dimension L in the embodiment of FIGS. 4A and 4B was about 20 mm, in FIGS. 4C and 4D, L has been shortened to about 8 mm. Other dimensions in FIG. 4C preferably are similar to those stated for FIGS. 4A and 4B. In FIGS. 4C and 4D, the inclusion of point-like regions 246 on the trailing edge of electrodes 242 seems to promote more efficient generation of ionized airflow. It will be appreciated that the configuration of second electrode array 240 in FIG. 4C can be more robust than the configuration of FIGS. 4A and 4B, by virtue of the shorter trailing edge geometry. As noted earlier, a symmetrical staggered geometry for the first and second electrode arrays is preferred for the configuration of FIG. 4C.

In the embodiment of FIG. 4D, the outermost second electrodes, denoted 242-1 and 242-2, have substantially no outermost trailing edges. Dimension L in FIG. 4D is preferably about 3 mm, and other dimensions may be as stated for the configuration of FIGS. 4A and 4B. Again, the $R2/R1$ ratio for the embodiment of FIG. 4D preferably exceeds about 20:1.

FIGS. 4E and 4F depict another embodiment of electrode assembly 220, in which the first electrode array comprises a single wire electrode 232, and the second electrode array comprises a single pair of curved "L"-shaped electrodes 242, in cross-section. Typical dimensions, where different than what has been stated for earlier-described embodiments, are $X1 \approx 12 \text{ mm}$, $Y1 \approx 6 \text{ mm}$, $Y2 \approx 5 \text{ mm}$, and $L1 \approx 3 \text{ mm}$. The effective $R2/R1$ ratio is again greater than about 20:1. The fewer electrodes comprising assembly 220 in FIGS. 4E and 4F promote economy of construction, and ease of cleaning, although more than one electrode 232, and more than two electrodes 242 could of course be employed. This embodiment again incorporates the staggered symmetry described earlier, in which electrode 232 is equidistant from two electrodes 242.

Turning now to FIG. 5A, a first embodiment of an electrode cleaning mechanism 500 is depicted. In the embodiment shown, mechanism 500 comprises a flexible sheet of insulat-

13

ing material such as Mylar or other high voltage, high temperature breakdown resistant material, having sheet thickness of perhaps 0.1 mm or so. Sheet 500 is attached at one end to the base or other mechanism 113 secured to the lower end of second electrode array 240. Sheet 500 extends or projects out from base 113 towards and beyond the location of first electrode array 230 electrodes 232. The overall projection length of sheet 500 in FIG. 5A will be sufficiently long to span the distance between base 113 of the second array 240 and the location of electrodes 232 in the first array 230. This span distance will depend upon the electrode array configuration but typically will be a few inches or so. Preferably the distal edge of sheet 500 will extend slightly beyond the location of electrodes 232, perhaps 0.5" beyond. As shown in FIGS. 5A and 5C, the distal edge, e.g., edge closest to electrodes 232, of material 500 is formed with a slot 510 corresponding to the location of an electrode 232. Preferably the inward end of the slot forms a small circle 520, which can promote flexibility.

The configuration of material 500 and slots 510 is such that each wire or wire-like electrode 232 in the first electrode array 230 fits snugly and frictionally within a corresponding slot 510. As indicated by FIG. 5A and shown in FIG. 5C, instead of a single sheet 500 that includes a plurality of slots 510, instead one can provide individual strips 515 of material 500, the distal end of each strip having a slot 510 that will surround an associated wire electrode 232. Note in FIGS. 5B and 5C that sheet 500 or sheets 515 may be formed with holes 119 that can attach to pegs 117 that project from the base portion 113 of the second electrode array 240. Of course other attachment mechanisms could be used including glue, double-sided tape, inserting the array 240-facing edge of the sheet into a horizontal slot or ledge in base member 113, and so forth.

FIG. 5A shows second electrode array 240 in the process of being moved upward, perhaps by a user intending to remove array 240 to remove particulate matter from the surfaces of its electrodes 242. Note that as array 240 moves up (or down), sheet 510 (or sheets 515) also move up (or down). This vertical movement of array 240 produces a vertical movement in sheet 510 or 515, which causes the outer surface of electrodes 232 to scrape against the inner surfaces of an associated slot 510. FIG. 5A, for example, shows debris and other deposits 612 (indicated by x's) on wires 232 above sheet 500. As array 240 and sheet 500 move upward, debris 612 is scraped off the wire electrodes, and falls downward (to be vaporized or collected as particulate matter when unit 100 is again reassembled and turned-on). Thus, the outer surface of electrodes 232 below sheet 500 in FIG. 5A is shown as being cleaner than the surface of the same electrodes above sheet 500, where scraping action has yet to occur.

A user hearing that excess noise or humming emanates from unit 100 might simply turn the unit off, and slide array 240 (and thus sheet 500 or sheets 515) up and down (as indicated by the up/down arrows in FIG. 5A) to scrape the wire electrodes in the first electrode array. This technique does not damage the wire electrodes, and allows the user to clean as required.

As noted earlier, a user may remove second electrode array 240 for cleaning (thus also removing sheet 500, which will have scraped electrodes 232 on its upward vertical path). If the user cleans electrodes 242 with water and returns array 240 to unit 100 without first completely drying the array 240, moisture might form on the upper surface of a horizontally disposed member 550 within unit 100. Thus, as shown in FIG. 5B, it is preferred that an upwardly projecting vane 560 be disposed near the base of each electrode 232 such that when array 240 is fully inserted into unit 100, the distal portion of sheet 500 or preferably sheet strips 515 deflect upward. While

14

sheet 500 or sheets 515 nominally will define an angle θ of about 90° , as base 113 becomes fully inserted into unit 100, the angle θ will increase, approaching 0° , e.g., until the sheet is extending almost vertically upward. If desired, a portion of sheet 500 or sheet strips 515 can be made stiffer by laminating two or more layers of Mylar or other material. For example, the distal tip of strip 515 in FIG. 5B might be one layer thick, whereas the half or so of the strip length nearest electrode 242 might be stiffened with an extra layer or two of Mylar or similar material.

The inclusion of a projecting vane 560 in the configuration of FIG. 5B advantageously disrupted physical contact between sheet 500 or sheet strips 515 and electrodes 232, thus tending to preserve a high ohmic impedance between the first and second electrode arrays 230, 240. The embodiment of FIGS. 6A-6D advantageously serves to pivot sheet 500 or sheet strips 515 upward, essentially parallel to electrodes 232, to help maintain a high impedance between the first and second electrode arrays. Note the creation of an air gap 513 resulting from the upward deflection of the slit distal tip of strip 515 in FIG. 5B.

In FIG. 6A, the lower edges of second array electrodes 242 are retained by a base member 113 from which project arms 677, which can pivot about pivot axle 687. Preferably axle 687 biases arms 677 into a horizontal disposition, e.g., such that $\theta \approx 90^\circ$. Arms 645 project from the longitudinal axis of base member 113 to help member 113 align itself within an opening 655 formed in member 550, described below. Preferably base member 113 and arms 677 are formed from a material that exhibits high voltage breakdown and can withstand high temperature. Ceramic is a preferred material (if cost and weight were not considered), but certain plastics could also be used. The unattached tip of each arm 677 terminates in a sheet strip 515 of Mylar, Kapton, or a similar material, whose distal tip terminates in a slot 510. It is seen that the pivotable arms 677 and sheet strips 515 are disposed such that each slot 510 will self-align with a wire or wire-like electrode 232 in first array 230. Electrodes 232 preferably extend from pylons 627 on a base member 550 that extends from legs 565 from the internal bottom of the housing of the transporter-conditioner unit. To further help maintain high impedance between the first and second electrode arrays, base member 550 preferably includes a barrier wall 665 and upwardly extending vanes 675. Vanes 675, pylons 627, and barrier wall 665 extend upward perhaps an inch or so, depending upon the configuration of the two electrode be formed integrally, e.g., by casting, from a material that exhibits high voltage breakdown and can withstand high temperature, ceramic, or certain plastics for example. As best seen in FIG. 6A, base member 550 includes an opening 655 sized to receive the lower portion of second electrode array base member 113. In FIGS. 6A and 6B, arms 677 and sheet material 515 are shown pivoting from base member 113 about axis 687 a tan angle $\theta \approx 90^\circ$. In this disposition, an electrode 232 will be within the slot 510 formed at the distal tip of each sheet material member 515.

Assume that a user had removed second electrode array 240 completely from the transporter-conditioner unit for cleaning, and that FIGS. 6A and 6B depict array 240 being reinserted into the unit. The coiled spring or other bias mechanism associated with pivot axle 687 will urge arms 677 into an approximate $\theta \approx 90^\circ$ orientation as the user inserts array 240 into unit 100. Side projections 645 help base member 113 align properly such that each wire or wire-like electrode 232 is caught within the slot 510 of a member 515 on an arm 677. As the user slides array 240 down into unit 100, there will be a scraping action between the portions of sheet member 515

15

on either side of a slot **510**, and the outer surface of an electrode **232** that is essentially captured within the slot. This friction will help remove debris or deposits that may have formed on the surface of electrodes **232**. The user may slide array **240** up and down the further promote the removal of debris or deposits from elements **232**.

In FIG. **6C** the user has slid array **240** down almost entirely into unit **100**. In the embodiment shown, when the lowest portion of base member **232** is perhaps an inch or so above the planar surface of member **550**, the upward edge of a vane **675** will strike the a lower surface region of a projection arm **677**. The result will be to pivot arm **677** and the attached slit-member **515** about axle **687** such that the angle θ decreases. In the disposition shown in FIG. **6C**, $\theta \approx 45^\circ$ and slit-contact with an associated electrode **232** is no longer made.

In FIG. **6D**, the user has firmly urged array **240** fully downward into transporter-conditioner unit **100**. In this disposition, as the projecting bottommost portion of member **113** begins to enter opening **655** in member **550** (see FIG. **6A**), contact between the inner wall **657** portion of member **550** urges each arm **677** to pivot fully upward, e.g., $\theta \approx 0^\circ$. Thus in the fully inserted disposition shown in FIG. **6D**, each slit electrode cleaning member **515** is rotated upward parallel to its associated electrode **232**. As such, neither arm **677** nor member **515** will decrease impedance between first and second electrode arrays **230**, **240**. Further, the presence of vanes **675** and barrier wall **665** further promote high impedance.

Thus, the embodiments shown in FIGS. **5A-6D** depict alternative configurations for a cleaning mechanism for a wire or wire-like electrode in a transporter-conditioner unit.

Turning now to FIGS. **7A-7E**, various bead-like mechanisms are shown for cleaning deposits from the outer surface of wire electrodes **232** in a first electrode array **230** in a transporter-converter unit. In FIG. **7A** a symmetrical bead **600** is shown surrounding wire element **232**, which is passed through bead channel **610** at the time the first electrode array is fabricated. Bead **600** is fabricated from a material that can withstand high temperature and high voltage, and is not likely to char, ceramic or glass, for example. While a metal bead would also work, an electrically conductive bead material would tend slightly to decrease the resistance path separating the first and second electrode arrays, e.g., by approximately the radius of the metal bead. In FIG. **7A**, debris and deposits **612** on electrode **232** are depicted as "x's". In FIG. **7A**, bead **600** is moving in the direction shown by the arrow relative to wire **232**. Such movement can result from the user inverting unit **100**, e.g., turning the unit upside down. As bead **600** slides in the direction of the arrow, debris and deposits **612** scrape against the interior walls of channel **610** and are removed. The removed debris can eventually collect at the bottom interior of the transporter-conditioner unit. Such debris will be broken down and vaporized as the unit is used, or will accumulate as particulate matter on the surface of electrodes **242**. If wire **232** has a nominal diameter of say 0.1 mm, the diameter of bead channel **610** will be several times larger, perhaps 0.8 mm or so, although greater or lesser size tolerances may be used. Bead **600** need not be circular and may instead be cylindrical as shown by bead **600'** in FIG. **7A**. A circular bead may have a diameter in the range of perhaps 0.3" to perhaps 0.5". A cylindrical bead might have a diameter of say 0.3" and be about 0.5" tall, although different sizes could of course be used.

As indicated by FIG. **7A**, an electrode **232** may be strung through more than one bead **600**, **600'**. Further, as shown by FIGS. **7B-7D**, beads having different channel symmetries and orientations may be used as well. It is to be noted that while it may be most convenient to form channels **610** with circular

16

cross-sections, the cross-sections could in fact be non-circular, e.g., triangular, square, irregular shape, etc.

FIG. **7B** shows a bead **600** similar to that of FIG. **7A**, but wherein channel **610** is formed off-center to give asymmetry to the bead. An off-center channel will have a mechanical moment and will tend to slightly tension wire electrode **232** as the bead slides up or down, and can improve cleaning characteristics. For ease of illustration, FIGS. **7B-7E** do not depict debris or deposits on or removed from wire or wire-like electrode **232**. In the embodiment of FIG. **7C**, bead channel **610** is substantially in the center of bead **600** but is inclined slightly, again to impart a different frictional cleaning action. In the embodiment of FIG. **7D**, beam **600** has a channel **610** that is both off center and inclined, again to impart a different frictional cleaning action. In general, asymmetrical bead channel or through-opening orientations are preferred.

FIG. **7E** depicts an embodiment in which a bell-shaped walled bead **620** is shaped and sized to fit over a pillar **550** connected to a horizontal portion **560** of an interior bottom portion of unit **100**. Pillar **550** retains the lower end of wire or wire-like electrode **232**, which passes through a channel **630** in bead **620**, and if desired, also through a channel **610** in another bead **600**. Bead **600** is shown in phantom in FIG. **7E** to indicate that it is optional.

Friction between debris **612** on electrode **232** and the mouth of channel **630** will tend to remove the debris from the electrode as bead **620** slides up and down the length of the electrode, e.g., when a user inverts transporter-conditioner unit **100**, to clean electrodes **232**. It is understood that each electrode **232** will include its own bead or beads, and some of the beads may have symmetrically disposed channels, while other beads may have asymmetrically disposed channels. An advantage of the configuration shown in FIG. **7E** is that when unit **100** is in use, e.g., when bead **620** surrounds pillar **550**, with an air gap therebetween, improved breakdown resistance is provided, especially when bead **620** is fabricated from glass or ceramic or other high voltage, high temperature breakdown material that will not readily char. The presence of an air gap between the outer surface of pillar **550** and the inner surface of the bell-shaped bead **620** helps increase this resistance to high voltage breakdown or arcing, and to charring.

Modifications and variations may be made to the disclosed embodiments without departing from the subject and spirit of the invention as defined by the following claims.

What is claimed is:

1. An air conditioner device, comprising:
 - a housing;
 - an emitter electrode, disposed in said housing;
 - a collector electrode, removably disposed in said housing; and
 - means associated with said collector electrode for frictionally cleaning said emitter electrode when said collector electrode is manually removed from said housing and when said collector electrode is returned to said housing.
2. The device of claim 1, wherein said means for frictionally cleaning includes a length of flexible insulating material having a first end connected with said collector electrode and a second end that extends toward said emitter electrode.
3. The device of claim 2, wherein said length of flexible insulating material comprises a strip or a sheet of flexible insulating material.
4. The device of claim 3, wherein said length of flexible insulating material scrapes against at least a portion of said emitter electrode when said collector electrode is removed from and returned to said housing.
5. The device of claim 1, wherein said means for frictionally cleaning includes a length of flexible insulating material

17

that moves when said collector electrode moves, and wherein said length of flexible insulating material scrapes against at least a portion of said emitter electrode when said collector is moved.

6. The device of claim 5, wherein said length of flexible insulating material comprises a strip or a sheet of flexible insulating material.

7. An air conditioner device, comprising:

a housing;

an emitter electrode, disposed in said housing;

a collector electrode, movably disposed in said housing; and

means associated with said collector electrode for frictionally cleaning said emitter electrode when said collector electrode is moved relative to said housing.

8. The device of claim 7, wherein said means for frictionally cleaning includes a length of flexible insulating material.

9. The device of claim 7, wherein said means for frictionally cleaning includes a length of material.

10. The device of claim 9, wherein said length of material is sufficiently long to span the distance between said emitter electrode and said collector electrode.

11. An air treatment apparatus comprising:

a housing;

an emitter electrode configured to be supported by the housing;

a collector electrode configured to be supported by the housing, the collector electrode being movable between a first position and a second position relative to the housing;

a cleaning element having an inner wall defining an opening sized to receive a portion of the emitter electrode such that the inner wall is at least partially in contact with the emitter electrode;

an arm configured to operatively connect the cleaning element to the collector electrode, the arm being operable to cause the cleaning element to move relative to the emitter electrode during the movement of the collector electrode, the inner wall cleaning the emitter electrode during the movement; and

a voltage generator supported by said housing, the voltage generator being operable to provide a potential difference between said emitter electrode and said collector electrode.

12. The air treatment apparatus of claim 11, wherein said cleaning element is selected from the group consisting of: (a) a length of material defining a slit; (b) a structure defining a substantially circular opening; and (c) a bead.

13. The air treatment apparatus of claim 12, wherein said cleaning element has insulating material.

14. The air treatment apparatus of claim 12, wherein said cleaning element is configured to frictionally clean said emitter electrode.

15. The air treatment apparatus of claim 12, wherein said cleaning element has a flexible characteristic.

16. The air treatment apparatus of claim 11, wherein the emitter electrode is selected from the group consisting of: (a) a rectangular-shaped electrode; (b) a wire-shaped electrode; and (c) a circular-shaped electrode.

17. The air treatment apparatus of claim 11, wherein the collector electrode is selected from the group consisting of: (a) a rectangular-shaped electrode; (b) a wire-shaped electrode; and (c) a circular-shaped electrode.

18. The air treatment apparatus of claim 11, wherein the collector electrode is configured to be removable from said housing.

18

19. The air treatment apparatus of claim 18, wherein said collector electrode is operatively coupled to a handle.

20. The air treatment apparatus of claim 11, wherein the inner wall is configured to clean the emitter electrode by scraping against at least a portion of said emitter electrode.

21. An air conditioner device, comprising:

a housing;

an emitter electrode, disposed in said housing such that said emitter electrode is stationary within said housing;

a collector electrode, removably disposed in said housing such that said collector electrode can be manually removed from said housing and then returned to a resting position in said housing;

a high voltage generator disposed in said housing, to provide a potential difference between said emitter electrode and said collector electrode when said collector electrode is in the resting position in said housing; a member connected to said collector electrode; and

a flexible length extending from said member toward said emitter electrode; wherein flexible length scrapes against at least a portion of said emitter electrode as said collector is manually removed from and returned to said housing, to thereby clean said emitter electrode.

22. The device of claim 21, further comprising a handle to assist a user in manually removing and returning said collector electrode.

23. The device of claim 22, further comprising a vane projecting from an interior region of said housing such that said vane contacts said length and urges said length upward and away from said emitter electrode when said collector electrode is in the resting position in said housing.

24. The device of claim 23, wherein said length disengages from contact with said vane, and scrapes against at least a portion of said emitter electrode, soon after said collector electrode is lifted from the resting position, in the process of being removed from said housing.

25. An air conditioner device, comprising:

a housing;

an emitter electrode, disposed in said housing such that said emitter electrode is stationary within said housing;

a collector electrode, movably disposed in said housing such that said collector electrode can be moved from and then returned to a resting position in said housing;

a high voltage generator disposed in said housing, to provide a high voltage potential to said collector electrode when said collector electrode is in the resting position; a member connected to said collector electrode; and

a flexible length extending from said member toward said emitter electrode; wherein flexible length scrapes against at least a portion of said emitter electrode as said collector is moved relative to said housing, to thereby clean said emitter electrode.

26. An air conditioner device, comprising:

an upstanding, elongated housing;

an ion generating unit positioned in said housing, including: an emitter electrode; a movable collector electrode, elongated along the direction of elongation of said housing; and

a user-liftable handle secured to said movable collector electrode, said handle accessible through an opening in a top portion of said housing, to assist a user with lifting said collector electrode from a resting position within said housing; and

a cleaning member associated with said collector electrode, wherein said cleaning member frictionally clean said emitter electrode when said collector is lifted using said handle.

19

27. The air conditioner device of claim 26, wherein said cleaning member has an insulating material.

28. The air conditioner device of claim 26, including an arm configured to operatively couple the cleaning member to the collector electrode.

29. The air conditioner device of claim 28, wherein said cleaning member is selected from the group consisting of: (a) a length of material defining an opening; (b) a length of material defining a slit; (c) a structure defining an opening; (d) a structure defining a substantially circular opening; and (e) a bead defining an opening.

20

30. The air conditioner device of claim 26, wherein the collector electrode is selected from the group consisting of: (a) a rectangular-shaped electrode; (b) a wire-shaped electrode; and (c) a circular-shaped electrode.

31. The air conditioner device of claim 26, wherein the emitter electrode is selected from the group consisting of: (a) a rectangular-shaped electrode; (b) a wire-shaped electrode; and (c) a circular-shaped electrode.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,404,935 B2
APPLICATION NO. : 10/685182
DATED : July 29, 2008
INVENTOR(S) : Shek Fai Lau et al.

Page 1 of 1


It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the title page, under Related U.S. Application Data, Paragraph (63), line 3, please replace "May 6, 2000" with --May 4, 2000--.

In column 1, line 13, please replace "May 6, 2000" with --May 4, 2000--.

Signed and Sealed this

Twenty-fifth Day of August, 2009

A handwritten signature in black ink that reads "David J. Kappos". The signature is written in a cursive, flowing style with a large initial 'D' and a stylized 'K'.

David J. Kappos
Director of the United States Patent and Trademark Office