US007318856B2

(12) **United States Patent**
Taylor et al.

(10) **Patent No.: US 7,318,856 B2**
(45) **Date of Patent: Jan. 15, 2008**

(54) **AIR TREATMENT APPARATUS HAVING AN ELECTRODE EXTENDING ALONG AN AXIS WHICH IS SUBSTANTIALLY PERPENDICULAR TO AN AIR FLOW PATH**

(75) Inventors: **Charles E. Taylor**, Punta Gorda, FL (US); **Andrew J. Parker**, Novato, CA (US)

(73) Assignee: **Sharper Image Corporation**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/003,035**

(22) Filed: **Dec. 3, 2004**

(65) **Prior Publication Data**

US 2005/0183576 A1 Aug. 25, 2005

Related U.S. Application Data

(63) Continuation-in-part of application No. 10/074,096, filed on Feb. 12, 2002, now Pat. No. 6,974,560, which is a continuation-in-part of application No. 09/924, 624, filed on Aug. 8, 2001, now abandoned, which is a continuation-in-part of application No. 09/774,198, filed on Jan. 29, 2001, now Pat. No. 6,544,485, which is a continuation of application No. 09/564,960, filed on May 4, 2000, now Pat. No. 6,350,417, which is a continuation-in-part of application No. 09/186,471, filed on Nov. 5, 1998, now Pat. No. 6,176,977.

(60) Provisional application No. 60/538,973, filed on Jan. 22, 2004, provisional application No. 60/341,179, filed on Dec. 13, 2001, provisional application No. 60/306,479, filed on Jul. 18, 2001.

(51) **Int. Cl.**
B03C 3/016 (2006.01)

(52) **U.S. Cl.** **96/16**; 96/39; 96/63; 96/80; 96/94; 96/224; 422/186.04; 422/186.3

(58) **Field of Classification Search** 96/60–65, 96/96, 97, 16, 224, 39, 94, 80–82; 55/DIG. 38; 95/78; 422/186.04, 186.3
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

653,421 A 7/1900 Lorey

(Continued)

FOREIGN PATENT DOCUMENTS

CN 2111112 U 7/1972

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 60/104,573, filed Oct. 16, 1998, Krichtafovitch.

(Continued)

Primary Examiner—Richard L. Chiesa
(74) *Attorney, Agent, or Firm*—Bell, Boyd & Lloyd LLP

(57) **ABSTRACT**

An air transporter-conditioner device is disclosed that can include an elongated housing having a bottom, a top and an elongated side wall. The housing can have an inlet located adjacent to the bottom and an outlet located adjacent to the elongated side wall, an emitter electrode and a collector electrode and a high voltage generator operably connected to both electrodes. An impeller can be used to draw air into the housing through the inlet and direct the air toward the outlet. The housing can also include a second elongated side wall and a baffle which can include a plurality of deflectors positioned along the second elongated side wall. The baffle can include a plurality of elongated columns of varying lengths and each column can include a deflector. The device can further include a second inlet located adjacent to the elongated side wall and a germicidal lamp located inside the elongated housing.

27 Claims, 25 Drawing Sheets



U.S. PATENT DOCUMENTS

895,729 A 8/1908 Carlborg
995,958 A 6/1911 Goldberg
1,791,338 A 2/1931 Wintermute
1,869,335 A 7/1932 Day
1,882,949 A 10/1932 Ruder
2,129,783 A 9/1938 Penney
2,247,409 A 7/1941 Rpoer
2,327,588 A 8/1943 Bennett
2,359,057 A 9/1944 Skinner
2,509,548 A 5/1950 White
2,590,447 A 3/1952 Nord et al.
2,949,550 A 8/1960 Brown
2,978,066 A 4/1961 Nodolf
3,018,394 A 1/1962 Brown
3,026,964 A 3/1962 Penney
3,295,440 A * 1/1967 Rarey et al. 101/114
3,374,941 A 3/1968 Okress
3,412,530 A 11/1968 Cardiff
3,518,462 A 6/1970 Brown
3,540,191 A 11/1970 Herman
3,581,470 A 6/1971 Aitkenhead et al.
3,638,058 A 1/1972 Fritzius
3,744,216 A 7/1973 Halloran
3,757,803 A * 9/1973 Chiang 131/188
3,768,258 A * 10/1973 Smith et al. 60/275
3,806,763 A 4/1974 Masuda
3,892,927 A 7/1975 Lindenberg
3,945,813 A 3/1976 Iinoya et al.
3,958,960 A 5/1976 Bakke
3,958,961 A 5/1976 Bakke
3,958,962 A 5/1976 Hayashi
3,981,695 A 9/1976 Fuchs
3,984,215 A 10/1976 Zucker
3,988,131 A 10/1976 Kanazawa et al.
4,007,024 A 2/1977 Sallee et al.
4,052,177 A 10/1977 Kide
4,056,372 A 11/1977 Hayashi
4,070,163 A 1/1978 Kolb et al.
4,074,983 A 2/1978 Bakke
4,092,134 A 5/1978 Kikuchi
4,097,252 A 6/1978 Kirchhoff et al.
4,102,654 A 7/1978 Pellin
4,104,042 A 8/1978 Brozenick
4,110,086 A 8/1978 Schwab et al.
4,119,415 A 10/1978 Hayashi et al.
4,126,434 A 11/1978 Keiichi
4,138,233 A 2/1979 Masuda
4,147,522 A 4/1979 Gonas et al.
4,155,792 A 5/1979 Gelhaar et al.
4,171,975 A 10/1979 Kato et al.
4,185,971 A 1/1980 Isahaya
4,189,308 A 2/1980 Feldman
4,205,969 A 6/1980 Matsumoto
4,209,306 A 6/1980 Feldman et al.
4,218,225 A 8/1980 Kirchhoff et al.
4,225,323 A 9/1980 Zarchy et al.
4,227,894 A 10/1980 Proynoff
4,231,766 A 11/1980 Spurgin
4,232,355 A 11/1980 Finger et al.
4,244,710 A 1/1981 Burger
4,244,712 A 1/1981 Tongret
4,251,234 A 2/1981 Chang
4,253,852 A 3/1981 Adams
4,259,093 A 3/1981 Vlastos et al.
4,259,452 A 3/1981 Yukuta et al.
4,259,707 A 3/1981 Penney
4,264,343 A 4/1981 Natarajan et al.
4,266,948 A 5/1981 Teague et al.
4,282,014 A 8/1981 Winkler et al.
4,284,420 A 8/1981 Borysiak
4,289,504 A 9/1981 Scholes
4,293,319 A 10/1981 Claassen, Jr.
4,308,036 A 12/1981 Zahedi et al.
4,315,188 A 2/1982 Cerny et al.
4,318,718 A 3/1982 Utsumi et al.
4,338,560 A 7/1982 Lemley
4,342,571 A 8/1982 Hayashi
4,349,359 A 9/1982 Fitch et al.
4,351,648 A 9/1982 Penney
4,354,861 A 10/1982 Kalt
4,357,150 A 11/1982 Masuda et al.
4,362,632 A 12/1982 Jacob
4,363,072 A 12/1982 Coggins
4,366,525 A 12/1982 Baumgartner
4,369,776 A 1/1983 Roberts
4,375,364 A 3/1983 Van Hoesen et al.
4,380,900 A 4/1983 Linder et al.
4,386,395 A 5/1983 Francis, Jr.
4,391,614 A 7/1983 Rozmus
4,394,239 A 7/1983 Kitzelmann et al.
4,405,342 A 9/1983 Bergman
4,406,671 A 9/1983 Rozmus
4,412,850 A 11/1983 Kurata et al.
4,413,225 A 11/1983 Donig et al.
4,414,603 A 11/1983 Masuda
4,435,190 A 3/1984 Taillet et al.
4,440,552 A 4/1984 Uchiya et al.
4,443,234 A 4/1984 Carlsson
4,445,911 A 5/1984 Lind
4,477,263 A 10/1984 Shaver et al.
4,477,268 A 10/1984 Kalt
4,481,017 A 11/1984 Furlong
4,496,375 A 1/1985 Levantine
4,502,002 A 2/1985 Ando
4,505,724 A 3/1985 Baab
4,509,958 A 4/1985 Masuda et al.
4,514,780 A 4/1985 Brussee et al.
4,515,982 A 5/1985 Lechtken et al.
4,516,991 A 5/1985 Kawashima
4,521,229 A 6/1985 Baker et al.
4,522,634 A 6/1985 Frank
4,534,776 A 8/1985 Mammel et al.
4,536,698 A 8/1985 Shevalenko et al.
4,544,382 A 10/1985 Taillet et al.
4,555,252 A 11/1985 Eckstein
4,569,684 A 2/1986 Ibbott
4,582,961 A 4/1986 Frederiksen
4,587,475 A 5/1986 Finney, Jr. et al.
4,588,423 A 5/1986 Gillingham et al.
4,590,042 A 5/1986 Drage
4,597,780 A 7/1986 Reif
4,597,781 A 7/1986 Spector
4,600,411 A 7/1986 Santamaria
4,601,733 A 7/1986 Ordines et al.
4,604,174 A 8/1986 Bollinger et al.
4,614,573 A 9/1986 Masuda
4,623,365 A 11/1986 Bergman
4,626,261 A 12/1986 Jorgensen
4,632,135 A 12/1986 Lenting et al.
4,632,746 A 12/1986 Bergman
4,636,981 A 1/1987 Ogura
4,643,744 A 2/1987 Brooks
4,643,745 A 2/1987 Sakakibara et al.
4,647,836 A 3/1987 Olsen
4,650,648 A 3/1987 Beer et al.
4,656,010 A 4/1987 Leitzke et al.
4,657,738 A 4/1987 Kanter et al.
4,659,342 A 4/1987 Lind
4,662,903 A 5/1987 Yanagawa
4,666,474 A 5/1987 Cook
4,668,479 A 5/1987 Manabe et al.
4,670,026 A 6/1987 Hoenig
4,673,416 A 6/1987 Sakakibara et al.
4,674,003 A 6/1987 Zylka

4,680,496 A 7/1987 Letournel et al.
4,686,370 A 8/1987 Blach
4,689,056 A 8/1987 Noguchi et al.
4,691,829 A 9/1987 Auer
4,692,174 A 9/1987 Gelfand et al.
4,693,869 A 9/1987 Pfaff
4,694,376 A 9/1987 Gesslauer
4,702,752 A 10/1987 Yanagawa
4,713,092 A 12/1987 Kikuchi et al.
4,713,093 A 12/1987 Hansson
4,713,724 A 12/1987 Voelkel
4,715,870 A 12/1987 Masuda et al.
4,725,289 A 2/1988 Quintilian
4,726,812 A 2/1988 Hirth
4,726,814 A 2/1988 Weitman
4,736,127 A 4/1988 Jacobsen
4,743,275 A 5/1988 Flanagan
4,749,390 A 6/1988 Burnett et al.
4,750,921 A 6/1988 Sugita et al.
4,760,302 A 7/1988 Jacobsen
4,760,303 A 7/1988 Miyake
4,765,802 A 8/1988 Gombos et al.
4,771,361 A 9/1988 Varga
4,772,297 A 9/1988 Anzai
4,779,182 A 10/1988 Mickal et al.
4,781,736 A 11/1988 Cheney et al.
4,786,844 A 11/1988 Farrell et al.
4,789,801 A 12/1988 Lee
4,808,200 A 2/1989 Dallhammer et al.
4,811,159 A 3/1989 Foster, Jr.
4,822,381 A 4/1989 Mosley et al.
4,853,005 A 8/1989 Jaisinghani et al.
4,869,736 A 9/1989 Ivester et al.
4,892,713 A 1/1990 Newman
4,929,139 A 5/1990 Vorreiter et al.
4,940,470 A 7/1990 Jaisinghani et al.
4,940,894 A 7/1990 Morters
4,941,068 A 7/1990 Hofmann
4,941,224 A 7/1990 Saeki et al.
4,944,778 A 7/1990 Yanagawa
4,954,320 A 9/1990 Birmingham et al.
4,955,991 A 9/1990 Torok et al.
4,966,666 A 10/1990 Waltonen
4,967,119 A 10/1990 Torok et al.
4,976,752 A 12/1990 Torok et al.
4,978,372 A 12/1990 Pick
D315,598 S 3/1991 Yamamoto et al.
5,003,774 A 4/1991 Leonard
5,006,761 A 4/1991 Torok et al.
5,010,869 A 4/1991 Lee
5,012,093 A 4/1991 Shimizu
5,012,094 A 4/1991 Hamade
5,012,159 A 4/1991 Torok et al.
5,022,979 A 6/1991 Hijikata et al.
5,024,685 A 6/1991 Torok et al.
5,030,254 A 7/1991 Heyen et al.
5,034,033 A 7/1991 Alsup et al.
5,037,456 A 8/1991 Yu
5,045,095 A 9/1991 You
5,053,912 A 10/1991 Loreth et al.
5,055,115 A * 10/1991 Yikai et al. 96/59
5,059,219 A 10/1991 Plaks et al.
5,061,462 A 10/1991 Suzuki
5,066,313 A 11/1991 Mallory, Sr.
5,072,746 A 12/1991 Kantor
5,076,820 A 12/1991 Gurvitz
5,077,468 A 12/1991 Hamade
5,077,500 A 12/1991 Torok et al.
5,100,440 A 3/1992 Stahel et al.
RE33,927 E 5/1992 Fuzimura
D326,514 S 5/1992 Alsup, Jr. et al.
5,118,942 A 6/1992 Hamade
5,125,936 A 6/1992 Johansson
5,136,461 A 8/1992 Zellweger
5,137,546 A 8/1992 Steinbacher et al.
5,141,529 A 8/1992 Oakley et al.
5,141,715 A 8/1992 Sackinger et al.
D329,284 S 9/1992 Patton
5,147,429 A 9/1992 Bartholomew et al.
5,154,733 A 10/1992 Fujii et al.
5,158,580 A 10/1992 Chang
D332,655 S 1/1993 Lytle et al.
5,180,404 A 1/1993 Loreth et al.
5,183,480 A 2/1993 Raterman et al.
5,196,171 A 3/1993 Peltier
5,198,003 A 3/1993 Haynes
5,199,257 A 4/1993 Colletta et al.
5,210,678 A 5/1993 Lain et al.
5,215,558 A 6/1993 Moon
5,217,504 A 6/1993 Johansson
5,217,511 A 6/1993 Plaks et al.
5,234,555 A 8/1993 Ibbott
5,248,324 A 9/1993 Hara
5,250,267 A 10/1993 Johnson et al.
5,254,155 A 10/1993 Mensi
5,266,004 A 11/1993 Tsumurai et al.
5,271,763 A 12/1993 Jang
5,282,891 A 2/1994 Durham
5,290,343 A 3/1994 Morita et al.
5,296,019 A 3/1994 Oakley et al.
5,302,190 A 4/1994 Williams
5,308,586 A 5/1994 Fritsche et al.
5,315,838 A 5/1994 Thompson
5,316,741 A 5/1994 Sewell et al.
5,330,559 A 7/1994 Cheney et al.
5,348,571 A 9/1994 Weber
5,376,168 A 12/1994 Inculet
5,378,978 A 1/1995 Gallo et al.
5,386,839 A 2/1995 Chen
5,395,430 A 3/1995 Lundgren et al.
5,401,301 A 3/1995 Schulmerich et al.
5,401,302 A 3/1995 Schulmerich et al.
5,403,383 A 4/1995 Jaisinghani
5,405,434 A 4/1995 Inculet
5,407,469 A 4/1995 Sun
5,407,639 A 4/1995 Watanabe et al.
5,417,936 A 5/1995 Suzuki et al.
5,419,953 A 5/1995 Chapman
5,433,772 A 7/1995 Sikora
5,435,817 A 7/1995 Davis et al.
5,435,978 A 7/1995 Yokomi
5,437,713 A 8/1995 Chang
5,437,843 A 8/1995 Kuan
5,445,798 A 8/1995 Ikeda et al.
5,466,279 A 11/1995 Hattori et al.
5,468,454 A 11/1995 Kim
5,474,599 A 12/1995 Cheney et al.
5,484,472 A 1/1996 Weinberg
5,484,473 A 1/1996 Bontempi
5,492,557 A * 2/1996 Vanella 96/16
5,492,678 A 2/1996 Ota et al.
5,501,844 A 3/1996 Kasting, Jr. et al.
5,503,808 A 4/1996 Garbutt et al.
5,503,809 A 4/1996 Coate et al.
5,505,914 A 4/1996 Tona-Serra
5,508,008 A 4/1996 Wasser
5,514,345 A 5/1996 Garbutt et al.
5,516,493 A 5/1996 Bell et al.
5,518,531 A 5/1996 Joannu
5,520,887 A 5/1996 Shimizu et al.
5,525,310 A 6/1996 Decker et al.
5,529,613 A 6/1996 Yavnieli
5,529,760 A 6/1996 Burris
5,532,798 A 7/1996 Nakagami et al.
5,535,089 A 7/1996 Ford et al.
5,536,477 A 7/1996 Cha et al.

5,538,695	A	7/1996	Shinjo et al.	
5,540,761	A	7/1996	Yamamoto	
5,542,967	A	8/1996	Ponizovsky et al.	
5,545,379	A	8/1996	Gray	
5,545,380	A	8/1996	Gray	
5,547,643	A	8/1996	Nomoto et al.	
5,549,874	A	8/1996	Kamiya et al.	
5,554,344	A	9/1996	Duarte	
5,554,345	A	9/1996	Kitchenman	
5,569,368	A	10/1996	Larsky et al.	
5,569,437	A	10/1996	Stiehl et al.	
D375,546	S	11/1996	Lee	
5,571,483	A	11/1996	Pfingstl et al.	
5,573,577	A	11/1996	Joannou	
5,573,730	A	11/1996	Gillum	
5,578,112	A	11/1996	Krause	
5,578,280	A	11/1996	Kazi et al.	
5,582,632	A	12/1996	Nohr et al.	
5,587,131	A	12/1996	Malkin et al.	
D377,523	S	1/1997	Marvin et al.	
5,591,253	A	1/1997	Altman et al.	
5,591,334	A	1/1997	Shimizu et al.	
5,591,412	A	1/1997	Jones et al.	
5,593,476	A	1/1997	Coppom	
5,601,636	A	2/1997	Glucksman	
5,603,752	A	2/1997	Hara	
5,603,893	A	2/1997	Gundersen et al.	
5,614,002	A	3/1997	Chen	
5,616,172	A *	4/1997	Tuckerman et al.	96/16
5,624,476	A	4/1997	Eyraud	
5,630,866	A	5/1997	Gregg	
5,630,990	A	5/1997	Conrad et al.	
5,632,806	A *	5/1997	Galassi	96/16
5,637,198	A	6/1997	Breault	
5,637,279	A	6/1997	Besen et al.	
5,641,342	A	6/1997	Smith et al.	
5,641,461	A	6/1997	Ferone	
5,647,890	A	7/1997	Yamamoto	
5,648,049	A	7/1997	Jones et al.	
5,655,210	A	8/1997	Gregoire et al.	
5,656,063	A	8/1997	Hsu	
5,665,147	A	9/1997	Taylor et al.	
5,667,563	A	9/1997	Silva, Jr.	
5,667,564	A	9/1997	Weinberg	
5,667,565	A	9/1997	Gondar	
5,667,756	A	9/1997	Ho	
5,669,963	A	9/1997	Horton et al.	
5,678,237	A	10/1997	Powell et al.	
5,681,434	A	10/1997	Eastlund	
5,681,533	A	10/1997	Hiromi	
5,698,164	A	12/1997	Kishioka et al.	
5,702,507	A	12/1997	Wang	
D389,567	S	1/1998	Gudefin	
5,733,360	A *	3/1998	Feldman et al.	95/78
5,766,318	A	6/1998	Loreth et al.	
5,779,769	A	7/1998	Jiang	
5,785,631	A	7/1998	Heidecke	
5,792,241	A *	8/1998	Browitt	96/52
5,814,135	A	9/1998	Weinberg	
5,837,035	A *	11/1998	Braun et al.	95/78
5,879,435	A	3/1999	Satyapal et al.	
5,893,977	A	4/1999	Pucci	
5,911,957	A	6/1999	Khatchatrian et al.	
5,951,742	A *	9/1999	Thwaites et al.	95/57
5,972,076	A	10/1999	Nichols et al.	
5,975,090	A	11/1999	Taylor et al.	
5,980,614	A	11/1999	Loreth et al.	
5,993,521	A	11/1999	Loreth et al.	
5,993,738	A	11/1999	Goswani	
5,997,619	A	12/1999	Knuth et al.	
6,019,815	A	2/2000	Satyapal et al.	
6,042,637	A	3/2000	Weinberg	
6,063,168	A	5/2000	Nichols et al.	

6,086,657	A	7/2000	Freije	
6,090,189	A	7/2000	Wikstrom et al.	
6,117,216	A	9/2000	Loreth	
6,118,645	A	9/2000	Partridge	
6,126,722	A	10/2000	Mitchell et al.	
6,126,727	A	10/2000	Lo	
6,149,717	A	11/2000	Satyapal et al.	
6,149,815	A	11/2000	Sauter	
6,152,146	A	11/2000	Taylor et al.	
6,163,098	A	12/2000	Taylor et al.	
6,176,977	B1	1/2001	Taylor et al.	
6,182,461	B1	2/2001	Washburn et al.	
6,182,671	B1	2/2001	Taylor et al.	
6,187,271	B1	2/2001	Lee et al.	
6,193,852	B1	2/2001	Caracciolo et al.	
6,203,600	B1	3/2001	Loreth	
6,212,883	B1	4/2001	Kang	
6,228,149	B1	5/2001	Alenichev et al.	
6,251,171	B1	6/2001	Marra et al.	
6,252,012	B1	6/2001	Egitto et al.	
6,270,733	B1	8/2001	Rodden	
6,277,248	B1	8/2001	Ishioka et al.	
6,282,106	B2	8/2001	Grass	
6,287,368	B1 *	9/2001	Ilmasti	96/19
D449,097	S	10/2001	Smith et al.	
D449,679	S	10/2001	Smith et al.	
6,296,692	B1	10/2001	Gutmann	
6,302,944	B1	10/2001	Hoenig	
6,309,514	B1	10/2001	Conrad et al.	
6,312,507	B1	11/2001	Taylor et al.	
6,315,821	B1	11/2001	Pillion et al.	
6,322,614	B1 *	11/2001	Tillmans	96/16
6,328,791	B1	12/2001	Pillion et al.	
6,348,103	B1	2/2002	Ahlborn et al.	
6,350,417	B1	2/2002	Lau et al.	
6,362,604	B1	3/2002	Cravey	
6,372,097	B1	4/2002	Chen	
6,373,723	B1	4/2002	Wallgren et al.	
6,379,427	B1	4/2002	Siess	
6,391,259	B1	5/2002	Malkin et al.	
6,398,852	B1	6/2002	Loreth	
6,413,302	B1 *	7/2002	Harrison et al.	96/63
6,447,587	B1	9/2002	Pillion et al.	
6,451,266	B1	9/2002	Lau et al.	
6,464,754	B1	10/2002	Ford	
6,471,753	B1	10/2002	Ahn et al.	
6,482,253	B1 *	11/2002	Dunn	96/62
6,494,940	B1	12/2002	Hak	
6,497,753	B1 *	12/2002	Gutmann	96/55
6,497,754	B2	12/2002	Joannou	
6,504,308	B1	1/2003	Krichtafovitch et al.	
6,506,238	B1	1/2003	Endo	
6,508,982	B1	1/2003	Shoji	
6,544,485	B1	4/2003	Taylor	
6,576,046	B2	6/2003	Pruette et al.	
6,585,935	B1	7/2003	Taylor et al.	
6,588,434	B2	7/2003	Taylor et al.	
6,603,268	B2	8/2003	Lee	
6,613,277	B1	9/2003	Monagan	
6,632,407	B1	10/2003	Lau et al.	
6,635,105	B2	10/2003	Ahlborn et al.	
6,635,106	B2	10/2003	Katou et al.	
6,656,253	B2 *	12/2003	Willey et al.	96/27
6,672,315	B2	1/2004	Taylor et al.	
6,709,484	B2	3/2004	Lau et al.	
6,713,026	B2	3/2004	Taylor et al.	
6,735,830	B1	5/2004	Merciel	
6,749,667	B2	6/2004	Reeves et al.	
6,753,652	B2	6/2004	Kim	
6,761,796	B2	7/2004	Srivastava et al.	
6,768,108	B2	7/2004	Hirano et al.	
6,768,110	B2	7/2004	Alani	
6,768,120	B2	7/2004	Leung et al.	

6,768,121	B2	7/2004	Horsky	
6,770,878	B2	8/2004	Uhlemann et al.	
6,774,359	B1	8/2004	Hirabayashi et al.	
6,777,686	B2	8/2004	Olson et al.	
6,777,699	B1	8/2004	Miley et al.	
6,777,882	B2	8/2004	Goldberg et al.	
6,781,136	B1	8/2004	Kato	
6,785,912	B1	9/2004	Julio	
6,791,814	B2	9/2004	Adachi et al.	
6,794,661	B2	9/2004	Tsukihara et al.	
6,797,339	B2	9/2004	Akizuki et al.	
6,797,964	B2	9/2004	Yamashita	
6,799,068	B1	9/2004	Hartmann et al.	
6,800,862	B2	10/2004	Matsumoto et al.	
6,803,585	B2	10/2004	Glukhoy	
6,805,916	B2	10/2004	Cadieu	
6,806,035	B1	10/2004	Atireklapvarodom et al.	
6,806,163	B2	10/2004	Wu et al.	
6,806,468	B2	10/2004	Laiko et al.	
6,808,606	B2	10/2004	Thomsen et al.	
6,809,310	B2	10/2004	Chen	
6,809,312	B1	10/2004	Park et al.	
6,809,325	B2	10/2004	Dahl et al.	
6,812,647	B2	11/2004	Cornelius	
6,815,690	B2	11/2004	Veerasamy et al.	
6,818,257	B2	11/2004	Amann et al.	
6,818,909	B2	11/2004	Murrell et al.	
6,819,053	B2	11/2004	Johnson	
6,863,869	B2	3/2005	Taylor et al.	
6,893,618	B2	5/2005	Kotlyar et al.	
6,896,853	B2	5/2005	Lau et al.	
6,897,617	B2	5/2005	Lee	
6,899,745	B2 *	5/2005	Gatchell et al.	95/76
6,908,501	B2	6/2005	Reeves et al.	
6,911,186	B2	6/2005	Taylor et al.	
6,958,134	B2	10/2005	Taylor et al.	
6,962,620	B2 *	11/2005	Chang et al.	96/60
6,974,560	B2	12/2005	Taylor et al.	
6,984,987	B2	1/2006	Taylor et al.	
2001/0029842	A1 *	10/2001	Hoenig	96/63
2001/0048906	A1	12/2001	Lau et al.	
2002/0069760	A1	6/2002	Pruette et al.	
2002/0079212	A1	6/2002	Taylor et al.	
2002/0098131	A1	7/2002	Taylor et al.	
2002/0122751	A1	9/2002	Sinaiko et al.	
2002/0122752	A1	9/2002	Taylor et al.	
2002/0127156	A1	9/2002	Taylor	
2002/0134664	A1	9/2002	Taylor et al.	
2002/0134665	A1	9/2002	Taylor et al.	
2002/0141914	A1	10/2002	Lau et al.	
2002/0144601	A1	10/2002	Palestro et al.	
2002/0146356	A1	10/2002	Sinaiko et al.	
2002/0150520	A1	10/2002	Taylor et al.	
2002/0152890	A1	10/2002	Leiser	
2002/0155041	A1	10/2002	McKinney, Jr. et al.	
2002/0170435	A1	11/2002	Joannou	
2002/0190658	A1	12/2002	Lee	
2002/0195951	A1	12/2002	Lee	
2003/0005824	A1	1/2003	Katou et al.	
2003/0170150	A1	9/2003	Law et al.	
2003/0206837	A1	11/2003	Taylor et al.	
2003/0206839	A1	11/2003	Taylor et al.	
2003/0206840	A1	11/2003	Taylor et al.	
2004/0033176	A1	2/2004	Lee et al.	
2004/0052700	A1	3/2004	Kotlyar et al.	
2004/0065202	A1	4/2004	Gatchell et al.	
2004/0096376	A1	5/2004	Taylor	
2004/0136863	A1	7/2004	Yates et al.	
2004/0166037	A1	8/2004	Youdell et al.	
2004/0226447	A1	11/2004	Lau et al.	
2004/0234431	A1	11/2004	Taylor et al.	
2004/0237787	A1	12/2004	Reeves et al.	
2004/0251124	A1	12/2004	Lau	
2004/0251909	A1	12/2004	Taylor et al.	
2005/0000793	A1	1/2005	Taylor et al.	

FOREIGN PATENT DOCUMENTS

CN	87210843	U	7/1988
CN	2138764	Y	6/1993
CN	2153231	Y	12/1993
DE	2206057		8/1973
DE	197 41 621 C 1		6/1999
EP	0433152	A1	12/1990
EP	0332624	B1	1/1992
FR	2690509		10/1993
GB	643363		9/1950
JP	S51-90077		8/1976
JP	S62-20653		2/1987
JP	S63-164948		10/1988
JP	10137007		5/1998
JP	11104223		4/1999
JP	2000236914		9/2000
WO	WO 92/05875	A1	4/1992
WO	WO 96/04703	A1	2/1996
WO	WO 99/07474	A1	2/1999
WO	WO 00/10713	A1	3/2000
WO	WO 01/47803	A1	7/2001
WO	WO 01/48781	A1	7/2001
WO	WO 01/64349	A1	9/2001
WO	WO 01/85348	A2	11/2001
WO	WO 02/20162	A2	3/2002
WO	WO 02/20163	A2	3/2002
WO	WO 2/30574	A1	4/2002
WO	WO 02/32578	A1	4/2002
WO	WO 02/42003	A1	5/2002
WO	WO 02/066167	A1	8/2002
WO	WO 03/009944	A1	2/2003
WO	WO 03/013620	A1	2/2003
WO	WO 03/013734 AA		2/2003

OTHER PUBLICATIONS

U.S. Appl. No. 60/306,479, filed Jul. 18, 2001, Taylor.
U.S. Appl. No. 60/341,179, filed Dec. 13, 2001, Taylor et al.
U.S. Appl. No. 60/340,702, filed Dec. 13, 2001, Taylor et al.
U.S. Appl. No. 60/341,377, filed Dec. 13, 2001, Taylor et al.
U.S. Appl. No. 60/341,518, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/340,288, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/341,176, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/340,462, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/340,090, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/341,433, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/341,592, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/341,320, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/391,070, filed Jun. 6, 2002, Reeves.
Blueair AV 402 Air Purifier, http://www.air-purifiers-usa.biz/Blueair_AV402.htm, 4 pp., 1996.
Blueair AV 501 Air Purifier, http://www.air-purifiers-usa.biz/Blueair_AV501.htm, 15 pp., 1997.
ConsumerReports.org, "Air Cleaners: Behind the Hype;" http://www.consumerreports.org/main/content/printable.jsp?FOLDER%3C%3EFOLDER_id, Oct. 2003, 6 pp.
Electrical schematic and promotional material available from Zenion Industries, 7 pages, Aug. 1990.
English Translation of German Patent Document DE 197 41 621 C1; Publication Date: Jun. 10, 1999.
English Translation of German Published Patent Application 2206057; Publication Date: Aug. 16, 1973.
English Translation of Japanese Unexamined Patent Application Bulletin No. S51-90077; Publication Date: Aug. 6, 1976.
English Translation of Japanese Unexamined Utility Model Application No. S62-20653; Publication Date: Feb. 7, 1987.
English Translation of Japanese Unexamined Utility Model Application No. S63-164948; Publication Date: Oct. 27, 1988.
Friedrich C-90A Electronic Air Cleaner, Service Information, Friedrich Air Conditioning Co., 12 pp., 1985.

Friedrich C-90A, "How the C-90A Works," BestAirCleaner.com http://www.bestaircleaner.com/faq/c90works.asp, 1 page.
"Household Air Cleaners," Consumer Reports Magazine, Oct. 1992, 6 pp.
LakeAir Excel and Maxum Portable Electronic Air Cleaners, Operating and Service Manual, LakeAir International, Inc., 11 pp., 1971.
LENTEK Sila™ Plug-In Air Purifier/Deodorizer product box copyrighted 1999, 13 pages.
Promotional material available from Zenion Industries for the Plasma-Pure 100/200/300, 2 pages, Aug. 1990.
Promotional material available from Zenion Industries for the Plasma-Tron, 2 pages, Aug. 1990.
Trion 120 Air Purifier, Model 442501-025, http://www.feddersoutled.com/trion120.html, 16 pp., believed to be at least one year prior to Nov. 5, 1998.
Trion 150 Air Purifier, Model 45000-002, http://www.feddersoutlet.com/trion150.html, 11 pp., believed to be at least one year prior to Nov. 5, 1998.
Trion 350 Air Purifier, Model 450111-010, http://www.feddersoutlet.com/trion350.html, 12 pp., believed to be at least one year prior to Nov. 5, 1998.
Trion Console 250 Electronic Air Cleaner, Model Series 442857 and 445600, Manual for Installation·Operation·Maintenance, Trion Inc., 7 pp., believed to be at least one year prior to Nov. 5, 1998.
"Zenion Elf Device," drawing, prior art, undated.

* cited by examiner



(PRIOR ART)
FIG. - 1


IN
102
S1
S3
S2
103
100
112
IN
224
IN
60
104
OUT
OUT
O_3
60
IN
60
OUT
O_3
IN
O_3
160

FIG. - 2A


112
242
240
242
102
104
100
232
106
104
500
106
113
106
104
230
108

FIG. - 2B



FIG. - 3A



FIG. - 3B



FIG. - 3C



FIG. - 3D



FIG. - 3E



FIG. - 4


260 OUT
212
B
B
w
L
244
242
242
240
242
X1
Y2
246
220
210
232
230
232
232
272
271
270
211
A
A
280
290
272
D
212
250 IN

FIG. - 5A



260
212
℄
B
B
244
240
242
246
220
232
232
210
211
230
274b
280
280
272
280
280
A
A
280
290
270
274a
212
℄

FIG. - 5B


OUT
260
212
200
240
244
244
244
242
242
242
246
246
246
210
220
232
232
230
270a
270b
270
211
280
280
290
A
A
280
280
251
IN
251
IN
253
250
IN

FIG. - 6


GERMICIDAL LAMP
218
218
290
110V AC
EMI FILTERS
110
ELECTRONIC BALAST
112
DC POWER SUPPLY
114
≈160 Vdc
≈12 Vdc
170
116
214
LO
MED
HI
MCU
130
AC VOLTAGE SENSE SIGNAL
LOW VOLTAGE PULSES
ARC SENSING SIGNAL
VOLTAGE DOUBLER
118
126
230
240
BOOST SIGNAL
INDICATOR LIGHT
219

FIG. - 7



START
802
SET ARCING THRESHOLD (A_TH) BASED ON AIRFLOW SETTING (e.g. HI, MED or LO)
804
INITIALIZE ARC_COUNT(AC) i.e. AC = 0
806
INITIALIZE SAMPLE_COUNT (SC) i.e., SC = 0
807
PERIODICALLY SAMPLE CURRENT & PRODUCE A RUNNING AVG. CURRENT VALUE (ACV)
808
ACV ≥ A_TH ?
810
NO
HAS ACV NOT EXCEEDED A_TH FOR PREDETERMINED TIME (e.g. 60 sec.) ?
822
NO
YES
YES
INCREMENT SAMPLE_COUNT i.e., SC = SC + 1
812
SC = SC_TH (e.g. 30) ?
814
NO
YES
TEMPORARILY SHUT DOWN UNIT (e.g., for 80 sec.)
816
INCREMENT ARC_COUNT i.e., AC = AC + 1
818
AC = AC_TH (e.g., 3) ?
820
NO
YES
SHUT DOWN UNIT (NO SELF RESTART)
824

FIG. - 8



FIG. 9



FIG. 10


200
290
112
230
1107
242
1106
1105
12
12
260
1104
1103
214
1102
906
902
210
904
108

FIG. 11



Fig. 12



FIG. 13



FIG. 14



Fig. 15



FIG. 16


200
290
112
1702
230
902
1702
212
210
250
214
902
1702
242
902
210
108

FIG. 17


242
230
902
1702
260
230
902
1702
214
242
230
902
1702
242
230
902
1702
212
250
242
210
108

FIG. 18


200
290
112
902
1702
250
260
902
1702
212
214
902
1702
902
1702
210
108

FIG. 19



FIG. 20

AIR TREATMENT APPARATUS HAVING AN ELECTRODE EXTENDING ALONG AN AXIS WHICH IS SUBSTANTIALLY PERPENDICULAR TO AN AIR FLOW PATH

CLAIM OF PRIORITY

This application claims priority to U.S. Provisional Patent Application No. 60/538,973, filed Jan. 22, 2004, and is a continuation-in-part of U.S. patent application Ser. No. 10/074,096, filed Feb. 12, 2002, now U.S. Pat. No. 6,974, 560, which claims priority to U.S. Provisional Patent Application No. 60/341,179, filed Dec. 13, 2001, and to U.S. Provisional Patent Application No. 60/306,479, filed Jul. 18, 2001, which is a continuation-in-part of U.S. patent application Ser. No. 09/774,198, filed Jan. 29, 2001, now U.S. Pat. No. 6,544,485, which is a continuation-in-part of U.S. patent application Ser. No. 09/924,624, filed Aug. 8, 2001, now abandoned which is a continuation of U.S. patent application Ser. No. 09/564,960, filed May 4, 2000, now U.S. Pat. No. 6,350,417, which is a continuation-in-part of U.S. patent application Ser. No. 09/186,471, filed Nov. 5, 1998, now U.S. Pat. No. 6,176,977. Priority is claimed to each of the applications recited above and each of these applications are incorporated herein by reference.

RELATED APPLICATIONS

This application is related to the following applications, all of which are hereby incorporated by reference herein:

U.S. patent application Ser. No. 10/304,182, filed Nov. 26, 2002, entitled "APPARATUS FOR CONDITIONING AIR," now abandoned;

U.S. patent application Ser. No. 10/375,806, filed Feb. 27, 2003, entitled "APPARATUS FOR CONDITIONING AIR WITH ANTI-MICROORGANISM CAPABILITY," now abandoned;

U.S. patent application Ser. No. 10/375,734, filed Feb. 27, 2003, entitled "AIR TRANSPORTER-CONDITIONER DEVICES WITH TUBULAR ELECTRODE CONFIGURATIONS," now abandoned; U.S. patent application Ser. No. 10/375,735, filed Feb. 27, 2003, entitled "APPARATUSES FOR CONDITIONING AIR WITH MEANS TO EXTEND EXPOSURE TIME TO ANTI-MICROORGANISM LAMP," now abandoned;

U.S. patent application Ser. No. 10/379,966, filed Mar. 5, 2003, entitled"PERSONAL AIR TRANSPORTER-CONDITIONER DEVICES WITH ANTI-MICROORGANISM CAPABILITY,"

U.S. patent application Ser. No. 10/435,289, filed May 9, 2003, entitled "AN ELECTRO-KINETIC AIR TRANSPORTER AND CONDITIONER DEVICES WITH SPECIAL DETECTORS AND INDICATORS"; and

This application is related to U.S. Pat. No. 6,176,977, issued Jan. 23, 2001, entitled "ELECTRO-KINETIC AIR TRANSPORTER-CONDITIONER".

This application is also related to the following commonly-owned co-pending patent applications:

U.S. Patent Application. Ser. No.	Filed
Ser. No. 90/007,276	Oct. 29, 2004
Ser. No. 11/041,926	Jan. 21, 2005
Ser. No. 11/091,243	Mar. 28, 2005
Ser. No. 11/062,057	Feb. 18, 2005
Ser. No. 11/071,779	Mar. 3, 2005
Ser. No. 10/994,869	Nov. 22, 2004
Ser. No. 11/007,556	Dec. 8, 2004
Ser. No. 10/074,209	Feb. 12, 2002
Ser. No. 10/685,182	Oct. 14, 2003
Ser. No. 10/944,016	Sep. 17, 2004
Ser. No. 10/795,934	Mar. 8, 2004
Ser. No. 11/064,797	Feb. 24, 2005
Ser. No. 11/003,671	Dec. 3,2004
Ser. No. 11/003,035	Dec. 3,2004
Ser. No. 11/007,395	Dec. 8, 2004
Ser. No. 10/876,495	Jun. 25, 2004
Ser. No. 10/809,923	Mar. 25, 2004
Ser. No. 11/004,397	Dec. 3, 2004
Ser. No. 10/895,799	Jul. 21, 2004
Ser. No. 10/642,927	Aug. 18, 2003
Ser. No. 11/823,346	Apr. 12, 2004
Ser. No. 10/662,591	Sep. 15, 2003
Ser. No. 11/061,967	Feb. 18, 2005
Ser. No. 11/150,046	Jun. 10, 2005
Ser. No. 11/188,448	Jul. 25, 2005
Ser. No. 11/188,478	Jul. 25, 2005
Ser. No. 11/293,538	Dec. 2, 2005
Ser. No. 11/457,396	Jul. 13, 2006
Ser. No. 11/464,139	Aug. 11,2006
Ser. No. 11/694,281	Mar. 30, 2007

FIELD OF THE INVENTION

The present invention relates generally to devices that transport and/or condition air.

BACKGROUND AND DESCRIPTION OF RELATED ART

FIG. **1** depicts a generic electro-kinetic device **10** to condition air. Device **10** includes a housing **20** that typically has at least one air input **30** and at least one air output **40**. Within housing **20** there is disposed an electrode assembly or system **50** comprising a first electrode array **60** having at least one electrode **70** and comprising a second electrode array **80** having at least one electrode **90**. System **10** further includes a high voltage generator **95** coupled between the first and second electrode arrays. As a result, ozone and ionized particles of air are generated within device **10**, and there is an electro-kinetic flow of air in the direction from the first electrode array **60** towards the second electrode array **80**. In FIG. **1**, the large arrow denoted IN represents ambient air that can enter input port **30**. The small "x"s denote particulate matter that may be present in the incoming ambient air. The air movement is in the direction of the large arrows, and the output airflow, denoted OUT, exits device **10** via outlet **40**. An advantage of electro-kinetic devices such as device **10** is that an airflow is created without using fans or other moving parts. Thus, device **10** in FIG. **1** can function somewhat as a fan to create an output airflow, but without requiring moving parts.

Preferably particulate matter "x" in the ambient air can be electrostatically attracted to the second electrode array **80**, with the result that the outflow (OUT) of air from device **10** not only contains ozone and ionized air, but can be cleaner than the ambient air. In such devices, it can become necessary to occasionally clean the second electrode array electrodes **80** to remove particulate matter and other debris from the surface of electrodes **90**. Accordingly, the outflow of air (OUT) is conditioned in that particulate matter is removed and the outflow includes appropriate amounts of ozone, and some ions.

An outflow of air containing ions and ozone may not, however, destroy or significantly reduce microorganisms such as germs, bacteria, fungi, viruses, and the like, collectively hereinafter "microorganisms." It is known in the art to destroy such microorganisms with, by way of example only, germicidal lamps. Such lamps can emit ultraviolet radiation having a wavelength of about 254 nm. For example, devices to condition air using mechanical fans, HEPA filters, and germicidal lamps are sold commercially by companies such as Austin Air, C.A.R.E. 2000, Amaircare, and others. Often these devices are somewhat cumbersome, and have the size and bulk of a small filing cabinet. Although such fan-powered devices can reduce or destroy microorganisms, the devices tend to be bulky, and are not necessarily silent in operation.

SUMMARY OF INVENTION

The present invention is directed to an air transporter-conditioner device, which comprises an elongated housing which has a bottom, a top and an elongated side wall. The housing has an inlet which located adjacent to the bottom and an outlet which located adjacent to the elongated side wall. The device includes an emitter electrode and a collector electrode as well as a high voltage generator which is operably connected to both electrodes. The device also includes a fan that is configured to draw air into the housing through the inlet as well as direct the air along the elongated housing. A baffle is configured in the device to direct air from the fan toward the outlet.

In one embodiment, the housing includes a second elongated side wall, whereby the baffle includes a plurality of deflectors which are positioned along the second elongated side wall to direct air flow toward the outlet.

In one embodiment, the baffle includes a plurality of elongated columns of varying lengths, wherein each column includes a deflector configured to direct air toward the outlet.

In one embodiment, the device includes a second inlet is located adjacent to the elongated side wall.

In one embodiment, a germicidal lamp located inside the elongated housing.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** depicts a generic electro-kinetic conditioner device that outputs ionized air and ozone, according to the prior art;

FIGS. **2A-2B**: FIG. **2A** is a perspective view of an embodiment of the housing; FIG. **2B** is a perspective view of the embodiment shown in FIG. **2A**, illustrating the removable array of second electrodes;

FIGS. **3A-3E**: FIG. **3A** is a perspective view of an embodiment of the device shown in FIGS. **2A-2B** without a base; FIG. **3B** is a top view of the embodiment of the embodiment illustrated in FIG. **3A**; FIG. **3C** is a partial perspective view of the embodiment shown in FIGS. **3A-3B**, illustrating the removable second array of electrodes; FIG. **3D** is a side view of the embodiment shown in FIG. **3A** including a base; FIG. **3E** is a perspective view of the embodiment in FIG. **3D**, illustrating a removable rear panel which exposes a germicidal lamp;

FIG. **4** is a perspective view of another embodiment of the device;

FIGS. **5A-5B**: FIG. **5A** is a top, partial cross-sectioned view of an embodiment of the device, illustrating one configuration of the germicidal lamp; FIG. **5B** is a top, partial cross-sectioned view of another embodiment of the device, illustrating another configuration of the germicidal lamp;

FIG. **6** is a top, partial cross-sectional view of yet another embodiment of the device;

FIG. **7** is an electrical block diagram of an embodiment of a circuit of the device;

FIG. **8** is a flow diagram used to describe embodiments of the device that sense and suppress arcing;

FIG. **9** is an alternate embodiment of the device which includes a fan;

FIG. **10** is an alternate embodiment of the device which includes a fan;

FIG. **11** is a further alternate embodiment of the device which includes a fan;

FIG. **12** is a plan cross-sectional view of the embodiment shown in FIG. **11**, through section **11-11**;

FIG. **13** is an alternate embodiment of the device which includes a fan;

FIG. **14** is an alternate embodiment of the device which includes a fan;

FIG. **15** is a plan cross-sectional view of the embodiment shown in FIG. **14**, through section **14-14**;

FIG. **16** is an alternate embodiment of the device which includes a fan;

FIG. **17** is an alternate embodiment of the device which includes fans;

FIG. **18** is an alternate embodiment of the device which includes fans;

FIG. **19** is an alternate embodiment of the device which includes fans;

FIG. **20** is an alternate embodiment of the device which includes a fan.

DETAILED DESCRIPTION OF THE PRESENT INVENTION

Overall Air Transporter-Conditioner System Configuration

FIGS. **2A-2B**

FIGS. **2A-2B** depict a system which does not have incorporated therein a germicidal lamp. However, these embodiments do include other aspects such as the removable second electrodes which can be included in the other described embodiments.

FIGS. **2A** and **2B** depict an electro-kinetic air transporter-conditioner system **100** whose housing **102** includes preferably rear-located intake vents or louvers **104** and preferably front-located exhaust vents **106**, and a base pedestal **108**. Preferably, the housing **102** is freestanding and/or upstandingly vertical and/or elongated. Internal to the transporter housing **102** is an ion generating unit **160**, preferably powered by an AC:DC power supply that is energizable or excitable using switch **S1**. Switch **S1**, along with the other below-described user operated switches, is conveniently located at the top **103** of the unit **100**. Ion generating unit **160** is self-contained in that other than ambient air, nothing is required from beyond the transporter housing **102**, save external operating potential, for operation of the present invention.

The upper surface **103** of the housing **102** includes a user-liftable handle member **112** to which is affixed a second array **240** of collector electrodes **242**. The housing **102** also encloses a first array of emitter electrodes **230**, or a single first emitter electrode shown here as a single wire or wire-shaped electrode **232**. (The terms "wire" and "wire-shaped" shall be used interchangeably herein to mean an electrode either made from a wire or, if thicker or stiffer than a wire, having the appearance of a wire.) In the embodiment shown, handle member **112** lifts second array electrodes **240** upward causing the second electrode to telescope out of the top of the housing and, if desired, out of unit **100** for cleaning, while the first electrode array **230** remains within unit **100**. As is evident from the figure, the second array of electrodes **240** can be lifted vertically out from the top **103** of unit **100** along the longitudinal axis or direction of the elongated housing **102**. This arrangement with the second electrodes removable from the top **103** of the unit **100**, makes it easy for the user to pull the second electrodes **242** out for cleaning. In FIG. **2**B, the bottom ends of second electrodes **242** are connected to a member **113**, to which is attached a mechanism **500**, which includes a flexible member and a slot for capturing and cleaning the first electrode **232**, whenever handle member **112** is moved upward or downward by a user. The first and second arrays of electrodes are coupled to the output terminals of ion generating unit **160**.

The general shape of the embodiment of the invention shown in FIGS. **2**A and **2**B is that of a figure eight in cross-section, although other shapes are within the spirit and scope of the invention. The top-to-bottom height in one preferred embodiment is 1 m, with a left-to-right width of preferably 15 cm, and a front-to-back depth of perhaps 10 cm, although other dimensions and shapes can of course be used. A louvered construction provides ample inlet and outlet venting in an ergonomical housing configuration. There need be no real distinction between vents **104** and **106**, except their location relative to the second electrodes. These vents serve to ensure that an adequate flow of ambient air can be drawn into or made available to the unit **100**, and that an adequate flow of ionized air that includes appropriate amounts of O_3 flows out from unit **100**.

As will be described, when unit **100** is energized by depressing switch S**1**, high voltage or high potential output by an ion generator **160** produces ions at the first electrode **232**, which ions are attracted to the second electrodes **242**. The movement of the ions in an "IN" to "OUT" direction carries with the ions air molecules, thus electro-kinetically producing an outflow of ionized air. The "IN" notation in FIGS. **2**A and **2**B denotes the intake of ambient air with particulate matter **60**. The "OUT" notation in the figures denotes the outflow of cleaned air substantially devoid of the particulate matter, which particulate matter adheres electrostatically to the surface of the second electrodes. In the process of generating the ionized airflow appropriate amounts of ozone (O_3) are beneficially produced. It maybe desired to provide the inner surface of housing **102** with an electrostatic shield to reduce detectable electromagnetic radiation. For example, a metal shield could be disposed within the housing, or portions of the interior of the housing can be coated with a metallic paint to reduce such radiation.

Embodiments of Air-Transporter-Conditioner System with Germicidal Lamp

FIGS. **3**A-**6** depict various embodiments of the device **200**, with an improved ability to diminish or destroy microorganisms including bacteria, germs, and viruses. Specifically, FIGS. **3**A-**6** illustrate various embodiments of the elongated and upstanding housing **210** with the operating controls located on the top surface **217** of the housing **210** for controlling the device **200**.

FIGS. **3**A-**3**E

FIG. **3**A illustrates a first preferred embodiment of the housing **210** of device **200**. The housing **210** is preferably made from a lightweight inexpensive material, ABS plastic for example. As a germicidal lamp (described hereinafter) is located within the housing **210**, the material must be able to withstand prolonged exposure to class UV-C light. Non-"hardened" material will degenerate over time if exposed to light such as UV-C. By way of example only, the housing **210** may be manufactured from CYCLOLAC7 ABS Resin (material designation VW300(f2)), which is manufactured by General Electric Plastics Global Products, and is certified by UL Inc. for use with ultraviolet light. It is within the scope of the present invention to manufacture the housing **210** from other UV appropriate materials.

In a preferred embodiment, the housing **210** is aerodynamically oval, elliptical, teardrop-shaped or egg-shaped. The housing **210** includes at least one air intake **250**, and at least one air outlet **260**. As used herein, it will be understood that the intake **250** is "upstream" relative to the outlet **260**, and that the outlet **260** is "downstream" from the intake **250**. "Upstream" and "downstream" describe the general flow of air into, through, and out of device **200**, as indicated by the large hollow arrows.

Covering the inlet **250** and the outlet **260** are fins, louvers, or baffles **212**. The fins **212** are preferably elongated and upstanding, and thus in the preferred embodiment, vertically oriented to minimize resistance to the airflow entering and exiting the device **200**. Preferably the fins **212** are vertical and parallel to at least the second collector electrode array **240** (see FIG. **5**A). The fins **212** can also be parallel to the first emitter electrode array **230**. This configuration assists in the flow of air through the device **200** and also assists in preventing UV radiation from the UV or germicidal lamp **290** (described hereinafter), or other germicidal source, from exiting the housing **210**. By way of example only, if the long width of the body from the inlet **250** to the outlet **260** is 8 inches, the collector electrode **242** (see FIG. **5**A) can be 1¼" wide in the direction of airflow, and the fins **212** can be ¾" or ½" wide in the direction of airflow. Other proportionate dimensions are within the spirit and scope of the invention. Further, other fin and housing shapes which may not be as aerodynamic are within the spirit and scope of the invention.

From the above it is evident that preferably the cross-section of the housing **210** is oval, elliptical, teardrop-shaped or egg-shaped, with the inlet **250** and outlet **260** narrower than the middle (see line A-A in FIG. **5**A) of the housing **210**. Accordingly, the airflow, as it passes across line A-A, is slower due to the increased width and area of the housing **210**. Any bacteria, germs, or virus within the airflow will have a greater dwell time and be neutralized by a germicidal device, such as, preferably, an ultraviolet lamp.

FIG. **3**B illustrates the operating controls for the device **200**. Located on top surface **217** of the housing **210** is an airflow speed control dial **214**, a boost button **216**, a function dial **218**, and an overload/cleaning light **219**. The airflow speed control dial **214** has three settings from which a user can choose: LOW, MED, and HIGH. The airflow rate is proportional to the voltage differential between the electrodes or electrode arrays coupled to the ion generator **160**. The LOW, MED, and HIGH settings generate a different predetermined voltage difference between the first and second arrays. For example, the LOW setting will create the smallest voltage difference, while the HIGH setting will create the largest voltage difference. Thus, the LOW setting will cause the device **200** to generate the slowest airflow rate, while the HIGH setting will cause the device **200** to generate the fastest airflow rate. These airflow rates are created by the electronic circuit disclosed in FIGS. **7**A-**7**B, and operate as disclosed below.

The function dial **218** enables a user to select "ON," "ON/GP," or "OFF." The unit **200** functions as an electrostatic air transporter-conditioner, creating an airflow from the inlet **250** to the outlet **260**, and removing the particles within the airflow when the function dial **218** is set to the "ON" setting. The germicidal lamp **290** does not operate, or emit UV light, when the function dial **218** is set to "ON." The device **200** also functions as an electrostatic air transporter-conditioner, creating an airflow from the inlet **250** to the outlet **260**, and removing particles within the airflow when the function dial **218** is set to the "ON/GP" setting. In addition, the "ON/GP" setting activates the germicidal lamp **290** to emit UV light to remove or kill bacteria within the airflow. The device **200** will not operate when the function dial **218** is set to the "OFF" setting.

As previously mentioned, the device **200** preferably generates small amounts of ozone to reduce odors within the room. If there is an extremely pungent odor within the room, or a user would like to temporarily accelerate the rate of cleaning, the device **200** has a boost button **216**. When the boost button **216** is depressed, the device **200** will temporarily increase the airflow rate to a predetermined maximum rate, and generate an increased amount of ozone. The increased amount of ozone will reduce the odor in the room faster than if the device **200** was set to HIGH. The maximum airflow rate will also increase the particle capture rate of the device **200**. In a preferred embodiment, pressing the boost button **216** will increase the airflow rate and ozone production continuously for 5 minutes. This time period may be longer or shorter. At the end of the preset time period (e.g., 5 minutes), the device **200** will return to the airflow rate previously selected by the control dial **214**.

The overload/cleaning light **219** indicates if the second electrodes **242** require cleaning, or if arcing occurs between the first and second electrode arrays. The overload/cleaning light **219** may illuminate either amber or red in color. The light **219** will turn amber if the device **200** has been operating continuously for more than two weeks and the second array **240** has not been removed for cleaning within the two-week period. The amber light is controlled by the below-described micro-controller unit **130** (see FIG. **7**). The device **200** will continue to operate after the light **219** turns amber. The light **219** is only an indicator. There are two ways to reset or turn the light **219** off. A user may remove and replace the second array **240** from the unit **200**. The user may also turn the control dial **218** to the OFF position, and subsequently turn the control dial **218** back to the "ON" or "ON/GP" position. The MCU **130** will begin counting a new two-week period upon completing either of these two steps.

The light **219** will turn red to indicate that continuous arcing has occurred between the first array **230** and the second array **240**, as sensed by the MCU **130**, which receives an arc sensing signal from the collector of an IGBT switch **126** shown in FIG. **7**, described in more detail below. When continuous arcing occurs, the device **200** will automatically shut itself off. The device **200** cannot be restarted until the device **200** is reset. To reset the device **200**, the second array **240** should first be removed from the housing **210** after the unit **200** is turned off. The second electrode **240** can then be cleaned and placed back into the housing **210**. Then, the device **200** is turned on. If no arcing occurs, the device **200** will operate and generate an airflow. If the arcing between the electrodes continues, the device **200** will again shut itself off, and need to be reset.

FIG. **3**C illustrates the second electrodes **242** partially removed from the housing **210**. In this embodiment, the handle **202** is attached to an electrode mounting bracket **203**. The bracket **203** secures the second electrodes **242** in a fixed, parallel configuration. Another similar bracket **203** is attached to the second electrodes **242** substantially at the bottom (not shown). The two brackets **203** align the second electrodes **242** parallel to each other, and in-line with the airflow traveling through the housing **210**. Preferably, the brackets **203** are non-conductive surfaces.

One of the various safety features can be seen with the second electrodes **242** partially removed. As shown in FIG. **3**C, an interlock post **204** extends from the bottom of the handle **202**. When the second electrodes **242** are placed completely into the housing **210**, the handle **202** rests within the top surface **217** of the housing, as shown by FIGS. **3**A-**3**B. In this position, the interlock post **204** protrudes into the interlock recess **206** and activates a switch connecting the electrical circuit of the unit **200**. When the handle **202** is removed from the housing **210**, the interlock post **204** is pulled out of the interlock recess **206** and the switch opens the electrical circuit. With the switch in an open position, the unit **200** will not operate. Thus, if the second electrodes **242** are removed from the housing **210** while the unit **200** is operating, the unit **200** will shut off as soon as the interlock post **204** is removed from the interlock recess **206**.

FIG. **3**D depicts the housing **210** mounted on a stand or base **215**. The housing **210** has an inlet **250** and an outlet **260**. The base **215** sits on a floor surface. The base **215** allows the housing **210** to remain in a vertical position. It is within the scope of the present invention for the housing **210** to be pivotally connected to the base **215**. As can be seen in FIG. **3**D, housing **210** includes sloped top surface **217** and sloped bottom surface **213**. These surfaces slope inwardly from inlet **250** to outlet **260** to additionally provide a streamlined appearance and effect.

FIG. **3**E illustrates that the housing **210** has a removable rear panel **224**, allowing a user to easily access and remove the germicidal lamp **290** from the housing **210** when the lamp **290** expires. This rear panel **224** in this embodiment defines the air inlet and comprises the vertical louvers. The rear panel **224** has locking tabs **226** located on each side, along the entire length of the panel **224**. The locking tabs **226**, as shown in FIG. **3**E, are "L"-shaped. Each tab **226** extends away from the panel **224**, inward towards the housing **210**, and then projects downward, parallel with the edge of the panel **224**. It is within the spirit and scope of the invention to have differently-shaped tabs **226**. Each tab **226** individually and slidably interlocks with recesses **228** formed within the housing **210**. The rear panel **224** also has a biased lever (not shown) located at the bottom of the panel **224** that interlocks with the recess **230**. To remove the panel **224** from the housing **210**, the lever is urged away from the housing **210**, and the panel **224** is slid vertically upward until the tabs **226** disengage the recesses **228**. The panel **224** is then pulled away from the housing **210**. Removing the panel **224** exposes the lamp **290** for replacement.

The panel **224** also has a safety mechanism to shut the device **200** off when the panel **224** is removed. The panel **224** has a rear projecting tab (not shown) that engages the safety interlock recess **227** when the panel **224** is secured to the housing **210**. By way of example only, the rear tab depresses a safety switch located within the recess **227** when the rear panel **224** is secured to the housing **210**. The device **200** will operate only when the rear tab in the panel **224** is fully inserted into the safety interlock recess **227**. When the panel **224** is removed from the housing **210**, the rear projecting tab is removed from the recess **227** and the power is cut-off to the entire device **200**. For example if a user removes the rear panel **224** while the device **200** is running, and the germicidal lamp **290** is emitting UV radiation, the device **200** will turn off as soon as the rear projecting tab disengages from the recess **227**. Preferably, the device **200** will turn off when the rear panel **224** is removed only a very short distance (e.g., ¼") from the housing **210**. This safety switch operates very similar to the interlocking post **204**, as shown in FIG. **3**C.

FIG. **4**

FIG. **4** illustrates yet another embodiment of the housing **210**. In this embodiment, the germicidal lamp **290** maybe removed from the housing **210** by lifting the germicidal lamp **290** out of the housing **210** through the top surface **217**. The housing **210** does not have a removable rear panel **224**. Instead, a handle **275** is affixed to the germicidal lamp **290**. The handle **275** is recessed within the top surface **217** of the housing **210** similar to the handle **202**, when the lamp **290** is within the housing **210**. To remove the lamp **290**, the handle **275** is vertically raised out of the housing **210**.

The lamp **290** is situated within the housing **210** in a similar manner as the second array of electrodes **240**. That is to say, that when the lamp **290** is pulled vertically out of the top **217** of the housing **210**, the electrical circuit that provides power to the lamp **290** is disconnected. The lamp **290** is mounted in a lamp fixture that has circuit contacts which engage the circuit in FIG. **7**A. As the lamp **290** and fixture are pulled out, the circuit contacts are disengaged. Further, as the handle **275** is lifted from the housing **210**, a cutoff switch will shut the entire device **200** off. This safety mechanism ensures that the device **200** will not operate without the lamp **290** placed securely in the housing **210**, preventing an individual from directly viewing the radiation emitted from the lamp **290**. Reinserting the lamp **290** into the housing **210** causes the lamp fixture to re-engage the circuit contacts as is known in the art. In similar, but less convenient fashion, the lamp **290** may be designed to be removed from the bottom of the housing **210**.

The germicidal lamp **290** is a preferably UV-C lamp that preferably emits viewable light and radiation (in combination referred to as radiation or light **280**) having wavelength of about 254 nm. This wavelength is effective in diminishing or destroying bacteria, germs, and viruses to which it is exposed. Lamps **290** are commercially available. For example, the lamp **290** may be a Phillips model TUV 15W/G15 T8, a 15 W tubular lamp measuring about 25 mm in diameter by about 43 cm in length. Another suitable lamp is the Phillips TUV 8WG8 T6, an 8 W lamp measuring about 15 mm in diameter by about 29 cm in length. Other lamps that emit the desired wavelength can instead be used.

FIGS. **5**A-**5**B

As previously mentioned, one role of the housing **210** is to prevent an individual from viewing, by way of example, ultraviolet (UV) radiation generated by a germicidal lamp **290** disposed within the housing **210**. FIGS. **5**A-**5**B illustrate preferred locations of the germicidal lamp **290** within the housing **210**. FIGS. **5**A-**5**B further show the spatial relationship between the germicidal lamp **290** and the electrode assembly **220**, the germicidal lamp **290** and the inlet **250**, and the outlet **260** and the inlet and outlet louvers.

In a preferred embodiment, the inner surface **211** of the housing **210** diffuses or absorbs the UV light emitted from the lamp **290**. FIGS. **5**A-**5**B illustrate that the lamp **290** does emit some light **280** directly onto the inner surface **211** of the housing **210**. By way of example only, the inner surface **211** of the housing **210** can be formed with a non-smooth finish, or a non-light reflecting finish or color, to also prevent the UV-C radiation from exiting through either the inlet **250** or the outlet **260**. The UV portion of the radiation **280** striking the wall **211** will be absorbed and disbursed as indicated above.

As discussed above, the fins **212** covering the inlet **250** and the outlet **260** also limit any line of sight of the user into the housing **210**. The fins **212** are vertically oriented within the inlet **250** and the outlet **260**. The depth D of each fin **212** is preferably deep enough to prevent an individual from directly viewing the interior wall **211**. In a preferred embodiment, an individual cannot directly view the inner surface **211** by moving from side-to-side, while looking into the outlet **260** or the inlet **250**. Looking between the fins **212** and into the housing **210** allows an individual to "see through" the device **200**. That is, a user can look into the inlet vent **250** or the outlet vent **260** and see out of the other vent. It is to be understood that it is acceptable to see light or a glow coming from within housing **210**, if the light has a non-UV wavelength that is acceptable for viewing. In general, a user viewing into the inlet **250** or the outlet **260** may be able to notice a light or glow emitted from within the housing **210**. This light is acceptable to view. In general, when the radiation **280** strikes the interior surface **211** of the housing **210**, the radiation **280** is shifted from its UV spectrum. The wavelength of the radiation changes from the UV spectrum into an appropriate viewable spectrum. Thus, any light emitted from within the housing **210** is appropriate to view.

As also discussed above, the housing **210** is designed to optimize the reduction of microorganisms within the airflow. The efficacy of radiation **280** upon microorganisms depends upon the length of time such organisms are subjected to the radiation **280**. Thus, the lamp **290** is preferably located within the housing **210** where the airflow is the slowest. In preferred embodiments, the lamp **290** is disposed within the housing **210** along line A-A (see FIGS. **5**A-**7**). Line A-A designates the largest width and cross-sectional area of the housing **210**, perpendicular to the airflow. The housing **210** creates a fixed volume for the air to pass through. In operation, air enters the inlet **250**, which has a smaller width, and cross-sectional area, than along line A-A. Since the width and cross-sectional area of the housing **210** along line A-A are larger than the width and cross-sectional area of the inlet **250**, the airflow will decelerate from the inlet **250** to the line A-A. By placing the lamp **290** substantially along line A-A, the air will have the longest dwell time as it passes through the radiation **280** emitted by the lamp **290**. In other words, the microorganisms within the air will be subjected to the radiation **280** for the longest period possible by placing the lamp **290** along line A-A. It is, however, within the scope of the present invention to locate the lamp **290** anywhere within the housing **210**, preferably upstream of the electrode assembly **220**.

A shell or housing **270** substantially surrounds the lamp **290**. The shell **270** prevents the light **280** from shining directly towards the inlet **250** or the outlet **260**. In a preferred embodiment, the interior surface of the shell **270** that faces the lamp **290** is a non-reflective surface. By way of example only, the interior surface of the shell **270** may be a rough surface, or painted a dark, non-gloss color such as black. The lamp **290**, as shown in FIGS. **5**A-**5**B, is a circular tube parallel to the housing **210**. In a preferred embodiment, the lamp **290** is substantially the same length as, or shorter than, the fins **212** covering the inlet **250** and outlet **260**. The lamp **290** emits the light **280** outward in a 360° pattern. The shell **270** blocks the portion of the light **280** emitted directly towards the inlet **250** and the outlet **260**. As shown in FIGS. **5**A and **5**B, there is no direct line of sight through the inlet **250** or the outlet **260** that would allow a person to view the lamp **290**. Alternatively, the shell **270** can have an internal reflective surface in order to reflect radiation into the air stream.

In the embodiment shown in FIG. **5**A, the lamp **290** is located along the side of the housing **210** and near the inlet **250**. After the air passes through the inlet **250**, the air is immediately exposed to the light **280** emitted by the lamp **290**. An elongated "U"-shaped shell **270** substantially encloses the lamp **290**. The shell **270** has two mounts to support and electrically connect the lamp **290** to the power supply.

In a preferred embodiment, as shown in FIG. **5**B, the shell **270** comprises two separate surfaces. The wall **274***a* is located between the lamp **290** and the inlet **250**. The first wall **274***a* is preferably "U"-shaped, with the concave surface facing the lamp **290**. The convex surface of the wall **274***a* is preferably a non-reflective surface. Alternatively, the convex surface of the wall **274***a* may reflect the light **280** outward toward the passing airflow. The wall **274***a* is integrally formed with the removable rear panel **224**. When the rear panel **224** is removed from the housing **210**, the wall **274***a* is also removed, exposing the germicidal lamp **290**. The germicidal lamp **290** is easily accessible in order to, as an example, replace the lamp **290** when it expires.

The wall **274***b*, as shown in FIG. **5**B, is "V"-shaped. The wall **274***b* is located between the lamp **290** and the electrode assembly **220** to prevent a user from directly looking through the outlet **260** and viewing the UV radiation emitted from the lamp **290**. In a preferred embodiment, the wall **274***b* is also anon-reflective surface. Alternatively, the wall **274***b* maybe a reflective surface to reflect the light **280**. It is within the scope of the present invention for the wall **274***b* to have other shapes such as, but not limited to, "U"-shaped or "C"-shaped.

The shell **270** may also have fins **272**. The fins **272** are spaced apart and preferably substantially perpendicular to the passing airflow. In general, the fins **272** further prevent the light **280** from shining directly towards the inlet **250** and the outlet **260**. The fins have a black or non-reflective surface. Alternatively, the fins **272** may have a reflective surface. Fins **272** with a reflective surface may shine more light **280** onto the passing airflow because the light **280** will be repeatedly reflected and not absorbed by a black surface. The shell **270** directs the radiation towards the fins **272**, maximizing the light emitted from the lamp **290** for irradiating the passing airflow. The shell **270** and fins **272** direct the radiation **280** emitted from the lamp **290** in a substantially perpendicular orientation to the crossing airflow traveling through the housing **210**. This prevents the radiation **280** from being emitted directly towards the inlet **250** or the outlet **260**.

FIG. **6**

FIG. **6** illustrates yet another embodiment of the device **200**. The embodiment shown in FIG. **6** is a smaller, more portable, desk version of the air transporter-conditioner. Air is brought into the housing **210** through the inlet **250**, as shown by the arrows marked "IN." The inlet **250** in this embodiment is an air chamber having multiple vertical slots **251** located along each side. In this embodiment, the slots are divided across the direction of the airflow into the housing **210**. The slots **251** preferably are spaced apart a similar distance as the fins **212** in the previously described embodiments, and are substantially the same height as the side walls of the air chamber. In operation, air enters the housing **210** by entering the chamber **250** and then exiting the chamber **250** through the slots **251**. The air contacts the interior wall **211** of the housing **210** and continues to travel through the housing **210** towards the outlet **260**. Since the rear wall **253** of the chamber is a solid wall, the device **200** only requires a single non-reflective housing **270** located between the germicidal lamp **290** and the electrode assembly **220** and the outlet **260**. The housing **270** in FIG. **6** is preferably "U"-shaped, with the convex surface **270***a* facing the germicidal lamp **290**. The surface **270***a* directs the light **280** toward the interior surface **211** of the housing **210** and maximizes the disbursement of radiation into the passing airflow. It is within the scope of the invention for the surface **270** to comprise other shapes such as, but not limited to, a "V"-shaped surface, or to have the concave surface **270***b* face the lamp **290**. Also in other embodiments the housing **270** can have a reflective surface in order to reflect radiation into the air stream. Similar to the previous embodiments, the air passes the lamp **290** and is irradiated by the light **280** soon after the air enters the housing **210**, and prior to reaching the electrode assembly **220**.

FIGS. **5A-6** illustrate embodiments of the electrode assembly **220**. The electrode assembly **220** comprises a first emitter electrode array **230** and a second particle collector electrode array **240**, which is preferably located downstream of the germicidal lamp **290**. The specific configurations of the electrode array **220** are discussed below, and it is to be understood that any of the electrode assembly configurations discussed below maybe used in the device depicted in FIGS. **2A-6** and FIGS. **9-12**. It is the electrode assembly **220** that creates ions and causes the air to flow electro-kinetically between the first emitter electrode array **230** and the second collector electrode array **240**. In the embodiments shown in FIGS. **5A-6**, the first array **230** comprises two wire-shaped electrodes **232**, while the second array **240** comprises three "U"-shaped electrodes **242**. Each "U"-shaped electrode has a nose **246** and two trailing sides **244**. It is within the scope of the invention for the first array **230** and the second array **240** to include electrodes having other shapes as mentioned above and described below.

Electrical Circuit for the Electro-Kinetic Device

FIG. **7**

FIG. **7** illustrates an electrical block diagram for the electro-kinetic device **200**, according to an embodiment of the present invention. The device **200** has an electrical power cord that plugs into a common electrical wall socket that provides a nominal 110 VAC. An electromagnetic interference (EMI) filter **110** is placed across the incoming nominal 110 VAC line to reduce and/or eliminate high frequencies generated by the various circuits within the device **200**, such as an electronic ballast **112**. The electronic ballast **112** is electrically connected to the germicidal lamp **290** to regulate, or control, the flow of current through the lamp **290**. A switch **218** is used to turn the lamp **290** on or off. Electrical components such as the EMI Filter **110** and electronic ballast **112** are well known in the art and do not require a further description.

A DC Power Supply **114** is designed to receive the incoming nominal 110 VAC and to output a first DC voltage (e.g., 160 VDC) for the high voltage generator **170**. The first DC voltage (e.g., 160 VDC) is also stepped down through a resistor network to a second DC voltage (e.g., about 12 VDC) that the micro-controller unit (MCU) **130** can monitor without being damaged. The MCU **130** can be, for example, a Motorola 68HC908 series micro-controller, available from Motorola. In accordance with an embodiment of the present invention, the MCU **130** monitors the stepped down voltage (e.g., about 12 VDC), which is labeled the AC voltage sense signal in FIG. **7**, to determine if the AC line voltage is above or below the nominal 110 VAC, and to sense changes in the AC line voltage. For example, if a nominal 110 VAC increases by 10% to 121 VAC, then the stepped-down DC voltage will also increase by 10%. The MCU **130** can sense this increase and then reduce the pulse width, duty cycle and/or frequency of the low-voltage pulses to maintain the output power (provided to the high-voltage generator **170**) to be the same as when the line voltage is at 110 VAC. Conversely, when the line voltage drops, the MCU **130** can sense this decrease and appropriately increase the pulse width, duty cycle and/or frequency of the low-voltage pulses to maintain a constant output power. Such voltage adjustment features of the present invention also enable the same unit **200** to be used in different countries that have different nominal voltages than in the United States (e.g., in Japan the nominal AC voltage is 100 VAC).

The high-voltage pulse generator **170** is coupled between the first electrode array **230** and the second electrode array **240**, to provide a potential difference between the arrays. Each array can include one or more electrodes. The high-voltage pulse generator **170** maybe implemented in many ways. In the embodiment shown, the high-voltage pulse generator **170** includes an electronic switch **126**, a step-up transformer **116** and a voltage doubler **118**. The primary side of the step-up transformer **116** receives the first DC voltage (e.g., 160 VDC) from the DC power supply. An electronic switch receives low-voltage pulses (of perhaps 20-25 KHz frequency) from the micro-controller unit (MCU) **130**. Such a switch is shown as an insulated gate bipolar transistor (IGBT) **126**. The IGBT **126**, or other appropriate switch, couples the low-voltage pulses from the MCU **130** to the input winding of the step-up transformer **116**. The secondary winding of the transformer **116** is coupled to the voltage doubler **118**, which outputs the high-voltage pulses to the first and second electrode arrays **230** and **240**. In general, the IGBT **126** operates as an electronic on/off switch. Such a transistor is well known in the art and does not require a further description.

When driven, the generator **170** receives the low-input DC voltage (e.g., 160 VDC) from the DC power supply **114** and the low-voltage pulses from the MCU **130**, and generates high-voltage pulses of preferably at least 5 KV peak-to-peak with a repetition rate of about 20 to 25 KHz. Preferably, the voltage doubler **118** outputs about 6 to 9 KV to the first array **230**, and about 12 to 18 KV to the second array **240**. It is within the scope of the present invention for the voltage doubler **118** to produce greater or smaller voltages. The high-voltage pulses preferably have a duty cycle of about 10%-15%, but may have other duty cycles, including a 100% duty cycle.

The MCU **130** receives an indication of whether the control dial **214** is set to the LOW, MEDIUM or HIGH airflow setting. The MCU **130** controls the pulse width, duty cycle and/or frequency of the low-voltage pulse signal provided to switch **126**, to thereby control the airflow output of the device **200**, based on the setting of the control dial **214**. To increase the airflow output, the MCU **130** can increase the pulse width, frequency and/or duty cycle. Conversely, to decrease the airflow output rate, the MCU **130** can reduce the pulse width, frequency and/or duty cycle. In accordance with an embodiment, the low-voltage pulse signal (provided from the MCU **130** to the high-voltage generator **170**) can have a fixed pulse width, frequency and duty cycle for the LOW setting, another fixed pulse width, frequency and duty cycle for the MEDIUM setting, and a further fixed pulse width, frequency and duty cycle for the HIGH setting. However, depending on the setting of the control dial **214**, the above-described embodiment may produce too much ozone (e.g., at the HIGH setting) or too little airflow output (e.g., at the LOW setting). Accordingly, a more elegant solution, described below, is preferred.

In accordance with an embodiment of the present invention, the low-voltage pulse signal created by the MCU **130** modulates between a “high” airflow signal and a “low” airflow signal, with the control dial setting specifying the durations of the “high” airflow signal and/or the “low” airflow signal. This will produce an acceptable airflow output, while limiting ozone production to acceptable levels, regardless of whether the control dial **214** is set to HIGH, MEDIUM or LOW. For example, the “high” airflow signal can have a pulse width of 5 microseconds and a period of 40 microseconds (i.e., a **12.5** % duty cycle), and the “low” airflow signal can have a pulse width of 4 microseconds and a period of 40 microseconds (i.e., a 10% duty cycle). When the control dial **214** is set to HIGH, the MCU **130** outputs a low-voltage pulse signal that modulates between the “low” airflow signal and the “high” airflow signal, with, for example, the “high” airflow signal being output for 2.0 seconds, followed by the “low” airflow signal being output for 8.0 seconds. When the control dial **214** is set to MEDIUM, the “low” airflow signal can be increased to, for example, 16 seconds (e.g., the low voltage pulse signal will include the “high” airflow signal for 2.0 seconds, followed by the “low” airflow signal for 16 seconds). When the control dial **214** is set to LOW, the “low” airflow signal can be further increased to, for example, 24 seconds (e.g., the low voltage pulse signal will include a “high” airflow signal for 2.0 seconds, followed by the “low” airflow signal for 24 seconds).

Alternatively, or additionally, the frequency of the low-voltage pulse signal (used to drive the transformer **116**) can be adjusted to distinguish between the LOW, MEDIUM and HIGH settings.

In accordance with another embodiment of the present invention, when the control dial **214** is set to HIGH, the electrical signal output from the MCU **130**, modulating between the “high” and “low” airflow signals, will continuously drive the high-voltage generator **170**. When the control dial **214** is set to MEDIUM, the electrical signal output from the MCU **130** will cyclically drive the high-voltage generator a further predetermined amount of time (e.g., a further 25 seconds). Thus, the overall airflow rate through the device **200** is slower when the dial **214** is set to MEDIUM than when the control dial **214** is set to HIGH. When the control dial **214** is set to LOW, the signal from the MCU **130** will cyclically drive the high-voltage generator **170** for a predetermined amount of time (e.g., 25 seconds), and then drop to a zero or a lower voltage for a longer time period (e.g., 75 seconds). It is within the scope and spirit of the present invention that the HIGH, MEDIUM, and LOW settings will drive the high-voltage generator **170** for longer or shorter periods of time.

The MCU **130** provides the low-voltage pulse signal, including “high” airflow signals and “low” airflow signals, to the high-voltage generator **170**, as described above. By way of example, the “high” airflow signal causes the voltage doubler **118** to provide 9 KV to the first array **230**, while 18 KV is provided to the second array **240**; and the “low” airflow signal causes the voltage doubler **118** to provide 6 KV to the first array **230**, while 12 KV is provided to the second array **240**. The voltage difference between the first array **230** and the second array **240** is proportional to the actual airflow output rate of the device **200**. In general, a greater voltage differential is created between the first and second array by the “high” airflow signal. It is within the scope of the present invention for the MCU **130** and the high-voltage generator **170** to produce other voltage potential differentials between the first and second arrays **230** and **240**. The various circuits and components comprising the high voltage pulse generator **170** can, for example, be fabricated on a printed circuit board mounted within housing **210**. The MCU **130** can be located on the same or a different circuit board.

As mentioned above, device **200** includes a boost button **216**. In accordance with an embodiment of the present invention, when the MCU **130** detects that the boost button **216** has been depressed, the MCU **130** drives the high-voltage generator **170** as if the control dial **214** was set to the HIGH setting for a predetermined amount of time (e.g., 5 minutes), even if the control dial **214** is set to LOW or MEDIUM (in effect overriding the setting specified by the dial **214**). This will cause the device **200** to run at a maximum airflow rate for the boost time period (e.g., a 5 minute period). Alternatively, the MCU **130** can drive the high-voltage generator **170** to even further increase the ozone and particle capture rate for the boost time period. For example, the MCU **130** can continually provide the “high” airflow signal to the high-voltage generator **170** for the entire boost time period, thereby creating increased amounts of ozone. The increased amounts of ozone will reduce the odor in a room faster than if the device **200** was set to HIGH. The maximum airflow rate will also increase the particle capture rate of the device **200**. In a preferred embodiment, pressing the boost button **216** will increase the airflow rate and ozone production continuously for 5 minutes. This time period maybe longer or shorter. At the end of the preset time period (e.g., 5 minutes), the device **200** will return to the airflow rate previously selected by the control dial **214**.

The MCU **130** can provide various timing and maintenance features. For example, the MCU **130** can provide a cleaning reminder feature (e.g., a 2-week timing feature) that provides a reminder to clean the device **200** (e.g., by causing indicator light **219** to turn on amber, and/or by triggering an audible alarm (not shown) that produces a buzzing or beeping noise). The MCU **130** can also provide arc sensing, suppression and indicator features, as well as the ability to shut down the high-voltage generator **170** in the case of continued arcing. These and other features are described in additional detail below.

Arc Sensing and Suppression

FIG. **8**

The flow diagram of FIG. **8** is used to describe embodiments of the present invention that sense and suppress arcing between the first electrode array **230** and the second electrode array **240**. The process begins at step **802**, which can be when the function dial is turned from “OFF” to “ON” or “GP/ON.” At a step **804**, an arcing threshold is set, based on the airflow setting specified (by a user) using the control dial **214**. For example, there can be a high threshold, a medium threshold and a low threshold. In accordance with an embodiment of the present invention, these thresholds are current thresholds, but it is possible that other thresholds, such as voltage thresholds, can be used. At a step **806**, an arc count is initialized. At a step **807** a sample count is initialized.

At a step **808**, a current associated with the electro-kinetic system is periodically sampled (e.g., one every 10 msec) to produce a running average current value. In accordance with an embodiment of the present invention, the MCU **130** performs this step by sampling the current at the emitter of the IGBT **126** of the high-voltage generator **170** (see FIG. **7**). The running average current value can be determined by averaging a sampled value with a previous number of samples (e.g., with the previous three samples). A benefit of using averages, rather than individual values, is that averaging has the effect of filtering out and thereby reducing false arcing detections. However, in alternative embodiments no averaging is used.

At a next step **810**, the average current value determined at step **808** is compared to the threshold value, which was specified at step **804**. If the average current value does not equal or exceed the threshold value (i.e., if the answer to step **810** is NO), then there is a determination at step **822** of whether the threshold has not been exceeded during a predetermined amount of time (e.g., over the past 60 seconds). If the answer to step **822** is NO (i.e., if the threshold has been exceeded during the past 60 seconds), then flow returns to step **808**, as shown. If the answer to step **822** is YES, then there is an assumption that the cause for any previous arcing is no longer present, and flow returns to step **806** and the arc count and the sample count are both reinitialized. Returning to step **810**, if the average current value reaches the threshold, then it is assumed that arcing has been detected (because arcing will cause an increase in the current), and the sample count is incremented at a step **812**.

The sample count is then compared to a sample count threshold (e.g., the sample count threshold=30) at a step **814**. Assuming, for example, a sample count threshold of 30, and a sample frequency of 10 msec, then the sample count equaling the sample count threshold corresponds to an accumulated arcing time of 300 msec (i.e., 10 msec*30=300 msec). If the sample count has not reached the sample count threshold (i.e., if the answer to step **814** is NO), then flow returns to step **808**. If the sample count equals the sample count threshold, then the MCU **130** temporarily shuts down the high-voltage generator **170** (e.g., by not driving the generator **170**) for a predetermined amount of time (e.g., 80 seconds) at a step **816**, to allow a temporary condition causing the arcing to potentially go away. For examples: temporary humidity may have caused the arcing; or an insect temporarily caught between the electrode arrays **230** and **240** may have caused the arcing. Additionally, the arc count is incremented at step **818**.

At a step **820**, there is a determination of whether the arc count has reached the arc count threshold (e.g., the arc count threshold=3), which would indicate unacceptable continued arcing. Assuming, for example, a sample count threshold of 30, and a sample frequency of 10 msec, and an arc count threshold of 3, then the arc count equaling the arc count threshold corresponds to an accumulated arcing time of 900 msec (i.e., 3*10 msec*30=900 msec). If the arc count has not reached the arc count threshold (i.e., if the answer to step **820** is NO), then flow returns to step **807**, where the sample count is reset to zero, as shown. If the arc count equals the arc count threshold (i.e., if the answer to step **820** is YES), then the high-voltage generator **170** is shut down at step **824**, to prevent continued arcing from damaging the device **200** or producing excessive ozone. At this point, the MCU **130** causes the overload/cleaning light **219** to light up red, thereby notifying the user that the device **200** has been “shut down.” The term “shut down,” in this respect, means that the MCU **130** stops driving the high-voltage generator **170**, and thus the device **200** stops producing ion and ozone containing airflow. However, even after “shut down,” the MCU **130** continues to operate.

Once the device **200** is shut down at step **824**, the MCU **130** will not again drive the high voltage generator **170** until the device **200** is reset. In accordance with an embodiment of the present invention, the device **200** can be reset by turning it off and back on (e.g., by turning function dial **218** to "OFF" and then to "ON" or "ON/GP"), which will in effect re-initialize the counters at step **806** and **807**. Alternatively, or additionally, the device **200** includes a sensor, switch, or other similar device, that is triggered by the removal of the second electrode array **240** (presumably for cleaning) and/or by the replacement of the second electrode array **240**. The device can alternately or additionally include a reset button or switch. The sensor, switch, reset button/switch or other similar device, provides a signal to the MCU **130** regarding the removal and/or replacement of the second electrode array **240**, causing the MCU **130** to re-initialize the counters (at step **806** and **807**) and again drive the high voltage generator **170**.

Arcing can occur, for example, because a carbon path is produced between the first electrode array **230** and the second electrode array **240**, e.g., due to a moth or other insect that got caught in the device **200**. Assuming the first and/or second electrode arrays **230** and **240** are appropriately cleaned prior to the device **200** being reset, the device should operate normally after being reset. However, if the arc-causing condition (e.g., the carbon path) persists after the device **200** is reset, then the features described with reference to FIG. **8** will quickly detect the arcing and again shut down the device **200**.

More generally, embodiments of the present invention provide for temporary shut down of the high voltage generator **170** to allow for a temporary arc-creating condition to potentially go away, and for a continued shut down of the high-voltage generator **170** if the arcing continues for an unacceptable duration. This enables the device **200** to continue to provide desirable quantities of ions and ozone (as well as airflow) following temporary arc-creating conditions. This also provides for a safety shut down in the case of continued arcing.

In accordance with alternative embodiments of the present invention, at step **816** rather than temporarily shutting down the high-voltage generator **170** for a predetermined amount of time, the power is temporarily lowered. The MCU **130** can accomplish this by appropriately adjusting the signal that it uses to drive the high-voltage generator **170**. For example, the MCU **130** can reduce the pulse width, duty cycle and/or frequency of the low-voltage pulse signal provided to switch **126** for a pre-determined amount of time before returning the low-voltage pulse signal to the level specified according to the setting of the control dial **214**. This has the effect of reducing the potential difference between the arrays **230** and **240** for the predetermined amount of time.

It would be apparent to one of ordinary skill in the relevant art that some of the steps in the flow diagram of FIG. **8** need not be performed in the exact order shown. For example, the order of steps **818** and **816** can be reversed or these steps can be performed simultaneously. However, it would also be apparent to one of ordinary skill in the relevant art that some of the steps should be performed before others. This is because certain steps use the results of other steps. The point is, the order of the steps is typically only important where a step uses results of another step. Accordingly, one of ordinary skill in the relevant art would appreciate that embodiments of the present invention should not be limited to the exact orders shown in the figures. Additionally, one of ordinary skill in the relevant art would appreciate that embodiments of the present invention can be implemented using subgroups of the steps that are shown in the figures.

In accordance with embodiments of the present invention, rather than periodically sampling a current or voltage associated with the electro-kinetic system at step **808**, the MCU **130** can more continually monitor or sample the current or voltage associated with the electro-kinetic system so that even narrow transient spikes (e.g., of about 1 msec. in duration) resulting from arcing can be detected. In such embodiments, the MCU **130** can continually compare an arc-sensing signal to an arcing threshold (similar to step **810**). For example, when the arc-sensing signal reaches or exceeds the arcing threshold, a triggering event occurs that causes the MCU **130** to react (e.g., by incrementing a count, as instep **812**). If the arcing threshold is exceeded more than a predetermined number of times (e.g., once, twice or three times, etc.) within a predetermined amount of time, then the unit **200** is temporarily shut down (similar to steps **810-816**). If arcing is not detected for a predetermined amount of time, then an arcing count can be reset (similar to step **822**). Thus, the flow chart of FIG. **8** applies to these event type (e.g., by interrupt) monitoring embodiments.

Other Electrode Configurations

In practice, unit **200** is placed in a room and connected to an appropriate source of operating potential, typically 110 VAC. The energizing ionization unit **200** emits ionized air and ozone via outlet vents **260**. The airflow, coupled with the ions and ozone, freshens the air in the room, and the ozone can beneficially destroy or at least diminish the undesired effects of certain odors, bacteria, germs, and the like. The airflow is indeed electro-kinetically produced, in that there are no intentionally moving parts within the unit. (Some mechanical vibration may occur within the electrodes.)

In the various embodiments, electrode assembly **220** comprises a first array **230** of at least one electrode or conductive surface, and further comprises a second array **240** of at least one electrode or conductive surface. Material(s) for electrodes, in one embodiment, conduct electricity, are resistant to corrosive effects from the application of high voltage, yet strong enough to be cleaned.

In the various electrode assemblies to be described herein, electrode(s) **232** in the first electrode array **230** can be fabricated, for example, from tungsten. Tungsten is sufficiently robust in order to withstand cleaning, has a high melting point to retard breakdown due to ionization, and has a rough exterior surface that seems to promote efficient ionization. On the other hand, electrode(s) **242** in the second electrode array **240** can have a highly polished exterior surface to minimize unwanted point-to-point radiation. As such, electrode(s) **242** can be fabricated, for example, from stainless steel and/or brass, among other materials. The polished surface of electrode(s) **242** also promotes ease of electrode cleaning.

The electrodes can be lightweight, easy to fabricate, and lend themselves to mass production. Further, electrodes described herein promote more efficient generation of ionized air, and appropriate amounts of ozone (indicated in several of the figures as O_3).

Various electrode configurations for use in the device **200** are described in U.S. patent application Ser. No. 10/074,082, filed Feb. 12, 2002, entitled "Electro-Kinetic Air Transporter-Conditioner Devices with an Upstream Focus Electrode," incorporated herein by reference, and in the related application mentioned above.

In one embodiment, the positive output terminal of high-voltage generator **170** is coupled to first electrode array **230**, and the negative output terminal is coupled to second electrode array **240**. It is believed that with this arrangement the net polarity of the emitted ions is positive, e.g., more positive ions than negative ions are emitted. This coupling polarity has been found to work well, including minimizing unwanted audible electrode vibration or hum. However, while generation of positive ions is conducive to a relatively silent airflow, from a health standpoint, it is desired that the output airflow be richer in negative ions, not positive ions. It is noted that in some embodiments, one port (such as the negative port) of the high voltage pulse generator **170** can in fact be the ambient air. Thus, electrodes in the second array need not be connected to the high-voltage pulse generator using a wire. Nonetheless, there will be an "effective connection" between the second array electrodes and one output port of the high-voltage pulse generator, in this instance, via ambient air. Alternatively the negative output terminal of the high-voltage pulse generator **170** can be connected to the first electrode array **230** and the positive output terminal can be connected to the second electrode array **240**. In either embodiment, the high-voltage generator **170** will produce a potential difference between the first electrode array **230** and the second electrode array **240**.

When voltage or pulses from high-voltage pulse generator **170** are coupled across first and second electrode arrays **230** and **240**, a plasma-like field is created surrounding electrodes in first array **230**. This electric field ionizes the ambient air between the first and second electrode arrays and establishes an "OUT" airflow that moves towards the second array.

Ozone and ions are generated simultaneously by the first array electrodes **230**, essentially as a function of the potential from generator **170** coupled to the first array of electrodes or conductive surfaces. Ozone generation can be increased or decreased by increasing or decreasing the potential at the first array. Coupling an opposite polarity potential to the second array electrodes **240** essentially accelerates the motion of ions generated at the first array, producing the out airflow. As the ions and ionized particulate move toward the second array, the ions and ionized particles push or move air molecules toward the second array. The relative velocity of this motion may be increased, by way of example, by decreasing the potential at the second array relative to the potential at the first array.

For example, if +10 KV were applied to the first array electrode(s), and no potential were applied to the second array electrode(s), a cloud of ions (whose net charge is positive) would form adjacent the first electrode array. Further, the relatively high 10 KV potential would generate substantial ozone. By coupling a relatively negative potential to the second array electrode(s), the velocity of the air mass moved by the net emitted ions increases.

On the other hand, if it were desired to maintain the same effective outflow (OUT) velocity, but to generate less ozone, the exemplary 10 KV potential could be divided between the electrode arrays. For example, generator **170** could provide +4 KV (or some other fraction) to the first array electrodes and −6 KV (or some other fraction) to the second array electrodes. In this example, it is understood that the +4 KV and the −6 KV are measured relative to ground. Understandably it is desired that the unit **200** operates to output appropriate amounts of ozone. Accordingly, in one embodiment, the high voltage is fractionalized with about +4 KV applied to the first array electrodes and about −6 KV applied to the second array electrodes.

In one embodiment, electrode assembly **220** comprises a first array **230** of wire-shaped electrodes, and a second array **240** of generally "U"-shaped electrodes **242**. In some embodiments, the number **N1** of electrodes comprising the first array **230** can differ by one relative to the number **N2** of electrodes comprising the second array **240**. In many of the embodiments shown, **N2>N1**. However, if desired, additional first electrodes could be added at the outer ends of the array such that **N1>N2**, e.g., five first electrodes compared to four second electrodes.

As previously indicated, first or emitter electrodes **232** can be lengths of tungsten wire, whereas collector electrodes **242** can be formed from sheet metal, such as stainless steel, although brass or other sheet metal could be used. The sheet metal can be readily configured to define side regions and bulbous nose region, forming a hollow, elongated "U"-shaped electrodes, for example.

In one embodiment, the spaced-apart configuration between the first and second arrays **230** and **240** is staggered. Each first array electrode **232** can be substantially equidistant from two second array electrodes **242**. This symmetrical staggering has been found to be an efficient electrode placement. The staggering geometry can be symmetrical in that adjacent electrodes in one plane and adjacent electrodes in a second plane are spaced-apart a constant distance, **Y1** and **Y2** respectively. However, a non-symmetrical configuration could also be used. Also, it is understood that the number of electrodes may differ from what is shown.

In one embodiment ionization occurs as a function of high-voltage electrodes. For example, increasing the peak-to-peak voltage amplitude and the duty cycle of the pulses from the high-voltage pulse generator **170** can increase ozone content in the output flow of ionized air.

In one embodiment, the second electrodes **242** can include a trail electrode pointed region which help produce the output of negative ions. In one embodiment the electrodes of the second array **242** of electrodes is "U"-shaped. In one embodiment a single pair of "L"-shaped electrode(s) in cross section can be additionally used.

In one embodiment, the electrodes assembly **220** has a focus electrode(s). The focus electrodes can produce an enhanced air flow exiting the devices. The focus electrode can have a shape that does not have sharp edges manufactured from a material that will not erode or oxides existing with steel. In one embodiment, the diameter of the focus electrode is 15 times greater than the diameter of the first electrode. The diameter of the focus electrode can be selected such that the focus electrode does not function as an ion-generating surface. In one embodiment, the focus electrodes are electrically connected to the first array **230**. Focus electrodes help direct the air flow toward the second electrode for guiding it towards particles towards the trailing sides of the second electrode.

The focus electrodes can be "U" or "C"-shaped with holes extending therethrough to minimize the resistance of the focus electrode on the air flow rate. In one embodiment, the electrode assembly **220** has a pin-ring electrode assembly. The pin-ring electrode assembly includes a pin, cone or triangle shaped, first electrode and a ring-shaped second electrode (with an opening) down-stream of the first electrode.

The system can use an additional downstream trailing electrode. The trailing electrode can be aerodynamically smooth so as not to interfere with the air flow. The trailing electrodes can have a negative electrical charge to reduce positively charged particles in the air flow. Trailing electrodes can also be floating or set to ground. Trailing electrodes can act as a second surface to collect positively-charged particles. Trailing electrodes can also reflect charged particles towards the second electrodes **242**. The trailing electrodes can also emit a small amount of negative ions into the air flow which can neutralize the positive ions emitted by the first electrodes **232**.

The assembly can also use interstitial electrodes positioned between the second electrodes **242**. The interstitial electrodes can float, be set to ground, or be put at a positive high voltage, such as a portion of the first electrode voltage. The interstitial electrodes can deflect particulate towards the second electrodes.

The first electrodes **232** can be made slack, kinked or coiled in order to increase the amount of ions emitted by the first electrode array **230**. Additional details about all of the above-described electrode configurations are provided in the above-mentioned applications, which have been incorporated herein by reference.

FIG. **9** illustrates an alternate embodiment of the device **200** shown in FIG. **2**A. In the embodiment shown in FIG. **9**, the housing **210** is made from a lightweight inexpensive material, ABS plastic for example. As a germicidal lamp **290** is located within the housing **210**, the material must be able to withstand prolonged exposure to class UV-C light. As described above, non-"hardened" material will degenerate over time if exposed to light such as UV-C. As described above, the housing **210** can be manufactured from CYCLOLAC7 ABS Resin (material designation VW300 (f2)), which is manufactured by General Electric Plastics Global Products, and is certified by UL Inc. for use with ultraviolet light. In alternative embodiments, the housing **210** can be manufactured from other UV appropriate materials.

In the embodiment shown in FIG. **9**, the housing **210** is oval, elliptical or teardrop-shaped. The housing **210** includes at least one air intake **250**, and at least one air outlet **260**. Covering the inlet **250** and the outlet **260** are fins or louvers **212** and **214**, respectively. The fins **212**,**214** are preferably elongated and upstanding, and in one embodiment, oriented to minimize resistance to the airflow entering and exiting the device **200**. However, other fin and housing shapes are also possible.

From the above it is evident that in the embodiment shown in FIG. **9**, the cross-section of the housing **210** is oval, elliptical, or teardrop-shaped with the inlet **250** and outlet **260** narrower than the middle (see line A-A in FIG. **5**A) of the housing **210**. Accordingly, the airflow, as it passes across line A-A, is slower due to the increased width and area of the housing **210**. Any bacteria, germs, or virus within the airflow will have a greater dwell time and be neutralized by a germicidal device, such as an ultraviolet lamp.

In the embodiment shown in FIG. **9**, the device also includes an impeller fan **902** which during operation produces very little noise. The fan **902** is designed to draw air into the device **200** through an opening **904** in the base of the device **200**. Air drawn into the device **200** through the opening **904** is directed vertically upward between the emitter electrodes **230** and the air intake **250** at the rear of the housing **210**. In the embodiment shown in FIG. **9**, redirection of the intake air is caused by a guide **906**. The interior of the housing **210** also includes a number of baffles **908** that are designed to direct the upward air flow caused by the fan **902** towards the air outlet **260**. While FIG. **9** depicts redirection of the intake air belt caused by a guide, any convenient mechanism can be employed.

In the embodiment shown in FIG. **9**, multiple arched baffles **908** are depicted. However, in alternate embodiments more or fewer baffles **908** having varying shapes can be used. Additionally, in one embodiment, the device **200** may not include any baffles **908**.

In the embodiment shown in FIG. **9**, the fan **902** is a "whisper" fan **902** which makes little or no humanly-audible noise while in operation. In alternate embodiments, an alternate fan can be used or in still further alternate embodiments any other device for moving air may be employed.

FIG. **10** illustrates an alternate embodiment of the device **200** shown in FIG. **2**A. In the embodiment shown in FIG. **10**, the housing **210** is made from a lightweight material, ABS plastic for example. As a germicidal lamp **290** is located within the housing **210**, the material must be able to withstand prolonged exposure to class UV-C light. As described above, non-"hardened" material will degenerate over time if exposed to light such as UV-C. In one embodiment, the housing **210** may be manufactured from CYCLOLAC7 ABS Resin (material designation VW300(f2)), which is manufactured by General Electric Plastics Global Products, and is certified by UL Inc. for use with ultraviolet light. However, in alternative embodiments the housing **210** can be manufactured from other UV appropriate materials.

In the embodiment shown in FIG. **10**, the housing **210** is aerodynamically oval, elliptical or teardrop-shaped. The housing **210** includes at least one air outlet **260**. Covering the outlet **260** are fins or louvers **214**. The fins **214** are preferably elongated and upstanding, and in one embodiment, oriented to minimize resistance to the airflow exiting the device **200**. However, in alternate embodiments other fin and housing shapes are also possible.

In the embodiment shown in FIG. **10**, the back side **1002** of the housing **210** is substantially solid to restrict air flow into the device from the back side **1002** of the housing **210**.

In the embodiment shown in FIG. **10**, the cross-section of the housing **210** is oval, elliptical, or teardrop-shaped with the outlet **260** narrower than the middle (see line A-A in FIG. **5**A) of the housing **210**. Accordingly, the airflow, as it passes across line A-A, is slower due to the increased width and area of the housing **210**. Any bacteria, germs, or virus within the airflow will have a greater dwell time and be neutralized by a germicidal device, such as an ultraviolet lamp.

In the embodiment shown in FIG. **10**, the device also includes an impeller fan **902** that during operation produces very little, if any, noise. The fan **902** is designed to draw air into the device **200** through an opening **904** in the base of the device **200**. Air drawn into the device **200** through the opening **904** is directed vertically upward between the emitter electrodes **230** and the back side **1002** of the housing **210**. In the embodiment shown in FIG. **10**, redirection of the intake air is caused by a guide **906**. The interior of the housing **210** also includes a number of baffles **908** coupled with the back side **1002** of the housing **1002**, that are designed to direct the upward air flow caused by the fan **902** and the guide **906** towards the air outlet **260**.

In the embodiment shown in FIG. **10**, multiple arched baffles **908** are depicted. However, in alternate embodiments more or fewer baffles **908** having varying shapes can be used. Additionally, in one embodiment, the device **200** may not include any baffles **908**.

In the embodiment shown in FIG. **10**, the fan **902** is a "whisper" fan **902** which makes little or no humanly-audible noise while in operation. In alternate embodiments, an alternate fan can be used or in still further alternate embodiments any other device for moving air may be employed.

FIG. **11** illustrates an alternate embodiment of the device **200** shown in FIG. **2**A. In the embodiment shown in FIG. **11**, the housing **210** is made from a lightweight material, ABS plastic for example. As a germicidal lamp **290** is located within the housing **210**, the material must be able to withstand prolonged exposure to class UV-C light. As described above, non-"hardened" material will degenerate over time if exposed to light such as UV-C. In the embodiment shown in FIG. **11**, the housing **210** may be manufactured from CYCLOLAC7 ABS Resin (material designation VW300 (f2)), which is manufactured by General Electric Plastics Global Products, and is certified by UL Inc. for use with ultraviolet light. However, it is within the scope of the present invention to manufacture the housing **210** from other UV appropriate materials.

In the embodiment shown in FIG. **11**, the housing **210** is oval, elliptical or teardrop-shaped. The housing **210** includes at least one air outlet **260**.

In the embodiment shown in FIG. **11**, the back side **1002** of the housing **210** is substantially solid to restrict air flow into the device from the back side **1002** of the housing **210**.

Covering the outlet **260** are fins or louvers **214**. The fins **214** are preferably elongated and upstanding, and thus in one embodiment, oriented to minimize resistance to the airflow exiting the device **200**. However, other fin and housing shapes are also possible.

In the embodiment shown in FIG. **11**, the cross-section of the housing **210** is oval, elliptical, or teardrop-shaped, with the outlet **260** narrower than the middle (see line A-A in FIG. **5**A) of the housing **210**. Accordingly, the airflow, as it passes across line A-A, is slower due to the increased width and area of the housing **210**. Any bacteria, germs, or virus within the airflow will have a greater dwell time and be neutralized by a germicidal device, such as an ultraviolet lamp.

In the embodiment shown in FIG. **11**, the device also includes an impeller fan **902** that during operation produces very little, if any, noise. The fan **902** is designed to draw air into the device **200** through an opening **904** in the base of the device **200**. Air drawn into the device **200** through the opening **904** is directed vertically upward between the emitter electrodes **230** and the back side **1002** of the housing **210**. In the embodiment shown in FIG. **10**, redirection of the intake air is caused by a guide **906**. The interior of the housing **210** also includes a number of conduits **1102**, **1104**, **1106** designed to vertically distribute the upward air flow caused by the fan **902** and the guide **906**.

In the embodiment shown in FIG. **1**, three semi-cylindrical conduits **1102**, **1104**, **1106** are depicted. However, in alternate embodiments more or fewer conduits **908** having varying shapes can be used. Additionally, in one embodiment, the device **200** may not include any conduits. In the embodiment shown in FIG. **11**, the conduits **1102**, **1104**, **1106** are each vertical. However, in alternate embodiments, the conduits may be angled or bent in any convenient manner to direct air flow.

In the embodiment shown in FIG. **11**, the fan **902** is a "whisper" fan **902** which makes little or no humanly-audible noise while in operation. In alternate embodiments, an alternate fan can be used or in still further alternate embodiments any other device for moving air may be employed.

FIG. **12** is atop-down cross-sectional view of the embodiment shown in FIG. **11**. FIG. **12** shows that the housing **210** contains emitter electrodes **230**, collector electrodes **242** and three conduits **1102**, **1104**, **1106**. Conduit **1106** is taller than conduit **1104** which is taller than conduit **1102**. In this embodiment, the conduits divide the device **200** into upper, middle and lower air flow regions. In the embodiment shown in FIG. **12**, the conduits **1102**, **1104**, **1106** are vertical and have a semi-cylindrical shape. Each of conduits **1102**, **1104**, **1106** include a top deflector **1103**, **1105**, **1107** respectively which redirects air toward the collector electrode **242**. However, in alternate embodiments the conduits **1102**, **1104**, **1106** may have any convenient shape and may be angled at any convenient angle. Additionally, the conduits **1102**, **1104**, **1106** may be bent or configured in any convenient manner to regulate the flow of air through the device **200**. Still alternatively, for all the embodiments depicted in FIGS. **9**-**12**, the air guide **906** can be eliminated and the collector electrode **242** can be as a baffle to divert the air flow from the fan **902** relative to the collector electrode **242**.

FIG. **13** illustrates an alternate embodiment of the device **200** shown in FIG. **2**A. As described above, the housing **210** can be made from a lightweight inexpensive material, ABS plastic for example. As a germicidal lamp **290** is located within the housing **210**, the material must be able to withstand prolonged exposure to class UV-C light. As described above, non-"hardened" material will degenerate over time if exposed to light such as UV-C. As described above, the housing **210** can be manufactured from CYCLOLAC7 ABS Resin (material designation VW300(f2)), which is manufactured by General Electric Plastics Global Products, and is certified by UL Inc. for use with ultraviolet light. In alternative embodiments, the housing **210** can be manufactured from other UV appropriate materials.

In the embodiment shown in FIG. **13**, the housing **210** is oval, elliptical or teardrop-shaped. The housing **210** includes at least one air intake **250**, and at least one air outlet **260**. Covering the inlet **250** and the outlet **260** are fins or louvers **212** and **214** respectively. The fins **212**, **214** are preferably elongated and upstanding, and in one embodiment, oriented to minimize resistance to the airflow entering and exiting the device **200**. However, other fin and housing shapes are also possible. The housing **210** also includes at least one opening **1302** at the top of the device **200** which can be partially or fully covered.

From the above it is evident that in the embodiment shown in FIG. **13**, the cross-section of the housing **210** is oval, elliptical, or teardrop-shaped with the inlet **250** and outlet **260** narrower than the middle (see line A-A in FIG. **5**A) of the housing **210**. Accordingly, the airflow, as it passes across line A-A, is slower due to the increased width and area of the housing **210**. Any bacteria, germs, or virus within the airflow will have a greater dwell time and be neutralized by a germicidal device, such as an ultraviolet lamp.

In the embodiment shown in FIG. **13**, the device also includes an impeller fan **902** which during operation produces very little noise. The fan **902** is designed to draw air into the device **200** through an opening **904** in the base of the device **200**. Air drawn into the device **200** through the opening **904** is directed vertically upward between the emitter electrodes **230** and the air intake **250** at the rear of the housing **210**. Air drawn into the device **200** by the fan **902** is directed upward towards the opening **1302** at the top of the housing **210**.

In the embodiment shown in FIG. **13**, the fan **902** is a "whisper" fan **902** which makes little or no humanly-audible noise while in operation. In alternate embodiments, an alternate fan can be used or in still further alternate embodiments any other device for moving air may be employed.

FIG. **14** illustrates an alternate embodiment of the device **200** shown in FIG. **2**A. As described above, the housing **210** can be made from a lightweight inexpensive material, ABS plastic for example. As a germicidal lamp **290** is located within the housing **210**, the material must be able to withstand prolonged exposure to class UV-C light. As described above, non-"hardened" material will degenerate over time if exposed to light such as UV-C. As described above, the housing **210** can be manufactured from CYCLOLAC7 ABS Resin (material designation VW300(f2)), which is manufactured by General Electric Plastics Global Products, and is certified by UL Inc. for use with ultraviolet light. In alternative embodiments, the housing **210** can be manufactured from other UV appropriate materials.

In the embodiment shown in FIG. **14**, the housing **210** is oval, elliptical or teardrop-shaped. The housing **210** includes at least one air intake **250**, and at least one air outlet **260**. Covering the inlet **250** and the outlet **260** are fins or louvers **212** and **214** respectively. The fins **212**, **214** are preferably elongated and upstanding, and in one embodiment, oriented to minimize resistance to the airflow entering and exiting the device **200**. However, other fin and housing shapes are also possible.

From the above it is evident that in the embodiment shown in FIG. **14**, the cross-section of the housing **210** is oval, elliptical, or teardrop-shaped with the inlet **250** and outlet **260** narrower than the middle (see line A-A in FIG. **5**A) of the housing **210**. Accordingly, the airflow, as it passes across line A-A, is slower due to the increased width and area of the housing **210**. Any bacteria, germs, or virus within the airflow will have a greater dwell time and be neutralized by a germicidal device, such as an ultraviolet lamp.

In the embodiment shown in FIG. **14**, the device also includes an impeller fan **902** which during operation produces very little noise. The fan **902** is designed to draw air into the device **200** through the inlet **250**. Air drawn into the device **200** through the inlet is directed horizontally towards the outlet **260**.

In the embodiment shown in FIG. **14**, the fan **902** is a vertical paddle wheel type "whisper" fan **902** which makes little or no humanly-audible noise while in operation. In the embodiment shown in FIG. **14**, the fan **902** is driven by a motor **1402** which is operably coupled with a drive shaft **1404** of the fan **902** in any convenient manner. In alternate embodiments, an alternate fan can be used or in still further alternate embodiments any other device for moving air may be employed.

FIG. **15** is a top-down cross-sectional view of the embodiment shown in FIG. **14**. FIGS. **14** and **15** show that the housing **210** contains emitter electrodes **230**, collector electrodes **242**, and a vertical fan **1402**. In the embodiment shown in FIGS. **14** and **15**, the fan **902** extends substantially from the top of the device **200** to the base of the device **200**. However, in alternate embodiments the fan **902** may not extend the entire length of the device **2003**. Additionally, in alternate embodiments various other drive mechanisms maybe used to drive the fan **902** and/or various other air movement mechanisms can be used.

FIG. **16** illustrates an alternate embodiment of the device **200** shown in FIG. **2**A. As described above, the housing **210** can be made from a lightweight inexpensive material, ABS plastic for example. As a germicidal lamp **290** is located within the housing **210**, the material must be able to withstand prolonged exposure to class UV-C light. As described above, non-"hardened" material will degenerate over time if exposed to light such as TV-C. As described above, the housing **210** can be manufactured from CYCLOLAC7 ABS Resin (material designation VW300(f2)), which is manufactured by General Electric Plastics Global Products, and is certified by UL Inc. for use with ultraviolet light. In alternative embodiments, the housing **210** can be manufactured from other UV appropriate materials.

In the embodiment shown in FIG. **16**, the housing **210** is oval, elliptical or teardrop-shaped. The housing **210** includes at least one air intake **250**, and at least one air outlet **260**. Covering the inlet **250** and the outlet **260** are fins or louvers **212** and **214** respectively. The fins **212**, **214** are preferably elongated and upstanding, and in one embodiment, oriented to minimize resistance to the airflow entering and exiting the device **200**. However, other fin and housing shapes are also possible.

In the embodiment shown in FIG. **16**, the airflow is from the base of the housing **210** to the top of the housing **210**. Any bacteria, germs, or virus within the airflow will have a dwell time within the housing **210** sufficient to neutralize the germs or virus by means of a germicidal device, such as an ultraviolet lamp.

In the embodiment shown in FIG. **16**, the device also includes an impeller fan **902** which during operation produces very little noise. The fan **902** is designed to draw air into the device **200** through the inlet **250**. Air drawn into the device **200** through the inlet is directed vertically towards the outlet **260**, through the housing.

In the embodiment shown in FIG. **16**, the fan **902** is a "whisper" fan **902** which makes little or no humanly-audible noise while in operation. In alternate embodiments, an alternate fan can be used or in still further alternate embodiments any other device for moving air may be employed. This embodiment does not include emitter and collector electrodes. This embodiment advantageously has a self-contained UV lamp and an advantageous upstanding, elongated vertical form factor which takes up very little floor space. This embodiment can conveniently be positioned anywhere in a room as needed and does not interfere with the placement of other objects such as furniture.

FIG. **17** illustrates an alternate embodiment of the device **200** shown in FIG. **2**A. As described above, the housing **210** can be made from a lightweight inexpensive material, ABS plastic for example. As a germicidal lamp **290** is located within the housing **210**, the material must be able to withstand prolonged exposure to class UV-C light. As described above, non-"hardened" material will degenerate over time if exposed to light such as UV-C. As described above, the housing **210** can be manufactured from CYCLOLAC7 ABS Resin (material designation VW300(f2)), which is manufactured by General Electric Plastics Global Products, and is certified by UL Inc. for use with ultraviolet light. In alternative embodiments, the housing **210** can be manufactured from other UV appropriate materials.

In the embodiment shown in FIG. **17**, the housing **210** is oval, elliptical or teardrop-shaped. The housing **210** includes at least one air intake **250**, and at least one air outlet **260**. Covering the inlet **250** and the outlet **260** are fins or louvers **212** and **214** respectively. The fins **212**, **214** are preferably elongated and upstanding, and in one embodiment, oriented to minimize resistance to the airflow entering and exiting the device **200**. However, other fin and housing shapes are also possible.

From the above it is evident that in the embodiment shown in FIG. **17**, the cross-section of the housing **210** is oval, elliptical, or teardrop-shaped with the inlet **250** and outlet **260** narrower than the middle (see line A-A in FIG. **5**A) of the housing **210**. Accordingly, the airflow, as it passes across line A-A, is slower due to the increased width and area of the housing **210**. Any bacteria, germs, or virus within the airflow will have a greater dwell time and be neutralized by a germicidal device, such as an ultraviolet lamp.

In the embodiment shown in FIG. **17**, the device also includes a plurality of impeller fans **902**, which during operation produce very little noise. The fans **902** are designed to draw air into the device **200** through the inlet **250**. Air drawn into the device **200** through the inlet is directed horizontally towards the outlet **260**. In this particular embodiment, the fans are stacked vertically one on top of the other along the upstanding vertical length of the housing **210** adjacent to the inlet **250**.

In the embodiment shown in FIG. **17**, the fans **902** are "whisper" fan **902** which makes little or no humanly-audible noise while in operation. In the embodiment shown in FIG. **17**, the fans **902** are driven by micro-motors **1702**. In alternate embodiments, an alternate fan or fans can be used or in still further alternate embodiments any other device for moving air may be employed.

FIG. **18** illustrates an alternate embodiment of the device **200** shown in FIG. **2**A. As described above, the housing **210** can be made from a lightweight inexpensive material, ABS plastic for example. As a germicidal lamp **290** is located within the housing **210**, the material must be able to withstand prolonged exposure to class UV-C light. As described above, non-"hardened" material will degenerate over time if exposed to light such as UV-C. As described above, the housing **210** can be manufactured from CYCLOLAC7 ABS Resin (material designation VW300(f2)), which is manufactured by General Electric Plastics Global Products, and is certified by UL Inc. for use with ultraviolet light. In alternative embodiments, the housing **210** can be manufactured from other UV appropriate materials.

In the embodiment shown in FIG. **18**, the housing **210** is oval, elliptical or teardrop-shaped. The housing **210** includes at least one air intake **250**, and at least one air outlet **260**. Covering the inlet **250** and the outlet **260** are fins or louvers **212** and **214**, respectively. The fins **212**, **214** are preferably elongated and upstanding, and in one embodiment, oriented to minimize resistance to the airflow entering and exiting the device **200**. However, other fin and housing shapes are also possible.

From the above it is evident that in the embodiment shown in FIG. **18**, the cross-section of the housing **210** is oval, elliptical, or teardrop-shaped with the inlet **250** and outlet **260** narrower than the middle (see line A-A in FIG. **5**A) of the housing **210**. Accordingly, the airflow, as it passes across line A-A, is slower due to the increased width and area of the housing **210**. Any bacteria, germs, or virus within the airflow will have a greater dwell time and be neutralized by a germicidal device, such as an ultraviolet lamp.

In the embodiment shown in FIG. **18**, the device also includes impeller fans **902** which during operation produce very little noise. The fans **902** are designed to draw air into the device **200** through the inlet **250**. Air drawn into the device **200** through the inlet is directed horizontally towards the outlet **260**. The fans in this embodiment are configured in a manner similar to the fans in FIG. **17**.

In the embodiment shown in FIG. **18**, the fans **902** are "whisper" fans **902** which make little or no humanly-audible noise while in operation. In the embodiment shown in FIG. **18**, the fans **902** are driven by micro-motors **1702**. In alternate embodiments, an alternate fan can be used or in still further alternate embodiments any other device for moving air may be employed.

In the embodiment shown in FIG. **18**, the emitter-collector system is a pin-ring electrode assembly, as described above with reference to FIG. **8**. In the embodiment shown in FIG. **18**, each pin-ring electrode assembly is horizontally aligned with a fan **902**. In alternate embodiments, the pin-ring electrode assemblies may be located in any convenient location in the housing **210**. Pin-ring electrodes are also described in U.S. Pat. No. 6,176,977, issued Jan. 23, 2001, entitled "ELECTRO-KINETIC AIR TRANSPORTER-CONDITIONER," which is incorporated herein by reference.

FIG. **19** illustrates an alternate embodiment of the device **200** shown in FIG. **2**A. As described above, the housing **210** can be made from a lightweight inexpensive material, ABS plastic for example. As a germicidal lamp **290** is located within the housing **210**, the material must be able to withstand prolonged exposure to class UV-C light. As described above, non-"hardened" material will degenerate over time if exposed to light such as UV-C. As described above, the housing **210** can be manufactured from CYCLOLAC7 ABS Resin (material designation VW300(f2)), which is manufactured by General Electric Plastics Global Products, and is certified by UL Inc. for use with ultraviolet light. In alternative embodiments, the housing **210** can be manufactured from other UV appropriate materials.

In the embodiment shown in FIG. **19**, the housing **210** is oval, elliptical or teardrop-shaped. The housing **210** includes at least one air intake **250**, and at least one air outlet **260**. Covering the inlet **250** and the outlet **260** are fins or louvers **212** and **214**, respectively. The fins **212**, **214** are preferably elongated and upstanding, and in one embodiment, oriented to minimize resistance to the airflow entering and exiting the device **200**. However, other fin and housing shapes are also possible.

From the above it is evident that in the embodiment shown in FIG. **19**, the cross-section of the housing **210** is oval, elliptical, or teardrop-shaped with the inlet **250** and outlet **260** narrower than the middle (see line A-A in FIG. **5**A) of the housing **210**. Accordingly, the airflow, as it passes across line A-A, is slower due to the increased width and area of the housing **210**. Any bacteria, germs, or virus within the airflow will have a greater dwell time and be neutralized by a germicidal device, such as an ultraviolet lamp.

In the embodiment shown in FIG. **19**, the device includes impeller fans **902** which during operation produce very little noise, but no emitter-collector arrays. The fans **902** are designed to draw air into the device **200** through the inlet **250**. Air drawn into the device **200** through the inlet is directed horizontally towards the outlet **260**.

In the embodiment shown in FIG. **19**, the fans **902** are "whisper" fans **902** which make little or no humanly-audible noise while in operation. In the embodiment shown in FIG. **19**, the fans **902** are driven by micro-motors **1702**. The fans in this embodiment are configured in a manner similar to the fans in FIG. **17**. In alternate embodiments, an alternate fan can be used or in still further alternate embodiments any other device for moving air may be employed. This embodiment includes a UV source, but without emitter and collector electrodes. This embodiment has advantages similar to the embodiment of FIG. **16**.

FIG. **20** illustrates an alternate embodiment of the device **200** shown in FIG. **2**A. As described above, the housing **210** can be made from a lightweight inexpensive material, ABS plastic for example. As a germicidal lamp **290** is located within the housing **210**, the material must be able to withstand prolonged exposure to class UV-C light. As described above, non-"hardened" material will degenerate over time if exposed to light such as UV-C. As described above, the housing **210** can be manufactured from CYCLOLAC7 ABS Resin (material designation VW300(f2)), which is manufactured by General Electric Plastics Global Products, and is certified by UL Inc. for use with ultraviolet light. In alternative embodiments, the housing **210** can be manufactured from other UV appropriate materials.

In the embodiment shown in FIG. **20**, the housing **210** is oval, elliptical or teardrop-shaped. The housing **210** includes at least one air intake **250**, and at least one air outlet **260**. Covering the inlet **250** and the outlet **260** are fins or louvers

212 and 214, respectively. The fins 212, 214 are preferably elongated and upstanding, and in one embodiment, oriented to minimize resistance to the airflow entering and exiting the device 200. However, other fin and housing shapes are also possible.

In the embodiment shown in FIG. 20, the airflow is from the base of the housing 210 to the top of the housing 210. Any bacteria, germs, or virus within the airflow will have a dwell time within the housing 210 sufficient to neutralize the germs or virus by means of a germicidal device, such as an ultraviolet lamp.

In the embodiment shown in FIG. 20, the device also includes an impeller fan 902 which during operation produces very little noise. The fan 902 is designed to draw air into the device 200 through the inlet 250. Air drawn into the device 200 through the inlet is directed vertically towards the outlet 260, through the housing.

In the embodiment shown in FIG. 20, the fan 902 is a "whisper" fan 902 which makes little or no humanly-audible noise while in operation. In alternate embodiments, an alternate fan can be used or in still further alternate embodiments any other device for moving air may be employed.

The foregoing description of the embodiments of the present invention has been provided for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations will be apparent to the practitioner skilled in the art. Modifications and variations maybe made to the disclosed embodiments without departing from the subject and spirit of the invention as defined by the following claims. Embodiments were chosen and described in order to best describe the principles of the invention and its practical application, thereby enabling others skilled in the art to understand the invention, the various embodiments and with various modifications that are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the following claims and their equivalents.

What is claimed is:

1. An air treatment apparatus, comprising:

housing having a bottom, a top, first side wall and a second side wall, the housing having:

(a) an axis extending between the bottom and the top;

(b) an inlet located adjacent to the first side wall; and

(c) an outlet located adjacent to the second side wall;

an elongated emitter electrode supportable by the housing so as to extend substantially parallel to the axis;

an elongated collector electrode supportable by the housing so as to extend substantially parallel to the axis, the collector electrode being movable between a first position and a second position relative to the housing;

a voltage generator operably coupled to the emitter electrode and the collector electrode, the voltage generator being operable to produce an electric field, the electric field being operable to cause a germicidal effect; and

at least one air movement mechanism supported by the housing, the air movement mechanism configured to cause air to move from the inlet through the outlet along a path which is substantially perpendicular to the axis.

2. The air treatment apparatus of claim 1, further including at least one airflow director, the airflow director being operable to direct air along the path.

3. The treatment apparatus of claim 1, wherein the air movement mechanism includes a fan.

4. The air treatment apparatus of claim 1, further comprising a second inlet located adjacent to the bottom of the housing.

5. The air treatment apparatus of claim 1, further including a germicidal light source operable to cause a germicidal effect other than the germicidal effect caused by the electric field.

6. The air treatment apparatus of claim 1, further comprising a base secured to the bottom of the housing.

7. The air treatment apparatus of claim 1, wherein the emitter electrode and the collector electrode at least partially create an ion and particle flow in a first direction toward the outlet, wherein the air movement mechanism directs a portion of the flow along the path.

8. An air treatment apparatus, comprising:

a housing having:

(a) a bottom and a top;

(b) an axis extending between the bottom and the top;

(c) an inlet; and

(d) an outlet;

an ion generator having:

i. an elongated first electrode supportable by the housing so as to extend substantially parallel to the axis;

ii. an elongated second electrode supportable by the housing so as to extend substantially parallel to the axis, the second electrode being movable between a first position and a second position relative to the housing; and

iii. a voltage generator operatively coupled to the first and second electrodes, the voltage generator being operable to produce an electric field, the electric field being operable to cause a germicidal effect; and

at least one air movement mechanism supported by the housing, the air movement mechanism configured to cause air to move from the inlet through the outlet along a path which is substantially perpendicular to the axis.

9. The air treatment apparatus of claim 8, further comprising at least one airflow director configured to direct at least a portion of the air moved through the outlet along the path.

10. The air treatment apparatus of claim 8, wherein the air movement mechanism includes a fan.

11. The air treatment apparatus of claim 8 further comprising, a germicidal light source supported by the housing, the germicidal light source being operable to cause a germicidal effect in addition to the germicidal effect of the electric field.

12. The air treatment apparatus of claim 8 wherein the first electrode includes at least one electrode with a characteristic selected from the group consisting of: (i) a tapered pin-shaped electrode that terminates in a pointed tip, (ii) a tapered pin-shaped electrode that terminates in a plurality of individual fibers, (iii) a plurality of concentric circles, (iv) a cylindrical shape, and (v) a wire.

13. The air treatment apparatus of claim 8, wherein the second electrode includes at least one electrode with a characteristic selected from the group consisting of:

i. an elongated cylindrical tube;

ii. a plurality of concentric circles; and

iii. an elongated plate shape.

14. The air treatment apparatus of claim 8, wherein the second electrode is downstream of the first electrode.

15. The air treatment apparatus of claim 8, further comprising a moisture-retaining element to place into the airflow

at least one of the following characteristics selected from the group consisting of: (i) humidity, (ii) scent, and (iii) medicinal content.

16. An air treatment apparatus, comprising:

a housing including:

(a) a top and a bottom;

(b) an axis extending between the top and the bottom;

(c) an inlet; and

(d) an outlet;

an ion generator supportable by the housing, the ion generator further comprising:

i. a voltage generator, the voltage generator being operable to produce an electric field, the electric field being operable to cause a germicidal effect;

ii. an elongated first electrode electrically coupled to a first output port of the voltage generator, the first electrode being supportable by the housing so as to extend substantially parallel to the axis; and

iii. an elongated second electrode electrically coupled to a second output port of the generator, the second electrode supportable by the housing so as to extend substantially parallel to the axis, the second electrode being movable between a first position and a second position relative to the housing;

and

at least one air movement mechanism supported by the housing, the air movement mechanism configured to cause air to move from the inlet through the outlet along a path which is substantially perpendicular to the axis.

17. The air treatment apparatus of claim 16, further comprising: a moisture-retaining material configured to increase humidity of the air flow.

18. The air treatment apparatus of claim 16 further comprising a germicidal light source operable to produce a light, the light having a germicidal effect in addition to that caused by the electric field.

19. An air treatment apparatus, comprising:

a housing having a bottom, a top, a first side wall and a second side wall, the housing having:

(a) an axis extending between the bottom and the top;

(b) an inlet located adjacent to the first side wall; and

(c) an outlet located adjacent to the second side wall;

at least one emitter electrode supportable by the housing so as to extend substantially parallel to the axis;

at least one collector electrode supportable by the housing so as to extend substantially parallel to the axis, the collector electrode being movable between a first position and a second position relative to the housing;

a voltage generator operatively coupled to the emitter electrode and the collector electrode, the voltage generator being operable to produce an electric field, the electric field being operable to cause a germicidal effect;

a germicidal light source supported by the housing and operable to cause a germicidal effect in addition to the germicidal effect caused by the electric field; and

at least one air movement mechanism supported by the housing, the air movement mechanism configured to cause air to move from the inlet through the outlet along a path which is substantially perpendicular to the axis.

20. An air treatment apparatus, comprising:

a housing having a bottom and a top, the housing having:

(a) an axis extending between the bottom and the top;

(b) an inlet; and

(c) an outlet;

a wire first electrode supportable by the housing so as to extend substantially parallel to the axis;

a removable second electrode supportable by the housing so as to extend substantially parallel to the axis, the second electrode being movable between a first position and a second position relative to the housing;

a voltage generator operatively coupled to the first electrode and the second electrode, the voltage generator being operable to produce an electric field;

at least one air movement mechanism, the air movement mechanism being configured to cause air to move from the inlet through the outlet along a path substantially perpendicular to the axis; and

a germicidal area defined by the housing where a germicidal effect is producible, the effect being producible by an apparatus selected from the group consisting of: (i) a germicidal device; (ii) the electric field produced by the voltage generator; (iii) a germicidal light source supported by the housing; and (iv) a combination of the electric field and the germicidal light source.

21. The air treatment apparatus of claim 20, wherein the air movement mechanism includes a fan.

22. The air treatment apparatus of claim 20, including

at least one air flow director, the air flow director being operable to direct air along the path.

23. The air treatment apparatus of claim 20, further including a moisture-retaining material configured to increase humidity of the air flow.

24. An air treatment apparatus, comprising:

at least one electrical power line operable to carry electrical current;

a housing having:

(a) a bottom and a top;

(b) an axis extending between the bottom and the top;

(c) an inlet; and

(d) an outlet;

an emitter electrode supportable by the housing so as to extend substantially parallel to the axis;

a collector electrode supportable by the housing so as to extend substantially parallel to the axis, the collector electrode being movable between a first position and a second position relative to the housing;

a voltage generator operatively coupled to: (i) the at least one electrical power line; (ii) the emitter electrode; and (iii) the collector electrode, the voltage generator operable to produce an electric field, the electric field being operable to cause a germicidal effect; and

an air movement mechanism supported by the housing, the air movement mechanism being operable to cause air to move from the inlet through the outlet along a path substantially perpendicular to the axis.

25. The air treatment apparatus of claim 24, wherein the air movement mechanism includes a fan.

26. The air treatment apparatus of claim 24, further including a germicidal light source operable to cause a germicidal effect in addition to the germicidal effect caused by the electric field.

27. The air treatment apparatus of claim 24, further including a moisture-retaining element to place into the airflow at least one of the following characteristics selected from the group consisting of: (i) humidity, (ii) scent, and (iii) medicinal content.

* * * * *