

(10) **Patent No.:** US 6,972,057 B2  
(45) **Date of Patent:** \*Dec. 6, 2005

- |             |         |                   |
|-------------|---------|-------------------|
| 1,869,335 A | 7/1932  | Day               |
| 2,327,588 A | 8/1943  | Bennett           |
| 2,359,057 A | 9/1944  | Skinner           |
| 2,509,548 A | 5/1950  | White             |
| 2,949,550 A | 8/1960  | Brown             |
| 3,018,394 A | 1/1962  | Brown             |
| 3,026,964 A | 3/1962  | Penney            |
| 3,374,941 A | 3/1968  | Okress            |
| 3,518,462 A | 6/1970  | Brown             |
| 3,540,191 A | 11/1970 | Herman            |
| 3,581,470 A | 6/1971  | Aitkenhead et al. |
| 3,638,058 A | 1/1972  | Fritzius          |
| 3,744,216 A | 7/1973  | Halloran          |
| 3,981,695 A | 9/1976  | Fuchs             |
| 3,984,215 A | 10/1976 | Zucker            |

(Continued)

- FOREIGN PATENT DOCUMENTS

CN 2111112 U 7/1972

- (Continued)

## OTHER PUBLICATIONS

U.S. Appl. No. 10/278,193, filed Oct. 21, 2002, Reeves et al.

- (Continued)

*Primary Examiner*—Michael Barr  
*Assistant Examiner*—Saeed Chaudhry  
*(74) Attorney, Agent, or Firm*—Bell, Boyd & Lloyd LLC

- (57) **ABSTRACT**

- Methods for cleaning a first group of electrodes contained within an air conditioner are provided. A second group of electrodes within the air conditioner has a cleaning device fastened therewith. The cleaning device engages the first group of electrodes. A method includes removing the second group of electrodes from the air conditioner, and replacing the second group of electrodes back into the air conditioner.

**9 Claims, 14 Drawing Sheets**

# US 6,972,057 B2

Page 2

## U.S. PATENT DOCUMENTS

U.S. PATENT DOCUMENTS									
4,052,177	A	10/1977	Kide		5,266,004	A	11/1993	Tsumurai et al.	
4,092,134	A *	5/1978	Kikuchi .....	96/51	5,290,343	A	3/1994	Morita et al.	
4,102,654	A	7/1978	Pellin		5,296,019	A	3/1994	Oakley et al.	
4,138,233	A	2/1979	Masuda		5,302,190	A	4/1994	Williams	
4,209,306	A	6/1980	Feldman et al.		5,315,838	A	5/1994	Thompson	
4,227,894	A	10/1980	Proynoff		5,316,741	A	5/1994	Sewell et al.	
4,231,766	A	11/1980	Spurgin		5,378,978	A	1/1995	Gallo et al.	
4,232,355	A	11/1980	Finger et al.		5,435,817	A	7/1995	Davis et al.	
4,244,710	A	1/1981	Burger		5,437,713	A *	8/1995	Chang .....	96/51
4,244,712	A	1/1981	Tongret		5,484,472	A	1/1996	Weinberg	
4,253,852	A	3/1981	Adams		5,532,798	A	7/1996	Nakagami et al.	
4,259,452	A	3/1981	Yukuta et al.		5,535,089	A	7/1996	Ford et al.	
4,266,948	A	5/1981	Teague et al.		D375,546	S	11/1996	Lee	
4,282,014	A	8/1981	Winkler et al.		5,578,112	A	11/1996	Krause	
4,284,420	A *	8/1981	Borysiak .....	96/40	D377,523	S	1/1997	Marvin et al.	
4,318,718	A *	3/1982	Utsumi et al. ....	96/51	5,601,636	A	2/1997	Glucksmann	
4,342,571	A	8/1982	Hayashi		5,641,342	A	6/1997	Smith et al.	
4,357,150	A	11/1982	Masuda et al.		5,656,063	A	8/1997	Hsu	
4,386,395	A	5/1983	Francis, Jr.		5,667,564	A	9/1997	Weinberg	
4,413,225	A	11/1983	Donig et al.		5,669,963	A	9/1997	Horton et al.	
4,445,911	A	5/1984	Lind		5,698,164	A	12/1997	Kishioka et al.	
4,477,263	A	10/1984	Shaver et al.		5,702,507	A	12/1997	Wang	
4,496,375	A	1/1985	Le Vantine		D389,567	S	1/1998	Gudefin	
4,502,002	A	2/1985	Ando		5,766,318	A	6/1998	Loreth et al.	
4,509,958	A	4/1985	Masuda et al.		5,779,769	A	7/1998	Jiang	
4,516,991	A	5/1985	Kawashima		5,814,135	A	9/1998	Weinberg	
4,536,698	A	8/1985	Shevalenko et al.		5,879,435	A	3/1999	Satyapal et al.	
4,587,475	A	5/1986	Finney, Jr. et al.		5,893,977	A	4/1999	Pucci	
4,600,411	A	7/1986	Santamaria		5,911,957	A	6/1999	Khatchatrian et al.	
4,601,733	A	7/1986	Ordines et al.		5,972,076	A	10/1999	Nichols et al.	
4,626,261	A	12/1986	Jorgensen		5,975,090	A	11/1999	Taylor et al.	
4,643,745	A	2/1987	Sakakibara et al.		5,980,614	A	11/1999	Loreth et al.	
4,659,342	A	4/1987	Lind		5,993,521	A	11/1999	Loreth et al.	
4,674,003	A	6/1987	Zylka		5,997,619	A	12/1999	Knuth et al.	
4,686,370	A	8/1987	Blach		6,019,815	A	2/2000	Satyapal et al.	
4,689,056	A	8/1987	Noguchi et al.		6,042,637	A	3/2000	Weinberg	
4,694,376	A	9/1987	Gesslauer		6,063,168	A	5/2000	Nichols et al.	
4,713,093	A	12/1987	Hansson		6,086,657	A	7/2000	Freije	
4,713,724	A	12/1987	Voelkel		6,117,216	A	9/2000	Loreth	
4,726,812	A	2/1988	Hirth		6,118,645	A	9/2000	Partridge	
4,726,814	A	2/1988	Weitman		6,126,722	A	10/2000	Mitchell et al.	
4,772,297	A	9/1988	Anzai		6,126,727	A	10/2000	Lo	
4,779,182	A	10/1988	Mickal et al.		6,149,717	A	11/2000	Satyapal et al.	
4,781,736	A	11/1988	Cheney et al.		6,149,815	A	11/2000	Sauter	
4,786,844	A	11/1988	Farrell et al.		6,152,146	A	11/2000	Taylor et al.	
4,789,801	A	12/1988	Lee		6,163,098	A	12/2000	Taylor et al.	
4,808,200	A	2/1989	Dallhammer et al.		6,176,977	B1	1/2001	Taylor et al.	
4,811,159	A	3/1989	Foster, Jr.		6,182,461	B1	2/2001	Washburn et al.	
4,940,470	A	7/1990	Jaisinghani et al.		6,182,671	B1	2/2001	Taylor et al.	
4,941,068	A	7/1990	Hofmann		6,193,852	B1	2/2001	Caracciolo et al.	
4,955,991	A	9/1990	Torok et al.		6,203,600	B1	3/2001	Loreth	
4,967,119	A	10/1990	Torok et al.		6,212,883	B1	4/2001	Kang	
4,976,752	A	12/1990	Torok et al.		6,228,149	B1	5/2001	Alenichev et al.	
D315,598	S	3/1991	Yamamoto et al.		6,252,012	B1	6/2001	Egitto et al.	
5,006,761	A	4/1991	Torok et al.		6,270,733	B1	8/2001	Rodden	
5,010,869	A	4/1991	Lee		6,277,248	B1	8/2001	Ishioka et al.	
5,012,093	A	4/1991	Shimizu		6,282,106	B2	8/2001	Grass	
5,012,159	A	4/1991	Torok et al.		D449,097	S	10/2001	Smith et al.	
5,024,685	A	6/1991	Torok et al.		D449,679	S	10/2001	Smith et al.	
5,053,912	A	10/1991	Loreth et al.		6,302,944	B1	10/2001	Hoenig	
5,077,500	A	12/1991	Torok et al.		6,309,514	B1	10/2001	Conrad et al.	
RE33,927	E	5/1992	Fuzimura		6,312,507	B1	11/2001	Taylor et al.	
5,141,529	A	8/1992	Oakley et al.		6,315,821	B1	11/2001	Pillion et al.	
D329,284	S	9/1992	Patton		6,328,791	B1	12/2001	Pillion et al.	
D332,655	S	1/1993	Lytte et al.		6,348,103	B1	2/2002	Ahlborn et al.	
5,180,404	A	1/1993	Loreth et al.		6,350,417	B1	2/2002	Lau et al.	
5,183,480	A	2/1993	Raterman et al.		6,362,604	B1	3/2002	Cravey	
5,196,171	A	3/1993	Peltier		6,372,097	B1	4/2002	Chen	
5,215,558	A	6/1993	Moon		6,373,723	B1	4/2002	Wallgren et al.	
5,217,504	A	6/1993	Johansson		6,379,427	B1	4/2002	Siess	
5,248,324	A	9/1993	Hara		6,391,259	B1	5/2002	Malkin et al.	
					6,398,852	B1	6/2002	Loreth	
					6,447,587	B1	9/2002	Pillion et al.	

6,451,266	B1	9/2002	Lau et al.
6,464,754	B1	10/2002	Ford
6,471,753	B1	10/2002	Ahn et al.
6,494,940	B1	12/2002	Hak
6,504,308	B1	1/2003	Krichtafovitch et al.
6,508,982	B1	1/2003	Shoji
6,544,485	B1	4/2003	Taylor
6,585,935	B1	7/2003	Taylor et al.
6,588,434	B2	7/2003	Taylor et al.
6,603,268	B2	8/2003	Lee
6,613,277	B1	9/2003	Monagan
6,632,407	B1	10/2003	Lau et al.
6,672,315	B2	1/2004	Taylor et al.
6,709,484	B2	3/2004	Lau et al.
6,713,026	B2	3/2004	Taylor et al.
6,863,869	B2	3/2005	Lau et al.
2001/0004046	A1	6/2001	Taylor et al.
2001/0048906	A1	12/2001	Lau et al.
2002/0069760	A1	6/2002	Pruette et al.
2002/0079212	A1	6/2002	Taylor et al.
2002/0098131	A1	7/2002	Taylor et al.
2002/0100488	A1	8/2002	Taylor et al.
2002/0122751	A1	9/2002	Sinaiko et al.
2002/0122752	A1	9/2002	Taylor et al.
2002/0127156	A1	9/2002	Taylor
2002/0134664	A1	9/2002	Taylor et al.
2002/0134665	A1	9/2002	Taylor et al.
2002/0141914	A1	10/2002	Lau et al.
2002/0144601	A1	10/2002	Palestro et al.
2002/0146356	A1	10/2002	Sinaiko et al.
2002/0150520	A1	10/2002	Taylor et al.
2002/0152890	A1	10/2002	Leiser
2002/0155041	A1	10/2002	McKinney, Jr. et al.
2002/0170435	A1	11/2002	Joannou
2002/0190658	A1	12/2002	Lee
2002/0195951	A1	12/2002	Lee
2003/0005824	A1	1/2003	Katou et al.
2003/0196887	A1	10/2003	Lau et al.
2003/0206837	A1	11/2003	Taylor et al.
2003/0206839	A1	11/2003	Taylor et al.
2003/0206840	A1	11/2003	Taylor et al.
2004/0052700	A1	3/2004	Kotlyar et al.
2004/0065202	A1	4/2004	Gatchell et al.
2004/0136863	A1	7/2004	Yates et al.
2004/0166037	A1	8/2004	Youdell et al.
2004/0226447	A1	11/2004	Lau et al.
2004/0234431	A1	11/2004	Taylor et al.
2004/0237787	A1	12/2004	Reeves et al.
2004/0251124	A1	12/2004	Lau
2004/0251909	A1	12/2004	Taylor et al.
2005/0000793	A1	1/2005	Taylor et al.

## FOREIGN PATENT DOCUMENTS

CN	87210843	U	7/1988
CN	2138764	Y	6/1993
CN	2153231	Y	12/1993
CN	2174002	Y	8/1994
DE	2206057		8/1973
EP	0433152	A1	12/1990
EP	0332624	B1	1/1992
FR	2690509		10/1993
GB	643363		9/1950
JP	S51-90077		8/1976
JP	S62-20653		2/1987

JP	10137007		5/1998
JP	10216561		8/1998
JP	11104223		4/1999
JP	2000236914		9/2000
WO	WO92/05875	A1	4/1992
WO	WO96/04703	A1	2/1996
WO	WO99/07474	A1	2/1999
WO	WO00/10713	A1	3/2000
WO	WO01/47803	A1	7/2001
WO	WO01/48781	A1	7/2001
WO	WO01/64349	A1	9/2001
WO	WO01/85348	A2	11/2001
WO	WO02/20162	A2	3/2002
WO	WO02/20163	A2	3/2002
WO	WO02/30574	A1	4/2002
WO	WO02/32578	A1	4/2002
WO	WO02/42003	A1	5/2002
WO	WO02/066167	A1	8/2002
WO	WO03/009944	A1	2/2003
WO	WO03/013620	A1	2/2003
WO	WO03/013734	AA	2/2003

## OTHER PUBLICATIONS

U.S. Appl. No. 10/405,193, filed Apr. 1, 2003, Lee et al.  
 "Zenion Elf Device," drawing, prior art.  
 Electrical schematic and promotional material available from Zenion Industries, 7 pages, Aug. 1990.  
 Promotional material available from Zenion Industries for the Plasma-Pure 100/200/300, 2 pages, Aug. 1990.  
 Promotional material available from Zenion Industries for the Plasma-Tron, 2 pages, Aug. 1990.  
 LENTEK Sila™ Plug-In Air Purifier/Deodorizer product box copyrighted 1999, 13 pages.  
 U.S. Appl. No. 60/104,573, Krichtafovitch, filed Oct. 16, 1998.  
 Trion Console 250 Electronic Air Cleaner, Model Series 442857 and 445600, Manual for Installation•Operation•Maintenance, Trion Inc., 7 pp., believed to be at least one year prior to Nov. 5, 1998.  
 Trion 350 Air Purifier, Model 450111-010, <http://www.feddersoutlet.com/trion350.html>, 12 pp., believed to be at least one year prior to Nov. 5, 1998.  
 Trion 150 Air Purifier, Model 45000-002, <http://www.feddersoutlet.com/trion150.html>, 11 pp., believed to be at least one year prior to Nov. 5, 1998.  
 Trion 120 Air Purifier, Model 442501-025, <http://www.feddersoutlet.com/trion120.html>, 16 pp., believed to be at least one year prior to Nov. 5, 1998.  
 Friedrich C-90A Electronic Air Cleaner, Service Information, Friedrich Air Conditioning Co., 12 pp., 1985.  
 LakeAir Excel and Maxum Portable Electronic Air Cleaners, Operating and Service Manual, LakeAir International, Inc., 11 pp., 1971.  
 Blueair AV 402 Air Purifier, [http://www.air-purifiers-usa.biz/Blueair\\_AV402.htm](http://www.air-purifiers-usa.biz/Blueair_AV402.htm), 4 pp., 1996.  
 Blueair AV 501 Air Purifier, [http://www.air-purifiers-usa.biz/Blueair\\_AV501.htm](http://www.air-purifiers-usa.biz/Blueair_AV501.htm), 15 pp., 1997.

\* cited by examiner




FIG. 1A (PRIOR ART)




FIG. 1B (PRIOR ART)




FIG. 2A




FIG. 2B




FIG. 3





FIG. 4A



**FIG. 4B**






FIG. 4C







FIG. 4D




**FIG. 4E**




**FIG. 4F**



**FIG. 5A**



**FIG. 5B**



**FIG. 5C**




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D






FIG. 7A

FIG. 7B

FIG. 7C

FIG. 7D

FIG. 7E

1

ELECTRODE CLEANING FOR AIR  
CONDITIONER DEVICES

## PRIORITY CLAIM

This application is a divisional of U.S. patent application Ser. No. 09/924,600 filed Aug. 8, 2001, to issue as U.S. Pat. No. 6,709,484, which is a continuation of U.S. patent application Ser. No. 09/564,960 filed May 4, 2000, now U.S. Pat. No. 6,350,417, which is a continuation-in-part of U.S. patent application Ser. No. 09/186,471, filed Nov. 5, 1998, now U.S. Pat. No. 6,176,977.

## FIELD OF THE INVENTION

This invention relates generally to devices that produce ozone and an electro-kinetic flow of air from which particulate matter has been substantially removed, and more particularly to cleaning the wire or wire-like electrodes present in such devices.

## BACKGROUND

The use of an electric motor to rotate a fan blade to create an air flow has long been known in the art. Unfortunately, such fans produce substantial noise, and can present a hazard to children who may be tempted to poke a finger or a pencil into the moving fan blade. Although such fans can produce substantial air flow, e.g., 1,000 ft<sup>3</sup>/minute or more, substantial electrical power is required to operate the motor, and essentially no conditioning of the flowing air occurs.

It is known to provide such fans with a HEPA-compliant filter element to remove particulate matter larger than perhaps 0.3  $\mu$ m. Unfortunately, the resistance to air flow presented by the filter element may require doubling the electric motor size to maintain a desired level of airflow. Further, HEPA-compliant filter elements are expensive, and can represent a substantial portion of the sale price of a HEPA-compliant filter-fan unit. While such filter-fan units can condition the air by removing large particles, particulate matter small enough to pass through the filter element is not removed, including bacteria, for example.

It is also known in the art to produce an air flow using electro-kinetic techniques, by which electrical power is directly converted into a flow of air without mechanically moving components. One such system is described in U.S. Pat. No. 4,789,801 to Lee (1988), depicted herein in simplified form as FIGS. 1A and 1B. Lee's system 10 includes an array of small area ("minisectional") electrodes 20 that is spaced-apart symmetrically from an array of larger area ("maxisectional") electrodes 30. The positive terminal of a pulse generator 40 that outputs a train of high voltage pulses (e.g., 0 to perhaps +5 KV) is coupled to the minisectional array, and the negative pulse generator terminal is coupled to the maxisectional array.

The high voltage pulses ionize the air between the arrays, and an air flow 50 from the minisectional array toward the maxisectional array results, without requiring any moving parts. Particulate matter 60 in the air is entrained within the airflow 50 and also moves towards the maxisectional electrodes 30. Much of the particulate matter is electrostatically attracted to the surface of the maxisectional electrode array, where it remains, thus conditioning the flow of air exiting system 10. Further, the high voltage field present between the electrode arrays can release ozone into the ambient environment, which appears to destroy or at least alter whatever is entrained in the airflow, including for example, bacteria.

2

In the embodiment of FIG. 1A, minisectional electrodes 20 are circular in cross-section, having a diameter of about 0.003" (0.08 mm), whereas the maxisectional electrodes 30 are substantially larger in area and define a "teardrop" shape in cross-section. The ratio of cross-sectional radii of curvature between the maxisectional and minisectional electrodes is not explicitly stated, but from Lee's figures appears to exceed 10:1. As shown in FIG. 1A herein, the bulbous front surfaces of the maxisectional electrodes face the minisectional electrodes, and the somewhat sharp trailing edges face the exit direction of the air flow. The "sharpened" trailing edges on the maxisectional electrodes apparently promote good electrostatic attachment of particular matter entrained in the airflow. Lee does not disclose how the teardrop shaped maxisectional electrodes are fabricated, but presumably they are produced using a relatively expensive mold-casting or an extrusion process.

In another embodiment shown herein as FIG. 1B, Lee's maxisectional sectional electrodes 30 are symmetrical and elongated in cross-section. The elongated trailing edges on the maxisectional electrodes provide increased area upon which particulate matter entrained in the airflow can attach. Lee states that precipitation efficiency and desired reduction of anion release into the environment can result from including a passive third array of electrodes 70. Understandably, increasing efficiency by adding a third array of electrodes will contribute to the cost of manufacturing and maintaining the resultant system.

While the electrostatic techniques disclosed by Lee are advantageous over conventional electric fan-filter units, Lee's maxisectional electrodes are relatively expensive to fabricate. Further, increased filter efficiency beyond what Lee's embodiments can produce would be advantageous, especially without including a third array of electrodes.

The invention in applicants' parent application provided a first and second electrode array configuration electro-kinetic air transporter-conditioner having improved efficiency over Lee-type systems, without requiring expensive production techniques to fabricate the electrodes. The condition also permitted user-selection of safe amounts of ozone to be generated.

The second array electrodes were intended to collect particulate matter, and to be user-removable from the transporter-conditioner for regular cleaning to remove such matter from the electrode surfaces. The user must take care, however, to ensure that if the second array electrodes were cleaned with water, that the electrodes are thoroughly dried before reinsertion into the transporter-conditioner unit. If the unit were turned on while moisture from newly cleaned electrodes was allowed to pool within the unit, or if moisture wicking could result in high voltage arcing from the first to the second electrode arrays, with possible damage to the unit.

The wire or wire-like electrodes in the first electrode array are less robust than the second array electrodes. (The terms "wire" and "wire-like" shall be used interchangeably herein to mean an electrode either made from a wire or, if thicker or stiffer than a wire, having the appearance of a wire.) In embodiments in which the first array electrodes were user-removable from the transporter-conditioner unit, care was required during cleaning to prevent excessive force from simply snapping the wire electrodes. But eventually the first array electrodes can accumulate a deposited layer or coating of fine ash-like material. If this deposit is allowed to accumulate, eventually efficiency of the conditioner-transporter will be degraded. Further, for reasons not entirely

understood, such deposits can produce an audible oscillation that can be annoying to persons near the conditioner-transporter.

Thus, there is a need for a mechanism by a conditioner-transporter unit that can be protected against moisture pooling in the unit as a result of user cleaning. Further, there is a need for a mechanism by which the wire electrodes in the first electrode array of a conditioner-transporter can be periodically cleaned. Preferably such cleaning mechanism should be straightforward to implement, should not require removal of the first array electrodes from the conditioner-transporter, and should be operable by a user on a periodic basis.

The present invention provides a method and apparatus.

### SUMMARY

Applicants' parent application provides an electro-kinetic system for transporting and conditioning air without moving parts. The air is conditioned in the sense that it is ionized and contains safe amounts of ozone. The electro-kinetic air transporter-conditioner disclosed therein includes a louvered or gridded body that houses an ionizer unit. The ionizer unit includes a high voltage DC inverter that boosts common 110 VAC to high voltage, and a generator that receives the high voltage DC and outputs high voltage pulses of perhaps 10 KV peak-to-peak, although an essentially 100% duty cycle (e.g., high voltage DC) output could be used instead of pulses. The unit also includes an electrode assembly unit comprising first and second spaced-apart arrays of conducting electrodes, the first array and second array being coupled, respectively, preferably to the positive and negative output ports of the high voltage generator.

The electrode assembly preferably is formed using first and second arrays of readily manufacturable electrode configurations. In the embodiments relevant to this present invention, the first array included wire (or wire-like) electrodes. The second array comprised "U"-shaped or "L"-shaped electrodes having one or two trailing surfaces and intentionally large outer surface areas upon which to collect particulate matter in the air. In the preferred embodiments, the ratio between effective radii of curvature of the second array electrodes to the first array electrodes is at least about 20:1.

The high voltage pulses create an electric field between the first and second electrode arrays. This field produces an electro-kinetic airflow going from the first array toward the second array, the airflow being rich in preferably a net surplus of negative ions and in ozone. Ambient air including dust particles and other undesired components (germs, perhaps) enter the housing through the grill or louver openings, and ionized clean air (with ozone) exits through openings on the downstream side of the housing.

The dust and other particulate matter attaches electrostatically to the second array (or collector) electrodes, and the output air is substantially clean of such particulate matter. Further, ozone generated by the transporter-conditioner unit can kill certain types of germs and the like, and also eliminates odors in the output air. Preferably the transporter operates in periodic bursts, and a control permits the user to temporarily increase the high voltage pulse generator output, e.g., to more rapidly eliminate odors in the environment.

Applicants' parent application provided second array electrode units that were very robust and user-removable from the transporter-conditioner unit for cleaning. These second array electrode units could simply be slid up and out of the transporter-conditioner unit, and wiped clean with a

moist cloth, and returned to the unit. However, on occasion, if electrode units are returned to the transporter-conditioner unit while still wet (from cleaning), moisture pooling can reduce resistance between the first and second electrode arrays to where high voltage arcing results.

Another problem is that over time the wire electrodes in the first electrode array become dirty and can accumulate a deposited layer or coating of fine ash-like material. This accumulated material on the first array electrodes can eventually reduce ionization efficiency. Further, this accumulated coating can also result in the transporter-conditioner unit producing 500 Hz to 5 KHz audible oscillations that can annoy people in the same room as the unit.

In a first embodiment, the present invention extends one or more thin flexible sheets of MYLAR or KAPTON type material from the lower portion of the removable second array electrode unit. This sheet or sheets faces the first array electrodes and is nominally in a plane perpendicular to the longitudinal axis of the first and second array electrodes. Such sheet material has high voltage breakdown, high dielectric constant, can withstand high temperature, and is flexible. A slit is cut in the distal edge of this sheet for each first array electrode such that each wire first array electrode fits into a slit in this sheet. Whenever the user removes the second electrode array from the transporter-conditioner unit, the sheet of material is also removed. However, in the removal process, the sheet of material is also pulled upward, and friction between the inner slit edge surrounding each wire tends to scrape off any coating on the first array electrode. When the second array electrode unit is reinserted into the transporter-conditioner unit, the slits in the sheet automatically surround the associated first electrode array electrode. Thus, there is an up and down scraping action on the first electrode array electrodes whenever the second array electrode unit is removed from, or simply moved up and down within, the transporter-conditioner unit.

Optionally, upwardly projecting pillars can be disposed on the inner bottom surface of the transporter-conditioner unit to deflect the distal edge of the sheet material upward, away from the first array electrodes when the second array electrode unit is fully inserted. This feature reduces the likelihood of the sheet itself lowering the resistance between the two electrode arrays.

In a presently preferred embodiment, the lower ends of the second array electrodes are mounted to a retainer that includes pivotable arms to which a strip of MYLAR or KAPTON type material is attached. The distal edge of each strip includes a slit, and each strip (and the slit therein) is disposed to self-align with an associated wire electrode. A pedestal extends downward from the base of the retainer, and when fully inserted in the transporter-conditioner unit, the pedestal extends into a pedestal opening in a sub-floor of the unit. The first electrode array-facing walls of the pedestal opening urge the arms and the strip on each arm to pivot upwardly, from a horizontal to a vertical disposition. This configuration can improve resistance between the electrode arrays.

Yet another embodiment provides a cleaning mechanism for the wires in the first electrode array in which one or more bead-like members surrounds each wire, the wire electrode passing through a channel in the bead. When the transporter-conditioner unit is inverted, top-for-bottom and then bottom-for-top, the beads slide the length of the wire they surround, scraping off debris in the process. The beads embodiments may be combined with any or all of the various sheets embodiments to provide mechanisms allowing a user to

5

safely clean the wire electrodes in the first electrode array in a transporter-conditioner unit.

Other features and advantages of the invention will appear from the following description in which the preferred embodiments have been set forth in detail, in conjunction with the accompanying drawings.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a plan, cross-sectional view, of a first embodiment of a prior art electro-kinetic air transporter-conditioner system, according to the prior art;

FIG. 1B is a plan, cross-sectional view, of a second embodiment of a prior art electro-kinetic air transporter-conditioner system, according to the prior art;

FIG. 2A is a perspective view of a preferred embodiment of the present invention;

FIG. 2B is a perspective view of the embodiment of FIG. 2A, with the second array electrode assembly partially withdrawn depicting a mechanism for self-cleaning the first array electrode assembly, according to the present invention;

FIG. 3 is an electrical block diagram of the present invention;

FIG. 4A is a perspective block diagram showing a first embodiment for an electrode assembly, according to the present invention;

FIG. 4B is a plan block diagram of the embodiment of FIG. 4A;

FIG. 4C is a perspective block diagram showing a second embodiment for an electrode assembly, according to the present invention;

FIG. 4D is a plan block diagram of a modified version of the embodiment of FIG. 4C;

FIG. 4E is a perspective block diagram showing a third embodiment for an electrode assembly, according to the present invention;

FIG. 4F is a plan block diagram of the embodiment of FIG. 4E;

FIG. 5A is a perspective view of an electrode assembly depicting a first embodiment of a mechanism to clean first electrode array electrodes, according to the present invention.

FIG. 5B is a side view depicting an electrode cleaning mechanism as shown in FIG. 5A, according to the present invention;

FIG. 5C is a plan view of the electrode cleaning mechanism shown in FIG. 5B, according to the present invention;

FIG. 6A is a perspective view of a pivotable electrode cleaning mechanism, according to the present invention;

FIGS. 6B–6D depict the cleaning mechanism of FIG. 6A in various positions, according to the present invention;

FIGS. 7A–7E depict cross-sectional views of bead-like mechanisms to clean first electrode array electrodes, according to the present invention.

## DETAILED DESCRIPTION

FIGS. 2A and 2B depict an electro-kinetic air transporter-conditioner system **100** whose housing **102** includes preferably rear-located intake vents or louvers **104** and preferably front and side-located exhaust vents **106**, and a base pedestal **108**. Internal to the transporter housing is an ion generating unit **160**, preferably powered by an AC:DC power supply that is energizable or excitable using switch **S1**. Ion generating unit **160** is self-contained in that other than ambient air, nothing is required from beyond the

6

transporter housing, save external operating potential, for operation of the present invention.

The upper surface of housing **102** includes a user-liftable handle member **112** to which is affixed a second array **240** of electrodes **242** within an electrode assembly **220**. Electrode assembly **220** also comprises a first array of electrodes **230**, shown here as a single wire or wire-like electrode **232**. In the embodiment shown, lifting member **112** upward lifts second array electrodes **240** up and, if desired, out of unit **100**, while the first electrode array **230** remains within unit **100**. In FIG. 2B, the bottom ends of second array electrode **242** are connected to a member **113**, to which is attached a mechanism **500** for cleaning the first electrode array electrodes, here electrode **232**, whenever handle member **112** is moved upward or downward by a user. FIGS. 5A–7E, described later herein, provide further details as to various mechanisms **500** for cleaning wire or wire-like electrodes **232** in the first electrode array **230**, and for maintaining high resistance between the first and second electrode arrays **220**, **230** even if some moisture is allowed to pool within the bottom interior of unit **100**.

The first and second arrays of electrodes are coupled in series between the output terminals of ion generating unit **160**, as best seen in FIG. 3. The ability to lift handle **112** provides ready access to the electrodes comprising the electrode assembly, for purposes of cleaning and, if necessary, replacement.

The general shape of the invention shown in FIGS. 2A and 2B is not critical. The top-to-bottom height of the preferred embodiment is perhaps 1 m, with a left-to-right width of perhaps 15 cm, and a front-to-back depth of perhaps 10 cm, although other dimensions and shapes may of course be used. A louvered construction provides ample inlet and outlet venting in an economical housing configuration. There need be no real distinction between vents **104** and **106**, except their location relative to the second array electrodes, and indeed a common vent could be used. These vents serve to ensure that an adequate flow of ambient air may be drawn into or made available to the unit **100**, and that an adequate flow of ionized air that includes safe amounts of  $O_3$  flows out from unit **130**.

As will be described, when unit **100** is energized with **S1**, high voltage output by ion generator **160** produces ions at the first electrode array, which ions are attracted to the second electrode array. The movement of the ions in an “IN” to “OUT” direction carries with them air molecules, thus electro kinetically producing an outflow of ionized air. The “IN” notion in FIGS. 2A and 2B denote the intake of ambient air with particulate matter **60**. The “OUT” notation in the figures denotes the outflow of cleaned air substantially devoid of the particulate matter, which adheres electrostatically to the surface of the second array electrodes. In the process of generating the ionized air flow, safe amounts of ozone ( $O_3$ ) are beneficially produced. It may be desired to provide the inner surface of housing **102** with an electrostatic shield to reduce detectable electromagnetic radiation. For example, a metal shield could be disposed within the housing, or portions of the interior of the housing could be coated with a metallic paint to reduce such radiation.

As best seen in FIG. 3, ion generating unit **160** includes a high voltage generator unit **170** and circuitry **180** for converting raw alternating voltage (e.g., 117 VAC) into direct current (“DC”) voltage. Circuitry **180** preferably includes circuitry controlling the shape and/or duty cycle of the generator unit output voltage (which control is altered with user switch **S2**). Circuitry **180** preferably also includes a pulse mode component, coupled to switch **S3**, to tempo-

rarily provide a burst of increased output ozone. Circuitry **180** can also include a timer circuit and a visual indicator such as a light emitting diode ("LED"). The LED or other indicator (including, if desired, audible indicator) signals when ion generation is occurring. The timer can automatically halt generation of ions and/or ozone after some pre-determined time, e.g., 30 minutes. indicator(s), and/or audible indicator(s).

As shown in FIG. 3, high voltage generator unit **170** preferably comprises a low voltage oscillator circuit **190** of perhaps 20 KHz frequency, that outputs low voltage pulses to an electronic switch **200**, e.g., a thyristor or the like. Switch **200** switchably couples the low voltage pulses to the input winding of a step-up transformer **T1**. The secondary winding of **T1** is coupled to a high voltage multiplier circuit **210** that outputs high voltage pulses. Preferably the circuitry and components comprising high voltage pulse generator **170** and circuit **180** are fabricated on a printed circuit board that is mounted within housing **102**. If desired, external audio input (e.g., from a stereo tuner) could be suitably coupled to oscillator **190** to acoustically modulate the kinetic airflow produced by unit **160**. The result would be an electrostatic loudspeaker, whose output air flow is audible to the human ear in accordance with the audio input signal. Further, the output air stream would still include ions and ozone.

Output pulses from high voltage generator **170** preferably are at least 10 KV peak-to-peak with an effective DC offset of perhaps half the peak-to-peak voltage, and have a frequency of perhaps 20 KHz. The pulse train output preferably has a duty cycle of perhaps 10%, which will promote battery lifetime. Of course, different peak-peak amplitudes, DC offsets, pulse train waveshapes, duty cycle, and/or repetition frequencies may instead be used. Indeed, a 100% pulse train (e.g., an essentially DC high voltage) may be used, albeit with shorter battery lifetime. Thus, generator unit **170** may (but need not) be referred to as a high voltage pulse generator.

Frequency of oscillation is not especially critical but frequency of at least about 20 KHz is preferred as being inaudible to humans. If pets will be in the same room as the unit **100**, it may be desired to utilize an even higher operating frequency, to prevent pet discomfort and/or howling by the pet. As noted with respect to FIGS. 5A-6E, to reduce likelihood of audible oscillations, it is desired to include at least one mechanism to clean the first electrode array **230** elements **232**.

The output from high voltage pulse generator unit **170** is coupled to an electrode assembly **220** that comprises a first electrode array **230** and a second electrode array **240**. Unit **170** functions as a DC:DC high voltage generator, and could be implemented using other circuitry and/or techniques to output high voltage pulses that are input to electrode assembly **220**.

In the embodiment of FIG. 3, the positive output terminal of unit **170** is coupled to first electrode array **230**, and the negative output terminal is coupled to second electrode array **240**. This coupling polarity has been found to work well, including minimizing unwanted audible electrode vibration or hum. An electrostatic flow of air is created, going from the first electrode array towards the second electrode array. (This flow is denoted "OUT" in the figures.) Accordingly electrode assembly **220** is mounted within transporter system **100** such that second electrode array **240** is closer to the OUT vents and first electrode array **230** is closer to the IN vents.

When voltage or pulses from high voltage pulse generator **170** are coupled across first and second electrode arrays **230** and **240**, it is believed that a plasma-like field is created surrounding electrodes **232** in first array **230**. This electric field ionizes the ambient air between the first and second electrode arrays and establishes an "OUT" airflow that moves towards the second array. It is understood that the IN flow enters via vent(s) **104**, and that the OUT flow exits via vent(s) **106**.

It is believed that ozone and ions are generated simultaneously by the first array electrode(s) **232**, essentially as a function of the potential from generator **170** coupled to the first array. Ozone generation may be increased or decreased by increasing or decreasing the potential at the first array. Coupling an opposite polarity potential to the second array electrode(s) **242** essentially accelerates the motion of ions generated at the first array, producing the air flow denoted as "OUT" in the figures. As the ions move toward the second array, it is believed that they push or move air molecules toward the second array. The relative velocity of this motion may be increased by decreasing the potential at the second array relative to the potential at the first array.

For example, if +10 KV were applied to the first array electrode(s), and no potential were applied to the second array electrode(s), a cloud of ions (whose net charge is positive) would form adjacent the first electrode array. Further, the relatively high 10 KV potential would generate substantial ozone. By coupling a relatively negative potential to the second array electrode(s), the velocity of the air mass moved by the net emitted ions increases, as momentum of the moving ions is conserved.

On the other hand, if it were desired to maintain the same effective outflow (OUT) velocity but to generate less ozone, the exemplary 10 KV potential could be divided between the electrode arrays. For example, generator **170** could provide +4 KV (or some other fraction) to the first array electrode(s) and -6 KV (or some other fraction) to the second array electrode(s). In this example, it is understood that the +4 KV and the -6 KV are measured relative to ground. Understandably it is desired that the unit **100** operate to output safe amounts of ozone. Accordingly, the high voltage is preferably fractionalized with about +4 KV applied to the first array electrode(s) and about -6 KV applied to the second array electrodes.

As noted, outflow (OUT) preferably includes safe amounts of  $O_3$  that can destroy or at least substantially alter bacteria, germs, and other living (or quasi-living) matter subjected to the outflow. Thus, when switch **S1** is closed and **131** has sufficient operating potential, pulses from high voltage pulse generator unit **170** create an outflow (OUT) of ionized air and  $O_3$ . When **S1** is closed, LED will visually signal when ionization is occurring.

Preferably operating parameters of unit **100** are set during manufacture and are not user-adjustable. For example, increasing the peak-to-peak output voltage and/or duty cycle in the high voltage pulses generated by unit **170** can increase air flowrate, ion content, and ozone content. In the preferred embodiment, output flowrate is about 200 feet/minute, ion content is about 2,000,000/cc and ozone content is about 40 ppb (over ambient) to perhaps 2,000 ppb (over ambient). Decreasing the R2/R1 ratio below about 20:1 will decrease flow rate, as will decreasing the peak-to-peak voltage and/or duty cycle of the high voltage pulses coupled between the first and second electrode arrays.

In practice, unit **100** is placed in a room and connected to an appropriate source of operating potential, typically 117 VAC. With **S1** energized, ionization unit **160** emits ionized

air and preferably some ozone ( $O_3$ ) via outlet vents **150**. The air flow, coupled with the ions and ozone freshens the air in the room, and the ozone can beneficially destroy or at least diminish the undesired effects of certain odors, bacteria, germs, and the like. The air flow is indeed electro-kinetically produced, in that there are no intentionally moving parts within unit **100**. (As noted, some mechanical vibration may occur within the electrodes.) As will be described with respect to FIG. 4A, it is desirable that unit **100** actually output a net surplus of negative ions, as these ions are deemed more beneficial to health than are positive ions.

Having described various aspects of the invention in general, preferred embodiments of electrode assembly **220** will now be described. In the various embodiments, electrode assembly **220** will comprise a first array **230** of at least one electrode **232**, and will further comprise a second array **240** of preferably at least one electrode **242**. Understandably material(s) for electrodes **232** and **242** should conduct electricity, be resilient to corrosive effects from the application of high voltage, yet be strong enough to be cleaned.

In the various electrode assemblies to be described herein, electrode(s) **232** in the first electrode array **230** are preferably fabricated from tungsten. Tungsten is sufficiently robust to withstand cleaning, has a high melting point to retard breakdown due to ionization, and has a rough exterior surface that seems to promote efficient ionization. On the other hand, electrodes **242** preferably will have a highly polished exterior surface to minimize unwanted point-to-point radiation. As such, electrodes **242** preferably are fabricated from stainless steel, brass, among other materials. The polished surface of electrodes **232** also promotes ease of electrode cleaning.

In contrast to the prior art electrodes disclosed by Lee, electrodes **232** and **242**, electrodes used in unit **100** are light weight, easy to fabricate, and lend themselves to mass production. Further, electrodes **232** and **242** described herein promote more efficient generation of ionized air, and production of safe amounts of ozone,  $O_3$ .

In unit **100**, a high voltage pulse generator **170** is coupled between the first electrode array **230** and the second electrode array **240**. The high voltage pulses produce a flow of ionized air that travels in the direction from the first array towards the second array (indicated herein by hollow arrows denoted "OUT"). As such, electrode(s) **232** may be referred to as an emitting electrode, and electrodes **242** may be referred to as collector electrodes. This outflow advantageously contains safe amounts of  $O_3$ , and exits unit **100** from vent(s) **106**.

It is preferred that the positive output terminal or port of the high voltage pulse generator be coupled to electrodes **232**, and that the negative output terminal or port be coupled to electrodes **242**. It is believed that the net polarity of the emitted ions is positive, e.g., more positive ions than negative ions are emitted. In any event, the preferred electrode assembly electrical coupling minimizes audible hum from electrodes **232** contrasted with reverse polarity (e.g., interchanging the positive and negative output port connections).

However, while generation of positive ions is conducive to a relatively silent air flow, from a health standpoint, it is desired that the output air flow be richer in negative ions, not positive ions. It is noted that in some embodiments, however, one port (preferably the negative port) of the high voltage pulse generator may in fact be the ambient air. Thus, electrodes in the second array need not be connected to the high voltage pulse generator using wire. Nonetheless, there will be an "effective connection" between the second array

electrodes and one output port of the high voltage pulse generator, in this instance, via ambient air.

Turning now to the embodiments of FIGS. 4A and 4B, electrode assembly **220** comprises a first array **230** of wire electrodes **232**, and a second array **240** of generally "U"-shaped electrodes **242**. In preferred embodiments, the number **N1** of electrodes comprising the first array will preferably differ by one relative to the number **N2** of electrodes comprising the second array. In many of the embodiments shown,  $N2 > N1$ . However, if desired, in FIG. 4A, additional first electrodes **232** could be added at the out ends of array **230** such that  $N1 > N2$ , e.g., five electrodes **232** compared to four electrodes **242**.

Electrodes **232** are preferably lengths of tungsten wire, whereas electrodes **242** are formed from sheet metal, preferably stainless steel, although brass or other sheet metal could be used. The sheet metal is readily formed to define side regions **244** and bulbous nose region **246** for hollow elongated "U" shaped electrodes **242**. While FIG. 4A depicts four electrodes **242** in second array **240** and three electrodes **232** in first array **230**, as noted, other numbers of electrodes in each array could be used, preferably retaining a symmetrically staggered configuration as shown. It is seen in FIG. 4A that while particulate matter **60** is present in the incoming (IN) air, the outflow (OUT) air is substantially devoid of particulate matter, which adheres to the preferably large surface area provided by the second array electrodes (see FIG. 4B).

As best seen in FIG. 4B, the spaced-apart configuration between the arrays is staggered such that each first array electrode **232** is substantially equidistant from two second array electrodes **242**. This symmetrical staggering has been found to be an especially efficient electrode placement. Preferably the staggering geometry is symmetrical in that adjacent electrodes **232** or adjacent electrodes **242** are spaced-apart a constant distance, **Y1** and **Y2** respectively. However, a non-symmetrical configuration could also be used, although ion emission and air flow would likely be diminished. Also, it is understood that the number of electrodes **232** and **242** may differ from what is shown.

In FIG. 4A, typically dimensions are as follows: diameter of electrodes **232** is about 0.08 mm, distances **Y1** and **Y2** are each about 16 mm, distance **X1** is about 16 mm, distance **L** is about 20 mm, and electrode heights **Z1** and **Z2** are each about 1 m. The width **W** of electrodes **242** is preferably about 4 mm, and the thickness of the material from which electrodes **242** are formed is about 0.5 mm. Of course other dimensions and shapes could be used. It is preferred that electrodes **232** be small in diameter to help establish a desired high voltage field. On the other hand, it is desired that electrodes **232** (as well as electrodes **242**) be sufficiently robust to withstand occasional cleaning.

Electrodes **232** in first array **230** are coupled by a conductor **234** to a first (preferably positive) output port of high voltage pulse generator **170**, and electrodes **242** in second array **240** are coupled by a conductor **244** to a second (preferably negative) output port of generator **170**. It is relatively unimportant where on the various electrodes electrical connection is made to conductors **234** or **244**. Thus, by way of example FIG. 4B depicts conductor **244** making connection with some electrodes **242** internal to bulbous end **246**, while other electrodes **242** make electrical connection to conductor **244** elsewhere on the electrode. Electrical connection to the various electrodes **242** could also be made on the electrode external surface providing no substantial impairment of the outflow airstream results.

11

To facilitate removing the electrode assembly from unit **100** (as shown in FIG. 2B), it is preferred that the lower end of the various electrodes fit against mating portions of wire or other conductors **234** or **244**. For example, "cup-like" members can be affixed to wires **234** and **244** into which the free ends of the various electrodes fit when electrode array **220** is inserted completely into housing **102** of unit **100**.

The ratio of the effective electric field emanating area of electrode **232** to the nearest effective area of electrodes **242** is at least about 15:1, and preferably is at least 20:1. Thus, in the embodiment of FIG. 4A and FIG. 4B, the ratio  $R2/R1 \approx 2 \text{ mm}/0.04 \text{ mm} \approx 50:1$ .

In this and the other embodiments to be described herein, ionization appears to occur at the smaller electrode(s) **232** in the first electrode array **230**, with ozone production occurring as a function of high voltage arcing. For example, increasing the peak-to-peak voltage amplitude and/or duty cycle of the pulses from the high voltage pulse generator **170** can increase ozone content in the output flow of ionized air. If desired, user-control **S2** can be used to somewhat vary ozone content by varying (in a safe manner) amplitude and/or duty cycle. Specific circuitry for achieving such control is known in the art and need not be described in detail herein.

Note the inclusion in FIGS. 4A and 4B of at least one output controlling electrode **243**, preferably electrically coupled to the same potential as the second array electrodes. Electrode **243** preferably defines a pointed shape in side profile, e.g., a triangle. The sharp point on electrode(s) **243** causes generation of substantial negative ions (since the electrode is coupled to relatively negative high potential). These negative ions neutralize excess positive ions otherwise present in the output air flow, such that the OUT flow has a net negative charge. Electrode(s) **243** preferably are stainless steel, copper, or other conductor, and are perhaps 20 mm high and about 12 mm wide at the base.

Another advantage of including pointed electrodes **243** is that they maybe stationarily mounted within the housing of unit **100**, and thus are not readily reached by human hands when cleaning the unit. Were it otherwise, the sharp point on electrode(s) **243** could easily cause cuts. The inclusion of one electrode **243** has been found sufficient to provide a sufficient number of output negative ions, but more such electrodes may be included.

In the embodiment of FIGS. 4A and 4C, each "U"-shaped electrode **242** has two trailing edges that promote efficient kinetic transport of the outflow of ionized air and  $O_3$ . Note the inclusion on at least one portion of a trailing edge of a pointed electrode region **243'**. Electrode region **243'** helps promote output of negative ions, in the same fashion as was described with respect to FIGS. 4A and 4B. Note, however, the higher likelihood of a user cutting himself or herself when wiping electrodes **242** with a cloth or the like to remove particulate matter deposited thereon. In FIG. 4C and the figures to follow, the particulate matter is omitted for ease of illustration. However, from what was shown in FIGS. 2A-4B, particulate matter will be present in the incoming air, and will be substantially absent from the outgoing air. As has been described, particulate matter **60** typically will be electrostatically precipitated upon the surface area of electrodes **242**. As indicated by FIG. 4C, it is relatively unimportant where on an electrode array electrical connection is made. Thus, first array electrodes **232** are shown connected together at their bottom regions, whereas second array electrodes **242** are shown connected together in their middle regions. Both arrays may be connected together in more than one region, e.g., at the top and at the bottom.

12

It is preferred that the wire or strips or other inter-connecting mechanisms be at the top or bottom or periphery of the second array electrodes **242**, so as to minimize obstructing stream air movement.

Note that the embodiments of FIGS. 4C and 4D depict somewhat truncated versions of electrodes **242**. Whereas dimension **L** in the embodiment of FIGS. 4A and 4B was about 20 mm, in FIGS. 4C and 4D, **L** has been shortened to about 8 mm. Other dimensions in FIG. 4C preferably are similar to those stated for FIGS. 4A and 4B. In FIGS. 4C and 4D, the inclusion of point-like regions **246** on the trailing edge of electrodes **242** seems to promote more efficient generation of ionized air flow. It will be appreciated that the configuration of second electrode array **240** in FIG. 4C can be more robust than the configuration of FIGS. 4A and 4B, by virtue of the shorter trailing edge geometry. As noted earlier, a symmetrical staggered geometry for the first and second electrode arrays is preferred for the configuration of FIG. 4C.

In the embodiment of FIG. 4D, the outermost second electrodes, denoted **242-1** and **242-2**, have substantially no outermost trailing edges. Dimension **L** in FIG. 4D is preferably about 3 mm, and other dimensions maybe as stated for the configuration of FIGS. 4A and 4B. Again, the  $R2/R1$  ratio for the embodiment of FIG. 4D preferably exceeds about 20:1.

FIGS. 4E and 4F depict another embodiment of electrode assembly **220**, in which the first electrode array comprises a single wire electrode **232**, and the second electrode array comprises a single pair of curved "L"-shaped electrodes **242**, in cross-section. Typical dimensions, where different than what has been stated for earlier-described embodiments, are  $X1 \approx 12 \text{ mm}$ ,  $Y1 \approx 6 \text{ mm}$ ,  $Y2 \approx 5 \text{ mm}$ , and  $L1 \approx 3 \text{ mm}$ . The effective  $R2/R1$  ratio is again greater than about 20:1. The fewer electrodes comprising assembly **220** in FIGS. 4E and 4F promote economy of construction, and ease of cleaning, although more than one electrode **232**, and more than two electrodes **242** could of course be employed. This embodiment again incorporates the staggered symmetry described earlier, in which electrode **232** is equidistant from two electrodes **242**.

Turning now to FIG. 5A, a first embodiment of an electrode cleaning mechanism **500** is depicted. In the embodiment shown, mechanism **500** comprises a flexible sheet of insulating material such as MYLAR or other high voltage, high temperature breakdown resistant material, having sheet thickness of perhaps 0.1 mm or so. Sheet **500** is attached at one end to the base or other mechanism **113** secured to the lower end of second electrode array **240**. Sheet **500** extends or projects out from base **113** towards and beyond the location of first electrode array **230** electrodes **232**. The overall projection length of sheet **500** in FIG. 5A will be sufficiently long to span the distance between base **113** of the second array **240** and the location of electrodes **232** in the first array **230**. This span distance will depend upon the electrode array configuration but typically will be a few inches or so. Preferably the distal edge of sheet **500** will extend slightly beyond the location of electrodes **232**, perhaps 0.5" beyond. As shown in FIGS. 5A and 5C, the distal edge, e.g., edge closest to electrodes **232**, of material **500** is formed with a slot **510** corresponding to the location of an electrode **232**. Preferably the inward end of the slot forms a small circle **520**, which can promote flexibility.

The configuration of material **500** and slots **510** is such that each wire or wire-like electrode **232** in the first electrode array **230** fits snugly and friction ally within a corresponding slot **510**. As indicated by FIG. 5A and shown in FIG. 5C,

## 13

instead of a single sheet **500** that includes a plurality of slots **510**, instead one can provide individual strips **515** of material **500**, the distal end of each strip having a slot **510** that will surround an associated wire electrode **232**. Note in FIGS. **5B** and **5C** that sheet **500** or sheets **515** may be formed with holes **119** that can attach to pegs **117** that project from the base portion **113** of the second electrode array **240**. Of course other attachment mechanisms could be used including glue, double-sided tape, inserting the array **240**-facing edge of the sheet into a horizontal slot or ledge in base member **113**, and so forth.

FIG. **5A** shows second electrode array **240** in the process of being moved upward, perhaps by a user intending to remove array **240** to remove particulate matter from the surfaces of its electrodes **242**. Note that as array **240** moves up (or down), sheet **510** (or sheets **515**) also move up (or down). This vertical movement of array **240** produces a vertical movement in sheet **510** or **515**, which causes the outer surface of electrodes **232** to scrape against the inner surfaces of an associated slot **510**. FIG. **5A**, for example, shows debris and other deposits **612** (indicated by x's) on wires **232** above sheet **500**. As array **240** and sheet **500** move upward, debris **612** is scraped off the wire electrodes, and falls downward (to be vaporized or collected as particulate matter when unit **100** is again reassembled and turned-on). Thus, the outer surface of electrodes **232** below sheet **500** in FIG. **5A** is shown as being cleaner than the surface of the same electrodes above sheet **500**, where scraping action has yet to occur.

A user hearing that excess noise or humming emanates from unit **100** might simply turn the unit off, and slide array **240** (and thus sheet **500** or sheets **515**) up and down (as indicated by the up/down arrows in FIG. **5A**) to scrape the wire electrodes in the first electrode array. This technique does not damage the wire electrodes, and allows the user to clean as required.

As noted earlier, a user may remove second electrode array **240** for cleaning (thus also removing sheet **500**, which will have scraped electrodes **232** on its upward vertical path). If the user cleans electrodes **242** with water and returns array **240** to unit **100** without first completely drying **240**, moisture might form on the upper surface of a horizontally disposed member **550** within unit **100**. Thus, as shown in FIG. **5B**, it is preferred that an upwardly projecting vane **560** be disposed near the base of each electrode **232** such that when array **240** is fully inserted into unit **100**, the distal portion of sheet **500** or preferably sheet strips **515** deflect upward. While sheet **500** or sheets **515** nominally will define an angle  $\theta$  of about  $90^\circ$ , as base **113** becomes fully inserted into unit **100**, the angle  $\theta$  will increase, approaching  $0^\circ$ , e.g., the sheet is extending almost vertically upward. If desired, a portion of sheet **500** or sheet strips **515** can be made stiffer by laminating two or more layers of MYLAR or other material. For example the distal tip of strip **515** in FIG. **5B** might be one layer thick, whereas the half or so of the strip length nearest electrode **242** might be stiffened with an extra layer or two of MYLAR or similar material.

The inclusion of a projecting vane **560** in the configuration of FIG. **5B** advantageously disrupted physical contact between sheet **500** or sheet strips **515** and electrodes **232**, thus tending to preserve a high ohmic impedance between the first and second electrode arrays **230**, **240**. The embodiment of FIGS. **6A**–**6D** advantageously serves to pivot sheet **500** or sheet strips **515** upward, essentially parallel to electrodes **232**, to help maintain a high impedance between the first and second electrode arrays. Note the creation of an

## 14

air gap **513** resulting from the upward deflection of the slit distal tip of strip **515** in FIG. **5B**.

In FIG. **6A**, the lower edges of second array electrodes **242** are retained by a base member **113** from which project arms **677**, which can pivot about pivot axle **687**. Preferably axle **687** biases arms **677** into a horizontal disposition, e.g., such that  $\theta \approx 90^\circ$ . Arms **645** project from the longitudinal axis of base member **113** to help member **113** align itself within an opening **655** formed in member **550**, described below. Preferably base member **113** and arms **677** are formed from a material that exhibits high voltage breakdown and can withstand high temperature. Ceramic is a preferred material (if cost and weight were not considered), but certain plastics could also be used. The unattached tip of each arm **677** terminates in a sheet strip **515** of MYLAR, KAPTON, or a similar material, whose distal tip terminates in a slot **510**. It is seen that the pivotable arms **677** and sheet strips **515** are disposed such that each slot **510** will self-align with a wire or wire-like electrode **232** in first array **230**. Electrodes **232** preferably extend from pylons **627** on a base member **550** that extends from legs **565** from the internal bottom of the housing of the transporter-conditioner unit. To further help maintain high impedance between the first and second electrode arrays, base member **550** preferably includes a barrier wall **665** and upwardly extending vanes **675**. Vanes **675**, pylons **627**, and barrier wall **665** extend upward perhaps an inch or so, depending upon the configuration of the two electrode be formed integrally, e.g., by casting, from a material that exhibits high voltage breakdown and can withstand high temperature, ceramic, or certain plastics for example.

As best seen in FIG. **6A**, base member **550** includes an opening **655** sized to receive the lower portion of second electrode array base member **113**. In FIGS. **6A** and **6B**, arms **677** and sheet material **515** are shown pivoting from base member **113** about axis **687** at an angle  $\theta \approx 90^\circ$ . In this disposition, an electrode **232** will be within the slot **510** formed at the distal tip of each sheet material member **515**.

Assume that a user had removed second electrode array **240** completely from the transporter-conditioner unit for cleaning, and that FIGS. **6A** and **6B** depict array **240** being reinserted into the unit. The coiled spring or other bias mechanism associated with pivot axle **687** will urge arms **677** into an approximate  $\theta \approx 90^\circ$  orientation as the user inserts array **240** into unit **100**. Side projections **645** help base member **113** align properly such that each wire or wire-like electrode **232** is caught within the slot **510** of a member **515** on an arm **677**. As the user slides array **240** down into unit **100**, there will be a scraping action between the portions of sheet member **515** on either side of a slot **510**, and the outer surface of an electrode **232** that is essentially captured within the slot. This friction will help remove debris or deposits that may have formed on the surface of electrodes **232**. The user may slide array **240** up and down the further promote the removal of debris or deposits from elements **232**.

In FIG. **6C** the user has slid array **240** down almost entirely into unit **100**. In the embodiment shown, when the lowest portion of base member **232** is perhaps an inch or so above the planar surface of member **550**, the upward edge of a vane **675** will strike the a lower surface region of a projection arm **677**. The result will be to pivot arm **677** and the attached slit-member **515** about axle **687** such that the angle  $\theta$  decreases. In the disposition shown in FIG. **6C**,  $\theta \approx 45^\circ$  and slitcontact with an associated electrode **232** is no longer made.



15

In FIG. 6D, the user has firmly urged array 240 fully downward into transporterconditioner unit 100. In this disposition, as the projecting bottommost portion of member 113 begins to enter opening 655 in member 550 (see FIG. 6A), contact between the inner wall 657 portion of member 550 urges each arm 677 to pivot fully upward, e.g.,  $\theta \approx 0^\circ$ . Thus in the fully inserted disposition shown in FIG. 6D, each slit electrode cleaning member 515 is rotated upward parallel to its associated electrode 232. As such, neither arm 677 nor member 515 will decrease impedance between first and second electrode arrays 230, 240. Further, the presence of vanes 675 and barrier wall 665 further promote high impedance.

Thus, the embodiments shown in FIGS. 5A–6D depict alternative configurations for a cleaning mechanism for a wire or wire-like electrode in a transporterconditioner unit.

Turning now to FIGS. 7A–7E, various bead-like mechanisms are shown for cleaning deposits from the outer surface of wire electrodes 232 in a first electrode array 230 in a transporter-converter unit. In FIG. 7A a symmetrical bead 600 is shown surrounding wire element 232, which is passed through bead channel 610 at the time the first electrode array is fabricated. Bead 600 is fabricated from a material that can withstand high temperature and high voltage, and is not likely to char, ceramic or glass, for example. While a metal bead would also work, an electrically conductive bead material would tend slightly to decrease the resistance path separating the first and second electrode arrays, e.g., by approximately the radius of the metal bead. In FIG. 7A, debris and deposits 612 on electrode 232 are depicted as “x’s”. In FIG. 7A, bead 600 is moving in the direction shown by the arrow relative to wire 232. Such movement can result from the user inverting unit 100, e.g., turning the unit upside down. As bead 600 slides in the direction of the arrow, debris and deposits 612 scrape against the interior walls of channel 610 and are removed. The removed debris can eventually collect at the bottom interior of the transporter-conditioner unit. Such debris will be broken down and vaporized as the unit is used, or will accumulate as particulate matter on the surface of electrodes 242. If wire 232 has a nominal diameter of say 0.1 mm, the diameter of bead channel 610 will be several times larger, perhaps 0.8 mm or so, although greater or lesser size tolerances may be used. Bead 600 need not be circular and may instead be cylindrical as shown by bead 600' in FIG. 7A. A circular bead may have a diameter in the range of perhaps 0.3" to perhaps 0.5". A cylindrical bead might have a diameter of say 0.3" and be about 0.5" tall, although different sizes could of course be used.

As indicated by FIG. 7A, an electrode 232 may be strung through more than one bead 600, 600'. Further, as shown by FIGS. 7B–7D, beads having different channel symmetries and orientations may be used as well. It is to be noted that while it may be most convenient to form channels 610 with circular cross-sections, the cross-sections could in fact be non-circular, e.g., triangular, square, irregular shape, etc.

FIG. 7B shows a bead 600 similar to that of FIG. 7A, but wherein channel 610 is formed off-center to give asymmetry to the bead. An off-center channel will have a mechanical moment and will tend to slightly tension wire electrode 232 as the bead slides up or down, and can improve cleaning characteristics. For ease of illustration, FIGS. 7B–7E do not depict debris or deposits on or removed from wire or wire-like electrode 232. In the embodiment of FIG. 7C, bead channel 610 is substantially in the center of bead 600 but is inclined slightly, again to impart a different frictional cleaning action. In the embodiment of FIG. 7D, beam 600 has a channel 610 that is both off center and inclined, again to

16

impart a different frictional cleaning action. In general, asymmetrical bead channel or through-opening orientations are preferred.

FIG. 7E depicts an embodiment in which a bell-shaped walled bead 620 is shaped and sized to fit over a pillar 550 connected to a horizontal portion 560 of an interior bottom portion of unit 100. Pillar 550 retains the lower end of wire or wire-like electrode 232, which passes through a channel 630 in bead 620, and if desired, also through a channel 610 in another bead 600. Bead 600 is shown in phantom in FIG. 7E to indicate that it is optional.

Friction between debris 612 on electrode 232 and the mouth of channel 630 will tend to remove the debris from the electrode as bead 620 slides up and down the length of the electrode, e.g., when a user inverts transporter-conditioner unit 100, to clean electrodes 232. It is understood that each electrode 232 will include its own bead or beads, and some of the beads may have symmetrically disposed channels, while other beads may have asymmetrically disposed channels. An advantage of the configuration shown in FIG. 7E is that when unit 100 is in use, e.g., when bead 620 surrounds pillar 550, with an air gap therebetween, improved breakdown resistance is provided, especially when bead 620 is fabricated from glass or ceramic or other high voltage, high temperature breakdown material that will not readily char. The presence of an air gap between the outer surface of pillar 550 and the inner surface of the bellshaped bead 620 helps increase this resistance to high voltage breakdown or arcing, and to charring.

Modifications and variations may be made to the disclosed embodiments without departing from the subject and spirit of the invention as defined by the following claims.

What is claimed:

1. A method for cleaning a first group of electrodes contained within an air conditioner housing, wherein a removable second group of electrodes within the air conditioner housing has a cleaning device fastened with the second group of electrodes, which also engage the first group of electrodes, the method comprising, in any order:

- (a) removing the second group of electrodes from the air conditioner housing; and
- (b) replacing the second group of electrodes back into the air conditioner housing.

2. A method as recited in claim 1, wherein removing the second group of electrodes from the air conditioner housing in step (a) causes the cleaning device to travel along the first group of electrodes and frictionally remove contaminants from the outer surface of the first group of electrodes.

3. A method for cleaning a first group of electrodes contained within an air conditioner, wherein a second group of electrodes within the air conditioner has a cleaning device fastened with the second group of electrodes, which also engage the first group of electrodes, the method comprising, in any order:

- (a) removing the second group of electrodes from the air conditioner; and
- (b) replacing the second group of electrodes back into the air conditioner;

wherein removing the second group of electrodes from the air conditioner in step (a) causes the cleaning device to travel along the first group of electrodes and frictionally remove contaminants from the outer surface of the first group of electrodes; and

wherein replacing the second group of electrodes back into air conditioner in step (b) deflects the cleaning device away from the first group of electrodes such that the cleaning device does not contact the first group of

17

electrodes when the second group of electrodes are completely placed back into the air conditioner.

4. A method for cleaning a first electrode contained within an air conditioner housing wherein a removable second electrode within the air conditioner housing has a cleaning device fastened with the second electrode, which also engage the first electrode, the method comprising, in any order:

- (a) removing the second electrode from the air conditioner housing; and
- (b) replacing the second electrode back into the air conditioner housing.

5. A method as recited in claim 4, wherein removing the second electrode from the air conditioner housing in step (a) causes the cleaning device to travel along the first electrode and frictionally remove contaminants from the outer surface of the first electrode.

6. A method for cleaning a first electrode contained within an air conditioner, wherein a second electrode within the air conditioner has a cleaning device fastened with the second electrode, which also engage the first electrode, the method comprising, in any order:

- (a) removing the second electrode from the air conditioner; and
- (b) replacing the second electrode back into the air conditioner;

wherein removing the second electrode from the air conditioner in step (a) causes the cleaning device to travel along the first electrode and frictionally remove contaminants from the outer surface of the first electrode; and

wherein replacing the second electrode back into the air conditioner in step (b) deflects the cleaning device away from the first electrode such that the cleaning device does not contact the first electrode when the second electrode is completely placed back into the air conditioner.

18

7. A method for cleaning a first electrode contained within an air conditioner housing wherein a removable second electrode within the air conditioner housing has a cleaning device associated with the second electrode, which also engage the first electrode, the method comprising, in any order, the steps of:

- (a) removing the second electrode from the air conditioner housing; and
- (b) replacing the second electrode back into the air conditioner housing.

8. A method as recited in claim 7, wherein removing the second electrode from the air conditioner housing in step (a) causes the cleaning device to travel along the first electrode and frictionally remove contaminants from the outer surface of the first electrode.

9. A method for cleaning a first electrode contained within an air conditioner, wherein a second electrode within the air conditioner has a cleaning device associated with the second electrode, which also engage the first electrode, the method comprising, in any order, the steps of:

- (a) removing the second electrode from the air conditioner; and (b) replacing the second electrode back into the air conditioner; and

wherein removing the second electrode from the air conditioner in step (a) causes the cleaning device to travel along the first electrode and frictionally remove contaminants from the outer surface of the first electrode; and

wherein replacing the second electrode back into the air conditioner in step (b) deflects the cleaning device away from the first electrode such that the cleaning device does not contact the first electrode when the second electrode is completely placed back into the air conditioner.

\* \* \* \* \*