



US007662348B2

(12) **United States Patent**  
**Taylor et al.**

(10) **Patent No.:** **US 7,662,348 B2**  
(45) **Date of Patent:** **Feb. 16, 2010**

(54) **AIR CONDITIONER DEVICES**

(75) Inventors: **Charles E. Taylor**, Sebastopol, CA  
(US); **Shek Fai Lau**, Foster City, CA  
(US)

(73) Assignee: **Sharper Image Acquisition LLC**, New  
York, NY (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 769 days.

(21) Appl. No.: **11/150,046**

(22) Filed: **Jun. 10, 2005**

(65) **Prior Publication Data**

US 2005/0232831 A1 Oct. 20, 2005

**Related U.S. Application Data**

(63) Continuation of application No. 10/815,230, filed on  
Mar. 30, 2004, now Pat. No. 6,953,556, which is a  
continuation of application No. 09/730,499, filed on  
Dec. 5, 2000, now Pat. No. 6,713,026, which is a  
continuation of application No. 09/186,471, filed on  
Nov. 5, 1998, now Pat. No. 6,176,977.

(51) **Int. Cl.**  
**B01J 19/08** (2006.01)

(52) **U.S. Cl.** ..... **422/186.04**; 422/121; 96/96

(58) **Field of Classification Search** ..... 422/186.04,  
422/121; 96/96

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

653,421 A 7/1900 Lorey  
895,729 A 8/1908 Carlborg  
995,958 A 6/1911 Goldberg  
1,791,338 A 2/1931 Wintermute  
1,869,335 A 7/1932 Day  
1,882,949 A 10/1932 Ruder

2,129,783 A 9/1938 Penney  
2,327,588 A 8/1943 Bennett  
2,359,057 A 9/1944 Skinner  
2,509,548 A 5/1950 White  
2,590,447 A 3/1952 Nord et al.  
2,949,550 A 8/1960 Brown  
3,018,394 A 1/1962 Brown  
3,026,964 A 3/1962 Penney  
3,374,941 A 3/1968 Okress  
3,518,462 A 6/1970 Brown  
3,540,191 A 11/1970 Herman

(Continued)

**FOREIGN PATENT DOCUMENTS**

CN 2111112 U 7/1972

(Continued)

**OTHER PUBLICATIONS**

U.S. Appl. No. 60/104,573, filed Oct. 16, 1998, Krichtafovitch.


(Continued)

*Primary Examiner*—Kishor Mayekar  
(74) *Attorney, Agent, or Firm*—Arent Fox LLP

(57) **ABSTRACT**

An air conditioner includes an ion generator that provides ions and safe amounts of ozone. The ion generator includes a high voltage generator that provides a voltage potential difference between first and second electrode arrays. At least one of the first and second arrays is removable from the housing for cleaning.

**24 Claims, 12 Drawing Sheets**



U.S. PATENT DOCUMENTS						
3,581,470	A	6/1971	Aitkenhead et al.	4,413,225	A	11/1983 Donig et al.
3,638,058	A	1/1972	Fritzius	4,414,603	A	11/1983 Masuda
3,744,216	A	7/1973	Halloran	4,435,190	A	3/1984 Taillet et al.
3,806,763	A	4/1974	Masuda	4,440,552	A	4/1984 Uchiya et al.
3,892,927	A	7/1975	Lindenberg	4,443,234	A	4/1984 Carlsson
3,945,813	A	3/1976	Iinoya et al.	4,445,911	A	5/1984 Lind
3,958,960	A	5/1976	Bakke	4,477,263	A	10/1984 Shaver et al.
3,958,961	A	5/1976	Bakke	4,477,268	A	10/1984 Kalt
3,958,962	A	5/1976	Hayashi	4,481,017	A	11/1984 Furlong
3,981,695	A	9/1976	Fuchs	4,496,375	A	1/1985 Levantine
3,984,215	A	10/1976	Zucker	4,502,002	A	2/1985 Ando
3,988,131	A	10/1976	Kanazawa et al.	4,505,724	A	3/1985 Baab
4,007,024	A	2/1977	Sallee et al.	4,509,958	A	4/1985 Masuda et al.
4,052,177	A	10/1977	Kide	4,514,780	A	4/1985 Brussee et al.
4,056,372	A	11/1977	Hayashi	4,515,982	A	5/1985 Lechtken et al.
4,070,163	A	1/1978	Kolb et al.	4,516,991	A	5/1985 Kawashima
4,074,983	A	2/1978	Bakke	4,521,229	A	6/1985 Baker et al.
4,092,134	A	5/1978	Kikuchi	4,522,634	A	6/1985 Frank
4,097,252	A	6/1978	Kirchhoff et al.	4,534,776	A	8/1985 Mammel et al.
4,102,654	A	7/1978	Pellin	4,536,698	A	8/1985 Shevalenko et al.
4,104,042	A	8/1978	Brozenick	4,544,382	A	10/1985 Taillet et al.
4,110,086	A	8/1978	Schwab et al.	4,555,252	A	11/1985 Eckstein
4,119,415	A	10/1978	Hayashi et al.	4,569,684	A	2/1986 Ibbott
4,126,434	A	11/1978	Keiichi	4,582,961	A	4/1986 Frederiksen
4,138,233	A	2/1979	Masuda	4,587,475	A	5/1986 Finney, Jr. et al.
4,147,522	A	4/1979	Gonas et al.	4,588,423	A	5/1986 Gillingham et al.
4,155,792	A	5/1979	Gelhaar et al.	4,590,042	A	5/1986 Drage
4,171,975	A	10/1979	Kato et al.	4,597,780	A	7/1986 Reif
4,185,971	A	1/1980	Isahaya	4,597,781	A	7/1986 Spector
4,189,308	A	2/1980	Feldman	4,600,411	A	7/1986 Santamaria
4,205,969	A	6/1980	Matsumoto	4,601,733	A	7/1986 Ordines et al.
4,209,306	A	6/1980	Feldman et al.	4,604,174	A	8/1986 Bollinger et al.
4,218,225	A	8/1980	Kirchhoff et al.	4,614,573	A	9/1986 Masuda
4,225,323	A	9/1980	Zarchy et al.	4,623,365	A	11/1986 Bergman
4,227,894	A	10/1980	Proynoff	4,626,261	A	12/1986 Jorgensen
4,231,766	A	11/1980	Spurgin	4,632,135	A	12/1986 Lenting et al.
4,232,355	A	11/1980	Finger et al.	4,632,746	A	12/1986 Bergman
4,244,710	A	1/1981	Burger	4,636,981	A	1/1987 Ogura
4,244,712	A	1/1981	Tongret	4,643,744	A	2/1987 Brooks
4,251,234	A	2/1981	Chang	4,643,745	A	2/1987 Sakakibara et al.
4,253,852	A	3/1981	Adams	4,647,836	A	3/1987 Olsen
4,259,093	A	3/1981	Vlastos et al.	4,650,648	A	3/1987 Beer et al.
4,259,452	A	3/1981	Yukuta et al.	4,656,010	A	4/1987 Leitzke et al.
4,259,707	A	3/1981	Penney	4,657,738	A	4/1987 Kanter et al.
4,264,343	A	4/1981	Natarajan et al.	4,659,342	A	4/1987 Lind
4,266,948	A	5/1981	Teague et al.	4,662,903	A	5/1987 Yanagawa
4,282,014	A	8/1981	Winkler et al.	4,666,474	A	5/1987 Cook
4,284,420	A	8/1981	Borysiak	4,668,479	A	5/1987 Manabe et al.
4,289,504	A	9/1981	Scholes	4,670,026	A	6/1987 Hoenig
4,293,319	A	10/1981	Claassen, Jr.	4,673,416	A *	6/1987 Sakakibara et al. .... 96/79
4,308,036	A	12/1981	Zahedi et al.	4,674,003	A	6/1987 Zylka
4,315,188	A	2/1982	Cerny et al.	4,680,496	A	7/1987 Letournel et al.
4,318,718	A	3/1982	Utsumi et al.	4,686,370	A	8/1987 Blach
4,338,560	A	7/1982	Lemley	4,689,056	A	8/1987 Noguchi et al.
4,342,571	A	8/1982	Hayashi	4,691,829	A	9/1987 Auer
4,349,359	A	9/1982	Fitch et al.	4,692,174	A	9/1987 Gelfand et al.
4,351,648	A	9/1982	Penney	4,693,869	A	9/1987 Pfaff
4,354,861	A	10/1982	Kalt	4,694,376	A	9/1987 Gesslauer
4,357,150	A	11/1982	Masuda et al.	4,702,752	A	10/1987 Yanagawa
4,362,632	A	12/1982	Jacob	4,713,092	A	12/1987 Kikuchi et al.
4,363,072	A	12/1982	Coggins	4,713,093	A	12/1987 Hansson
4,366,525	A	12/1982	Baumgartner	4,713,724	A	12/1987 Voelkel
4,369,776	A	1/1983	Roberts	4,715,870	A	12/1987 Masuda et al.
4,375,364	A	3/1983	Van Hoesen et al.	4,725,289	A	2/1988 Quintilian
4,380,900	A	4/1983	Linder et al.	4,726,812	A	2/1988 Hirth
4,386,395	A	5/1983	Francis, Jr.	4,726,814	A	2/1988 Weitman
4,391,614	A	7/1983	Rozmus	4,736,127	A	4/1988 Jacobsen
4,394,239	A	7/1983	Kitzelmann et al.	4,743,275	A	5/1988 Flanagan
4,405,342	A	9/1983	Bergman	4,749,390	A	6/1988 Burnett et al.
4,406,671	A	9/1983	Rozmus	4,750,921	A	6/1988 Sugita et al.
4,412,850	A	11/1983	Kurata et al.	4,760,302	A	7/1988 Jacobsen
				4,760,303	A	7/1988 Miyake
				4,765,802	A	8/1988 Gombos et al.

# US 7,662,348 B2

Page 3

4,771,361 A	9/1988	Varga	5,271,763 A	12/1993	Jang
4,772,297 A	9/1988	Anzai	5,282,891 A	2/1994	Durham
4,779,182 A	10/1988	Mickal et al.	5,290,343 A *	3/1994	Morita et al. .... 96/39
4,781,736 A	11/1988	Cheney et al.	5,296,019 A	3/1994	Oakley et al.
4,786,844 A	11/1988	Farrell et al.	5,302,190 A	4/1994	Williams
4,789,801 A	12/1988	Lee	5,308,586 A	5/1994	Fritzsche et al.
4,808,200 A	2/1989	Dallhammer et al.	5,315,838 A	5/1994	Thompson
4,811,159 A	3/1989	Foster, Jr.	5,316,741 A	5/1994	Sewell et al.
4,822,381 A	4/1989	Mosley et al.	5,330,559 A	7/1994	Cheney et al.
4,853,005 A	8/1989	Jaisinghani et al.	5,348,571 A	9/1994	Weber
4,869,736 A	9/1989	Ivester et al.	5,376,168 A	12/1994	Inculet
4,892,713 A	1/1990	Newman	5,378,978 A	1/1995	Gallo et al.
4,929,139 A	5/1990	Vorreiter et al.	5,386,839 A	2/1995	Chen
4,940,470 A	7/1990	Jaisinghani et al.	5,395,430 A	3/1995	Lundgren et al.
4,940,894 A	7/1990	Morters	5,401,301 A	3/1995	Schulmerich et al.
4,941,068 A	7/1990	Hofmann	5,401,302 A	3/1995	Schulmerich et al.
4,941,224 A	7/1990	Saeki et al.	5,403,383 A	4/1995	Jaisinghani
4,944,778 A	7/1990	Yanagawa	5,405,434 A	4/1995	Inculet
4,954,320 A	9/1990	Birmingham et al.	5,407,469 A	4/1995	Sun
4,955,991 A	9/1990	Torok et al.	5,407,639 A	4/1995	Watanabe et al.
4,966,666 A	10/1990	Waltonen	5,417,936 A	5/1995	Suzuki et al.
4,967,119 A	10/1990	Torok et al.	5,419,953 A	5/1995	Chapman
4,976,752 A	12/1990	Torok et al.	5,433,772 A	7/1995	Sikora
4,978,372 A	12/1990	Pick	5,435,817 A	7/1995	Davis et al.
D315,598 S	3/1991	Yamamoto et al.	5,435,978 A	7/1995	Yokomi
5,003,774 A	4/1991	Leonard	5,437,713 A	8/1995	Chang
5,006,761 A	4/1991	Torok et al.	5,437,843 A	8/1995	Kuan
5,010,869 A	4/1991	Lee	5,445,798 A	8/1995	Ikeda et al.
5,012,093 A	4/1991	Shimizu	5,466,279 A	11/1995	Hattori et al.
5,012,094 A	4/1991	Hamade	5,468,454 A	11/1995	Kim
5,012,159 A	4/1991	Torok et al.	5,474,599 A	12/1995	Cheney et al.
5,022,979 A	6/1991	Hijikata et al.	5,484,472 A	1/1996	Weinberg
5,024,685 A	6/1991	Torok et al.	5,484,473 A	1/1996	Bontempi
5,030,254 A	7/1991	Heyen et al.	5,492,678 A	2/1996	Ota et al.
5,034,033 A	7/1991	Alsup et al.	5,501,844 A	3/1996	Kasting, Jr. et al.
5,037,456 A	8/1991	Yu	5,503,808 A	4/1996	Garbutt et al.
5,045,095 A	9/1991	You	5,503,809 A	4/1996	Coate et al.
5,053,912 A	10/1991	Loreth et al.	5,505,914 A	4/1996	Tona-Serra
5,059,219 A	10/1991	Plaks et al.	5,508,008 A	4/1996	Wasser
5,061,462 A	10/1991	Suzuki	5,514,345 A	5/1996	Garbutt et al.
5,066,313 A	11/1991	Mallory, Sr.	5,516,493 A	5/1996	Bell et al.
5,072,746 A	12/1991	Kantor	5,518,531 A	5/1996	Joannu
5,076,820 A	12/1991	Gurvitz	5,520,887 A	5/1996	Shimizu et al.
5,077,468 A	12/1991	Hamade	5,525,310 A	6/1996	Decker et al.
5,077,500 A	12/1991	Torok et al.	5,529,613 A	6/1996	Yavnieli
5,100,440 A	3/1992	Stahel et al.	5,529,760 A	6/1996	Burris
RE33,927 E	5/1992	Fuzimura	5,532,798 A	7/1996	Nakagami et al.
D326,514 S	5/1992	Alsup et al.	5,535,089 A	7/1996	Ford et al.
5,118,942 A	6/1992	Hamade	5,536,477 A	7/1996	Cha et al.
5,125,936 A	6/1992	Johansson	5,538,695 A	7/1996	Shinjo et al.
5,136,461 A	8/1992	Zellweger	5,540,761 A	7/1996	Yamamoto
5,137,546 A	8/1992	Steinbacher et al.	5,542,967 A	8/1996	Ponizovsky et al.
5,141,529 A	8/1992	Oakley et al.	5,545,379 A	8/1996	Gray
5,141,715 A	8/1992	Sackinger et al.	5,545,380 A	8/1996	Gray
D329,284 S	9/1992	Patton	5,547,643 A	8/1996	Nomoto et al.
5,147,429 A	9/1992	Bartholomew et al.	5,549,874 A	8/1996	Kimiya et al.
5,154,733 A	10/1992	Fujii et al.	5,554,344 A	9/1996	Duarte
5,158,580 A	10/1992	Chang	5,554,345 A	9/1996	Kitchenman
D332,655 S	1/1993	Lytfe et al.	5,569,368 A	10/1996	Larsky et al.
5,180,404 A	1/1993	Loreth et al.	5,569,437 A	10/1996	Stiehl et al.
5,183,480 A	2/1993	Rateman et al.	D375,546 S	11/1996	Lee
5,196,171 A	3/1993	Peltier	5,571,483 A	11/1996	Pfingstl et al.
5,198,003 A	3/1993	Haynes	5,573,577 A	11/1996	Joannou
5,199,257 A	4/1993	Colletta et al.	5,573,730 A	11/1996	Gillum
5,210,678 A	5/1993	Lain et al.	5,578,112 A	11/1996	Krause
5,215,558 A	6/1993	Moon	5,578,280 A	11/1996	Kazi et al.
5,217,504 A	6/1993	Johansson	5,582,632 A	12/1996	Nohr et al.
5,217,511 A	6/1993	Plaks et al.	5,587,131 A	12/1996	Malkin et al.
5,234,555 A	8/1993	Ibbott	D377,523 S	1/1997	Marvin et al.
5,248,324 A	9/1993	Hara	5,591,253 A	1/1997	Altman et al.
5,250,267 A	10/1993	Johnson et al.	5,591,334 A	1/1997	Shimizu et al.
5,254,155 A	10/1993	Mensi	5,591,412 A	1/1997	Jones et al.
5,266,004 A	11/1993	Tsumurai et al.	5,593,476 A	1/1997	Coppom

# US 7,662,348 B2

Page 4

5,601,636 A	2/1997	Glucksman	6,362,604 B1	3/2002	Cravey
5,603,752 A	2/1997	Hara	6,372,097 B1	4/2002	Chen
5,603,893 A	2/1997	Gundersen et al.	6,373,723 B1	4/2002	Wallgren et al.
5,614,002 A	3/1997	Chen	6,379,427 B1	4/2002	Siess
5,624,476 A	4/1997	Eyraud	6,391,259 B1	5/2002	Malkin et al.
5,630,866 A	5/1997	Gregg	6,398,852 B1	6/2002	Loreth
5,630,990 A	5/1997	Conrad et al.	6,447,587 B1	9/2002	Pillion et al.
5,637,198 A	6/1997	Breault	6,451,266 B1	9/2002	Lau et al.
5,637,279 A	6/1997	Besen et al.	6,464,754 B1	10/2002	Ford
5,641,342 A	6/1997	Smith et al.	6,471,753 B1	10/2002	Ahn et al.
5,641,461 A	6/1997	Ferone	6,494,940 B1	12/2002	Hak
5,647,890 A	7/1997	Yamamoto	6,504,308 B1	1/2003	Krichtafovitch et al.
5,648,049 A	7/1997	Jones et al.	6,508,982 B1	1/2003	Shoji
5,655,210 A	8/1997	Gregoire et al.	6,544,485 B1	4/2003	Taylor
5,656,063 A	8/1997	Hsu	6,585,935 B1	7/2003	Taylor et al.
5,665,147 A	9/1997	Taylor et al.	6,588,434 B2	7/2003	Taylor et al.
5,667,563 A	9/1997	Silva, Jr.	6,603,268 B2	8/2003	Lee
5,667,564 A	9/1997	Weinberg	6,613,277 B1	9/2003	Monagan
5,667,565 A	9/1997	Gondar	6,632,407 B1	10/2003	Lau et al.
5,667,756 A	9/1997	Ho	6,635,105 B2	10/2003	Ahlborn et al.
5,669,963 A	9/1997	Horton et al.	6,672,315 B2	1/2004	Taylor et al.
5,678,237 A	10/1997	Powell et al.	6,709,484 B2	3/2004	Lau et al.
5,681,434 A	10/1997	Eastlund	6,713,026 B2 *	3/2004	Taylor et al. .... 422/186.04
5,681,533 A	10/1997	Hiromi	6,735,830 B1	5/2004	Merciel
5,698,164 A	12/1997	Kishioka et al.	6,749,667 B2	6/2004	Reeves et al.
5,702,507 A	12/1997	Wang	6,753,652 B2	6/2004	Kim
D389,567 S	1/1998	Gudefin	6,761,796 B2	7/2004	Srivastava et al.
5,766,318 A	6/1998	Loreth et al.	6,768,108 B2	7/2004	Hirano et al.
5,779,769 A	7/1998	Jiang	6,768,110 B2	7/2004	Alani
5,814,135 A	9/1998	Weinberg	6,768,120 B2	7/2004	Leung et al.
5,879,435 A	3/1999	Satyapal et al.	6,768,121 B2	7/2004	Horsky et al.
5,893,977 A	4/1999	Pucci	6,770,878 B2	8/2004	Uhlemann et al.
5,911,957 A	6/1999	Khatchatrian et al.	6,774,359 B1	8/2004	Hirabayashi et al.
5,925,172 A *	7/1999	Rick et al. .... 96/397	6,777,686 B2	8/2004	Olson et al.
5,972,076 A	10/1999	Nichols et al.	6,777,699 B1	8/2004	Miley et al.
5,975,090 A	11/1999	Taylor et al.	6,777,882 B2	8/2004	Goldberg et al.
5,980,614 A	11/1999	Loreth et al.	6,781,136 B1	8/2004	Kato
5,993,521 A	11/1999	Loreth et al.	6,785,912 B1	9/2004	Julio
5,997,619 A	12/1999	Knuth et al.	6,791,814 B2	9/2004	Adachi et al.
6,019,815 A	2/2000	Satyapal et al.	6,794,661 B2	9/2004	Tsukihara et al.
6,036,757 A *	3/2000	Gatchell et al. .... 96/424	6,797,339 B2	9/2004	Akizuki et al.
6,042,637 A	3/2000	Weinberg	6,797,964 B2	9/2004	Yamashita
6,063,168 A	5/2000	Nichols et al.	6,799,068 B1	9/2004	Hartmann et al.
6,086,657 A	7/2000	Freije	6,800,862 B2	10/2004	Matsumoto et al.
6,117,216 A	9/2000	Loreth	6,803,585 B2	10/2004	Glukhoy
6,118,645 A	9/2000	Partridge	6,805,916 B2	10/2004	Cadieu
6,126,722 A	10/2000	Mitchell et al.	6,806,035 B1	10/2004	Atireklapvarodom et al.
6,126,727 A	10/2000	Lo	6,806,163 B2	10/2004	Wu et al.
6,149,717 A	11/2000	Satyapal et al.	6,806,468 B2	10/2004	Laiko et al.
6,149,815 A	11/2000	Sauter	6,808,606 B2	10/2004	Thomsen et al.
6,152,146 A	11/2000	Taylor et al.	6,809,310 B2	10/2004	Chen
6,163,098 A	12/2000	Taylor et al.	6,809,312 B1	10/2004	Park et al.
6,176,977 B1	1/2001	Taylor et al.	6,809,325 B2	10/2004	Dahl et al.
6,182,461 B1	2/2001	Washburn et al.	6,812,647 B2	11/2004	Cornelius
6,182,671 B1	2/2001	Taylor et al.	6,815,690 B2	11/2004	Veerasamy et al.
6,193,852 B1	2/2001	Caracciolo et al.	6,818,257 B2	11/2004	Amann et al.
6,203,600 B1	3/2001	Loreth	6,818,909 B2	11/2004	Murrell et al.
6,212,883 B1	4/2001	Kang	6,819,053 B2	11/2004	Johnson
6,228,149 B1	5/2001	Alenichev et al.	6,863,869 B2	3/2005	Taylor et al.
6,252,012 B1	6/2001	Egitto et al.	6,896,853 B2	5/2005	Law et al.
6,270,733 B1	8/2001	Rodden	6,911,186 B2	6/2005	Taylor et al.
6,277,248 B1	8/2001	Ishioka et al.	2001/0048906 A1	12/2001	Lau et al.
6,282,106 B2	8/2001	Grass	2002/0069760 A1	6/2002	Pruette et al.
D449,097 S	10/2001	Smith et al.	2002/0079212 A1	6/2002	Taylor et al.
D449,679 S	10/2001	Smith et al.	2002/0098131 A1	7/2002	Taylor et al.
6,296,692 B1	10/2001	Gutmann	2002/0122751 A1	9/2002	Sinaiko et al.
6,302,944 B1	10/2001	Hoenig	2002/0122752 A1	9/2002	Taylor et al.
6,309,514 B1	10/2001	Conrad et al.	2002/0127156 A1	9/2002	Taylor
6,312,507 B1	11/2001	Taylor et al.	2002/0134664 A1	9/2002	Taylor et al.
6,315,821 B1	11/2001	Pillion et al.	2002/0134665 A1	9/2002	Taylor et al.
6,328,791 B1	12/2001	Pillion et al.	2002/0141914 A1	10/2002	Lau et al.
6,348,103 B1	2/2002	Ahlborn et al.	2002/0144601 A1	10/2002	Palestro et al.
6,350,417 B1	2/2002	Lau et al.	2002/0146356 A1	10/2002	Sinaiko et al.

2002/0150520 A1 10/2002 Taylor et al.  
 2002/0152890 A1 10/2002 Leiser  
 2002/0155041 A1 10/2002 McKinney, Jr. et al.  
 2002/0170435 A1 11/2002 Joannou  
 2002/0190658 A1 12/2002 Lee  
 2002/0195951 A1 12/2002 Lee  
 2003/0005824 A1 1/2003 Katou et al.  
 2003/0170150 A1 9/2003 Lau et al.  
 2003/0206837 A1 11/2003 Taylor et al.  
 2003/0206839 A1 11/2003 Taylor et al.  
 2003/0206840 A1 11/2003 Taylor et al.  
 2004/0033176 A1 2/2004 Lee et al.  
 2004/0052700 A1 3/2004 Kotlyar et al.  
 2004/0065202 A1 4/2004 Gatchell et al.  
 2004/0096376 A1 5/2004 Taylor et al.  
 2004/0136863 A1 7/2004 Yates et al.  
 2004/0166037 A1 8/2004 Youdell et al.  
 2004/0226447 A1 11/2004 Lau et al.  
 2004/0234431 A1 11/2004 Taylor et al.  
 2004/0237787 A1 12/2004 Reeves et al.  
 2004/0251124 A1 12/2004 Lau  
 2004/0251909 A1 12/2004 Taylor et al.  
 2005/0000793 A1 1/2005 Taylor et al.

## FOREIGN PATENT DOCUMENTS


CN 87210843 U 7/1988  
 CN 2138764 Y 6/1993  
 CN 2153231 Y 12/1993  
 DE 2206057 8/1973  
 DE 197 41 621 C 1 6/1999  
 EP 0433152 A1 12/1990  
 EP 0332624 B1 1/1992  
 FR 2690509 10/1993  
 GB 643363 9/1950  
 JP S51-90077 8/1976  
 JP S62-20653 2/1987  
 JP S63-164948 10/1988  
 JP 10137007 5/1998  
 JP 11104223 4/1999  
 JP 2000236914 9/2000  
 WO WO 92/05875 A1 4/1992  
 WO WO 96/04703 A1 2/1996  
 WO WO 99/07474 A1 2/1999  
 WO WO 00/10713 A1 3/2000  
 WO WO 01/47803 A1 7/2001  
 WO WO 01/48781 A1 7/2001  
 WO WO 01/64349 A1 9/2001  
 WO WO 01/85348 A2 11/2001  
 WO WO 02/20162 A2 3/2002  
 WO WO 02/20163 A2 3/2002  
 WO WO 02/30574 A1 4/2002  
 WO WO 02/32578 A1 4/2002  
 WO WO 02/42003 A1 5/2002  
 WO WO 02/066167 A1 8/2002  
 WO WO 03/009944 A1 2/2003  
 WO WO 03/013620 A1 2/2003  
 WO WO 03/013734 AA 2/2003

## OTHER PUBLICATIONS


U.S. Appl. No. 60/306,479, filed Jul. 18, 2001, Taylor.  
 U.S. Appl. No. 60/341,179, filed Dec. 13, 2001, Taylor et al.

U.S. Appl. No. 60/340,702, filed Dec. 13, 2001, Taylor et al.  
 U.S. Appl. No. 60/341,377, filed Dec. 13, 2001, Taylor et al.  
 U.S. Appl. No. 60/341,518, filed Dec. 13, 2001, Taylor.  
 U.S. Appl. No. 60/340,288, filed Dec. 13, 2001, Taylor.  
 U.S. Appl. No. 60/341,176, filed Dec. 13, 2001, Taylor.  
 U.S. Appl. No. 60/340,462, filed Dec. 13, 2001, Taylor.  
 U.S. Appl. No. 60/340,090, filed Dec. 13, 2001, Taylor.  
 U.S. Appl. No. 60/341,433, filed Dec. 13, 2001, Taylor.  
 U.S. Appl. No. 60/341,592, filed Dec. 13, 2001, Taylor.  
 U.S. Appl. No. 60/341,320, filed Dec. 13, 2001, Taylor.  
 U.S. Appl. No. 60/391,070, filed Jun. 6, 2002, Reeves.  
 Electrical schematic and promotional material available from Zenion Industries, 7 pages, Aug. 1990.  
 Promotional material available from Zenion Industries for the Plasma-Pure 100/200/300, 2 pages, Aug. 1990.  
 Promotional material available from Zenion Industries for the Plasma-Tron, 2 pages, Aug. 1990.  
 LENTEK Sila™ Plug-In Air Purifier/Deodorizer product box copy-righted 1999, 13 pages.  
 Trion Console 250 Electronic Air Cleaner, Model Series 442857 and 445600, Manual for Installation•Operation•Maintenance, Trion Inc., 7 pp., believed to be at least one year prior to Nov. 5, 1998.  
 Trion 350 Air Purifier, Model 450111-010, <http://www.feddersoutlet.com/trion350.html>, 12 pp., believed to be at least one year prior to Nov. 5, 1998.  
 Trion 150 Air Purifier, Model 45000-002, <http://www.feddersoutlet.com/trion150.html>, 11 pp., believed to be at least one year prior to Nov. 5, 1998.  
 Trion 120 Air Purifier, Model 442501-025, <http://www.feddersoutlet.com/trion120.html>, 16 pp., believed to be at least one year prior to Nov. 5, 1998.  
 Friedrich C-90A Electronic Air Cleaner, Service Information, Friedrich Air Conditioning Co., 12 pp., 1985.  
 LakeAir Excel and Maxum Portable Electronic Air Cleaners, Operating and Service Manual, LakeAir International, Inc., 11 pp., 1971.  
 Blueair AV 402 Air Purifier, [http://www.air-purifiers-usa.biz/Blueair\\_AV402.htm](http://www.air-purifiers-usa.biz/Blueair_AV402.htm), 4 pp., 1996.  
 Blueair AV 501 Air Purifier, [http://www.air-purifiers-usa.biz/Blueair\\_AV501.htm](http://www.air-purifiers-usa.biz/Blueair_AV501.htm), 15 pp., 1997.  
 ConsumerReports.org, "Air Cleaners: Behind the Hype," [http://www.consumerreports.org/main/content/printable.jsp?FOLDER%3C%3EFOLDER\\_id](http://www.consumerreports.org/main/content/printable.jsp?FOLDER%3C%3EFOLDER_id), Oct. 2003, 6 pp.  
 "Household Air Cleaners," Consumer Reports Magazine, Oct. 1992, 6 pp.  
 Friedrich C-90A, "How the C-90A Works," BestAirCleaner.com <http://www.bestaircleaner.com/faq/c90works.asp>, 1 page.  
 English Translation of Japanese Unexamined Utility Model Application No. S62-20653; Publication Date: Feb. 7, 1987.  
 English Translation of Japanese Unexamined Patent Application Bulletin No. S51-90077; Publication Date: Aug. 6, 1976.  
 English Translation of German Published Patent Application 2206057; Publication Date: Aug. 16, 1973.  
 English Translation of Japanese Unexamined Utility Model Application No. S63-164948; Publication Date: Oct. 27, 1988.  
 English Translation of German Patent Document DE 197 41 621 C1; Publication Date: Jun. 10, 1999.

\* cited by examiner



**FIG. 1A (PRIOR ART)**



**FIG. 1B (PRIOR ART)**




FIG. 2A




FIG. 2B






FIG. 3





**FIG. 4A**



**FIG. 4B**




FIG. 4C




FIG. 4D




FIG. 4E




FIG. 4F




FIG. 4G






FIG. 4H






**FIG. 4I**



**FIG. 4J**



**FIG. 4K**

## AIR CONDITIONER DEVICES

## CLAIM OF PRIORITY

This application claims priority to and is a continuation of U.S. patent application Ser. No. 09/730,499, filed on Dec. 5, 2000 and entitled "Electro-Kinetic Air Transporter-Conditioner," now U.S. Pat. No. 6,713,026, which is a continuation of U.S. patent application Ser. No. 09/186,471, filed on Nov. 5, 1998 and entitled "Electro-Kinetic Air Transporter-Conditioner," now U.S. Pat. No. 6,176,977, both of which applications are incorporated herein by reference.

## FIELD OF THE INVENTION

This invention relates to electro-kinetic conversion of electrical energy into fluid flow of an ionizable dielectric medium, and more specifically to methods and devices for electro-kinetically producing a flow of air from which particulate matter has been substantially removed. Preferably the air flow should contain safe amounts of ozone ( $O_3$ ).

## BACKGROUND OF THE INVENTION

The use of an electric motor to rotate a fan blade to create an air flow has long been known in the art. Unfortunately, such fans produce substantial noise, and can present a hazard to children who may be tempted to poke a finger or a pencil into the moving fan blade. Although such fans can produce substantial air flow, e.g., 1,000 ft<sup>3</sup>/minute or more, substantial electrical power is required to operate the motor, and essentially no conditioning of the flowing air occurs.

It is known to provide such fans with a HEPA-compliant filter element to remove particulate matter larger than perhaps 0.3  $\mu$ m. Unfortunately, the resistance to air flow presented by the filter element may require doubling the electric motor size to maintain a desired level of airflow. Further, HEPA-compliant filter elements are expensive, and can represent a substantial portion of the sale price of a HEPA-compliant filter-fan unit. While such filter-fan units can condition the air by removing large particles, particulate matter small enough to pass through the filter element is not removed, including bacteria, for example.

It is also known in the art to produce an air flow using electro-kinetic techniques, by which electrical power is directly converted into a flow of air without mechanically moving components. One such system is described in U.S. Pat. No. 4,789,801 to Lee (1988), depicted herein in simplified form as FIGS. 1A and 1B. Lee's system 10 includes an array of small area ("minisectional") electrodes 20 that is spaced-apart symmetrically from an array of larger area ("maxisectional") electrodes 30. The positive terminal of a pulse generator 40 that outputs a train of high voltage pulses (e.g., 0 to perhaps +5 KV) is coupled to the minisectional array, and the negative pulse generator terminal is coupled to the maxisectional array.

The high voltage pulses ionize the air between the arrays, and an air flow 50 from the minisectional array toward the maxisectional array results, without requiring any moving parts. Particulate matter 60 in the air is entrained within the airflow 50 and also moves towards the maxisectional electrodes 30. Much of the particulate matter is electrostatically attracted to the surface of the maxisectional electrode array, where it remains, thus conditioning the flow of air exiting system 10. Further, the high voltage field present between the electrode arrays can release ozone into the ambient environ-

ment, which appears to destroy or at least alter whatever is entrained in the airflow, including for example, bacteria.

In the embodiment of FIG. 1A, minisectional electrodes 20 are circular in cross-section, having a diameter of about 0.003" (0.08 mm), whereas the maxisectional electrodes 30 are substantially larger in area and define a "teardrop" shape in cross-section. The ratio of cross-sectional areas between the maxisectional and minisectional electrodes is not explicitly stated, but from Lee's figures appears to exceed 10:1. As shown in FIG. 1A herein, the bulbous front surfaces of the maxisectional electrodes face the minisectional electrodes, and the somewhat sharp trailing edges face the exit direction of the air flow. The "sharpened" trailing edges on the maxisectional electrodes apparently promote good electrostatic attachment of particular matter entrained in the airflow. Lee does not disclose how the teardrop shaped maxisectional electrodes are fabricated, but presumably they are produced using a relatively expensive mold-casting or an extrusion process.

In another embodiment shown herein as FIG. 1B, Lee's maxisectional electrodes 30 are symmetrical and elongated in cross-section. The elongated trailing edges on the maxisectional electrodes provide increased area upon which particulate matter entrained in the airflow can attach. Lee states that precipitation efficiency and desired reduction of anion release into the environment can result from including a passive third array of electrodes 70. Understandably, increasing efficiency by adding a third array of electrodes will contribute to the cost of manufacturing and maintaining the resultant system.

While the electrostatic techniques disclosed by Lee are advantageous to conventional electric fan-filter units, Lee's maxisectional electrodes are relatively expensive to fabricate. Further, increased filter efficiency beyond what Lee's embodiments can produce would be advantageous, especially without including a third array of electrodes.

Thus, there is a need for an electro-kinetic air transporter-conditioner that provides improved efficiency over Lee-type systems, without requiring expensive production techniques to fabricate the electrodes. Preferably such a conditioner should function efficiently without requiring a third array of electrodes. Further, such a conditioner should permit user-selection of safe amounts of ozone to be generated, for example to remove odor from the ambient environment.

The present invention provides a method and apparatus for electro-kinetically transporting and conditioning air.

## SUMMARY OF THE PRESENT INVENTION

The present invention provides an electro-kinetic system for transporting and conditioning air without moving parts. The air is conditioned in the sense that it is ionized and contains safe amounts of ozone.

Applicants' electro-kinetic air transporter-conditioner includes a louvered or gridded body that houses an ionizer unit. The ionizer unit includes a high voltage DC inverter that boosts common 110 VAC to high voltage, and a generator that receives the high voltage DC and outputs high voltage pulses of perhaps 10 KV peak-to-peak, although an essentially 100% duty cycle (e.g., high voltage DC) output could be used instead of pulses. The unit also includes an electrode assembly unit comprising first and second spaced-apart arrays of conducting electrodes, the first array and second array being coupled, respectively, preferably to the positive and negative output ports of the high voltage generator.

The electrode assembly preferably is formed using first and second arrays of readily manufacturable electrode types. In

3

one embodiment, the first array comprises wire-like electrodes and the second array comprises "U"-shaped electrodes having one or two trailing surfaces. In an even more efficient embodiment, the first array includes at least one pin or cone-like electrode and the second array is an annular washer-like electrode. The electrode assembly may comprise various combinations of the described first and second array electrodes. In the various embodiments, the ratio between effective area of the second array electrodes to the first array electrodes is at least about 20:1.

The high voltage pulses create an electric field between the first and second electrode arrays. This field produces an electro-kinetic airflow going from the first array toward the second array, the airflow being rich in preferably a net surplus of negative ions and in ozone. Ambient air including dust particles and other undesired components (germs, perhaps) enter the housing through the grill or louver openings, and ionized clean air (with ozone) exits through openings on the downstream side of the housing.

The dust and other particulate matter attaches electrostatically to the second array (or collector) electrodes, and the output air is substantially clean of such particulate matter. Further, ozone generated by the present invention can kill certain types of germs and the like, and also eliminates odors in the output air. Preferably the transporter operates in periodic bursts, and a control permits the user to temporarily increase the high voltage pulse generator output, e.g., to more rapidly eliminate odors in the environment.

Other features and advantages of the invention will appear from the following description in which the preferred embodiments have been set forth in detail, in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a plan, cross-sectional view, of a first embodiment of a prior art electro-kinetic air transporter-conditioner system, according to the prior art.

FIG. 1B is a plan, cross-sectional view, of a second embodiment of a prior art electro-kinetic air transporter-conditioner system, according to the prior art.

FIG. 2A is an perspective view of a preferred embodiment of the present invention.

FIG. 2B is a perspective view of the embodiment of FIG. 2A, with the electrode assembly partially withdrawn, according to the present invention.

FIG. 3 is an electrical block diagram of the present invention.

FIG. 4A is a perspective block diagram showing a first embodiment for an electrode assembly, according to the present invention.

FIG. 4B is a plan block diagram of the embodiment of FIG. 4A.

FIG. 4C is a perspective block diagram showing a second embodiment for an electrode assembly, according to the present invention.

FIG. 4D is a plan block diagram of a modified version of the embodiment of FIG. 4C.

FIG. 4E is a perspective block diagram showing a third embodiment for an electrode assembly, according to the present invention.

FIG. 4F is a plan block diagram of the embodiment of FIG. 4E.

FIG. 4G is a perspective block diagram showing a fourth embodiment for an electrode assembly, according to the present invention.

4

FIG. 4H is a plan block diagram of the embodiment of FIG. 4G.

FIG. 4I is a perspective block diagram showing a fifth embodiment for an electrode assembly, according to the present invention.

FIG. 4J is a detailed cross-sectional view of a portion of the embodiment of FIG. 4I.

FIG. 4K is a detailed cross-sectional view of a portion of an alternative to the embodiment of FIG. 4I.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

FIGS. 2A and 2B depict an electro-kinetic air transporter-conditioner system **100** whose housing **102** includes preferably rear-located intake vents or louvers **104** and preferably front and side-located exhaust vents **106**, and a base pedestal **108**. Internal to the transporter housing is an ion generating unit **160**, preferably powered by an AC:DC power supply that is energizable using switch **S1**. Ion generating unit **160** is self-contained in that other than ambient air, nothing is required from beyond the transporter housing, save external operating potential, for operation of the present invention.

The upper surface of housing **102** includes a user-liftable handle **112** to which is affixed an electrode assembly **220** that comprises a first array **230** of electrodes **232** and a second array **240** of electrodes **242**. The first and second arrays of electrodes are coupled in series between the output terminals of ion generating unit **160**, as best seen in FIG. 3. The ability to lift handle **112** provides ready access to the electrodes comprising the electrode assembly, for purposes of cleaning and, if necessary, replacement.

The general shape of the invention shown in FIGS. 2A and 2B is not critical. The top-to-bottom height of the preferred embodiment is perhaps 1 m, with a left-to-right width of perhaps 15 cm, and a front-to-back depth of perhaps 10 cm, although other dimensions and shapes may of course be used. A louvered construction provides ample inlet and outlet venting in an economical housing configuration. There need be no real distinction between vents **104** and **106**, except their location relative to the second array electrodes, and indeed a common vent could be used. These vents serve to ensure that an adequate flow of ambient air may be drawn into or made available to the present invention, and that an adequate flow of ionized air that includes safe amounts of  $O_3$  flows out from unit **130**.

As will be described, when unit **100** is energized with **S1**, high voltage output by ion generator **160** produces ions at the first electrode array, which ions are attracted to the second electrode array. The movement of the ions in an "IN" to "OUT" direction carries with them air molecules, thus electrokinetically producing an outflow of ionized air. The "IN" notion in FIGS. 2A and 2B denote the intake of ambient air with particulate matter **60**. The "OUT" notation in the figures denotes the outflow of cleaned air substantially devoid of the particulate matter, which adheres electrostatically to the surface of the second array electrodes. In the process of generating the ionized air flow, safe amounts of ozone ( $O_3$ ) are beneficially produced. It may be desired to provide the inner surface of housing **102** with an electrostatic shield to reduce detectable electromagnetic radiation. For example, a metal shield could be disposed within the housing, or portions of the interior of the housing could be coated with a metallic paint to reduce such radiation.

As best seen in FIG. 3, ion generating unit **160** includes a high voltage generator unit **170** and circuitry **180** for converting raw alternating voltage (e.g., 117 VAC) into direct current

5

("DC") voltage. Circuitry **180** preferably includes circuitry controlling the shape and/or duty cycle of the generator unit output voltage (which control is altered with user switch **S2**). Circuitry **180** preferably also includes a pulse mode component, coupled to switch **S3**, to temporarily provide a burst of increased output ozone. Circuitry **180** can also include a timer circuit and a visual indicator such as a light emitting diode ("LED"). The LED or other indicator (including, if desired, audible indicator) signals when ion generation is occurring. The timer can automatically halt generation of ions and/or ozone after some predetermined time, e.g., 30 minutes. indicator(s), and/or audible indicator(s).

As shown in FIG. 3, high voltage generator unit **170** preferably comprises a low voltage oscillator circuit **190** of perhaps 20 KHz frequency, that outputs low voltage pulses to an electronic switch **200**, e.g., a thyristor or the like. Switch **200** switchably couples the low voltage pulses to the input winding of a step-up transformer **T1**. The secondary winding of **T1** is coupled to a high voltage multiplier circuit **210** that outputs high voltage pulses. Preferably the circuitry and components comprising high voltage pulse generator **170** and circuit **180** are fabricated on a printed circuit board that is mounted within housing **102**. If desired, external audio input (e.g., from a stereo tuner) could be suitably coupled to oscillator **190** to acoustically modulate the kinetic airflow produced by unit **160**. The result would be an electrostatic loudspeaker, whose output air flow is audible to the human ear in accordance with the audio input signal. Further, the output air stream would still include ions and ozone.

Output pulses from high voltage generator **170** preferably are at least 10 KV peak-to-peak with an effective DC offset of perhaps half the peak-to-peak voltage, and have a frequency of perhaps 20 KHz. The pulse train output preferably has a duty cycle of perhaps 10%, which will promote battery lifetime. Of course, different peak-peak amplitudes, DC offsets, pulse train waveshapes, duty cycle, and/or repetition frequencies may instead be used. Indeed, a 100% pulse train (e.g., an essentially DC high voltage) may be used, albeit with shorter battery lifetime. Thus, generator unit **170** may (but need not) be referred to as a high voltage pulse generator.

Frequency of oscillation is not especially critical but frequency of at least about 20 KHz is preferred as being inaudible to humans. If pets will be in the same room as the present invention, it may be desired to utilize an even higher operating frequency, to prevent pet discomfort and/or howling by the pet.

The output from high voltage pulse generator unit **170** is coupled to an electrode assembly **220** that comprises a first electrode array **230** and a second electrode array **240**. Unit **170** functions as a DC:DC high voltage generator, and could be implemented using other circuitry and/or techniques to output high voltage pulses that are input to electrode assembly **220**.

In the embodiment of FIG. 3, the positive output terminal of unit **170** is coupled to first electrode array **230**, and the negative output terminal is coupled to second electrode array **240**. This coupling polarity has been found to work well, including minimizing unwanted audible electrode vibration or hum. An electrostatic flow of air is created, going from the first electrode array towards the second electrode array. (This flow is denoted "OUT" in the figures.) Accordingly electrode assembly **220** is mounted within transporter system **100** such that second electrode array **240** is closer to the OUT vents and first electrode array **230** is closer to the IN vents.

When voltage or pulses from high voltage pulse generator **170** are coupled across first and second electrode arrays **230** and **240**, it is believed that a plasma-like field is created

6

surrounding electrodes **232** in first array **230**. This electric field ionizes the ambient air between the first and second electrode arrays and establishes an "OUT" airflow that moves towards the second array. It is understood that the IN flow enters via vent(s) **104**, and that the OUT flow exits via vent(s) **106**.

It is believed that ozone and ions are generated simultaneously by the first array electrode(s) **232**, essentially as a function of the potential from generator **170** coupled to the first array. Ozone generation may be increased or decreased by increasing or decreasing the potential at the first array. Coupling an opposite polarity potential to the second array electrode(s) **242** essentially accelerates the motion of ions generated at the first array, producing the air flow denoted as "OUT" in the figures. As the ions move toward the second array, it is believed that they push or move air molecules toward the second array. The relative velocity of this motion may be increased by decreasing the potential at the second array relative to the potential at the first array.

For example, if +10 KV were applied to the first array electrode(s), and no potential were applied to the second array electrode(s), a cloud of ions (whose net charge is positive) would form adjacent the first electrode array. Further, the relatively high 10 KV potential would generate substantial ozone. By coupling a relatively negative potential to the second array electrode(s), the velocity of the air mass moved by the net emitted ions increases, as momentum of the moving ions is conserved.

On the other hand, if it were desired to maintain the same effective outflow (OUT) velocity but to generate less ozone, the exemplary 10 KV potential could be divided between the electrode arrays. For example, generator **170** could provide +4 KV (or some other fraction) to the first array electrode(s) and -6 KV (or some other fraction) to the second array electrode(s). In this example, it is understood that the +4 KV and the -6 KV are measured relative to ground. Understandably it is desired that the present invention operate to output safe amounts of ozone. Accordingly, the high voltage is preferably fractionalized with about +4 KV applied to the first array electrode(s) and about -6 KV applied to the second array electrodes.

As noted, outflow (OUT) preferably includes safe amounts of O<sub>3</sub> that can destroy or at least substantially alter bacteria, germs, and other living (or quasi-living) matter subjected to the outflow. Thus, when switch **S1** is closed and **B1** has sufficient operating potential, pulses from high voltage pulse generator unit **170** create an outflow (OUT) of ionized air and O<sub>3</sub>. When **S1** is closed, LED will visually signal when ionization is occurring.

Preferably operating parameters of the present invention are set during manufacture and are not user-adjustable. For example, increasing the peak-to-peak output voltage and/or duty cycle in the high voltage pulses generated by unit **170** can increase air flowrate, ion content, and ozone content. In the preferred embodiment, output flowrate is about 200 feet/minute, ion content is about 2,000,000/cc and ozone content is about 40 ppb (over ambient) to perhaps 2,000 ppb (over ambient). Decreasing the R2/R1 ratio below about 20:1 will decrease flow rate, as will decreasing the peak-to-peak voltage and/or duty cycle of the high voltage pulses coupled between the first and second electrode arrays.

In practice, unit **100** is placed in a room and connected to an appropriate source of operating potential, typically 117 VAC. With **S1** energized, ionization unit **160** emits ionized air and preferably some ozone (O<sub>3</sub>) via outlet vents **150**. The air flow, coupled with the ions and ozone freshens the air in the room, and the ozone can beneficially destroy or at least diminish the

undesired effects of certain odors, bacteria, germs, and the like. The air flow is indeed electro-kinetically produced, in that there are no intentionally moving parts within the present invention. (As noted, some mechanical vibration may occur within the electrodes.) As will be described with respect to FIG. 4A, it is desirable that the present invention actually output a net surplus of negative ions, as these ions are deemed more beneficial to health than are positive ions.

Having described various aspects of the invention in general, preferred embodiments of electrode assembly 220 will now be described. In the various embodiments, electrode assembly 220 will comprise a first array 230 of at least one electrode 232, and will further comprise a second array 240 of preferably at least one electrode 242. Understandably material(s) for electrodes 232 and 242 should conduct electricity, be resilient to corrosive effects from the application of high voltage, yet be strong enough to be cleaned.

In the various electrode assemblies to be described herein, electrode(s) 232 in the first electrode array 230 are preferably fabricated from tungsten. Tungsten is sufficiently robust to withstand cleaning, has a high melting point to retard breakdown due to ionization, and has a rough exterior surface that seems to promote efficient ionization. On the other hand, electrodes 242 preferably will have a highly polished exterior surface to minimize unwanted point-to-point radiation. As such, electrodes 242 preferably are fabricated from stainless steel, brass, among other materials. The polished surface of electrodes 232 also promotes ease of electrode cleaning.

In contrast to the prior art electrodes disclosed by Lee, electrodes 232 and 242 according to the present invention are light weight, easy to fabricate, and lend themselves to mass production. Further, electrodes 232 and 242 described herein promote more efficient generation of ionized air, and production of safe amounts of ozone, O<sub>3</sub>.

In the present invention, a high voltage pulse generator 170 is coupled between the first electrode array 230 and the second electrode array 240. The high voltage pulses produce a flow of ionized air that travels in the direction from the first array towards the second array (indicated herein by hollow arrows denoted "OUT"). As such, electrode(s) 232 may be referred to as an emitting electrode, and electrodes 242 may be referred to as collector electrodes. This outflow advantageously contains safe amounts of O<sub>3</sub>, and exits the present invention from vent(s) 106.

According to the present invention, it is preferred that the positive output terminal or port of the high voltage pulse generator be coupled to electrodes 232, and that the negative output terminal or port be coupled to electrodes 242. It is believed that the net polarity of the emitted ions is positive, e.g., more positive ions than negative ions are emitted. In any event, the preferred electrode assembly electrical coupling minimizes audible hum from electrodes 232 contrasted with reverse polarity (e.g., interchanging the positive and negative output port connections).

However, while generation of positive ions is conducive to a relatively silent air flow, from a health standpoint, it is desired that the output air flow be richer in negative ions, not positive ions. It is noted that in some embodiments, however, one port (preferably the negative port) of the high voltage pulse generator may in fact be the ambient air. Thus, electrodes in the second array need not be connected to the high voltage pulse generator using wire. Nonetheless, there will be an "effective connection" between the second array electrodes and one output port of the high voltage pulse generator, in this instance, via ambient air.

Turning now to the embodiments of FIGS. 4A and 4B, electrode assembly 220 comprises a first array 230 of wire

electrodes 232, and a second array 240 of generally "U"-shaped electrodes 242. In preferred embodiments, the number N1 of electrodes comprising the first array will preferably differ by one relative to the number N2 of electrodes comprising the second array. In many of the embodiments shown, N2>N1. However, if desired, in FIG. 4A, addition first electrodes 232 could be added at the out ends of array 230 such that N1>N2, e.g., five electrodes 232 compared to four electrodes 242.

Electrodes 232 are preferably lengths of tungsten wire, whereas electrodes 242 are formed from sheet metal, preferably stainless steel, although brass or other sheet metal could be used. The sheet metal is readily formed to define side regions 244 and bulbous nose region 246 for hollow elongated "U" shaped electrodes 242. While FIG. 4A depicts four electrodes 242 in second array 240 and three electrodes 232 in first array 230, as noted, other numbers of electrodes in each array could be used, preferably retaining a symmetrically staggered configuration as shown. It is seen in FIG. 4A that while particulate matter 60 is present in the incoming (IN) air, the outflow (OUT) air is substantially devoid of particulate matter, which adheres to the preferably large surface area provided by the second array electrodes (see FIG. 4B).

As best seen in FIG. 4B, the spaced-apart configuration between the arrays is staggered such that each first array electrode 232 is substantially equidistant from two second array electrodes 242. This symmetrical staggering has been found to be an especially efficient electrode placement. Preferably the staggering geometry is symmetrical in that adjacent electrodes 232 or adjacent electrodes 242 are spaced-apart a constant distance, Y1 and Y2 respectively. However, a non-symmetrical configuration could also be used, although ion emission and air flow would likely be diminished. Also, it is understood that the number of electrodes 232 and 242 may differ from what is shown.

In FIG. 4A, typically dimensions are as follows: diameter of electrodes 232 is about 0.08 mm, distances Y1 and Y2 are each about 16 mm, distance X1 is about 16 mm, distance L is about 20 mm, and electrode heights Z1 and Z2 are each about 1 m. The width W of electrodes 242 is preferably about 4 mm, and the thickness of the material from which electrodes 242 are formed is about 0.5 mm. Of course other dimensions and shapes could be used. It is preferred that electrodes 232 be small in diameter to help establish a desired high voltage field. On the other hand, it is desired that electrodes 232 (as well as electrodes 242) be sufficiently robust to withstand occasional cleaning.

Electrodes 232 in first array 230 are coupled by a conductor 234 to a first (preferably positive) output port of high voltage pulse generator 170, and electrodes 242 in second array 240 are coupled by a conductor 244 to a second (preferably negative) output port of generator 170. It is relatively unimportant where on the various electrodes electrical connection is made to conductors 234 or 244. Thus, by way of example FIG. 4B depicts conductor 244 making connection with some electrodes 242 internal to bulbous end 246, while other electrodes 242 make electrical connection to conductor 244 elsewhere on the electrode. Electrical connection to the various electrodes 242 could also be made on the electrode external surface providing no substantial impairment of the outflow airstream results.

To facilitate removing the electrode assembly from unit 100 (as shown in FIG. 2B), it is preferred that the lower end of the various electrodes fit against mating portions of wire or other conductors 234 or 244. For example, "cup-like" members can be affixed to wires 234 and 244 into which the free

ends of the various electrodes fit when electrode array 220 is inserted completely into housing 102 of unit 100.

The ratio of the effective electric field emanating area of electrode 232 to the nearest effective area of electrodes 242 is at least about 15:1, and preferably is at least 20:1. Thus, in the embodiment of FIG. 4A and FIG. 4B, the ratio  $R2/R1 \approx 2 \text{ mm}/0.04 \text{ mm} \approx 50:1$ .

In this and the other embodiments to be described herein, ionization appears to occur at the smaller electrode(s) 232 in the first electrode array 230, with ozone production occurring as a function of high voltage arcing. For example, increasing the peak-to-peak voltage amplitude and/or duty cycle of the pulses from the high voltage pulse generator 170 can increase ozone content in the output flow of ionized air. If desired, user-control S2 can be used to somewhat vary ozone content by varying (in a safe manner) amplitude and/or duty cycle. Specific circuitry for achieving such control is known in the art and need not be described in detail herein.

Note the inclusion in FIGS. 4A and 4B of at least one output controlling electrode 243, preferably electrically coupled to the same potential as the second array electrodes. Electrode 243 preferably defines a pointed shape in side profile, e.g., a triangle. The sharp point on electrode(s) 243 causes generation of substantial negative ions (since the electrode is coupled to relatively negative high potential). These negative ions neutralize excess positive ions otherwise present in the output air flow, such that the OUT flow has a net negative charge. Electrode(s) 243 preferably are stainless steel, copper, or other conductor, and are perhaps 20 mm high and about 12 mm wide at the base.

Another advantage of including pointed electrodes 243 is that they may be stationarily mounted within the housing of unit 100, and thus are not readily reached by human hands when cleaning the unit. Were it otherwise, the sharp point on electrode(s) 243 could easily cause cuts. The inclusion of one electrode 243 has been found sufficient to provide a sufficient number of output negative ions, but more such electrodes may be included.

In the embodiment of FIGS. 4A and 4C, each "U"-shaped electrode 242 has two trailing edges that promote efficient kinetic transport of the outflow of ionized air and  $O_3$ . Note the inclusion on at least one portion of a trailing edge of a pointed electrode region 243'. Electrode region 243' helps promote output of negative ions, in the same fashion as was described with respect to FIGS. 4A and 4B. Note, however, the higher likelihood of a user cutting himself or herself when wiping electrodes 242 with a cloth or the like to remove particulate matter deposited thereon. In FIG. 4C and the figures to follow, the particulate matter is omitted for ease of illustration. However, from what was shown in FIGS. 2A-4B, particulate matter will be present in the incoming air, and will be substantially absent from the outgoing air. As has been described, particulate matter 60 typically will be electrostatically precipitated upon the surface area of electrodes 242.

Note that the embodiments of FIGS. 4C and 4D depict somewhat truncated versions of electrodes 242. Whereas dimension L in the embodiment of FIGS. 4A and 4B was about 20 mm, in FIGS. 4C and 4D, L has been shortened to about 8 mm. Other dimensions in FIG. 4C preferably are similar to those stated for FIGS. 4A and 4B. In FIGS. 4C and 4D, the inclusion of point-like regions 246 on the trailing edge of electrodes 242 seems to promote more efficient generation of ionized air flow. It will be appreciated that the configuration of second electrode array 240 in FIG. 4C can be more robust than the configuration of FIGS. 4A and 4B, by virtue of the shorter trailing edge geometry. As noted earlier, a sym-

metrical staggered geometry for the first and second electrode arrays is preferred for the configuration of FIG. 4C.

In the embodiment of FIG. 4D, the outermost second electrodes, denoted 242-1 and 242-2, have substantially no outermost trailing edges. Dimension L in FIG. 4D is preferably about 3 mm, and other dimensions may be as stated for the configuration of FIGS. 4A and 4B. Again, the  $R2/R1$  ratio for the embodiment of FIG. 4D preferably exceeds about 20:1.

FIGS. 4E and 4F depict another embodiment of electrode assembly 220, in which the first electrode array comprises a single wire electrode 232, and the second electrode array comprises a single pair of curved "L"-shaped electrodes 242, in cross-section. Typical dimensions, where different than what has been stated for earlier-described embodiments, are  $X1 \approx 12 \text{ mm}$ ,  $Y1 \approx 6 \text{ mm}$ ,  $Y2 \approx 5 \text{ mm}$ , and  $L1 \approx 3 \text{ mm}$ . The effective  $R2/R1$  ratio is again greater than about 20:1. The fewer electrodes comprising assembly 220 in FIGS. 4E and 4F promote economy of construction, and ease of cleaning, although more than one electrode 232, and more than two electrodes 242 could of course be employed. This embodiment again incorporates the staggered symmetry described earlier, in which electrode 232 is equidistant from two electrodes 242.

FIGS. 4G and 4H shown yet another embodiment for electrode assembly 220. In this embodiment, first electrode array 230 is a length of wire 232, while the second electrode array 240 comprises a pair of rod or columnar electrodes 242. As in embodiments described earlier herein, it is preferred that electrode 232 be symmetrically equidistant from electrodes 242. Wire electrode 232 is preferably perhaps 0.08 mm tungsten, whereas columnar electrodes 242 are perhaps 2 mm diameter stainless steel. Thus, in this embodiment the  $R2/R1$  ratio is about 25:1. Other dimensions may be similar to other configurations, e.g., FIGS. 4E, 4F. Of course electrode assembly 220 may comprise more than one electrode 232, and more than two electrodes 242.

An especially preferred embodiment is shown in FIG. 4I and FIG. 4J. In these figures, the first electrode assembly comprises a single pin-like element 232 disposed coaxially with a second electrode array that comprises a single ring-like electrode 242 having a rounded inner opening 246. However, as indicated by phantom elements 232', 242', electrode assembly 220 may comprise a plurality of such pin-like and ring-like elements. Preferably electrode 232 is tungsten, and electrode 242 is stainless steel.

Typical dimensions for the embodiment of FIG. 4I and FIG. 4J are  $L1 \approx 10 \text{ mm}$ ,  $X1 \approx 9.5 \text{ mm}$ ,  $T \approx 0.5 \text{ mm}$ , and the diameter of opening 246 is about 12 mm. Dimension L1 preferably is sufficiently long that upstream portions of electrode 232 (e.g., portions to the left in FIG. 4I) do not interfere with the electrical field between electrode 232 and the collector electrode 242. However, as shown in FIG. 4J, the effect  $R2/R1$  ratio is governed by the tip geometry of electrode 232. Again, in the preferred embodiment, this ratio exceeds about 20:1. Lines drawn in phantom in FIG. 4J depict theoretical electric force field lines, emanating from emitter electrode 232, and terminating on the curved surface of collector electrode 246. Preferably the bulk of the field emanates within about  $\pm 45^\circ$  of coaxial axis between electrode 232 and electrode 242. On the other hand, if the opening in electrode 242 and/or electrode 232 and 242 geometry is such that too narrow an angle about the coaxial axis exists, air flow will be unduly restricted.

One advantage of the ring-pin electrode assembly configuration shown in FIG. 4I is that the flat regions of ring-like

## 11

electrode **242** provide sufficient surface area to which particulate matter **60** entrained in the moving air stream can attach, yet be readily cleaned.

Further, the ring-pin configuration advantageously generates more ozone than prior art configurations, or the configurations of FIGS. **4A-4H**. For example, whereas the configurations of FIGS. **4A-4H** may generate perhaps 50 ppb ozone, the configuration of FIG. **4I** can generate about 2,000 ppb ozone.

Nonetheless it will be appreciated that applicants' first array pin electrodes may be utilized with the second array electrodes of FIGS. **4A-4H**. Further, applicants' second array ring electrodes may be utilized with the first array electrodes of FIGS. **4A-4H**. For example, in modifications of the embodiments of FIGS. **4A-4H**, each wire or columnar electrode **232** is replaced by a column of electrically series-connected pin electrodes (e.g., as shown in FIGS. **4I-4K**), while retaining the second electrode arrays as depicted in these figures. By the same token, in other modifications of the embodiments of FIGS. **4A-4H**, the first array electrodes can remain as depicted, but each of the second array electrodes **242** is replaced by a column of electrically series-connected ring electrodes (e.g., as shown in FIGS. **4I-4K**).

In FIG. **4J**, a detailed cross-sectional view of the central portion of electrode **242** in FIG. **4I** is shown. As best seen in FIG. **4J**, curved region **246** adjacent the central opening in electrode **242** appears to provide an acceptably large surface area to which many ionization paths from the distal tip of electrode **232** have substantially equal path length. Thus, while the distal tip (or emitting tip) of electrode **232** is advantageously small to concentrate the electric field between the electrode arrays, the adjacent regions of electrode **242** preferably provide many equidistant inter-electrode array paths. A high exit flowrate of perhaps 90 feet/minute and 2,000 ppb range ozone emission attainable with this configuration confirm a high operating efficiency.

In FIG. **4K**, one or more electrodes **232** is replaced by a conductive block **232'** of carbon fibers, the block having a distal surface in which projecting fibers **233-1, . . . 233-N** take on the appearance of a "bed of nails". The projecting fibers can each act as an emitting electrode and provide a plurality of emitting surfaces. Over a period of time, some or all of the electrodes will literally be consumed, whereupon graphite block **232'** will be replaced. Materials other than graphite may be used for block **232'** providing the material has a surface with projecting conductive fibers such as **233-N**.

As described, the net output of ions is influenced by placing a bias element (e.g., element **243**) near the output stream and preferably near the downstream side of the second array electrodes. If no ion output were desired, such an element could achieve substantial neutralization. It will also be appreciated that the present invention could be adjusted to produce ions without producing ozone, if desired.

Modifications and variations may be made to the disclosed embodiments without departing from the subject and spirit of the invention as defined by the following claims.

We claim:

1. An air treatment apparatus comprising:

a housing having:

(a) a bottom portion;

(b) a top portion; and

(c) a body portion positioned between the bottom portion and the top portion, the body portion extending along a first axis, the body portion having:

(i) at least one intake vent; and

(ii) at least one exhaust vent;

a first electrode supported by the housing;

## 12

a second electrode configured to be removably supported by the housing;

a voltage generator operatively coupled to the electrodes, the voltage generator being configured to cause a plurality of ions to flow toward the second electrode along a second axis, the second axis being substantially perpendicular to the first axis; and

a circuitry supported by the housing, the circuitry configured to cause the voltage generator to increase the flow of ions for a designated period of time after a designated event occurs by increasing the potential of the first electrode.

2. The air treatment apparatus of claim 1, the body portion of the housing having an inner wall, the inner wall defining a slot configured to receive the second electrode, the second electrode configured to be slidably removable through the slot.

3. The air treatment apparatus of claim 2, which includes a handle coupled to the second electrode.

4. The air treatment apparatus of claim 1, which includes a grasp coupled to the second electrode.

5. The air treatment apparatus of claim 1, which includes a pedestal coupled to the bottom portion of the housing.

6. The air treatment apparatus of claim 1, which includes at least one input device coupled to the top portion of the housing.

7. The air treatment apparatus of claim 1, which includes at least one output device coupled to the top portion of the housing.

8. The air treatment apparatus of claim 7, the output device including a light source.

9. The air treatment apparatus of claim 1, which includes the circuitry supported by the housing, the circuitry configured to cause the voltage generator to increase the flow of ions based on an input provided by a user.

10. An air treatment apparatus comprising:

a housing having:

(a) a bottom portion;

(b) a top portion; and

(c) a body portion positioned between the bottom portion and the top portion, the body portion extending along a first axis, the body portion having:

(i) at least one intake vent;

(ii) at least one exhaust vent; and

(iii) an inner wall which defines a slot;

a first electrode supported by the housing;

a second electrode configured to be:

(i) removably supported by the housing; and

(ii) slidably removable through the slot;

a voltage generator operatively coupled to the electrodes, the voltage generator being configured to cause a plurality of ions to flow toward the second electrode along a second axis, the second axis being substantially perpendicular to the first; and

a circuitry supported by the housing, the circuitry configured to cause the voltage generator to increase the flow of ions for a designated period of time after a designated event occurs by increasing the potential of the first electrode.

11. The air treatment apparatus of claim 10, which includes a grasp coupled to the second electrode.

12. The air treatment apparatus of claim 11, which includes a handle coupled to the second electrode.

13. The air treatment apparatus of claim 10, which includes a pedestal coupled to the bottom portion of the housing.

## 13

14. The air treatment apparatus of claim 10, which includes at least one input device coupled to the top portion of the housing.

15. The air treatment apparatus of claim 10, which includes at least one output device coupled to the top portion of the housing. 5

16. The air treatment apparatus of claim 15, the output device including a light source.

17. The air treatment apparatus of claim 10, which includes the circuitry supported by the housing, the circuitry configured to cause the voltage generator to increase the flow of ions based on an input provided by a user. 10

18. An air treatment apparatus comprising:  
an housing having:

- (a) an elongated shape;
- (b) a bottom portion;
- (c) a top portion; and

(d) a body portion positioned between the bottom portion and the top portion, the body portion extending along a first axis, the body portion having: 20

- (i) at least one intake vent;
  - (ii) at least one exhaust vent; and
  - (iii) an inner wall which defines a slot;
- a first electrode supported by the housing;
- a second electrode configured to be:
- (i) removably supported by the housing; and
  - (ii) slidably removable through the slot;

## 14

a voltage generator operatively coupled to the electrodes, the voltage generator being configured to cause a plurality of ions to flow toward the second electrode along a second axis, the second axis being substantially perpendicular to the first axis;

a circuitry supported by the housing, the circuitry configured to cause the voltage generator to increase the flow of ions for a designated period of time after a designated event occurs by increasing the potential of the first electrode; and

a grasp coupled to the second electrode.

19. The air treatment apparatus of claim 18, which includes a handle coupled to the second electrode.

20. The air treatment apparatus of claim 18, which includes a pedestal coupled to the bottom portion of the housing. 15

21. The air treatment apparatus of claim 18, which includes at least one input device coupled to the top portion of the housing.

22. The air treatment apparatus of claim 18, which includes at least one output device coupled to the top portion of the housing.

23. The air treatment apparatus of claim 22, the output device including a light source.

24. The air treatment apparatus of claim 18, which includes the circuitry supported by the housing, the circuitry configured to cause the voltage generator to increase the flow of ions based on an input provided by a user. 25

\* \* \* \* \*