

(12) **United States Patent**
Taylor et al.

(10) **Patent No.:** **US 7,291,207 B2**
(45) **Date of Patent:** **Nov. 6, 2007**

(54) **AIR TREATMENT APPARATUS WITH ATTACHABLE GRILL**

995,958 A 6/1911 Goldberg
1,791,338 A 2/1931 Wintermute
1,869,335 A 7/1932 Day

(75) Inventors: **Charles E. Taylor**, Punta Gorda, FL (US); **Andrew J. Parker**, Novato, CA (US); **Igor Y. Botvinnik**, Novato, CA (US); **Shek Fai Lau**, Foster City, CA (US); **Gregory S. Snyder**, Novato, CA (US); **John Paul Reeves**, Hong Kong (CN)

(Continued)

FOREIGN PATENT DOCUMENTS

CN 2111112 U 7/1972

(73) Assignee: **Sharper Image Corporation**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 214 days.

(Continued)

OTHER PUBLICATIONS

(21) Appl. No.: **11/007,556**

U.S. Appl. No. 60/104,573, filed Oct. 16, 1998, Krichtafovitch.

(22) Filed: **Dec. 8, 2004**

(Continued)

(65) **Prior Publication Data**

Primary Examiner—Richard L. Chiesa

(74) *Attorney, Agent, or Firm*—Bell, Boyd & Lloyd, LLP

US 2006/0018811 A1 Jan. 26, 2006

(57)

ABSTRACT

Related U.S. Application Data

(60) Provisional application No. 60/590,688, filed on Jul. 23, 2004.

(51) **Int. Cl.**
B03C 3/40 (2006.01)

(52) **U.S. Cl.** **96/83**; 96/16; 96/84; 96/86; 96/87; 96/94; 422/186.04

(58) **Field of Classification Search** 96/39–41, 96/16, 30, 51, 83–87, 94, 224; 95/57, 74; 422/186.04

See application file for complete search history.


(56) **References Cited**

U.S. PATENT DOCUMENTS

653,421 A 7/1900 Lorey
895,729 A 8/1908 Carlborg

Embodiments of the present invention are directed to a method and apparatus for moving air using an air treatment apparatus, the air treatment apparatus preferably including at least one first electrode, at least one second electrode, and at least one third electrode, and at least a portion of the third electrode is positioned downstream of the second electrode. The air treatment apparatus includes a grill configured to be attached to the air treatment apparatus, and the grill is movable between a first position in which the grill covers the portion of the third electrode and a second position in which the portion of the third electrode is uncovered. The grill is attached to or detached from the housing when in the second position.

29 Claims, 14 Drawing Sheets



US 7,291,207 B2

Page 2

U.S. PATENT DOCUMENTS

1,882,949	A	10/1932	Ruder	4,351,648	A	9/1982	Penney
2,129,783	A	9/1938	Penney	4,354,861	A	10/1982	Kalt
2,247,409	A	7/1941	Roper	4,357,150	A	11/1982	Masuda et al.
2,327,588	A	8/1943	Bennett	4,362,632	A	12/1982	Jacob
2,359,057	A	9/1944	Skinner	4,363,072	A	12/1982	Coggins
2,509,548	A	5/1950	White	4,366,525	A	12/1982	Baumgartner
2,590,447	A	3/1952	Nord et al.	4,369,776	A	1/1983	Roberts
2,949,550	A	8/1960	Brown	4,375,364	A	3/1983	Van Hoesen et al.
2,978,066	A *	4/1961	Nodolf 96/87	4,380,900	A	4/1983	Linder et al.
3,018,394	A	1/1962	Brown	4,386,395	A	5/1983	Francis, Jr.
3,026,964	A	3/1962	Penney	4,391,614	A	7/1983	Rozmus
3,374,941	A	3/1968	Okress	4,394,239	A	7/1983	Kitzelmann et al.
3,412,530	A	11/1968	Cardiff	4,405,342	A	9/1983	Bergman
3,518,462	A	6/1970	Brown	4,406,671	A	9/1983	Rozmus
3,540,191	A	11/1970	Herman	4,412,850	A	11/1983	Kurata et al.
3,581,470	A	6/1971	Aitkenhead et al.	4,413,225	A	11/1983	Donig et al.
3,638,058	A	1/1972	Fritzius	4,414,603	A	11/1983	Masuda
3,744,216	A	7/1973	Halloran	4,435,190	A	3/1984	Taillet et al.
3,806,763	A	4/1974	Masuda	4,440,552	A	4/1984	Uchiya et al.
3,892,927	A	7/1975	Lindenberg	4,443,234	A	4/1984	Carlsson
3,945,813	A	3/1976	Iinoya et al.	4,445,911	A	5/1984	Lind
3,958,960	A	5/1976	Bakke	4,477,263	A	10/1984	Shaver et al.
3,958,961	A	5/1976	Bakke	4,477,268	A	10/1984	Kalt
3,958,962	A	5/1976	Hayashi	4,481,017	A	11/1984	Furlong
3,981,695	A	9/1976	Fuchs	4,496,375	A	1/1985	Levantine
3,984,215	A	10/1976	Zucker	4,502,002	A	2/1985	Ando
3,988,131	A	10/1976	Kanazawa et al.	4,505,724	A	3/1985	Baab
4,007,024	A	2/1977	Sallee et al.	4,509,958	A	4/1985	Masuda et al.
4,052,177	A	10/1977	Kide	4,514,780	A	4/1985	Brussee et al.
4,056,372	A	11/1977	Hayashi	4,515,982	A	5/1985	Lechtken et al.
4,070,163	A	1/1978	Kolb et al.	4,516,991	A	5/1985	Kawashima
4,074,983	A	2/1978	Bakke	4,521,229	A	6/1985	Baker et al.
4,092,134	A	5/1978	Kikuchi	4,522,634	A	6/1985	Frank
4,097,252	A	6/1978	Kirchhoff et al.	4,534,776	A	8/1985	Mammel et al.
4,102,654	A	7/1978	Pellin	4,536,698	A	8/1985	Shevalenko et al.
4,104,042	A	8/1978	Brozenick	4,544,382	A	10/1985	Taillet et al.
4,110,086	A	8/1978	Schwab et al.	4,555,252	A	11/1985	Eckstein
4,119,415	A	10/1978	Hayashi et al.	4,569,684	A	2/1986	Ibbott
4,126,434	A	11/1978	Keiichi	4,582,961	A	4/1986	Frederiksen
4,138,233	A	2/1979	Masuda	4,587,475	A	5/1986	Finney, Jr. et al.
4,147,522	A	4/1979	Gonas et al.	4,588,423	A	5/1986	Gillingham et al.
4,155,792	A	5/1979	Gelhaar et al.	4,590,042	A	5/1986	Drage
4,171,975	A	10/1979	Kato et al.	4,597,780	A	7/1986	Reif
4,185,971	A	1/1980	Isahaya	4,597,781	A	7/1986	Spector
4,189,308	A	2/1980	Feldman	4,600,411	A	7/1986	Santamaria
4,205,969	A	6/1980	Matsumoto	4,601,733	A	7/1986	Ordines et al.
4,209,306	A	6/1980	Feldman et al.	4,604,174	A	8/1986	Bollinger et al.
4,218,225	A	8/1980	Kirchhoff et al.	4,614,573	A	9/1986	Masuda
4,225,323	A	9/1980	Zarchy et al.	4,623,365	A	11/1986	Bergman
4,227,894	A	10/1980	Proynoff	4,626,261	A	12/1986	Jorgensen
4,231,766	A	11/1980	Spurgin	4,632,135	A	12/1986	Lenting et al.
4,232,355	A	11/1980	Finger et al.	4,632,746	A	12/1986	Bergman
4,244,710	A	1/1981	Burger	4,636,981	A	1/1987	Ogura
4,244,712	A	1/1981	Tongret	4,643,744	A	2/1987	Brooks
4,251,234	A	2/1981	Chang	4,643,745	A	2/1987	Sakakibara et al.
4,253,852	A	3/1981	Adams	4,647,836	A	3/1987	Olsen
4,259,093	A	3/1981	Vlastos et al.	4,650,648	A	3/1987	Beer et al.
4,259,452	A	3/1981	Yukuta et al.	4,656,010	A	4/1987	Leitzke et al.
4,259,707	A	3/1981	Penney	4,657,738	A	4/1987	Kanter et al.
4,264,343	A *	4/1981	Natarajan et al. 96/48	4,659,342	A	4/1987	Lind
4,266,948	A	5/1981	Teague et al.	4,662,903	A	5/1987	Yanagawa
4,282,014	A	8/1981	Winkler et al.	4,666,474	A	5/1987	Cook
4,284,420	A	8/1981	Borysiak	4,668,479	A	5/1987	Manabe et al.
4,289,504	A	9/1981	Scholes	4,670,026	A	6/1987	Hoenig
4,293,319	A	10/1981	Claassen, Jr.	4,673,416	A	6/1987	Sakakibara et al.
4,308,036	A	12/1981	Zahedi et al.	4,674,003	A	6/1987	Zylka
4,315,188	A	2/1982	Cerny et al.	4,680,496	A	7/1987	Letournel et al.
4,318,718	A	3/1982	Utsumi et al.	4,686,370	A	8/1987	Blach
4,338,560	A	7/1982	Lemley	4,689,056	A	8/1987	Noguchi et al.
4,342,571	A	8/1982	Hayashi	4,691,829	A	9/1987	Auer
4,349,359	A	9/1982	Fitch et al.	4,692,174	A	9/1987	Gelfand et al.
				4,693,869	A	9/1987	Pfaff
				4,694,376	A	9/1987	Gesslauer

US 7,291,207 B2

Page 3

4,702,752 A	10/1987	Yanagawa	D332,655 S	1/1993	Lytle et al.
4,713,092 A	12/1987	Kikuchi et al.	5,180,404 A	1/1993	Loreth et al.
4,713,093 A	12/1987	Hansson	5,183,480 A	2/1993	Rateman et al.
4,713,724 A	12/1987	Voelkel	5,196,171 A	3/1993	Peltier
4,715,870 A	12/1987	Masuda et al.	5,198,003 A	3/1993	Haynes
4,725,289 A	2/1988	Quintilian	5,199,257 A	4/1993	Colletta et al.
4,726,812 A	2/1988	Hirth	5,210,678 A	5/1993	Lain et al.
4,726,814 A	2/1988	Weitman	5,215,558 A	6/1993	Moon
4,736,127 A	4/1988	Jacobsen	5,217,504 A	6/1993	Johansson
4,743,275 A	5/1988	Flanagan	5,217,511 A	6/1993	Plaks et al.
4,749,390 A	6/1988	Burnett et al.	5,234,555 A	8/1993	Ibbott
4,750,921 A	6/1988	Sugita et al.	5,248,324 A	9/1993	Hara
4,760,302 A	7/1988	Jacobsen	5,250,267 A	10/1993	Johnson et al.
4,760,303 A	7/1988	Miyake	5,254,155 A	10/1993	Mensi
4,765,802 A	8/1988	Gombos et al.	5,266,004 A	11/1993	Tsumurai et al.
4,771,361 A	9/1988	Varga	5,271,763 A	12/1993	Jang
4,772,297 A	9/1988	Anzai	5,282,891 A	2/1994	Durham
4,779,182 A	10/1988	Mickal et al.	5,290,343 A	3/1994	Morita et al.
4,781,736 A	11/1988	Cheney et al.	5,296,019 A	3/1994	Oakley et al.
4,786,844 A	11/1988	Farrell et al.	5,302,190 A	4/1994	Williams
4,789,801 A	12/1988	Lee	5,308,586 A	5/1994	Fritsche et al.
4,808,200 A	2/1989	Dallhammer et al.	5,315,838 A	5/1994	Thompson
4,811,159 A	3/1989	Foster, Jr.	5,316,741 A	5/1994	Sewell et al.
4,822,381 A	4/1989	Mosley et al.	5,330,559 A	7/1994	Cheney et al.
4,853,005 A	8/1989	Jaisinghani et al.	5,348,571 A	9/1994	Weber
4,869,736 A	9/1989	Ivester et al.	5,376,168 A	12/1994	Inculet
4,892,713 A	1/1990	Newman	5,378,978 A	1/1995	Gallo et al.
4,929,139 A	5/1990	Vorreiter et al.	5,386,839 A	2/1995	Chen
4,940,470 A	7/1990	Jaisinghani et al.	5,395,430 A	3/1995	Lundgren et al.
4,940,894 A	7/1990	Morters	5,401,301 A	3/1995	Schulmerich et al.
4,941,068 A	7/1990	Hofmann	5,401,302 A	3/1995	Schulmerich et al.
4,941,224 A	7/1990	Saeki et al.	5,403,383 A	4/1995	Jaisinghani
4,944,778 A	7/1990	Yanagawa	5,405,434 A	4/1995	Inculet
4,954,320 A	9/1990	Birmingham et al.	5,407,469 A	4/1995	Sun
4,955,991 A	9/1990	Torok et al.	5,407,639 A	4/1995	Watanabe et al.
4,966,666 A	10/1990	Waltonen	5,417,936 A	5/1995	Suzuki et al.
4,967,119 A	10/1990	Torok et al.	5,419,953 A	5/1995	Chapman
4,976,752 A	12/1990	Torok et al.	5,433,772 A	7/1995	Sikora
4,978,372 A	12/1990	Pick	5,435,817 A	7/1995	Davis et al.
D315,598 S	3/1991	Yamamoto et al.	5,435,978 A	7/1995	Yokomi
5,003,774 A	4/1991	Leonard	5,437,713 A	8/1995	Chang
5,006,761 A	4/1991	Torok et al.	5,437,843 A	8/1995	Kuan
5,010,869 A	4/1991	Lee	5,445,798 A	8/1995	Ikeda et al.
5,012,093 A	4/1991	Shimizu	5,466,279 A	11/1995	Hattori et al.
5,012,094 A	4/1991	Hamade	5,468,454 A	11/1995	Kim
5,012,159 A	4/1991	Torok et al.	5,474,599 A	12/1995	Cheney et al.
5,022,979 A	6/1991	Hijikata et al.	5,484,472 A	1/1996	Weinberg
5,024,685 A	6/1991	Torok et al.	5,484,473 A	1/1996	Bontempi
5,030,254 A	7/1991	Heyen et al.	5,492,678 A	2/1996	Ota et al.
5,034,033 A	7/1991	Alsup et al.	5,501,844 A	3/1996	Kasting, Jr. et al.
5,037,456 A	8/1991	Yu	5,503,808 A	4/1996	Garbutt et al.
5,045,095 A	9/1991	You	5,503,809 A	4/1996	Coate et al.
5,053,912 A	10/1991	Loreth et al.	5,505,914 A	4/1996	Tona-Serra
5,059,219 A	10/1991	Plaks et al.	5,508,008 A	4/1996	Wasser
5,061,462 A	10/1991	Suzuki	5,514,345 A	5/1996	Garbutt et al.
5,066,313 A	11/1991	Mallory, Sr.	5,516,493 A	5/1996	Bell et al.
5,072,746 A	12/1991	Kantor	5,518,531 A	5/1996	Joannu
5,076,820 A	12/1991	Gurvitz	5,520,887 A	5/1996	Shimizu et al.
5,077,468 A	12/1991	Hamade	5,525,310 A	6/1996	Decker et al.
5,077,500 A	12/1991	Torok et al.	5,529,613 A	6/1996	Yavnieli
5,100,440 A	3/1992	Stahel et al.	5,529,760 A	6/1996	Burris
RE33,927 E	5/1992	Fuzimura	5,532,798 A	7/1996	Nakagami et al.
D326,514 S	5/1992	Alsup et al.	5,535,089 A	7/1996	Ford et al.
5,118,942 A	6/1992	Hamade	5,536,477 A	7/1996	Cha et al.
5,125,936 A	6/1992	Johansson	5,538,695 A	7/1996	Shinjo et al.
5,136,461 A	8/1992	Zellweger	5,540,761 A	7/1996	Yamamoto
5,137,546 A	8/1992	Steinbacher et al.	5,542,967 A	8/1996	Ponizovsky et al.
5,141,529 A	8/1992	Oakley et al.	5,545,379 A	8/1996	Gray
5,141,715 A	8/1992	Sackinger et al.	5,545,380 A	8/1996	Gray
D329,284 S	9/1992	Patton	5,547,643 A	8/1996	Nomoto et al.
5,147,429 A	9/1992	Bartholomew et al.	5,549,874 A	8/1996	Kamiya et al.
5,154,733 A	10/1992	Fujii et al.	5,554,344 A	9/1996	Duarte
5,158,580 A	10/1992	Chang	5,554,345 A	9/1996	Kitchenman

US 7,291,207 B2

Page 4

5,565,685 A	10/1996	Czako et al.	6,193,852 B1	2/2001	Caracciolo et al.
5,569,368 A	10/1996	Larsky et al.	6,203,600 B1	3/2001	Loreth
5,569,437 A	10/1996	Stiehl et al.	6,212,883 B1	4/2001	Kang
D375,546 S	11/1996	Lee	6,228,149 B1	5/2001	Alenichev et al.
5,571,483 A	11/1996	Pfingstl et al.	6,251,171 B1	6/2001	Marra et al.
5,573,577 A	11/1996	Joannou	6,252,012 B1	6/2001	Egitto et al.
5,573,730 A	11/1996	Gillum	6,270,733 B1	8/2001	Rodden
5,578,112 A	11/1996	Krause	6,277,248 B1	8/2001	Ishioka et al.
5,578,280 A	11/1996	Kazi et al.	6,282,106 B2	8/2001	Grass
5,582,632 A	12/1996	Nohr et al.	D449,097 S	10/2001	Smith et al.
5,587,131 A	12/1996	Malkin et al.	D449,679 S	10/2001	Smith et al.
D377,523 S	1/1997	Marvin et al.	6,296,692 B1	10/2001	Gutmann
5,591,253 A	1/1997	Altman et al.	6,302,944 B1	10/2001	Hoenig
5,591,334 A	1/1997	Shimizu et al.	6,309,514 B1	10/2001	Conrad et al.
5,591,412 A	1/1997	Jones et al.	6,312,507 B1 *	11/2001	Taylor et al. 96/19
5,593,476 A	1/1997	Coppom	6,315,821 B1	11/2001	Pillion et al.
5,601,636 A	2/1997	Glucksmann	6,328,791 B1	12/2001	Pillion et al.
5,603,752 A	2/1997	Hara	6,348,103 B1	2/2002	Ahlborn et al.
5,603,893 A	2/1997	Gundersen et al.	6,350,417 B1	2/2002	Lau et al.
5,614,002 A	3/1997	Chen	6,362,604 B1	3/2002	Cravey
5,624,476 A	4/1997	Eyraud	6,372,097 B1	4/2002	Chen
5,630,866 A	5/1997	Gregg	6,373,723 B1	4/2002	Wallgren et al.
5,630,990 A	5/1997	Conrad et al.	6,379,427 B1	4/2002	Siess
5,637,198 A	6/1997	Breault	6,391,259 B1	5/2002	Malkin et al.
5,637,279 A	6/1997	Besen et al.	6,398,852 B1	6/2002	Loreth
5,641,342 A	6/1997	Smith et al.	6,447,587 B1	9/2002	Pillion et al.
5,641,461 A	6/1997	Ferone	6,451,266 B1	9/2002	Lau et al.
5,647,890 A	7/1997	Yamamoto	6,464,754 B1	10/2002	Ford
5,648,049 A	7/1997	Jones et al.	6,471,753 B1	10/2002	Ahn et al.
5,655,210 A	8/1997	Gregoire et al.	6,494,940 B1	12/2002	Hak
5,656,063 A	8/1997	Hsu	6,497,754 B2	12/2002	Joannou
5,665,147 A	9/1997	Taylor et al.	6,504,308 B1	1/2003	Krichtafovitch et al.
5,667,563 A	9/1997	Silva, Jr.	6,506,238 B1	1/2003	Endo
5,667,564 A	9/1997	Weinberg	6,508,982 B1	1/2003	Shoji
5,667,565 A	9/1997	Gondar	6,544,485 B1 *	4/2003	Taylor 422/186.04
5,667,756 A	9/1997	Ho	6,576,046 B2	6/2003	Pruette et al.
5,669,963 A	9/1997	Horton et al.	6,588,434 B2	7/2003	Taylor et al.
5,678,237 A	10/1997	Powell et al.	6,603,268 B2	8/2003	Lee
5,681,434 A	10/1997	Eastlund	6,613,277 B1	9/2003	Monagan
5,681,533 A	10/1997	Hiromi	6,632,407 B1	10/2003	Lau et al.
5,698,164 A	12/1997	Kishioka et al.	6,635,105 B2	10/2003	Ahlborn et al.
5,702,507 A	12/1997	Wang	6,635,106 B2	10/2003	Katou et al.
D389,567 S	1/1998	Gudefin	6,672,315 B2	1/2004	Taylor et al.
5,766,318 A	6/1998	Loreth et al.	6,680,028 B1	1/2004	Harris
5,779,769 A	7/1998	Jiang	6,709,484 B2	3/2004	Lau et al.
5,785,631 A	7/1998	Heidecke	6,713,026 B2	3/2004	Taylor et al.
5,814,135 A	9/1998	Weinberg	6,735,830 B1	5/2004	Merciel
5,879,435 A	3/1999	Satyapal et al.	6,749,667 B2	6/2004	Reeves et al.
5,893,977 A	4/1999	Pucci	6,753,652 B2	6/2004	Kim
5,911,957 A	6/1999	Khatchatrian et al.	6,761,796 B2	7/2004	Srivastava et al.
5,972,076 A	10/1999	Nichols et al.	6,768,108 B2	7/2004	Hirano et al.
5,975,090 A	11/1999	Taylor et al.	6,768,110 B2	7/2004	Alani
5,980,614 A	11/1999	Loreth et al.	6,768,120 B2	7/2004	Leung et al.
5,993,521 A	11/1999	Loreth et al.	6,768,121 B2	7/2004	Horsky
5,993,738 A	11/1999	Goswami	6,770,878 B2	8/2004	Uhlemann et al.
5,997,619 A	12/1999	Knuth et al.	6,774,359 B1	8/2004	Hirabayashi et al.
6,019,815 A	2/2000	Satyapal et al.	6,777,686 B2	8/2004	Olson et al.
6,042,637 A	3/2000	Weinberg	6,777,699 B1	8/2004	Miley et al.
6,063,168 A	5/2000	Nichols et al.	6,777,882 B2	8/2004	Goldberg et al.
6,086,657 A	7/2000	Freije	6,781,136 B1	8/2004	Kato
6,090,189 A	7/2000	Wikström et al.	6,785,912 B1	9/2004	Julio
6,117,216 A	9/2000	Loreth	6,791,814 B2	9/2004	Adachi et al.
6,118,645 A	9/2000	Partridge	6,794,661 B2	9/2004	Tsukihara et al.
6,126,722 A	10/2000	Mitchell et al.	6,797,339 B2	9/2004	Akizuki et al.
6,126,727 A	10/2000	Lo	6,797,964 B2	9/2004	Yamashita
6,149,717 A	11/2000	Satyapal et al.	6,799,068 B1	9/2004	Hartmann et al.
6,149,815 A	11/2000	Sauter	6,800,862 B2	10/2004	Matsumoto et al.
6,152,146 A	11/2000	Taylor et al.	6,803,585 B2	10/2004	Glukhoy
6,163,098 A	12/2000	Taylor et al.	6,805,916 B2	10/2004	Cadieu
6,176,977 B1 *	1/2001	Taylor et al. 204/176	6,806,035 B1	10/2004	Atireklapvarodom et al.
6,182,461 B1	2/2001	Washburn et al.	6,806,163 B2	10/2004	Wu et al.
6,182,671 B1	2/2001	Taylor et al.	6,806,468 B2	10/2004	Laiko et al.
6,187,271 B1	2/2001	Lee et al.	6,808,606 B2	10/2004	Thomsen et al.

US 7,291,207 B2

Page 5

6,809,310 B2	10/2004	Chen	CN	2153231 Y	12/1993
6,809,312 B1	10/2004	Park et al.	DE	2206057	8/1973
6,809,325 B2	10/2004	Dahl et al.	DE	197 41 621 C 1	6/1999
6,812,647 B2	11/2004	Cornelius	EP	0433152 A1	12/1990
6,815,690 B2	11/2004	Veerasamy et al.	EP	0332624 B1	1/1992
6,818,257 B2	11/2004	Amann et al.	FR	2690509	10/1993
6,818,909 B2	11/2004	Murrell et al.	GB	643363	9/1950
6,819,053 B2	11/2004	Johnson	JP	S51-90077	8/1976
6,863,869 B2	3/2005	Lau	JP	S62-20653	2/1987
6,893,618 B2	5/2005	Kotlyar et al.	JP	S63-164948	10/1988
6,897,617 B2	5/2005	Lee	JP	10137007	5/1998
6,899,745 B2	5/2005	Gatchell et al.	JP	11104223	4/1999
6,908,501 B2	6/2005	Reeves et al.	JP	2000236914	9/2000
6,958,134 B2	10/2005	Taylor et al.	WO	92/05875 A1	4/1992
6,974,560 B2	12/2005	Taylor et al.	WO	96/04703 A1	2/1996
6,984,987 B2	1/2006	Taylor et al.	WO	99/07474 A1	2/1999
7,077,890 B2 *	7/2006	Botvinnik 96/69	WO	00/10713 A1	3/2000
2001/0048906 A1	12/2001	Lau et al.	WO	01/47803 A1	7/2001
2002/0079212 A1	6/2002	Taylor et al.	WO	01/48781 A1	7/2001
2002/0098131 A1	7/2002	Taylor et al.	WO	01/64349 A1	9/2001
2002/0122751 A1	9/2002	Sinaiko et al.	WO	01/85348 A2	11/2001
2002/0122752 A1	9/2002	Taylor et al.	WO	02/20162 A2	3/2002
2002/0127156 A1	9/2002	Taylor	WO	02/20163 A2	3/2002
2002/0134665 A1	9/2002	Taylor et al.	WO	02/30574 A1	4/2002
2002/0144601 A1	10/2002	Palestro et al.	WO	02/32578 A1	4/2002
2002/0146356 A1	10/2002	Sinaiko et al.	WO	02/42003 A1	5/2002
2002/0150520 A1	10/2002	Taylor et al.	WO	02/066167 A1	8/2002
2002/0152890 A1	10/2002	Leiser	WO	03/009944 A1	2/2003
2002/0155041 A1	10/2002	McKinney, Jr. et al.	WO	03/013620	2/2003
2002/0190658 A1	12/2002	Lee	WO	03/013734 AA	2/2003
2002/0195951 A1	12/2002	Lee			
2003/0170150 A1	9/2003	Law et al.			
2003/0206837 A1	11/2003	Taylor et al.			
2004/0033176 A1	2/2004	Lee et al.			
2004/0096376 A1	5/2004	Taylor			
2004/0136863 A1	7/2004	Yates et al.			
2004/0166037 A1	8/2004	Youdell et al.			
2004/0226447 A1	11/2004	Lau et al.			
2004/0234431 A1	11/2004	Taylor et al.			
2004/0251124 A1	12/2004	Lau			
2005/0000793 A1	1/2005	Taylor et al.			
2005/0051028 A1 *	3/2005	Botvinnik 96/88			
2005/0051420 A1 *	3/2005	Botvinnik et al. 204/164			

FOREIGN PATENT DOCUMENTS

CN 2138764 Y 6/1993

OTHER PUBLICATIONS

U.S. Appl. No. 60/306,479, filed Jul. 18, 2001, Taylor.
U.S. Appl. No. 60/341,179, filed Dec. 13, 2001, Taylor et al.
U.S. Appl. No. 60/340,702, filed Dec. 13, 2001, Taylor et al.
U.S. Appl. No. 60/341,377, filed Dec. 13, 2001, Taylor et al.
U.S. Appl. No. 60/341,518, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/340,288, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/341,176, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/340,462, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/340,090, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/341,433, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/341,592, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/341,320, filed Dec. 13, 2001, Taylor.
U.S. Appl. No. 60/391,070, filed Jun. 6, 2002, Reeves.

* cited by examiner




Fig. 1A (PRIOR ART)




Fig. 1B (PRIOR ART)




Fig. 2A





Fig. 2B






Fig. 3B




Fig. 4




Fig. 5




Fig. 6




Fig. 7A





Fig. 7B






Fig. 8B




Fig. 9A





Fig. 9B






Fig. 10B

1

AIR TREATMENT APPARATUS WITH ATTACHABLE GRILL

CLAIM OF PRIORITY

The present application claims priority under 35 U.S.C. 119(e) to now abandoned U.S. Provisional Patent Application Ser. No. 60/590,688, filed Jul. 23, 2004, entitled "Air Conditioner Device With Removable Interstitial Driver Electrodes" which is hereby incorporated herein by reference.

INCORPORATION BY REFERENCE

The following patent applications and patents are incorporated herein by reference:

U.S. patent application Ser. No. 10/074,207, filed Feb. 12, 2002;
 U.S. Pat. No. 6,176,977, issued Jan. 23, 2001;
 U.S. Pat. No. 6,544,485, issued Apr. 8, 2003;
 U.S. patent application Ser. No. 10/074,347, filed Feb. 12, 2002, now U.S. Pat. No. 6,911,186;
 U.S. patent application Ser. No. 10/717,420, filed Nov. 19, 2003;
 U.S. patent application Ser. No. 10/625,401, filed Jul. 23, 2003, now U.S. Pat. No. 6,984,987;
 U.S. Pat. No. 6,350,417 issued May 4, 2000;
 U.S. Pat. No. 6,709,484, issued Mar. 23, 2004;
 U.S. Pat. No. 6,350,417 issued May 4, 2000;
 U.S. Patent Application No. 60/590,735, filed Jul. 23, 2004;
 U.S. Patent Application No. 60/590,960, filed Jul. 23, 2004;
 U.S. Patent Application No. 60/590,445, filed Jul. 23, 2004;
 U.S. patent application Ser. No. 11/003,032, filed Dec. 3, 2004;
 U.S. patent application Ser. No. 11/007,395, filed Dec. 8, 2004;
 U.S. patent application Ser. No. 11/003,894, filed Dec. 3, 2004;
 U.S. patent application Ser. No. 11/003,671, filed Dec. 3, 2004;
 U.S. patent application Ser. No. 11/003,516, filed Dec. 3, 2004;
 U.S. patent application Ser. No. 11/004,397, filed Dec. 3, 2004;
 U.S. patent application Ser. No. 11/003,034, filed Dec. 3, 2004.

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is related to the following commonly-owned co-pending patent applications: U.S. patent application Ser. No. 90/007,276, filed Oct. 29, 2004; U.S. patent application Ser. No. 11/041,926, filed Jan. 21, 2005; U.S. patent application Ser. No. 11/091,243, filed Mar. 28, 2005; U.S. patent application Ser. No. 11/062,057, filed Feb. 18, 2005; U.S. patent application Ser. No. 11/071,779, filed Mar. 3, 2005; U.S. patent application Ser. No. 10/994,869, filed Nov. 22, 2004; U.S. patent application Ser. No. 11/007,556, filed Dec. 8, 2004; U.S. patent application Ser. No. 11/003,894, filed Dec. 3, 2004; U.S. patent application Ser. No. 10/074,209, filed Feb. 12, 2002; U.S. patent application Ser. No. 10/023,460, filed Dec. 13, 2001; U.S. patent application Ser. No. 10/379,966, filed Mar. 5, 2003; U.S. patent appli-

2

cation Ser. No. 10/685,182, filed Oct. 14, 2003; U.S. patent application Ser. No. 10/944,016, filed Sep. 17, 2004; U.S. patent application Ser. No. 10/795,934, filed Mar. 8, 2004; U.S. patent application Ser. No. 10/435,289, filed May 9, 2003; U.S. patent application Ser. No. 11/064,797, filed Feb. 24, 2005; U.S. patent application Ser. No. 11/003,034, filed Dec. 3, 2004; U.S. patent application Ser. No. 11/003,671, filed Dec. 3, 2004; U.S. patent application Ser. No. 11/003,035, filed Dec. 3, 2004; U.S. patent application Ser. No. 11/007,395, filed Dec. 8, 2004; U.S. patent application Ser. No. 10/876,495, filed Jun. 25, 2004; U.S. patent application Ser. No. 10/809,923, filed Mar. 25, 2004; U.S. patent application Ser. No. 11/062,173, filed Feb. 18, 2005; U.S. patent application Ser. No. 11/004,397, filed Dec. 3, 2004; U.S. patent application Ser. No. 10/895,799, filed Jul. 21, 2004; U.S. patent application Ser. No. 10/642,927, filed Aug. 18, 2003; U.S. patent application Ser. No. 11/823,346, filed Apr. 12, 2004; U.S. patent application Ser. No. 10/662,591, filed Sep. 15, 2003; U.S. patent application Ser. No. 11/061,967, filed Feb. 18, 2005; U.S. patent application Ser. No. 11/150,046, filed Jun. 10, 2005; U.S. patent application Ser. No. 11/188,448, filed Jul. 25, 2005; U.S. patent application Ser. No. 11/188,478, filed Jul. 25, 2005; U.S. patent application Ser. No. 11/293,538, filed Dec. 2, 2005; U.S. patent application Ser. No. 11/457,396, filed Jul. 13, 2006; and U.S. patent application Ser. No. 11/464,139, filed Aug. 11, 2006.

FIELD OF THE INVENTION

The present invention is related generally to a device for conditioning air.

BACKGROUND OF THE INVENTION

The use of an electric motor to rotate a fan blade to create an airflow has long been known in the art. Although such fans can produce substantial airflow (e.g., 1,000 ft³/minute or more), substantial electrical power is required to operate the motor, and essentially no conditioning of the flowing air occurs.

It is known to provide such fans with a HEPA-compliant filter element to remove particulate matter larger than perhaps 0.3 μ m. Unfortunately, the resistance to airflow presented by the filter element may require doubling the electric motor size to maintain a desired level of airflow. Further, HEPA-compliant filter elements are expensive, and can represent a substantial portion of the sale price of a HEPA-compliant filter-fan unit. While such filter-fan units can condition the air by removing large particles, particulate matter small enough to pass through the filter element is not removed, including bacteria, for example.

It is also known in the art to produce an airflow using electro-kinetic techniques, whereby electrical power is converted into a flow of air without utilizing mechanically moving components. One such system is described in U.S. Pat. No. 4,789,801 to Lee (1988), depicted herein in simplified form as FIG. 1A, which is hereby incorporated by reference. System 10 includes an array of first ("emitter") electrodes or conductive surfaces 20 that are preferably spaced-apart symmetrically from an array of second ("collector") electrodes or conductive surfaces 30. The positive terminal of a generator such as, for example, pulse generator 40 which outputs a train of high voltage pulses (e.g., 0 to perhaps +5 KV) is coupled to the first array 20, and the negative pulse generator terminal is coupled to the second array 30 in this example.

3

In another particular embodiment shown herein as FIG. 1B, second electrodes 30 are preferably symmetrical and elongated in cross-section. The elongated trailing edges on the second electrodes 30 are symmetrically and elongated in cross-section. The elongated trailing edges on the second electrodes 30 provide increased area upon which particulate matter 60 entrained in the airflow can attach. While the electrostatic techniques disclosed by the '801 patent are advantageous over conventional electric fan-filter units, further increased air conditioning efficiency would be advantageous. One method of increasing air conditioning efficiency is to position driver electrodes between the collector electrodes whereby the driver electrodes aid in driving the particulates toward the collector electrodes.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1A illustrates a plan, cross sectional view, of the electro-kinetic air conditioner system according to the prior art.

FIG. 1B illustrates a plan cross sectional view of the electro-kinetic air conditioner system according to the prior art.

FIG. 2A illustrates a perspective view of the device in accordance with one embodiment of the present invention.

FIG. 2B illustrates a perspective view of the device in FIG. 2A with the removable collector electrode in accordance with one embodiment of the present invention.

FIG. 3A illustrates an electrical block diagram of the high voltage power source of one embodiment of the present invention.

FIG. 3B illustrates an electrical block diagram of the high voltage power source in accordance with one embodiment of the present invention.

FIG. 4 illustrates a perspective view of the electrode assembly according to one embodiment of the present invention.

FIG. 5 illustrates a plan view of the electrode assembly according to one embodiment of the present invention.

FIG. 6 illustrates a perspective view of the air conditioner system according to one embodiment of the present invention.

FIG. 7A illustrates an exploded view of the air conditioner system in accordance with one embodiment of the present invention.

FIG. 7B illustrates a perspective cutaway view of the air conditioner system in accordance with one embodiment of the present invention.

FIG. 8A illustrates a perspective view of the front exhaust grill with the driver electrodes coupled thereto in accordance with one embodiment of the present invention.

FIG. 8B illustrates a detailed view of the embodiment shown in FIG. 8A in accordance with one embodiment of the present invention.

FIG. 9A illustrates a perspective view of the air conditioner system with an electrode assembly positioned therein.

FIG. 9B illustrates a perspective view of the air conditioner system with an electrode assembly partially removed in accordance with one embodiment of the present invention.

FIG. 10A illustrates a perspective view of an electrode assembly in accordance with one embodiment of the present invention.

FIG. 10B illustrates an exploded view of an electrode assembly in accordance with one embodiment of the present invention.

4

DETAILED DESCRIPTION OF THE PRESENT INVENTION

Embodiments of the present invention are directed to method and apparatus for moving air preferably using an air conditioning system therein, with or without a fan, whereby the system preferably includes at least one emitter electrode, at least one collector electrode, at least one driver electrode disposed adjacent to the collector electrode, and at least one trailing electrode positioned downstream of the collector electrode. The collector electrode and the driver electrode are removable from the device. In one embodiment, the driver electrodes are removable from the device and/or the collector electrode. The ability to remove the collector electrode as well as the driver electrode allows for easy cleaning of the electrodes. In one embodiment, the present device includes a removable exhaust grill upon which the driver electrode and trailing electrode are coupled to. The removable grill allows the user to easily clean the driver electrode without having to remove the collector electrode.

One aspect of the present invention is directed to an air-conditioning device which comprises a housing that has an inlet and an outlet. The present invention includes an ion generator that is located in the housing and is configured to at least create ions in a flow of air. Also, the invention includes a driver electrode that is located proximal to the outlet, wherein the driver electrode is removable from the housing.

Another aspect of the present invention is directed to an air-conditioning device which comprises a housing with a removable grill. The present invention includes an ion generator which is located in the housing; and a driver electrode that is located adjacent to a collector electrode of the ion generator, wherein the driver electrode is coupled to the removable grill.

Another aspect of the present invention is directed to an air-conditioning device which comprises a housing which has an upper portion with a removable grill. The present invention includes an emitter electrode located in the housing as well as a collector electrode located in the housing, wherein the collector electrode is removable through the upper portion of the housing. The present invention includes a high voltage source that is operatively connected to at least one of the emitter electrode and the collector electrode. The present invention includes a driver electrode that is preferably coupled to the removable grill, wherein the driver electrode is removable from the housing.

Another aspect of the present invention is directed to an air-conditioning device which comprises a housing, an emitter electrode that is located in the housing, and a collector electrode located in the housing, wherein the collector electrode is removable from the housing. The present invention includes a high voltage source that is adapted to provide a voltage differential between the emitter electrode and the collector electrode. The present invention includes a driver electrode that is preferably removable from the housing with the collector electrode, wherein the driver electrode is removable from the collector electrode when the collector electrode is removed from the housing.

In yet another aspect of the present invention, an air-conditioning device which comprises a housing having an inlet grill and an outlet grill. The present invention includes at least one emitter electrode positioned within the housing proximal to the inlet grill. The present invention includes at least two collector electrodes, each having a leading portion and a trailing portion, wherein the collector electrodes are positioned proximal to the outlet grill. The present invention

5

includes a high voltage source that is adapted to provide a voltage differential between the at least one emitter electrode and the collector electrodes. The present invention includes at least one removable driver electrode that is positioned between the at least two second electrodes proximal to the trailing portions.

Another aspect of the present invention is directed to a method of providing an air-conditioning device which comprises providing a housing; positioning an emitter electrode in the housing; and positioning a collector electrode downstream of the emitter electrode. The present method includes coupling a high voltage source that is adapted to provide a voltage differential between the emitter electrode and the collector electrode and positioning a removable driver electrode adjacent to the collector electrode in the housing.

Another aspect of the present invention includes a method of removing an electrode assembly for cleaning. The electrode assembly is positioned within an elongated housing of an air-conditioning device, wherein the housing has an upper portion and a grill that is configured to be selectively removable from a side of the housing. The electrode assembly includes an emitter electrode which is spaced from the collector electrodes. The electrode assembly includes a driver electrode positioned between the collector electrodes, wherein the emitter electrode and the collector electrodes are electrically coupled to a high voltage source. The method comprises lifting the electrode assembly from the housing through the upper portion, wherein the collector electrodes are at least partially exposed. The method further comprises removing the driver electrode from the lifted electrodes assembly. The method further alternatively comprises removing the grill from the side of the housing, wherein the driver electrode is at least partially exposed and is capable of being removably secured to an interior surface of the grill.

Another aspect of the present invention is directed to a method of removing an electrode assembly which includes collector and driver electrodes for cleaning. The electrode assembly is positioned within a housing of an air-conditioning device, wherein the housing has an upper portion. The method comprising the step of lifting the electrode assembly from the housing through the upper portion, wherein the collector electrodes and the driver electrodes are accessible.

Another aspect of the present invention is directed to a method of removing an electrode assembly which includes collector and driver electrodes for cleaning. The electrode assembly is positioned within a housing of an air-conditioning device, wherein the housing has an upper portion. The method comprises the step of lifting the electrode assembly from the housing through the upper portion. The method also includes the step of removing the driver electrode from the lifted electrode assembly.

Another aspect of the present invention is directed to a method of cleaning a driver electrode that is positioned within an elongated housing of an air-conditioning device which has a grill that is removable from a side of the housing. The method comprises removing the grill from the side of the housing, wherein the driver electrode is at least partially exposed.

FIGS. 2A and 2B illustrate one embodiment of the air conditioner system 100 whose housing 102 includes rear-located intake vents with vent grills or louvers 104, front-located exhaust vents with vent grills or louvers 106, and a base pedestal 108. The system 100 includes at least one emitter electrode 232 and at least one collector electrode 242, which is preferably removable as discussed below. The front and rear grills 104, 106 preferably include several fins, whereby each fin is a thin ridge spaced-apart from the next

6

fin so that each fin creates minimal resistance as air flows through the housing 102. In one embodiment, the fins are arranged vertically and are directed along the elongated vertical upstanding housing 102 of the unit 100 (FIG. 6). Alternatively, as shown in FIG. 2A and 2B the fins are perpendicular to the electrodes 232, 242 and are configured horizontally. The inlet and outlet fins are aligned to give the unit a “see through” appearance. Thus, a user can “see through” the unit 100 from the inlet to the outlet or vice versa. The user will see no moving parts within the housing, but just a quiet unit that cleans the air passing therethrough. Other orientations of fins and electrodes are contemplated in other embodiments, such as a configuration in which the user is unable to see through the unit 100, whereby the unit 100 contains a germicidal lamp 290 (FIG. 3A) therein.

The unit 100 is energized by activating switch S1 on the top surface of the housing 102, whereby high voltage or high potential output by the voltage generator 170 produces ions at the emitter electrode 232 which are attracted to the collector electrodes 242. The ions move from an “IN” to an “OUT” direction from the emitter electrodes 232 to the collector electrodes 242 and are carried along with air molecules. In one embodiment, the device 100 electrokinetically produces an outflow of ionized air. In another embodiment, the device 100 is an electro-static precipitator, whereby the device 100 produces ions in an airflow created by a fan or other device. The “IN” notation in FIG. 2A denotes the intake of ambient air with particulate matter 60 through the inlet vents. The “OUT” notation in FIG. 2A denotes the outflow of cleaned air through the outlet vent substantially devoid of the particulate matter 60. In the process of generating the ionized airflow, appropriate amounts of ozone (O₃) are beneficially produced. It is alternatively desired to provide the inner surface of the housing 102 with a shield to reduce detectable electromagnetic radiation. For example, a metal shield (not shown) is disposed within the housing 102, or portions of the interior of the housing 102 are alternatively coated with a metallic paint to reduce such radiation.

FIG. 3A illustrates an electrical circuit diagram for the system 100, according to one embodiment of the present invention. The system 100 has an electrical power cord that plugs into a common electrical wall socket that provides a nominal 110 VAC. An electromagnetic interference (EMI) filter 110 is placed across the incoming nominal 110 VAC line to reduce and/or eliminate high frequencies generated by the various circuits within the system 100, such as the electronic ballast 112. In one embodiment, the electronic ballast 112 is electrically connected to a germicidal lamp 290 (e.g. an ultraviolet lamp) to regulate, or control, the flow of current through the lamp 290. A switch 218 is used to turn the lamp 290 on or off. The EMI Filter 110 is well known in the art and does not require a further description. In another embodiment, the system 100 does not include the germicidal lamp 290, whereby the circuit diagram shown in FIG. 3A would not include the electronic ballast 112, the germicidal lamp 290, nor the switch 218 used to operate the germicidal lamp 290.

The EMI filter 110 is coupled to a DC power supply 114. The DC power supply 114 is coupled to the first HVS 170 as well as the second high voltage power source 172. The high voltage power source can also be referred to as a pulse generator. The DC power supply 114 is also coupled to the micro-controller unit (MCU) 130. The MCU 130 can be, for example, a Motorola 68HC908 series micro-controller, available from Motorola. Alternatively, any other type of MCU is contemplated. The MCU 130 can receive a signal

from the switch **S1** as well as a boost signal from the boost button **216**. The MCU **130** also includes an indicator light **219** which specifies when the electrode assembly is ready to be cleaned.

The DC Power Supply **114** is designed to receive the incoming nominal 110 VAC and to output a first DC voltage (e.g., 160 VDC) to the first HVS **170**. The DC Power Supply **114** voltage (e.g., 160 VDC) is also stepped down to a second DC voltage (e.g., 12 VDC) for powering the micro-controller unit (MCU) **130**, the HVS **172**, and other internal logic of the system **100**. The voltage is stepped down through a resistor network, transformer or other component.

As shown in FIG. 3A, the first HVS **170** is coupled to the first electrode set **230** and the second electrode set **240** to provide a potential difference between the electrode sets. In one embodiment, the first HVS **170** is electrically coupled to the driver electrode **246**, as described above. In addition, the first HVS **170** is coupled to the MCU **130**, whereby the MCU receives arc sensing signals **128** from the first HVS **170** and provides low voltage pulses **120** to the first HVS **170**. Also shown in FIG. 3A is the second HVS **172** which provides a voltage to the trailing electrodes **222**. In addition, the second HVS **172** is coupled to the MCU **130**, whereby the MCU receives arc sensing signals **128** from the second HVS **172** and provides low voltage pulses **120** to the second HVS **172**.

In accordance with one embodiment of the present invention, the MCU **130** monitors the stepped down voltage (e.g., about 12 VDC), which is referred to as the AC voltage sense signal **132** in FIG. 3A, to determine if the AC line voltage is above or below the nominal 110 VAC, and to sense changes in the AC line voltage. For example, if a nominal 110 VAC increases by 10% to 121 VAC, then the stepped down DC voltage will also increase by 10%. The MCU **130** can sense this increase and then reduce the pulse width, duty cycle and/or frequency of the low voltage pulses to maintain the output power (provided to the HVS **170**) to be the same as when the line voltage is at 110 VAC. Conversely, when the line voltage drops, the MCU **130** can sense this decrease and appropriately increase the pulse width, duty cycle and/or frequency of the low voltage pulses to maintain a constant output power. Such voltage adjustment features of the present invention also enable the same system **100** to be used in different countries that have different nominal voltages than in the United States (e.g., in Japan the nominal AC voltage is 100 VAC).

FIG. 3B illustrates a schematic block diagram of the high voltage power supply in accordance with one embodiment of the present invention. For the present description, the first and second HVSs **170**, **172** include the same or similar components as that shown in FIG. 3B. However, it is apparent to one skilled in the art that the first and second HVSs **170**, **172** are alternatively comprised of different components from each other as well as those shown in FIG. 3B.

In the embodiment shown in FIG. 3B, the HVSs **170**, **172** include an electronic switch **126**, a step-up transformer **116** and a voltage multiplier **118**. The primary side of the step-up transformer **116** receives the DC voltage from the DC power supply **114**. For the first HVS **170**, the DC voltage received from the DC power supply **114** is approximately 160 Vdc. For the second HVS **172**, the DC voltage received from the DC power supply **114** is approximately 12 Vdc. An electronic switch **126** receives low voltage pulses **120** (of perhaps 20-25 KHz frequency) from the MCU **130**. Such a switch is shown as an insulated gate bipolar transistor (IGBT) **126**. The IGBT **126**, or other appropriate switch,

couples the low voltage pulses **120** from the MCU **130** to the input winding of the step-up transformer **116**. The secondary winding of the transformer **116** is coupled to the voltage multiplier **118**, which outputs the high voltage pulses to the electrode(s). For the first HVS **170**, the electrode(s) are the emitter and collector electrode sets **230** and **240**. For the second HVS **172**, the electrode(s) are the trailing electrodes **222**. In general, the IGBT **126** operates as an electronic on/off switch. Such a transistor is well known in the art and does not require a further description.

When driven, the first and second HVSs **170**, **172** receive the low input DC voltage from the DC power supply **114** and the low voltage pulses from the MCU **130** and generate high voltage pulses of preferably at least 5 KV peak-to-peak with a repetition rate of about 20 to 25 KHz. The voltage multiplier **118** in the first HVS **170** outputs between 5 to 9 KV to the first set of electrodes **230** and between -6 to -18 KV to the second set of electrodes **240**. In the preferred embodiment, the emitter electrodes **232** receive approximately 5 to 6 KV whereas the collector electrodes **242** receive approximately -9 to -10 KV. The voltage multiplier **118** in the second HVS **172** outputs approximately -12 KV to the trailing electrodes **222**. In one embodiment, the driver electrodes **246** are preferably connected to ground. It is within the scope of the present invention for the voltage multiplier **118** to produce greater or smaller voltages. The high voltage pulses preferably have a duty cycle of about 10%-15%, but may have other duty cycles, including a 100% duty cycle.

The MCU **130** is coupled to a control dial **S1**, as discussed above, which can be set to a LOW, MEDIUM or HIGH airflow setting as shown in FIG. 3A. The MCU **130** controls the amplitude, pulse width, duty cycle and/or frequency of the low voltage pulse signal to control the airflow output of the system **100**, based on the setting of the control dial **S1**. To increase the airflow output, the MCU **130** can be set to increase the amplitude, pulse width, frequency and/or duty cycle. Conversely, to decrease the airflow output rate, the MCU **130** is able to reduce the amplitude, pulse width, frequency and/or duty cycle. In accordance with one embodiment, the low voltage pulse signal **120** has a fixed pulse width, frequency and duty cycle for the LOW setting, another fixed pulse width, frequency and duty cycle for the MEDIUM setting, and a further fixed pulse width, frequency and duty cycle for the HIGH setting.

In accordance with one embodiment of the present invention, the low voltage pulse signal **120** modulates between a predetermined duration of a "high" airflow signal and a "low" airflow signal. It is preferred that the low voltage signal modulates between a predetermined amount of time when the airflow is to be at the greater "high" flow rate, followed by another predetermined amount of time in which the airflow is to be at the lesser "low" flow rate. This is preferably executed by adjusting the voltages provided by the first HVS to the first and second sets of electrodes for the greater flow rate period and the lesser flow rate period. This produces an acceptable airflow output while limiting the ozone production to acceptable levels, regardless of whether the control dial **S1** is set to HIGH, MEDIUM or LOW. For example, the "high" airflow signal can have a pulse width of 5 microseconds and a period of 40 microseconds (i.e., a 12.5% duty cycle), and the "low" airflow signal can have a pulse width of 4 microseconds and a period of 40 microseconds (i.e., a 10% duty cycle).

In general, the voltage difference between the first set **230** and the second set **240** is proportional to the actual airflow output rate of the system **100**. Thus, the greater voltage

differential is created between the first and second set electrodes **230**, **240** by the “high” airflow signal, whereas the lesser voltage differential is created between the first and second set electrodes **230**, **240** by the “low” airflow signal. In one embodiment, the airflow signal causes the voltage multiplier **118** to provide between 5 and 9 KV to the first set electrodes **230** and between -9 and -10 KV to the second set electrodes **240**. For example, the “high” airflow signal causes the voltage multiplier **118** to provide 5.9 KV to the first set electrodes **230** and -9.8 KV to the second set electrodes **240**. In the example, the “low” airflow signal causes the voltage multiplier **118** to provide 5.3 KV to the first set electrodes **230** and -9.5 KV to the second set electrodes **240**. It is within the scope of the present invention for the MCU **130** and the first HVS **170** to produce voltage potential differentials between the first and second sets electrodes **230** and **240** other than the values provided above and is in no way limited by the values specified.

In accordance with the preferred embodiment of the present invention, when the control dial **S1** is set to HIGH, the electrical signal output from the MCU **130** will continuously drive the first HVS **170** and the airflow, whereby the electrical signal output modulates between the “high” and “low” airflow signals stated above (e.g. 2 seconds “high” and 10 seconds “low”). When the control dial **S1** is set to MEDIUM, the electrical signal output from the MCU **130** will cyclically drive the first HVS **170** (i.e. airflow is “On”) for a predetermined amount of time (e.g., 20 seconds), and then drop to a zero or a lower voltage for a further predetermined amount of time (e.g., a further 20 seconds). It is to be noted that the cyclical drive when the airflow is “On” is preferably modulated between the “high” and “low” airflow signals (e.g. 2 seconds “high” and 10 seconds “low”), as stated above. When the control dial **S1** is set to LOW, the signal from the MCU **130** will cyclically drive the first HVS **170** (i.e. airflow is “On”) for a predetermined amount of time (e.g., 20 seconds), and then drop to a zero or a lower voltage for a longer time period (e.g., 80 seconds). Again, it is to be noted that the cyclical drive when the airflow is “On” is preferably modulated between the “high” and “low” airflow signals (e.g. 2 seconds “high” and 10 seconds “low”), as stated above. It is within the scope and spirit of the present invention the HIGH, MEDIUM, and LOW settings will drive the first HVS **170** for longer or shorter periods of time. It is also contemplated that the cyclic drive between “high” and “low” airflow signals are durations and voltages other than that described herein.

Cyclically driving airflow through the system **100** for a period of time, followed by little or no airflow for another period of time (i.e. MEDIUM and LOW settings) allows the overall airflow rate through the system **100** to be slower than when the dial **S1** is set to HIGH. In addition, cyclical driving reduces the amount of ozone emitted by the system since little or no ions are produced during the period in which lesser or no airflow is being output by the system. Further, the duration in which little or no airflow is driven through the system **100** provides the air already inside the system a longer dwell time, thereby increasing particle collection efficiency. In one embodiment, the long dwell time allows air to be exposed to a germicidal lamp, if present.

Regarding the second HVS **172**, approximately 12 volts DC is applied to the second HVS **172** from the DC Power Supply **114**. The second HVS **172** provides a negative charge (e.g. -12 KV) to one or more trailing electrodes **222** in one embodiment. However, it is contemplated that the second HVS **172** provides a voltage in the range of, and

including, -10 KV to -60 KV in other embodiments. In one embodiment, other voltages produced by the second HVS **172** are contemplated.

In one embodiment, the second HVS **172** is controllable independently from the first HVS **170** (as for example by the boost button **216**) to allow the user to variably increase or decrease the amount of negative ions output by the trailing electrodes **222** without correspondingly increasing or decreasing the amount of voltage provided to the first and second set of electrodes **230**, **240**. The second HVS **172** thus provides freedom to operate the trailing electrodes **222** independently of the remainder of the electrode assembly **220** to reduce static electricity, eliminate odors and the like. In addition, the second HVS **172** allows the trailing electrodes **222** to operate at a different duty cycle, amplitude, pulse width, and/or frequency than the electrode sets **230** and **240**. In one embodiment, the user is able to vary the voltage supplied by the second HVS **172** to the trailing electrodes **222** at any time by depressing the button **216**. In one embodiment, the user is able to turn on or turn off the second HVS **172**, and thus the trailing electrodes **222**, without affecting operation of the electrode assembly **220** and/or the germicidal lamp **290**. It should be noted that the second HVS **172** can also be used to control electrical components other than the trailing electrodes **222** (e.g. driver electrodes and germicidal lamp).

As mentioned above, the system **100** includes a boost button **216**. In one embodiment, the trailing electrodes **222** as well as the electrode sets **230**, **240** are controlled by the boost signal from the boost button **216** input into the MCU **130**. In one embodiment, as mentioned above, the boost button **216** cycles through a set of operating settings upon the boost button **216** being depressed. In the example embodiment discussed below, the system **100** includes three operating settings. However, any number of operating settings are contemplated within the scope of the invention.

The following discussion presents methods of operation of the boost button **216** which are variations of the methods discussed above. In particular, the system **100** will operate in a first boost setting when the boost button **216** is pressed once. In the first boost setting, the MCU **130** drives the first HVS **170** as if the control dial **S1** was set to the HIGH setting for a predetermined amount of time (e.g., 6 minutes), even if the control dial **S1** is set to LOW or MEDIUM (in effect overriding the setting specified by the dial **S1**). The predetermined time period may be longer or shorter than 6 minutes. For example, the predetermined period can also preferably be 20 minutes if a higher cleaning setting for a longer period of time is desired. This will cause the system **100** to run at a maximum airflow rate for the predetermined boost time period. In one embodiment, the low voltage signal modulates between the “high” airflow signal and the “low” airflow signal for predetermined amount of times and voltages, as stated above, when operating in the first boost setting. In another embodiment, the low voltage signal does not modulate between the “high” and “low” airflow signals.

In the first boost setting, the MCU **130** will also operate the second HVS **172** to operate the trailing electrode **222** to generate ions, preferably negative, into the airflow. In one embodiment, the trailing electrode **222** will preferably repeatedly emit ions for one second and then terminate for five seconds for the entire predetermined boost time period. The increased amounts of ozone from the boost level will further reduce odors in the entering airflow as well as increase the particle capture rate of the system **100**. At the end of the predetermined boost period, the system **100** will return to the airflow rate previously selected by the control

11

dial S1. It should be noted that the on/off cycle at which the trailing electrodes 222 operate are not limited to the cycles and periods described above.

In the example, once the boost button 216 is pressed again, the system 100 operates in the second setting, which is an increased ion generation or “feel good” mode. In the second setting, the MCU 130 drives the first HVS 170 as if the control dial S1 was set to the LOW setting, even if the control dial S1 is set to HIGH or MEDIUM (in effect overriding the setting specified by the dial S1). Thus, the airflow is not continuous, but “On” and then at a lesser or zero airflow for a predetermined amount of time (e.g. 6 minutes). In addition, the MCU 130 will operate the second HVS 172 to operate the trailing electrode 222 to generate negative ions into the airflow. In one embodiment, the trailing electrode 222 will repeatedly emit ions for one second and then terminate for five seconds for the predetermined amount of time. It should be noted that the on/off cycle at which the trailing electrodes 222 operate are not limited to the cycles and periods described above.

In the example, upon the boost button 216 being pressed again, the MCU 130 will operate the system 100 in a third operating setting, which is a normal operating mode. In the third setting, the MCU 130 drives the first HVS 170 depending on the which setting the control dial S1 is set to (e.g. HIGH, MEDIUM or LOW). In addition, the MCU 130 will operate the second HVS 172 to operate the trailing electrode 222 to generate ions, preferably negative, into the airflow at a predetermined interval. In one embodiment, the trailing electrode 222 will repeatedly emit ions for one second and then terminate for nine seconds. In another embodiment, the trailing electrode 222 does not operate at all in this mode. The system 100 will continue to operate in the third setting by default until the boost button 216 is pressed. It should be noted that the on/off cycle at which the trailing electrodes 222 operate are not limited to the cycles and periods described above.

In one embodiment, the present system 100 operates in an automatic boost mode upon the system 100 being initially plugged into the wall and/or initially being turned on after being off for a predetermined amount of time. In particular, upon the system 100 being turned on, the MCU 130 automatically drives the first HVS 170 as if the control dial S1 was set to the HIGH setting for a predetermined amount of time, as discussed above, even if the control dial S1 is set to LOW or MEDIUM, thereby causing the system 100 to run at a maximum airflow rate for the amount of time. In addition, the MCU 130 automatically operates the second HVS 172 to operate the trailing electrode 222 at a maximum ion emitting rate to generate ions, preferably negative, into the airflow for the same amount of time. This configuration allows the system 100 to effectively clean stale, pungent, and/or polluted air in a room which the system 100 has not been continuously operating in. This feature improves the air quality at a faster rate while emitting negative “feel good” ions to quickly eliminate any odor in the room. Once the system 100 has been operating in the first setting boost mode, the system 100 automatically adjusts the airflow rate and ion emitting rate to the third setting (i.e. normal operating mode). For example, in this initial plug-in or initial turn-on mode, the system can operate in the high setting for 20 minutes to enhance the removal of particulates and to more rapidly clean the air as well as deodorize the room.

In addition, the system 100 will include an indicator light which informs the user what mode the system 100 is operating in when the boost button 216 is depressed. In one embodiment, the indicator light is the same as the cleaning

12

indicator light 219 discussed above. In another embodiment, the indicator light is a separate light from the indicator light 219. For example only, the indicator light will emit a blue light when the system 100 operates in the first setting. In addition, the indicator light will emit a green light when the system 100 operates in the second setting. In the example, the indicator light will not emit a light when the system 100 is operating in the third setting.

The MCU 130 provides various timing and maintenance features in one embodiment. For example, the MCU 130 can provide a cleaning reminder feature (e.g., a 2 week timing feature) that provides a reminder to clean the system 100 (e.g., by causing indicator light 219 to turn on amber, and/or by triggering an audible alarm that produces a buzzing or beeping noise). The MCU 130 can also provide arc sensing, suppression and indicator features, as well as the ability to shut down the first HVS 170 in the case of continued arcing. Details regarding arc sensing, suppression and indicator features are described in U.S. patent application Ser. No. 10/625,401 which is incorporated by reference above.

FIG. 4 illustrates a perspective view of one embodiment of the electrode assembly 220 in accordance with the present invention. As shown in FIG. 4, the electrode assembly 220 comprises a first set 230 of at least one emitter electrode 232, and further comprises a second set 240 of at least one collector electrode 242. It is preferred that the number N1 of emitter electrodes 232 in the first set 230 differ by one relative to the number N2 of collector electrodes 242 in the second set 240. Preferably, the system includes a greater number of collector electrodes 242 than emitter electrodes 232. However, if desired, additional emitter electrodes 232 are alternatively positioned at the outer ends of set 230 such that $N1 > N2$, e.g., five emitter electrodes 232 compared to four collector electrodes 242. Alternatively, instead of multiple electrodes, single electrodes or single conductive surfaces are substituted.

The material(s) of the electrodes 232 and 242 should conduct electricity and be resistant to the corrosive effects from the application of high voltage, but yet be strong and durable enough to be cleaned periodically. In one embodiment, the emitter electrodes 232 are fabricated from tungsten. Tungsten is sufficiently robust in order to withstand cleaning, has a high melting point to retard breakdown due to ionization, and has a rough exterior surface that promotes efficient ionization. The collector electrodes 242 preferably have a highly polished exterior surface to minimize unwanted point-to-point radiation. As such, the collector electrodes 242 are fabricated from stainless steel and/or brass, among other appropriate materials. The polished surface of electrodes 232 also promotes ease of electrode cleaning. The materials and construction of the electrodes 232 and 242, allow the electrodes 232, 242 to be light weight, easy to fabricate, and lend themselves to mass production. Further, electrodes 232 and 242 described herein promote more efficient generation of ionized air, and appropriate amounts of ozone.

As shown in FIG. 4, the electrode assembly 220 is electrically connected to the high voltage source unit, such as a high voltage pulse generator 170. In one embodiment, the positive output terminal of the high voltage source 170 is coupled to the emitter electrodes 232, and the negative output terminal of high voltage source 170 is coupled to the collector electrodes 242 as shown in FIG. 4. This coupling polarity has been found to work well and minimizes unwanted audible electrode vibration or hum. However, while generation of positive ions is conducive to a relatively silent airflow, from a health standpoint it is desired that the

13

output airflow be richer in negative ions than positive ions. It is noted that in some embodiments, one port (preferably the negative port) of the high voltage pulse generator 170 can in fact be the ambient air. Thus, the collector electrodes 242 need not be connected to the high voltage pulse generator 170 using a wire. Nonetheless, there will be an “effective connection” between the collector electrodes 242 and one output port of the high voltage pulse generator 170, in this instance, via ambient air. Alternatively the negative output terminal of unit 170 is connected to the emitter electrodes 232 and the positive output terminal is connected to the collector electrodes 242.

When voltage or pulses from the high voltage source 170 are generated across the emitter and collector electrodes 232, 242, a plasma-like field is created surrounding the emitter electrodes 232. This electric field ionizes the ambient air between the emitter and the collector electrodes 232, 242 and establishes an “OUT” airflow that moves towards the collector electrodes 242. Ozone and ions are generated simultaneously by the emitter electrodes 232 from the voltage potential provided by the high voltage source 170. Ozone generation can be increased or decreased by increasing or decreasing the voltage potential at the emitter electrodes 232. Coupling an opposite polarity potential to the collector electrodes 242 accelerates the motion of ions generated at the emitter electrodes 232, thereby producing ions. Molecules as well as particulates in the air thus become ionized with the charge emitted by the emitter electrodes 232 as they pass by the electrodes 232. As the ions and ionized particulates 60 move toward or along the collector electrodes 242, the opposite polarity of the collector electrodes 242 causes the ionized particles 60 to be attracted and thereby move toward the collector electrodes 242. Therefore, the collector electrodes 242 collect the ionized particulates 60 in the air, thereby allowing the device 100 to output cleaner, fresher air.

FIG. 5 illustrates a plan view schematic of one embodiment of the electrode assembly 220. Each collector electrode 242 in the embodiment shown in FIG. 5 includes a nose 243, two parallel trailing sides 244 and an end 241 opposite the nose 243. In addition, the electrode assembly 220 includes a set of driver electrodes 246. The driver electrodes 246 include two sides which are parallel to each other, as well as a front end and a rear end. In another embodiment, the driver electrode is a wire or a series of wires configured in a line. Although two driver electrodes 246 are shown, it is apparent that any number of driver electrodes, including only one, is contemplated within the scope of the present invention.

In the embodiment shown in FIG. 5, the driver electrodes 246 are located midway, interstitially between the collector electrodes 242. It is preferred that the driver electrodes 246 are positioned proximal to the trailing end 241 of the collector electrodes 242, although not necessarily. In one embodiment, the driver electrodes 246 are electrically connected to the positive terminal of the high voltage source 170, as shown in FIG. 5. In another embodiment, the driver electrodes 246 are electrically connected to the emitter electrodes 232. Alternatively, the driver electrodes 246 have a floating potential or are alternatively grounded. Ionized particles traveling toward the driver electrodes 246 are preferably repelled by the driver electrodes 246 towards the collector electrodes 242, especially in the embodiment in which the driver electrodes 246 are positively charged.

As shown in FIG. 5, each insulated driver electrode 246 includes an underlying electrically conductive electrode 253 that is covered by a dielectric material 254. In accordance with one embodiment of the present invention, the electri-

14

cally conductive electrode 253 is located on a printed circuit board (PCB) covered by one or more additional layers of insulated material 254. Exemplary insulated PCBs are generally commercially available and may be found from a variety of sources, including for example Electronic Service and Design Corp., of Harrisburg, Pa. Alternatively, the dielectric material 254 could be heat shrink tubing wherein during manufacture, heat shrink tubing is placed over the conductive electrodes 253 and then heated, which causes the tubing to shrink to the shape of the conductive electrodes 253. An exemplary heat shrinkable tubing is type FP-301 flexible polyolefin tubing available from 3M of St. Paul, Minn.

Alternatively, the dielectric material 254 maybe an insulating varnish, lacquer or resin. For example, a varnish, after being applied to the surface of a conductive electrode, dries and forms an insulating coat or film, a few mils (thousands of an inch) in thickness, covering the electrodes 253. The dielectric strength of the varnish or lacquer can be, for example, above 1000 V/mil (Volts per thousands of an inch). Such insulating varnishes, lacquers and resins are commercially available from various sources, such as from John C. Dolph Company of Monmouth Junction, N.J., and Ranbar Electrical Materials Inc. of Manor, Pa.

Other possible dielectric materials that can be used to insulate the driver electrodes 246 include ceramic or porcelain enamel or fiberglass. These are just a few examples of dielectric materials 254 that can be used to insulate the driver electrodes 246. It is within the spirit and scope of the present invention that other insulating dielectric materials 254 can be used to insulate the driver electrodes 246. In one embodiment, the driver electrodes 246 are coated with an ozone reducing catalyst. It should be appreciated that other electrodes may also be coated with an ozone reducing catalyst.

As shown in FIG. 5, the electrode assembly 220 preferably includes a set of at least one trailing electrode 222 positioned downstream of the collector electrodes 242. In the embodiment shown in FIG. 5, three trailing electrodes 222 are positioned directly downstream and in-line with the collector electrodes 242. In another embodiment, the trailing electrodes 222 are positioned adjacent to the collector electrodes 242. In another embodiment, the trailing electrodes 222 are positioned adjacent to the driver electrodes 246. The trailing electrodes 222 are preferably electrically connected to the negative terminal of the high voltage source 170, whereby the trailing electrodes 222 promote additional negative ions into the air exiting the unit 100. The trailing electrodes 222 are configured to be wire shaped and extend substantially along the length of the electrode assembly 220. The wire shaped trailing electrodes 222 are advantageous, because negative ions are produced along the entire length of the electrode 222. This production of negative ions along the entire length of the electrode 222 allows more ions to be freely dissipated in the air as the air flows past the electrode assembly 220. Alternatively, or additionally, the trailing electrode 222 is a triangular shape with pointed ends, instead of a wire.

FIG. 6 illustrates a perspective view of the air conditioner device in accordance with one embodiment of the present invention. The device 400 of the present invention includes a housing 402A which is coupled to the base 403, whereby the housing 402A preferably stands upright from the base 403 and has a freestanding, elongated shape. The housing 402A also includes a top surface 436 which includes one or more switches 401 as well as a liftable handle 406. The switch 401 has already been discussed and it is contemplated

15

that the switch **401** replaces or substitutes switches **S1**, **S2**, **S3** shown in FIGS. 2A and 2B. The housing **402A** has a cylindrical shape and generally has a front end **432** as well as a back end **434**. The outlet vent, also referred to as the exhaust grill **402B**, is coupled to the front end **432** of the housing **402A**, and an inlet or intake grill **402C** is coupled to the back end **434** of the housing **402A**.

The exhaust grill **402B** and intake grill **402C** preferably include fins which run longitudinally or vertically along the length of the upstanding housing **402A** as shown in FIGS. 6 and 7A. However, it is contemplated by one skilled in the art that the fins are configured in any other direction and are not limited to the vertical direction.

In one embodiment shown in FIG. 7A, the driver electrodes are removable by removing the exhaust grill **402B** from the housing **402A**. The removable exhaust grill **402B** allows the user convenient access to the electrode assembly **420** as well as to the driver electrodes **246** to clean the electrode assembly **420** and/or other components. The exhaust grill **402B** is removable either partially or completely from the housing **402A** as shown in FIG. 7A. In particular, the exhaust grill **402B** includes several L-shaped coupling tabs **421** which secure the exhaust grill **402B** to the housing **402A**. The housing **402A** includes a number of receiving slots **423** which are positioned to receive and engage the L-shaped coupling tabs **421** when the exhaust grill **402B** is coupled to the housing **402A**. The exhaust grill **402B** is removed from the housing **402A** by lifting the exhaust grill **402B** in an upward, vertical direction relative to the housing **402A** to raise the L-shape coupling tabs **421** from the corresponding engaging slots **423** on the housing **402A**. Once the L-shaped coupling tabs **421** are disengaged, the user is able to pull the exhaust grill **402B** laterally away from the housing **402A** to expose the electrode assembly **420** within the housing **402A**. In one embodiment, the exhaust grill **402B** is coupled to the housing **402A** by any alternative mechanism. For example only, the exhaust grill **402B** is attached to the housing **402A** on a set of hinges, whereby the exhaust grill **402B** pivotably opens with respect to the housing **402A** to allow access to the electrode assembly. It is preferred that the driver electrodes **246** and collector electrodes **242** are configured to allow the collector electrodes **242** to be vertically lifted while the driver electrodes **246** remain within the housing **402A**.

FIG. 7B illustrates a cutaway view of the back end **434** of the air conditioner device **400** in accordance with one embodiment of the present invention. As shown in FIG. 7B, the electrode assembly **420** is positioned within the housing **402A** and the exhaust grill **402B** is coupled thereto. As shown in FIG. 7B, the collector electrodes of the electrode assembly **420** preferably includes a top mount **404A**, a bottom mount **404B**, and several collector electrodes **242**, **246** positioned therebetween. In particular, a number of collector electrodes **242** are coupled to the top mount **404A** and the bottom mount **404B** and positioned therebetween. The collector electrodes **242** are preferably positioned parallel to one another. In addition, as shown in FIG. 7B, two driver electrodes **246** are located within the housing **402A** and positioned in between the parallel collector electrodes **242**. The collector electrodes **242** and driver electrodes **246** are positioned proximal to the exhaust grill **402B** to cause the air to flow out of the unit **400** through the exhaust grill **402B**. In addition the electrode assembly **420** includes one or more emitter electrodes which are attached to the emitter electrode pillars **410** disposed on the top and bottom mounts **404A**, **404B**, respectively. The emitter electrodes are shown in dashed lines in FIG. 7B for clarity purposes.

16

FIG. 8A illustrates a perspective view of the removable exhaust grill **402B** in accordance with one embodiment of the present invention. As shown in FIG. 8A, the exhaust grill **402B** includes a top end **436** and a bottom end **438**. The grill **402B** preferably has a concave shape. In one embodiment, the length of the exhaust grill **402B** is substantially the height of the elongated housing **402A**, although it is not necessary. The driver electrodes **246** are securely coupled to one or more clips **416** disposed on the interior surface of the exhaust grill **402B** as shown in FIG. 8A. The clips **416** are located on the inside of the exhaust grill **402B** to position the driver electrodes **246** preferably in between the collector electrodes **242**, as discussed above, when the grill **402B** is coupled to the body **402A**. The driver electrodes **246** are removably coupled to the clips **416** by a friction fit in one embodiment. The driver electrodes **246** are removable from the clips by any other method or mechanism. In one embodiment, the driver electrodes **246** are not removable from the clips **416** of the exhaust grill **402B**.

The driver electrodes **246** are preferably coupled to the negative terminal (FIG. 7B) or ground of the high voltage generator **170** (FIG. 3A) via a pair of conductors located on the top base component **404A** and/or bottom base component **404B**. Alternatively the conductors are positioned elsewhere in the device **400**. The conductors provide voltage to or ground the driver electrodes **246** when the exhaust grill **402B** is coupled to the housing portion **402A**. The conductors come into contact with the driver electrodes **246** when the exhaust grill **402B** is coupled to the housing **402A**. Thus, the driver electrodes **246** are energized or grounded when the exhaust grill **402B** is secured to the housing **402A**. In contrast, the driver electrodes **246** are not energized when the exhaust grill **402B** is removed from the housing **402A**, because the driver electrodes **246** are not in electrical contact with the conductors. This allows the user to clean the driver electrodes **246**. It is apparent to one skilled in that art that any other method is alternatively used to energize the driver electrode **246**.

In one embodiment, the grill **402B** includes the set of trailing electrodes **222** which are disposed downstream of the driver electrodes **246** and near the inner surface of the exhaust grill **402B**. An illustration of the trailing electrodes **222** is shown in FIG. 8B. It should be noted that the trailing electrodes **222** are present in FIG. 8A, although not shown for clarity purposes. In the embodiment that the driver electrodes **246** are removable from the exhaust grill **402B**, the user is able to access to the trailing electrodes **222** for cleaning purposes. In another embodiment, driver electrodes **246** are not removable and the trailing electrodes **222** include a cleaning mechanism such as a slidable member or the like such as by way of example, a bead (not shown), as described above with respect to cleaning the emitter electrodes **232** in U.S. Pat. Nos. 6,350,417 and 6,709,484, which are incorporated by reference above.

The trailing electrodes **222** are preferably secured to the interior of the exhaust grill **402B** by a number of coils **418**, as shown in FIGS. 8A and 8B. As shown in FIGS. 8A and 8B, the coils **418** and the trailing electrodes **222** are preferably coupled to an attaching member of **426**. The attaching member **426** is secured to the inner surface of the exhaust grill **402B**, whereby the attaching member **426** and electrodes **222** remain with the grill **402B** when the grill **402B** is removed from the housing **402A**. Although not shown in the figures, the present invention also includes a set of coils **418** also positioned near the top **436** of the exhaust grill **402B**, whereby the coils **418** hold the trailing electrodes **222** taut against the inside surface of the exhaust grill **402B**.

17

Alternatively, the length of the trailing electrodes 222 are longer than the distance between the coils 418 on opposite ends of the exhaust grill 402B. Therefore, the trailing electrodes 222 are slack against the inside surface of the exhaust grill 402B. Although three sets of coils 418 and three trailing electrodes 222 are shown in FIGS. 8A and 8B, it is contemplated that any number of trailing electrodes 222, including only one trailing electrode, is alternatively used.

The attaching member 426 is preferably conductive and electrically connects the trailing electrodes 222 to the high voltage generator 172 (FIG. 3A) when the exhaust grill 402B is coupled to the housing 402A. The attaching member 426 comes into contact with a terminal of the high voltage generator 170 when the exhaust grill 402B is coupled to the housing 402A. Thus, the trailing electrodes 222 are energized when the exhaust grill 402B is secured to the housing 402A. In contrast, the trailing electrodes 222 are not energized when the exhaust grill 402B is removed from the housing 402A, because the attaching member 426 is not in electrical contact with the generator 172. This allows the user to clean the trailing electrodes 222. It is apparent to one skilled in that art that any other method is alternatively used to energize the trailing electrodes 222.

Although the trailing electrodes 222 are shown coupled to the interior surface of the exhaust grill 402B, the trailing electrodes 222 are alternatively configured to be free-standing downstream from the collector electrodes 242. Thus, the trailing electrodes 222 remain stationary with respect to the housing 402A when the exhaust grill 402B and/or the collector electrodes of the electrode assembly 420 is removed from the unit 400. In one embodiment, the free-standing trailing electrodes 222 are attached to a set of brackets, whereby the brackets are removable from within the housing 402A. Alternatively, the brackets are secured to the housing, and the trailing electrodes 222 are not removable from within the housing 402A.

In operation, once the exhaust grill 402B is removed from the housing 402A, the user is able to remove the driver electrodes 246 from the clips 416 by simply pulling on the driver electrodes 246. Alternatively, the driver electrodes 246 are disengaged from the clips 416 by any other appropriate known method or mechanism. Alternatively, the driver electrodes 246 are secured to the exhaust grill 402B and can be cleaned as secured to the exhaust grill 402B. As stated above, in one embodiment, the user is also able to clean the trailing electrodes 222 (FIG. 8B) once the driver electrodes 246 are disengaged from the clips 416.

With the exhaust grill 402B removed, the electrode assembly 420 within the housing 402A is exposed. In one embodiment, the user is able to clean the emitter 232 and the collector electrodes 242 while the electrodes are positioned within the housing 402A. In one embodiment, the user is able to vertically lift the handle 406 and pull the collector electrodes 240 of the electrode assembly 420 telescopically out through the upper portion of the housing 402A without having to remove the exhaust grill 402B. The user is thereby able to completely remove the collector electrodes 240 of the electrode assembly 420 from the housing portion 402A and have complete access to the collector electrodes 242. Once the collector electrodes 242 are cleaned, the user is then able to re-insert the collector electrodes 240 of the electrode assembly 420 vertically downwards, with the assistance of gravity, into the housing portion of 402A until the collector electrodes 240 of the electrode assembly 420 is secured inside the housing portion 402A. With the driver electrodes 246 secured to the exhaust grill 402B, the user is able to couple the exhaust grill 402B to the housing portion

18

402A in the manner discussed above. Thus, it is apparent that the collector electrodes 240 of the electrode assembly 420 and the exhaust grill 402B are independently removable from the housing 402A to clean the electrodes. In one embodiment, the electrode assembly 420 includes a mechanism which includes a flexible member and a slot for capturing and cleaning the emitter electrode 232 whenever the electrode assembly 420 is inserted and/or removed. More detail regarding the mechanism is provided in U.S. Pat. No. 6,709,484 which was incorporated by reference above.

FIGS. 9A and 9B illustrate another embodiment of the air conditioner device 500 in accordance with the present invention. The embodiment shown in FIG. 9A is similar to the device 400 described in FIGS. 6-8B. However, the driver electrodes 246 in the embodiment shown in FIGS. 9A-10B are removably secured to the collector electrode assembly 540 and are removable from the housing 502A with the collector electrode assembly 540. In one embodiment, the exhaust grill is not removable from the housing portion 502A. In another embodiment, the exhaust grill is removable from the housing portion 502A in the manner described above in regards to FIGS. 6-8B.

In the embodiment shown in FIGS. 9A-10B, the collector electrode assembly 540 is removable from the unit 500 by lifting the handle 506 in a vertical direction and pulling the collector electrode assembly 540 telescopically out of the housing 502A. The driver electrodes 246 are then removable from the collector electrode assembly 540 after the collector electrode assembly 540 has been removed from the unit 500, as will be discussed below.

FIG. 10A illustrates a perspective view of the collector electrode assembly 540 in accordance with the present invention. As shown in FIG. 10A, the collector electrode assembly 540 comprises the set of collector electrodes 242 and the set of driver electrodes 246 positioned adjacent to the collector electrodes 242. As shown in FIG. 10A, the collector electrodes 242 are coupled to a top mount 504A and a bottom mount 504B, whereby the mounts 504A, 504B preferably arrange the collector electrodes 242 in a fixed, parallel configuration. The liftable handle 506 is coupled to the top mount 504A. The top and bottom mounts 504A, 504B are designed to allow the collector electrodes 242 to be inserted and removed from the device 500. The top and/or the bottom mounts 504A, 504B include one or more contact terminals which electrically connect the collector electrodes 242 to the high voltage source 170 when the collector electrodes 242 are inserted in the housing 502A. It is preferred that the contact terminals come out of contact with the corresponding terminals within the housing 502A when the collector electrodes 242 are removed from the housing 502A.

In the embodiment shown in FIG. 10A, three collector electrodes 242 are positioned between the top mount 504A and the bottom mount 504B. However, any number of collector electrodes 242 are alternatively positioned between the top mount 504A and the bottom mount 504B. The collector and driver electrodes 242, 246, as shown in FIGS. 10A and 10B, are preferably symmetrical about the vertical axis, which is designated as the axis parallel to the electrodes 242, 246 in one embodiment. Alternatively, or additionally, the collector and driver electrodes 242, 246 are symmetrical about the horizontal axis, which is designated as the axis perpendicular and across the electrodes 242, 246. It is apparent to one skilled in the art that the electrode assembly is alternatively non-symmetrical with respect to the vertical and/or the horizontal axis.

19

In addition as shown in FIG. 10A, a set of driver electrodes 246 are positioned between a top driver mount 516A and a bottom driver mount 516B. Although two driver electrodes 246 are shown between the top driver mount 516A and a bottom driver mount 516B, any number of driver electrodes 246, including only one driver electrode, is contemplated. The top driver mount 516A and bottom driver mount 516B are configured to allow the driver electrodes 246 to be removable from the collector electrodes 242, as discussed below. The top and bottom driver mounts 516A and 516B preferably include a set of contact terminals which deliver voltage from the high voltage pulse generator 170 (FIGS. 4 and 5) to the driver electrodes 246 when the driver electrodes 246 are coupled to the collector electrodes 242. Alternatively, the driver electrodes 246 are grounded. Accordingly, the top and/or bottom driver mounts 516A, 516B include contact terminals which come into contact with the contact terminals of the mount(s) 504 when the driver electrodes 246 are coupled to the collector electrodes 242.

The collector electrode assembly 540 includes a release mechanism 518 located in the top mount 504A in one embodiment. The release mechanism 518, when depressed, releases the locking mechanism which secures the top and bottom driver mounts 516A, 516B to the top and bottom mounts 504A, 504B. Any appropriate type of locking mechanism is contemplated and is well known in the art. In one embodiment, the release mechanism 518 unfastens the top driver mount 516A from the collector electrode assembly 540, allowing the top driver mount 516A to pivot out and release the bottom driver mount 516B from a protrusion that the bottom driver mount 516B is fitted over and held in place by. Thus, the driver electrodes 246 are removable as shown in FIG. 10B. Alternatively, the bottom driver mount 516B includes protrusions 517 that can retain the driver electrodes in the bottom mount 504B of the collector electrode array 540. In another embodiment, the driver electrodes 246 are removed from the collector electrode assembly 540 by being slid in a direction perpendicular to the elongated length of the collector electrode assembly 540 as shown in FIG. 10B. It is apparent that the release mechanism 518 is alternatively located elsewhere in the collector electrode assembly 540. As shown in FIG. 10B, the driver electrodes 246 are removable by lifting or pulling the driver electrodes 246 from the collector electrodes 242 upon activating the release mechanism 518. In particular, the top and/or bottom driver mounts 516A, 516B are lifted from the top and bottom mounts 504A, 504B, respectively. The removed driver electrodes 246 are then able to be easily cleaned. In addition, the removal of the driver electrodes 246 increases the amount of space between the collector electrodes 242, thereby allowing the user to easily clean the collector electrodes 242.

In one embodiment, securing the driver electrodes 246 to the top and bottom mounts 504A, 504B, the user aligns the bottom driver mount 516B with the bottom mount 504B. Once aligned, the user pivots the top driver mount 516A toward the top mount 504A until the locking mechanism engages the corresponding feature(s) in the top and/or bottom mounts. The driver electrodes 246 are then secured to the rest of the collector electrode assembly 540, whereby the electrode assembly 520 is then able to be inserted back into the housing 502A as one piece. In another embodiment, the driver electrodes 246 are secured to the top and bottom mounts 504A, 504B by aligning the top and bottom driver mounts 516A, 516B with the top and bottom mounts 504A, 504B and laterally inserting the top and bottom driver mounts 516A, 516B into the receptacles of the top and

20

bottom mounts 504A, 504B until the locking mechanism engages the corresponding feature(s) in the top and/or bottom mounts 504A, 504B.

As stated above, the driver electrodes 246 are preferably symmetrical about the vertical and/or horizontal axis. In one embodiment, the top and bottom driver mounts 516A, 516B are configured such that the driver electrodes 246 are able to be reversibly coupled to the top and bottom mounts 504A, 504B. Thus, the bottom driver mount 516B would couple to the top mount 504A, and the top driver mount 516A would couple to the bottom mount 504B. This feature allows the driver electrodes 246 to properly operate irrespective of whether the driver electrodes 246 are right-side-up or upside down. In another embodiment, less than all of the driver electrodes 246 are removable from the mounts 504A, 504B, whereby one or more of the driver electrodes 246 are independently removable from one another.

In another embodiment, the driver electrodes 246 removable from the collector electrodes 242 without first removing the entire collector electrode assembly 540 from the housing 502A. For example, the user can remove the exhaust grill 402B (FIG. 8A) and depress the release mechanism 518, whereby the driver electrodes 246 are pulled out through the front of the housing 502A. The user is then able to clean the collector electrodes 242 still positioned with the housing 502A. The user is also alternatively able to then lift the collector electrodes 242 out of the housing 502A by lifting the handle 506 as discussed above.

The foregoing description of preferred and alternative embodiments of the present invention has been provided for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations will be apparent to one of ordinary skill in the relevant arts. The embodiments were chosen and described in order to best explain the principles of the invention and its practical application, thereby enabling others skilled in the art to understand the invention for various embodiments and with various modifications that are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the claims and their equivalence.

What is claimed is:

1. An air treatment apparatus comprising:

- a. a housing;
- b. at least one power source;
- c. at least one first electrode;
- d. at least one second electrode coupled to the power source and spaced apart from the first electrode, the first and second electrode being operable to produce a stream of ions moving from the first electrode toward the second electrode;
- e. at least one third electrode coupled to the power source, at least a portion of the third electrode being positioned downstream of the second electrode; and
- f. a grill configured to be attached to the housing, the grill defining a plurality of openings, the grill being movable between:
 - (i) a first position in which the grill covers the portion of the third electrode; and
 - (ii) a second position in which the portion of the third electrode is uncovered, the grill being attached to or detached from the housing when in the second position.

2. The air treatment apparatus of claim 1, wherein the housing is vertically elongated and includes an upper portion, wherein the second electrode is removable from the

21

housing through the upper portion and the third electrode is removable through a side of the housing.

3. The air treatment apparatus of claim 1, wherein: (i) the housing is vertically elongated and includes an upper portion; (ii) the second electrode is removable from the housing through the upper portion; and the third electrode is capable of remaining in the housing when the second electrode is removed from the housing.

4. The air treatment apparatus of claim 1, wherein the third electrode includes an electrode selected from the group consisting of: a trailing electrode; a driver electrode; and an electrode including an interstitial electrode.

5. The air treatment apparatus of claim 1, further comprising a germicidal lamp within the housing.

6. The air treatment apparatus of claim 1, wherein the third electrode is insulated.

7. The air treatment apparatus of claim 1, wherein the third electrode is coated with an ozone reducing catalyst.

8. The air treatment apparatus of claim 1, wherein the grill has at least one pivot point enabling the grill to pivot between the first position and the second position.

9. The air treatment apparatus of claim 1, which includes at least one grill fastener which attaches the grill to the housing, the grill fastener having a fastener selected from the group consisting of: a hinge and an L-shaped tab.

10. An air treatment apparatus comprising:

a. a housing having a top, a bottom and a side;

b. at least one power source;

c. at least one first electrode supported by the housing;

d. at least one second electrode supported by the housing, the second electrode being coupled to the power source and spaced apart from the first electrode, the first and second electrode being operable to produce a stream of ions moving from the first electrode toward the second electrode, the second electrode being removable from the housing through the top;

e. at least one third electrode coupled to the power source, at least a portion of the third electrode being positioned downstream of the second electrode, the third electrode being removable from the housing through the side; and

f. a grill configured to be attached to the housing, the grill defining a plurality of openings, the grill being movable between:

(i) a first position in which the grill covers the portion of the third electrode; and

(ii) a second position in which the portion of the third electrode is uncovered, the grill being attached to or detached from the housing when in the second position.

11. The air treatment apparatus of claim 10, wherein the third electrode is capable of being removed from the housing while the second electrode is within the housing.

12. The air treatment apparatus of claim 10, wherein the third electrode includes an electrode selected from the group consisting of: a trailing electrode, a driver electrode; and an electrode including an interstitial electrode.

13. The air treatment apparatus of claim 10, wherein the third electrode is removed from the housing in a direction substantially perpendicular to the second electrode.

14. The air treatment apparatus of claim 10, wherein the third electrode is insulated.

15. The air treatment apparatus of claim 10, wherein the third electrode is coated with an ozone reducing catalyst.

16. The air treatment apparatus of claim 10, wherein the grill has at least one pivot point enabling the grill to pivot between the first position and the second position.

22

17. The air treatment apparatus of claim 10, which includes at least one grill fastener which attaches the grill to the housing, the grill fastener having a fastener selected from the group consisting of: a hinge and an L-shaped tab.

18. An air treatment apparatus comprising:

a. a housing having an upper portion;

b. at least one power source;

c. at least one first electrode supported by the housing;

d. at least one second electrode removably supported by the housing, the second electrode being coupled to the power source and spaced apart from the first electrode, the first and second electrodes being operable to produce a stream of ions moving from the first electrode toward the second electrode;

e. at least one third electrode coupled to the power source, at least a portion of the third electrode being positioned downstream of the second electrode, the third electrode being removable from the housing independent of the second electrode; and

f. a grill configured to be mountable to the housing, the grill defining a plurality of openings, the grill being movable between:

(i) a first position in which the grill covers the portion of the third electrode; and

(ii) a second position in which the portion of the third electrode is uncovered, the grill being mounted to or demounted from the housing when in the second position.

19. The air treatment apparatus of claim 18, wherein at least a portion of the third electrode is positioned between two of the at least one second electrodes when the grill is mounted to the housing.

20. The air treatment apparatus of claim 18, wherein the third electrode is configured to be removed from within the housing when the grill is demounted from the housing.

21. The air treatment apparatus of claim 18, wherein the third electrode includes an electrode selected from the group consisting of: a trailing electrode, a driver electrode and an electrode including an interstitial electrode.

22. The air treatment apparatus of claim 18, wherein the third electrode is removed from the housing in a direction substantially perpendicular to the second electrode.

23. The air treatment apparatus of claim 18, wherein the third electrode is insulated.

24. The air treatment apparatus of claim 18, wherein the third electrode is coated with an ozone reducing catalyst.

25. The air treatment apparatus of claim 18, wherein the grill has at least one pivot point enabling the grill to pivot between the first position and the second position.

26. The air treatment apparatus of claim 18, which includes at least one grill fastener which attaches the grill to the housing, the grill fastener having a fastener selected from the group consisting of: a hinge and an L-shaped tab.

27. An air treatment apparatus comprising:

a housing;

at least one power source;

at least one emitter electrode coupled to the power source;

at least one collector electrode coupled to the power source and spaced apart from the emitter electrode, the emitter and collector electrodes being operable to produce a stream of ions moving from the emitter electrode toward the collector electrode;

at least one trailing electrode coupled to the power source, at least a portion of the trailing electrode being positioned downstream of the collector electrode; and

23

a grill configured to be attached to the housing, the grill defining a plurality of openings, the grill being movable between:

- (a) a first position in which the grill covers the portion of the trailing electrode; and
- (b) a second position in which the portion of the trailing electrode is uncovered, the grill being attached to or detached from the housing when in the second position.

24

28. The air treatment apparatus of claim **27**, wherein the grill has at least one pivot point enabling the grill to pivot between the first position and the second position.

- 29.** The air treatment apparatus of claim **27**, which includes at least one grill fastener which attaches the grill to the housing, the grill fastener having a fastener selected from the group consisting of: a hinge and an L-shaped tab.

* * * * *