



US006896853B2

(12) **United States Patent**
Lau et al.

(10) **Patent No.:** **US 6,896,853 B2**
(45) **Date of Patent:** **May 24, 2005**

(54) **PERSONAL ELECTRO-KINETIC AIR
TRANSPORTER-CONDITIONER**

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Shek Fai Lau**, Foster City, CA (US);
Charles E. Taylor, Punta Gorda, FL
(US)

CN	2111112 U	7/1972
CN	87210843 U	7/1988
CN	2138764 Y	6/1993

(Continued)

(73) Assignee: **Sharper Image Corporation**, San
Francisco, CA (US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

U.S. Appl. No. 10/278,193, filed Oct. 21, 2002, Reeves.
U.S. Appl. No. 10/405,193, filed Apr. 1, 2003, Taylor.
"Zenion Elf Device," drawing, prior art.

(Continued)

(21) Appl. No.: **10/658,721**

Primary Examiner—Rodney G. McDonald

(22) Filed: **Sep. 9, 2003**

(74) *Attorney, Agent, or Firm*—Fliesler & Meyer LLP

(65) **Prior Publication Data**

(57) **ABSTRACT**

US 2004/0047775 A1 Mar. 11, 2004

Related U.S. Application Data

(63) Continuation of application No. 09/669,253, filed on Sep.
25, 2000, now Pat. No. 6,632,407, which is a continuation-
in-part of application No. 09/186,471, filed on Nov. 5, 1998,
now Pat. No. 6,176,977.

(51) **Int. Cl.**⁷ **B01J 19/08**

(52) **U.S. Cl.** **422/186; 422/186.07; 422/186.1**

(58) **Field of Search** **422/186, 186.07,
422/186.1, 186.7**

(56) **References Cited**


U.S. PATENT DOCUMENTS

653,421 A	7/1900 Lorey	210/330
995,958 A	6/1911 Goldberg	422/186.18
1,791,338 A	2/1931 Wintermute	96/51

(Continued)

A personal electro-kinetic electro-static air conditioner includes a self-contained ion generator that provides electro-kinetically moved air with ions and safe amounts of ozone, and includes a water retaining element to increase humidity of the output air flow. The ion generator includes a high voltage pulse generator whose output pulses are coupled between first and second electrode arrays. Preferably the first electrode array includes first and second pointed electrodes, and the second electrode array includes annular-like electrodes having a central opening coaxial with the associated pointed electrode. The surface of the annular-like electrodes is smooth and continuous through the opening and into a collar region through which the air flows. A water retaining member is disposed surrounding the output airflow to increase humidity of the output air, which is substantially cleansed of particulate matter, and contains safe amounts of ozone.

22 Claims, 14 Drawing Sheets



US 6,896,853 B2

Page 2

U.S. PATENT DOCUMENTS

1,869,335 A	7/1932	Day	95/77	5,006,761 A	4/1991	Torok et al.	315/111.91
2,327,588 A	8/1943	Bennett	315/326	5,010,869 A	4/1991	Lee	123/539
2,359,057 A	9/1944	Skinner	96/224	5,012,093 A	4/1991	Shimizu	399/100
2,509,548 A	5/1950	White	96/82	5,012,159 A	4/1991	Torok et al.	315/111.91
2,590,447 A	3/1952	Nord, Jr. et al.	607/79	5,024,685 A	6/1991	Torok et al.	96/43
2,949,950 A	8/1960	Brown	310/308	5,053,912 A	10/1991	Loreth et al.	399/100
3,018,394 A	1/1962	Brown	310/308	5,072,746 A	12/1991	Kantor	132/219
3,026,964 A	3/1962	Penney	96/74	5,077,500 A	12/1991	Torok et al.	315/111.91
3,374,941 A	3/1968	Okress	315/111.91	RE33,927 E	5/1992	Fuzimura	96/62
3,518,462 A	6/1970	Brown	310/10	5,141,529 A	8/1992	Oakley et al.	95/57
3,581,470 A	6/1971	Aitkenhead et al.	96/79	D329,284 S	9/1992	Patton	D23/378
3,638,058 A	1/1972	Fritzius	313/359.1	D332,655 S	1/1993	Lytle et al.	96/56
3,744,216 A	7/1973	Halloran	96/16	5,180,404 A	1/1993	Loreth et al.	D23/378
3,981,695 A	9/1976	Fuchs	96/77	5,183,480 A	2/1993	Rateman et al.	95/74
3,984,215 A	10/1976	Zucker	95/81	5,196,171 A	3/1993	Peltier	422/121
4,052,177 A	10/1977	Kide	96/82	5,215,558 A	6/1993	Moon	96/62
4,092,134 A	5/1978	Kikuchi	96/51	5,217,504 A	6/1993	Johansson	95/7
4,102,654 A	7/1978	Pellin	96/16	5,248,324 A	9/1993	Hara	96/37
4,138,233 A	2/1979	Masuda	96/82	5,266,004 A	11/1993	Tsumurai et al.	416/100
4,209,306 A	6/1980	Feldman et al.	95/80	5,290,343 A	3/1994	Morita et al.	96/39
4,227,894 A	10/1980	Proynoff	96/58	5,296,019 A	3/1994	Oakley et al.	96/95
4,231,766 A	11/1980	Spurgin	96/79	5,302,190 A	4/1994	Williams	95/57
4,232,355 A	11/1980	Finger et al.	361/235	5,315,838 A	5/1994	Thompson	62/129
4,244,710 A	1/1981	Burger	95/69	5,316,741 A	5/1994	Sewell et al.	422/186.21
4,244,712 A	1/1981	Tongret	96/25	5,378,978 A	1/1995	Gallo et al.	323/241
4,253,852 A	3/1981	Adams	96/58	5,386,839 A	2/1995	Chen	132/152
4,259,452 A	3/1981	Yukuta et al.	521/52	5,435,817 A	7/1995	Davis et al.	55/337
4,266,948 A	5/1981	Teague et al.	96/57	5,437,713 A	8/1995	Chang	96/51
4,282,014 A	8/1981	Winkler et al.	96/26	5,484,472 A	1/1996	Weinberg	96/26
4,284,420 A	8/1981	Borysiak	96/40	5,532,798 A	7/1996	Nakagami et al.	399/170
4,318,718 A	3/1982	Utsumi et al.	96/51	5,535,089 A	7/1996	Ford et al.	361/231
4,342,571 A	8/1982	Hayashi	96/76	5,569,368 A	10/1996	Larsky et al.	204/600
4,357,150 A	11/1982	Masuda et al.	95/63	D375,546 S	11/1996	Lee	D23/364
4,386,395 A	5/1983	Francis, Jr.	363/27	5,578,112 A	11/1996	Krause	96/24
4,413,225 A	11/1983	Donig et al.	323/246	D377,523 S	1/1997	Marvin et al.	D23/364
4,445,911 A	5/1984	Lind	95/6	5,601,636 A	2/1997	Glucksman	96/63
4,477,263 A	10/1984	Shaver et al.	96/66	5,641,342 A	6/1997	Smith et al.	96/77
4,496,375 A	1/1985	Le Vantine	96/19	5,656,063 A	8/1997	Hsu	95/58
4,502,002 A	2/1985	Ando	96/60	5,667,564 A	9/1997	Weinberg	96/58
4,509,958 A	4/1985	Masuda et al.	96/60	5,669,963 A	9/1997	Horton et al.	96/77
4,516,991 A	5/1985	Kawashima	96/55	5,698,164 A	12/1997	Kishioka et al.	422/121
4,536,698 A	8/1985	Shevalenko et al.	95/7	5,702,507 A	12/1997	Wang	96/55
4,587,475 A	5/1986	Finney, Jr. et al.	323/241	D389,567 S	1/1998	Gudefin	D23/378
4,600,411 A	7/1986	Santamaria	96/82	5,766,318 A	6/1998	Loreth et al.	96/69
4,601,733 A	7/1986	Ordines et al.	96/82	5,779,769 A	7/1998	Jiang	96/55
4,626,261 A	12/1986	Jorgensen	95/6	5,814,135 A	9/1998	Weinberg	96/58
4,632,135 A	12/1986	Lenting et al.	132/313	5,879,435 A	3/1999	Satyapal et al.	96/16
4,643,745 A	2/1987	Sakakibara et al.	96/76	5,893,977 A	4/1999	Pucci	210/739
4,659,342 A	4/1987	Lind	95/5	5,911,957 A	6/1999	Khatchatrian et al.	422/186.01
4,674,003 A	6/1987	Zylka	361/235	5,972,076 A	10/1999	Nichols et al.	95/81
4,686,370 A	8/1987	Blach	250/423 R	5,975,090 A	11/1999	Taylor et al.	132/116
4,689,056 A	8/1987	Noguchi et al.	96/79	5,980,614 A	11/1999	Loreth et al.	96/63
4,694,376 A	9/1987	Gesslauer	361/235	5,993,521 A	11/1999	Loreth et al.	96/69
4,713,093 A	12/1987	Hansson	96/82	5,997,619 A	12/1999	Knuth et al.	96/224
4,713,724 A	12/1987	Voelkel	361/231	6,019,815 A	2/2000	Satyapal et al.	95/74
4,726,812 A	2/1988	Hirth	95/80	6,042,637 A	3/2000	Weinberg	96/58
4,726,814 A	2/1988	Weitman	95/73	6,063,168 A	5/2000	Nichols et al.	96/80
4,772,297 A	9/1988	Anzai	96/19	6,086,657 A	7/2000	Freije	95/2
4,779,182 A	10/1988	Mickal et al.	96/82	6,117,216 A	9/2000	Loreth	96/62
4,781,736 A	11/1988	Cheney et al.	96/60	6,118,645 A	9/2000	Partridge	361/231
4,786,844 A	11/1988	Farrell et al.	315/111.21	6,126,722 A	10/2000	Mitchell et al.	95/57
4,789,801 A	12/1988	Lee	310/308	6,126,727 A	10/2000	Lo	96/39
4,808,200 A	2/1989	Dallhammer et al.	95/6	6,149,717 A	11/2000	Satyapal et al.	96/16
4,811,159 A	3/1989	Foster, Jr.	361/231	6,149,815 A	11/2000	Sauter	210/635
4,940,470 A	7/1990	Jaisinghani et al.	95/78	6,152,146 A	11/2000	Taylor et al.	132/116
4,941,068 A	7/1990	Hofmann	361/231	6,163,098 A	12/2000	Taylor et al.	310/308
4,955,991 A	9/1990	Torok et al.	96/50	6,176,977 B1	1/2001	Taylor et al.	204/176
4,967,119 A	10/1990	Torok et al.	315/111.91	6,182,461 B1	2/2001	Washburn et al.	62/264
4,976,752 A	12/1990	Torok et al.	96/43	6,182,671 B1	2/2001	Taylor et al.	132/116
D315,598 S	3/1991	Yamamoto et al.	D23/378	6,193,852 B1	2/2001	Caracciolo et al.	204/176
				6,203,600 B1	3/2001	Loreth	96/40

6,212,883	B1	4/2001	Kang	60/275
6,228,149	B1	5/2001	Alenichev et al.	95/78
6,252,012	B1	6/2001	Egitto et al.	525/431
6,270,733	B1	8/2001	Rodden	422/196.07
6,277,248	B1	8/2001	Ishioka et al.	204/176
6,282,106	B2	8/2001	Grass	363/37
D449,097	S	10/2001	Smith et al.	D23/364
D449,679	S	10/2001	Smith et al.	D23/365
6,302,944	B1	10/2001	Hoenig	96/16
6,309,514	B1	10/2001	Conrad et al.	204/164
6,312,507	B1	11/2001	Taylor et al.	96/19
6,315,821	B1	11/2001	Pillion et al.	96/416
6,328,791	B1	12/2001	Pillion et al.	96/418
6,348,103	B1	2/2002	Ahlborn et al.	134/6
6,350,417	B1	2/2002	Lau et al.	422/186.04
6,362,604	B1	3/2002	Cravey	323/241
6,372,097	B1	4/2002	Chen	204/176
6,373,723	B1	4/2002	Wallgren et al.	363/16
6,379,427	B1	4/2002	Siess	95/57
6,391,259	B1	5/2002	Malkin et al.	422/28
6,398,852	B1	6/2002	Loreth	96/63
6,447,587	B1	9/2002	Pillion et al.	96/418
6,451,266	B1	9/2002	Lau et al.	422/106.07
6,464,754	B1	10/2002	Ford	95/26
6,471,753	B1	10/2002	Ahn et al.	96/27
6,494,940	B1	12/2002	Hak	96/224
6,504,308	B1	1/2003	Krichtafovitch et al.	315/111.91
6,508,982	B1	1/2003	Shoji	422/22
6,544,485	B1	4/2003	Taylor	422/186.04
6,585,935	B1	7/2003	Taylor et al.	422/29
6,588,434	B2	7/2003	Taylor et al.	132/116
6,603,268	B2	8/2003	Lee	315/111.01
6,613,277	B1	9/2003	Monagan	422/24
6,632,407	B1	10/2003	Lau et al.	422/186
6,672,315	B2	1/2004	Taylor et al.	132/116
6,709,484	B2	3/2004	Lau et al.	95/76
6,713,026	B2	3/2004	Taylor et al.	422/186.04
6,749,667	B2	6/2004	Reeves et al.	95/76
2001/0004046	A1	6/2001	Taylor et al.	
2001/0048906	A1	12/2001	Lau et al.	
2002/0069760	A1	6/2002	Pruette et al.	
2002/0079212	A1	6/2002	Taylor et al.	
2002/0098131	A1	7/2002	Taylor et al.	
2002/0100488	A1	8/2002	Taylor et al.	
2002/0122751	A1	9/2002	Sinaiko et al.	
2002/0122752	A1	9/2002	Taylor et al.	
2002/0127156	A1	9/2002	Taylor	
2002/0134664	A1	9/2002	Taylor et al.	
2002/0134665	A1	9/2002	Taylor et al.	
2002/0141914	A1	10/2002	Lau et al.	
2002/0144601	A1	10/2002	Palestro et al.	
2002/0146356	A1	10/2002	Sinaiko et al.	
2002/0150520	A1	10/2002	Taylor et al.	
2002/0152890	A1	10/2002	Leiser	
2002/0155041	A1	10/2002	McKinney, Jr. et al.	
2002/0170435	A1	11/2002	Joannou	
2002/0190658	A1	12/2002	Lee	
2002/0195951	A1	12/2002	Lee	
2003/0005824	A1	1/2003	Katou et al.	
2003/0196887	A1	10/2003	Lau et al.	
2003/0206837	A1	11/2003	Taylor et al.	
2003/0206839	A1	11/2003	Taylor et al.	
2003/0206840	A1	11/2003	Taylor et al.	
2004/0052700	A1	3/2004	Kotlyar et al.	
2004/0065202	A1	4/2004	Gatchell et al.	
2004/0136863	A1	7/2004	Yates et al.	
2004/0166037	A1	8/2004	Youdeil et al.	

FOREIGN PATENT DOCUMENTS

CN	2153231	Y	12/1993
DE	2206057		8/1973
EP	0433152	A1	12/1990
EP	0332624	B1	1/1992
FR	2690509		10/1993
GB	643363		9/1950
JP	S51-90077		8/1976
JP	58-27654	*	2/1983
JP	S62-20653		2/1987
JP	10137007		5/1998
JP	11104223		4/1999
JP	2000236914		9/2000
WO	WO92/05875	A1	4/1992
WO	WO96/04703	A1	2/1996
WO	WO99/07474	A1	2/1999
WO	WO00/10713	A1	3/2000
WO	WO 01/47803	A1	7/2001
WO	WO 01/48781	A1	7/2001
WO	WO01/64349	A1	9/2001
WO	WO01/85348	A2	11/2001
WO	WO02/20162	A2	3/2002
WO	WO02/20163	A2	3/2002
WO	WO02/30574	A1	4/2002
WO	WO02/32578	A1	4/2002
WO	WO02/42003	A1	5/2002
WO	WO02/066167	A1	8/2002
WO	WO03/009944	A1	2/2003
WO	WO03/013620	A1	2/2003
WO	WO03/013734	A1	2/2003

OTHER PUBLICATIONS

Electrical schematic and promotional material available from Zenion Industries, 7 pages, Aug. 1990.

Promotional material available from Zenion Industries for the Plasma-Pure 100/200/300, 2 pages, Aug. 1990.

Promotional material available from Zenion Industries for the Plasma-Tron, 2 pages, Aug. 1990.

LENTEK Sila™ Plug-In Air Purifier/Deodorizer product box copyrighted 1999, 13 pages.

U.S. Appl. No. 60/104,573, filed Oct. 16, 1998, Krichtafovitch.

Trion Console 250 Electronic Air Cleaner, Model Series 442857 and 445600, Manual for Installation•Operation•Maintenance, Trion Inc., 7 pp., believed to be at least one year prior to Nov. 5, 1998.

Trion 350 Air Purifier, Model 450111-010, <http://www.feddersoutlet.com/trion350.html>, 12 pp., believed to be at least one year prior to Nov. 5, 1998.

Trion 150 Air Purifier, Model 45000-002, <http://www.feddersoutlet.com/trion150.html>, 11 pp., believed to be at least one year prior to Nov. 5, 1998.

Trion 120 Air Purifier, Model 442501-025, <http://www.feddersoutlet.com/trion120.html>, 16 pp., believed to be at least one year prior to Nov. 5, 1998.



Friedrich C-90A Electronic Air Cleaner, Service Information, Friedrich Air Conditioning Co., 12 pp., 1985.

LakeAir Excel and Maxum Portable Electronic Air Cleaners, Operating and Service Manual, LakeAir International, Inc., 11 pp., 1971.

Blueair AV 402 Air Purifier, http://www.air-purifiers-usa.biz/Blueair_AV402.htm, 4pp., 1996.

Blueair AV 501 Air Purifier, http://www.air-purifiers-usa.biz/Blueair_AV501.htm, 15 pp., 1997.

* cited by examiner

**FIG. 1A (PRIOR ART)****FIG. 1B (PRIOR ART)**




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 4E




FIG. 4F




FIG. 4G




FIG. 4H




FIG. 4I




FIG. 4J




FIG. 4K




FIG. 4L




FIG. 4M




FIG. 4N

PERSONAL ELECTRO-KINETIC AIR TRANSPORTER-CONDITIONER

RELATION TO CO-PENDING APPLICATION

This application is a continuation of U.S. patent application Ser. No. 09/669,253, filed Sep. 25, 2000 entitled PERSONAL ELECTRO-KINETIC AIR TRANSPORTER-CONDITIONER, now U.S. Pat. No. 6,632,407 which is a continuation-in-part of U.S. patent application Ser. No. 09/186,471, filed Nov. 5, 1998 entitled ELECTRO-KINETIC AIR TRANSPORTER-CONDITIONER, now U.S. Pat. No. 6,176,977.

FIELD OF THE INVENTION

This invention relates to electro-kinetic conversion of electrical energy into fluid flow of an ionizable dielectric medium in which an electro-kinetically produced flow of air is created, the air containing safe amounts of ozone and from which air particulate matter has been substantially removed, and more particularly to portable such units adapted for use in a confined area in which some degree of humidity control is desired.

BACKGROUND OF THE INVENTION

The use of an electric motor to rotate a fan blade to create an air flow has long been known in the art. Unfortunately, such fans produce substantial noise, and can present a hazard to children who may be tempted to poke a finger or a pencil into the moving fan blade. Although such fans can produce substantial air flow, e.g., 1,000 ft³/minute or more, substantial electrical power is required to operate the motor, and essentially no conditioning of the flowing air occurs.

It is known to provide such fans with a HEPA-compliant filter element to remove particulate matter larger than perhaps 0.3 μ m. Unfortunately, the resistance to air flow presented by the filter element may require doubling the electric motor size to maintain a desired level of airflow. Further, HEPA-compliant filter elements are expensive, and can represent a substantial portion of the sale price of a HEPA-compliant filter-fan unit. While such filter-fan units can condition the air by removing large particles, particulate matter small enough to pass through the filter element is not removed, including bacteria, for example.

It is also known in the art to produce an air flow using electro-kinetic techniques, by which electrical power is directly converted into a flow of air without mechanically moving components. One such system is described in U.S. Pat. No. 4,789,801 to Lee (1988), depicted herein in simplified form as FIGS. 1A and 1B. Lee's system 10 includes an array of small area ("minisectional") electrodes 20 that is spaced-apart symmetrically from an array of larger area ("maxisectional") electrodes 30. The positive terminal of a pulse generator 40 that outputs a train of high voltage pulses (e.g., 0 to perhaps +5 KV) is coupled to the minisectional array, and the negative pulse generator terminal is coupled to the maxisectional array.

The high voltage pulses ionize the air between the arrays, and an air flow 50 from the minisectional array toward the maxisectional array results, without requiring any moving parts. Particulate matter 60 in the air is entrained within the airflow 50 and also moves towards the maxisectional electrodes 30. Much of the particulate matter is electrostatically attracted to the surface of the maxisectional electrode array, where it remains, thus conditioning the flow of air exiting system 10. Further, the high voltage field present between

the electrode arrays can release ozone into the ambient environment, which appears to destroy or at least alter whatever is entrained in the airflow, including for example, bacteria.

In the embodiment of FIG. 1A, minisectional electrodes 20 are circular in cross-section, having a diameter of about 0.003" (0.08 mm), whereas the maxisectional electrodes 30 are substantially larger in area and define a "teardrop" shape in cross-section. The ratio of cross-sectional areas between the maxisectional and minisectional electrodes is not explicitly stated, but from Lee's figures appears to exceed 10:1. As shown in FIG. 1A herein, the bulbous front surfaces of the maxisectional electrodes face the minisectional electrodes, and the somewhat sharp trailing edges face the exit direction of the air flow. The "sharpened" trailing edges on the maxisectional electrodes apparently promote good electrostatic attachment of particulate matter entrained in the airflow and help airflow. Lee does not disclose how the teardrop shaped maxisectional electrodes are fabricated, but presumably they are produced using a relatively expensive mold-casting or an extrusion process.

In another embodiment shown herein as FIG. 1B, Lee's maxisectional electrodes 30 are symmetrical and elongated in cross-section. The elongated trailing edges on the maxisectional electrodes provide increased area upon which particulate matter entrained in the airflow can attach. Lee states that precipitation efficiency and desired reduction of anion release into the environment can result from including a passive third array of electrodes 70. Understandably, increasing efficiency by adding a third array of electrodes will contribute to the cost of manufacturing and maintaining the resultant system.

While the electrostatic techniques disclosed by Lee are advantageous to conventional electric fan-filter units, Lee's maxisectional electrodes are relatively expensive to fabricate. Increased filter efficiency beyond what Lee's embodiments can produce would be advantageous, especially without including a third array of electrodes. Further, Lee's system does not provide for changing the moisture content of the output flow of air, and does not lend itself to being fabricated in a small form factor, for example hand holdable.

While a Lee-type system may be useful in a room, it does not lend itself to portability, for example for use in a confined relatively small area such as the seating compartment of a motor vehicle or an airplane.

Thus, there is a need for a portable electro-kinetic air transporter-conditioner that provides improved efficiency over Lee-type systems, without requiring expensive production techniques to fabricate the electrodes. Preferably such a conditioner should function efficiently without requiring a third array of electrodes. Such a conditioner should permit user-selection of safe amounts of ozone to be generated, for example to remove odor from the ambient environment, and should be implementable in a hand held form factor so as to be portable. Further, such a conditioner should permit increasing the moisture content of the output airflow.

The present invention provides a method and portable apparatus for electro-kinetically transporting and conditioning air.

SUMMARY OF THE PRESENT INVENTION

The present invention provides a preferably portable electro-kinetic system for transporting and conditioning air without moving parts. The air is conditioned in the sense that it is ionized and contains safe amounts of ozone, and, optionally, can benefit from augmented moisture content or

aromatic content. Indeed users who are asthmatics may wish to provide the invention with an asthma inhalant that is added to the outflow of clean air, for their personal benefit.

Applicants' electro-kinetic air transporter-conditioner includes a housing with at least one vent through which ambient air may enter, and an ionizer unit disposed within the housing. The ionizer unit includes a high voltage DC inverter that boosts low voltage (e.g., perhaps 6 VDC to about 12 VDC) to high voltage DC, and a generator that receives the high voltage DC and outputs high voltage pulses. The high voltage pulses are perhaps 10 KV peak-to-peak, although an essentially 100% duty cycle (e.g., high voltage DC) output could be used instead of pulses. The unit also includes at least one and preferably two electrode assembly units, each unit comprising spaced-apart first and second arrays of conducting electrodes coupled between the positive and negative output ports of the high voltage generator. Preferably at least one moisture-containing member is disposed adjacent a downstream region of each second-array electrodes so as to increase humidity of the output airstream.

Preferably two electrode assemblies are used, in which each assembly is formed using first and second arrays of readily manufacturable electrode types. In one embodiment, the first array comprises wire-like electrodes and the second array comprises "U"-shaped electrodes having one or two trailing surfaces. In a preferred, even more efficient embodiment, each first array includes at least one pin or cone-like electrode and the second array is an annular washer-like electrode. The electrode assemblies may comprise various combinations of the described first and second array electrodes. In the various embodiments, the ratio between effective radius of the second array electrodes to the first array electrodes is at least about 20:1.

The high voltage pulses create an electric field between the first and second electrode arrays in each electrode assembly. This field produces an electro-kinetic airflow going from the first array toward the second array, the airflow being rich in preferably a net surplus of negative ions and in ozone. Ambient air including dust particles and other undesired components (germs, perhaps) enter the housing through the input vent, and ionized clean air (with ozone) exits through openings on the downstream side of the housing. When the moisture-containing member is wet, the exiting air flow can have increased humidity.

The dust and other particulate matter attaches electrostatically to the second array (or collector) electrodes, and the output air is substantially clean of such particulate matter. Further, ozone generated by the present invention can kill certain types of germs and the like, and also eliminates odors in the output air. Preferably the transporter operates in periodic bursts, and a control permits the user to temporarily increase the high voltage pulse generator output, e.g., to more rapidly eliminate odors in the environment.

In one embodiment, the system includes an internal battery power supply and can be suspended by a cord from a user's neck, with the outflow airstream directly generally upward toward the user. This embodiment is especially useful in a confined area where the air might be stale or germ-laden, for example the seating compartment of an airline, or a bus. A similar embodiment can be used within and powered from the power supply of a motor vehicle, for example, from the cigarette lighter accessory plug of an automobile or truck. This embodiment includes an electronic timer that causes the system to operate for a predetermined time (perhaps half an hour) each time the power

supply is turned-on, with an option for the user to cause the system to operate more than once per system turn-on. Alternatively a motion sensor switch comprising a sound or force detecting transducer and movable objects can turn-on the system whenever the vehicle is moving sufficiently to agitate the movable objects such that their vibration-motion is transducer detected.

Other features and advantages of the invention will appear from the following description in which the preferred embodiments have been set forth in detail, in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a plan, cross-sectional view, of a first embodiment of a prior art electro-kinetic air transporter-conditioner system, according to the prior art;

FIG. 1B is a plan, cross-sectional view, of a second embodiment of a prior art electro-kinetic air transporter-conditioner system, according to the prior art;

FIG. 2A depicts a preferred embodiment of the present invention worn on the person of a user;

FIG. 2B depicts a preferred embodiment of the present invention used in a motor vehicle;

FIG. 2C is a perspective view of the present invention;

FIG. 2D is a breakaway perspective view of the present invention;

FIG. 3A is an electrical block diagram of the present invention;

FIG. 3B is a vibration-sensing module to activate the system of FIG. 3A, according to the present invention;

FIG. 4A is a perspective block diagram showing a first embodiment for an electrode assembly, according to the present invention;

FIG. 4B is a plan block diagram of the embodiment of FIG. 4A;

FIG. 4C is a perspective block diagram showing a second embodiment for an electrode assembly, according to the present invention;

FIG. 4D is a plan block diagram of a modified version of the embodiment of FIG. 4C;

FIG. 4E is a perspective block diagram showing a third embodiment for an electrode assembly, according to the present invention;

FIG. 4F is a plan block diagram of the embodiment of FIG. 4E;

FIG. 4G is a perspective block diagram showing a fourth embodiment for an electrode assembly, according to the present invention;

FIG. 4H is a plan block diagram of the embodiment of FIG. 4G;

FIG. 4I is a perspective block diagram showing an especially preferred embodiment for an electrode assembly, according to the present invention;

FIG. 4J is a detailed cross-sectional view of a portion of the electrode assembly embodiment of FIG. 4I;

FIG. 4K is a detailed cross-sectional view of a portion of an alternative electrode assembly to the embodiment of FIG. 4I;

FIG. 4L is a detailed cross-sectional view of a portion of a further alternative electrode assembly to the embodiment of FIG. 4I;

FIG. 4M is a cross-section of a portion of the second array electrode shown in the embodiment of FIG. 2D; and

5

FIG. 4N is a detailed cross-sectional view showing a further alternative electrode assembly to the embodiment of FIG. 4L.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

FIG. 2A depicts a preferred embodiment of an electro-kinetic air transporter-conditioner system **100** suspended by a flexible cord **101** from the neck of a user. System **100** is formed within a housing **102** that preferably is a lightweight easily formed material, ABS plastic for example. Housing **102** includes ambient air intake vents **104** and at least one and preferably two output or exhaust vents **106**. Ambient air enters vents **104** and exits vents **106**, preferably with a higher moisture content, with at least some particulate matter in the ambient air removed (e.g., dust), and with safe amounts of ozone (O_3). Housing **102** contains an ion generating unit **160**, powered from a battery source **B1**, also disposed within the housing. Ion generating unit **160** is self-contained in that other than ambient air, nothing is required from beyond the transporter housing for operation of the present invention.

FIG. 2B depicts system **100** mounted on or to the interior of a motor vehicle, for example, mounted with Velcro™ material (a closure including a piece of fabric of small hooks that sticks to a corresponding fabric of small loops) to the dashboard **109** of an automobile. In this embodiment, since the vehicle power supply is available, operating power to ion generating unit **160** preferably is obtained via an electrical cable **111** connected between a power inlet jack **J1** on housing **102** and the motor vehicle cigarette light auxiliary power source **113**. System **100** in FIG. 2B may otherwise be identical to system **100** in FIG. 2A except that an optional mechanical motion detector **211** is included. Motion detector **211** is shown in detail in FIG. 3B and advantageously can be used to power-on system **100** whenever the vehicle containing dashboard **109** is moving.

FIG. 2C is a perspective view of system **100** and housing **102**. Internal to housing **100**, ion generating unit **160** includes a first array **230** of at least one electrode **232** and a second array **240** of at least one electrode **242**. The second array electrodes are disposed closer to outlet port **106** in the downstream direction from the first array electrodes, e.g., the air stream created by the present invention will flow generally from the first array electrodes toward the second array electrodes and then out of housing **100** via ports **106**. The first and second arrays of electrodes are coupled in series between the output terminals of ion generating unit **160**, shown and described with respect to FIG. 3A. In the embodiment of FIGS. 2C and 2D, the first array electrodes **232** are pointed elements, whereas the second array electrodes **242** are somewhat disk-like annular elements with a central opening, in which the first array electrode facing surface of the disk transitions smoothly and continuously into a collar that helps define the through opening in the disk. As will be described later herein with respect to FIGS. 4K and 4L, the profile of the collar may be parallel or somewhat cone-shaped, e.g., tending to converge toward the outlet opening.

Optionally, the present invention advantageously can augment moisture content in the output air flow and includes a moisture-retaining member **112** adjacent at least one outlet port **106**, preferably disposed as to present the least resistance to the outflow of air. In the preferred embodiment, moisture-retaining member **112** is a hollow collar-like cylinder, perhaps 0.125" thick of ultra-high molecular

6

weight polyethelene (UHMW) material, marketed under the trademark Porex™ (e.g., Porex™ UHMW X-4901), that the user will moisten with water. Such material has a polyethylene base and exhibits a wicking action, and can absorb and retain substantial amounts of moisture such as water. An asthmatic user may wish to moisten member **112** with an asthma medication such that the output flow of air is clean, contains beneficial amounts of ozone, has increased humidity and may also provide asthma relief by virtue of the medication also present in the output air.

In the embodiment of FIG. 2B, it may be desired to replace the moisture-retaining material with a scent-imparting material, that can freshen the air within the motor vehicle. If desired, an air humidifying and air scenting function can be employed by combining the Porex™ type material with a scene-imparting material.

FIG. 2D is a breakaway view of the present invention. Housing **102** may (but need not be) formed with an upper member **119** that includes the intake vents **104**, a bottom member **121** that includes a battery hatch **123**, and a detachable front member **125** that includes output ports **106** and moisture-retaining and/or scent-imparting material **112**. The overall dimensions of housing **102** are not critical. In the preferred example, the overall thickness, top to bottom is perhaps 1" (2.5 cm), the width is about 3.5" (8.8 cm) and the length is perhaps 5" (12 cm).

As will be described, when unit **100** is energized, e.g., by closing switch **S1** (or the equivalent, e.g., module **211**), high voltage output by ion generator **160** produces ions at the first electrode array, which ions are attracted to the second electrode array. The movement of the ions in an "IN" to "OUT" direction carries with them air molecules, thus electro-kinetically producing an outflow of ionized air. The "IN" notion in FIG. 2A denotes the intake of ambient air with particulate matter **60**. The "OUT" notation in the figures denotes the outflow of cleaned air substantially devoid of the particulate matter, which adheres electrostatically to the surface of the second array electrodes. In the process of generating the ionized air flow, safe amounts of ozone (O_3) are beneficially produced. It may be desired to provide the inner surface of housing **102** with an electrostatic shield to reduce detectable electromagnetic radiation. For example, a metal shield could be disposed within the housing, or portions of the interior of the housing could be coated with a metallic paint to reduce such radiation.

As best seen in FIG. 3A, ion generating unit **160** includes a high voltage generator unit **170** for converting low input voltage, e.g., perhaps 6 VDC from a battery supply **B1** or perhaps 12 VDC from a vehicle battery into kilovolt level pulses. High voltage generator unit **170** preferably comprises a low voltage oscillator circuit **190** of perhaps 20 KHz frequency, that outputs low voltage pulses to an electronic switch **200**, e.g., a thyristor or the like. Switch **200** switchably couples the low voltage pulses to the input winding of a step-up transformer **T1**. The secondary winding of **T1** is coupled to a high voltage multiplier circuit **210** that outputs high voltage pulses. Preferably the circuitry and components comprising high voltage pulse generator **170** and circuit **180** are fabricated on a printed circuit board that is mounted within housing **102**.

Output pulses from high voltage generator **170** preferably are at least 10 KV peak-to-peak with an effective DC offset of perhaps half the peak-to-peak voltage, and have a frequency of perhaps 20 KHz. The pulse train output preferably has a duty cycle of perhaps 10%, which will promote battery lifetime for the embodiment of FIG. 2A. Of course, different

peak-peak amplitudes, DC offsets, pulse train waveshapes, duty cycle, and/or repetition frequencies may instead be used. Indeed, a 100% pulse train (e.g., an essentially DC high voltage) may be used, albeit with shorter battery lifetime. Thus, generator unit **170** may (but need not) be referred to as a DC:DC high voltage pulse generator. Frequency of oscillation is not especially critical but frequency of at least about 20 KHz is preferred as being inaudible to humans.

As shown in FIG. 3A, the output from high voltage pulse generator unit **170** is coupled to an electrode assembly **220** that comprises a first electrode array **230** (that includes at least one first electrode **232**) and a second electrode array **240** (that includes at least one second electrode **242**). As further shown by FIG. 3A, ion generating unit **160** also includes circuitry **180** that can also include a timer circuit and a visual indicator such as a light emitting diode (LED) that can advise a user when ion generation is occurring. (Of course an audible signal could also or instead be used.) The timer can be set to function for a predetermined time when power is first applied (e.g., with switch **S1**), for example 30 minutes, and then turn-off system **100**. The user could of course again press **S1** to obtain another 30 minute outflow of ionized, cleaned air with increased humidity and/or scent. If desired, circuitry **190** and/or **200** could be caused to output a temporary burst of increased ionized air in response to user pressing of a control on housing **102**.

For the vehicle embodiment of FIG. 2B, a vibration sensor **211** as shown in FIG. 3B may be attached within housing **102** to turn-on system **100** whenever the vehicle in which system **100** is used is moving. Vibration sensor **211** comprises a sound or force detecting transducer **213** mounted to a small container **215** within which are metal BB's **217** or the like. Sensor **213** may be a Keyocera transducer having perhaps 20 mm diameter, and housing **215** may have a top-to-bottom depth of perhaps 10 mm. As housing **102** is vibrated by the moving vehicle, BB's **217** rattle around within container **215** and the resultant noise or physical impact with the transducer is detected by transducer **213**. Wires **219** couple the transducer output to the circuitry shown in FIG. 3A. The result is that when system **100** is plugged into the vehicle cigarette lighter, even if switch **S1** is open, when the vehicle moves with sufficient vibration, the rattling BB noise causes transducer **213** to turn-on the electronics shown in FIG. 3A. Preferably the electronics are thus turned-on for a predetermined time, e.g., 30 minutes. After 30 minutes the electronics can turn-off but when the vehicle again produces a sufficiently large vibration, system **100** will be turned-on for an additional 30 minutes.

In some modern vehicles, mechanical vibration is so small that it is desired to have system **100** activated automatically whenever ignition switch is turned-on. Thus, whenever the vehicle is started, system **100** will operate for a pre-determined time (e.g., perhaps 30 minutes or so, determined by circuit **180**) and then turn-off. The user can press **S1** (or an equivalent switch) to recycle system **100** to function for an additional 30 minutes, etc.

In the embodiment of FIG. 3A, the positive output terminal of unit **170** is coupled to first electrode array **230**, and the negative output terminal is coupled to second electrode array **240**. This coupling polarity has been found to work well, including minimizing unwanted audible electrode vibration or hum. An electrostatic flow of air is created, going from the first electrode array towards the second electrode array. (This flow is denoted "OUT" in the figures.) Accordingly electrode assembly **220** is mounted within transporter system **100** such that second electrode array **240**

is closer to the OUT vents and first electrode array **230** is closer to the IN vents.

When voltage or pulses from high voltage pulse generator **170** are coupled across first and second electrode arrays **230** and **240**, it is believed that a plasma-like field is created surrounding electrodes **232** in first array **230**. This electric field ionizes the ambient air between the first and second electrode arrays and establishes an "OUT" airflow that moves towards the second array. It is understood that the IN flow enters via vent(s) **104**, and that the OUT flow exits via vent(s) **106**.

It is believed that ozone and ions are generated simultaneously by the first array electrode(s) **232**, essentially as a function of the potential from generator **170** coupled to the first array. Ozone generation may be increased or decreased by increasing or decreasing the potential at the first array. Coupling an opposite polarity potential to the second array electrode(s) **242** essentially accelerates the motion of ions generated at the first array, producing the air flow denoted as "OUT" in the figures. As the ions move toward the second array, it is believed that they push or move air molecules toward the second array. The relative velocity of this motion may be increased by decreasing the potential at the second array relative to the potential at the first array.

For example, if +10 KV were applied to the first array electrode(s), and no potential were applied to the second array electrode(s), a cloud of ions (whose net charge is positive) would form adjacent the first electrode array. Further, the relatively high 10 KV potential would generate substantial ozone. By coupling a relatively negative potential to the second array electrode(s), the velocity of the air mass moved by the net emitted ions increases, as momentum of the moving ions is conserved.

On the other hand, if it were desired to maintain the same effective outflow (OUT) velocity but to generate less ozone, the exemplary 10 KV potential could be divided between the electrode arrays. For example, generator **170** could provide +4 KV (or some other fraction) to the first array electrode(s) and -6 KV (or some other fraction) to the second array electrode(s). In this example, it is understood that the +4 KV and the -6 KV are measured relative to ground. Understandably it is desired that the present invention operate to output safe amounts of ozone. Accordingly, the high voltage is preferably fractionalized with about +4 KV applied to the first array electrode(s) and about -6 KV applied to the second array electrodes.

As noted, outflow (OUT) preferably includes safe amounts of O_3 that can destroy or at least substantially alter bacteria, germs, and other living (or quasi-living) matter subjected to the outflow. Thus, when switch **S1** is closed and **B1** has sufficient operating potential, pulses from high voltage pulse generator unit **170** create an outflow (OUT) of ionized air and O_3 . When **S1** is closed, LED will visually signal when ionization is occurring.

Preferably operating parameters of the present invention are set during manufacture and are not user-adjustable. For example, increasing the peak-to-peak output voltage and/or duty cycle in the high voltage pulses generated by unit **170** can increase air flowrate, ion content, and ozone content. In the preferred embodiment, output flowrate is about 200 feet/minute, ion content is about 2,000,000/cc and ozone content is about 40 ppb (over ambient) to perhaps 2,000 ppb (over ambient). As described herein, decreasing the second electrode/first electrode radius of curvature $R2/R1$ ratio below about 20:1 will decrease flow rate, as will decreasing the peak-to-peak voltage and/or duty cycle of the high voltage pulses coupled between the first and second electrode arrays.

In practice, unit **100** is energized from **B1** or a vehicle battery, whereupon an output flow of clean ionized air is emitted from vents **106**. If member **112** is wet with water, the outflow of air will exhibit increased humidity. If member **112** is instead (or in addition) a material that imparts a scent, e.g., perhaps pine or mint odor, the outflow air will also smell fresh. The air flow, coupled with the ions and ozone freshens the air that the user adjacent the unit will breathe, and can be especially beneficial in a closed area such as an airline or motor vehicle passenger compartment. The ozone can beneficially destroy or at least diminish the undesired effects of certain odors, bacteria, germs, and the like. Further, the air flow is indeed electro-kinetically produced, in that there are no intentionally moving parts within the present invention. (As noted, some mechanical vibration may occur within some electrode configurations.) Preferably the present invention is used to output a net surplus of negative ions, as these ions are deemed more beneficial to health than are positive ions.

Having described various aspects of the invention in general, various embodiments of electrode assembly **220** will now be described. In the various embodiments, electrode assembly **220** will comprise a first array **230** of at least one electrode **232**, and will further comprise a second array **240** of preferably at least one electrode **242**. Understandably material(s) for electrodes **232** and **242** should conduct electricity, be resilient to corrosive effects from the application of high voltage, yet be strong enough to be cleaned.

FIG. **4A** depicts an electrode array **220** that is especially good for removing particulate matter (shown as **60**) from incoming ambient air in that the downstream electrodes **242** in second array **240** have relatively large collection surfaces **244** whereon particulate matter **60** can be electrostatically attracted and accumulated, until cleaned by the user. In this embodiment, electrode(s) **232** in the first electrode array **230** are wire or wire-like and are preferably fabricated from tungsten. Tungsten is sufficiently robust to withstand occasional cleaning, has a high melting point to retard breakdown due to ionization, and has a rough exterior surface that seems to promote efficient ionization. On the other hand, electrodes **242** preferably will have a highly polished exterior surface to minimize unwanted point-to-point radiation. As such, electrodes **242** preferably are fabricated from stainless steel, brass, among other materials. The polished surface of electrodes **232** also promotes ease of electrode cleaning.

In contrast to the prior art electrodes disclosed by Lee, electrodes **232** and **242** according to the present invention are light weight, easy to fabricate, and lend themselves to mass production. Further, electrodes **232** and **242** described herein promote more efficient generation of ionized air, and production of safe amounts of ozone, O_3 . Shown generally in FIG. **4A** is moisture and/or scent imparting member **112**, disposed in the downstream region of the invention. If member **112** is made wet with water, air passing by member **112** en route to outlet port **106** will increase in humidity. By the same token, if member **112** contains a pleasant scent, air passing by en route to outlet port **106** will exit the present invention with a more pleasant aroma.

As shown in FIGS. **4A** and **4B**, high voltage pulse generator **170** is coupled between the first electrode array **230** and the second electrode array **240**. As noted, high voltage pulses from generator **170** produce a flow of ionized air that travels in the direction from the first array towards the second array (indicated herein by hollow arrows denoted "OUT"). As such, electrode(s) **232** may be referred to as an emitting electrode, and electrodes **242** may be referred to as

collector electrodes or accelerator electrodes. This outflow advantageously contains safe amounts of O_3 , and exits the present invention from vent(s) **106**.

According to the present invention, it is preferred that the positive output terminal or port of the high voltage pulse generator be coupled to electrodes **232**, and that the negative output terminal or port be coupled to electrodes **242**. It is believed that the net polarity of the emitted ions is positive, e.g., more positive ions than negative ions are emitted. In any event, the preferred electrode assembly electrical coupling minimizes audible hum from electrodes **232** contrasted with reverse polarity (e.g., interchanging the positive and negative output port connections).

However, while generation of positive ions is conducive to a relatively silent air flow, from a health standpoint, it is desired that the output air flow be richer in negative ions, not positive ions. It is noted that in some embodiments, however, one port (preferably the negative port) of the high voltage pulse generator may in fact be the ambient air. Thus, electrodes in the second array need not be connected to the high voltage pulse generator using wire. Nonetheless, there will be an "effective connection" between the second array electrodes and one output port of the high voltage pulse generator, in this instance, via ambient air.

In the embodiments of FIGS. **4A** and **4B**, electrode assembly **220** comprises a first array **230** of wire electrodes **232**, whereas second array **240** includes generally "U"-shaped preferably hollow electrodes **242**. In preferred embodiments, the number **N1** of electrodes comprising the first array will preferably differ by one relative to the number **N2** of electrodes comprising the second array. In many of the embodiments shown, $N2 > N1$. However, if desired, in FIG. **4A**, addition first electrodes **232** could be added at the out ends of array **230** such that $N1 > N2$, e.g., five electrodes **232** compared to four electrodes **242**.

Electrodes **242** are formed from sheet metal, preferably stainless steel, although brass or other sheet metal could be used. The sheet metal is readily formed to define side regions **244** and bulbous nose region **246** for hollow elongated "U" shaped electrodes **242**. While FIG. **4A** depicts four electrodes **242** in second array **240** and three electrodes **232** in first array **230**, as noted, other numbers of electrodes in each array could be used, preferably retaining a symmetrically staggered configuration as shown. It is seen in FIG. **4A** that while particulate matter **60** is present in the incoming (IN) air, the outflow (OUT) air is substantially devoid of particulate matter, which adheres to the preferably large surface area provided by the second array electrodes (see FIG. **4B**).

As best seen in FIG. **4B**, the spaced-apart configuration between the arrays is staggered such that each first array electrode **232** is substantially equidistant from two second array electrodes **242**. This symmetrical staggering has been found to be an especially efficient electrode placement. Preferably the staggering geometry is symmetrical in that adjacent electrodes **232** or adjacent electrodes **242** are spaced-apart a constant distance, **Y1** and **Y2** respectively. However, a non-symmetrical configuration could also be used, although ion emission and air flow would likely be diminished. Also, it is understood that the number of electrodes **232** and **242** may differ from what is shown.

Assume that system **100** has overall dimensions of perhaps 6" height (15 cm), 4" width (10 cm) and perhaps 1" thickness (2.5 cm). In FIG. **4A**, typically dimensions would be as follows: diameter of electrodes **232** is about 0.08 mm, distances **Y1** and **Y2** are each about 16 mm, distance **X1** is about 16 mm, distance **L** is about 10 mm, and electrode

11

heights **Z1** and **Z2** are each about 12 cm. The width **W** of electrodes **242** is preferably about 4 mm, and the thickness of the material from which electrodes **242** are formed is about 0.5 mm. Of course other dimensions and shapes could be used. It is preferred that electrodes **232** be small in diameter to help establish a desired high voltage field. On the other hand, it is desired that electrodes **232** (as well as electrodes **242**) be sufficiently robust to withstand occasional cleaning.

Electrodes **232** in first array **230** are coupled by a conductor **234** to a first (preferably positive) output port of high voltage pulse generator **170**, and electrodes **242** in second array **240** are coupled by a conductor **244** to a second (preferably negative) output port of generator **170**. It is relatively unimportant where on the various electrodes electrical connection is made to conductors **234** or **244**. Thus, by way of example FIG. **4B** depicts conductor **244** making connection with some electrodes **242** internal to bulbous end **246**, while other electrodes **242** make electrical connection to conductor **244** elsewhere on the electrode. Electrical connection to the various electrodes **242** could also be made on the electrode external surface providing no substantial impairment of the outflow airstream results.

It is preferred that at least electrode assembly **240** is readily removable from housing **102** for cleaning, e.g., removing accumulated particulate matter **60** from the electrode surfaces. Thus, housing **102** may be provided with a user-removable second array **240**, or the housing may include a break-away feature providing the user with access to the second array for such periodic cleaning as may be required.

Referring to the geometry of the electrodes shown in FIGS. **4A** and **4B**, and indeed in other configurations shown herein, the ratio of the effective electric field emanating radius of electrode **232** to the nearest effective radius of electrodes **242** is at least about 15:1, and preferably is at least 20:1. Thus, in the embodiment of FIG. **4A** and FIG. **4B**, the ratio $R2/R1 \approx 2 \text{ mm}/0.04 \text{ mm} \approx 50:1$. Other dimensions may be used in other configurations, but preferably a minimum $R2/R1$ ratio is maintain that is at least about 15:1.

In this and the other embodiments to be described herein, ionization appears to occur at the smaller electrode(s) **232** in the first electrode array **230**, with ozone production occurring as a function of high voltage arcing. For example, increasing the peak-to-peak voltage amplitude and/or duty cycle of the pulses from the high voltage pulse generator **170** can increase ozone content in the output flow of ionized air. If desired, user-control **S2** can be used to somewhat vary ozone content by varying (in a safe manner) amplitude and/or duty cycle. Specific circuitry for achieving such control is known in the art and need not be described in detail herein.

Note the inclusion in FIGS. **4A** and **4B** of at least one output controlling electrode **243**, preferably electrically coupled to the same potential as the second array electrodes. Electrode **243** preferably defines a pointed shape in side profile, e.g., a triangle. The sharp point on electrode(s) **243** causes generation of substantial negative ions (since the electrode is coupled to relatively negative high potential). These negative ions neutralize excess positive ions otherwise present in the output air flow, such that the OUT flow has a net negative charge. Electrode(s) **243** preferably are stainless steel, copper, or other conductor, and are perhaps 20 mm high and about 12 mm wide at the base although other shapes and/or dimensions could be used.

Another advantage of including pointed electrodes **243** is that they may be stationarily mounted within the housing of

12

unit **100**, and thus are not readily reached by human hands when cleaning the unit. Were it otherwise, the sharp point on electrode(s) **243** could easily cause cuts. The inclusion of one electrode **243** has been found sufficient to provide a sufficient number of output negative ions, but more such electrodes may be included.

The electrode configurations of FIGS. **4C** and **4D** will now be described. In the embodiment of FIGS. **4A** and **4C**, each "U"-shaped electrode **242** has two trailing edges that promote efficient kinetic transport of the outflow of ionized air and O_3 . Note the inclusion on at least one portion of a trailing edge of a pointed electrode region **243'**. Electrode region **243'** helps promote output of negative ions, in the same fashion as was described with respect to FIGS. **4A** and **4B**. Note, however, the higher likelihood of a user cutting himself or herself when wiping electrodes **242** with a cloth or the like to remove particulate matter deposited thereon. In FIG. **4C** and the figures to follow, the particulate matter is omitted for ease of illustration. However, from what was shown in FIGS. **2A-4B**, particulate matter will be present in the incoming air, and will be substantially absent from the outgoing air. As has been described, particulate matter **60** typically will be electrostatically precipitated upon the surface area of electrodes **242**.

Note that the embodiments of FIGS. **4C** and **4D** depict somewhat truncated versions of electrodes **242**. Whereas dimension **L** in the embodiment of FIGS. **4A** and **4B** was about 10 mm, in FIGS. **4C** and **4D**, **L** has been shortened to about 5 mm. Other dimensions in FIG. **4C** preferably are similar to those stated for FIGS. **4A** and **4B**. In FIGS. **4C** and **4D**, the inclusion of point-like regions **246** on the trailing edge of electrodes **242** seems to promote more efficient generation of ionized air flow. It will be appreciated that the configuration of second electrode array **240** in FIG. **4C** can be more robust than the configuration of FIGS. **4A** and **4B**, by virtue of the shorter trailing edge geometry. As noted earlier, a symmetrical staggered geometry for the first and second electrode arrays is preferred for the configuration of FIG. **4C**.

In the embodiment of FIG. **4D**, the outermost second electrodes, denoted **242-1** and **242-2**, have substantially no outermost trailing edges. Dimension **L** in FIG. **4D** is preferably about 3 mm, and other dimensions may be as stated for the configuration of FIGS. **4A** and **4B**. Again, the $R2/R1$ ratio for the embodiment of FIG. **4D** preferably exceeds about 20:1.

FIGS. **4E** and **4F** depict another embodiment of electrode assembly **220**, in which the first electrode array comprises a single wire electrode **232**, and the second electrode array comprises a single pair of curved "L"-shaped electrodes **242**, in cross-section. Typical dimensions, where different than what has been stated for earlier-described embodiments, are $X1 \approx 12 \text{ mm}$, $Y1 \approx 6 \text{ mm}$, $Y2 \approx 5 \text{ mm}$, and $L1 \approx 3 \text{ mm}$. The effective $R2/R1$ ratio is again greater than about 20:1. The fewer electrodes comprising assembly **220** in FIGS. **4E** and **4F** promote economy of construction, and ease of cleaning, although more than one electrode **232**, and more than two electrodes **242** could of course be employed. This embodiment again incorporates the staggered symmetry described earlier, in which electrode **232** is equidistant from two electrodes **242**.

FIGS. **4G** and **4H** shown yet another embodiment for electrode assembly **220**. In this embodiment, first electrode array **230** is a length of wire **232**, while the second electrode array **240** comprises a pair of rod or columnar electrodes **242**. As in embodiments described earlier herein, it is

13

preferred that electrode 232 be symmetrically equidistant from electrodes 242. Wire electrode 232 is preferably perhaps 0.08 mm tungsten, whereas columnar electrodes 242 are perhaps 2 mm diameter stainless steel. Thus, in this embodiment the R2/R1 ratio is about 25:1. Other dimensions may be similar to other configurations, e.g., FIGS. 4E, 4F. Of course electrode assembly 220 may comprise more than one electrode 232, and more than two electrodes 242.

An especially preferred embodiment is shown in FIGS. 4I-4K, and to a lesser extent FIG. 4L as well. Referring now to FIG. 4I, the upstream or first electrode array 230 comprises first and second pin-like or pointed electrodes 232, downstream substantially co-axial from which are disposed first and second annular-like electrodes 242 in the second electrode array 240. Note that the first array electrodes 232 may be pointed, or pin-like, or cone-like and that more than one first array electrode 232, 232' may be provided for a single second array electrode 242. Preferably each second array electrode 242 has a smoothly rounded inner opening 246. The surface of electrode 242 that faces electrode 232 will transition smoothly and continuously into this opening to form a collar region 247, best seen in FIGS. 4J-4N. The material comprising second array electrode 242 surrounds this opening, which preferably is coaxial with and downstream from the pointed end or tapered end of electrode 232.

Note that particulate matter 60 will be electro-kinetically transported towards and will tend to electrostatically adhere to the surface of electrodes 242 facing upstream, e.g., towards pointed electrodes 232. Preferably electrodes 232 are tungsten, and electrodes 242 are stainless steel. In the various electrode embodiments described herein, the upstream electrodes 232 preferably will be tungsten as this material can sustain high temperature associated with ionization. By contrast, the downstream electrodes 242 typically are machined or fabricated and will be made from a material more workable than tungsten, yet durable, stainless steel being a preferred such material.

FIG. 4I also depicts member 112 disposed adjacent a downstream region of the electrode array, preferably downstream from second electrodes 242. By forming member 112 with an annular opening 113. Member 112 has a length Lt of about 1" (2.5 cm) and the annular opening has a diameter of perhaps 0.5" (1.2 cm). In the preferred embodiment, the diameter of the annular opening in member 112 is greater than the diameter D' (about 0.375" or 9.5 mm) of the opening 249 formed in electrodes 242. If Porex™ material or similar moisture-containing material is used and is saturated with water, humidity of the airstream exiting the present invention may be increased by about 10% to about 20% compared to ambient air. In an aircraft cabin environment where ambient air is especially dry (as well as being stale and perhaps germ laden), the ability of a user to generate and breath clean air with ozone and increased humidity can make air travel or car travel more enjoyable. As noted, member 112 may also or instead be moistened with medication, e.g., for an asthmatic user, or may include a scent improving chemical to enhance the aroma of the output air.

Referring briefly to FIG. 2D, member 41 is a cylinder of preferably Porex™ material 112 inserted from the rear (with electrode 242 temporarily removed) within plastic cylinder 131 of housing portion 125. Housing member 125 is user-removable from the rest of the housing, whereupon material 112 may be wet with water, medication, scent material, etc. after which housing member 125 is joined to the remainder of the housing.

Typical dimensions for the embodiment of FIGS. 4I-4N are L1≈10 mm, X1≈9.5 mm, T≈0.5 mm, and the diameter of

14

opening 246 is about 12 mm. Dimension L1 preferably is sufficiently long that upstream portions of electrode 232 (e.g., portions to the left in FIG. 4I) do not interfere with the electrical field between electrode 232 and the collector electrode 242. However, as shown in FIG. 4J, the effective R2/R1 ratio is governed by the tip geometry of electrode 232. Again, in the preferred embodiment, this ratio exceeds about 15:1 and more preferably exceeds about 20:1. Lines drawn in phantom in FIGS. 4J-4N depict theoretical electric force field lines, emanating from emitter electrode 232, and terminating on the curved surface of collector electrode 246. Preferably the bulk of the field emanates within about ±45° of coaxial axis between electrode 232 and electrode 242. On the other hand, if the opening in electrode 242 and/or electrode 232 and 242 geometry is such that too narrow an angle about the coaxial axis exists, air flow will be unduly restricted.

One advantage of the ring-pin electrode assembly configuration shown in FIG. 4I is that the upstream-facing flat surface regions of annular-like electrode 242 provide sufficient surface area to which particulate matter 60 entrained in the moving air stream can attach, yet be readily cleaned. Further, the ring-pin type configuration shown in FIGS. 4I-4N advantageously can generate more ozone than prior art configurations, or the configurations of FIGS. 4A-4H. For example, whereas the configurations of FIGS. 4A-4H may generate perhaps 50 ppb ozone, the configuration of FIG. 4I can generate about 2,000 ppb ozone.

In FIG. 4J, a detailed cross-sectional view of the central portion of electrode 242 in FIG. 4I is shown. As best seen in FIG. 4J, curved region 246 adjacent the central opening 249 in electrode 242 forms a smooth transition between the planar regions of electrode 242 (whereon particulate matter tends to collect), and the collar region 247 through which the clean and ionized air flow passes in going through electrode 242. In FIG. 4K, collar region 247 is elongated relative to the embodiment of FIG. 4J, and the collar region in cross-section may be said to define a cylinder. Compare, for example, collar region 247 in FIG. 4L, which region in cross-section defines a converging cone, e.g., opposite surfaces of the region are not parallel but rather tend to converge, in a narrowed exit opening.

In the various embodiments shown in FIGS. 4I-4N, the relatively smooth and continuous transition between the planar surface of electrode 242 and the interior of the collar region aids the flow of air therethrough. Further, the continuous surface so defined provides an acceptably large surface area to which many ionization paths from the distal tip of electrode 232 have substantially equal path length. Thus, while the distal tip (or emitting tip) of electrode 232 is pointed or sharp and is advantageously small to concentrate the electric field between the electrode arrays, the adjacent regions of electrode 242 preferably provide many equidistant inter-electrode array paths. A high exit flowrate of perhaps 90 feet/minute and 2,000 ppb range ozone emission attainable with the configurations of FIGS. 4I-4M confirm a high operating efficiency.

FIG. 4M is a cross-section of a portion of the cylindrical portion 131 of front housing member 125 showing the relationship between the preferably plastic housing portion 131, the moisture-retaining cylinder of material 112 within this housing portion, and a lipped annular electrode 160 that is adhesively attached to the rearmost (e.g., facing pin-like electrode 232) section of housing portion 131. The user need only remove housing portion 125 from the remainder of the housing, run water or other liquid through port opening 106 to thoroughly wet material 112, and then re-insert housing

15

portion **125** into the remainder of housing **102**. Housing portion **125** is retained within housing **102** by a spring-loaded mechanism that the user can release with a sliding mechanism on the lower surface of housing **102** (not shown in FIG. 2D for clarity) when necessary. Once well wet with water (or other liquid), member **112** will act to increase humidity of clear air output by the present invention for an hour or two before it is necessary to re-moisten member **112**.

In FIG. 4N, one or more pointed electrodes **232** is replaced by a conductive block **232**" of carbon fibers, the block having a distal surface in which projecting fibers **233-1, . . . 233-N** take on the appearance of a "bed of nails". The projecting fibers can each act as an emitting electrode and provide a plurality of emitting surfaces. Over a period of time, some or all of the electrodes will literally be consumed, whereupon graphite block **232**" will be replaced. Materials other than graphite may be used for block **232**" providing the material has a surface with projecting conductive fibers such as **233-N**.

It will be appreciated that applicants' first array pin-like or pointed electrodes may be utilized with the second array electrodes of FIGS. 4A-4H if desired. Further, applicants' second array annular ring-like electrodes may be utilized with the first array electrodes of FIGS. 4A-4H. For example, in modifications of the embodiments of FIGS. 4A-4H, each wire or columnar electrode **232** is replaced by a column of electrically series-connected pin electrodes (e.g., as shown in FIGS. 4I-4K), while retaining the second electrode arrays as depicted in these figures. By the same token, in other modifications of the embodiments of FIGS. 4A-4H, the first array electrodes can remain as depicted, but each of the second array electrodes **242** is replaced by a column of electrically series-connected ring electrodes (e.g., as shown in FIGS. 4I-4K).

As described, the net output of ions is influenced by placing a bias element (e.g., element **243**) near the output stream and preferably near the downstream side of the second array electrodes. If no ion output were desired, such an element could achieve substantial neutralization. It will also be appreciated that the present invention could be adjusted to produce ions without producing ozone, if desired. In practice, increasing humidity of the output air by using a moistened member **112** will tend to decrease ozone content somewhat.

In summary, when operated from internal batteries, the present invention can provide several hours of clean air with safe amounts of ozone and, if desired, an increase in humidity of perhaps 10% to 20%. If desired, the air outflow may be augmented with other than water, for example an inhalant or other substance. If desired, the invention may be powered from an external source such as a motor vehicle 12 V battery. While the preferred embodiment includes two pair of electrodes, it will be appreciated that the present invention may be implemented with more or fewer electrodes.

Modifications and variations may be made to the disclosed embodiments without departing from the subject and spirit of the invention as defined by the following claims.

What is claimed is:

1. A personal electro-kinetic air transporter-conditioner device, comprising:

a portable housing defining an intake vent and an outlet vent;

a self-container ion generator disposed in said housing, said ion generator including:
an electrode assembly comprising a first electrode and a second electrode; and

16

a high voltage generator that provides a voltage difference between said first electrode and said second electrode; and

a moisture retaining material adjacent said outlet vent;

wherein said first electrode includes a base and an apex, said base being wider than said apex, and said apex aimed generally toward said second electrode;

wherein said second electrode includes at least one electrically conductive member through which there is defined an opening disposed generally in front of said apex,

wherein said ion generator produces an air flow from said intake vent to said outlet vent,

wherein said moisture retaining material increases humidity of said air flow; and

wherein said moisture retaining material includes a further opening disposed generally in front of said opening of said second electrode.

2. A personal electro-kinetic air transporter-conditioner device, comprising:

a portable housing defining an intake vent and an outlet vent;

a self-container ion generator disposed in said housing, said ion generator including:

an electrode assembly comprising a first electrode and a second electrode; and

a high voltage generator that provides a voltage difference between said first electrode and said second electrode; and

a moisture retaining material adjacent said outlet vent;

wherein said ion generator produces an air flow from said intake vent to said outlet vent;

wherein said moisture retaining material increases humidity of said air flow;

wherein said first electrode is located closer to the intake vent than is said second electrode;

wherein said second electrode is located closer to the outlet vent than is said first electrode; and

wherein said moisture retaining material is located between said second electrode and said outlet vent.

3. The device of claim 2, wherein said moisture retaining material has a generally cylindrical shape through which a further opening is defined.

4. The device of claim 3, wherein a diameter of said further opening defined in said moisture retaining material is greater than a diameter of said opening of said second electrode.

5. The device of claim 4, wherein said high voltage generator outputs a signal having a duty cycle between about 10% to about 100%.

6. A personal transporter-conditioner, comprising:

a portable housing;

a self-container ion generator disposed in said housing that produces an air flow from said intake vent to said outlet vent;

a container retaining at least one small object, wherein vibrations cause said small object to move within said container and generate noise; and

a transducer to detect noise and that is generated when said small object moves within said container;

wherein said ion generator turns-on in response to said transducer detecting noise.

7. The device of claim 6, further comprising a moisture retaining material that increases humidity of said air flow.

8. The device of claim 6, wherein after being turned-on in response to said transducer detecting noise, said ion generator turns off after being on for a predetermined amount of time.

17

9. The device of claim 6, further comprising a moisture holder that increases humidity of said air flow.

10. A personal transporter-conditioner device, comprising:

a portable housing;

a self-container ion generator disposed in said housing that produces an air flow from said intake vent to said outlet vent;

a container retaining at least one small object, wherein vibrations cause said small object to move within said container and generate force; and

a transducer to detect force and that is generated when said small object moves within said container;

wherein said ion generator turns-on in response to said transducer detecting force.

11. The device of claim 10, further comprising a moisture retaining material that increases humidity of said air flow.

12. The device of claim 10, wherein after being turned-on in response to said transducer detecting force, ion generator turns off after being on for a predetermined amount of time.

13. The device of claim 10, further comprising a moisture holder that increases humidity of said air flow.

14. A personal transporter-conditioner device, comprising:

a portable housing;

a self-container ion generator disposed in said housing that produces an air flow from said intake vent to said outlet vent;

a container retaining at least one small object, wherein vibrations cause said small object to move within said container and generate at least one of noise and force; and

a transducer to detect at least one of noise and force and that is generated when said small object moves within said container;

wherein said ion generator turns-on in response to said transducer detecting at least one of noise and force.

15. The device of claim 14, further comprising a moisture retaining material that increases humidity of said air flow.

16. The device of claim 14, wherein after being turned-on in response to said transducer detecting at least one of noise and force, said ion generator turns off after being on for a predetermined amount of time.

17. The device of claim 14, further comprising a moisture holder that increases humidity of said air flow.

18. A personal electro-kinetic air transporter-conditioner device, comprising:

a portable housing defining an intake vent and an outlet vent;

a self-container ion generator disposed in said housing that produces an air flow from said intake vent to said outlet vent;

said housing including a detachable front member that includes said outlet vent; and

18

a moisture retaining material also included in said detachable front member;

wherein said detachable front member can be removed from said portable housing to allow said moisture retaining material to be easily wetted; and

wherein said moisture retaining material increases the humidity of the air flow exiting said outlet vent.

19. A personal electro-kinetic air transporter-conditioner device, comprising:

a portable housing defining an intake vent and an outlet vent;

a self-container ion generator disposed in said housing, said ion generator including:

an electrode assembly comprising a first electrode and a second electrode; and

a high voltage generator that provides a voltage difference between said first electrode and said second electrode; and

a cord attached to said housing and forming a loop that enables said housing to be suspended from a neck of a user;

said housing including a detachable front member that includes said outlet vent; and

a moisture retaining material also included in said detachable front member;

wherein said detachable front member can be removed from said portable housing to allow said moisture retaining material to be easily wetted; and

wherein said ion generator produces an air flow from said intake vent to said outlet vent toward.

20. The device of claim 19, wherein said moisture retaining material increases humidity of said air flow.

21. The device of claim 20, wherein said moisture retaining material can, be wet with at least one of water, medication and scent.

22. A personal electro-kinetic air transporter-conditioner device, comprising:

a portable housing defining an intake vent and an outlet vent;

a self-container ion generator disposed in said housing that produces an air flow from said intake vent to said outlet vent;

said housing including a detachable front member that includes said outlet vent; and

a moisture holder also included in said detachable front member;

wherein said detachable front member can be removed from said portable housing to provide easy access to said moisture holder; and

wherein said moisture holder increases the humidity of the air flow exiting said outlet vent.

* * * * *