TUPLES MCQ

1.Tuples are _____
(a) Mutable (b) Immutable
(c) Mutable to some extent (d) None of the above

2.Which of the following is a Python tuple?
a) [1, 2, 3 b) (1, 2, 3)
c) {1, 2, 3} d) {}

3.Tuples can contain elements of any data type.(T/F)
a. True b. False

4.Suppose t = (1, 2, 4, 3), which of the following is incorrect?
a) print(t[3]) b) t[3] = 45
c) print(max(t)) d) print(len(t))

5.What will be the output of the following Python code?

```
t=(1,2,4,3)
t[1:3]
```

a) (1, 2) b) (1, 2, 4)
c) (2, 4) d) (2, 4, 3)

6. What will be the output of the following Python code?

```
t=(1,2,4,3)
t[1:-1]
```

a) (1, 2) b) (1, 2, 4)
c) (2, 4) d) (2, 4, 3)

7.What will be the output of the following Python code?

```
t = (1, 2)
2 * t
```

a) (1, 2, 1, 2) b) [1, 2, 1, 2]
c) (1, 1, 2, 2) d) [1, 1, 2, 2]

8.What will be the output of the following Python code?

```
t1 = (1, 2, 4, 3)
t2 = (1, 2, 3, 4)
t1 < t2
```

a) True b) False
c) Error d) None

9.What will be the output of the following Python code?

```
my_tuple = (1, 2, 3, 4)
my_tuple.append( (5, 6, 7) )
print len(my_tuple)
```

a) 1 b) 2
c) 5 d) Error

10. What is the data type of (1,)?
a) Tuple b) Integer
c) List d) Both tuple and integer

11. If a=(1,2,3,4), a[1:-1] is _____
a) Error, tuple slicing doesn't exist b) [2,3]
c) (2,3,4) d) (2,3)

12.What will be the output of the following Python code?

```
a=("Check",)*3
print(a)
```

a) ('Check','Check','Check') b) ('CheckCheckCheck')
d) Syntax error d) * Operator not valid for tuples

13.What will be the output of the following Python code?

```
a=(1,2,3,4)
del(a[2])
```

a) Now, a=(1,2,4) b) Now, a=(1,3,4)
c) Now a=(3,4) d) Error as tuple is immutable

14.What will be the output of the following Python code?

```
a=(2,3,4)
sum(a,3)
```

a) Too many arguments for sum() method
b) The method sum() doesn't exist for tuples
c) 12
d) 9

15.Is the following Python code valid?

```
a=(1,2,3,4)
del a
```

a) No because tuple is immutable
b) Yes, first element in the tuple is deleted
c) Yes, the entire tuple is deleted
d) No, invalid syntax for del method

16.In tuples values are enclosed in_____
a. Square brackets b. Curly brackets
c. Parenthesis d. None of the above

17.Write the output of the following.

```
A = tuple("Python")
print(A)
```

a. (python) b. ("Python")
c. ('P' , 'y' , 't' , 'h' , 'o' , 'n') d. None of the above

18.len( ) function returns the number of elements in tuple.(T/F)

a. True b. False

19.Write the output of the following:

```
A = list(tuple("Python"))
print(A)
```

a. ('P', 'y', 't', 'h', 'o', 'n') b. ['P', 'y', 't', 'h', 'o', 'n']
c. none of the above d. Error

20.Write the output of the following.

```
a=(23,34,65,20,5)
print(a[0]+a.index(5))
```

a. 28 b. 29
c. 27 d. 26

21.Which of the following is not a function of tuple?

a. update( ) b. min( )
c. max( ) d. count( )

22.Write the output of the following:

```
a=(23,34,65,20,5)
s=0
for i in a:
    if i%2==0:
        s=s+a[i]
print(s)
```

a. 54 b. 93
c. 94 d. Error

23. Write the output of the following:

```
a=(1, 2, 3, 2, 3, 4, 5)
print(min(a) + max(a) + a.count(2))
```

a. 13 b. 6
c. 8 d. Error

24.Which of the following is/are features of tuple?

a. Tuple is immutable
b. Tuple is a sequence data type.
c. In tuple, elements are enclosed in Parenthesis.
d. All of the above

25.Which of the following is not a tuple?

a. P = 1,2,3,4,5 b. Q = ('a', 'b', 'c')
c. R = (1, 2, 3, 4) d. None of the above

26.Which of the following statement will create an empty tuple?

a. P = ( ) b. Q = tuple( )
c. Both of the above d. None of the above

27. Which of the following is a tuple with single element?

a. t = (1,) b. t = 1,
c. Both of the above d. None of the above

28. Write the output of the following:

```
t = (1)
type(t)
```

a. <class 'int'> b. <class 'float'>
c. <class 'tuple'> d. <class 'list'>

29. What is the length of the given tuple?

```
t1=(1,2,(3,4,5))
```

a. 1 b. 2
c. 3 d. 4

30.Write the output of the following:

```
t1 = (1,2,3,4,5)
t2=t1
t2
```

a. Error b. (1,2,3,4,5)
c. 1,2,3,4,5 d. [1,2,3,4,5]

31.Write the output of the following:

```
t1= ('a', 'b')
t2 = (1,2,3)
t2+t1
```

a. ('a', 'b', 1, 2, 3) b. (1, 2, 3, 'a', 'b')
c. (1, 'a', 2, 'b', 3) d. None of the above

32.Which of the following statement will return an error. T1 is a tuple.

a. T1 + (23) b. T1 + [3]
c. Both of the above d. None of the above

33.Which mathematical operator is used to replicate a tuple?

a. Addition b. Multiplication
c. Exponent d. Modulus

34.Write the output of the following:

```
t1 = (23, 45, 67, 43, 21, 41)
print(t1[1:2])
```

a. (45) b. (45,)
c. (45, 67) d. None of the above

35.Write the output of the following:

```
t1 = ('1', '2', '3', '4', '5')
print(t1 + tuple("tuple"))
```

a. ('1', '2', '3', '4', '5', 't', 'u', 'p', 'l', 'e')
b. ('1', '2', '3', '4', '5', 'tuple')
c. Error d. None of the above

36.Which function returns the length of tuple?
a. length( ) b. len( )
c. size( ) d. None of the above

37.Write the output of the following :
```
t1 = (1,2)
t2 = (2,1)
t1 == t2
```
a. True b. False
c. Error d. None of the above

38.Write the output of the following :
```
t1 = (1,2)
t2 = (1.0, 2.0)
t1 == t2
```
a. True b. False
c. Error d. None of the above

39.del t1 statement will delete the tuple named 't1'.(T/F)
a. True b. False

40.What type of error is shown by following statement?
```
t1 =(1, 2)
t2
```
a. ValueError b. TypeError
c. NameError d. None of the above

41. Write the output of the following.
```
t1=((1,2),(3,4),(9,))
max(t1)
```
a. 9 b. (9,)
c. (3,4) d. Error

42.min(t1) will return an error if the tuple t1 contains value of mixed data type.(T/F)
a. True b. False

43.Which of the following function return the frequency of particular element in tuple?
a. index( ) b. max( )
c. count( ) d. None of the above

44. Write the output of the following :
```
t1=(1,2,3,4,5,6,7)
t1[t1[1]]
```
a. 2 b. 1
c. 3 d. 4

45.Write the output of the following :
```
t1=(1,2,3,4,5,6,7)
t1[t1[1]] + t1[t1[-4]]
```
a. 8 b. 9
c. 6 d. 7

46. Write the output of :
```
tuple("ComputerScience").count("i")
```
a. 1 b. 2
c. 3 d. Error

47.Write the output of : `sorted(tuple("Amit"))`
a. ['t', 'i', 'm', 'A'] b. ['A', 'm', 'i', 't']
c. ['A', 'i', 'm', 't'] d. None of the above

48.Which of the following statement create tuple?
a. t1 = (1, 2, 3, 4) b. t1[1] = (1, 2, 3, 4)
c. Both of the above d. None of the above

49.Which of the following operation work on tuples?
a. Concatenation b. Slicing
c. Repetition d. All of the above

50.Write the output of the following:
```
(n1,n2)=tuple("25")
n2+n1
```
a. 7 b. 25
c. 52 d. Error

51.What is the length of given tuple?
```
((((1,2,3,4),'a','b'),'g',1,3),"Sonu")
```
a. 4 b. 3
c. 2 d. 1

52.Write the output of the following:
```
t1= ((101,"Amit",98), (102,"Geetu",95),
    (103,"Manoj",87),(104,"Sawan",79))
    str(st[2][2]) + str(st[3][2])
```
a. 193 b. 9587
c. 8779 d. 166

53.Which function takes tuple as argument?
a. max( ) b. min( )
c. sum( ) d. All of the above

54.Write the output of the following:
```
a=("Amit", "Sumit","Ashish","Sumanta")
print(max(a))
```
a. Sumanta b. Ashish
c. Sumit d. Amit

55.What type of error is returned by following code :
```
a=("Amit", "Sumit","Ashish","Sumanta")
print(a.index("Suman"))
```
a. SyntaxError b. ValueError
c. TypeError d. NameError

56.Write the output of the following :

```
a=(“Amit”, “Sumit”,”Ashish”,”Sumanta”)
print(a.index(“Sumit”)+4//3**2)
```

a. 2 b. 4
c. 1 d. 3

57.Write the output of the following:

```
a=(“Amit”,“Sumit”,”Ashish”,”Sumanta”)
print(a.count(“Sum”))
```

a. 1 b. 2
c. 0 d. Error

58.Write the output of the following :

```
a=("Amit", "Sumit","Ashish","Sumanta")
for i in a:
    print(len(i)**2)
```

a.
0
1
4
9

b.
16
25
36
49

c.
Error

d.
1
4
9
16

59.Write the output of the following:

```
a=(6,8,9,"Sumanta",1)
for i in a:
      print(str(i)*2)
```

a.
66
88
99
SumantaSumanta
11

b.
66
88
99
Error

c
Error

d.
66
88
99
SumantaSumanta
Error

60. Write the output of the following:

```
a="blog"
b=list(a)
c=tuple(b)
print(c)
```

a. Error b. [‘b’ , ‘l’ , ‘o’ , ‘g’]
c. (‘b’ , ‘l’ , ‘o’ , ‘g’) d. (blog)

61.Write the output of the following :

```
a=("Hello","How","are","you")
for i in a:
print(i,end=" ")
```

a. “Hello” , “How” , “are” , “you”
b. Hello , How , are , you
c. Hello How are you
d. Error

62.Write the output of the following:

```
a=("Hello","How","are","you")
for i in a:
    print(a.index(i),end=" ")
```

a. 0 1 2 3 b. “Hello” , “How” , “are” , “you”
c. Error d. 0 2 3

63.Write the output of the following:

```
a=(“Hello”,”How”,”are”,”you”)
b=list(a)
print(a==b)
```

a. SyntaxError b. ValueError
c. True d. False

64.Write the output of the following:

```
a=("Amita", "How", "are", "you", "a")
 for i in range(len(a)):
     if(a[i]=="a"):
         print(a[i])
```

a. Hello b. How
c. a d. you

65.To which of the following the “in” operator can be used to check if an item is in it?

a.Lists b.Dictionary
c.Tuples d.All of the above

66. Which of the following is a Python tuple?

a. [1, 2, 3] b.(1,2,3)
c.{1, 2, 3} d.{}

67.Suppose t = (1, 2, 4, 3), which of the following is incorrect?

a. print(t[3]) b.T[3] = 45
c.print(max(t)) d.print(len(t))

68. What will be the output of the following Python code?

```
t=(1,2,4,3)
t[1:3]
```

a. (1, 2) b.(1, 2, 4)
c. (2,4) d.(2, 4, 3)

69. What will be the output of the following Python code?

```
t=(1,2,4,3)
t[1:-1]
```

a. (1, 2) b.(1, 2, 4)
c. (2,4) d.(2, 4, 3)

70.What will be the output of the following Python code?

```
t = (1, 2, 4, 3, 8, 9)
[t[i] for i in range(0, len(t), 2)]
```

a. [2, 3, 9] b. [1, 2, 4, 3, 8, 9]
c. [1, 4, 8] d.(1, 4, 8)

71. What will be the output of the following Python code?

```
t = (1, 2)
2 * t
```

a.(1, 2, 1, 2) b. [1, 2, 1, 2]
c.(1, 1, 2, 2) d.[1, 1, 2, 2]

72. What will be the output of the following Python code?

```
t1 = (1, 2, 4, 3)
t2 = (1, 2, 3, 4)
t1 < t2
```

a.True b.False
c.Error d.None

LISTS MCQ

1.Which of the following commands will create a list?
a) list1 = list() b) list1 = [ ]
c) list1 = list([1, 2, 3]) d) all of above

2.What is the output when we execute **`list("hello")`**?
a) ['h', 'e', 'l', 'l', 'o'] b) ['hello']
c) ['llo'] d) ['olleh']

3.Suppose list L is **`['h','e','l','l','o']`**, what is **`len(L)?`**
a) 5 b) 4
c) None d) Error

4.Suppose list1 is **`[2445,133,12454,123]`**, what is **`max(list1)`**?
a) 2445 b) 133
c) 12454 d) 123

5.Suppose list1 is **`[3, 5, 25, 1, 3]`**, what is **`min(list1)`**?
a) 3 b) 5
c) 25 d) 1

6.Suppose list1 is **`[1, 5, 9],`** what is **`sum(list1)`**?
a) 1 b) 9
c) 15 d) Error

7.To shuffle the list(say list1) what function do we use?
a) list1.shuffle() b) shuffle(list1)
c) random.shuffle(list1) d) random.shuffleList(list1)

8.Suppose list1 is [4, 2, 2, 4, 5, 2, 1, 0], Which of the following is correct syntax for slicing operation?
a) print(list1[0]) b) print(list1[:2])
c) print(list1[:-2]) d) all of the mentioned

9.Suppose list1 is [2,33,222,14,25], What is list1[:-1]?
a) [2, 33, 222, 14] b) Error
c) 25 d) [25, 14, 222, 33, 2]

10.What will be the output of the following Python code?

```
names=['Amir','Bear','Charlton','Daman']
print(names[-1][-1])
```

a) A b) Daman
c) Error d) n

11.What will be the output of the following Python code?

```
names1=['Amir','Bear','Charlton','Daman']
names2 = names1
names3 = names1[:]
names2[0] = 'Alice'
names3[1] = 'Bob'
sum = 0
for ls in(names1, names2, names3):
    if ls[0] == 'Alice':
        sum += 1
    if ls[1] == 'Bob':
        sum += 10
print sum
```

a) 11 b) 12
c) 21 d) 22

12.Suppose list1 is [1, 3, 2], What is **`list1*2`**?
a) [2, 6, 4] b) [1, 3, 2, 1, 3]
c) [1, 3, 2, 1, 3, 2] d) [1, 3, 2, 3, 2, 1]

13.Suppose list1 = [0.5 * x for x in range(0, 4)], list1 is:
a) [0, 1, 2, 3]
b) [0, 1, 2, 3, 4]
c) [0.0, 0.5, 1.0, 1.5]
d) [0.0, 0.5, 1.0, 1.5, 2.0]

14.What will be the output of the following Python code?

```
list1 = [11, 2, 23]
list2 = [11, 2, 2]
list1 < list2
```

a) True
b) False
c) Error
d) None

15.To add a new element to a list we use which command?
a) list1.add(5)
b) list1.append(5)
c) list1.addLast(5)
d) list1.addEnd(5)

16.To insert 5 to the third position in list1, we use which command?
a) list1.insert(3, 5)
b) list1.insert(2, 5)
c) list1.add(3, 5)
d) list1.append(3, 5)

17.To remove string “hello” from list1, we use which command?
a) list1.remove(“hello”)
b) list1.remove(hello)
c) list1.removeAll(“hello”)
d) list1.removeOne(“hello”)

18.Suppose list1 is [3, 4, 5, 20, 5], what is list1.index(5)?
a) 0
b) 1
c) 4
d) 2

19.Suppose list1 is [3, 4, 5, 20, 5, 25, 1, 3], what is **`list1.count(5)?`**
a) 0
b) 4
c) 1
d) 2

20.Suppose list1 is [3, 4, 5, 20, 5, 25, 1, 3], what is list1 after **`list1.reverse()?`**
a) [3, 4, 5, 20, 5, 25, 1, 3]
b) [1, 3, 3, 4, 5, 5, 20, 25]
c) [25, 20, 5, 5, 4, 3, 3, 1]
d) [3, 1, 25, 5, 20, 5, 4, 3]

21.Suppose listExample is [3, 4, 5, 20, 5, 25, 1, 3], what is list1 after **`listExample.extend([34, 5])`**?
a) [3, 4, 5, 20, 5, 25, 1, 3, 34, 5]
b) [1, 3, 3, 4, 5, 5, 20, 25, 34, 5]
c) [25, 20, 5, 5, 4, 3, 3, 1, 34, 5]
d) [1, 3, 4, 5, 20, 5, 25, 3, 34, 5]

22.Suppose listExample is [3, 4, 5, 20, 5, 25, 1, 3], what is list1 after **`listExample.pop(1)`**?
a) [3, 4, 5, 20, 5, 25, 1, 3]
b) [1, 3, 3, 4, 5, 5, 20, 25]
c) [3, 5, 20, 5, 25, 1, 3]
d) [1, 3, 4, 5, 20, 5, 25]

23.Suppose listExample is [3, 4, 5, 20, 5, 25, 1, 3], what is list1 after **`listExample.pop()?`**
a) [3, 4, 5, 20, 5, 25, 1]
b) [1, 3, 3, 4, 5, 5, 20, 25]
c) [3, 5, 20, 5, 25, 1, 3]
d) [1, 3, 4, 5, 20, 5, 25]

24.What will be the output of the following Python code?

```
"Welcome to Python".split()
```

a) [“Welcome”, “to”, “Python”]
b) (“Welcome”, “to”, “Python”)
c) {“Welcome”, “to”, “Python”}
d) “Welcome”, “to”, “Python”

25.What will be the output of the following Python code?

```
list("a#b#c#d".split('#'))
```

a) [‘a’, ‘b’, ‘c’, ‘d’]
b) [‘a b c d’]
c) [‘a#b#c#d’]
d) [‘abcd’]

26.What will be the output of the following Python code?

```
myList = [1, 2, 3, 4, 5, 6]
for i in range(1, 6):
    myList[i - 1] = myList[i]
for i in range(0, 6):
    print(myList[i], end = " ")
```

a) 2 3 4 5 6 1
b) 6 1 2 3 4 5
c) 2 3 4 5 6 6
d) 1 1 2 3 4 5

27.What will be the output of the following Python code?

```
list1 = [1, 3]
list2 = list1
list1[0] = 4
print(list2)
```

a) [1, 3]
b) [4, 3]
c) [1, 4]
d) [1, 3, 4]

28.What will be the output of the following Python code?

```
def f(values):
 values[0] = 44

v = [1, 2, 3]
f(v)
print(v)
```

a) [1, 44] b) [1, 2, 3, 44]
c) [44, 2, 3] d) [1, 2, 3]

29.What will be the output of the following Python code?

```
names1 = ['Amir', 'Bala', 'Chales']
if 'amir' in names1:
      print(1)
else:
      print(2)
```

a) None b) 1
c) 2 d) Error

30.What will be the output of the following Python code?

```
numbers = [1, 2, 3, 4]
numbers.append([5,6,7,8])
print(len(numbers))
```

a) 4 b) 5
c) 8 d) 12

31.To which of the following the "in" operator can be used to check if an item is in it?

a) Lists b) Dictionary
c) Tuple d) All of the mentioned

32.What will be the output of the following Python code?

```
list1 = [1, 2, 3, 4]
list2 = [5, 6, 7, 8]
print(len(list1 + list2))
```

a) 2 b) 4
c) 5 d) 8

33. What will be the output of the following Python code?

```
def addItem(listParam):
    listParam += [1]
 mylist = [1, 2, 3, 4]
 addItem(mylist)
print(len(mylist))
```

a) 1 b) 4
c) 5 d) 8

34.What will be the output of the following Python code?

```
veggies=['carrot','broccoli','potato','asparagus']
veggies.insert(veggies.index('broccoli'),'celery')
print(veggies)
```

a)['carrot','celery','broccoli','potato', 'asparagus']
b)['carrot', 'celery', 'potato', 'asparagus']
c)['carrot','broccoli','celery', 'potato','asparagus']
d)['celery','carrot', 'broccoli','potato','asparagus']

35.What will be the output of the following Python code?

```
data=[[[1,2],[3,4]],[[5,6],[7,8]]]
print(data[1][0][0])
```

a) 1 b) 2
c) 4 d) 5

36.What will be the output of the following Python code?

```
a=[10,23,56,[78]]
b=list(a)
a[3][0]=95
a[1]=34
print(b)
```

a) [10,34,56,[95]] b) [10,23,56,[78]]
c) [10,23,56,[95]] d) [10,34,56,[78]]

37. What will be the output of the following Python code?

```
lst=[3,4,6,1,2]
lst[1:2]=[7,8]
print(lst)
```

a) [3, 7, 8, 6, 1, 2] b) Syntax error
c) [3,[7,8],6,1,2] d) [3,4,6,7,8]

38.What will be the output of the following Python code?

```
a=[13,56,17]
a.append([87])
a.extend([45,67])
print(a)
```

a) [13, 56, 17, [87], 45, 67]
b) [13, 56, 17, 87, 45, 67]
c) [13, 56, 17, 87,[45, 67]]
d) [13, 56, 17, [87], [45, 67]]

39.What is the output of the following piece of code?

```
a=list((45,)*4)
print((45)*4)
print(a)
```

(a) 180
[(45),(45),(45),(45)]

(b) (45,45,45,45)
[45,45,45,45]
(c) 180
[45,45,45,45]
(d) Syntax Error

40.What will be the output of the following Python code?

```
word1="Apple"
word2="Apple"
list1=[1,2,3]
list2=[1,2,3]
print(word1 is word2)
print(list1 is list2)
```

(a) True
True
(b) False
True
(c) False
False
(d) True
False

41.What will be the output of the following Python code?

```
def change(var, lst):
    var = 1
    lst[0] = 44
k = 3
a = [1, 2, 3]
change(k, a)
print(k)
print(a)
```

(a) 3
[44,2,3]
(b) 1
[1,2,3]
(c) 3
[1,2,3]
(d) 1
[44,2,3]

DICTIONARY MCQ

1. Which of the following statements create a dictionary?

a. D = {}
b. D = {“john”:40, “peter”:45}
c. D = {40:”john”, 45:”peter”}
d. All of the mentioned

2. What will be the output of the following Python code?

```
d = {"john":40, "peter":45}
d["john"]
```

a. 40 b.45
c.“john” d.“peter”

3. What will be the output of the following Python code snippet?

```
d = {"john":40, "peter":45}
d.keys()
```

a. “john”, 40, 45, and “peter”
b. “john” and “peter”
c.40 and 45
d. D = (40:”john”, 45:”peter”)

4. What will be the output of the following Python code snippet?

```
d = {"john":40, "peter":45}
"john" in d
```

a.True b.False
c.None d. Error

5. Which of these about a dictionary is false?
   a. The values of a dictionary can be accessed using keys
   b. The keys of a dictionary can be accessed using values
   c. Dictionaries aren’t ordered
   d. Dictionaries are mutable

6. Which of the following is not a declaration of the dictionary?
   a. {1: ‘A’, 2: ‘B’}
   b. Dict([[1,”A”],[2,”B”]])
   c.{1,”A”,2”B”}
   d.{ }

7. What will be the output of the following Python code snippet?

```
a={1:"A",2:"B",3:"C"}
for i,j in a.items():
      print(i,j,end=" ")
```

a.1 A 2 B 3 C
b.1 2 3
c. A B C
d. 1:"A" 2:"B" 3:"C"

8. What will be the output of the following Python code snippet?

```
a={1:"A",2:"B",3:"C"}
print(a.get(1,4))
```

a.1 b.A
c.4 d.Invalid syntax for get method

9. What will be the output of the following Python code snippet?

```
a={1:"A",2:"B",3:"C"}
print(a.get(5,4))
```

a. Error, invalid syntax b. A
c. 5 d. 4

10. Which of the statements about dictionary values if false?

a.More than one key can have the same value
b.The values of the dictionary can be accessed as dict[key]
c.Values of a dictionary must be unique
d.Values of a dictionary can be a mixture of letters and numbers

11.What will be the output of the following Python code snippet?

```
a={1:"A",2:"B",3:"C"}
del a
```

a. Method del doesn't exist for the dictionary
b. Del deletes the values in the dictionary
c. Del deletes the entire dictionary
d. Del deletes the keys in the dictionary

12. If a is a dictionary with some key-value pairs, what does **`a.popitem()`** do?

a. Removes an arbitrary element
b. Removes all the key-value pairs
c. Removes the key-value pair for the key given as an argument
d. Invalid method for dictionary

13. What will be the output of the following Python code snippet?

```
d1 = {"john":40, "peter":45}
d2 = {"john":466, "peter":45}
d1 == d2
```

a) True b) False
c) None d) Error

14. What will be the output of the following Python code snippet?

```
d1 = {"john":40, "peter":45}
d2 = {"john":466, "peter":45}
d1 > d2
```

a) True b) False
c) Error d) None

15. Suppose **`d = {"john":40, "peter":45},`** to delete the entry for "john" what command do we use?

a) d.delete("john":40) b) d.delete("john")
c) del d["john"] d) del d("john":40)

16. Suppose **`d = {"john":40, "peter":45}.`** To obtain the number of entries in dictionary which command do we use?

a) d.size() b) len(d)
c) size(d) d) d.len()

17. What will be the output of the following Python code snippet?

```
d = {"john":40, "peter":45}
print(list(d.keys()))
```

a) ["john", "peter"] b) ["john":40, "peter":45]
c) ("john", "peter") d) ("john":40, "peter":45)

18. Suppose **`d = {"john":40, "peter":45}`**, what happens when we try to retrieve a value using the expression **`d["susan"]`**?

a) Since "susan" is not a value in the set, Python raises a Value exception
b) It is executed fine and no exception is raised, and it returns None
c) Since "susan" is not a key in the set, Python raises a KeyError exception
d) Since "susan" is not a key in the set, Python raises a syntax error

19. What will be the output of the following Python code snippet?

```
a={1:"A",2:"B",3:"C"}
print(a.setdefault(3))
```

a) {1: 'A', 2: 'B', 3: 'C'}
b) C
c) {1: 3, 2: 3, 3: 3}
d) No method called setdefault() exists for dictionary

20. What will be the output of the following Python code?

```
a={1:"A",2:"B",3:"C"}
b={4:"D",5:"E"}
a.update(b)
print(a)
```

a) {1: ‘A’, 2: ‘B’, 3: ‘C’}
b) Method update() doesn’t exist for dictionaries
c) {1: ‘A’, 2: ‘B’, 3: ‘C’, 4: ‘D’, 5: ‘E’}
d) {4: ‘D’, 5: ‘E’}

21. What will be the output of the following Python code?

```
a={1:"A",2:"B",3:"C"}
b=a.copy()
b[2]="D"
print(a)
```

a) Error, copy() method doesn’t exist for dictionaries
b) {1: ‘A’, 2: ‘B’, 3: ‘C’}
c) {1: ‘A’, 2: ‘D’, 3: ‘C’}
d) “None” is printed

22. What will be the output of the following Python code?

```
a={1:"A",2:"B",3:"C"}
a.clear()
print(a)
```

a) None
b) { None:None, None:None, None:None}
c) {1:None, 2:None, 3:None}
d) { }

23. Which of the following isn’t true about dictionary keys?

a) More than one key isn’t allowed
b) Keys must be immutable
c) Keys must be integers
d) When duplicate keys encountered, the last assignment wins

24. What will be the output of the following Python code?

```
a={1:5,2:3,3:4}
a.pop(3)
print(a)
```

a) {1: 5}
b) {1: 5, 2: 3}
c) Error, syntax error for pop() method
d) {1: 5, 3: 4}

25. What will be the output of the following Python code snippet?

```
total={}
def insert(items):
    if items in total:
        total[items] += 1
    else:
        total[items] = 1
insert('Apple')
insert('Ball')
insert('Apple')
print (len(total))
```

a) 3
b) 1
c) 2
d) 0

26. What will be the output of the following Python code snippet?

```
a = {}
a[1] = 1
a['1'] = 2
a[1]=a[1]+1
count = 0
for i in a:
    count += a[i]
print(count)
```

a) 1
b) 2
c) 4
d) Error, the keys can’t be a mixture of letters and numbers

27. What will be the output of the following Python code snippet?

```
numbers = {}
letters = {}
comb = {}
numbers[1] = 56
numbers[3] = 7
letters[4] = 'B'
comb['Numbers'] = numbers
comb['Letters'] = letters
print(comb)
```

a) Error, dictionary in a dictionary can’t exist
b) ‘Numbers’: {1: 56, 3: 7}
c) {‘Numbers’: {1: 56}, ‘Letters’: {4: ‘B’}}
d) {‘Numbers’: {1: 56, 3: 7}, ‘Letters’: {4: ‘B’}}

28. What will be the output of the following Python code snippet?

```
test = {1:'A', 2:'B', 3:'C'}
test = {}
print(len(test))
```

a) 0
b) None
c) 3
d) An exception is thrown

29. What will be the output of the following Python code snippet?

```
test = {1:'A', 2:'B', 3:'C'}
del test[1]
test[1] = 'D'
del test[2]
print(len(test))
```

a) 0
b) 2
c) Error as the key-value pair of 1:'A' is already deleted
d) 1

30. What will be the output of the following Python code snippet?

```
a = {}
a[1] = 1
a['1'] = 2
a[1.0]=4
count = 0
for i in a:
    count += a[i]
print(count)
```

a) An exception is thrown b) 3
c) 6 d) 2

31. What will be the output of the following Python code snippet?

```
a={}
a['a']=1
a['b']=[2,3,4]
print(a)
```

a) Exception is thrown b) {'b': [2], 'a': 1}
c) {'b': [2], 'a': [3]} d) {'b': [2, 3, 4], 'a': 1}

32. What will be the output of the following Python code?

```
count={}
count[(1,2,4)] = 5
count[(4,2,1)] = 7
count[(1,2)] = 6
count[(4,2,1)] = 2
tot = 0
for i in count:
    tot=tot+count[i]
print(len(count)+tot)
```

a) 25 b) 17
c) 16 d) Tuples can't be made keys of a dictionary

33. What will be the output of the following Python code?

```
a={}
a[2]=1
a[1]=[2,3,4]
print(a[1][1])
```

a) [2,3,4] b) 3
c) 2 d) An exception is thrown

34. What will be the output of the following Python code?

```
a={'B':5,'A':9,'C':7}
sorted(a)
```

a) ['A','B','C'] b) ['B','C','A']
c) [5,7,9] d) [9,5,7]

35. What will be the output of the following Python code?

```
a=dict()
a[1]
```

a) An exception is thrown since the dictionary is empty
b) ' '
c) 1
d) 0

36. Which of the following is correct with respect to above Python code?

```
d={"a":3,"b":7}
```

a). a dictionary d is created.
b). a and b are the keys of dictionary d.
c). 3 and 7 are the values of dictionary d
d). All of the above.

37. Which one of the following is correct?
a). In python, a dictionary can have two same keys with different values.
b). In python, a dictionary can have two same values with different keys
c). In python, a dictionary can have two same keys or same values but cannot have two same key-value pair
d). In python, a dictionary can neither have two same keys nor two same values.

38. What will be the output of above Python code?

```
d1={"abc":5,"def":6,"ghi":7}
print(d1[0])
```

a). abc b). 5
c). {"abc":5} d). Error

39. What will the above Python code do?

```
dict={"Phy":94,"Che":70,"Bio":82,"Eng":95}
dict.update({"Che":72,"Bio":80})
```

a) It will create new dictionary as dict={"Che":72,"Bio":80} and old dict will be deleted.
b) It will throw an error as dictionary cannot be updated.
c) It will simply update the dictionary as dict={"Phy":94,"Che":72,"Bio":80,"Eng":95}
d) It will not throw any error but it will not do any changes in dict

40. Which of the following will delete key_value pair for key="tiger" in dictionary?

```
dic={"lion":"wild","tiger":"wild",
     "cat":"domestic","dog":"domestic"}
```

a). del dic["tiger"] b). dic["tiger"].delete()
c). delete(dic.["tiger"]) d). del(dic.["tiger"])

41. Which of the following will give error?

```
Suppose dict1={"a":1,"b":2,"c":3}
```

a). print(len(dict1)) b). print(dict1.get("b"))
c). dict1["a"]=5 d). None of these.

42. Suppose the dictionary is

```
dict={"diary":1,"book":3,"novel":5}
```

Which of the following Python codes will give same output if

(i) dict.pop("book")
(ii) del dict["book"]
(iii) dict.update({"diary":1,"novel":5})

a) i,ii,iii b) i,ii
c) i, iii d) ii, iii

43. Which line of code correctly adds an item to the fruits dictionary with a key of 'grapes' and a value of 15?

```
fruits = {'apples': 1, 'bananas': 4,
          'pears': 17, 'oranges': 14}
```

a) fruits['grapes'] b) fruits['grapes'] = 15
c) insert 'grapes' in fruits d) fruits[15] = 'grapes'

44. What will be the output of above Python code?

```
food={"Fruit":['Apple','Orange', 'Banana']}
food["Fruit"][2]= "Watermelon"
print(food)
```

(a) {"Fruit":['Apple','Orange','Banana','Watermelon']}
(b) {['Apple','Orange','Watermelon']}
(c) {"Fruit":['Apple','Orange','Watermelon']}
(d) {'Fruit'}

45. What will be the output of above Python code?

```
C={1:'R',2:'T',3:'Y',40:'B',25:'V'}
C.update({'60':'NE'})
print(C['60'])
```

(a) NE (b) 'NE'
(c) ' ' (d) Error