WORKSHEET 1- TUPLE

1. Fill up the blanks using the following words

(key ,heterogeneous , immutable homogeneous)

a) We generally use tuple for ……………………datatypes and list for ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, datatypes.
b) Since tuple are…………, iterating through tuple is faster than with list. So there is a slight performance boost.
c) Tuples that contain immutable elements can be used as ……………….for a dictionary. With list, this is not possible.

2. Which of the following is a Python tuple?

a. [1, 2, 3]
b. (1, 2, 3)
c. {1, 2, 3}
d. {}

3. Suppose t = (1, 2, 4, 3), which of the following is incorrect?

a. print(t[3])
b. t[3] = 45
c. print(max(t))
d. print(len(t))

4. What will be the output?

```
>>>t=(1,2,4,3)
>>>t[1:3]
```

a. (1, 2)
b. (1, 2, 4)
c. (2, 4)
d. (2, 4, 3)

5. What will be the output?

```
>>>t=(1,2,4,3)
>>>t[1:-1]
```

a. (1, 2)
b. (1, 2, 4)
c. (2, 4)
d. (2, 4, 3)

6. What will be the output?

```
 d = {"john":40, "peter":45}
```

```
d["john"]
```

---

a. 40
b. 45
c. "john"?
d. "peter"?

7. What will be the output?

```
>>>t = (1, 2)
>>>2 * t
```

---

a. (1, 2, 1, 2)
b. [1, 2, 1, 2]
c. (1, 1, 2, 2)
d. [1, 1, 2, 2]

8. What will be the output?

```
>>>my_tuple = (1, 2, 3, 4)
>>>my_tuple.append( (5, 6, 7) )
>>>print len(my_tuple)
```

---

a. 1
b. 2
c. 5
d. Error

9. What will be the output?

```
numberGames = {}
numberGames[(1,2,4)] = 8
numberGames[(4,2,1)] = 10
numberGames[(1,2)] = 12

sum = 0
for k in numberGames:
  sum += numberGames[k]

print len(numberGames) + sum
```

---

a. 30
b. 24
c. 33
d. 12

10. What will be the output?

```
numberGames = {}
numberGames[(1,2,4)] = 8
numberGames[(4,2,1)] = 10
numberGames[(1,2)] = 12
?
sum = 0
for k in numberGames:
    sum += numberGames[k]
?
print len(numberGames) + sum
```

---

a. 30
b. 24
c. 33
d. 12

11. What will be the output?

```
>>>t1 = (1, 2, 4, 3)
>>>t2 = (1, 2, 3, 4)
>>>t1 < t2
```

a)True

b)False

c)Error

d) None