

Lab 1: Implementing RBAC

Query

Query History

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

```
CREATE ROLE cashier_role;

CREATE USER Mike WITH PASSWORD 'Mike123';
CREATE USER Jon WITH PASSWORD 'Jon123';

GRANT cashier_role TO Mike;
GRANT cashier_role TO Jon;

GRANT SELECT ON film, staff TO cashier_role;
GRANT SELECT, INSERT ON payment TO cashier_role;

ALTER TABLE payment ENABLE ROW LEVEL SECURITY;
```

Data Output

Messages

Notifications

CREATE ROLE

Query returned successfully in 36 msec.

Query

Query History

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

```
CREATE ROLE cashier_role;

CREATE USER Mike WITH PASSWORD 'Mike123';
CREATE USER Jon WITH PASSWORD 'Jon123';

GRANT cashier_role TO Mike;
GRANT cashier_role TO Jon;

GRANT SELECT ON film, staff TO cashier_role;
GRANT SELECT, INSERT ON payment TO cashier_role;

ALTER TABLE payment ENABLE ROW LEVEL SECURITY;
```

Data Output

Messages

Notifications

```
CREATE ROLE

Query returned successfully in 36 msec.
```

✓ Query returned successfully in 36 msec. ✕

Query

Query History

1

CREATE ROLE cashier_role;

2

3

CREATE USER Mike WITH PASSWORD 'Mike123';

4

CREATE USER Jon WITH PASSWORD 'Jon123';

5

6

GRANT cashier_role TO Mike;

7

GRANT cashier_role TO Jon;

8

9

GRANT SELECT ON film, staff TO cashier_role;

10

GRANT SELECT, INSERT ON payment TO cashier_role;

11

12

13

ALTER TABLE payment ENABLE ROW LEVEL SECURITY;

14

15

Data Output

Messages

Notifications

GRANT ROLE

Query returned successfully in 45 msec.

✓ Query returned successfully in 45 msec. ✕

Query

Query History

AltF5

1

2

3

4

5

6

7

8

9

10

11

12

13

14

```
CREATE ROLE cashier_role;

CREATE USER Mike WITH PASSWORD 'Mike123';
CREATE USER Jon WITH PASSWORD 'Jon123';

GRANT cashier_role TO Mike;
GRANT cashier_role TO Jon;

GRANT SELECT ON film, staff TO cashier_role;
GRANT SELECT, INSERT ON payment TO cashier_role;

ALTER TABLE payment ENABLE ROW LEVEL SECURITY;
```

Data Output

Messages

Notifications

GRANT

Query returned successfully in 38 msec.

✓ Query returned successfully in 38 msec. ✕

Lab 2: Implementing RLS

11
12
13
14
15

```
ALTER TABLE payment ENABLE ROW LEVEL SECURITY;
```

Data Output Messages Notifications

ALTER TABLE

Query returned successfully in 36 msec.

✓ Query returned successfully in 36 msec. ✕

QueryQuery History

Execute query
AltF5

```
6 GRANT cashier_role TO Mike;
7 GRANT cashier_role TO Jon;
8
9 GRANT SELECT ON film, staff TO cashier_role;
10 GRANT SELECT, INSERT ON payment TO cashier_role;
11
12
13 ALTER TABLE payment ENABLE ROW LEVEL SECURITY;
14
15 CREATE POLICY isolation_cashier_payments ON payment
16 FOR SELECT
17 TO cashier_role
18 USING (
19     staff_id = (SELECT staff_id FROM staff WHERE LOWER(username) = current_user)
20 );
21
```

Data OutputMessagesNotifications

CREATE POLICY

Query returned successfully in 37 msec.

QueryQuery History

```
14
15 CREATE POLICY isolation_cashier_payments ON payment
16 FOR SELECT
17 TO cashier_role
18 USING (
19     staff_id = (SELECT staff_id FROM staff WHERE LOWER(username) = cur
20 );
21
22 SET ROLE Mike;
23 SELECT COUNT(*) FROM payment;
24
25 SET ROLE Jon;
26 SELECT COUNT(*) FROM payment;
```

Data OutputMessagesNotifications

≡+

📄

▼

📋

▼

🗑️

🗄️

⬇️

📈

SQL

Showing rows: 1 to 1

✎

Page No: 1 of 1

⏪⏩⏴⏵

	count bigint🔒
1	7292

Query Query History

```
14
15 CREATE POLICY isolation_cashier_payments ON payment
16 FOR SELECT
17 TO cashier_role
18 USING (
19     staff_id = (SELECT staff_id FROM staff WHERE LOWER(username) = cur
20 );
21
22 SET ROLE Mike;
23 SELECT COUNT(*) FROM payment;
24
25 SET ROLE Jon;
26 SELECT COUNT(*) FROM payment;
```

Data Output Messages Notifications



Showing rows: 1 to 1

Page No: 1 of 1



	count bigint
1	7305