

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     printf("Hello, World!");
5     return 0;
6 }
```

	Expected	Got	
✓	Hello, World!	Hello, World!	✓

```
1 #include<stdio.h>
2 int main()
3 {
4     char ch;
5     scanf("%c",&ch);
6     printf("%c",ch);
7     return 0;
8 }
```

	Input	Expected	Got	
✓	c	c	c	✓

Passed all tests! ✓

```

1  #include<stdio.h>
2  int main() {
3      int a,b;
4      float c,d;
5      scanf("%d%d",&a,&b);
6      scanf("%f%f",&c,&d);
7      printf("%d %d \n",a+b,a-b);
8      printf("%.1f %.1f",c+d,c-d);
9      return 0;
10 }

```

	Input	Expected	Got	
✓	10 4 4.0 2.0	14 6 6.0 2.0	14 6 6.0 2.0	✓
✓	20 8 0.0 1.0	28 12 12.0 1.0	28 12 12.0 1.0	✓

```
2 int main()
3 {
4     char name;
5     scanf("%c",&name);
6     printf("%c\n",name);
7     int m1,m2,m3;
8     scanf("%d%d%d",&m1,&m2,&m3);
9     int c=(m1+m2+m3)/3;
10    printf("%d\n",c);
11    return 0;
12 }
```

	Input	Expected	Got	
✓	A 3 4 6	A 4	A 4	✓
✓	T 7 3 8	T 6	T 6	✓

```

1 #include<stdio.h>
2 int main()
3 {
4     int a;
5     long b;
6     char c;
7     float d;
8     double e;
9     scanf("%d %ld %c %f %lf",&a,&b,&c,&d,&e);
10    printf("%d \n%ld \n%c \n%.3f \n%.9lf",a,b,c,d,e);
11    return 0;
12 }

```

	Input	Expected	Got	
✓	3 12345678912345 a 334.23 14049.30493	3 12345678912345 a 334.230 14049.304930000	3 12345678912345 a 334.230 14049.304930000	✓

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     char a;
5     int s;
6     scanf("%c",&a);
7     s=(int) a;
8     printf("%d\n",s);
9     printf("%c %c",s-1,s+1);
10    return 0;
11 }
```

	Input	Expected	Got	
✓	E	69 D F	69 D F	✓

```

1  #include<stdio.h>
2  int main()
3  {
4      int a;
5      long b;
6      char c;
7      float d;
8      double e;
9      scanf("%d %ld %c %f %lf",&a,&b,&c,&d,&e);
10     printf("%d \n%ld \n%c \n%.3f \n%.9lf",a,b,c,d,e);
11     return 0;
12 }

```

	Input	Expected	Got	
✓	3 12345678912345 a 334.23 14049.30493	3 12345678912345 a 334.230 14049.304930000	3 12345678912345 a 334.230 14049.304930000	✓