

[Flag question](#)**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int x,y;
5     scanf("%d %d",&x,&y);
6     if(x%10==y%10)
7     {
8         printf("true");
9     }
10    else
11    {
12        printf("false");
13    }
14 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n;
5     scanf("%d",&n);
6     if (n%2!=0)
7     {
8         printf("Weird");
9     }
10    if(n%2==0)
11    {
12        if (n>=2 && n<=5)
13        {
14            printf("Not Weird");
15        }
16        if(n>=6 && n<=20)
17        {
18            printf("Weird");
19        }
20        else
21        {
22            if(n>20)
23            {
24                printf("Not Weird");
25            }
26        }
27    }
28 }
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Question 3

Correct

Marked out of
7.00[Flag question](#)

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d %d %d",&a,&b,&c);
6     if(a>b && a>c)
7     {
8         if(a*a==b*b+c*c)
9         {
10             printf("yes");
```

```
5 scanf("%d %d %d",&a,&b,&c);
6 if(a>b && a>c)
7 {
8     if(a*a==b*b+c*c)
9     {
10         printf("yes");
11     }
12     else
13     {
14         printf("no");
15     }
16 }
17 if(b>a && b>c)
18 {
19     if(b*b==a*a+c*c)
20     {
21         printf("yes");
22     }
23     else
24     {
25         printf("no");
26     }
27 }
28 else
29 {
30     if(c*c==a*a+b*b)
31     {
32         printf("yes");
33     }
34     else
35     {
36         printf("no");
37     }
38 }
```

```
32     printf("yes");
33 }
34 else
35 {
36     printf("no");
37 }
38 }
39 }
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓

Finish review

```
2 int main()
3 {
4     int n;
5     scanf("%d",&n);
6     switch(n)
7     {
8         case 3:
9             printf("Triangle");
10            break;
11            case 4:
12                printf("Quadrilateral");
13                break;
14            case 5:
15                printf("Pentagon");
16                break;
17            case 6:
18                printf("Hexagon");
19                break;
20            case 7:
21                printf("Heptagon");
22                break;
23            case 8:
24                printf("Octagon");
25                break;
26            case 9:
27                printf("Nonagon");
28                break;
29            case 10:
30                printf("Decagon");
31                break;
32            default:
33                printf("The number of sides is not supported.");
34
```

```
22         break;
23     case 8:
24         printf("Octagon");
25         break;
26     case 9:
27         printf("Nonagon");
28         break;
29     case 10:
30         printf("Decagon");
31         break;
32     default:
33         printf("The number of sides is not supported.");
34
35 }
36 }
```

	Input	Expected	Got	
✓	3	Triangle	Triangle	✓
✓	7	Heptagon	Heptagon	✓
✓	11	The number of sides is not supported.	The number of sides is not supported.	✓

Passed all tests! ✓

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,x;
5     scanf("%d",&n);
6     x=n%12;
7     switch(x)
8     {
9         case 8:
10             printf("Dragon");
11             break;
12         case 9:
13             printf("Snake");
14             break;
15         case 10:
16             printf("Horse");
17             break;
18         case 11:
19             printf("Sheep");
20             break;
21         case 0:
22             printf("Monkey");
23             break;
24         case 1:
25             printf("Rooster");
26             break;
27         case 2:
28             printf("Dog");
29             break;
30         case 3:
31             printf("Pig");
32             break;
33         case 4:
34             printf("Rat");
```



```
36     case 5:  
37         printf("0x");  
38         break;  
39     case 6:  
40         printf("Tiger");  
41         break;  
42     case 7:  
43         printf("Hare");  
44         break;  
45  
46     }  
47 }
```

	Input	Expected	Got	
✓	2004	Monkey	Monkey	✓
✓	2010	Tiger	Tiger	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of

7.00

Positions on a chess board are identified by a letter and a number. The letter identifies the column, while the number identifies the row, as shown below:

```
1 #include<stdio.h>
2 int main()
3 {
4     int n;
5     char ch;
6     scanf("%c %d",&ch,&n);
7     if((n%2!=0 && ch%2!=0) || (n%2==0 && ch%2==0))
8         printf("The square is black.");
9     else if((n%2!=0 && ch%2==0) || (n%2==0 && ch%2!=0))
10        printf("The square is white.");
11    return 0 ;
12 }
```

	Input	Expected	Got	
✓	a 1	The square is black.	The square is black.	✓
✓	d 5	The square is white.	The square is white.	✓

Passed all tests! ✓

```
1 #include<stdio.h>
2 int isleapyear(int year)
3 {
4     if(year%4==0)
5
6         if (year%100==0)
7         {
8             if(year%400==0)
9                 return 1;
10
11             else
12                 return 0;
13         }
14         else
15             return 1;
16     }
17     else
18         return 0;
19 }
20 int main()
21 {
22     int day,month,year,dayofyear=0;
23     int dayinmonths[]={31,28,31,30,31,30,31,31,30,31,30,31};
24     scanf("%d %d %d",&day,&month,&year);
25     if (isleapyear(year))
26     {
27         dayinmonth[1]=29;
28     }
29     for(int i=0;i<month-1;i++)
30     {
31         dayofyear += daysinmonth[i];
32     }
33     dayofyear += day;
```

```
1 #include<stdio.h>
2 int main()
3 {
4     char shape;
5     int side1,side2;
6     scanf("%c %d %d",&shape,&side1,&side2);
7     int area;
8     switch(shape)
9     {
10     case 'R':
11         area=side1*side2;
12         break;
13     case 'S':
14         area=(side1*side2)/2;
15         break;
16     case 'T':
17         area=side1*side2;
18         break;
19     default :
20         area=0;
21     }
22     printf("%d\n",area);
23     return 0;
24 }
```

	Input	Expected	Got	
✓	T 10	200	200	✓

```
1 //REC100C\src\src101.c
2 int main()
3 {
4     int n;
5     char*days[]=
6     {"Sunday","Monday","Tuesday","Wednesday","Thursday","Friday","Saturday","Kryptonday","Coluday"}
7     scanf("%d",&n);
8     int arrival_day=(n%296)%10;
9     printf("%s\n",days[arrival_day]);
10    return 0;
11 }
```

	Input	Expected	Got	
✓	7	Kryptonday	Kryptonday	✓
✓	1	Monday	Monday	✓

Passed all tests! ✓