TObject

fUniqueID	kIsReferenced	kZombie
fBits	kHasUUID	kBitMask
fgDtorOnly	kCannotPick	kSingleKey
fgObjectStat	kNoContextMenu	kOverwrite
kCanDelete	kInvalidObject	kWriteDelete
kMustCleanup	kIsOnHeap	fgIsA
kObjInCanvas	kNotDeleted	

@~TObject	GetObjectInfo	operator new@[@]
MakeZombie	GetTitle	operator delete
DoError	HandleTimer	operator delete@[@]
TObject	Hash	operator delete
TObject	InheritsFrom	operator delete@[@]
operator=	InheritsFrom	SetBit
AppendPad	Inspect	SetBit
Browse	IsFolder	ResetBit
ClassName	IsEqual	TestBit
Clear	IsSortable	TestBits
Clone	IsOnHeap	InvertBit
Compare	IsZombie	Info
Copy	Notify	Warning
Delete	ls	Error
DistancetoPrimitive	Paint	SysError
Draw	Pop	Fatal
DrawClass	Print	AbstractMethod
DrawClone	Read	MayNotUse
Dump	RecursiveRemove	Obsolete
Execute	SaveAs	GetDtorOnly
Execute	SavePrimitive	SetDtorOnly
ExecuteEvent	SetDrawOption	GetObjectStat
FindObject	SetUniqueID	SetObjectStat
FindObject	UseCurrentStyle	Class
GetDrawOption	Write	Class_Name
GetUniqueID	Write	IsA
GetName	operator new	ShowMembers
GetIconName	operator new@[@]	
GetOption	operator new	

TMapFile

fFd	fWritable
fVersion	fSemaphore
fName	fhSemaphore
fTitle	fGetting
fOption	fWritten
fMmallocDesc	fSumBuffer
fBaseAddr	fSum2Buffer
fSize	fgMapAddress
fFirst	fgMmallocDesc
fLast	kDefaultMapSize
fOffset	fgIsA
fDirectory	
fBrowseList	

@~TMapFile	GetSize	
TMapFile	GetOption	
TMapFile	GetTitle	
TMapFile	GetFirst	
operator=	GetLast	
FindShadowMapFile	IsFolder	
InitDirectory	IsWritable	
Remove	OrgAddress	
Remove	Print	
SumBuffer	ls	
GetBestBuffer	cd	
CreateSemaphore	Add	
AcquireSemaphore	Update	
ReleaseSemaphore	Remove	
DeleteSemaphore	Remove	
MapToAddress	RemoveAll	
operator delete	Get	
Browse	Create	
Close	WhichMapFile	
GetBaseAddr	SetMapAddress	
GetBreakval	Class	
GetDirectory	Class_Name	
GetFd	IsA	
GetMmallocDesc	ShowMembers	
GetName		