

the value of π is 3.1416, and the function to read a table is `read.table()`.

```
rmnorm(10)

## [1] -0.56048 -0.23018 1.55871 0.07051 0.12929 1.71506
## [7] 0.46092 -1.26506 -0.68685 -0.44566
```

```
getOption("width")

## [1] 60

x = 1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1
```

```
getOption("width")

## [1] 60

x = 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1
```

You can also tell knitr not to touch your source code using the chunk option `tidy=FALSE`, so that you can format the source code in any way you want:

```
1 + 1 +
  1+1+
  1

## [1] 5

f = function() {
  paste('I want to break the line',
        'here!')
}
```

Compare the above chunk to the default behavior (`tidy=TRUE`):

```
1 + 1 + 1 + 1 + 1

## [1] 5

f = function() {
  paste("I want to break the line", "here!")
}
```

I only mentioned how to control the width of source code. For the width of output, it is much trickier; see <http://yihui.org/knitr/demo/output/>.