### ◆ Addons & Files

**`addons_path`** – Folders where Odoo looks for modules (default + custom).
**`data_dir`** – Where uploaded files (images, PDFs, attachments) are stored.

---

### ◆ Security

**`admin_passwd`** – Master password for creating/deleting databases.
**`db_sslmode`** – Controls secure (SSL) connection to PostgreSQL.

---

### ◆ Database Connection

**`db_host`** – Where the database server is (local or remote).
**`db_port`** – Database server port (default 5432).
**`db_user`** – PostgreSQL username Odoo uses.
**`db_password`** – Password for that database user.
**`db_name`** – Specific database Odoo should use.
**`dbfilter`** – Filters which databases appear in Odoo (used in multi-DB setups).

---

### ◆ Database Performance

**`db_maxconn`** – Max total database connections Odoo can open.
**`db_maxconn_gevent`** – Max DB connections for Gevent (live chat, long polling).
**`db_replica_host`** – Read-only replica database server (if used).
**`db_replica_port`** – Port of replica database.
**`db_template`** – Template DB used when creating a new database.

---

### ◆ Server / Network

**`http_interface`** – IP address Odoo listens on (`0.0.0.0` = all).
**`http_port`** – Port where Odoo runs in browser (e.g., 8069/8072/9019).
**`gevent_port`** – Port for live chat / long-polling service.

---

### ◆ Email

**`email_from`** – Default sender email for outgoing emails.
**`from_filter`** – Restricts allowed sender addresses.

---

### ◆ GeoIP

**`geoip_city_db`** – Path to GeoIP city database file.
**`geoip_country_db`** – Path to GeoIP country database file.

---

### ◆ Limits (Performance & Safety)

**`limit_memory_hard`** – Max memory per worker (hard stop).
**`limit_memory_soft`** – Memory limit where worker restarts safely.
**`limit_request`** – Requests a worker handles before restart.
**`limit_time_cpu`** – Max CPU time per request.
**`limit_time_real`** – Max real time per request.
**`limit_time_real_cron`** – Time limit for cron jobs.
**`limit_time_worker_cron`** – Worker time limit for cron tasks.

---

### ◆ Other

**`list_db`** – If `True`, users can see database list on login screen.
**`csv_internal_sep`** – Separator for multiple values inside one CSV field.

### ◆ Logging

**`log_db`** – Stores logs inside the database.
**`log_db_level`** – Log level for database logs (warning, info, debug).
**`log_handler`** – Controls how logs are handled (INFO, DEBUG, etc.).
**`log_level`** – Overall logging level for Odoo.
**`logfile`** – File where Odoo logs are saved.

---

### ◆ Cron / Background Jobs

**`max_cron_threads`** – Number of cron jobs that can run at the same time.

---

### ◆ System / Paths

**`osv_memory_count_limit`** – Memory record limit for old ORM system (rarely used now).
**`pg_path`** – Path to PostgreSQL tools (like pg_dump).
**`pidfile`** – File where Odoo stores its process ID.
**`pre_upgrade_scripts`** – Scripts to run before upgrading modules.
**`upgrade_path`** – Path where upgrade scripts are stored.

---

### ◆ Proxy & Reporting

**`proxy_mode`** – Enable if Odoo is behind Nginx/Apache reverse proxy.
**`reportgz`** – Compress PDF reports to reduce size.

---

### ◆ Screenshots / Testing

**`screencasts`** – Folder to store screen recordings (testing use).
**`screenshots`** – Folder to store screenshots (testing/debugging).

---

### ◆ Modules

**`server_wide_modules`** – Modules loaded globally (like `web`, `base`, `rpc`).

---

### ◆ Installation

**`skip_auto_install`** – Prevents automatic installation of some modules.
**`with_demo`** – If True, demo data is installed with modules.

---

### ◆ Email (Outgoing Mail Server)

**`smtp_server`** – Outgoing mail server address.
**`smtp_port`** – SMTP server port (25, 465, 587, etc.).
**`smtp_user`** – Username for SMTP login.
**`smtp_password`** – Password for SMTP login.
**`smtp_ssl`** – Use SSL for email sending.
**`smtp_ssl_certificate_filename`** – SSL certificate file path.
**`smtp_ssl_private_key_filename`** – SSL private key file path.

---

### ◆ Logging (System)

`syslog` – Sends logs to system log instead of file.

---

### ◆ Database Behavior

`transient_age_limit` – Time limit for temporary records before cleanup.

---

### ◆ Text Processing

`unaccent` – Improves searching by ignoring accents (é = e).

---

### ◆ Websocket / Live Features

`websocket_keep_alive_timeout` – Time before inactive websocket closes.
`websocket_rate_limit_burst` – Max burst messages allowed.
`websocket_rate_limit_delay` – Delay between websocket messages.

---

### ◆ Misc

`reportgz` – Compress generated reports.
`list_db` – Show database list on login screen.

### ◆ Demo Data

`with_demo` – If True, demo data is installed with modules.

---

### ◆ Workers

`workers` – Number of worker processes for handling requests (0 = single-thread mode).

---

### ◆ File Sending

`x_sendfile` – Lets web server (like Nginx) send files directly for better performance.