

# Password Authenticated Key Exchange: From Two Party Methods to Group Schemes

Stephen Melczer, Taras Mychaskiw, and Yi Zhang



# Introduction

1. Classical Two Party PAKEs
  - 1.1 Background and Security Properties
  - 1.2 J-PAKE
  - 1.3 Dragonfly
  - 1.4 PAK/PPK
2. Extension to Group Setting (GPAKEs)
  - 2.1 Fairy-Ring Dance
  - 2.2 Examples of GPAKEs
3. Timings
4. Conclusion

PART 1

Classical Two Party PAKEs

# Password Authenticated Key Exchange (PAKE)


PAKEs allow two parties sharing a *short/weak* password to establish a shared key

Cannot broadcast password directly – would need to be protected (expensive)

Instead, modern PAKEs use *zero-knowledge proof* and/or *hash* of password in protocol

# First Protocol: EKE (Bellare and Merritt 1992)


Pick prim. root  $\alpha \in \mathbb{Z}_p$



Alice and Bob share  $K = \alpha^{x_a \cdot x_b}$ .

# First Protocol: EKE (Bellare and Merritt 1992)

Pick prim. root  $\alpha \in \mathbb{Z}_p$




Alice and Bob share  $K = \alpha^{x_a \cdot x_b}$ .

Uses password directly  $\implies$  many insecurities found

# First Protocol: EKE (Bellare and Merritt 1992)

Pick prim. root  $\alpha \in \mathbb{Z}_p$



Alice and Bob share  $K = \alpha^{x_a \cdot x_b}$ .

Uses password directly  $\implies$  many insecurities found

Ex: Decypher  $[\alpha^{x_a}]_{s'}$  – rule out  $s'$  if output in  $[p, 2^n - 1]$

# Desired Security Properties

## **Offline dictionary attack resistance**

Don't leak info which can be used in brute force search

## **Forward secrecy for established keys**

Past keys secure if password disclosed

Implies passive attacker w/ password cannot compute key

## **Known session security**

All secrets of one session reveals nothing about others

## **Online dictionary attack resistance**

Attacker can only test one password per protocol execution



# J-PAKE

**Setup** Let  $G = \langle g \rangle$  be an order  $q$  subgroup of  $\mathbb{Z}_p^*$

Alice picks  $x_1 \in_R [0, q-1]$  and  $x_2 \in_R [1, q-1]$

Bob picks  $x_3 \in_R [0, q-1]$  and  $x_4 \in_R [1, q-1]$

# J-PAKE

**Setup** Let  $G = \langle g \rangle$  be an order  $q$  subgroup of  $\mathbb{Z}_p^*$

Alice picks  $x_1 \in_R [0, q-1]$  and  $x_2 \in_R [1, q-1]$

Bob picks  $x_3 \in_R [0, q-1]$  and  $x_4 \in_R [1, q-1]$

**Rd 1** Alice sends  $g^{x_1}, g^{x_2}$  and ZKPs of  $x_1$  and  $x_2$  to Bob

Bob sends  $g^{x_3}, g^{x_4}$  and ZKPs of  $x_3$  and  $x_4$  to Alice

[Alice and Bob verify ZKPs and  $g^{x_2}, g^{x_4} \neq 1$ ]

# J-PAKE

**Setup** Let  $G = \langle g \rangle$  be an order  $q$  subgroup of  $\mathbb{Z}_p^*$

Alice picks  $x_1 \in_R [0, q-1]$  and  $x_2 \in_R [1, q-1]$

Bob picks  $x_3 \in_R [0, q-1]$  and  $x_4 \in_R [1, q-1]$

**Rd 1** Alice sends  $g^{x_1}, g^{x_2}$  and ZKPs of  $x_1$  and  $x_2$  to Bob  
Bob sends  $g^{x_3}, g^{x_4}$  and ZKPs of  $x_3$  and  $x_4$  to Alice  
[Alice and Bob verify ZKPs and  $g^{x_2}, g^{x_4} \neq 1$ ]

**Rd 2** Alice sends  $A = g^{(x_1+x_3+x_4)x_2 \cdot s}$  and ZKP of  $x_2 s$   
Bob sends  $B = g^{(x_1+x_2+x_3)x_4 \cdot s}$  and ZKP of  $x_4 s$

# J-PAKE

**Setup** Let  $G = \langle g \rangle$  be an order  $q$  subgroup of  $\mathbb{Z}_p^*$

Alice picks  $x_1 \in_R [0, q-1]$  and  $x_2 \in_R [1, q-1]$

Bob picks  $x_3 \in_R [0, q-1]$  and  $x_4 \in_R [1, q-1]$

**Rd 1** Alice sends  $g^{x_1}, g^{x_2}$  and ZKPs of  $x_1$  and  $x_2$  to Bob

Bob sends  $g^{x_3}, g^{x_4}$  and ZKPs of  $x_3$  and  $x_4$  to Alice

[Alice and Bob verify ZKPs and  $g^{x_2}, g^{x_4} \neq 1$ ]

**Rd 2** Alice sends  $A = g^{(x_1+x_3+x_4)x_2 \cdot s}$  and ZKP of  $x_2 \cdot s$

Bob sends  $B = g^{(x_1+x_2+x_3)x_4 \cdot s}$  and ZKP of  $x_4 \cdot s$

They share

$$K = \underbrace{(B/g^{x_2x_4s})^{x_2}}_{\text{Computable by Alice}} = g^{(x_1+x_3)x_2x_4s} = \underbrace{(A/g^{x_2x_4s})^{x_4}}_{\text{Computable by Bob}} .$$

# J-PAKE

Satisfies all 4 desired properties  
(under DDH and CDH assumptions)

Only two rounds of communication

No *explicit* key confirmation (only implicit)

Not patented

# Dragonfly

Description of protocol

Security properties

# PAK/PPK – PAK

**Setup** Let  $G = \langle g \rangle$  be an order  $q$  subgroup of  $\mathbb{Z}_p^*$

Let  $p = rq + 1$  where  $r, q$  relatively prime.

Let  $\pi$  be the password and  $H_1, H_{2a}, H_{2b}, H_3$  be random, independent hash functions.

# PAK/PPK – PAK

**Setup** Let  $G = \langle g \rangle$  be an order  $q$  subgroup of  $\mathbb{Z}_p^*$

Let  $p = rq + 1$  where  $r, q$  relatively prime.

Let  $\pi$  be the password and  $H_1, H_{2a}, H_{2b}, H_3$  be random, independent hash functions.

## PAK

$A$

$B$

$$x \in_R \mathbb{Z}_q$$

$$m = g^x \cdot (H_1(A, B, \pi))^r$$

$$\xrightarrow{m}$$

$$\text{Test } m \stackrel{?}{\neq} 0 \pmod{p}$$

$$y \in_R \mathbb{Z}_q$$

$$\mu = g^y$$

$$\sigma = \left( \frac{m}{(H_1(A, B, \pi))^r} \right)^y$$

$$\sigma = \mu^x$$

$$\xleftarrow{\mu, k}$$

$$k = H_{2a}(A, B, m, \mu, \sigma, \pi)$$

$$\text{Test } k \stackrel{?}{=} H_{2a}(A, B, m, \mu, \sigma, \pi)$$

$$k' = H_{2b}(A, B, m, \mu, \sigma, \pi)$$

$$K = H_3(A, B, m, \mu, \sigma, \pi)$$

$$\xrightarrow{k'}$$

$$\text{Test } k' \stackrel{?}{=} H_{2b}(A, B, m, \mu, \sigma, \pi)$$

$$K = H_3(A, B, m, \mu, \sigma, \pi)$$



# PAK/PPK – PPK

**Setup** Let  $G = \langle g \rangle$  be an order  $q$  subgroup of  $\mathbb{Z}_p^*$

Let  $p = rq + 1$  where  $r, q$  relatively prime.

Let  $\pi$  be the password and  $H_1, H_3$  be random, independent hash functions.

# PAK/PPK – PPK

**Setup** Let  $G = \langle g \rangle$  be an order  $q$  subgroup of  $\mathbb{Z}_p^*$

Let  $p = rq + 1$  where  $r, q$  relatively prime.

Let  $\pi$  be the password and  $H_1, H_3$  be random, independent hash functions.

## PPK

$A$

$B$

$x \in_R \mathbb{Z}_q$

$$m = g^x \cdot (H_1(A, B, \pi))^r$$

$\xrightarrow{m}$

Test  $m \stackrel{?}{\neq} 0 \bmod p$

$y \in_R \mathbb{Z}_q$

$$\mu = g^y \cdot (H_1(A, B, \pi))^r$$

$$\sigma = \left( \frac{m}{(H_1(A, B, \pi))^r} \right)^y$$

Test  $\mu \stackrel{?}{\neq} 0 \bmod p$

$$\sigma = \left( \frac{\mu}{(H_1(A, B, \pi))^r} \right)^x$$

$$K = H_3(A, B, m, \mu, \sigma, \pi)$$

$\xleftarrow{\mu}$

$$K = H_3(A, B, m, \mu, \sigma, \pi)$$

# PAK/PPK

Proposes a new formal security model  
based on the random oracle model

Satisfies all 4 desired properties  
(under DDH assumptions)

Only two/three rounds of communication

PAK has explicit key confirmation  
PPK has implicit key confirmation

# PART 2

## Extension to Group Setting

# The Fairy-Ring Dance

Description of general procedure

How pairwise + group keys are constructed

# J-PAKE+

Description of J-PAKE+

Uses 3 rounds as J-PAKE does not have explicit key confirmation

# Dragonfly+

Description of Dragonfly+

PPK+

Description of PPK+



# PART 3


## Timings

# Specifications


Computer info + how timings done (Java version etc.)

# Results


Latency measurement in SPEKE




Latency measurement in JPAKE



Latency measurement in Dragonfly



Latency measurement in PPK



## Conclusion

# Conclusion

It is possible to transfer PAKEs into GPAKEs while preserving round efficiency

SPEKE+ is very slow

J-PAKE+ is a bit slow, but proven secure (under CDH)

PPK is faster but weaker security proof

Dragonfly is fastest, but no security proof  
(despite IEEE 802.11-2012 standard)

THANK YOU