

# Password Authenticated Key Exchange: From Two Party Methods to Group Schemes

Stephen Melczer, Taras Mychaskiw, and Yi Zhang



# Introduction

1. Classical Two Party PAKEs
  - 1.1 Background and Security Properties
  - 1.2 J-PAKE
  - 1.3 Dragonfly
  - 1.4 PAK/PPK
2. Extension to Group Setting (GPAKEs)
  - 2.1 Fairy-Ring Dance
  - 2.2 Examples of GPAKEs
3. Timings
4. Conclusion

# PART 1

## Classical Two Party PAKEs

# Password Authenticated Key Exchange (PAKE)


PAKEs allow two parties sharing a *short/weak* password to establish a shared key

Cannot broadcast password directly – would need to be protected (expensive)

Instead, modern PAKEs use *zero-knowledge proof* of password in protocol

# First Protocol: EKE (Bellare and Merritt 1992)


Pick prim. root  $\alpha \in \mathbb{Z}_p$



Alice and Bob share  $K = \alpha^{x_a \cdot x_b}$ .

# First Protocol: EKE (Bellare and Merritt 1992)

Pick prim. root  $\alpha \in \mathbb{Z}_p$




Alice and Bob share  $K = \alpha^{x_a \cdot x_b}$ .

Uses password directly  $\implies$  many insecurities found

# First Protocol: EKE (Bellare and Merritt 1992)

Pick prim. root  $\alpha \in \mathbb{Z}_p$



Alice and Bob share  $K = \alpha^{x_a \cdot x_b}$ .

Uses password directly  $\implies$  many insecurities found

Ex: Decypher  $[\alpha^{x_a}]_{s'}$  – rule out  $s'$  if output in  $[p, 2^n - 1]$

# Desired Security Properties

## **Offline dictionary attack resistance**

Don't leak info which can be used in brute force search

## **Forward secrecy for established keys**

Past keys secure if password disclosed

Implies passive attacker w/ password cannot compute key

## **Known session security**

All secrets of one session reveals nothing about others

## **Online dictionary attack resistance**

Attacker can only test one password per protocol execution



# J-PAKE

**Setup** Let  $G = \langle g \rangle$  be an order  $q$  subgroup of  $\mathbb{Z}_p^*$

Alice picks  $x_1 \in_R [0, q-1]$  and  $x_2 \in_R [1, q-1]$

Bob picks  $x_3 \in_R [0, q-1]$  and  $x_4 \in_R [1, q-1]$

# J-PAKE

**Setup** Let  $G = \langle g \rangle$  be an order  $q$  subgroup of  $\mathbb{Z}_p^*$

Alice picks  $x_1 \in_R [0, q - 1]$  and  $x_2 \in_R [1, q - 1]$

Bob picks  $x_3 \in_R [0, q - 1]$  and  $x_4 \in_R [1, q - 1]$

**Rd 1** Alice sends  $g^{x_1}, g^{x_2}$  and ZKPs of  $x_1$  and  $x_2$  to Bob

Bob sends  $g^{x_3}, g^{x_4}$  and ZKPs of  $x_3$  and  $x_4$  to Alice

[Alice and Bob verify ZKPs and  $g^{x_2}, g^{x_4} \neq 1$ ]

# J-PAKE

**Setup** Let  $G = \langle g \rangle$  be an order  $q$  subgroup of  $\mathbb{Z}_p^*$

Alice picks  $x_1 \in_R [0, q - 1]$  and  $x_2 \in_R [1, q - 1]$

Bob picks  $x_3 \in_R [0, q - 1]$  and  $x_4 \in_R [1, q - 1]$

**Rd 1** Alice sends  $g^{x_1}, g^{x_2}$  and ZKPs of  $x_1$  and  $x_2$  to Bob  
Bob sends  $g^{x_3}, g^{x_4}$  and ZKPs of  $x_3$  and  $x_4$  to Alice  
[Alice and Bob verify ZKPs and  $g^{x_2}, g^{x_4} \neq 1$ ]

**Rd 2** Alice sends  $A = g^{(x_1+x_3+x_4)x_2 \cdot s}$  and ZKP of  $x_2 s$   
Bob sends  $B = g^{(x_1+x_2+x_3)x_4 \cdot s}$  and ZKP of  $x_4 s$

# J-PAKE

**Setup** Let  $G = \langle g \rangle$  be an order  $q$  subgroup of  $\mathbb{Z}_p^*$

Alice picks  $x_1 \in_R [0, q-1]$  and  $x_2 \in_R [1, q-1]$

Bob picks  $x_3 \in_R [0, q-1]$  and  $x_4 \in_R [1, q-1]$

**Rd 1** Alice sends  $g^{x_1}, g^{x_2}$  and ZKPs of  $x_1$  and  $x_2$  to Bob

Bob sends  $g^{x_3}, g^{x_4}$  and ZKPs of  $x_3$  and  $x_4$  to Alice

[Alice and Bob verify ZKPs and  $g^{x_2}, g^{x_4} \neq 1$ ]

**Rd 2** Alice sends  $A = g^{(x_1+x_3+x_4)x_2 \cdot s}$  and ZKP of  $x_2 \cdot s$

Bob sends  $B = g^{(x_1+x_2+x_3)x_4 \cdot s}$  and ZKP of  $x_4 \cdot s$

They share

$$K = \underbrace{(B/g^{x_2x_4s})^{x_2}}_{\text{Computable by Alice}} = g^{(x_1+x_3)x_2x_4s} = \underbrace{(A/g^{x_2x_4s})^{x_4}}_{\text{Computable by Bob}} .$$

# J-PAKE

Satisfies all 4 desired properties  
(under DDH and CDH assumptions)

Only two rounds of communication

No *explicit* key confirmation (only implicit)

Not patented

# Dragonfly

**Setup** Let  $Q$  be a cyclic subgroup of  $\mathbb{Z}_p^*$  with prime order  $q$ .

Alice picks  $r_A, m_A \in_R \mathbb{Z}_q^*$

Bob picks  $r_B, m_B \in_R \mathbb{Z}_q^*$

# Dragonfly

**Setup** Let  $Q$  be a cyclic subgroup of  $\mathbb{Z}_p^*$  with prime order  $q$ .

Alice picks  $r_A, m_A \in_R \mathbb{Z}_q^*$

Bob picks  $r_B, m_B \in_R \mathbb{Z}_q^*$

**Rd 1** Alice sends  $s_A = r_A + m_A \pmod q$  and  $E_A = \pi^{-m_A} \pmod p$

Bob sends  $s_B = r_B + m_B \pmod q$  and  $E_B = \pi^{-m_B} \pmod p$

[Alice and Bob check that  $s_A \neq s_B$  or  $E_A \neq E_B$ ]

# Dragonfly

**Setup** Let  $Q$  be a cyclic subgroup of  $\mathbb{Z}_p^*$  with prime order  $q$ .

Alice picks  $r_A, m_A \in_R \mathbb{Z}_q^*$

Bob picks  $r_B, m_B \in_R \mathbb{Z}_q^*$

**Rd 1** Alice sends  $s_A = r_A + m_A \pmod q$  and  $E_A = \pi^{-m_A} \pmod p$

Bob sends  $s_B = r_B + m_B \pmod q$  and  $E_B = \pi^{-m_B} \pmod p$

[Alice and Bob check that  $s_A \neq s_B$  or  $E_A \neq E_B$ ]

**Rn 2** Alice computes  $ss = (\pi^{s_B} E_B)^{r_A} = \pi^{r_A r_B}$

Bob computes  $ss = (\pi^{s_A} E_A)^{r_B} = \pi^{r_A r_B}$

Alice sends  $H(ss|E_A|s_A|E_B|s_B)$

Bob sends  $H(ss|E_B|s_B|E_A|s_A)$

Each member confirms the hashes.



# Dragonfly

**Setup** Let  $Q$  be a cyclic subgroup of  $\mathbb{Z}_p^*$  with prime order  $q$ .

Alice picks  $r_A, m_A \in_R \mathbb{Z}_q^*$

Bob picks  $r_B, m_B \in_R \mathbb{Z}_q^*$

**Rd 1** Alice sends  $s_A = r_A + m_A \pmod q$  and  $E_A = \pi^{-m_A} \pmod p$

Bob sends  $s_B = r_B + m_B \pmod q$  and  $E_B = \pi^{-m_B} \pmod p$

[Alice and Bob check that  $s_A \neq s_B$  or  $E_A \neq E_B$ ]

**Rn 2** Alice computes  $ss = (\pi^{s_B} E_B)^{r_A} = \pi^{r_A r_B}$

Bob computes  $ss = (\pi^{s_A} E_A)^{r_B} = \pi^{r_A r_B}$

Alice sends  $H(ss|E_A|s_A|E_B|s_B)$

Bob sends  $H(ss|E_B|s_B|E_A|s_A)$

Each member confirms the hashes.

They share:

$$K = H(ss|E_A \times E_B|(s_A + s_B) \pmod q)$$

# Dragonfly

No formal security proofs, but claims resistance to offline dictionary attacks

Only two rounds of communication

Very fast compared to other protocols

# PAK/PPK

Description of protocol

Security properties

## PART 2

### Extension to Group Setting

# The Fairy-Ring Dance

Description of general procedure

How pairwise + group keys are constructed

# J-PAKE+

Description of J-PAKE+

Uses 3 rounds as J-PAKE does not have explicit key confirmation

# Dragonfly+

Description of Dragonfly+

PPK+

Description of PPK+



# PART 3


## Timings

# Specifications


- ▶ All protocol benchmarks were implemented in Java 1.6 and run on a server (3GHz AMD processor, 6GB of RAM) running Ubuntu 12.04.
- ▶ Benchmarks measured latency, the amount of work each device would have to do in the group excluding communication.

# Results


Latency measurement in SPEKE




Latency measurement in JPAKE



Latency measurement in Dragonfly



Latency measurement in PPK



## Conclusion

# Conclusion

It is possible to transfer PAKEs into GPAKEs while preserving round efficiency

SPEKE+ is very slow

J-PAKE+ is a bit slow, but proven secure (under CDH)

PPK is faster but weaker security proof

Dragonfly is fastest, but no security proof  
(despite IEEE 802.11-2012 standard)

THANK YOU