

R-600A, R-400A-G, AND R-233G TELEMETRY RECEIVERS

NO LONGER AVAILABLE



Features:

- The R-600A will receive any frequency and work with any transmitter in the 216, 217, 218, 219, 220 & 221 MHz frequency bands for the ultimate coverage. **(R-400A-G frequency coverage is 215-220 MHz & R-233G frequency coverage is 233-237 MHz)*
- Super sensitive @ -150dbm to hear the weakest signals.
- Synthesized design for extreme frequency stability under all temperature conditions. Frequency steps are 1KHz with $\pm 500\text{Hz}$ fine tuning on all frequencies from 215-220 MHz and 233-237MHz
- Supplied with high gain directional folding antenna w/removable pistol grip and soft carrying case. Receiver mounts directly to top of folding antenna body. Allows convenient one hand operation. Receiver may also be removed and a yagi with coax can be connected to BNC connector. Three step attenuator allows full receiver sensitivity for longest range or reduced sensitivity for one foot or less close-in range.
- Easy to change 9 volt alkaline battery.
- Very sensitive meter for received signal strength and monitoring battery voltage.
- Extremely selective front end to reject the most troublesome interference.
- Full 2 year warranty, 30 day no questions asked return policy.
- Size of receiver without antenna is 6.2" x 3.5" x 1.4". Total footprint of receiver and antenna when viewed from above is 20.25" x 11.25". When antenna elements are folded, footprint becomes 12" x 4.75".
- Loud, great sounding audio for in vehicle use.
- Total weight of receiver and antenna combined is 31 oz.
- Fast, same day shipping.