

CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft



Auto Air Refresh
(G2 China Market)
Product Requirements Document (PRD)
V1.3.5

Document Status: Draft

Document Type: Product Requirements Document (PRD)

Classification: Confidential

Department: EC

Author: Stella Shi

Project: on Sync+ for China Market

Reviewing Manager:	
Document Location:	
Date Released:	<Date the reviewing manager approved this document MM/DD>



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Contents

1	General Assumptions	3
1.1	User.....	3
1.2	Vehicle	3
1.3	APP	3
2	Auto Air Refresh.....	3
2.1	Description	3
2.2	Assumptions	3
2.3	User stories	3
2.4	Requirements.....	4
2.5	User Cases	6
3.	Status	24
3	Classification Key	30
4	Document Status Key	30
5	Terms, Acronyms and Definitions.....	31
6	Changes.....	32
7	Contacts.....	32
8	Appendix	32



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

1 General Assumptions

1.1 User

The user is assumed to be responsible for:

- Vehicle equipped with AAR feature which includes cabin PM sensor
- User will use Lincoln Way App by adding vehicle to enable AAR on LW app.

1.2 Vehicle

For a vehicle to support the DuerOS related feature, the vehicle must have all of the following:

- PM sensor installed and AAR feature enabled. Compatible AAR related modules including at least the climate control module installed. Modules configured for AAR feature typically via DIDs. VIN associated to G1DAG feature code in backend systems.
- TCU installed and activated
- HMI screen to show PM2.5 status both cabin and outside.

1.3 APP

Not compatible in this document.

2 Auto Air Refresh

2.1 Description

- AAR is a plant-installed solution, to allow the user to monitor cabin and outside PM2.5 values.
- Blue shield is the enhanced version of AAR with some automatic logic on IVI system.
- Chinese Name for AAR (different Chinese name for Ford & Lincoln per Lincoln branding team's request)
 - FORD – 智能馨风
 - Lincoln – 智能新风

2.2 Assumptions

- IVI has GPS module and must apply shifted GPS
- IVI can get Cabin PM2.5 data via CAN signals.
- IVI can get exterior PM2.5 data from cloud.
- IVI can send Cabin PM2.5 data to cloud and to rear screen if equipped.

2.3 User stories

User Story ID	User Story
---------------	------------




CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

2.3.1	User can see the Cabin PM2.5 data
2.3.2	User can see the exterior PM2.5 data
2.3.3	User can see detail exterior PM station
2.3.4	User can see the Cabin PM2.5 history
2.3.5	User can hear the voice reminder of tips or alerts
2.3.6	User can receive reminder when the PM filter need to be replaced.
2.3.7	Auto Recirc Control Strategy
2.3.8	PM2.5 Auto Climate on when Engine Ignition
2.3.9	High Cabin PM2.5 Alarm
2.3.10	User can see the filter status on FP/LW app
2.3.11	User can reset the filter status on App

2.4 Requirements

2.4.1 Cloud solution flowchart



Note and Assumptions:

Account information be optional for the SYNC+ AAR Phase 5, it NOT require account login.

If there is any VIN or sensitive data transfer between IVI and cloud, it shall leverage IVI encryption & decryption to protect.

1. Outside PM data from cloud (previous solution is Baidu which is yellow in above diagram)
Solution TBD

2. AAR filter status
BESL - TMC



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

2.4.2 PM 2.5 color information

should align with the color in Sync as below table:

Levels, Ranges & Colors

[H26g, R003.02] The (PMTyp) text shall be the PM type on all screens, as configured in the APIM (e.g. (PMTyp)='PM2.5', if configured for PM2.5); DE07.3.3=0 (PM2.5) or =1 (PM10)
[H26g, R005.01] The colors displayed in the Inside Color Display Areas and Outside Color Display Area on all screens shall match the (PMTyp) table information (e.g. if (PMTyp)='PM2.5' use Table 2).

Table 2
(PMTyp) PM2.5 Information

Level	Cabin Color Range & Outside Color Range	Default Color Range	High Value	Color Examples	R	G	B	States transmitted to the rear display (e.g. via the PmCabinLv_D_Stat signal)
	PmCabin_Conc_Actl > 500			Grey	130	130	130	NotKnown (default)
6	(251)	500 for Cabin; 999 for Outside		Black	126	0	35	Pm_Level_6_Worst
5	(151)	Level 6 Low Value -1		Purple	153	0	76	Pm_Level_5
4	(116)	Level 5 Low Value -1		Red	255	0	0	Pm_Level_4
3	(76)	Level 4 Low Value -1		Orange	255	126	0	Pm_Level_3
2	(36)	Level 3 Low Value -1		Yellow	255	255	0	Pm_Level_2
1	0	Level 2 Low Value -1		Green	0	228	0	Pm_Level_1_Best

Table 2a
(PMTyp) PM10 Information

Level	Cabin Color Range & Outside Color Range	Default Color Range	High Value	Color Examples	R	G	B	States transmitted to the rear display (e.g. via the PmCabinLv_D_Stat signal)
	PmCabin_Conc_Actl > 500			Grey	130	130	130	NotKnown (default)
6	421	500 for Cabin; 999 for Outside		Black	126	0	35	Pm_Level_6_Worst
5	351	Level 6 Low Value -1		Purple	153	0	76	Pm_Level_5
4	251	Level 5 Low Value -1		Red	255	0	0	Pm_Level_4
3	151	Level 4 Low Value -1		Orange	255	126	0	Pm_Level_3
2	51	Level 3 Low Value -1		Yellow	255	255	0	Pm_Level_2
1	0	Level 2 Low Value -1		Green	0	228	0	Pm_Level_1_Best

2.4.3 Feature code

PM2.5 sensor should be equipped for AAR feasibility.

Feature Code / MFAL Code : **G1DAG**

- For IVI, below feature code should be checked for AAR feasibility: **DE03, byte3, bit7: value=3** (Phase2,3,4)

D	E	F	G	H	I	J	K	L	M	
Definition	中文描述	百度界面功能	Baidu HMI impact	Length	0x0	0x1	0x2	0x3	0x4	0x5
MT/AT	手动/自动挡 (区别倒车信号)		N	4	AT	MT				
Climate domain	空调 (前排)		Y	4	N/A	Single Zone	Dual Zone			
Rear Hvac	后排空调		Y	4	N/A	Fan only	Manual	Auto	4 Zone	
heat cool seat	加热/制冷座椅		Y	4	N/A	Heat only	Heat/cool	Cool only		
heated SW	方向盘加热		Y	4	N/A	Y				
Fresh air Cabin	清新空气		Y	4	N/A	lite (519, 568)	G1DAB	gen1+ (U611 AAR) G1DAG		
suppress climate fan speed during low speed	低速输入时降低风扇速度		N	4	N/A	Y				
heated windshield	前挡风玻璃电热丝加热		N	4	N/A	Y				
Climate auto levels	空调Auto分级		N	4	N/A	3 Levels				

- Phase5 :CDX707

DE04	2	3	1	Fresh Air Cabin	清新空气AAR	0x0: Disabled 0x1: Enabledd
------	---	---	---	-----------------	---------	--------------------------------



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

- For App, it should check for AAR feasibility through VCS.



2.5 User Cases

2.5.1 On HMI


All the screenshots or pictures used below are not final design and just for UE purpose.




CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.1
Use Case	User can see the Cabin PM2.5 data on HMI
Pre-Conditions	1. Ignition on
Trigger	
Expected Behavior	<p>User can see the Cabin PM2.5 data on HMI on below scenarios:</p> <ol style="list-style-type: none"> For Phase2/3/4, on launcher, weather page  <p>For Phase 5, CDX707, there's no weather on launcher. But on Weather app (widget), there's entrance for AAR.</p> <ol style="list-style-type: none"> FOR some programs like CX482, AAR status icon with cabin PM2.5 data exist on the bottom/top status bar, but some are not. Please refer to HMI UE doc or final design. AAR button on AC screen AAR status in notification scroll bar. IF rear screen is equipped, Cabin PM2.5 data as well as the AAR status should be displayed on the rear screen which should be the same as Front Sync+ screen.
Post Conditions	<p>When user tap the above areas, it will lead to AAR screen.</p> 
Exceptions	If no data condition, value should not be displayed as (“-”).



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.2
Use Case	User can see the exterior PM2.5 data on HMI
Pre-Conditions	<ol style="list-style-type: none"> 1. Ignition on 2. GPS enabled
Trigger	<p>User can tap the AAR button on HMI on below scenarios to see the outside PM 2.5 data:</p> <ol style="list-style-type: none"> 1. For Phase2/3/4, on launcher, weather page  2. For Phase5, CDX707, there's no weather on launcher. But on Weather app (widget), there's Cabin & Exterior PM2.5 data displayed. 3. FOR some programs like CX482, AAR status icon with cabin PM2.5 data exist on the bottom/top status bar, but some are not. Please refer to HMI UE doc or final design. 4. AAR button on AC screen 5. AAR status in notification scroll bar.


CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Expected Behavior	<div>User can see the Exterior PM2.5 data on HMI</div> <div></div> <div><p>** As CAF required, the Chinese text of the pollution level should not be displayed together with PM2.5 data to avoid unnecessary confusion. Only color indication of different level needed. But the Chinese – color corresponding diagram should be displayed in somewhere within AAR screens.</p><p>** The exterior PM2.5 data should be refreshed every 5 minutes.</p></div>																				
Post Conditions	/																				
Exceptions	<div>1. If no data condition, value should not be displayed.</div> <table><tr><td></td><td colspan="4">车外 PM2.5</td></tr><tr><td>显示</td><td>正常显示</td><td>初始化</td><td>未获取到数据</td><td>未获取到定位</td></tr><tr><td>Launcher</td><td>XX XX 区 PM2.5</td><td>-- XX 区 PM2.5</td><td>-- XX 区 PM2.5</td><td>-- 网络 PM2.5</td></tr><tr><td>AAR</td><td>XX 区 PM2.5 XX</td><td>XX 区 PM2.5 初始化图 标</td><td>XX 区 PM2.5 未获取到数据图 标</td><td>网络 PM2.5 未获取到数据图 标</td></tr></table> <div>备注：新增未获取定位逻辑，其余显示图标及内容以交互、视觉为准</div>		车外 PM2.5				显示	正常显示	初始化	未获取到数据	未获取到定位	Launcher	XX XX 区 PM2.5	-- XX 区 PM2.5	-- XX 区 PM2.5	-- 网络 PM2.5	AAR	XX 区 PM2.5 XX	XX 区 PM2.5 初始化图 标	XX 区 PM2.5 未获取到数据图 标	网络 PM2.5 未获取到数据图 标
	车外 PM2.5																				
显示	正常显示	初始化	未获取到数据	未获取到定位																	
Launcher	XX XX 区 PM2.5	-- XX 区 PM2.5	-- XX 区 PM2.5	-- 网络 PM2.5																	
AAR	XX 区 PM2.5 XX	XX 区 PM2.5 初始化图 标	XX 区 PM2.5 未获取到数据图 标	网络 PM2.5 未获取到数据图 标																	

CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.3
Use Case	User can see the Cabin PM2.5 history on HMI
Pre-Conditions	1. Ignition on
Trigger	User enter AAR screen or user tap 'history Cabin PM2.5' tab on AAR screen
Expected Behavior	<p>For different programs, the AAR HMI designs are different. In some case, Cabin PM2.5 history is displayed directly on AAR screen. But sometime, it's displayed in a separate page which should be reached by tapping the 'history Cabin PM2.5' tab on AAR screen.</p> <p>User can see the Cabin PM history on HMI</p> <ol style="list-style-type: none"> The Air Quality History bottom time scale shall be 10 data points <ol style="list-style-type: none"> the <oldest time> to the left The <newest time> time to the right The time displayed for a bar is the time at the END of the 2 minute duration for that respective bar   <ol style="list-style-type: none"> On Sync+, the history data will be displayed as line graph instead of bar graph for Phase2/3/4 and bar chart for Phase5 and later. Please take UE for reference.
Post Conditions	/
Exceptions	If no data condition, 'No information available' should be displayed.

CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.4
Use Case	User can see the detail exterior PM station info on HMI
Pre-Conditions	<ol style="list-style-type: none"> 1. Ignition on 2. GPS enabled
Trigger	User tap the exterior PM buton on HMI
Expected Behavior	<p>User can see the detail info of exterior PM station on HMI</p> <ol style="list-style-type: none"> 1. Location/update time/other weather info 
Post Conditions	<ol style="list-style-type: none"> 1. Will refresh the data if user tap the “refresh” button
Exceptions	<ol style="list-style-type: none"> 1. If no data condition, ‘No information available’ should be displayed.

Use Case ID	2.5.1.5
Use Case	User can hear the voice reminder or receive messages of Tips or alerts
Pre-Conditions	<ol style="list-style-type: none"> 1. Ignition on 2. GPS enabled 3. Switch of Voice reminder of AAR is ON
Trigger	Edge cases: (Will be subdivided into different sub-cases)
Expected Behavior	<p>User can hear voice alerts or tips accordingly: (see below sub-cases)</p> <p>*user experience : Do not remind again in 30 minutes (TBD?)</p>
Post Conditions	/
Exceptions	/

CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.5.1
Use Case	User can hear the voice reminder of Tips or alerts – subcase 1
Pre-Conditions	<ol style="list-style-type: none"> 1. Ignition on 2. GPS enabled 3. Switch of Voice reminder of AAR is ON 4. Blue shield automatic recirc logic is not feasible. This case is disabled when in blue shield auto recirc logic.
Trigger	Condition1 – if (Exterior PM > 75) AND Condition2- if (35<CabPM < Exterior PM) AND Condition3- About situation continue more than 6 minutes AND Condition4- if (AC is in fresh air mode)
Expected Behavior	User can hear voice alerts or tips accordingly: Voice reminder – “Do you want to change to recirc mode?” The reminder(pop up alert) and notification could not be too often. The same alert or notification should be sent again within 30 minutes
Post Conditions	-If user answer “yes”, IVI should change the mode from “fresh air mode” to “Recirc Air mode” -If user answer “no”, no change needed
Exceptions	/



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.5.2
Use Case	User can hear the voice reminder of Tips or alerts – subcase 2
Pre-Conditions	<ol style="list-style-type: none"> 1. Ignition on 2. GPS enabled 3. Switch of Voice reminder of AAR is ON 4. Blue shield automatic recircle logic is not feasible. This case is disabled when in blue shield auto recir logic.
Trigger	<p>Condition1 – if (Exterior PM <20)</p> <p>Condition2- if (CabPM – Exterior PM > 30)</p> <p>Condition3 – above situation continues more than 120 seconds</p> <p>Condition4- if (AC is in recirc mode)</p> <p>Condition5 – Doors and windows are closed</p>
Expected Behavior	<p>User can hear voice alerts or tips accordingly: voice reminder – “Do you want to change to fresh air mode?”</p> <p>The reminder(pop up alert) and notification could not be too often. The same alert or notification should be sent again within 30 minutes</p>
Post Conditions	<p>-If user answer “yes”, IVI should change the mode to “fresh air mode”</p> <p>-If user answer “no”, no change needed</p>
Exceptions	/



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.5.3
Use Case	User can receive reminder when the PM filter need to be replaced on IVI.
Pre-Conditions	1. Ignition on
Trigger	<p>PM filter need to be replaced</p> <p>IVI get status from Cloud (check logic on cloud)</p> <p>There are 2 phases for the filter checking logic for backend: Phase A: Reminder calculated without DMS maintenance record, no DMS integration required. Condition: time > 1 year or odometer > 15000 KM Phase B: Reminder calculated with DMS maintenance record.</p> <p>*IVI sends the odometer to cloud every ignition on for above calculation logic.</p>
Expected Behavior	<p>User can see a highlight in HMI to remind user to replace the filter.</p> <p>If switch of Voice Reminder is ON THEN user can hear voice alert accordingly: "Please replace the PM filter"</p> <p>.....</p> <p>The reminder(pop up alert) and notification could not be too often. It should be limited to total 3 times every life circle and once every day. Total 3 times every life cycle (before the filter status being changed).</p>
Post Conditions	/
Exceptions	/



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.5.4
Use Case	User can receive message when the PM filter need to be replaced on IVI.
Pre-Conditions	1. Ignition on
Trigger	<p>PM filter need to be replaced</p> <p>Cloud(BESL) send notification to vehicle (check logic on cloud)</p> <p>There are 2 phases for the filter checking logic for backend: Phase A: Reminder calculated without DMS maintenance record, no DMS integration required. Condition: time > 1 year or odometer > 15000 KM Phase B: Reminder calculated with DMS maintenance record.</p> <p>*IVI sends the odometer to cloud every ignition on for above calculation logic.</p>
Expected Behavior	<p>User can see a highlight in HMI to remind user to replace the filter.</p> <p>If switch of Voice Reminder is ON THEN user can hear voice alert accordingly: “Please replace the PM filter”</p> <p>.....</p> <p>BESL will push the notification 3 times.</p>
Post Conditions	/
Exceptions	/



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.5.5
Use Case	User can reset PM filter status on IVI.
Pre-Conditions	1. Ignition on
Trigger	<p>When user tap the filter status(normal or need to be replaced) button, there will be a pop up of advisement for the user to replace the filter. There is a reset button on the pop up.</p> <p>When user tap the reset button, there should a double confirm information to make the user sure that if he/she tap the 'reset', the filter status will be changed.</p> <p>After the 'reset' button is finally tapped, the reset function will be triggered.</p>
Expected Behavior	<p>On HMI, the filter status will be changed to NORMAL.</p> <p>The reset info should be sent to Cloud for further use.</p>
Post Conditions	/
Exceptions	/

Use Case ID	2.5.1.6
Use Case	User can turn on/off the voice reminder in HMI
Pre-Conditions	/
Trigger	User tap the configuration button or other entrance in HMI
Expected Behavior	<p>User can see the existing setting status (on or off) of voice reminder of AAR</p> <p>User can change the configurable choice in HMI to turn on/off of voice reminder.</p> <p>Default status is ON.</p>
Post Conditions	If the user change the setting (from on to off or from off to on), the value should be sent to Cloud
Exceptions	/



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.7
Use Case	User can start Cabin Refresh
Pre-Conditions	1. Ignition ON
Trigger	User tap the 'Cabin Refresh" button – (the button location should depends on HMI final design. It maybe different for different program.) FORD: on AAR Screen Lincoln: on AC Screen
Expected Behavior	If AC is ON: turn to fresh mode for 90s If AC is OFF: turn ON AC and change to fresh mode
Post Conditions	User can tap the 'cabin refresh' button to turn off this feature during 90s *Turn Off Cabin Refresh is only available from Phase4
Exceptions	/















CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.8																						
Use Case	User can see different text display in different condition																						
Pre-Conditions	1. Ignition on																						
Trigger	By checking the CAN signal state, different state for different text displayed.																						
Expected Behavior	<div>ta</div> <div>Table 3</div> <table><tr><th>Ignition Status (Ignition_Status from BCM)</th><th>No data signal state (PmSnsCabn_D_Stat)</th><th>[no data text]</th></tr><tr><td>!=Run or !=Start</td><td>All Conditions</td><td>"blank"—do not display anything in the [no data text] field</td></tr><tr><td rowspan="6">=Run or =Start</td><td>Initializing</td><td>Initializing</td></tr><tr><td>Clean_Sensor</td><td>Sensor Blocked</td></tr><tr><td>Replace_Sensor</td><td>Replace Sensor</td></tr><tr><td>Intermittent_Inhibit</td><td>Environmental Limit</td></tr><tr><td>Blank_Field</td><td>"blank"—do not display anything in the [no data text] field</td></tr><tr><td>No_Issue (Note: this is a fault condition that should not occur. This signal state should not occur while PmCabn_Conc_Actl CAN signal equals 510 or 511)</td><td>"blank"—do not display anything in the [no data text] field</td></tr><tr><td></td><td>Missing message while PmCabn_Conc_Actl CAN signal equals 510 or 511</td><td>"blank"—do not display anything in the [no data text] field</td></tr></table>	Ignition Status (Ignition_Status from BCM)	No data signal state (PmSnsCabn_D_Stat)	[no data text]	!=Run or !=Start	All Conditions	"blank"—do not display anything in the [no data text] field	=Run or =Start	Initializing	Initializing	Clean_Sensor	Sensor Blocked	Replace_Sensor	Replace Sensor	Intermittent_Inhibit	Environmental Limit	Blank_Field	"blank"—do not display anything in the [no data text] field	No_Issue (Note: this is a fault condition that should not occur. This signal state should not occur while PmCabn_Conc_Actl CAN signal equals 510 or 511)	"blank"—do not display anything in the [no data text] field		Missing message while PmCabn_Conc_Actl CAN signal equals 510 or 511	"blank"—do not display anything in the [no data text] field
Ignition Status (Ignition_Status from BCM)	No data signal state (PmSnsCabn_D_Stat)	[no data text]																					
!=Run or !=Start	All Conditions	"blank"—do not display anything in the [no data text] field																					
=Run or =Start	Initializing	Initializing																					
	Clean_Sensor	Sensor Blocked																					
	Replace_Sensor	Replace Sensor																					
	Intermittent_Inhibit	Environmental Limit																					
	Blank_Field	"blank"—do not display anything in the [no data text] field																					
	No_Issue (Note: this is a fault condition that should not occur. This signal state should not occur while PmCabn_Conc_Actl CAN signal equals 510 or 511)	"blank"—do not display anything in the [no data text] field																					
	Missing message while PmCabn_Conc_Actl CAN signal equals 510 or 511	"blank"—do not display anything in the [no data text] field																					
Post Conditions	/																						
Exceptions	/																						



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.9																																																																																																																																																																																																								
Use Case	User can see different AAR status in IVI																																																																																																																																																																																																								
Pre-Conditions	1. Ignition ON																																																																																																																																																																																																								
Trigger	/																																																																																																																																																																																																								
Expected Behavior	<div>1. AAR status icon will always displayed in IVI status bar</div> <div>2. AAR status icon will be changed according to different status as below:</div> <div><div>Icons</div><div><div>H26g.R004.02]The (air quality)_icon on all screens shall be per Table 1, and shall be transmitted to the Rear Climate (Display) Module. [H26g.R043.01] Filtering On = Climate Control System On and Filtering Off = Climate Control System Off (see rule 44). Reference Tables 2 and 2a for the Level 1 information.</div></div><div>Table 1</div><table><tr><th colspan="6">Conditions</th><th colspan="3">Result</th><th>Comments</th></tr><tr><th>Ignition Status (Ignition_State via from BCM)</th><th>CCM Ignited Power Button CAN Data</th><th>CCM Power Button State</th><th>CCM Ignited Sensor CAN Data</th><th>Sensor PM Concentration Information from PreCabin_Conc_Act signal/interpreted by SYNC</th><th>Sensor Diagnostic State from PreCabin_D_Stat signal / Interpreted by SYNC</th><th>(air quality)_icon Displayed</th><th>Sample Graphic</th><th>State transmitted to the rear display module (e.g. via the PreCabin_D_Stat signal)</th><th></th></tr><tr><td>!Run or !+Start</td><td>All conditions</td><td></td><td></td><td></td><td></td><td>None (Blank)</td><td></td><td>NotKnown</td><td></td></tr><tr><td>+Run or +Start</td><td>Missing (Wake Up)</td><td>Unknown</td><td>All conditions</td><td></td><td></td><td>None (Blank)</td><td></td><td>NotKnown</td><td>1. See Rule 45. 2. SYNC display is "blank" and RACM_RICM is "NotKnown", due to no CAN state for "blank".</td></tr><tr><td></td><td>Present</td><td>On</td><td>Missing</td><td>Unknown</td><td>Unknown</td><td>on_icon</td><td></td><td>Filtering_On</td><td>See rule 44</td></tr><tr><td></td><td>Present</td><td>On</td><td>Present</td><td>S01-50</td><td>Any</td><td></td><td></td><td></td><td>See rule 44</td></tr><tr><td></td><td>Present</td><td>On</td><td>Present</td><td>Level >1</td><td>Any</td><td></td><td></td><td></td><td>See Table 3</td></tr><tr><td></td><td>Present</td><td>On</td><td>Present</td><td>No_Data_Exists or Faulty</td><td>Blank the Field</td><td></td><td></td><td></td><td>See Table 3</td></tr><tr><td></td><td>Present</td><td>On</td><td>Present</td><td>No_Data_Exists or Faulty</td><td>Initializing</td><td></td><td></td><td></td><td>See Table 3</td></tr><tr><td></td><td>Present</td><td>On</td><td>Present</td><td>No_Data_Exists or Faulty</td><td>no_issue</td><td></td><td></td><td></td><td>This case would be a programming error.</td></tr><tr><td></td><td>Present</td><td>On</td><td>Present</td><td>Level = 1</td><td>Any</td><td>on & clean_icon</td><td></td><td>Filtering_Complete</td><td></td></tr><tr><td></td><td>Present</td><td>Off</td><td>Missing</td><td>Unknown</td><td>Unknown</td><td>off_icon</td><td></td><td>Filtering_Off</td><td>See rule 44</td></tr><tr><td></td><td>Present</td><td>Off</td><td>Present</td><td>S01-50</td><td>Any</td><td></td><td></td><td></td><td>See rule 44</td></tr><tr><td></td><td>Present</td><td>Off</td><td>Present</td><td>Level >0</td><td>Any</td><td></td><td></td><td></td><td>See Table 3</td></tr><tr><td></td><td>Present</td><td>Off</td><td>Present</td><td>No_Data_Exists or Faulty</td><td>Blank the Field</td><td></td><td></td><td></td><td>See Table 3</td></tr><tr><td></td><td>Present</td><td>Off</td><td>Present</td><td>No_Data_Exists or Faulty</td><td>Initializing</td><td></td><td></td><td></td><td>See Table 3</td></tr><tr><td></td><td>Present</td><td>Off</td><td>Present</td><td>No_Data_Exists or Faulty</td><td>no_issue</td><td></td><td></td><td></td><td>This case would be a programming error.</td></tr><tr><td></td><td>Present</td><td>On</td><td>Present</td><td>No_Data_Exists or Faulty</td><td>Sensor Blocked, Replace Sensor Environmental Limit</td><td>error_icon</td><td></td><td>NotKnown</td><td>See Table 3</td></tr><tr><td></td><td>Present</td><td>Off</td><td>Present</td><td>No_Data_Exists or Faulty</td><td>Sensor Blocked, Replace Sensor Environmental Limit</td><td></td><td></td><td></td><td>See Table 3</td></tr><tr><td>Missing (After initially received)</td><td>Unknown</td><td></td><td>All conditions</td><td></td><td></td><td></td><td></td><td></td><td>See rule 45.</td></tr></table></div>	Conditions						Result			Comments	Ignition Status (Ignition_State via from BCM)	CCM Ignited Power Button CAN Data	CCM Power Button State	CCM Ignited Sensor CAN Data	Sensor PM Concentration Information from PreCabin_Conc_Act signal/interpreted by SYNC	Sensor Diagnostic State from PreCabin_D_Stat signal / Interpreted by SYNC	(air quality)_icon Displayed	Sample Graphic	State transmitted to the rear display module (e.g. via the PreCabin_D_Stat signal)		!Run or !+Start	All conditions					None (Blank)		NotKnown		+Run or +Start	Missing (Wake Up)	Unknown	All conditions			None (Blank)		NotKnown	1. See Rule 45. 2. SYNC display is "blank" and RACM_RICM is "NotKnown", due to no CAN state for "blank".		Present	On	Missing	Unknown	Unknown	on_icon		Filtering_On	See rule 44		Present	On	Present	S01-50	Any				See rule 44		Present	On	Present	Level >1	Any				See Table 3		Present	On	Present	No_Data_Exists or Faulty	Blank the Field				See Table 3		Present	On	Present	No_Data_Exists or Faulty	Initializing				See Table 3		Present	On	Present	No_Data_Exists or Faulty	no_issue				This case would be a programming error.		Present	On	Present	Level = 1	Any	on & clean_icon		Filtering_Complete			Present	Off	Missing	Unknown	Unknown	off_icon		Filtering_Off	See rule 44		Present	Off	Present	S01-50	Any				See rule 44		Present	Off	Present	Level >0	Any				See Table 3		Present	Off	Present	No_Data_Exists or Faulty	Blank the Field				See Table 3		Present	Off	Present	No_Data_Exists or Faulty	Initializing				See Table 3		Present	Off	Present	No_Data_Exists or Faulty	no_issue				This case would be a programming error.		Present	On	Present	No_Data_Exists or Faulty	Sensor Blocked, Replace Sensor Environmental Limit	error_icon		NotKnown	See Table 3		Present	Off	Present	No_Data_Exists or Faulty	Sensor Blocked, Replace Sensor Environmental Limit				See Table 3	Missing (After initially received)	Unknown		All conditions						See rule 45.
Conditions						Result			Comments																																																																																																																																																																																																
Ignition Status (Ignition_State via from BCM)	CCM Ignited Power Button CAN Data	CCM Power Button State	CCM Ignited Sensor CAN Data	Sensor PM Concentration Information from PreCabin_Conc_Act signal/interpreted by SYNC	Sensor Diagnostic State from PreCabin_D_Stat signal / Interpreted by SYNC	(air quality)_icon Displayed	Sample Graphic	State transmitted to the rear display module (e.g. via the PreCabin_D_Stat signal)																																																																																																																																																																																																	
!Run or !+Start	All conditions					None (Blank)		NotKnown																																																																																																																																																																																																	
+Run or +Start	Missing (Wake Up)	Unknown	All conditions			None (Blank)		NotKnown	1. See Rule 45. 2. SYNC display is "blank" and RACM_RICM is "NotKnown", due to no CAN state for "blank".																																																																																																																																																																																																
	Present	On	Missing	Unknown	Unknown	on_icon		Filtering_On	See rule 44																																																																																																																																																																																																
	Present	On	Present	S01-50	Any				See rule 44																																																																																																																																																																																																
	Present	On	Present	Level >1	Any				See Table 3																																																																																																																																																																																																
	Present	On	Present	No_Data_Exists or Faulty	Blank the Field				See Table 3																																																																																																																																																																																																
	Present	On	Present	No_Data_Exists or Faulty	Initializing				See Table 3																																																																																																																																																																																																
	Present	On	Present	No_Data_Exists or Faulty	no_issue				This case would be a programming error.																																																																																																																																																																																																
	Present	On	Present	Level = 1	Any	on & clean_icon		Filtering_Complete																																																																																																																																																																																																	
	Present	Off	Missing	Unknown	Unknown	off_icon		Filtering_Off	See rule 44																																																																																																																																																																																																
	Present	Off	Present	S01-50	Any				See rule 44																																																																																																																																																																																																
	Present	Off	Present	Level >0	Any				See Table 3																																																																																																																																																																																																
	Present	Off	Present	No_Data_Exists or Faulty	Blank the Field				See Table 3																																																																																																																																																																																																
	Present	Off	Present	No_Data_Exists or Faulty	Initializing				See Table 3																																																																																																																																																																																																
	Present	Off	Present	No_Data_Exists or Faulty	no_issue				This case would be a programming error.																																																																																																																																																																																																
	Present	On	Present	No_Data_Exists or Faulty	Sensor Blocked, Replace Sensor Environmental Limit	error_icon		NotKnown	See Table 3																																																																																																																																																																																																
	Present	Off	Present	No_Data_Exists or Faulty	Sensor Blocked, Replace Sensor Environmental Limit				See Table 3																																																																																																																																																																																																
Missing (After initially received)	Unknown		All conditions						See rule 45.																																																																																																																																																																																																
Post Conditions	/																																																																																																																																																																																																								
Exceptions	/																																																																																																																																																																																																								

Level 1 see table in 2.4.2

3. When the status changes, IVI will receive message in message center. And user can tap the message to enter AAR main screen.



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.10						
Use Case	User can enable/disable PM2.5 Auto Recirc Control Strategy						
Pre-Conditions	1. Ignition on						
Trigger	On AAR screen, user tap the enable/disable button of Auto Recirc Control.						
Expected Behavior	<div>1. If the previous status is ON: only Disable button displayed</div> <div>2. If the previous status is OFF: only Enabe button displayed</div> <div>After user tap the button, the configuration will be changed to enable or disable accordingly.</div> <div>**If strategy is implemented in DuerOS system, customer should get HMI to disable / enable this strategy. If both DuerOS system and RCCM has this strategy, DuerOS system should honor RCCM output, and show RCCM control result in HMI for customer. But when customer choose to disable this strategy in DuerOS HMI, it means this strategy disabled in both DuerOS and RCCM.</div> <div><table><tr><td>Flag name</td><td>state</td><td>Effect</td></tr><tr><td>AAR_ActivatePM2.5BaseRec</td><td>0 / 1</td><td>Enable / disable the PM2.5 auto recirc</td></tr></table></div> <div>When AAR_ActivatePM2.5BaseRec is 1, DuerOS system activate this strategy;</div> <div>When AAR_ActivatePM2.5BaseRec is 0, this control strategy will be disabled.</div> <div>Default status is ON.</div>	Flag name	state	Effect	AAR_ActivatePM2.5BaseRec	0 / 1	Enable / disable the PM2.5 auto recirc
Flag name	state	Effect					
AAR_ActivatePM2.5BaseRec	0 / 1	Enable / disable the PM2.5 auto recirc					
Post Conditions	/						
Exceptions	/						




CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.11
Use Case	PM2.5 Auto Recirc Control Strategy
Pre-Conditions	<ol style="list-style-type: none"> 1. Ignition on 2. Strategy enabled 3. 5 minutes after ignition ON as the auto-recirc should be enabled after auto start finished. 4. Precondition of PM2.5 Auto Recirc strategy: (AND conditions) <ol style="list-style-type: none"> 1) VehState = NORMAL_RUN OR REMOTE START; 2) The selected climate control air flow mode (AMC_AirDistrModeDrState) is not WS or WS/FL; 3) The front or rear windscreen heat is off (HblMirrIndRq and HwsStat equals off); 4) The compressor request (CompsrOnRq) "HvacAirCond_B_Rq" is on; 5) PM2.5 sensor reading is available;




Trigger

Checking logic by IVI as below diagram
Original diagram:



New diagram from Baidu: (phase4 for reference only)



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

	<div> 1. Input <div> <div>VehState: Vehicle operation state</div> <div>AppRdc_AqsEngRunWS : Engine start running timer</div> <div>AMC_AirDistrModeDrState: Requested air distribution mode position, PN, FL, WS</div> <div>AmbTe_Err : Error flag for OAT CAN signal</div> <div>PmCabn_Conc_Actl: Cabin PM2.5 number</div> <div> <div>Historical Data:</div> <div> <div>PmCabn02Mnte_Conc_Actl PmCabn04Mnte_Conc_Actl</div> <div>PmCabn06Mnte_Conc_Actl PmCabn08Mnte_Conc_Actl</div> <div>PmCabn10Mnte_Conc_Actl PmCabn12Mnte_Conc_Actl</div> <div>PmCabn14Mnte_Conc_Actl PmCabn16Mnte_Conc_Actl</div> <div>PmCabn18Mnte_Conc_Actl PmCabn20Mnte_Conc_Actl</div> </div> </div> </div> </div> <div> 2. output <div> <div>AR_PM2.5RecDrState Requested Recirc door position by DuerOS system;</div> </div> </div>
--	---

CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Expected Behavior	<p>3. Status</p> <p>Status 1 – Cabin clean at recirc; Status 2 – Cabin clean at fresh; Status 3 – Pull down at recirc; Status 4 – Pull down at fresh;</p> <p>4. Some definitions</p> <ul style="list-style-type: none"> IF Cabin PM2.5 is increasing, when Cabin PM2.5 > 30 means not clean. IF Cabin PM2.5 is decreasing, when Cabin PM2.5 < 24 means clean. Rapid increase: If cabin PM2.5 reading increase 150 within 30 sec, then judge cabin PM2.5 is rapidly increasing. Cabin Max PM : Take last 3 PM2.5 data every 5 seconds to get the average. If the average data is higher than 250, it reaches Max PM.; at Max PM status, system choose to fresh mode to introduce outside air flow to pull down cabin PM2.5; The reason is that pollution may come from cabin inside like smoking. Cabin pull down – comparing 2min average PM2.5 reading . If decrease by more than 20%, then judge system is in “pull down” mode. $\frac{(\text{PmCabn02Mnte_Conc_Actl} - \text{PmCabn04Mnte_Conc_Actl})}{\text{PmCabn02Mnte_Conc_Actl}} > 20\%$ If system is at status 4, wait at least 7 min to make the judgment. In Status 3, SHALL wait 2 minutes to get a new history value for calculating pull down. In Status 4, SHALL wait 7 minutes to get the latest 2 min & 4 min value (PmCabn02Mnte_Conc_Actl , PmCabn04Mnte_Conc_Actl) for calculating pull down. In Status1/2, IF Cabin PM2.5 > 30, system should jump out the current status and start from recirc mode checking.
Post Conditions	/
Exceptions	<ol style="list-style-type: none"> IF Cabin PM2.5 data is error, the auto-recirc will be terminated and it should be restart after receiving the normal cabin PM2.5 data. During the auto-recirc, IF user manually change the recirc mode (by checking Recirc_Btn_Stt Status & blueshield auto-recirc logic), the auto-recirc should be terminated until next ignition cycle. During the auto-recirc, IF user disable the ‘Auto Recirc’ by IVI setting, the auto recirc should be terminated; IF user reopen it, it should be restart after receiving the system callback. In Status 1 & Status 2, once cabin PM2.5>30, it should jump out of th status and start a new check from the beginning.



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.12						
Use Case	User can enable/disable ‘PM2.5 Auto Climate on when Engine Ignition’ logic						
Pre-Conditions	Ignition on						
Trigger	On AAR screen, user tap the enable/disable button of Auto Climate on when Engine Ignition						
Expected Behavior	<div>1. If the previous status is ON: only Disable button displayed</div> <div>2. If the previous status is OFF: only Enabe button displayed</div> <p>After user tap the button, the configuration will be changed to enable or disable accordingly.</p> <p>** This strategy can be disabled / enabled in DuerOS system, customer should can get HMI to disable / enable this strategy.</p> <table><tr><td>Flag name</td><td>state</td><td>Effect</td></tr><tr><td>AAR_ActivatePM2.5Base</td><td>0 / 1</td><td>Disable / Enable the PM2.5 auto AC on</td></tr></table> <p>When AAR_ActivatePM2.5Base is 1, DuerOS system activate this strategy;</p> <p>When AAR_ActivatePM2.5Base is 0, this control strategy will be disabled.</p> <p>Default status is DISABLE.</p>	Flag name	state	Effect	AAR_ActivatePM2.5Base	0 / 1	Disable / Enable the PM2.5 auto AC on
Flag name	state	Effect					
AAR_ActivatePM2.5Base	0 / 1	Disable / Enable the PM2.5 auto AC on					
Post Conditions	/						
Exceptions	/						



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft


Use Case ID	2.5.1.13
Use Case	PM2.5 Auto Climate on when Engine Ignition
Pre-Conditions	Logic enabled



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Trigger

Checking logic by IVI
Original diagram:



New diagram from supplier: TBD

Input

- VehState: Vehicle operating state
- PmCabr_Conc_Actl Cabin: PM2.5 number (clean : <30)
- CC_Fr_Btn_User_Adj:
UFC status:
0x11 Active : con
0x12 Complete : NO CONFLICT
0x13 Interrupt : NO CONFLICT
0x00~0x10/0x14~0x1F. : NO CONFLICT
(Unlock purge : 90 seconds)

Output

- AAR_ClmtStateOnPM2.5:
Requested to turn on climate system through DuerOS system;



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Expected Behavior	<ul style="list-style-type: none"> When vehicle state (VehState) transit from Off to Normal Run, this strategy will be start. If initial cabin PM2.5 is polluted, and climate system is off, then DualOS system will request to turn on climate. HMI will show note in screen to customer which may say "AAR system is going to turn on AC system in 10 sec". HMI offer a button in the note to allow customer to stop this strategy. IF user cancel the above start, the case is terminated for the ignition cycle. Limitation 1: 5 minutes after Normal Run. The strategy will not triggered after 5 minutes for safty purpose. Limitation 2: IF speed>30, terminate the loop. Function should not work when driving.
Post Conditions	When climate system is turn on, system will be set to auto mode directly. This request will be transfer to CCH / RCCM.
Exceptions	If there is UFC function conflict, system will be turn on to auto mode just after UFC function complete or disturb.



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.1.14
Use Case	High Cabin PM2.5 Alarm- When vehicle is driving, IVI will remind customer to turn on climate system
Pre-Conditions	Ignition on during driving (normal driving for 15 mins) (*normal driving : ignition on & speed >0 start timer 15 mins)
Trigger	Cabin PM2.5 data > 35 AND climate system not work
Expected Behavior	User can see text alert or reminder on HMI to ask if user wan to turn on the climate system. If Voice is enabled, Voice reminder will also be heard. The reminder(pop up alert) and notification could not be too often. It should be limited to once every ignition circle.
Post Conditions	According to user's choice to turn on climate or do nothing.
Exceptions	/

2.5.2 On App

Use Case ID	2.5.2.1
Use Case	User can see the filter status on FP/LW app
Pre-Conditions	<ol style="list-style-type: none"> 1. VIN has been added in app and activated 2. The vehicle has AAR equipped (capability check) 3. The VIN is authorized.
Trigger	User enter the vehicle
Expected Behavior	User can see the filter status as below: (App will fetch the CNESL API to get the filter status) 'NORMAL' or 'Need to be replaced' And the last reset time if available
Post Conditions	
Exceptions	If response from CNESL is unnormal or not available, 'UNKOWN' will be diaplyed.



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

Use Case ID	2.5.2.2
Use Case	User can reset the filter status on FP/LW app
Pre-Conditions	<ol style="list-style-type: none"> VIN has been added in app and activated The vehicle has AAR equipped
Trigger	User enter the vehicle
Expected Behavior	User can reset the filter status by tapping the “reset” button on filter status screen,
Post Conditions	App will display the latest filter status and reset time after reset.
Exceptions	If reset failed (app received the error response or timeout from CNESL), App will display the ‘reset failure’ notice and back to the previous filter status screen.

3 Classification Key

Classification	Notes
Proprietary	Information created or obtained in the normal course of business and not classified as Secret or Confidential
Confidential	Information that provides the Company with a competitive advantage, that supports its technical or financial position, and which, if disclosed without authorization, could cause damage to the Company.
Secret	Information of a strategic or highly sensitive nature that, if disclosed without authorization, would cause substantial, severe, or irreparable damage to the Company or its relationships.

4 Document Status Key

Status	Notes
DRAFT	Document currently being worked on. Shall not be used as a solid reference to information included in this document.
AFR	Available For Review. Document information is not eligible for changes. Approving manager will revise this document and if all the information is found to be completely valid, then the document will change to REL status. If the document is found to have errors, the document will change to DRAFT status.



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

REL	Released. Document is completely valid at time of review, and is now available to be used as a solid reference of information.
-----	--

5 Terms, Acronyms and Definitions

Term or Acronym	Definition



CVPP	AAR	Authors: Stella Shi
DuerOS IVI	PRD v1.3.5	Document Status: Draft

6 Changes

Author	Date (YYYY/MM/DD)	Status	Notes
Stella	2018/10/18	DRAFT	Version 1.0 – Initial draft at compiling all use cases, available information and existing requirements
Stella	2018/10/24	DRAFT	1. More info displayed on IVI AAR screen with history cabin PM data 2. Display Outside PM data on a map view
Stella	2019/2/21	DRAFT	Update the reminders.
Stella	2019/10/14	DRAFT	Update the reminder limit in 2.5.1.5.3 & 2.5.2.5
Stella	2019/12/12	DRAFT	Update the blueshield auto logic
Stella	2020/7/16	DRAFT	Update the Sequence Diagram in 2.4.1
Stella	2020/12/2	DRAFT	Update some detail logic for Blue Shield
Stella	2021/7/12		Add filter reset in app Add filter status display in app
Stella	2021/8/23		Change “Auto Climate ON” default to DISABLE
Stella	2022/6/6		Update Cloud solution flowchart

7 Contacts

For assistance or correction, please contact any of the following:
Stella Shi, Feature Owner – Ford Motor Company
Email: jshi32@ford.com

8 Appendix

“AAR Gen2 Strategy V3.pdf” from Harold Li of Climate Control Team

