

Mozrest Integration

1. Overview

1.1 Description

Mozrest Integration connects **Mozrest** (restaurant reservation platform) with **Newo Platform**.

It enables:

- Checking real-time table availability for a given date, time, and party size
- Booking restaurant reservations with full guest details
- Cancelling existing reservations
- Restaurant area/location management with AI-powered area matching
- Party size and booking window validation

This integration is designed for **restaurants and hospitality businesses** who need **automated reservation management through a conversational AI agent** (voice or chat).

1.2 Use Cases

- When a guest asks about availability → Query Mozrest for open slots with party size and preferred date/time
- When a guest wants to book a table → Validate details, match area via LLM, create reservation in Mozrest
- When a guest wants to cancel a reservation → Delete the booking from Mozrest
- When a guest mentions a preferred area → AI matches the description to available restaurant locations

1.3 Supported Features

Feature	Supported	Notes
Check Availability	✓	By date, time, party size, and timezone
Book Reservation	✓	Full guest details with area selection
Cancel Reservation	✓	By booking ID
Area/Location Management	✓	Cached per session from availability response
AI Area Matching	✓	LLM matches guest description to restaurant areas
Party Size Handling	✓	Passed to availability and booking APIs
Large Group Detection	✓	Configurable minimum party size threshold
Booking Window Validation	✓	Max days in advance configurable
SMS Booking Confirmation	✓	Schema template for confirmation messages
Reschedule Reservation	✗	Cancel + rebook as workaround
Waitlist Management	✗	Not implemented
Multi-Restaurant Support	✗	Single restaurant per integration instance

2. Requirements

Before installation:

- Active **Mozrest** account with API access
- Restaurant configured in Mozrest with areas/locations
- **Mozrest connector** credentials (configured at platform level)

3. How to Setup

3.1 Step 1 — Configure Mozrest Connector

1. Ensure your Mozrest account is active and API-enabled
2. Configure the Mozrest connector in the Newo platform with your account credentials
3. Verify the restaurant ID is available in project attributes

3.2 Step 2 — Connect in Platform

1. Open **Newo** → **Projects**
2. Verify the following attributes in **Builder / Attributes**:

Attribute	Required	Description
project_business_time_zone	✓	Restaurant timezone (e.g., America/New_York)
project_business_name	✓	Restaurant name
project_attributes_private_dynamic_restaurant_google_restaurant_id	✓	Restaurant identifier for Mozrest
mozrest_enable_slot_check	✗	Enable availability checking (default: True)
mozrest_enable_booking	✗	Enable booking capability (default: True)
mozrest_enable_cancellation	✗	Enable cancellation capability (default: True)

3. Click **Save + Publish All**
4. On publish, the SetupFlow automatically:
 - Creates Mozrest and HTTP connectors
 - Injects booking, availability, and validation payload schemas for the agent
 - Enables booking, availability, and cancellation features

4. How to Use

This section explains how the integration works, how to configure automation, and how to test it.

4.1 How the Integration Works

The integration uses Mozrest's reservation API for table management. Availability returns a list of areas with open slots, which are cached per session. During booking, an LLM matches the guest's area preference to available locations before creating the reservation.

- A **Trigger** is a system event that starts a flow
- An **Action** is the API operation performed in Mozrest

Available Triggers

Trigger	Event	Description
Check Availability	get_available_slots	When the agent needs to look up open slots
Book Reservation	book_slot	When the agent confirms a booking
Cancel Reservation	convo_agent_cancel_booking	When the agent processes a cancellation
Setup	project_publish_finish	Initializes integration on deploy
Test	integration_test	Webhook test endpoints for each flow

Available Actions

- **Get Available Slots** — Query availability by date/time/party size (command: `get_available_slots`)
- **Book Restaurant Slot** — Create reservation with guest details and area (command: `book_restaurant_slot`)
- **Cancel Booking** — Cancel existing reservation (command: `cancel_booking`)

4.2 Architecture Diagrams

Overall Sequence

```
sequenceDiagram
    participant U as User
    participant A as ConvoAgent
    participant I as Mozrest Integration
    participant API as Mozrest API

    Note over I: Setup (on publish)
    A->>I: project_publish_finish
    I->>I: Create connectors, inject schemas
    I->>A: Tools configured

    Note over U,API: Availability Check
    U->>A: "Table for 4 tomorrow at 7 PM?"
    A->>I: get_available_slots (partySize, dateTime)
    I->>API: get_available_slots (partySize, timeZone, dateTime)
    API-->>I: Available slots + areas
    I->>I: Cache areas in persona
    I->>A: result_success (availability[])
```

A->>U: "Here are the available times..."

Note over U,API: Booking

U->>A: "Book the patio at 7:30 PM"

A->>I: book_slot (customerInfo, dateTime, area)

I->>I: LLM match "patio" -> area ID

I->>I: Validate all required fields

I->>API: book_restaurant_slot (dateTime, partySize, guest details, areaId)

API-->>I: booking_id

I->>A: result_success (booking_id)

A->>U: "Your reservation is confirmed!"

Note over U,API: Cancellation

U->>A: "Cancel my reservation"

A->>I: convo_agent_cancel_booking (booking_id)

I->>API: cancel_booking (bookingId, cancelActor: agent)

API-->>I: Confirmation

I->>A: result_success (cancelled)

A->>U: "Your reservation has been cancelled"

AvailabilityFlow

flowchart TD

```
E["get_available_slots"] --> GATE{{"Slot check<br>enabled?"}}
GATE -->|"No"| SKIP["Skip"]
GATE -->|"Yes"| VAL{{"partySize &<br>dateTime present?"}}
VAL -->|"No"| ERR["ResultError"]
VAL -->|"Yes"| API["SendCommand:<br>get_available_slots<br>{partySize, timeZone,<br>dateTime}"]
API --> OK{{"Success?"}}
OK -->|"No"| ERR
OK -->|"Yes"| PARSE["Parse availability<br>Extract areas:<br>location,<br>locationId"]
PARSE --> CACHE["Store areas<br>in persona attribute"]
CACHE --> OUT["result_success<br>{availability[]}"]
```

BookingFlow

flowchart TD

```
E["book_slot"] --> GATE{{"Booking<br>enabled?"}}
GATE -->|"No"| SKIP["Skip"]
GATE -->|"Yes"| LLM["LLM match area:<br>user description -><br>area ID from<br>cached areas"]
LLM --> VAL{{"All fields<br>present?"}}
VAL -->|"No"| ERR["ResultError<br>(missing fields)"]
VAL -->|"Yes"| NORM["Normalize phone<br>(strip + prefix)"]
NORM --> API["SendCommand:<br>book_restaurant_slot<br>{dateTime, partySize,<br>name, email, phone,<br>areaId, notes}"]
API --> OK{{"Success?"}}
```

```
OK -->|"No"| ERR2["ResultError<br>(server error)"]
OK -->|"Yes"| OUT["result_success<br>{booking_id}"]
```

CancellationFlow

```
flowchart TD
    E["convo_agent_cancel_booking"] --> GATE{"Cancellation<br>enabled?"}
    GATE -->|"No"| SKIP["Skip"]
    GATE -->|"Yes"| EXTRACT["Extract booking_id<br>from payload.meta"]
    EXTRACT --> API["SendCommand:<br>cancel_booking<br>{bookingId,<br>cancelActor:<br>agent}"]
    API --> OK{"Success?"}
    OK -->|"No"| ERR["ResultError"]
    OK -->|"Yes"| OUT["result_success<br>{booking_id}"]
```

SetupFlow

```
flowchart TD
    E["project_publish_finish"] --> ATTRS["Define project attributes:<br>enable_slot_check,<br>enable_booking,<br>enable_cancellation"]
    ATTRS --> AGENT["Set SuperAgent attributes:<br>booking, availability,<br>cancellation = enabled"]
    AGENT --> CONN["Create connectors:<br>mozrest connector<br>http connector"]
    CONN --> SCHEMAS["Inject JSON schemas:<br>booking payload,<br>availability payload,<br>validation schema,<br>SMS template"]
    SCHEMAS --> DONE["Setup complete"]
```

4.3 Where to Test

Testing can be done through the **Newo conversation interface** (chat or voice channel). Each flow (Availability, Booking, Cancellation) has a dedicated `integration_test` webhook endpoint for connectivity validation.

4.4 Testing and Verification

To test the integration:

1. **Setup:** Publish the project and verify connectors are created and schemas injected
2. **Availability:** Ask "Do you have a table for 4 tomorrow at 7 PM?" — verify available slots returned with area information
3. **Booking:** Complete a reservation — verify booking created in Mozrest with correct guest details and area
4. **Cancellation:** Cancel a reservation — verify booking removed from Mozrest

If no action occurs:

- Ensure Mozrest connector is properly configured with valid credentials
- Verify `project_business_time_zone` is set correctly
- Verify the restaurant ID attribute is populated
- Check feature flags are enabled (`mozrest_enable_slot_check` , `mozrest_enable_booking` , `mozrest_enable_cancellation`)
- Confirm the integration was re-published after changes

- Test individual flows via `integration_test` webhook endpoints

Note: This integration performs real operations in Mozrest. Reservations created or cancelled through the agent are reflected in the live restaurant system.

5. FAQ

Q: How does the AI select the restaurant area? A: During availability checking, Mozrest returns a list of areas (e.g., patio, main dining, bar). These are cached per session. When the guest books, an LLM (Gemini 2.5 Flash) matches the guest's area description (e.g., "outside" or "by the window") to the closest available area. The matching uses low temperature (0.2) for deterministic results.

Q: What guest information is required for booking? A: All of the following: first name, last name, email, phone number, date/time, party size, and area preference. Optional: notes for special requests.

Q: Can I connect multiple restaurants? A: Each integration instance supports one restaurant. For multiple restaurants, create separate integration instances.

Q: How are phone numbers handled? A: Phone numbers are expected in E.164 format (e.g., `+15551234567`). The integration strips the leading `+` before sending to the Mozrest API.

Q: What happens if the guest doesn't specify an area? A: The area field is required in the booking payload. The agent should ask the guest for their preference, or suggest available areas returned from the availability check.

Q: Does the integration support large group reservations? A: Yes. The availability payload schema includes a `regularGroup` validation field and a configurable minimum party size threshold (`project_attributes_restaurant_large_group_reservation_minimum_party_size`) for special handling of large parties.

Q: How far in advance can reservations be made? A: Configurable via `project_attributes_setting_booking_check_availability_max_days_in_advance` . The availability validation schema enforces this booking window.

Q: Does the integration handle waitlists? A: No. If no slots are available for the requested date/time/party size, the agent can only suggest alternative times from the availability results.