HouseCallPro Integration

1. Overview

1.1 Description

HouseCallPro Integration connects **HouseCallPro** (field service management platform) with **Newo Platform**.

It enables:

- Checking available appointment slots with intelligent employee selection (by role, job type, or zip code)
- Booking appointments with automatic customer search, creation, address comparison, and job management
- Cancelling existing appointments
- Recognizing returning customers on inbound calls with upcoming job context
- Caching company data (employees, job types, locations) with configurable refresh intervals
- Automatic line item matching using AI for job cost estimation

This integration is designed for **home service businesses** (HVAC, plumbing, electrical, cleaning, etc.) who need **automated appointment scheduling through a conversational AI agent** (voice or chat).

1.2 Use Cases

- When a customer asks about available slots -> AI selects the right employee and returns open time slots
- When a customer wants to book a service -> Search or create customer record, create job with line items, and schedule appointment
- When a customer wants to cancel -> Cancel the appointment via HouseCallPro API
- When an inbound call arrives -> Automatically look up customer by phone and display upcoming jobs to the agent
- When a customer describes a service need -> AI matches the description to job types and line items for accurate quoting
- When a session starts -> Static data (employees, job types, company info) is refreshed if cache is stale

1.3 Supported Features

Feature	Supported	Notes
Check Availability	Yes	With 3 employee selection methods (POC, job type, zip)
Book Appointment	Yes	Creates job + appointment with customer management
Cancel Appointment	Yes	Requires booking_id and job_id from prior booking
Employee Selection (POC)	Yes	Assigns Point of Contact employee (default method)
Employee Selection (Job Type)	Yes	AI matches job description to employee skills/tags

Employee Selection (Zip Code)	Yes	Matches employee by service area zip code tags
Customer Search	Yes	By phone number via HouseCallPro API
Customer Creation	Yes	Auto-creates during booking flow with address
Address Comparison	Yes	Compares provided address with HCP profile, adds new address if different
Existing Client Recognition	Yes	Looks up customer + upcoming jobs on inbound call
Auto Line Item Matching	Yes	AI matches service description to catalog items
Static Data Caching	Yes	Employees, job types, company info with 24h TTL
Multi-Location Support	Yes	Location-specific employee filtering
Token Auto-Refresh	No	Uses static API key (Bearer token)
Reschedule Appointment	No	Cancel + rebook as workaround
Historical Data Import	No	Only new events after activation

2. Requirements

Before installation:

- Active **HouseCallPro** account (Pro plan or higher for API access)
- **HouseCallPro API key** for authentication
- At least one employee configured with appropriate permissions
- For POC method: at least one employee marked as Point of Contact in HouseCallPro

3. How to Setup

3.1 Step 1 — Get API Credentials

1. Log in to your **HouseCallPro** account
2. Navigate to account settings or developer/API section
3. Generate or locate your **API key**
4. Note your company timezone setting

3.2 Step 2 — Connect in Platform

1. Open **Newo -> Projects**
2. Set the following attributes in **Builder / Attributes**:

Attribute	Required	Description
`hcp_api_key`	Yes	HouseCallPro API key for authentication
`hcp_base_url`	No	API base URL (default: `https://api.housecallpro.com/`)
`hcp_enable_slot_check`	No	Enable availability checks (default: `True`)

`hcp_enable_booking`	No	Enable appointment creation (default: `True`)
`hcp_enable_cancellation`	No	Enable cancellations (default: `True`)
`hcp_auto_employee_type`	No	Employee assignment method: `poc`, `job_type`, or `zip_code` (default: `poc`)
`hcp_booking_duration`	No	Appointment duration in minutes (default: `120`; legacy values `1..12` are interpreted as hours)
`hcp_show_for_days`	No	Days to search for availability (default: `5`)
`hcp_availability_offset`	No	Days before first available slot (default: `2`)
`hcp_check_existing_client`	No	Look up customer on inbound call (default: `True`)
`hcp_auto_add_line_items`	No	Auto-match line items to jobs via AI (default: `False`)
`hcp_line_items`	No	Service catalog as JSON array of items
`hcp_job_type_employee_selection_prompt`	No	Custom LLM prompt for job-type employee matching
`hcp_static_data_update_interval`	No	Cache refresh interval in seconds (default: `86400`)

3. Click **Save + Publish All**
4. On publish, the SetupFlow automatically:
    - Creates an HTTP connector for all API operations
    - Fetches and caches company info, employees, and job types
    - Registers availability, booking, and cancellation tools with the agent
    - Injects payload schemas for the ConvoAgent tool calling framework

4. How to Use

This section explains how the integration works, how to configure automation, and how to test it.

4.1 How the Integration Works

The integration uses HouseCallPro's REST API for job management, appointment scheduling, customer records, and employee data. A key architectural feature is the two-level booking model: a **Job** is created first (representing the service request), then an **Appointment** is attached to it (representing the scheduled time slot). Employee selection supports three AI-powered strategies. Static data is cached with a configurable TTL to minimize API calls.

- A **Trigger** is a system event that starts a flow
- An **Action** is the API operation performed in HouseCallPro

Available Triggers

Trigger	Event	Description
Check Availability	`get_available_slots`	When the agent needs to look up open slots

Book Appointment	`book_slot`	When the agent confirms a booking
Cancel Appointment	`convo_agent_cancel_booking`	When the agent processes a cancellation
Session Start	`session_started`	Refreshes static data cache if stale
Inbound Call	`define_user_phone_number`	Looks up existing customer and upcoming jobs
Setup	`project_publish_finish`	Initializes integration on deploy
Session End	`end_session`	Clears temporary customer data

Available Actions

- **Get Company** — Fetch company info and locations (GET `/company`)
- **Get Job Types** — Fetch available service types (GET `/job_fields/job_types`)
- **Get Employees** — Fetch employees, optionally by location (GET `/employees`)
- **Get Booking Windows** — Fetch available time slots (GET `/company/schedule_availability/booking_windows`)
- **Get Jobs** — Fetch scheduled jobs for conflict detection (GET `/jobs`)
- **Get Events** — Fetch calendar events for conflict detection (GET `/events`)
- **Search Customer** — Find existing customer by phone (GET `/customers`)
- **Create Customer** — Create a new customer record (POST `/customers`)
- **Add Customer Address** — Add a new address to an existing customer (POST `/customers/{id}/addresses`)
- **Create Job** — Create a service job (POST `/jobs`)
- **Create Appointment** — Schedule a time slot on a job (POST `/jobs/{id}/appointments`)
- **Cancel Appointment** — Delete a scheduled appointment (DELETE `/jobs/{id}/appointments/{apt_id}`)
- **Get Job Appointments** — Fetch appointments for a job (GET `/jobs/{id}/appointments`)

4.2 Architecture Diagrams

Overall Sequence

```
sequenceDiagram
    participant U as User
    participant A as ConvoAgent
    participant I as HCP Integration
    participant API as HouseCallPro API

    Note over I,API: Setup (on publish)
    A->>I: project_publish_finish
    I->>API: GET /company
    I->>API: GET /job_fields/job_types
    I->>API: GET /employees
    I->>A: Tools registered, data cached

    Note over I,API: Inbound Call
    A->>I: define_user_phone_number
    I->>API: GET /customers?q={phone}
```

```
    API-->>I: Customer data
    I->>API: GET /jobs?customer_id={id}
    API-->>I: Upcoming jobs
    I->>A: ExistingCustomerInfo injected

    Note over U,API: Availability Check
    U->>A: "Any slots this week?"
    A->>I: get_available_slots (job_description, zip_code)
    I->>I: Select employees (POC/job_type/zip)
    I->>API: GET /schedule_availability/booking_windows
    API-->>I: Available windows
    I->>A: result_success (availability[])
    A->>U: "Here are the available times..."

    Note over U,API: Booking
    U->>A: "Book Tuesday 10 AM"
    A->>I: book_slot (customerInfo, address, dateTime)
    I->>API: GET /customers?q={phone}
    alt Customer not found
        I->>API: POST /customers
    else Customer found, address differs
        I->>API: POST /customers/{id}/addresses
        Note over I: "Address updated" added to notes
    end
    I->>API: POST /jobs (customer_id, address_id, notes)
    I->>API: POST /jobs/{id}/appointments (time, employee)
    API-->>I: appointment_id
    I->>A: result_success (booking_id, job_id)
    A->>U: "Your appointment is confirmed!"

    Note over U,API: Cancellation
    U->>A: "Cancel my appointment"
    A->>I: convo_agent_cancel_booking (booking_id, job_id)
    I->>API: DELETE /jobs/{job_id}/appointments/{booking_id}
    API-->>I: Confirmation
    I->>A: result_success (cancelled)
    A->>U: "Your appointment has been cancelled"
```

StaticDataFlow (Caching)

```
flowchart TD
    E["session_started /<br>hcp_update_static_data"] --> CHK["Check cache age:
<br>updated_at vs now"]
    CHK --> STALE{"Cache older than<br>update_interval?"}
    STALE -->|"No"| SKIP["Use cached data"]
    STALE -->|"Yes"| COMP["GET /company<br>Extract locations, timezone"]
    COMP --> TYPES["GET /job_fields/job_types<br>Cache all job types"]
    TYPES --> LOC{"Multiple<br>locations?"}
    LOC -->|"No"| EMP["GET /employees?page_size=100"]
    LOC -->|"Yes"| EMP_LOC["GET /employees<br>per location_id"]
```

```
    EMP --> SAVE["Save to hcp_company_employees<br>Update timestamp"]
    EMP_LOC --> SAVE_LOC["Save to hcp_location_employees<br>Update timestamp"]
```

AvailabilityFlow (Employee Selection)

```
flowchart TD
    E["get_available_slots"] --> CHK{"Slot check<br>enabled?"}
    CHK -->|"No"| SKIP["Return (disabled)"]
    CHK -->|"Yes"| METHOD{"Employee<br>selection method?"}

    METHOD -->|"poc"| POC["Filter employees:<br>is_point_of_contact = true"]
    METHOD -->|"job_type"| JT["LLM matches job_description<br>to employee
tags/skills<br>(Gemini 2.5 Flash, temp 0.15)"]
    METHOD -->|"zip_code"| ZIP["Filter employees:<br>tags contain customer zip"]

    POC --> POC_API["GET /schedule_availability<br>/booking_windows<br>?
show_for_days=...&start_date=..."]
    POC_API --> POC_PARSE["Parse booking windows:<br>filter available=true,<br>group
by date"]

    JT --> FALLBACK{"Employees<br>found?"}
    ZIP --> FALLBACK
    FALLBACK -->|"No"| POC
    FALLBACK -->|"Yes"| MULTI["For each employee:"]
    MULTI --> JOBS["GET /jobs<br>?employee_ids[]={id}<br>&scheduled_start_min=
{date}"]
    JOBS --> EVENTS["GET /events<br>?page_size=20"]
    EVENTS --> CONFLICT["Detect conflicts:<br>exclude busy intervals<br>from
available windows"]
    CONFLICT --> BEST["Select employee with<br>earliest available slot"]

    POC_PARSE --> OUT["result_success<br>{availability[]}"]
    BEST --> OUT
```

BookingFlow

```
flowchart TD
    E["book_slot"] --> CHK{"Booking<br>enabled?"}
    CHK -->|"No"| SKIP["Return (disabled)"]
    CHK -->|"Yes"| PHONE["Format phone:<br>strip +, remove leading 1"]
    PHONE --> SEARCH["GET /customers?q={phone}"]
    SEARCH --> FOUND{"Customer<br>found?"}
    FOUND -->|"Yes"| ADDR{"Address matches<br>HCP profile?<br>(street + zip)"}
    FOUND -->|"No"| CREATE["POST /customers<br>{first_name, last_name,<br>phone,
email, address}"]
    CREATE --> NEW["Extract new<br>customer_id + address_id"]
    ADDR -->|"Yes"| USE["Use existing<br>address_id"]
    ADDR -->|"No"| ADD["POST /customers/{id}/addresses<br>Add new address"]
    ADD --> NOTE["Append 'Address updated'<br>to job notes"]
    NOTE --> JOB["POST /jobs<br>{customer_id, address_id, notes}"]
```

```
    USE --> JOB
    NEW --> JOB
    JOB --> LINE{"Auto line items<br>enabled?"}
    LINE -->|"Yes"| LLM["LLM matches description<br>to line_items catalog<br>and
job_types"]
    LINE -->|"No"| EMP["Get selected employee<br>(from availability step)"]
    LLM --> EMP
    EMP --> APPT["POST /jobs/{job_id}/appointments<br>{start_time (UTC),<br>end_time
(+duration hours),<br>dispatched_employees_ids[]}"]
    APPT --> OK{"Success?"}
    OK -->|"No"| ERR["result_error"]
    OK -->|"Yes"| OUT["result_success<br>{booking_id, job_id}"]
```

CancellationFlow

```
flowchart TD
    E["convo_agent_cancel_booking"] --> CHK{"Cancellation<br>enabled?"}
    CHK -->|"No"| SKIP["Return (disabled)"]
    CHK -->|"Yes"| VAL{"booking_id and<br>job_id present?"}
    VAL -->|"No"| ERR["result_error:<br>missing IDs"]
    VAL -->|"Yes"| API["DELETE /jobs/{job_id}<br>/appointments/{booking_id}"]
    API --> OK{"Success?"}
    OK -->|"No"| ERR2["result_error"]
    OK -->|"Yes"| OUT["result_success<br>{cancel_booking}"]
```

ExistingClientFlow (Caller Recognition)

```
flowchart TD
    E["define_user_phone_number"] --> CHK{"Check existing<br>client enabled?"}
    CHK -->|"No"| SKIP["Skip lookup"]
    CHK -->|"Yes"| SEARCH["GET /customers?q={phone}"]
    SEARCH --> FOUND{"Customer<br>found?"}
    FOUND -->|"No"| DONE["No context injected"]
    FOUND -->|"Yes"| INFO["Extract: name, email,<br>phone, address"]
    INFO --> JOBS["GET /jobs?customer_id={id}<br>&scheduled_start_min={today}"]
    JOBS --> APPTS["For each job:<br>GET /jobs/{id}/appointments"]
    APPTS --> INJECT["Inject ExistingCustomerInfo<br>into agent context"]
    INJECT --> DONE2["Agent sees customer<br>history on greeting"]
```

4.3 Where to Test

Testing can be done through the **Newo conversation interface** (voice or chat). Each flow has a dedicated webhook test endpoint:

- `availability_test_event` — AvailabilityFlow
- `appointment_test_event` — AppointmentFlow
- `appointment_test_cancel_event` — CancellationFlow
- `get_client_test_event` — ExistingClientFlow
- `update_static_test_event` — StaticDataFlow

4.4 Testing and Verification

To test the integration:

1. **Setup**: Publish the project and verify static data is cached (check `hcp_company_employees` is populated)
2. **Static Data**: Verify `hcp_company_info`, `hcp_job_types`, and `hcp_time_zone` are populated
3. **Existing Client**: Call from a known customer's phone — verify agent greets with context
4. **Availability**: Ask "What slots are available this week?" — verify slots returned with correct times
5. **Booking**: Complete a booking conversation with address — verify job and appointment appear in HouseCallPro
6. **Cancellation**: Request cancellation — verify appointment removed from HouseCallPro

If no action occurs:

- Ensure `hcp_api_key` is set correctly and has appropriate permissions
- Verify static data was cached (check `hcp_company_employees` is not empty)
- Confirm the relevant feature flags are enabled (`hcp_enable_booking`, `hcp_enable_slot_check`, `hcp_enable_cancellation`)
- For POC method: verify at least one employee has Point of Contact permission enabled in HouseCallPro
- For job_type method: verify employees have relevant tags/skills configured
- For zip_code method: verify employees have zip code tags matching the service area
- Check that `hcp_booking_duration` is set to the intended number of minutes. Legacy values `1..12` are still interpreted as hours for backward compatibility.
- Check that `hcp_show_for_days` is a reasonable value
- Re-publish the project if the API key was changed

> *Note: This integration performs real operations in HouseCallPro. Jobs, appointments, and customers created or cancelled through the agent are reflected in the live HouseCallPro system.*

5. FAQ

Q: What are the three employee selection methods and when should I use each? A: **POC** (default) assigns the Point of Contact employee — best for single-technician businesses or when one person handles all dispatch. **Job Type** uses AI to match the customer's service description to employee skills/tags — best for multi-specialty teams. **Zip Code** matches by service area — best for geographically distributed teams. Set via `hcp_auto_employee_type`.

Q: How does the AI line item matching work? A: When `hcp_auto_add_line_items` is enabled, the integration uses Gemini 2.5 Flash to match the customer's service description against the `hcp_line_items` catalog and `hcp_job_types`. The AI selects the most relevant items and attaches them to the job for accurate quoting.

Q: What customer information is required for booking? A: First name, phone number (E.164 format), and full service address (street, city, state, zip, country) are required. Last name defaults to the first name if not provided. Email is optional.

Q: How often is static data refreshed? A: By default every 24 hours (`hcp_static_data_update_interval` = 86400 seconds). The cache is checked on each session start. You can trigger a manual refresh via the `hcp_update_static_data` event or by re-publishing the project.

Q: What is the default appointment duration? A: 120 minutes, configurable via `hcp_booking_duration`. The end time is calculated as start time + duration in minutes. For backward compatibility, legacy values

`1..12` are still treated as hours and converted to minutes before sending requests to the API. Times are converted from the business timezone to UTC for the API.

Q: How does existing customer recognition work? A: When `hcp_check_existing_client` is enabled, the integration looks up the caller's phone number on inbound calls. If a customer is found, their profile and upcoming jobs are injected into the agent's context as `ExistingCustomerInfo`, allowing the agent to greet them by name and reference their scheduled services.

Q: What happens if the customer provides a different address than what's in their HCP profile? A: The integration compares the provided address against all stored addresses by **street + zip code** (case-insensitive). If no match is found, the new address is automatically added to the customer's profile via `POST /customers/{id}/addresses`, and the job notes include `"Address updated: {new address}"` so dispatchers are aware. The job is created with the new address ID.

Q: What happens if no employees match the selected method? A: The integration falls back to the POC method. If no POC employee is found either, the availability check will return no slots and the agent will inform the customer accordingly.