HubSpot Integration

1. Overview

1.1 Description

HubSpot Integration connects **HubSpot Meetings + CRM** with **Newo Platform**.

It currently supports:

- checking appointment availability from a HubSpot meeting link
- creating bookings with contact lookup / contact creation in HubSpot CRM
- cancelling existing meetings by exact booking datetime
- existing customer lookup by phone/email with prompt injection
- storing upcoming bookings in persona data
- optional outbound conversation note sync after phone sessions
- optional default canvas seeding for booking and cancellation scenarios

This integration is designed for **service businesses and sales teams** that use a single HubSpot meeting link and want an AI agent to handle appointment availability, booking, and cancellation through chat or voice.

1.2 Use Cases

- When a customer asks about available times -> the agent checks HubSpot meeting-link availability and returns free slots
- When a customer wants to book an appointment -> the agent finds or creates a HubSpot contact and submits the booking
- When a customer wants to cancel an appointment -> the agent finds the matching HubSpot meeting by start time and deletes it
- When the platform detects a caller's phone number -> the integration looks up the existing HubSpot contact and injects customer context
- When a future meeting exists for that contact -> the integration stores it in persona `bookings`
- When an outbound phone session ends -> the integration can write a HubSpot note with transcript/summary

1.3 Supported Features

Feature	Supported	Notes
Check Availability	✅	Uses HubSpot meeting-link booking endpoint
Book Appointment	✅	Searches contact by email, creates contact if missing, then books
Cancel Appointment	✅	Finds meeting by exact start datetime, then deletes it
Existing Client Detection	✅	Searches HubSpot contacts by phone/email
Existing Booking Storage	✅	Saves future meetings into persona `bookings`
Silent Availability Preload	✅	`session_started` can trigger a silent availability check
Outbound Conversation Note Sync	✅	Only for `Outgoing Phone` sessions and when enabled

Canvas Auto Setup	✅	Seeds default booking/cancellation scenarios when enabled
Multi-Calendar / Multi-Slug	❌	Single `hubspot_slug_name`
Native Reschedule Flow	❌	Use cancel + rebook flow
Deal / Pipeline Automation	❌	Not implemented in current agent flows

2. Requirements

Before setup:

- active **HubSpot** account
- **HubSpot Meetings** enabled
- one working **meeting link slug**
- one **HubSpot Service Key** (PAT-style token) with the scopes your booking flows require
- correct business timezone

Current setup is **token-based** from the customer side.

3. How to Setup

3.1 Step 1 — Create a HubSpot Service Key

1. Open HubSpot.
2. Go to **Settings > Integrations > Service Keys**.
3. Create a new key with the CRM / Meetings permissions your flow needs.
4. Copy the generated token.

3.2 Step 2 — Find the Meeting Link Slug

Example:

- full link: `https://meetings-eu1.hubspot.com/test-meetings-page`
- slug: `test-meetings-page`

Put only the last path segment into `hubspot_slug_name`.

3.3 Step 3 — Configure Attributes in Newo

Open **Newo -> Projects -> Builder / Attributes** and set:

Attribute	Required	Description
`hubspot_auth_type`	✅	Current customer-facing mode is `Token`
`hubspot_service_key`	✅	HubSpot Service Key / PAT
`hubspot_slug_name`	✅	HubSpot meeting link slug
`hubspot_base_api_url`	❌	Defaults to `https://api.hubapi.com`
`hubspot_timezone`	❌	Defaults to project business timezone
`hubspot_duration`	❌	Slot length in minutes, default `30`

`hubspot_show_for_days`	❌	Search window in days, default `1`
`hubspot_slots_available`	❌	Enable / disable availability flow
`hubspot_booking_available`	❌	Enable / disable booking flow
`hubspot_cancelation_available`	❌	Enable / disable cancellation flow
`hubspot_sync_conversation`	❌	Enable / disable outbound phone note sync
`hubspot_setup_scenarios`	❌	Auto-add default booking/cancellation scenarios to canvas

Hidden/system attributes are managed by setup automatically, for example:

- `hubspot_override_agent_attributes`
- `setup_persona_id`

3.4 Step 4 — Publish

On publish, the current setup logic:

- syncs project attributes and tool-gating attributes
- injects booking and availability payload schemas
- ensures both `api` and `http` connector entries exist for `hubspot_connector`
- creates / reuses the setup persona
- validates the HubSpot connection with: `GET /crm/v3/objects/contacts?limit=1`

If `hubspot_setup_scenarios = True`, the integration also participates in workflow-builder canvas setup through `CanvasSetupFlow`.

4. How It Works

4.1 Flows

Flow	Purpose
`SetupFlow`	Attribute sync, tool gating, setup persona creation, connection validation
`CanvasSetupFlow`	Auto-seeds booking/cancellation canvas items when enabled
`UtilsFlow`	Normalizes outbound HubSpot requests and routes connector results
`AvailabilityFlow`	Checks meeting-link availability and returns free slots
`BookingFlow`	Searches/creates contact and books the meeting link
`CancellationFlow`	Finds the meeting by start time and deletes it
`ExistingClientFlow`	Finds HubSpot contact by phone/email and stores future meetings
`ConversationFlow`	Writes outbound phone conversation notes into HubSpot
`MetadataFlow`	Returns integration version

4.2 Triggers

Trigger	Event	Flow
Check Availability	`get_available_slots`	`AvailabilityFlow`
Book Appointment	`book_slot`	`BookingFlow`
Cancel Appointment	`convo_agent_cancel_booking`	`CancellationFlow`
Existing Client Lookup	`define_user_phone_number`	`ExistingClientFlow`
Silent Availability	`session_started`	`AvailabilityFlow`
Setup	`project_publish_finish`	`SetupFlow`
Canvas Rebuild	`gm_workflow_builder_canvas_built`	`CanvasSetupFlow`
Outbound Session Sync	`session_ended`	`ConversationFlow`

4.3 Main API Actions

Action	Method	Endpoint
Validate Connection	`GET`	`/crm/v3/objects/contacts?limit=1`
Search Contact	`POST`	`/crm/v3/objects/contacts/search`
Create Contact	`POST`	`/crm/v3/objects/contacts`
Get Availability	`GET`	`/scheduler/v3/meetings/meeting-links/book/{slug}?timezone={tz}`
Book Meeting	`POST`	`/scheduler/v3/meetings/meeting-links/book?timezone={tz}`
Search Meetings	`POST`	`/crm/v3/objects/meetings/search`
Delete Meeting	`DELETE`	`/crm/v3/objects/meetings/{id}`
Create Note	`POST`	`/crm/v3/objects/notes`

4.4 Overall Sequence

```
sequenceDiagram
    participant U as User
    participant A as ConvoAgent
    participant I as HubSpotAgent
    participant API as HubSpot API

    Note over I: Setup
    A->>I: project_publish_finish
    I->>API: GET /crm/v3/objects/contacts?limit=1
    API-->>I: connection validated

    Note over U,API: Existing Client
    A->>I: define_user_phone_number
    I->>API: POST /crm/v3/objects/contacts/search
    API-->>I: contact result
```

```
    I->>A: set_prompt_custom_section(ExistingCustomerInfo)
    I->>API: POST /crm/v3/objects/meetings/search
    API-->>I: future meetings

    Note over U,API: Availability
    U->>A: asks for slots
    A->>I: get_available_slots
    I->>API: GET /scheduler/v3/meetings/meeting-links/book/{slug}
    API-->>I: busy time payload
    I->>I: build free slots
    I->>A: result_success(availability)

    Note over U,API: Booking
    U->>A: confirms datetime
    A->>I: book_slot
    I->>API: POST /crm/v3/objects/contacts/search
    alt contact missing
        I->>API: POST /crm/v3/objects/contacts
        API-->>I: contact id
    end
    I->>API: POST /scheduler/v3/meetings/meeting-links/book
    API-->>I: booking result
    I->>A: result_success or result_error

    Note over U,API: Cancellation
    U->>A: asks to cancel
    A->>I: convo_agent_cancel_booking
    I->>API: POST /crm/v3/objects/meetings/search
    API-->>I: meeting id
    I->>API: DELETE /crm/v3/objects/meetings/{id}
    API-->>I: cancellation result
    I->>A: result_success or result_error
```

4.5 AvailabilityFlow

```
flowchart TD
    E["get_available_slots / session_started"] --> G{"hubspot_slots_available?"}
    G -->|"No"| SKIP["Return"]
    G -->|"Yes"| PREP["Build search window from date + hubspot_show_for_days"]
    PREP --> API["GET meeting-link booking endpoint"]
    API --> OK{"HTTP success?"}
    OK -->|"No"| ERR["ExecuteResultError -> result_error"]
    OK -->|"Yes"| BUSY["Read allUsersBusyTimes"]
    BUSY --> CALC["Generate free slots using hubspot_duration"]
    CALC --> OUT["result_success with availability[]"]
```

Current implementation detail:

- availability is generated from `allUsersBusyTimes`
- the flow does **not** use `linkAvailabilityByDuration` as the authoritative slot list

4.6 BookingFlow

```
flowchart TD
    E["book_slot"] --> G{"hubspot_booking_available?"}
    G -->|"No"| SKIP["Return"]
    G -->|"Yes"| SEARCH["POST contacts/search by email"]
    SEARCH --> FOUND{"Contact found?"}
    FOUND -->|"Yes"| BOOK["POST booking endpoint"]
    FOUND -->|"No"| CREATE["POST contacts"]
    CREATE --> BOOK
    BOOK --> OK{"calendarEventId present?"}
    OK -->|"Yes"| OUT["result_success"]
    OK -->|"No"| ERR["ExecuteResultError -> result_error"]
```

Important runtime details:

- contact search is by **email**
- booking uses exact `bookingDateTime`
- booking request body includes: `slug`, `firstName`, `lastName`, `email`, `startTime`, `duration`, `timezone`

4.7 CancellationFlow

```
flowchart TD
    E["convo_agent_cancel_booking"] --> G{"hubspot_cancelation_available?"}
    G -->|"No"| SKIP["Return"]
    G -->|"Yes"| UTC["Convert local datetime to UTC"]
    UTC --> FIND["POST meetings/search by hs_meeting_start_time"]
    FIND --> FOUND{"Meeting id found?"}
    FOUND -->|"No"| ERR["ExecuteResultError -> result_error"]
    FOUND -->|"Yes"| DEL["DELETE meeting by id"]
    DEL --> OUT["result_success / result_error"]
```

Important runtime detail:

- cancellation is driven by exact `datetime`
- the flow does **not** cancel by booking URL or contact association

4.8 ExistingClientFlow

```
flowchart TD
    E["define_user_phone_number"] --> SEARCH["POST contacts/search by phone OR
email"]
    SEARCH --> FOUND{"Contact found?"}
    FOUND -->|"No"| DONE["Return"]
    FOUND -->|"Yes"| INJECT["set_prompt_custom_section ExistingCustomerInfo"]
    INJECT --> APPTS["POST meetings/search by associations.contact"]
    APPTS --> FILTER["Keep only future meetings"]
    FILTER --> SAVE["Store into persona bookings"]
```

Runtime outputs:

- custom prompt section: `ExistingCustomerInfo role="context"`
- persona storage: `bookings`

4.9 ConversationFlow

This flow is only for outbound phone-note sync.

It runs on `session_ended` and:

- checks `hubspot_sync_conversation`
- only continues for channel `Outgoing Phone`
- resolves the contact by `contact_id`, phone, or email
- creates a HubSpot note with summary/transcript data

5. Canvas Setup

`CanvasSetupFlow` exists and auto-runs on:

- `gm_workflow_builder_canvas_built`

Current behavior:

- `SetupLibrarySkill` seeds custom `hubspot_*` intents and scenarios into the library
- `SetupCanvasSkill` currently inserts common appointment/cancellation library items into the active canvas
- auto-setup is controlled by visible attribute: `hubspot_setup_scenarios`

6. Testing

6.1 Conversation Testing

Recommended live checks:

1. publish the integration
2. verify setup validation succeeds
3. ask for availability on a concrete date/time
4. book a new customer with email + phone
5. cancel by exact appointment datetime
6. test existing-client lookup by known phone number

6.2 Webhook Test Events

The integration also exposes test hooks for direct flow testing:

Event	Flow	Purpose
`availability_wh`	`AvailabilityFlow`	Trigger availability test payload
`book_wh`	`BookingFlow`	Trigger booking test payload
`cancel_wh`	`CancellationFlow`	Trigger cancellation test payload

6.3 What to Verify

- `SetupFlow`: token validation request succeeds

- `CanvasSetupFlow` : default items are added when `hubspot_setup_scenarios=True`
- `AvailabilityFlow` : returned slots match the current meeting-link behavior
- `BookingFlow` : contact search/create works and booking endpoint accepts the chosen time
- `CancellationFlow` : meeting search finds the correct meeting and delete succeeds
- `ExistingClientFlow` : `ExistingCustomerInfo` appears and future bookings are stored

6.4 Troubleshooting

If setup fails:

- confirm `hubspot_service_key` is valid
- confirm the token has the scopes needed by your booking flows
- confirm `hubspot_base_api_url` is correct

If availability works but booking fails:

- verify the chosen time is still valid for the meeting link
- verify timezone alignment between `hubspot_timezone` , user request, and HubSpot meeting settings
- note that the current implementation computes free slots from `allUsersBusyTimes` ; HubSpot may still reject a time if it does not fit the meeting link's live availability settings

If existing-client lookup does nothing:

- confirm the incoming phone number/email matches a HubSpot contact
- confirm the contact has future meetings associated to it

If outbound note sync does nothing:

- confirm `hubspot_sync_conversation=True`
- confirm the session channel is exactly `Outgoing Phone`

7. FAQ

Q: What authentication method does the current setup use?
A: Current customer-facing setup uses a **HubSpot Service Key / Token**. The visible auth attribute is `hubspot_auth_type` , and in the current setup it is fixed to `Token` .

Q: Does this integration still use the old OAuth-code + refresh-token setup?
A: No. The current README and current setup flow are token-based from the customer side. The old `hubspot_oauth_code` , `client_id` , `client_secret` , and refresh-token instructions are obsolete.

Q: How are contacts matched during booking?
A: Booking first searches HubSpot contacts by **email**. If no contact is found, a new contact is created.

Q: How does cancellation identify the meeting to delete?
A: It converts the requested local datetime to UTC, searches meetings by exact `hs_meeting_start_time` , then deletes the found meeting ID.

Q: What customer context is injected into the prompt?
A: `ExistingClientFlow` injects `ExistingCustomerInfo role="context"` and stores future meetings in persona `bookings` .

Q: Why can availability say a slot is open but booking still fail?
A: The current availability logic derives free slots from `allUsersBusyTimes` . HubSpot booking still validates the submitted `startTime` against its own live meeting-link availability settings.

Q: Can I disable the default canvas scenarios?
A: Yes. Set `hubspot_setup_scenarios` to `False`.

Q: What is the meeting slug?
A: It is the last path segment of your HubSpot meeting link, stored in `hubspot_slug_name`.