

Cal.com Integration

What the AI can do

Summary

Cal.com Integration connects **Cal.com** (open-source scheduling platform) with **Newo Platform**.

It enables:

- Checking real-time availability slots with configurable booking window
- Booking appointments with dynamic custom field support
- Cancelling existing appointments
- Rescheduling appointments using AI-powered extraction from conversation
- Two operation modes: strict availability ("general") and overbooking-friendly ("guest")

This integration is designed for **businesses and service providers** who need **automated appointment scheduling through a conversational AI agent** (voice or chat) using hosted Cal.com US or EU accounts.

Common use cases

- When a client asks about available slots → Check Cal.com availability and return open time slots for the configured booking window
- When a client wants to book an appointment → Collect customer info and custom fields, create booking in Cal.com
- When a client wants to cancel an appointment → Cancel the booking in Cal.com with reason
- When a client wants to reschedule → AI extracts booking details from conversation and reschedules in Cal.com
- When a conversation starts → Silently preload nearest available slots into agent's prompt context

Features at a glance

Feature	Supported	Notes
Check Availability	✓	Configurable booking window (default: 5 days)
Book Appointment	✓	With dynamic custom booking fields from event type
Cancel Appointment	✓	With cancellation reason
Reschedule Appointment	✓	AI-powered payload extraction from conversation
Silent Availability Preload	✓	Injects slots into prompt on session start
General Mode	✓	Strict availability — prevents overbooking
Guest Mode	✓	Allows overbooking, adds manager as guest
Personal Event Types	✓	Individual calendar events
Team Event Types	✓	Team-level calendar events
Dynamic Custom Fields	✓	Auto-discovered from Cal.com event type configuration
Self-Hosted Cal.com	✓	Configurable base URL

Multi-Location Support	✗	One event type per instance; use multiple instances
Existing Client Lookup	✗	ExistingClientFlow is a placeholder

Before You Start

Before installation:

- Active hosted **Cal.com** account in the US or EU environment
- **Cal.com API Token** (Bearer token for v2 API)
- Cal.com hosting region (**US** or **EU**)

Setup

Create the Newo project

If this project already exists in **Newo Builder**, skip this subsection and continue with the integration-specific settings below.

1. In **Newo Builder**, open the projects list and click **Create Project** (or **Create New Project** from the top-right menu).

 Create New Project menu in Newo Builder

2. Fill **IDN** and **Title**. The exact names do not matter; use any clear names your team will recognize.
3. In **Registry**, choose the release channel:
 - **staging** — the newest module fixes appear here first. Use it when you need the latest fix, but expect possible unfinished changes.
 - **production** — the final stable version for live projects.
4. In **Module**, select the module for this integration.

 Create Project form showing IDN, Title, Registry, and Module fields 5. Leave **Module version** on **Latest version** unless support tells you to pin a specific version, then click **Create**.

3.1 Step 1 — Generate API Token in Cal.com

1. Log in to your **Cal.com** account
2. Navigate to **Settings → Developer → API Keys**
3. Click **Create API Key**
4. Copy the generated token and store it securely

3.2 Step 2 — Connect in Platform

1. Open **Newo → Projects**
2. Set the following attributes in **Builder / Attributes**:

Attribute	Required	Description
calcom_api_token	✓	Bearer token for Cal.com API authentication
calcom_region	✗	Hosting region: US or EU (default: US)

calcom_base_url	✗	API base URL; managed automatically from calcom_region
calcom_mode	✗	Operation mode: general or guest (default: general)
calcom_event_mode	✗	Event source: Personal or Team (default: Personal)
calcom_event_type	✗	Auto-populated during setup from available event types
calcom_booking_window	✗	Days into future to show slots (default: 5)
calcom_enable_slot_check	✗	Enable availability checking (default: True)
calcom_enable_booking	✗	Enable booking capability (default: True)
calcom_enable_cancellation	✗	Enable cancellation capability (default: True)
calcom_required_field_descriptions	✗	Descriptions for custom fields (one per line: field: desc)

3. Click **Save + Publish All**

4. On publish, the SetupFlow automatically:

- Validates the API token
- Fetches available teams from Cal.com
- Fetches and selects event types (Personal or Team)
- Extracts custom booking fields from event type configuration
- Injects dynamic booking schemas for the agent

How to use the integration

This section explains how the integration works, how to configure automation, and how to test it.

4.1 How the Integration Works

The integration operates based on **Triggers and Actions** via the event-driven system.

- A **Trigger** is a system event that starts a flow
- An **Action** is the API operation performed in Cal.com

Where to test

Testing can be done through the **Newo conversation interface** (chat or voice channel) by interacting with the agent. Use the chat transcript and external-system console to confirm the result.

How to test that everything works

To test the integration:

1. **Setup:** Publish the project and verify logs show successful event type discovery and schema injection
2. **Availability:** Ask the agent "What slots are available this week?" — verify slots returned from Cal.com
3. **Booking:** Complete a booking conversation with name, email, phone — verify appointment appears in Cal.com dashboard

4. **Cancellation:** Request cancellation of a booked appointment — verify status changed in Cal.com
5. **Reschedule:** Ask to move an existing appointment — verify new time in Cal.com

If no action occurs:

- Ensure `calcom_api_token` is set correctly
- Verify `calcom_base_url` points to the correct Cal.com instance
- Confirm `calcom_event_type` was populated during setup (re-publish if empty)
- Check that the relevant feature flags are enabled (`calcom_enable_booking` , `calcom_enable_slot_check` , `calcom_enable_cancellation`)
- Verify `calcom_mode` is set to the desired operation mode

Note: This integration performs real operations in Cal.com. Appointments created, cancelled, or rescheduled through the agent are reflected in the live Cal.com system.

FAQ

Q: Does the integration import historical appointments? A: No. Only appointments created after activation are processed. Rescheduling references bookings stored in persona attributes from prior agent interactions.

Q: Can I connect multiple Cal.com accounts? A: Each integration instance supports one API token and one event type. For multiple accounts or event types, create separate integration instances.

Q: What is the difference between "general" and "guest" mode? A: In **general** mode, the agent checks availability before booking — overbooking is prevented. In **guest** mode, availability checks are bypassed and the manager is added as a guest to the meeting, allowing overbooking.

Q: How are custom booking fields handled? A: During setup, the integration auto-discovers required custom fields from the Cal.com event type configuration. These fields are injected into the booking schema so the agent knows to collect them from the user. Field descriptions can be customized via the `calcom_required_field_descriptions` attribute.

Q: Does it work with self-hosted Cal.com? A: The current hosted-region setup supports Cal.com US and EU endpoints. Self-hosted instances are not part of this setup flow.

Q: What happens on session start? A: If `calcom_enable_slot_check` is enabled, the integration silently fetches today's availability and injects it into the agent's prompt context. This allows the agent to proactively mention available slots without the user asking first.

Q: What slot durations are supported? A: Slot duration is determined by the selected Cal.com event type (e.g., 15, 30, 60 min). The `calcom_booking_window` attribute controls how many days ahead to show slots (default: 5 days).