

# Kommo Integration

See also: [TESTING\\_GUIDE.md](#)

## 1. Overview

### 1.1 Description

**Kommo Integration** connects **KommoCRM** (sales-focused CRM platform) with **Newo Platform**.

It enables:

- Automatic contact creation and updates in KommoCRM after each conversation
- Lead management with AI-powered pipeline stage selection
- Conversation transcript and analysis notes attached to CRM records
- Lead deduplication and tagging for tracking Newo-originated deals
- OAuth 2.0 authentication with automatic token refresh

This integration is designed for **sales teams and business owners** who need **automatic CRM synchronization based on conversational AI agent interactions** (voice or chat).

### 1.2 Use Cases

- When a conversation ends → Analyze results and create/update contact and lead in KommoCRM
- When a new caller is detected → Create contact with phone number and name in CRM
- When a returning caller contacts → Find existing contact, update notes, and adjust lead stage
- When a conversation is successful → Move lead to the appropriate pipeline stage based on AI analysis
- When a conversation fails → Move lead to the corresponding failure stage based on custom rules

### 1.3 Supported Features

| Feature                    | Supported | Notes                                            |
|----------------------------|-----------|--------------------------------------------------|
| Contact Creation           | ✓         | By phone number, first/last name                 |
| Contact Lookup             | ✓         | Search by phone number                           |
| Contact Notes              | ✓         | Full conversation analysis attached as note      |
| Lead Creation              | ✓         | With pipeline, stage, tag, and contact link      |
| Lead Stage Update          | ✓         | AI-powered stage selection via LLM (Gemini)      |
| Lead Deduplication         | ✓         | Filters by configurable tag (default: "newo")    |
| Pipeline Discovery         | ✓         | Auto-fetches available pipelines and stages      |
| Custom Decision Rules      | ✓         | Free-text business rules for stage selection     |
| OAuth 2.0 Token Management | ✓         | Auto-refresh with retry logic (up to 3 attempts) |
| Public Integration Mode    | ✓         | Pre-configured with Newo's OAuth app             |
| Private Integration Mode   | ✓         | Customer's own OAuth app credentials             |

|                        |   |                                     |
|------------------------|---|-------------------------------------|
| Booking / Availability | ✗ | CRM-only integration, no scheduling |
|------------------------|---|-------------------------------------|

## 2. Requirements

Before installation:

- Active **KommoCRM** account
- **OAuth 2.0 authorization** — either via Newo's public app or your own private OAuth app
- Kommo account **subdomain** (e.g., `mycompany` from `mycompany.kommo.com` )

## 3. How to Setup

### 3.1 Step 1 — Authorize in KommoCRM

**Public Integration (recommended):**

1. In Newo platform, set `kommo_subdomain` to your Kommo subdomain
2. Click the KommoCRM authorization link provided by the platform
3. Authorize the Newo app in your KommoCRM account
4. Select the sub-account (workspace) if prompted
5. Copy the **authorization code** from the redirect URL
6. Paste the code into the `kommo_oauth_code` attribute

**Private Integration:**

1. Log in to **KommoCRM → Settings → Integrations**
2. Create a new **private integration**
3. Copy the **Client ID** and **Client Secret**
4. Set `kommo_integration_type` to "Private Integration"
5. Enter your Client ID and Client Secret in the corresponding attributes
6. Complete the OAuth authorization and paste the code

### 3.2 Step 2 — Connect in Platform

1. Open **Newo → Projects**
2. Set the following attributes in **Builder / Attributes**:

| Attribute                                  | Required | Description                                                   |
|--------------------------------------------|----------|---------------------------------------------------------------|
| <code>kommo_subdomain</code>               | ✓        | Your Kommo account subdomain (e.g., <code>mycompany</code> )  |
| <code>kommo_oauth_code</code>              | ✓        | One-time OAuth authorization code                             |
| <code>kommo_integration_type</code>        | ✗        | Public Integration Or Private Integration (default: Private)  |
| <code>kommo_client_id</code>               | ✗        | OAuth Client ID (only for Private Integration)                |
| <code>kommo_client_secret</code>           | ✗        | OAuth Client Secret (only for Private Integration)            |
| <code>kommo_enable_client_history</code>   | ✗        | Enable CRM sync on session end (default: <code>False</code> ) |
| <code>kommo_pipeline</code>                | ✗        | Auto-populated from available pipelines                       |
| <code>kommo_pipeline_decision_rules</code> | ✗        | Custom business rules for AI stage selection                  |

|                |   |                                            |
|----------------|---|--------------------------------------------|
| kommo_lead_tag | ✗ | Tag for Newo-created leads (default: newo) |
|----------------|---|--------------------------------------------|

3. Click **Save + Publish All**

4. On publish, the SetupFlow automatically:

- Exchanges the OAuth code for access and refresh tokens
- Fetches available pipelines from KommoCRM
- Fetches pipeline stages for the selected pipeline
- Stores tokens and pipeline configuration

## 4. How to Use

This section explains how the integration works, how to configure automation, and how to test it.

### 4.1 How the Integration Works

The integration operates based on **Triggers and Actions** via the event-driven system.

Unlike scheduling integrations, Kommo integration is **post-conversation** — it processes results after the conversation ends, not during it.

- A **Trigger** is a system event that starts a flow
- An **Action** is the API operation performed in KommoCRM

#### Available Triggers

| Trigger              | Event                  | Description                                 |
|----------------------|------------------------|---------------------------------------------|
| <b>Session Ended</b> | session_ended          | When a conversation finishes — main trigger |
| <b>Setup</b>         | project_publish_finish | Initializes integration on deploy           |
| <b>Test</b>          | test_integration       | Webhook test with sample conversation data  |

#### Available Actions

- **Search Contact** — Find existing contact by phone number (GET `/contacts` )
- **Create Contact** — Create new contact with phone and name (POST `/contacts` )
- **Add Note** — Attach conversation analysis to contact (POST `/contacts/{id}/notes` )
- **Create Lead** — Create lead with pipeline stage and contact link (POST `/leads` )
- **Update Lead** — Change lead pipeline stage (PATCH `/leads/{id}` )
- **Get Lead** — Retrieve existing leads to check for deduplication (GET `/leads` )
- **Get Pipelines** — Discover available pipelines (GET `/leads/pipelines` )
- **Get Stages** — Fetch pipeline stages (GET `/leads/pipelines/{id}/statuses` )

### 4.2 Architecture Diagrams

#### Overall Sequence

```
sequenceDiagram
    participant U as User
    participant A as ConvoAgent
    participant I as Kommo Integration
    participant T as Kommo OAuth
    participant API as KommoCRM API
```

```

Note over I,T: Setup (on publish)
A->>I: project_publish_finish
I->>T: POST /oauth2/access_token (code)
T-->>I: access_token + refresh_token
I->>API: GET /leads/pipelines
API-->>I: Pipelines list
I->>API: GET /leads/pipelines/(id)/statuses
API-->>I: Pipeline stages
I->>A: Pipeline configured

```

```

Note over U,API: Conversation happens
U->>A: (conversation takes place)
A->>U: (agent responds, conversation ends)

```

```

Note over U,API: Post-Conversation CRM Sync
A->>I: session_ended (summary, category, success, transcript, phone)
I->>I: LLM analyze conversation -> select pipeline stage
I->>API: GET /contacts?query=(phone)
API-->>I: Contact results
alt Contact not found
    I->>API: POST /contacts (name, phone)
    API-->>I: New contact_id
end
I->>API: POST /contacts/(id)/notes (analysis)
API-->>I: Note created
alt Existing lead with "newo" tag
    I->>API: PATCH /leads/(id) (status_id)
    API-->>I: Lead updated
else No existing lead
    I->>API: POST /leads (pipeline, stage, contact, tag)
    API-->>I: Lead created
end

```

## SalesFlow (Main Flow)

```

flowchart TD
    E["session_ended"] --> G1["GATE{Client history<br>enabled?}"]
    G1 -->|"No"| S1["SKIP{Skip}"]
    G1 -->|"Yes"| L1["LLM[LLM analyze conversation:<br>stage_id, first_name,<br>last_name, explanation]"]
    L1 --> S2["SEARCH[GET /contacts<br>?query={phone}]"]
    S2 --> F1["FOUND{Contact<br>found?}"]
    F1 -->|"No"| C1["CREATE[POST /contacts<br>{name, phone}]"]
    C1 --> N1["NOTE"]
    F1 -->|"Yes"| N2["NOTE[POST /contacts/{id}/notes<br>{summary, transcript}]"]
    N1 --> L2["LEADS{Has existing<br>leads?}"]
    L2 -->|"No"| N3["NEW_LEAD[POST /leads<br>{pipeline, stage,<br>contact, tag:newo}]"]
    L2 -->|"Yes"| G2["GET_LEAD[GET /leads<br>?filter[id]={ids}&with=tags]"]
    G2 --> T1["TAGGED{Lead with<br>newo tag?}"]

```

```

TAGGED -->|"Yes"| UPDATE["PATCH /leads/{id}<br>{status_id}"]
TAGGED -->|"No"| NEW_LEAD
UPDATE --> DONE["Done"]
NEW_LEAD --> DONE

```

### SetupFlow

```

flowchart TD
    E["project_publish_finish"] --> INIT["Initialize attributes<br>and connectors"]
    INIT --> CODE{"OAuth code<br>provided?"}
    CODE -->|"No"| WAIT["Wait for code"]
    CODE -->|"Yes"| TOKEN["POST /oauth2/access_token<br>{code, client_id, secret}"]
    TOKEN --> OK1{"Tokens<br>received?"}
    OK1 -->|"No"| ERR["ResultError"]
    OK1 -->|"Yes"| SAVE["Save access_token<br>and refresh_token"]
    SAVE --> PIPE["GET /leads/pipelines"]
    PIPE --> SELECT["Auto-select pipeline<br>Create enum attribute"]
    SELECT --> STAGES["GET /leads/pipelines/{id}/statuses"]
    STAGES --> STORE["Store stages as JSON<br>for LLM decision-making"]
    STORE --> DONE["Setup complete"]

```

### Token Refresh (UtilsFlow)

```

flowchart TD
    REQ["Any API request"] --> HTTP["Send via<br>kommo_connector"]
    HTTP --> STATUS{"HTTP<br>status?"}
    STATUS -->|"2xx"| SUCCESS["kommo_result_success"]
    STATUS -->|"401"| REFRESH["POST /oauth2/access_token<br>{grant_type: refresh_token}"]
    REFRESH --> TOK_OK{"New token<br>received?"}
    TOK_OK -->|"Yes"| RETRY["Save tokens<br>Retry original request<br>(max 3 attempts)"]
    TOK_OK -->|"No"| ERR["kommo_result_error"]
    STATUS -->|"4xx/5xx"| ERR
    RETRY --> HTTP

```

## 4.3 Where to Test

Testing can be done by:

- Triggering a real conversation through the **Newo conversation interface** (chat or voice) and verifying CRM records after the session ends
- Using the `test_integration` webhook event with sample conversation data

## 4.4 Testing and Verification

To test the integration:

1. **Setup**: Publish the project and verify logs show successful OAuth token exchange and pipeline discovery
2. **CRM Sync**: Complete a conversation through the agent — after session ends, verify:

- Contact appears in KommoCRM with correct phone and name
- Conversation note is attached to the contact
- Lead is created in the correct pipeline stage with "newo" tag

3. **Lead Update:** Complete a second conversation with the same phone number — verify:

- Existing contact is found (not duplicated)
- New note is added
- Existing "newo"-tagged lead stage is updated (not duplicated)

**If no action occurs:**

- Ensure `kommo_enable_client_history` is set to `True`
- Verify OAuth tokens were obtained (check `kommo_access_token` is not empty)
- Confirm `kommo_subdomain` is correct
- Check that `kommo_pipeline` is selected
- Verify the OAuth code hasn't expired (codes are single-use)
- Re-publish the project if credentials were changed

*Note: This integration performs real operations in KommoCRM. Contacts and leads created through the agent are reflected in the live CRM system.*

## 5. FAQ

**Q: Does the integration import historical CRM data?** A: No. The integration only creates/updates contacts and leads based on conversations that happen after activation.

**Q: Can I connect multiple KommoCRM accounts?** A: Each integration instance supports one Kommo account (subdomain). For multiple accounts, create separate integration instances.

**Q: How does the AI select the pipeline stage?** A: After each conversation, an LLM (Gemini) analyzes the conversation summary, category, success status, and transcript. It applies custom business rules from `kommo_pipeline_decision_rules` and selects the most appropriate stage. The decision includes an explanation for transparency.

**Q: What is the difference between Public and Private integration?** A: **Public Integration** uses Newo's pre-registered OAuth app in KommoCRM — no additional setup needed. **Private Integration** lets you use your own OAuth app credentials, giving you more control over permissions and branding.

**Q: How are duplicate leads prevented?** A: Leads created by Newo are tagged with a configurable tag (default: "newo"). When a returning caller is detected, the integration searches for existing leads with this tag. If found, the lead's stage is updated. If not, a new lead is created.

**Q: What data is stored in the contact note?** A: Each note contains the full conversation analysis: summary, category, success/failure status, detailed results, and the complete transcript. This provides full context for sales team review.

**Q: What happens if the OAuth token expires?** A: The integration automatically detects HTTP 401 responses and refreshes the token using the refresh token. It retries the failed request up to 3 times. Token refresh uses a separate HTTP connector for isolation.