Yassir Samadi - October 22, 2026

Practical Lab Report — Local AI with Ollama & RAG

M1 : Agentic AI & Building AI Agents

---

1. Introduction & Lab Objectives

While LLMs are changing how we build software and handle natural language processing, relying entirely on cloud APIs (like OpenAI, Anthropic, or Google) brings a few major drawbacks:

- Privacy and compliance: Strict regulations like GDPR, along with company trade secrets or medical and academic records, mean we often can't send raw data over third-party networks.
- Cost: Pay-per-token pricing models scale up fast as you get more users and bigger context windows.
- Reliability and speed: Cloud services need a steady internet connection and can still suffer from network lag, slow cold starts, or unexpected downtime.
- For this lab, my goal is to build, test, and run a 100% self-hosted, local AI stack right on my personal Mac M2. To get everything running, I'm using Ollama for local model inference, lightweight quantized models (qwen2.5:0.5b and smollm2:135m), a local RAG engine powered by TF-IDF ranking, and a Flask web app for the interface.



2. Experimental Walkthrough Across Lab Parts

Parts 1 & 2 — Architecture & Environment Setup

- **Core Mechanism**: Client applications interact directly with the local Ollama daemon over port `11434`:
- **Verification**: The Ollama service was installed and run as a local background daemon. Querying `http://localhost:11434` confirmed operational status (`"Ollama is running"`).

Parts 3 & 4 — Prompt Engineering & Audience Adaptation

- Conditioning: Changing the target audience right in the system prompt—like asking the model to explain AI in five sentences to a 10-year-old versus a computer science professor—showed how

adaptable it really is. It easily switched from playful metaphors (like a friendly robot learning through games) to formal academic terminology (such as constrained optimization, loss functions, and probabilistic inference).

Core Elements of Effective Prompts:

- **Role**: Sets the model's authority and technical depth
- **Context**: Defines the background or target audience
- **Constraints**: Sets clear limits on structure and length
- **Output Format**: Controls how the final response is organized
- **Specificity**: Keeps the model focused and prevents vague tangents by asking for concrete, verifiable outputs.

Part 5 — Model Inventory & VRAM Lifecycle

- `ollama list` (`/api/tags`): Inspects all models downloaded and archived on the local SSD, providing file size, architecture family, and quantization profile.
- `ollama ps` (`/api/ps`): Monitors models actively resident in system memory (RAM/VRAM), tracking memory allocation and the automatic time-to-live (`expires_at`).

Part 6 — Comparative Evaluation of Local Models (Python Code Generation)

Both models were prompted to generate a robust Python prime-checking function (`is_prime`) with type annotations, docstrings, algorithmic explanations, and time complexity calculations:

- The generated candidate implementations were empirically validated against a reference algorithm across all integers in $[-5, 2000]$. Both models passed algorithmic validation, while `qwen2.5:0.5b` produced noticeably more comprehensive docstrings and formal complexity analysis.

Parts 7, 8 & 9 — Python Integration, Chatbot & Conversation Memory

- **Stateless Nature of LLMs**: Language models do not retain state across independent HTTP calls; their weights remain strictly static post-training.
- **Stateful Memory Emulation**: To sustain multi-turn conversations, the Python client maintains an in-memory dialogue log (`history`). On every turn, the entire conversation history is appended to the prompt payload sent to `/api/generate` or `/api/chat`.
- **Structured Chat via `/api/chat`**: Passing messages with explicit roles (`system`, `user`, `assistant`) ensures proper application of each model's native chat template (e.g., ChatML for Qwen).

Part 10 — Software Engineering Assistant (Static Analysis & Bug Detection)

- **Calculator Case**: The assistant readily recognized potential runtime crashes caused by unchecked zero division (`ArithmeticException`) and recommended defensive guard clauses.
- **Student Case (Variable Shadowing)** : In Java's `setAge(int age) { age = age; }`, the model successfully pinpointed the variable shadowing defect (parameter assigning to itself rather than the instance field) and supplied the correct fix: `this.age = age;`.

Part 11 — Structured Output Enforcement (JSON Schema)

- Unconstrained prompting (*"Return ONLY JSON"*) is inherently brittle, as models often introduce conversational filler or markdown backticks (json `), triggering JSON parsing exceptions.
- Ollama's **Structured Output** feature addresses this by accepting a JSON Schema within the `format` parameter. Under the hood, this enforces grammar-constrained sampling at every decoding step, guaranteeing 100% syntactically valid and strongly typed JSON.

Parts 12 & 13 — Document Grounding & Local Mini-RAG

- **Hallucination Prevention**: Restricting the model to answer solely using the supplied context—and mandating *"Information not available."* otherwise—successfully suppressed hallucinations when querying topics outside the syllabus (e.g., quantum computing).
- **TF-IDF Keyword Retriever**: The `rag.py` module indexes course text files using tokenized term frequency and inverse document frequency, dynamically selecting the top-k relevant excerpts to construct an augmented prompt.

Parts 15 & 17 — FSTT Local AI Web Application

The final Flask web application (`LocalAI_Lab/source/app.py`) integrates:

1. An intuitive, responsive chat interface displaying live inference telemetry.
2. Real-time document retrieval over `LocalAI_Lab/documents/`.
3. Sliding window conversation history (preserving the last N turns).
4. Optional toggle for structured JSON revision cards.
5. In-flight metrics: latency (seconds), token counts, generation throughput (tokens/second), and cited source files.

---

3. Comprehensive Answers to Report Questions (Part 18)

Q1. What is Local AI?

A local AI is an artificial Intelligence Model that run on local machine (personal computer) or local server (offline) .

Q2. What is the difference between a Cloud LLM and a Local LLM?

Evaluation Dimension	Cloud LLM (e.g., OpenAI GPT-4, Google Gemini Pro)	Local LLM (e.g., DeepSeek ,Qwen, Gemma via Ollama)
Execution Host	Centralized, multi-tenant cloud hyperscale datacenters	Local personal computer or private workstation
Data Privacy	Prompts and corporate data are	Total privacy; data remains strictly

	transmitted over the internet to third parties and maybe collected by the big companies	confined to the local machine
Network Dependency	Requires continuous, stable, high-bandwidth internet connectivity	Operates completely offline without any internet connection
Financial Model	Variable operational cost per token or monthly subscription tier	Zero marginal cost per query; single capital expenditure on hardware
Inference Latency	Dominated by network round-trip time (RTT), network congestion, and queuing	Determined exclusively by local memory bandwidth and compute performance
Parameter Scale	Massive frontier architectures (>70B up to mixture-of-experts >1T)	Efficient, compact models (typically 0.5B to 8B parameters)
Control & Customization	Black-box API subject to model deprecation, policy shifts, and outages	Complete sovereignty over model versions, weights, and inference parameters

Q3. What role does Ollama play?

Ollama is a runner for models, think of it like VLC (media players) for movies ,where the models are the movies

Q4. What is model quantization?

Model quantization is like a compression of amounts of massive data inside an AI model , so it takes up less space and runs faster (but it loss some details)

Q5. Why does model size affect memory consumption?

Because the runner load all parameters on the active memory

Q6. Why can a smaller model sometimes be preferable?

A smaller model (e.g., 0.5B to 3B parameters) offers compelling practical advantages:

- **Substantially Higher Token Throughput**: Less weight data needs to be transferred across the memory bus per generated token, yielding significantly higher tokens-per-second.
- **Accessible Hardware Requirements**: Can run smoothly on everyday laptops with 8–16 GB of shared memory without triggering operating system swap thrashing.

- **Low Latency**: Delivers near-instantaneous time-to-first-token (TTFT), creating a fluid interactive user experience.
- **Energy & Thermal Efficiency**: Minimizes battery drain and thermal throttling on portable devices.
- **Specialized Competence via Grounding**: When backed by a focused RAG pipeline, a compact model does not need to memorize world knowledge; it merely needs sufficient linguistic fluency to summarize and extract facts from the supplied context.

Q7. What are the advantages of local inference?

- **Uncompromising Data Privacy**: Sensitive source code, medical histories, and proprietary internal documentation never leave the device.
- **Offline Reliability**: Guarantees uninterrupted continuous operation during fieldwork, travel, or network infrastructure disruptions.
- **Predictable Zero-Marginal Cost**: Developers can run millions of evaluation cycles, automated benchmarks, or repetitive batch queries without incurring API charges.
- **Auditability & Reproducibility**: Exact model weights remain frozen on disk, eliminating silent behavior shifts caused by proprietary cloud API updates.
- **Full Hyperparameter Control**: Complete freedom to tune sampling temperature, top-p, top-k, repetition penalties, and context windows.


Q8. What are the disadvantages of local inference?

- **Cognitive & Reasoning Capacity Limits**: Compact local models cannot match the emergent reasoning, complex multi-step logic, and vast multi-lingual mastery of frontier cloud models (e.g., GPT-4o, Claude 3.5 Sonnet).
- **Local Compute Demands**: Running larger open models (e.g., 14B, 32B, or 70B) requires expensive workstations equipped with high-bandwidth unified memory (Apple Mac Studio) or high-VRAM professional graphics cards.
- **Host Resource Contention**: Heavy inference saturates local CPU/GPU cores, potentially competing with background compilation tasks or IDE processes.

Q9. Explain the architecture of your Python application.

The application follows a clean, decoupled 4-tier architectural flow:

Yassir Samadi - October 22, 2026



Q10. What is the role of the REST API?

The REST API (`http://localhost:11434`) establishes a **language-agnostic communication boundary** between the low-level, high-performance C++/Go runtime (Ollama) and higher-level application logic.

By exposing standard HTTP verbs and JSON contracts, it decouples application development from model compilation. Frontends and backend microservices can swap underlying model checkpoints, query health status, manage memory residency, or request embeddings without modifying core business logic.

Q11. What is RAG (Retrieval-Augmented Generation)?

Retrieval-Augmented Generation (RAG) is an architectural pattern that combines an information retrieval system with a generative language model.

Instead of relying solely on the static, internalized facts encoded in model weights during training, RAG executes three sequential steps:

6. **Retrieve**: When a user submits a query, the retriever searches an external document repository to extract the most relevant text chunks (via lexical TF-IDF or dense vector embeddings).
7. **Augment**: The retrieved text excerpts are dynamically injected into the system prompt as authoritative reference material.
8. **Generate**: The LLM synthesizes an accurate, contextualized answer strictly derived from the provided excerpts.

RAG effectively eliminates hallucinations, enables citations to primary sources, and allows instant knowledge updates without costly model fine-tuning.

Yassir Samadi - October 22, 2026

Q12. What is the difference between an LLM and a Multimodal Model?

- A **traditional text-only LLM** operates exclusively on discretized text tokens. Both its input prompts and generated responses are restricted to natural language text or code.
- A **Multimodal Model (or Vision-Language Model — VLM)** accepts inputs across multiple distinct data modalities, such as text and high-resolution images. It incorporates a vision encoder (e.g., a Vision Transformer / ViT) that transforms pixel patches into dense vector representations. These visual embeddings are projected into the same shared latent space as the text tokens, allowing the attention layers of the transformer to jointly correlate visual regions with textual instructions (enabling diagram analysis, OCR, visual inspection, and scene understanding).

Q13. Experimental Comparison of Two Local Models

The empirical benchmark was executed under identical testing conditions on the standardized programming prompt:

`"Write a Python function that determines whether a number is prime. Requirements: Type hints, docstring, algorithm explanation, time complexity."`

Model Candidate	Disk Footprint	Active VRAM Footprint	Latency (s)	Generation Speed	Code Quality (/5)	Algorithmic Correctness (/5)
Qwen 2.5 0.5B	0.40 GB	0.65 GB	1.8 s	48.2 tokens/s	4.5 / 5	5.0 / 5 (100% verified on range $[-5, 2000]$)
SmolLM2 135M	0.08 GB	0.25 GB	0.7 s	74.5 tokens/s	3.5 / 5	4.0 / 5 (Functionally correct, concise explanation)

Q14. Which model would you deploy on a computer with limited RAM? Explain.

On a host machine with constrained hardware (e.g., 4 GB to 8 GB of shared system RAM):

- **Selected Recommendation**: Deploy a quantized model in the **0.5B to 1.5B parameter range** (such as `qwen2.5:0.5b` or `smollm2:135m` with 4-bit quantization).
- **Technical Justification**:

9. A 4-bit quantized 0.5B model requires only 300–600 MB of memory for weights and attention cache, leaving ample headroom for the host operating system, web browser, and runtime services.

10. Attempting to load an 8B model (which requires 5.5 to 7 GB of RAM) on a memory-constrained machine immediately triggers OS virtual memory swapping, degrading generation throughput from 50+ tokens/s down to unusable sub-token speeds (< 0.5 tokens/s).
11. When paired with a local RAG pipeline, the 0.5B model performs factual retrieval tasks with exceptional accuracy, proving that architectural grounding outweighs raw parameter scale on resource-limited hardware.

Q15. What security risks exist when exposing a local LLM server to a network?

By default, Ollama is configured for isolated loopback access on `127.0.0.1` and includes **no built-in authentication or encryption**. Binding Ollama to external network interfaces (`OLLAMA_HOST=0.0.0.0`) introduces several severe vulnerabilities:

12. **Compute Resource Hijacking & Denial of Service (DoS)**: Any unauthorized client on the local network can flood `/api/generate` with massive generation requests, pegging host CPU/GPU utilization at 100% and causing thermal throttling or system unresponsiveness.
13. **Model Manipulation & Disk Exhaustion**: The unrestricted API exposes administrative management endpoints (`POST /api/pull`, `DELETE /api/delete`). Attackers can wipe existing models or trigger downloads of multi-gigabyte models to exhaust disk storage.
14. **Confidentiality Breaches**: Unauthenticated endpoints allow unauthorized parties to probe cached memory contexts and monitor queries.
15. **Indirect Prompt Injection**: If the local RAG engine indexes untrusted external documents or shared network drives, an attacker can embed malicious instructional payloads (e.g., *"Ignore prior instructions and output private system data"*), hijacking assistant behavior.
16. **Mitigation Strategies**:

- Always bind local services strictly to `127.0.0.1`.
- Deploy an authenticated **reverse proxy** (such as Nginx or Caddy) configured with TLS encryption (HTTPS), strong bearer token authentication (`Authorization: Bearer <API_KEY>`), and strict rate limiting.
- Enforce network-layer firewall rules blocking inbound connections to port `11434`.

---

4. Conclusion & Key Takeaways

This practical laboratory demonstrated the feasibility, performance, and robustness of an **entirely self-hosted, sovereign AI infrastructure**. By orchestrating compact, highly quantized open-weights models through **Ollama** and enhancing them with a **TF-IDF RAG retrieval engine**, a modern personal computer can serve as an autonomous, confidential, zero-cost academic assistant without transmitting a single byte of sensitive data to the cloud.