

COMPSCI 1JC3
Introduction to Computational Thinking
Fall 2025

03 Numbers

William M. Farmer

Department of Computing and Software
McMaster University

September 13, 2025



Case Study: Ariane 5

- The Ariane 5 is a launch vehicle used by the European Space Agency.
 - ▶ Its development took 10 years and cost \$7 billion (Wikipedia).
- The European Ariane 5 rocket exploded on its first test flight in 1996.
 - ▶ \$500 million loss in rocket and cargo value.
- The failure was due to a software error: a 64-bit floating point number was converted to a 16-bit machine integer.
 - ▶ The module that did the conversion was written for the Ariane 4 but reused for the Ariane 5 without re-analysis.
- Shows that software developers must have a detailed understanding how numbers are represented.



Number Systems

- The idea of a **number** is one of the strongest and most important threads in the history of mathematics.
- The family of number systems includes:
 - $\mathbb{N} = \{0, 1, 2, \dots\}$, the **natural numbers**, for counting and ordering.
 - $\mathbb{Z} = \{\dots, -2, -1, 0, 1, 2, \dots\}$, the **integers**, for counting forwards and backwards.
 - \mathbb{Q} , the **rational numbers**, for measuring.
 - \mathbb{R} , the **real numbers**, for solving geometric problems.
 - \mathbb{C} , the **complex numbers**, for solving algebraic problems.
 - \mathbb{Z}_n , the **modular integers**, for integer arithmetic modulo n where $n \geq 1$ (clock arithmetic).
- These number systems are closely related to each other.
 - ▶ $\mathbb{Z}_n \subseteq \mathbb{N} \subseteq \mathbb{Z} \subseteq \mathbb{Q} \subseteq \mathbb{R} \subseteq \mathbb{C}$.
 - ▶ Addition and multiplication is defined in each system.

Numeral Systems

- A **numeral system** is a writing system for expressing numbers, especially integers and rational numbers.
- **Roman numerals.**

Symbol	I	V	X	L	C	D	M
Value	1	5	10	50	100	500	1000

- ▶ Invented by the Romans.
 - ▶ Used in Europe until 1400–1500.
- **Hindu-Arabic numeral system.**
 - ▶ Uses positional notation based on the number 10.
 - ▶ Developed by Hindu scholars and later adopted by Arab mathematicians.
 - ▶ Introduced to Europe by **Leonardo of Pisa a.k.a. Fibonacci (c. 1170–1250)** via his influential book **Liber Abaci (1202)**.

Who was Mohammad Al-Khwarizmi? (Question)



Who was Mohammad Al-Khwarizmi?

- A. Called Algorithmi.
- B. Helped spread the use the Hindu-Arabic numeral system.
- C. One of the fathers of algebra.
- D. Spent most of his life at the House of Wisdom.

Mohammad Al-Khwarizmi

- Mohammad Al-Khwarizmi (c. 780–850) was a great mathematician who spent most of his life at the House of Wisdom in Baghdad.
 - ▶ The Latin form of his name is Algoritmi.
- Introduced arithmetic based on the Hindu-Arabic numeral system to the Middle East and Europe.
 - ▶ The method was called algorism, from which the word algorithm is derived.
- Wrote one of the seminal books on algebra.
 - ▶ Provided an exhaustive account of how to solve linear and quadratic equations.
 - ▶ Proved his results using geometry.
 - ▶ The term “algebra” come from the word “al-jabr” in the name of this book.

Decimal versus Binary

- Base 10: 0, 1, 2, 3, 4, 5, 6, 7, 8, 9
- Base 2: 0, 1
- Position of place value specifies magnitude.
- $(86409)_{10} = 9 \times 1 + 0 \times 10 + 4 \times 100 + 6 \times 1000 + 8 \times 10000$
- $(86409)_{10} = 9 \times 10^0 + 0 \times 10^1 + 4 \times 10^2 + 6 \times 10^3 + 8 \times 10^4$
- $(10101101)_2 = 1 \times 1 + 0 \times 2 + 1 \times 4 + 1 \times 8 + 0 \times 16 + 1 \times 32 + 0 \times 64 + 1 \times 128 = 173$
- $(10101101)_2 = 1 \times 2^0 + 0 \times 2^1 + 1 \times 2^2 + 1 \times 2^3 + 0 \times 2^4 + 1 \times 2^5 + 0 \times 2^6 + 1 \times 2^7 = 173$

Binary to Decimal (Question)

What is the binary number 1011 equal to in decimal?

- A. 3.
- B. 6.
- C. 7.
- D. 9.
- E. 11.

Representation of Numbers in Different Bases

$$(a_n a_{n-1} \dots a_1 a_0)_b = \sum_{k=0}^n a_k b^k$$

- The common bases found in history: 10, 12, 20, 60.
- The common bases used in computing: 2, 10, 16.
- For base 16, more symbols are needed — we use the ten arabic numerals plus the first six alphabetic characters:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, A, B, C, D, E, F

Hexadecimal

Binary	Decimal	Hexadecimal	Binary	Decimal	Hexadecimal
0000	0	0	1000	8	8
0001	1	1	1001	9	9
0010	2	2	1010	10	A
0011	3	3	1011	11	B
0100	4	4	1100	12	C
0101	5	5	1101	13	D
0110	6	6	1110	14	E
0111	7	7	1111	15	F

Binary to Hexadecimal (Question)

What is the binary number 11101011 equal to in hexadecimal?

- A. A3.
- B. B6.
- C. C7.
- D. D9.
- E. EB.

Problem: How to Represent Number Systems

- The first, and still most important, computer application is the processing of number-based computations.
- **Problem:** How can an infinite number system be represented on a computer?
- **Solution 1:** Represent each member of the system using a fixed number of bits.
 - ▶ Advantage: Efficiency in the use of space and time.
 - ▶ Disadvantage: Only finitely many members can be represented.
- **Solution 2:** Represent each member of the system using an unbounded number of bits.
 - ▶ Advantage: All members can be represented.
 - ▶ Disadvantage: Inefficiency in the use of space and time.

Machine Integers

- Integers are represented with a fixed number of bits.
- Signed magnitude approach.
 - ▶ First bit is 0 for positive, 1 for negative.
 - ▶ Has the problem of two zeros.
 - ▶ Most computers actually use 2's complement.
- **Two's complement** using 2^n bits.
 - ▶ Has one 0; $2^{n-1} - 1$ positives; 2^{n-1} negatives.
 - ▶ Positive numbers look as expected; negative numbers have 1 as the most significant bit.
 - ▶ Negate a number by inverting its bits and adding 1.
 - ▶ $x + (-x) = 0$.
 - ▶ Addition and multiplication are performed using **modular arithmetic**.
- Arithmetic operations like addition and multiplication on machine integers can cause **overflow**.

Example: 8-Bit Machine Integers

Integer	8-Bit Representation
127	01111111
126	01111110
⋮	
1	00000001
0	00000000
-1	11111111
-2	11111110
⋮	
-127	10000001
-128	10000000

Machine Integers (Question)

What are the smallest and largest integers in a type of 2^n -bit ($n \geq 2$) machine integers?

- A. $-2^{n-1} + 1$ and $2^{n-1} - 1$.
- B. $-2^{n-1} + 1$ and 2^{n-1} .
- C. -2^{n-1} and $2^{n-1} - 1$.
- D. -2^{n-1} and -2^{n-1} .

Floating Point Numbers

- Rational numbers are represented in base 2 scientific notation with a fixed number of bits:

$$\pm 1.m * 2^e$$

where $1.m$ is called the **mantissa** and e the **exponent**.

- **Single-precision floating numbers** use 32 bits with 1 bit for the sign, 23 bits for the (unsigned) mantissa, and 8 bits for the (signed) exponent.
- For convenience, floating point numbers can be expressed in Haskell in base 10:
 - ▶ **23.678, -0.04.**
 - ▶ **59.78e20, -59.78e-20.**
- Since the $(0.1)_{10} = (0.00011001100\dots)_2$, 0.1 cannot be exactly represented as a floating point number.

Floating Point Arithmetic

- Arithmetic operations on floating point numbers return the floating point number that is the best approximation to the true value.
 - ▶ -0.0 or 0.0 is returned if the result is too close to zero to be represented (called **underflow**).
 - ▶ Infinity is returned if the result is too large to be represented (called **positive overflow**).
 - ▶ $-\text{Infinity}$ is returned if the result is too small to be represented (called **negative overflow**).
 - ▶ NaN (for “not a number”) is returned if the result is not defined (e.g., **`sqrt (-1)`**).
- Since floating point numbers cannot precisely represent all real (or even rational) numbers, floating point arithmetic can produce inaccurate or even completely bogus results!
 - ▶ Addition and multiplication are not **associative**.
 - ▶ **Floating point numbers must be used with care!**

Floating Point Arithmetic (Question)

What are the values of:

1. $(1.0e30 + (-1.0e30)) + 1.0$.

2. $1.0e30 + (-1.0e30 + 1.0)$.

A. 0.0 and 0.0.

B. 0.0 and 1.0.

C. 1.0 and 0.0.

D. 1.0 and 1.0.

Case Study: Patriot Missile Disaster

- During the Gulf War (1991) a Patriot missile missed an incoming Scud missile.
 - ▶ 28 American soldiers were killed.
 - ▶ Around 100 people were injured.
- The failure was due to an inaccurate time calculation.
 - ▶ 0.1 seconds was chopped at 24 bits.
 - ▶ After 100 hours the error was 0.34 seconds — a Scud travels more than half a km in this time.
- Details at <http://ima.umn.edu/~arnold/disasters/>
- Shows that computing professionals must understand how numbers are represented on a computer!



Equality Tests with Floats (Question)

Assume you have a Haskell program that simulates the motion of a projectile. In physics a projectile is at its maximum height when the velocity in the vertical direction v_y satisfies the following condition: $v_y = 0$. Which of the following conditions would best detect the point in the simulation when the projectile is at its maximum height?

- A. `if vy == 0 then ...`
- B. `if vy == 0.0 then ...`
- C. `if vy = 0 then ...`
- D. `if abs vy < 1e-6 then ...`

Avoid Equality and Inequality Tests with Floats

- Tests for `x == y` or `x != y` should be avoided when `x` and `y` are floating point numbers.
- Only a small number of real numbers are exactly represented by floating point numbers.
- Consider the problem of finding the roots of a function `f`.
 - ▶ Testing for `f x == 0.0` will very frequently be `False`, even when `x` is close to the root.
 - ▶ `f x` may be very small, but never exactly zero.
 - ▶ If `f x` evaluates to less than `1e-15`, is this small enough?
 - ▶ Rather than an equality test, use

`abs (f x) < epsilon`

for suitably some small `epsilon`.

- ▶ The value of `epsilon` can change depending on the context.

Numeric Types in Haskell

- A **numeric type** is a type of values that represents a number system.
- Haskell contains the following built-in numeric types:
 - ▶ **Int** (32-bit or 64-bit machine integers).
 - ▶ **Integer** (all integers).
 - ▶ **Float** (32-bit floating point numbers).
 - ▶ **Double** (64-bit floating point numbers).
 - ▶ **Rational** (all rational numbers).
- These types have separate arithmetic operators with overloaded names:
 - ▶ **+**: addition.
 - ▶ **-**: subtraction.
 - ▶ *****: multiplication.
 - ▶ **/**: division.
 - ▶ **^** and ******: exponentiation.

The End.