

Computation expressions and monads

Peter Sestoft

BSWU BFNP 2016-03-15

Agenda

- Computation expressions, or monads
- Sequence expressions as computation exprs.
- Relation to list and array expressions
- Monad laws
- Simple expressions and evaluators
 - Return int, standard evaluation
 - Return int option, evaluation may fail
 - Return int Set, evaluation may produce a set
 - Return int trace, evaluation traces operators
 - Express all this uniformly using comp. expr.
- Thursday: async as computation expression

What is a computation expression?

- A *computation expression* such as

```
seq { for x in [1 .. 3] do yield x*x }
```

is *syntactic sugar* for a standard functional expression, such as

```
Seq.collect (fun x -> Seq.singleton(x*x))  
            [1 .. 3]
```
- This gives a systematic way to combine operations or propagate "background" data
- Computation expressions are sometimes called *monads* (in mathematics, Haskell, ...)

Computation expressions in F#

- `seq {...}` is a computation expression
- `async {...}` is a comp. expr. (next week)
- We can define our own computation exprs:
 - Optional result (None or Some)
 - Set of results
 - Trace of operations
 - ...

Sequences as computation expressions (H&R p 281)

- This sequence expression

```
seq { for i in [1 .. 3] do  
      for ch in ['a' .. 'd'] do  
        yield (i,ch) }
```

- is syntactic sugar for this expression

```
Seq.collect  
  (fun i ->  
    Seq.collect  
      (fun ch ->  
        Seq.singleton (i, ch))  
      ['a' .. 'd'])  
  [1 .. 3]
```

Transformation of seq {...}

The compiler rewrites `for` and `yield` keywords to normal function calls:

Seq construct C	Transformation T(C)
<code>for x in e do ce</code>	<code>For(e, fun x -> T(ce))</code>
<code>yield e</code>	<code>Yield(e)</code>

The `For` and `Yield` functions must be defined:

```
For      : seq<'a> * ('a -> seq<'b>) -> seq<'b>
Yield    : 'a -> seq<'a>
```

```
For(xs, f) = Seq.collect f xs
Yield a    = Seq.singleton a
```

How to define our own mySeq {...}?

- Define a MySeqBuilder class with For, Yield:

```
type MySeqBuilder() =  
  member this.For(xs, f) = Seq.collect f xs  
  member this.Yield x = Seq.singleton x
```

- Make an object of that class:

```
let mySeq = new MySeqBuilder()
```

- The object can now indicate a comp expr:

```
mySeq { for i in [1 .. 3] do  
        for ch in ['a' .. 'd'] do  
          yield (i, ch) };;
```

Homemade
sequence
expression

Transformation and implementation

- The computation expression

```
mySeq { for x in [1..3] do yield x*x }
```

gets transformed (by the compiler) to

```
mySeq.For([1..3], fun x -> mySeq.Yield(x*x))
```

- Using the definitions of functions For and Yield in mySeq, this means

```
Seq.collect (fun x -> Seq.singleton (x*x))  
           [1..3]
```


Understanding the H&R example

```
seq { for i in [1 .. 3] do
      for ch in ['a' .. 'd'] do
        yield (i,ch) }
```

- Lift inner **for** out as a function:

```
let inner i =
  seq { for ch in ['a' .. 'd'] do yield (i,ch) }
```

```
let inner i =
  Seq.collect (fun ch -> Seq.singleton (i, ch)) ['a' .. 'd']
```

Same thing

- Outer **for** is just this:

```
Seq.collect (fun i -> inner i) [1 .. 3]
```

- So in total

```
Seq.collect (fun i ->
  Seq.collect (fun ch -> Seq.singleton (i, ch)) ['a' .. 'd'])
[1 .. 3]
```

List and array expressions

- The F# list expression:

```
[ for x in [1..3] do yield x*x ]
```

- is syntactic sugar for the seq expression

```
Seq.toList(seq {for x in [1..3] do yield x*x })
```

- Similarly for F# array expressions:

```
[| for x in [1..3] do yield x*x |]
```

- See F# Specification §6.3.13 and §6.3.14
- F# has no "list computation expression", it boils down to seq computation expressions

Questions

- In `seq {...}` expressions one can use `if`

```
let sift a xs =  
  mySeq { for n in xs do  
    if n % a <> 0 then  
      yield n };;
```

- Q1: What function to add to `MySeqBuilder` to support the `if` operator? (H&R Table 12.2)
- Q2: What member of the `Seq` module should be used to define it? (H&R Table 11.1)

For=Bind=let!, and Yield=Return

- For and Yield are special names that make sense in seq{...} expressions
- Normal names are Bind/let! and Return
- One could define sillySeq using Bind/Return:

```
type SillySeqBuilder() =  
  member this.Bind(xs, f) = Seq.collect f xs  
  member this.Return x = Seq.singleton x
```

```
let sillySeq = new SillySeqBuilder()
```

```
sillySeq {  
  let! i = [1 .. 3]  
  let! ch = ['a' .. 'd']  
  return (i, ch) }
```

```
seq {  
  for i in [1 .. 3] do  
    for ch in ['a' .. 'd'] do  
      yield (i, ch) }
```

More
sensible, but
exact same
meaning

Kært barn har mange navne

- Function **Bind** in computation expression is
 - **for** and **For** in **seq** {...}
 - **List.collect** on F# lists
 - **Seq.collect** on F# sequences
 - **flatMap** on Scala and Haskell lists, sequences, ...
 - **flatMap** in Java 8 streams
 - **SelectMany** in Microsoft Linq (eg. C#P p. 205)
 - **bind** in monads
- Function **Return** in computation expressions
 - **yield** in **seq** {...}
 - **(fun x -> [x])** on F# lists
 - **Seq.singleton** on F# sequences
 - **unit** or **return** in monads

Transformation of computation expressions

The compiler rewrites to normal function calls:

Comp. exp. construct C	Transformation T(C)
<code>let! x = e</code> <code>ce</code>	<code>Bind(e, fun x -> T(ce))</code>
<code>return e</code>	<code>Return(e)</code>
<code>return! e</code>	<code>ReturnFrom(e)</code>

The functions must have suitable types:

```
Bind      : com<'a> * ('a -> com<'b>) -> com<'b>
Return    : 'a -> com<'a>
ReturnFrom : com<'a> -> com<'a>
```

See H&R Tables 12.2 and 12.3 for more

The option {...} computation expr.

A form of error propagation

```
optM { let x = 56  
      let! y = Some 78  
      return x+y };;
```



```
let x = 56  
optM.Bind(Some 78,  
  fun y ->  
    optM.Return(x+y))
```

Some 134

```
optM { let x = 56  
      let! y = Some 78  
      let! z = None  
      return x+y };;
```



```
let x = 56  
optM.Bind(Some 78,  
  fun y ->  
    optM.Bind(None,  
      fun z ->  
        optM.Return(x+y)))
```

None

```
type OptionBuilder() =  
  member this.Bind(x, f) =  
    match x with  
    | None    -> None  
    | Some v -> f v  
  member this.Return(x) = Some x  
let optM = OptionBuilder()
```

let!

return

Question: What's happening here

```
type OptionBuilder() =  
  member this.Bind(x, f) =  
    printfn "this.Bind: %A" x  
    match x with  
    | None    -> None  
    | Some v  -> f v  
  member this.Return(x) = Some x  
let optM = OptionBuilder()
```

Print when
called

```
optM { let x = 56  
      let! y = Some 78  
      let! z = None  
      let! v = Some 42  
      return x+y+v };;
```

New line
here

Monad laws

- $\text{For}(\text{Yield } a, f) = f(a)$
 $\text{collect } f (\text{singleton } a) = f(a)$
- $\text{For}(xs, \text{Yield}) = xs$
 $\text{collect singleton } xs = xs$
- The laws are the same with
 - Bind instead of For, and Return instead of Yield
- Let's check them for the **optM** monad

A standard simple evaluator

- Very simple expressions like $7 + 9 * 10$

```
type expr =  
  | CstI of int  
  | Prim of string * expr * expr
```

```
Prim("+",  
      CstI(7),  
      Prim("*", CstI(9),
```

- A simple evaluator:

```
let rec eval1 e : int =  
  match e with  
  | CstI i -> i  
  | Prim(op, e1, e2) ->  
    let v1 = eval1 e1  
    let v2 = eval1 e2
```

```
  match op with  
  | "+" -> v1 + v2  
  | "*" -> v1 * v2  
  | "/" -> v1 / v2
```

```
let opEval op v1 v2 : int =  
  match op with  
  | "+" -> v1 + v2  
  | "*" -> v1 * v2  
  | "/" -> v1 / v2
```

```
let rec eval2 e : int =  
  match e with  
  | CstI i -> i  
  | Prim(op, e1, e2) ->  
    let v1 = eval2 e1  
    let v2 = eval2 e2  
    opEval op v1 v2
```

An evaluator that may fail (w. None)

```
let opEvalOpt op v1 v2 : int option =  
  match op with  
  | "+" -> Some(v1 + v2)  
  | "*" -> Some(v1 * v2)  
  | "/" -> if v2 = 0 then None else Some(v1 / v2)
```

```
let rec optionEval2 e : int option =  
  match e with  
  | CstI i -> Some i  
  | Prim(op, e1, e2) ->  
    match optionEval2 e1 with  
    | None -> None  
    | Some v1 ->  
      match optionEval2 e2 with  
      | None -> None  
      | Some v2 -> opEvalOpt op v1 v2
```

An evaluator giving a set of results

```
let opEvalSet op v1 v2 : int Set =  
  match op with  
  | "+" -> Set [v1 + v2]  
  | "*" -> Set [v1 * v2]  
  | "/" -> if v2 = 0 then Set.empty else Set [v1 / v2]  
  | "choose" -> Set [v1; v2]
```

```
let rec setEval1 e : int Set =  
  match e with  
  | CstI i -> Set [i]  
  | Prim(op, e1, e2) ->  
    let s1 = setEval1 e1  
    let yss =  
      Set.map (fun v1 ->  
        let s2 = setEval1 e2  
        let xss = Set.map (fun v2->opEvalSet op v1 v2) s2  
        Set.unionMany xss)  
      s1  
    Set.unionMany yss
```

An evaluator tracing the operators

```
type 'a trace = string list * 'a

let opEvalTrace op v1 v2 : int trace =
  match op with
  | "+" -> (["+"], v1 + v2)
  | "*" -> (["*"], v1 * v2)
  | "/" -> (["/"], v1 / v2)
```

```
let rec traceEval1 e : int trace =
  match e with
  | CstI i -> ([], i)
  | Prim(op, e1, e2) ->
    let (trace1, v1) = traceEval1 e1
    let (trace2, v2) = traceEval1 e2
    let (trace3, res) = opEvalTrace op v1 v2
    (trace1 @ trace2 @ trace3, res)
```

A mess; comp expr to the rescue

- The four evaluators look very different
- ... and very complicated
- By defining the combining operations as computation expressions,
 - the evaluators all get to look the same
 - the evaluators look much simpler

An evaluator that may fail, NEW

```
type OptionBuilder() =  
  member this.Bind(x, f) =  
    match x with  
    | None    -> None  
    | Some v -> f v  
  member this.Return x = Some x  
  member this.ReturnFrom x = x  
  
let optionM = OptionBuilder();;
```

```
let rec optionEval3 e : int option =  
  match e with  
  | CstI i -> optionM { return i }  
  | Prim(op, e1, e2) ->  
    optionM { let! v1 = optionEval3 e1  
              let! v2 = optionEval3 e2  
              return! opEvalOpt op v1 v2 }
```

An evaluator ... set of results, NEW

```
type SetBuilder() =  
  member this.Bind(x, f) =  
    Set.unionMany (Set.map f x)  
  member this.Return x = Set [x]  
  member this.ReturnFrom x = x  
  
let setM = SetBuilder();;
```

```
let rec setEval3 e      : int Set =  
  match e with  
  | CstI i -> setM      { return i }  
  | Prim(op, e1, e2) ->  
    setM      { let! v1 = setEval3 e1  
                let! v2 = setEval3 e2  
                return! opEvalSet op v1 v2 }
```


An evaluator ... trace operators, NEW

```
type TraceBuilder() =  
  member this.Bind(x, f) =  
    let (trace1, v) = x  
    let (trace2, res) = f v  
    (trace1 @ trace2, res)  
  member this.Return x = ([], x)  
  member this.ReturnFrom x = x  
  
let traceM = TraceBuilder();;
```

```
let rec traceEval3 e : int trace =  
  match e with  
  | CstI i -> traceM { return i }  
  | Prim(op, e1, e2) ->  
    traceM { let! v1 = traceEval3 e1  
             let! v2 = traceEval3 e2  
             return! opEvalTrace op v1 v2 }
```

A standard evaluator, NEW

```
type IdentityBuilder() =  
  member this.Bind(x, f) = f x  
  member this.Return x = x  
  member this.ReturnFrom x = x  
  
let identM = new IdentityBuilder();;
```

```
let rec eval3 e          : int =  
  match e with  
  | CstI i -> identM { return i }  
  | Prim(op, e1, e2) ->  
    identM { let! v1 = eval3 e1  
              let! v2 = eval3 e2  
              return! opEval op v1 v2 }
```

Reflections on computation expressions

- They reveal similarities
 - between different kinds of computations
 - between different kinds of data: list, seq, option, ...
- They clarify the structure of the evaluators
- Unfortunately, in F# a computation expression builder (optionM, setM, traceM, identM) cannot be a parameter to a function
- Hence one cannot have a single "super-eval" that unifies all the {opt,set,trace}Evals
- ... but in Scala one can!

Types of the monad functions

Monad	Bind/For	Return/Yield
mySeq	<code>seq<'a> * ('a -> seq<'c>) -> seq<'c></code>	<code>'a -> seq<'a></code>
optionM	<code>'a option * ('a -> 'b option) -> 'b option</code>	<code>'a -> 'a option</code>
setM	<code>Set<'a> * ('a -> Set<'b>) -> Set<'b></code>	<code>'a -> Set<'a></code>
traceM	<code>('a list * 'b) * ('b -> 'a list * 'c) -> 'a list * 'c</code>	<code>'a -> 'b list * 'a</code>
traceM	<code>'b trace * ('b -> 'c trace) -> 'c trace</code>	<code>'a -> 'a trace</code>
monad M	<code>'a M * ('a -> 'b M) -> 'b M</code>	<code>'a -> 'a M</code>

References

- F# computation expressions
 - Hansen and Rischel chapter 12
 - http://en.wikibooks.org/wiki/F_Sharp_Programming/Computation_Expressions
 - <http://msdn.microsoft.com/en-us/library/dd233182.aspx>