

# Structures

November 8, 2021

## 1 Structures

### 1.1 Topics

- compound and heterogeneous types
- structures and records types
- examples of structures and objects
- aggregate operations on objects
- passing structure to and returning from functions
- array of structures
- structures in another structures

### 1.2 Compound and heterogeneous types

- most of the data types we've worked with so far represent a single value
  - an integer, floating-point value, char, etc.
- we've also worked with array of similar values such as string, array of integers or array of strings
- array, vector and string can be considered as compound types but all elements are **homogeneous (same) type**
- C++ possibly can't provide all the types of data that programs need to efficiently represent and handle
- e.g. Complex numbers, Points in coordinates, various records (student records, police records, etc.)
- a large number of these types are compound but mixture of **heterogeneous (mixed) types**
  - e.g. student records may have integer for ID, string for names and addresses, float for GPA and grades, etc.
- the following figure shows some sample student records that a program may have to represent:

	A	B	C	D	E
1	ID	firstName	lastName	MI	GPA
2	7001	John	Doe	K	4.00
3	7002	Jane	Smith	L	3.99
4					
5					
6					

- two records displayed in the figure have the same heterogeneous structure

- we can represent these records and store them in memory using array of structure
- via **struct** and **class** constructs, C++ allows us to create any type of heterogeneous data records that we want to represent
- we do not include any library to use **struct** and **class** keywords
- **class** is a big topic typically covered in **Data Structures** and **Object Oriented Programming** courses

### 1.3 Structures

- structures are user-defined, compound and typically heterogeneous types
- the following figure demonstrates student record represented using structure
- allows us to organize many different types of data under ONE compound type
- each type of data is represented by its own name and is called a member of the structure
- makes it easier to manipulate and move the data records around in a program using a single object/variable
- using structures is a three-step process:
  1. define the new structure type
  2. declare objects using the new structure type
  3. access members to store, update and read data
- keyword **struct** short for structure is used to define structure type
- syntax to define structure:

```
struct structureName {
    type1 memberName1;
    type2 memberName2;
    type3 memberName3;
    type4 memberName4;
    //...
};
```

- note the required semi-colon ; after closing curly brace
- when defining struct, we don't initialize members; they are merely the blueprint (template) not actual variables
- syntax to declare objects of struct type:

```
structureName objectName;
```

- exactly like declaring simple variables
- this step actually allocates all the memory required to store one record for some instance objectName
- the process of creating objects from **struct type** is called **instantiation**
- compound variables that could hold more than 1 values are typically called **objects**
- syntax to access members:

```
objectName.memberName
```

- each member is used like a single variable; only difference is the way they're accessed

- member can be accessed only by its instance (object) name

#### **1.4 Define structure type to represent student records**

- representing the student record displayed in the figure above
- TBD in class

#### **1.5 Declare objects to store students' records**


- TBD in class
- declare and initialize using uniform initialization

#### **1.6 Access members of students' objects/records**

- TBD in class

#### **1.7 Point structure definition**

- a point in Cartesian coordinate (2-D geometry) is two numbers called coordinates
- there may be a large number of points on the plain, but each point is treated collectively as a single object
- e.g.  $(0, 0)$  indicates the origin, and  $(x, y)$  indicates the point  $x$  units from  $x$ -axis and  $y$  units from the  $y$ -axis



- how can we represent 2-D points in C++?
  - we can use structure!

```
[1]: #include <iostream>
#include <string>
#include <cmath>

using namespace std;
```

```
[2]: // define a point structure
struct Point {
    // can be declared as int x, y;
    int x; // member 1
    int y; // member 2
    // any other member?
    // parenthesis are common on all points and used only for representation
```

```

    // we don't need members for parenthesis
};
// do not initialize members as the memory is not allocated just yet!

```

## 1.8 Point objects

- recall Point structure is just the definition and doesn't actually store data
- need to declare Point objects to actually store the data values (coordinates)
- we can also declare pointers to struct types
- syntax to declare struct objects and pointers is similar to declaring variables
  - afterall, struct is a user-defined type

```
structName objectName;
```

- objects created are automatic or stored in stack memory segment

```
[3]: // declare/instantiate some point objects
Point pt1, pt2;
```

```
[4]: // declare and initialize point objects
// using uniform initialization
// members are initialized in the order they're defined
Point origin = {0, 0};
```

```
[5]: // explicitly casting two values as Point type
pt1 = Point({2, 3});
```

```
[6]: // implicit coercion of two values as a Point type
pt2 = {3, 0};
```

```
[7]: // declared a pointer of Point type and initialize with nullptr
Point * pt_ptr = nullptr;
```

```
[8]: // assign value/address to pt_ptr
// recall, pointers store memory addresses only!
pt_ptr = &pt1;
```

```
[9]: // two addresses must be equal!
cout << pt_ptr << " == " << &pt1 << endl;
```

```
0x10bcf72d0 == 0x10bcf72d0
```

### 1.8.1 Dynamic objects

- memory needed for any struct objects can be allocated in heap memory segment
- the syntax to allocate dynamic objects:

```
structName * ptrName = new structName();
```

- the syntax is same as declaring dynamic variables covered in **Pointers** chapter

```
[10]: // instantiate a pointer object
Point * pt_ptr1 = new Point;
```

```
[11]: // instantiate and initialize a pointer object
Point * pt_ptr2 = new Point({100, -200});
```

## 1.9 Point members

- each member of Point object can be accessed using . member access operator
- syntax:

```
object.member;
ptrObject->member;
```

- members are same as variables that allow us to store and access data
- if a pointer object is used, -> arrow/pointer operator is used to access member

```
[12]: // access members using . (member access) operator
cout << "origin = (" << origin.x << "," << origin.y << ")" << endl;
```

```
origin = (0,0)
```

```
[13]: // assign values to pt1 and pt2;
pt1.x = -3;
pt1.y = 1;
```

```
[14]: // find the distance between pt1 and pt2
float dist;
```

```
[15]: dist = sqrt(pow(pt1.x-pt2.x, 2) + pow(pt1.y-pt2.y, 2))
```

```
[15]: 6.08276f
```

```
[16]: cout << "distance = " << dist << endl;
```

```
distance = 6.08276
```

```
[17]: // accessing members using pointer variables
pt_ptr1->x = -3;
pt_ptr1->y = 1;
```

```
[18]: // we get the same result as above
dist = sqrt(pow(pt_ptr1->x-pt2.x, 2) + pow(pt_ptr1->y-pt2.y, 2))
```

```
[18]: 6.08276f
```

### 1.9.1 Visualize struct and objects in [pythontutor.com](http://pythontutor.com)

## 1.10 Template structures

- notice that Point class defined above uses **int** as type for  $x$  and  $y$  coordinates
- what if we had a coordinate system that used floating point values
  - we'd have to define another struct to represent Point using floating point values
- similar to template function, we can use **template type** in struct definition
  - acts as a placeholder for type that will be passed when the objects are instantiated
- templated struct helps create one generic struct definition that meets all type requirements for its members
- syntax to define template struct type:

```
template<class T1, class T2, ...>
struct structName {
    T1 member1;
    T2 member2;
    type member3;
    // more templated type or actual type members
};
```

- notice the syntax is same as the function template syntax
- 'template<class, class, ... > construct let's you use 1 or more templated type/class separated by comma
- syntax to instantiate objects of template struct types:

```
structName<actualType1, actualType2, ...> objectName;
```

- actualType1 replaces T1, actualType2 replaces T2, and so on...

### 1.10.1 Templated rectangle type

- sides of rectangle may be of various types such as integer, or float or double, etc.
- we define templated rectangle type to account for those types

```
[19]: // assuming both length and width of any rectangle will have the same type T
template<class T>
struct Rectangle {
    T length, width;
    // could use an array of T type
    // T sides[2];
    // length and width are better names than array
};
```

```
[20]: // instantiate some objects of Rectangle types
Rectangle<int> r1;
Rectangle<float> r2;
```

```
[21]: // instantiate and initialize rectangle objects
Rectangle<int> r3 = {10, 5};
```

```
[22]: Rectangle<float> r4 = {8.5f, 5.5f};
```

```
[23]: Rectangle<double> r5 = {100.999, 55.898};
```

### 1.11 Aggregate operations on struct objects

- for any type one has to wonder what operators work out of the box
  - e.g. on strings, we could use +, =, comparison operators (>, ==, etc.)
- no aggregate operations such as input and output are allowed on struct objects as a whole
  - e.g. can't cin >> or cout << objects as a whole
  - it may not make sense to compare two objects (however, compare based on which members?)
- for most operations (except for assignment), objects must be accessed one member at a time!
  - Note, there are ways to explicitly overload aggregate operations by writing extra code
  - that is usually covered in CS2 or *Object Oriented Programming* courses

```
[24]: // try cout; can't!!  
      // pt1 is an object of Point type  
      //cout << pt1;  
      // cout may be broken if you run this! so restart the kernel if you get error
```

```
input_line_35:4:6: error: invalid operands to binary
```

```
expression ('std::__1::ostream' (aka 'basic_ostream<char>') and 'Point')
```

```
cout << pt1;
```

```
~~~~ ~~~
```

```
/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:219:20:
```

```
note: candidate function not viable: no known conversion from
```

```
'Point' to 'const void *' for 1st argument; take
```

```
the address of the argument with &
```

```
basic_ostream& operator<<(const void* __p);
```

```
/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/type_traits:4034:3:
```

```
note: candidate function not viable: no known conversion from
```

```
'std::__1::ostream' (aka 'basic_ostream<char>') to
```

```
'std::byte' for 1st argument
```

```
operator<< (byte __lhs, _Integer __shift) noexcept
```

```
/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:195:20:
```

```
note: candidate function not viable: no known conversion from
```

```
'Point' to 'std::__1::basic_ostream<char>
```

```
&(*) (std::__1::basic_ostream<char> &)' for 1st argument
```

```
basic_ostream& operator<<(basic_ostream& (*__pf)(basic_ostream&))
```



```

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:199:20:
note: candidate function not viable: no known conversion from
'Point' to 'basic_ios<std::__1::basic_ostream<char,
      std::__1::char_traits<char> >::char_type, std::__1::basic_ostream<char,
std::__1::char_traits<char>
      >::traits_type> &(*) (basic_ios<std::__1::basic_ostream<char,
std::__1::char_traits<char>
      >::char_type, std::__1::basic_ostream<char, std::__1::char_traits<char>
>::traits_type> &)' (aka
      'basic_ios<char, std::__1::char_traits<char> > &(*) (basic_ios<char,
std::__1::char_traits<char> >
      &)' ) for 1st argument
      basic_ostream& operator<<(basic_ios<char_type, traits_type>&

```

```

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:204:20:
note: candidate function not viable: no known conversion from
'Point' to 'std::__1::ios_base
      &(*) (std::__1::ios_base &)' for 1st argument
      basic_ostream& operator<<(ios_base& (*__pf)(ios_base&))

```

```

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:207:20:
note: candidate function not viable: no known conversion from
'Point' to 'bool' for 1st argument
      basic_ostream& operator<<(bool __n);

```

```

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:208:20:
note: candidate function not viable: no known conversion from
'Point' to 'short' for 1st argument
      basic_ostream& operator<<(short __n);

```

```

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:209:20:
note: candidate function not viable: no known conversion from
'Point' to 'unsigned short' for 1st argument
      basic_ostream& operator<<(unsigned short __n);

```

```

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:210:20:
note: candidate function not viable: no known conversion from
'Point' to 'int' for 1st argument
      basic_ostream& operator<<(int __n);

```

^  
/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:211:20:

note: candidate function not viable: no known conversion from  
'Point' to 'unsigned int' for 1st argument

basic\_ostream& operator<<(unsigned int \_\_n);  
^

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:212:20:

note: candidate function not viable: no known conversion from  
'Point' to 'long' for 1st argument

basic\_ostream& operator<<(long \_\_n);  
^

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:213:20:

note: candidate function not viable: no known conversion from  
'Point' to 'unsigned long' for 1st argument

basic\_ostream& operator<<(unsigned long \_\_n);  
^

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:214:20:

note: candidate function not viable: no known conversion from  
'Point' to 'long long' for 1st argument

basic\_ostream& operator<<(long long \_\_n);  
^

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:215:20:

note: candidate function not viable: no known conversion from  
'Point' to 'unsigned long long' for 1st argument

basic\_ostream& operator<<(unsigned long long \_\_n);  
^

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:216:20:

note: candidate function not viable: no known conversion from  
'Point' to 'float' for 1st argument

basic\_ostream& operator<<(float \_\_f);  
^

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:217:20:

note: candidate function not viable: no known conversion from  
'Point' to 'double' for 1st argument

basic\_ostream& operator<<(double \_\_f);  
^

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:218:20:

note: candidate function not viable: no known conversion from  
'Point' to 'long double' for 1st argument

```

    basic_ostream& operator<<(long double __f);
    ^

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:220:20:
note: candidate function not viable: no known conversion from
'Point' to
    'basic_streambuf<std::__1::basic_ostream<char, std::__1::char_traits<char>
>::char_type,
    std::__1::basic_ostream<char, std::__1::char_traits<char> >::traits_type>
*' (aka
    'basic_streambuf<char, std::__1::char_traits<char> > *') for 1st
argument
    basic_ostream& operator<<(basic_streambuf<char_type, traits_type>* __sb);
    ^

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:223:20:
note: candidate function not viable: no known conversion from
'Point' to 'std::nullptr_t' (aka 'nullptr_t') for
    1st argument
    basic_ostream& operator<<(nullptr_t)
    ^

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:760:1:
note: candidate function not viable: no known conversion from
'Point' to 'char' for 2nd argument
operator<<(basic_ostream<_CharT, _Traits>& __os, char __cn)
^

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:793:1:
note: candidate function not viable: no known conversion from
'Point' to 'char' for 2nd argument
operator<<(basic_ostream<char, _Traits>& __os, char __c)
^

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:800:1:
note: candidate function not viable: no known conversion from
'Point' to 'signed char' for 2nd argument
operator<<(basic_ostream<char, _Traits>& __os, signed char __c)
^

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:807:1:
note: candidate function not viable: no known conversion from
'Point' to 'unsigned char' for 2nd argument
operator<<(basic_ostream<char, _Traits>& __os, unsigned char __c)

```

```

~

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:821:1:
note: candidate function not viable: no known conversion from
'Point' to 'const char *' for 2nd argument
operator<<(basic_ostream<_CharT, _Traits>& __os, const char* __strn)
~

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:867:1:
note: candidate function not viable: no known conversion from
'Point' to 'const char *' for 2nd argument
operator<<(basic_ostream<char, _Traits>& __os, const char* __str)
~

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:874:1:
note: candidate function not viable: no known conversion from
'Point' to 'const signed char *' for 2nd argument
operator<<(basic_ostream<char, _Traits>& __os, const signed char* __str)
~

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:882:1:
note: candidate function not viable: no known conversion from
'Point' to 'const unsigned char *' for 2nd argument
operator<<(basic_ostream<char, _Traits>& __os, const unsigned char* __str)
~

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:1066:1:
note: candidate function not viable: no known conversion from
'Point' to 'const std::__1::error_code' for 2nd
      argument
operator<<(basic_ostream<_CharT, _Traits>& __os, const error_code& __ec)
~

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:753:1:
note: candidate template ignored: deduced conflicting types for
parameter '_CharT' ('char' vs. 'Point')
operator<<(basic_ostream<_CharT, _Traits>& __os, _CharT __c)
~

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:1057:1:
note: candidate template ignored: could not match
'basic_string_view<type-parameter-0-0, type-parameter-0-1>'
      against 'Point'
operator<<(basic_ostream<_CharT, _Traits>& __os,

```

```

~/
/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:1086:1:
note: candidate template ignored: could not match
'unique_ptr<type-parameter-0-2, type-parameter-0-3>' against
'Point'
operator<<(basic_ostream<_CharT, _Traits>& __os, unique_ptr<_Yp, _Dp> const&
__p)
~/
/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/iomanip:477:5:
note: candidate template ignored: could not match
'__iom_t10<type-parameter-0-0>' against 'Point'
operator<<(basic_ostream<_Cp, _Traits>& __os, const __iom_t10<_Cp>& __x);
~/
/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/iomanip:572:33:
note: candidate template ignored: could not match
'__quoted_output_proxy<type-parameter-0-0, type-parameter-0-2,
type-parameter-0-1>' against 'Point'
basic_ostream<_CharT, _Traits>& operator<<(
~/
/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/iomanip:592:33:
note: candidate template ignored: could not match
'__quoted_proxy<type-parameter-0-0, type-parameter-0-1,
type-parameter-0-2>' against 'Point'
basic_ostream<_CharT, _Traits>& operator<<(
~/
/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:1039:1:
note: candidate template ignored: requirement
'!is_lvalue_reference<basic_ostream<char> &>::value' was not
satisfied [with _Stream = std::__1::basic_ostream<char> &, _Tp =
Point]
operator<<(_Stream&& __os, const _Tp& __x)
~/
/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:814:1:
note: candidate template ignored: could not match 'const _CharT
*' against 'Point'
operator<<(basic_ostream<_CharT, _Traits>& __os, const _CharT* __str)
~/
/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:1093:1:
note: candidate template ignored: could not match
'bitset<_Size>' against 'Point'

```

```

operator<<(basic_ostream<_CharT, _Traits>& __os, const bitset<_Size>& __x)
~

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/valarray:4165:1:
note: candidate template ignored: substitution failure [with
_Expr1 = std::__1::basic_ostream<char>, _Expr2 =
      Point]: no type named 'value_type' in 'std::__1::basic_ostream<char>'
operator<<(const _Expr1& __x, const _Expr2& __y)
~

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/valarray:4180:1:
note: candidate template ignored: substitution failure [with
_Expr = std::__1::basic_ostream<char>]: no type
      named 'value_type' in 'std::__1::basic_ostream<char>'
operator<<(const _Expr& __x, const typename _Expr::value_type& __y)
~

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/valarray:4196:1:
note: candidate template ignored: substitution failure [with
_Expr = Point]: no type named 'value_type' in
      'Point'
operator<<(const typename _Expr::value_type& __x, const _Expr& __y)
~

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:1049:1:
note: candidate template ignored: could not match
'basic_string<type-parameter-0-0, type-parameter-0-1,
      type-parameter-0-2>' against 'Point'
operator<<(basic_ostream<_CharT, _Traits>& __os,
~

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/ostream:1074:1:
note: candidate template ignored: could not match
'shared_ptr<type-parameter-0-2>' against 'Point'
operator<<(basic_ostream<_CharT, _Traits>& __os, shared_ptr<_Yp> const& __p)
~

/Users/rbasnet/anaconda3/envs/cpp/include/c++/v1/iomanip:362:1:
note: candidate template ignored: could not match
'__iom_t8<type-parameter-0-2>' against 'Point'
operator<<(basic_ostream<_CharT, _Traits>& __os, const __iom_t8<MoneyT>& __x)
~

```

Interpreter Error:

```
[24]: // read in/store data one member at a time
char ch;
Point pt3;
```

```
[26]: cout << "Enter a point in (x, y) format: ";
cin >> ch >> pt3.x >> ch >> pt3.y >> ch;
// ch is just a place variable for unnecessary character to read and ignore
```

Enter a point in (x, y) format: (1, 2)

```
[26]: @0x10bcaad70
```

```
[27]: // print the point in right format; accessing one member at a time
cout << "pt3 = (" << pt3.x << ", " << pt3.y << ")";
```

pt3 = (1, 2)

#### 1.11.1 aggregate copy (=) is allowed

- one struct object can be copied into another out of the box
- object is copied member by member from source to destination

```
[28]: Point pt4 = pt3;
```

### 1.12 Passing struct objects to functions

- struct objects can be passed to functions both by value and by reference

#### 1.12.1 pass by value

- struct objects can be copied into another same type of struct objects using = assignment operator
- this allows us to pass struct to functions by value (by copying the data)
  - though not recommended! why?

```
[29]: // passing some constant Point
void printPoint(const Point pt) {
    cout << "(" << pt.x << ", " << pt.y << ")";
}
```

```
[30]: printPoint(pt4);
```

(1, 2)

#### 1.12.2 pass by reference

- any data type can be explicitly pass by reference in C++
- recommended!

```
[31]: void getPoint(Point & pt) {
        cout << "Enter a point in (x, y) format: ";
        cin >> ch >> pt.x >> ch >> pt.y >> ch;
        // Note: when using terminal, after the last character ) is read \n is left
        ↪behind
        // getline() will fail!
        // good idea to read \n whitespace and ignore it!
    }
```

```
[32]: Point pt5;
```

```
[34]: getPoint(pt5);
```

Enter a point in (x, y) format: (8, 0)

```
[35]: printPoint(pt5);
```

(8, 0)

```
[36]: // function finds the distance between two points
        // sqrt( (x1-x2)^2 + (y1-y2)^2 )
        float distance(const Point & p1, const Point & p2) {
            return sqrt(pow(p1.x-p2.x, 2) + pow(p1.y-p2.y, 2));
        }
```

```
[37]: cout << "distance between ";
        printPoint(pt4);
        cout << " and ";
        printPoint(pt5);
        cout << " = " << distance(pt4, pt5);
```

distance between (1, 2) and (8, 0) = 7.28011

### 1.13 Returning struct from functions

- as the = assignment works on structs, functions can return struct types
- though not recommended! why?

```
[38]: // function returns Point type object
        Point getPoint() {
            Point pt;
            cout << "Enter a point in (x, y) format: ";
            cin >> ch >> pt.x >> ch >> pt.y >> ch;
            return pt;
        }
```

```
[39]: // assign the returned object from getPoint() to pt6 object
        Point pt6 = getPoint();
```



Enter a point in (x, y) format: (4, 4)

```
[40]: printPoint(pt6);
```

(4, 4)

## 1.14 Array/vectors of structs

- if more than one similar records/structs need to be stored
  - we can use array or vector of struct type
- let's say, we need to store a bunch of coordinate points in memory
  - array/vector of points is a natural choice!

```
[41]: // declare and initialize array
Point points[] = {{1, 2}, {3, 4}, {6, 7}, {-1, -1}, {0, 0}};
```

```
[42]: // declare array of points
Point points1[2];
```

```
[43]: // accessing point element in array
printPoint(points[0]);
```

(1, 2)

```
[44]: // accessing point element's member in array
cout << "first point's x = " << points[0].x << endl;
```

first point's x = 1

```
[45]: // assigning values to array
points1[0] = getPoint();
```

Enter a point in (x, y) format: (10, 5)

```
[46]: points1[1] = getPoint();
```

Enter a point in (x, y) format: (-4, -10)

### 1.14.1 vectors of struct type

- vectors, like arrays, can be used to store user-defined **struct** types

```
[54]: // declare and initialize vector of Point
vector<Point> point_vector = {{0, 0}, {1, 1}, {2, 2}};
```

```
[48]: // create vector of RectangleType
vector<Rectangle<int>> rects;
```

```
[49]: // add r1 rectangle object to rects vector
      rects.push_back(r1);
```

```
[51]: // can't add Rectangle r2 because its type is float
      rects.push_back(r3);
```

```
[52]: // declare and initialize rectangles vector with two rectangles
      vector<Rectangle<float>> rectangles = {{10, 5}, {8.5, 2.6}};
```

```
[55]: // calculate area of first rectangle stored in rectangles vector
      cout << "area = " << rectangles[0].length*rectangles[1].width << endl;
```

area = 26

```
[56]: // traversing vectors
      // auto also works on user-defined type
      for(auto rect: rectangles) {
          cout << "rectangle info - length x width: " << rect.length << " x " << rect.
      ↪width << endl;
      }
```

rectangle info - length x width: 10 x 5  
rectangle info - length x width: 8.5 x 2.6

```
[ ]: // same as above
      for(RectangleType rect: rectangles) {
          cout << "rectangle info - length x width: " << rect.length << " x " << rect.
      ↪width << endl;
      }
```

```
[57]: // using index
      for(int i=0; i<rectangles.size(); i++) {
          cout << "rectangle area: "
              << rectangles[i].length << "x"
              << rectangles[i].width << " = "
              << rectangles[i].length*rectangles[i].width << endl;
      }
```

rectangle area: 10x5 = 50  
rectangle area: 8.5x2.6 = 22.1

## 1.15 Array/vector in struct

- array or vector of any type can be used as a member of a struct
- if there are several members of same types that don't need their own names, we can use an array/vector member
- having each member their own name makes program more readable and struct intuitive to use, however!

```
[2]: #include <vector>
```

```
[3]: // let's define a structure to store student record
struct Student {
    string firstName;
    char MI;
    string lastName;
    vector<float> test_scores; // each test doesn't have a unique name
    string pri_contact_fName;
    char pri_contact_MI;
    string pri_contact_lName;
    bool semester_finished[2]; // semesters though have names Freshman Fall,
    ↪etc.; we can use 1st, 2nd etc.
};
```

```
[4]: // declaration of st1
Student st1;
```

```
[5]: st1.firstName = "John";
```

```
[6]: // accessing an array member
// NOTE: array can be accessed one element at a time
st1.test_scores.push_back(100);
st1.test_scores.push_back(95.5);
```

```
[7]: // accessing another array member
st1.semester_finished[0] = true;
st1.semester_finished[1] = false;
```

```
[7]: // instantiate and initialize
// Note the order of values and how each member is initialized based on its type
Student st2 = {"Jane", 'A', "Smith", {0, 0, 0}, "Jim", 'J', "Smith", {false,
    ↪false}};
```

```
[9]: // Access student 2's first test score
st2.test_scores[0]
```

```
[9]: 0.00000f
```

```
[10]: // Access student 2's last test score
st2.test_scores.back()
```

```
[10]: 0.00000f
```

```
[12]: // student 1's first test socre
st1.test_scores.front()
```

```
[12]: 100.000f
```

### 1.16 Struct in another struct

- any struct type can be used as a member type in another struct type
- in Student structure above, firstName, MI and lastNames can be repeated for various names
  - student name, primary contact, secondary contact, father's name, mother's name, etc.
- we can convert the repeating group of members into its own struct type

```
[2]: // most people have three names
struct NameType {
    string firstName;
    char MI;
    string lastName;
};
```

```
[3]: // let's redefine Student type with NameType
struct StudentType {
    NameType name;
    float test_scores[3];
    NameType primary_contact;
    bool semester_finished[2];
};
// Notice how shorter the StudentType has become using NameType?
// we can declare as many names of NameType as we wish
// makes the StudentType concise yet readable and intuitive
```

```
[4]: // instantiate objects
StudentType st3;
```

```
[5]: // assign values to name member
// "name" is a member of st3 object but it itself is a struct type object
// keep drilling down until we come to the actual member name that stores the
    ↪ data
st3.name.firstName = "David";
st3.name.MI = 'A';
st3.name.lastName = "Johnson";
```

```
[9]: // shorter way to assign to a struct type object
st3.name = {"Dave", 'A', "Johnson"};
```

```
[6]: // create an array of student records
StudentType students[2];
```

```
[15]: students[0] = st3;
```

```
[16]: // access member of array and member of struct
students[0].semester_finished[0] = true;
```

### 1.17 Reading structured data

- one must know the structure of data in order to properly read/parse and store it into a program
- reading unstructured data is difficult
  - best way is to read line by line and process each line
- reading structured data is a bit easier
- let's read the structured data provided in [studentgrades.txt](#) file
  - there are 3 rows or records and 5 columns (values) for each record
  - first 2 columns are string (names) and the rest 3 columns are integers (grades)
- most Kattis problems provide some structures in their input data so the programmers can correctly parse the data

```
[1]: #include <iostream>
#include <fstream>
#include <string>
#include <functional>
#include <algorithm>
#include <vector>

using namespace std;
```

```
[2]: // struct type is a perfect way to read these student's grades
struct StudentGrade {
    string firstName;
    string lastName;
    int grades[3];
    float averageGrade;
    char letterGrade;
};
```

```
[3]: // let's create a vector of Student type to store all the records
vector<StudentGrade> gradebook;
```

```
[4]: ifstream fin;
```

```
[5]: // let's read the data
// fin is ifstream object declared above
fin.open("studentgrades.txt");
```

```
[6]: // let's compute average grade
float average(const StudentGrade & s) {
    float sum = s.grades[0] + s.grades[1] + s.grades[2];
    return sum/3.0;
}
```

```
[7]: while(!fin.eof()) { // eof() checks if end-of-file has been reached
    // create Student object to hold the data temporarily
    StudentGrade temp;
    fin >> temp.firstName >> temp.lastName >> temp.grades[0] >> temp.grades[1]
    &#219;>> temp.grades[2];
    if (!fin.good()) break;
    temp.averageGrade = average(temp);
    // add the temp to gradebook
    gradebook.push_back(temp);
}
```

```
[8]: // close file
fin.close();
```

```
[9]: // let's write a function to print Student's info
void printStudent(const StudentGrade & s) {
    cout << s.firstName << " " << s.lastName << " " << s.grades[0] << " "
        << s.grades[1] << " " << s.grades[2] << " avg: " << s.averageGrade;
}
```

```
[10]: // let's print the first student's info
printStudent(gradebook[0]);
```

John Smith 100 95 85 avg: 93.3333

```
[11]: // print all the students' info
for(StudentGrade s: gradebook) {
    printStudent(s);
    cout << endl;
}
```

John Smith 100 95 85 avg: 93.3333  
Jane Doe 85 89 99 avg: 91  
Jill Jones 56 89 99 avg: 81.3333

```
[13]: // sort the student records based on average score?
// need to define a comparision function and pass it to sort
// compares two students' average grades in ascending order
bool compareSmaller(const StudentGrade & s1, const StudentGrade & s2) {
    return (s1.averageGrade < s2.averageGrade);
}
```

```
[14]: // now we can sort the gradebook
sort(gradebook.begin(), gradebook.end(), compareSmaller);
```

```
[15]: // print all the students' info
for(StudentGrade s: gradebook) {
```

```

    printStudent(s);
    cout << endl;
}

```

```

Jill Jones 56 89 99 avg: 81.3333
Jane Doe 85 89 99 avg: 91
John Smith 100 95 85 avg: 93.3333

```

```

[17]: // let's write a compare function for descending order
bool compareGreater(const StudentGrade & s1, const StudentGrade & s2) {
    return (s1.averageGrade > s2.averageGrade);
}

```

```

[18]: // now we can sort the gradebook in descending order using our own compare_
      ↪function
sort(gradebook.begin(), gradebook.end(), compareGreater);

```

```

[19]: // print all the students' info
      // looks like this could go into a function...
for(StudentGrade s: gradebook) {
    printStudent(s);
    cout << endl;
}

```

```

John Smith 100 95 85 avg: 93.3333
Jane Doe 85 89 99 avg: 91
Jill Jones 56 89 99 avg: 81.3333

```

## 1.18 Writing structured data to file

- print students' grades report in a tabular format

```

[20]: // let's create and open a file to write data to
ofstream fout("studentgradereport.txt");

```

```

[22]: int colWidth;

```

```

[23]: colWidth = 20;

```

```

[25]: // print all the students' info to the fout stream

      // write column headers
fout << setw(90) << setfill('=') << " " << setfill(' ') << endl;
fout << setw(colWidth) << left << "First Name"
    << setw(colWidth) << left << "Last Name";
      // students grades
for(int i=0; i<3; i++) {
    string testHeader = "test" + to_string(i+1);

```

```

        fout << setw(10) << right << testHeader;
    }

    fout << setw(15) << right << "Avgerage" << endl;
    fout << setw(90) << right << setfill('=') << " " << endl;

    // write records
    fout << setfill(' ') << fixed << setprecision(1);
    for(StudentGrade s: gradebook) {
        fout << setw(colWidth) << left << s.firstName
            << setw(colWidth) << left << s.lastName;
        for(int i=0; i<3; i++)
            fout << setw(10) << right << s.grades[i];
        fout << setw(15) << right << s.averageGrade << endl;
    }
    fout << setw(90) << setfill('*') << " " << endl;

```

```

[27]: // convert the above code to a function!
      // all the stream objects must be passed-by reference!
      // out is a generic ostream parameter (can be cout or fout)
      void writeResults(ostream & out) {
          // print all the students' info to the fout stream

          // write column headers
          out << setw(90) << setfill('=') << " " << setfill(' ') << endl;
          out << setw(colWidth) << left << "First Name"
              << setw(colWidth) << left << "Last Name";
          // students grades
          for(int i=0; i<3; i++) {
              string testHeader = "test" + to_string(i+1);
              out << setw(10) << right << testHeader;
          }
          out << setw(15) << right << "Avgerage" << endl;
          out << setw(90) << setfill('=') << " " << endl;

          // write records
          out << setfill(' ') << fixed << setprecision(1);
          for(StudentGrade s: gradebook) {
              out << setw(colWidth) << left << s.firstName
                  << setw(colWidth) << left << s.lastName;
              for(int i=0; i<3; i++)
                  out << setw(10) << right << s.grades[i];
              out << setw(15) << right << s.averageGrade << endl;
          }
          out << setw(90) << setfill('*') << " " << endl;
      }

```



```
[28]: // write to standard output/console
writeResults(cout);
```

```
=====
=====
First Name      Last Name      test1    test2    test3
Avgerage
=====
=====
John            Smith          100      95       85
93.3
Jane            Doe            85       89       99
91.0
Jill            Jones          56       89       99
81.3
*****
*****
```

```
[29]: // write to file output
writeResults(fout);
// check the contents of file
```

```
[30]: // close the file
fout.close();
```

## 1.19 Exercises

1. Write a program that computes distance between two points in Cartesian coordinates.
  - use struct to represent Point
  - prompt user to enter two points
  - use as many function(s) as possible
  - write at least 3 test cases for each computing functions
  - program continues to run until user wants to quit
  - most of the part is done in Jupyter Notebook demo
2. Write a program to compute area and circumference of a circle using struct.
  - use struct to represent Circle
  - prompt user to enter radius of a circle
  - use as many function(s) as possible
  - write at least 3 test cases for each computing functions
  - program continues to run until user wants to quit
3. Write a program to compute area and perimeter of a rectangle using struct.
  - use struct to represent Rectangle
  - prompt user to enter length and width of a rectangle
  - use as many function(s) as possible
  - write at least 3 test cases for each computing functions
  - program continues to run until user wants to quit
4. Write a program to compute area and perimeter of a triangle given 3 sides.

- use struct to represent Triangle
- prompt user to enter 3 sides of a triangle
- use as many function(s) as possible
- write at least 3 test cases for each computing functions
- program continues to run until user wants to quit

```
[1]: // Sample solution for #4
// using incremental development
// using functions as possible to break the problem
#include <iostream>
#include <cmath>
#include <string>
#include <cassert>
#include <sstream>
#include <iomanip>

using namespace std;
```

```
[2]: // use struct to represent Triangle
// could be a templated struct
struct Triangle {
    float side1, side2, side3;
    // can be an array
    // float sides[3];
};
```

```
[3]: // function to check if 3 sides form a triangle
bool validTriangle(float s1, float s2, float s3) {
    // sum of every pair must be greater than the third
    return (s1+s2 > s3 && (s2+s3 > s1) && (s1+s3 > s2))? true: false;
}
```

```
[4]: void test_validTriangle() {
    assert(validTriangle(2, 3, 4) == true);
    assert(validTriangle(1, 2, 3) == false);
    assert(validTriangle(4, 5, 10) == false);
    cerr << "all test cases passed for validTriangle()\n";
}
```

```
[5]: test_validTriangle()
```

all test cases passed for validTriangle()

```
[6]: // function prompts user to enter 3 sides of a triangle
// creates and returns a triangle
Triangle getTriangle() {
    float s1, s2, s3;
    // input validation
```

```

do {
    cout << "Enter three sides of a triangle separated by space: ";
    cin >> s1 >> s2 >> s3;
    // check if three sides form a triangle
    if (!validTriangle(s1, s2, s3))
        cout << "3 sides do not form a triangle.\n"
              << "Sum of any 2 sides must be greater than the third!\n";
    else
        break;
} while(true);
return Triangle({s1, s2, s3});
}

```

```

[7]: // let's manually test getTriangle
Triangle t1;

```

```

[8]: t1 = getTriangle();

```

```

Enter three sides of a triangle separated by space:
1 2 3
3 sides do not form a triangle.
Sum of any 2 sides must be greater than the third!
Enter three sides of a triangle separated by space: 3 4 5

```

```

[ ]: float trianglePerimeter(const Triangle & t) {
    return t.side1 + t.side2 + t.side3;
}

```

```

[ ]: // write 3 test cases for trianglePerimeter
void test_trianglePerimeter() {
    assert(trianglePerimeter(Triangle({2, 3, 4})) == 9);
    assert(trianglePerimeter(Triangle({3, 4, 5})) == 12);
    assert(trianglePerimeter(Triangle({2.5, 3.5, 4.5})) == 10.5);
    cerr << "all test cases passed for trianglePerimeter()\n";
}

```

```

[13]: test_trianglePerimeter();

```

```

all test cases passed for trianglePerimeter()

```

```

[14]: // function to compute area of a triangle
float triangleArea(const Triangle & t) {
    // use heron's formula: https://www.mathsisfun.com/geometry/herons-formula.html
    float s = trianglePerimeter(t)/2;
    return sqrt(s*(s-t.side1)*(s-t.side2)*(s-t.side3));
}

```

```
[15]: // wrapper function to test if two floating numbers are equal upto precision
      ↪ decimal points
void assertAlmostEqual(float value1, float value2, int precision) {
    ostringstream oss;
    // create output string stream with precision for floating-point values
    oss << fixed << setprecision(precision) << value1 << " " << value2;
    // create input string stream from output string stream
    istreamstream iss(oss.str());
    float v1, v2;
    // extract the values as float
    iss >> v1 >> v2;
    assert(v1 == v2);
}
```

```
[16]: // write 3 test cases for triangleArea
void test_triangleArea() {
    assert(triangleArea(Triangle({3, 4, 5})) == 6.0);
    float area = triangleArea({2, 4, 5}); // coercion of 3 values into Triangle
    ↪ type
    assertAlmostEqual(area, 3.799671038392666, 4); // accuracy upto 4 decimal
    ↪ points
    assertAlmostEqual(triangleArea({3, 4, 6}), 5.3326822, 4);
    cerr << "all test cases passed for triangleArea()\n";
}
```

```
[17]: test_triangleArea();
```

all test cases passed for triangleArea()

```
[18]: // function to calculate and print the result on triangle
void printResult(const Triangle & t) {
    cout << "Triangle info: \n"
         << "3 sides length: " << t.side1 << " " << t.side2 << " " << t.side3
         << "\narea: " << triangleArea(t)
         << "\nperimeter: " << trianglePerimeter(t);
}
```

```
[19]: // complete program
void program() {
    Triangle t;
    string cont;
    do {
        t = getTriangle();
        printResult(t);
        cout << "\nWant to enter another triangle? [yes|y]: ";
        cin >> cont;
        if (cont == "yes" || cont == "y") continue;
    }
```

```

        else break;
    }while(true);
    cout << "Good bye...";
}

```

[20]: `program();`

```

Enter three sides of a triangle separated by space: 1 2 3
3 sides do not form a traingle.
Sum of any 2 sides must be greater than the third!
Enter three sides of a triangle separated by space: 4 5 6
Triangle info:
3 sides length: 4 5 6
area: 9.92157
perimeter: 15
Want to enter another triangle? [yes|y]: yes
Enter three sides of a triangle separated by space: 4 5 6
Triangle info:
3 sides length: 4 5 6
area: 9.92157
perimeter: 15
Want to enter another triangle? [yes|y]: no
Good bye...

```

see complete sample solution for exercise 4 in [demos/structs/triangle/triangle.cpp](#)

#### 5. A Grade Book:

- Write a C++ menu-driven program that let's professors keep track of students grades with the following requirements:
- program must use struct to keep track of students grades
- program prompts user to enter name of the input text file that contains students information in the following format
  - first name, last name, test1, test2, test3, test4, test5
- program calculates avearge grade and the letter grade (A-F) based on the average grade
- program sorts the student records based on grade in non-increasing order (highest to lowest)
- program lets user add a new student
- program lets user update existing student's information
- program lets user delete existing student
- program saves the data back into the same input file as a database
- program creates a cleanly formatted report of students' grades

## 1.20 Kattis problems

- struct is not a strict requirement to solve Kattis problems
- struct is generally used when the problems can be better solved using your own type

## 1.21 Summary

- this chapter covered a new concept of creating user-defined type using struct
- saw many examples of struct types and objects instantiated with those types
- learned that array can be a member of struct
- learned that a larger number of records (struct type) can be stored in an array
- learned about out-of-the-box aggregate operations on struct objects
  - assignment (=) is the only one that works out-of-the-box
- learned how to pass struct objects to functions and return from them as well
- exercises and a sample solutions using incremental development technique

[ ]: