

INTRODUCTION


STATIC VS DYNAMIC MEMORY ALLOCATION

```
void main()  
{
```

```
    int a;  
    float b;
```

```
}
```

Stack frame
→
Activation record



HOW DOES STACK WORK?

```
void fun2(int i)  
{
```

```
    int a;  
    _____  
    _____
```

```
}
```

```
void fun1()  
{
```


```
    int x;  
    fun2(x);
```

```
}
```

```
void main()  
{
```

```
    int a;  
    float b;  
    fun1();
```

```
}
```



1. Stack is always organised memory.


HOW DOES HEAP MEMORY WORK?

1. Heap may be organised memory or unorganised memory.
2. Heap must be treated as a resource i.e when it is needed, we must use it and when not needed, free it so that it can be used by other applications.

For eg- printer is a resource.


```
void main()
{
    int *p;

    for C++ p = new int[5];
    for C   p = (int*) malloc(2*5);
    //      ^ for array
    DEALLOCATION delete []p;
               p = NULL;
}
```



DATA TYPE?

- 1. Representation of data.
- 2. Operation on data.



ABSTRACT DATATYPE

↳ hiding internal details

(part of object oriented programming)

What does log mean?

$\log_2 n$ → This gets divided by this until it reaches 1.

Time and Space complexity

```
void swap(x, y)
{
```

```
    int t;
```

```
    t = x;
```

```
    x = y;
```

```
    y = t;
```

```
}
```

$O(1)$

```
int sum(int A[], int n)
{
```

```
    int s, i;
```

```
    s = 0;
```

```
    for(i = 0; i < n; i++)
```

```
    {
```

```
        s = s + A[i];
```

```
    }
```

```
    return s;
```

```
}
```

$2n + 3$

$O(n)$

because i will be initialized (+1) and i will be incremented for n no of times and 1 time it will fail too (+n)

// because one time it will fail too.

```
Void Add (int n)
{
```

```
    int i, j;
```

```
    for (i=0; i<n; i++)
```

```
    {
```

```
        for (j=0; j<n; j++)
```

```
        {
```

```
            c[i][j] = A[i][j] + B[i][j];
```

```
        }
```

```
    }
```

```
}
```

_____ $n+1$

_____ $n * (n+1)$

_____ $n * n$

$$f(n) = 2n^2 + 2n + 1$$

$$O(n^2)$$

because the nested loop
will run again and
again for $(n+1)$ no of
times.