REST-INTERFACE SPECS

bluem

RESTfull Web Services with tokenAccess
Documentation

viamijnbank

REST-INTERFAC

Contents

CONTENTS 2

1 INTRODUCTION 4

2 ACCESS TO THE REST WEBSERVICES 5

2.1 EPayment service – production environment 5

2.2 EMandate service – production environment 5

2.3 IDentity service – production environment 5

2.4 IBANCheck service – production environment 5

2.5 CRUKSCheck service – production environment 5

2.6 CCBRCheck service – production environment 5

2.7 Refund service – production environment 5

2.8 AddressLookup service – production environment 5

2.9 AMLCompliance service – production environment 5

2.10 CIRCheck service – production environment 5

2.11 Acceptance environment (ACC) 6

2.12 Test environment (TEST) 6

3 CONSTRUCTING THE REQUEST 8

3.1 Request headers 8

3.2 Request content 9

3.3 Authentication 9

4 REQUESTS 10

4.1 Types of requests 11

4.1.1 EPayment createTransaction (PTX) 11

4.1.2 EPayment requestStatus (PSX) 11

4.1.3 EMandate createTransaction (TRX) 11

© 2025 Bluem b.v. - All rights reserved.

4.1.4 EMandate requestStatus (SRX) 11
4.1.5 IDentity createTransaction (ITX) 12
4.1.6 IDentity requestStatus (ISX) 12
4.1.7 IBANCheck createTransaction (INX) 12
4.1.8 CRUKSCheck createTransaction (CTX) 12
4.1.9 CCBRCheck createTransaction (CBX) 12
4.1.10 Refund createTransaction (RTX) 13
4.1.11 AddressLookup createTransaction (ATX) 13
4.1.12 AMLCompliance createTransaction (ACX) 13
4.1.13 CIRCheck createTransaction (CIX) 13

5 RESPONSES 14

6 IMPORTANT NOTES 15

7 EXAMPLES 16

7.1 Create transaction request 16

7.2 Transaction status request 16

© 2025 Bluem b.v. - All rights reserved.

1 INTRODUCTION

Bluem eServices system provides a REST interface to submit single payment, mandate, identity, IBAN name check, CRUKS check, CCBR check, CIR check, AddressLookup, AML Compliance (PEP, Sanction, CriminalWatchlist) screening or Refund transaction requests using a Single URL (over HTTPS) POST request. The interface can also be used for requesting the status of a single payment, mandate or identity transaction. This document describes the REST web service with **accessToken.**

Documentation version = v1.0.9

© 2025 Bluem b.v. - All rights reserved.

2 Access to the REST webservices

2.1 EPayment service – production environment

- *Create transaction*: https://viamijnbank.net/**pr**/createTransactionWithToken?token=<accessToken>
- *Request transaction status*: https://viamijnbank.net/**pr**/requestTransactionStatusWithToken?token=<accessToken>

2.2 EMandate service – production environment

- *Create transaction*: https://viamijnbank.net/**mr**/createTransactionWithToken?token=<accessToken>
- *Request transaction status*: https://viamijnbank.net/**mr**/requestTransactionStatusWithToken?token=<accessToken>

2.3 IDentity service – production environment

- *Create transaction*: https://viamijnbank.net/**ir**/createTransactionWithToken?token=<accessToken>
- *Request transaction status*: https://viamijnbank.net/**ir**/requestTransactionStatusWithToken?token=<accessToken>

2.4 IBANCheck service – production environment

- *Create transaction*: https://viamijnbank.net/**icr**/createTransactionWithToken?token=<accessToken>

2.5 CRUKSCheck service – production environment

- *Create transaction*: https://viamijnbank.net/**ccr**/createTransactionWithToken?token=<accessToken>

2.6 CCBRCheck service – production environment

- *Create transaction*: https://viamijnbank.net/**cbr**/createTransactionWithToken?token=<accessToken>

2.7 Refund service – production environment

- *Create transaction*: https://viamijnbank.net/**rr**/createTransactionWithToken?token=<accessToken>

2.8 AddressLookup service – production environment

- *Create transaction*: https://viamijnbank.net/**ar**/createTransactionWithToken?token=<accessToken>

2.9 AMLCompliance service – production environment

- *Create transaction*: https://viamijnbank.net/**acr**/createTransactionWithToken?token=<accessToken>

2.10 CIRCheck service – production environment

- *Create transaction*: https://v2.viamijnbank.net/**cir**/createTransactionWithToken?token=<accessToken>

© 2025 Bluem b.v. - All rights reserved.

2.11 Acceptance environment (ACC)

- *Create transaction (ePayment)*: https://acc.viamijnbank.net/pr/createTransactionWithToken?token=<accessToken>
- *Request transaction status (ePayment)*: https://acc.viamijnbank.net/pr/requestTransactionStatusWithToken?token=<accessToken>
- *Create transaction (eMandate)*: https://acc.viamijnbank.net/mr/createTransactionWithToken?token=<accessToken>
- *Request transaction status (eMandate)*: https://acc.viamijnbank.net/mr/requestTransactionStatusWithToken?token=<accessToken>
- *Create transaction (Identity)*: https://acc.viamijnbank.net/ir/createTransactionWithToken?token=<accessToken>
- *Request transaction status (Identity)*: https://acc.viamijnbank.net/ir/requestTransactionStatusWithToken?token=<accessToken>
- *Create transaction (IBANCheck):* https://acc.viamijnbank.net/icr/createTransactionWithToken?token=<accessToken>
- *Create transaction (CRUKSCheck):* https://acc.viamijnbank.net/ccr/createTransactionWithToken?token=<accessToken>
- *Create transaction (CCBRCheck):* https://acc.viamijnbank.net/cbr/createTransactionWithToken?token=<accessToken>
- *Create transaction (Refund):* https://acc.viamijnbank.net/rr/createTransactionWithToken?token=<accessToken>
- *Create transaction (AddressLookup):* https://acc.viamijnbank.net/ar/createTransactionWithToken?token=<accessToken>
- *Create transaction (AMLCompliance):* https://acc.viamijnbank.net/acr/createTransactionWithToken?token=<accessToken>
- *Create transaction (CIRCheck):* https://acc.v2.viamijnbank.net/cir/createTransactionWithToken?token=<accessToken>

The ACC system of Bluem is connected to the test environment of the banks (for Payments, Refund, Emandates, Identity, IBANCheck) and test CRUKS of the KSA. The Bluem ACC and TEST for CCBR and CIR is connected to PROD environment of Rechtspraak Nederland. There is no TEST environment at Rechtspraak Nederland. The TEST and ACC environment for AddressLookup and AML Compliance (Sanction&PEP&CriminalList) also connect to production of our sources.

At ACC system, all outgoing mail, if any, will be sent to the email address specified in the request. ACC is only setup at request.

2.12 Test environment (TEST)

- *Create transaction (ePayment)*: https://test.viamijnbank.net/pr/createTransactionWithToken?token=<accessToken>
- *Request transaction status (ePayment)*: https://test.viamijnbank.net/pr/requestTransactionStatusWithToken?token=<accessToken>
- *Create transaction (eMandate)*: https://test.viamijnbank.net/mr/createTransactionWithToken?token=<accessToken>
- *Request transaction status (eMandate)*: https://test.viamijnbank.net/mr/requestTransactionStatusWithToken?token=<accessToken>
- *Create transaction (Identity)*: https://test.viamijnbank.net/ir/createTransactionWithToken?token=<accessToken>
- *Request transaction status (Identity)*: https://test.viamijnbank.net/ir/requestTransactionStatusWithToken?token=<accessToken>
- *Create transaction (IBANCheck):* https://test.viamijnbank.net/icr/createTransactionWithToken?token=<accessToken>
- *Create transaction (CRUKSCheck):* https://test.viamijnbank.net/ccr/createTransactionWithToken?token=<accessToken>
- *Create transaction (CCBRCheck):* https://test.viamijnbank.net/cbr/createTransactionWithToken?token=<accessToken>
- *Create transaction (Refund):* https://test.viamijnbank.net/rr/createTransactionWithToken?token=<accessToken>
- *Create transaction (AddressLookup):* https://test.viamijnbank.net/ar/createTransactionWithToken?token=<accessToken>
- *Create transaction (AMLCompliance):* https://test.viamijnbank.net/acr/createTransactionWithToken?token=<accessToken>
- *Create transaction (CIRCheck):* https://test.v2.viamijnbank.net/cir/createTransactionWithToken?token=<accessToken>

To test ePayment status with TEST bank system, you have to use specific Amounts. When you set the Amount from 1 to 7, you can get different statuses.

Amount	EndStatus

© 2025 Bluem b.v. - All rights reserved.

1.00 or any other values	Success
4.00	Open
2.00	Cancelled
3.00	Expired
5.00	Failure
7.00	Failure in system

To test **Identity (iDIN)** status with the TEST bank system, you have to use specific entranceCode that starts with the a specific entranceCode_prefix**<blaBla>** at TEST => by doing so, you will get selected status from the bank back. For iDIN the following issuer responses can be tested by sending special values in the entranceCode:
Issuer Response Trigger value Entrance Code
Success 100 entranceCode = succesHIO100OIHtest<blaBla>
Cancelled 200 entranceCode = cancelledHIO200OIHtest<blaBla>
Expired 300 entranceCode = expiredHIO300OIHtest<blaBla>
Open 400 entranceCode = openHIO400OIHtest<blaBla>
Failure 500 entranceCode = failureHIO500OIHtest<blaBla>
IX1100 701 entranceCode = receivedXMLNotValidHIO701OIHtest<blaBla>
SO1100 702 entranceCode = systemUnavailabilityHIO702OIHtest<blaBla>
SE2700 703 entranceCode = invalidElectronicSignatureHIO703OIHtest<blaBla>
BR1200 704 entranceCode = versionNumberInvalidHIO704OIHtest<blaBla>
AP3000 705 entranceCode = productSpecificErrorHIO705OIHtest<blaBla>

“EntranceCode<blaBla>” in total is not allowed to be longer than 40 positions! The reason which many parties integrate a timestamp with milliseconds as part of the entranceCode is that it needs to unique in time for the transaction. So each entranceCode you generate needs to be unique in time!

For **eMandates,** you can control the status you get back at TEST with the following composition of the entranceCode:

EntranceCode that starts with:	EndStatus	**Adviestekst voor melding op uw website Mandates**
HIO100OIH…	Success	*Wij hebben uw Digitale Incassomachtiging ontvangen.*(Your eMandate is successful).
HIO200OIH…	Cancelled	*U heeft uw incassomachtiging afgebroken.* (You have cancelled your eMandate).
HIO300OIH…	Expired	N.v.t.
HIO500OIH…	Failure	*Uw Incassomachtiging is niet geslaagd.* (Your eMandate has not been successful).
HIO400OIH…	Open	*We hebben van uw bank nog geen bevestiging ontvangen.* (We did not receive a confirmation from your bank yet).
HIO600OIH…	Pending	*Uw IncassoMachtiging vereist nog akkoord van een geautoriseerde gebruiker in internetbankieren. /* (Your eMandate requires confirmation of an authorised user); this one can only occur with B2B incasso, where a bank account might stipulate that 2 persons have to confirm the emandate.

Important note emandate at TEST: at TEST Emandate, always use Bluem merchantID 0020000387

At TEST, if you use DebtorWallet, and already pre-select bank, please preselect at TEST always Rabobank, bic = RABONL2U

At TEST, all outgoing mail, if any, will be sent to predefined TEST emails. TEST will ignore the email address in the request specified to ease the testing.

The Bluem TEST for CCBR and CIR is connected to PROD environment of Rechtspraak Nederland. There is no TEST environment at Rechtspraak Nederland. Also for Sanction & PEP as well as AddressLookup, at TEST you get real answers.

© 2025 Bluem b.v. - All rights reserved.

3 Constructing the Request

Below is a high level description of the steps to follow in order to construct the ***Request*** (for example a POST request):

Important: The webservice expects a **single *Request*** with the XML content and the request headers as described further in this document.

1. Create the HTTP ***Request***, i.g. a POST request
2. Set the following request headers for the ***Request*** (for details see 3.1):
    a. **x-ttrs-date**
    b. **x-ttrs-files-count**
    c. **x-ttrs-filename**
3. Set the content of the ***Request*** with the following content headers (for details see 3.2):
    a. Content-Type: application/xml;
    b. **type=TRX** (or PTX, ITX, INX, CTX, CBX, RTX, ATX, ACX, CIX, SRX, PSX, ISX);
    c. charset=utf-8;

3.1 Request headers

Every REST request must contain the following headers:

x-ttrs-date

Contains the time the request was created. Format of the date value is as specified in RFC1123. (GMT without summertime correction).

For security reasons HTTP requests are valid for only a limited amount of time. The amount of time is set to 15 minutes from the time of creation as specified by the x-ttrs-date HTTP header. If Bluem's system receives a request which is older than 15 minutes or is set in the future, the authorization will fail.

Important: Due to the fact that the value of the **x-ttrs-date** header takes part in the request signature generation, subsequent changes of the **x-ttrs-date** value imply that the request signature must be regenerated. Otherwise, the request will be rejected because of an invalid signature.

Example:

x-ttrs-date: Mon, 30 Sep 2013 09:33:06 GMT

x-ttrs-files-count

Specifies how many files are being sent

Important: Allowed value: 1

Example (EPayment createTransaction):

x-ttrs-files-count: 1

x-ttrs-filename

The header contains information about the file being sent. The format of the filename must be <FileType>-<SenderID>-BSP1-<yyyymmddHHMMssSSS>.xml. For example PTX-S441-BSP1-20171109072514001.xml

Note: SenderID is provided by Bluem per party/account, and has always the format S####. Ask Bluem what your SenderID is. BSP1 is an indicator for Bluem.

Example (EMandate createTransaction):

x-ttrs-filename: TRX-S321-BSP1-20150723105815000.xml

© 2025 Bluem b.v. - All rights reserved.

example Header Request Mandates (other services, likewise):

POST /mr/createTransactionWithToken?token=<yourToken> HTTP/1.1

x-ttrs-date: Tue, 11 Apr 2017 19:32:05 GMT

x-ttrs-files-count: 1

x-ttrs-filename: TRX-S441-BSP1- 20170116100000000.xml

Content-Length: 1727

Content-Type: application/xml;type=TRX;charset=UTF-8

Host: viamijnbank.net

3.2 Request content

The request content SHOULD specify its content-type, type and charset – the XML data must be sent as string with Content-Type "application/xml;**type=xxx**;charset=utf-8" (this needs to be together, not at separate header lines!!).

The value of type can be TRX, PTX, ITX, INX, CTX, CBX, RTX, SRX, PSX or ISX

EPayment **create**Transaction (PTX)

EPayment requestStatus (PSX)

EMandate **create**Transaction (TRX)

EMandate requestStatus (SRX)

IDentity **create**Transaction (ITX)

IDentity requestStatus (ISX)

IBANCheck **create**Transaction (INX)

CRUKSCheck **create**Transaction (CTX)

CCBRCheck **create**Transaction (CBX)

Refund **create**Transaction (RTX)

AddressLookup **create**Transaction (ATX)

AMLComplianceCheck **create**Transaction (ACX)

CIRCheck **create**Transaction (CIX)

Example (EMandate createTransaction):

Content-Type: application/xml; **type=TRX**; charset=utf-8;

3.3 Authentication

Requests are allowed or denied based on the identity of the requestor. The Single URL request method is secured with a token. Bluem creates a token for each sender who is using the token authentication interface. The identity of the requestor is verified based on the combination of the token and the senderID.

© 2025 Bluem b.v. - All rights reserved.

4 Requests

For instruction how to construct the request see Chapter 3.

- **Method**: Only POST requests are allowed for creating new transactions or for getting status requests.
- **Body**: Requests require XML formatted data (see *eServices Interface API*):
- **Service URL**: REST requests use the following URL's to create and retrieve data:
  - **Production**:
    - *Create transaction (ePayment)*:
      https://viamijnbank.net/pr/createTransactionWithToken?token=<accessToken>
    - *Request transaction status (ePayment)*:
      https://viamijnbank.net/pr/requestTransactionStatusWithToken?token=<accessToken>
    - *Create transaction (eMandate)*:
      https://viamijnbank.net/mr/createTransactionWithToken?token=<accessToken>
    - *Request transaction status (eMandate)*:
      https://viamijnbank.net/mr/requestTransactionStatusWithToken?token=<accessToken>
    - *Create transaction (Identity)*:
      https://viamijnbank.net/ir/createTransactionWithToken?token=<accessToken>
    - *Request transaction status (Identity)*:
      https://viamijnbank.net/ir/requestTransactionStatusWithToken?token=<accessToken>
    - *Create transaction (IBANCheck)*:
      https://viamijnbank.net/icr/createTransactionWithToken?token=<accessToken>
    - *Create transaction (CRUKSCheck)*:
      https://viamijnbank.net/ccr/createTransactionWithToken?token=<accessToken>
    - *Create transaction (CCBRCheck)*:
      https://viamijnbank.net/cbr/createTransactionWithToken?token=<accessToken>
    - *Create transaction (Refund)*:
      https://viamijnbank.net/rr/createTransactionWithToken?token=<accessToken>
    - *Create transaction (AddressLookup)*:
      https://viamijnbank.net/ar/createTransactionWithToken?token=<accessToken>
    - *Create transaction (AMLCompliance)*:
      https://viamijnbank.net/acr/createTransactionWithToken?token=<accessToken>
    - *Create transaction (CIRCheck)*
      https://viamijnbank.net/cir/createTransactionWithToken?token=<accessToken>

  - **Test**:
    - *Create transaction (ePayment)*:
      https://test.viamijnbank.net/pr/createTransactionWithToken?token=<accessToken>
    - *Request transaction status (ePayment)*:
      https://test.viamijnbank.net/pr/requestTransactionStatusWithToken?token=<accessToken>
    - *Create transaction (eMandate)*:
      https://test.viamijnbank.net/mr/createTransactionWithToken?token=<accessToken>
    - *Request transaction status (eMandate)*:
      https://test.viamijnbank.net/mr/requestTransactionStatusWithToken?token=<accessToken>
    - *Create transaction (Identity)*:
      https://test.viamijnbank.net/ir/createTransactionWithToken?token=<accessToken>

© 2025 Bluem b.v. - All rights reserved.

- *Request transaction status (Identity)*:
  https://test.viamijnbank.net/ir/requestTransactionStatusWithToken?token=<accessToken>
- *Create transaction (IBANCheck)*:
  https://test.viamijnbank.net/icr/createTransactionWithToken?token=<accessToken>
- *Create transaction (CRUKSCheck)*:
  https://test.viamijnbank.net/ccr/createTransactionWithToken?token=<accessToken>
- *Create transaction (CCBRCheck)*:
  https://test.viamijnbank.net/cbr/createTransactionWithToken?token=<accessToken>
- *Create transaction (Refund)*:
  https://test.viamijnbank.net/rr/createTransactionWithToken?token=<accessToken>
- *Create transaction (AddressLookup)*:
  https://test.viamijnbank.net/ar/createTransactionWithToken?token=<accessToken>
- *Create transaction (AMLCompliance)*:
  https://test.viamijnbank.net/acr/createTransactionWithToken?token=<accessToken>
- *Create transaction (CIRCheck)*
  https://test.viamijnbank.net/cir/createTransactionWithToken?token=<accessToken>

4.1 Types of requests

4.1.1 EPayment createTransaction (PTX)

URL: https://viamijnbank.net/pr/createTransactionWithToken?token=<accessToken>
HTTP Verb: POST
POST Body content: XML: **PaymentTransactionRequest**
Purpose: Create a new payment transaction
Result: **PaymentTransactionResponse** or **PaymentErrorResponse**

4.1.2 EPayment requestStatus (PSX)

URL: https://viamijnbank.net/pr/requestTransactionStatusWithToken?token=<accessToken>
HTTP Verb: POST
POST Body content: XML: **PaymentStatusRequest**
Purpose: Request the status of a payment transaction
Result: **PaymentStatusUpdate** or **PaymentErrorResponse**

4.1.3 EMandate createTransaction (TRX)

URL: https://viamijnbank.net/mr/createTransactionWithToken?token=<accessToken>
HTTP Verb: POST
POST Body content: XML: **EMandateTransactionRequest**
Purpose: Create a new eMandate transaction
Result: **EMandateTransactionResponse** or **EMandateErrorResponse**

4.1.4 EMandate requestStatus (SRX)

URL: https://viamijnbank.net/mr/requestTransactionStatusWithToken?token=<accessToken>

© 2025 Bluem b.v. - All rights reserved.

HTTP Verb: POST

POST Body content: XML: **EMandateStatusRequest**

Purpose: Request the status of an eMandate transaction

Result: **EMandateStatusUpdate** or **EMandateErrorResponse**

4.1.5 IDentity createTransaction (ITX)

URL: https://viamijnbank.net/ir/createTransactionWithToken?token=<accessToken>

HTTP Verb: POST

POST Body content: XML: **IDentityTransactionRequest**

Purpose: Create a new IDentity transaction

Result: **IDentityTransactionResponse** or **IDentityErrorResponse**

4.1.6 IDentity requestStatus (ISX)

URL: https://viamijnbank.net/ir/requestTransactionStatusWithToken?token=<accessToken>

HTTP Verb: POST

POST Body content: XML: **IDentityStatusRequest**

Purpose: Request the status of an IDentity transaction

Result: **IDentityStatusUpdate** or **IDentityErrorResponse**

4.1.7 IBANCheck createTransaction (INX)

URL: https://viamijnbank.net/icr/createTransactionWithToken?token=<accessToken>

HTTP Verb: POST

POST Body content: XML: **IBANCheckTransactionRequest**

Purpose: Create a new IBANCheck transaction

Result: **IBANCheckTransactionResponse** or **IBANCheckErrorResponse**

4.1.8 CRUKSCheck createTransaction (CTX)

URL: https://viamijnbank.net/ccr/createTransactionWithToken?token=<accessToken>

HTTP Verb: POST

POST Body content: XML: **CRUKSCheckTransactionRequest**

Purpose: Create a new CRUKSCheck transaction

Result: **CRUKSCheckTransactionResponse** or **CRUKSCheckErrorResponse**

4.1.9 CCBRCheck createTransaction (CBX)

URL: https://viamijnbank.net/cbr/createTransactionWithToken?token=<accessToken>

HTTP Verb: POST

POST Body content: XML: **CCBRCheckTransactionRequest**

Purpose: Create a new CCBRCheck transaction

Result: **CCBRCheckTransactionResponse** or **CCBRCheckErrorResponse**

© 2025 Bluem b.v. - All rights reserved.

4.1.10 Refund createTransaction (RTX)

URL: https://viamijnbank.net/rr/createTransactionWithToken?token=<accessToken>

HTTP Verb: POST

POST Body content: XML: **RefundTransactionRequest**

Purpose: Create a new Refund transaction

Result: **RefundTransactionResponse** or **RefundErrorResponse**

4.1.11 AddressLookup createTransaction (ATX)

URL: https://viamijnbank.net/ar/createTransactionWithToken?token=<accessToken>

HTTP Verb: POST

POST Body content: XML: **AddressLookupTransactionRequest**

Purpose: Create a new AddressLookup transaction

Result: **AddressLookupTransactionResponse** or **AddressLookupErrorResponse**

4.1.12 AMLCompliance createTransaction (ACX)

URL: https://viamijnbank.net/acr/createTransactionWithToken?token=<accessToken>

HTTP Verb: POST

POST Body content: XML: **AMLComplianceTransactionRequest**

Purpose: Create a new AMLCompliance transaction

Result: **AMLComplianceTransactionResponse** or **AMLComplianceErrorResponse**

4.1.13 CIRCheck createTransaction (CIX)

URL: https://viamijnbank.net/cir/createTransactionWithToken?token=<accessToken>

HTTP Verb: POST

POST Body content: XML: **CIRCheckTransactionRequest**

Purpose: Create a new CIRCheck transaction

Result: **CIRCheckTransactionResponse** or **CIRCheckErrorResponse**

NOTE: For the format of the XML in the request body content or the response see *eServices Interface API of the respective service.*

© 2025 Bluem b.v. - All rights reserved.

5 Responses

Responses consist of two parts: Headers and Body. Body contains the XML Response, as described below:

Response	Content / Status
HTTP 200 OK	XML for: one of: ▪ **PaymentTransactionResponse** ▪ **EMandateTransactionResponse** ▪ **IDentityTransactionResponse** ▪ **IBANCheckTransactionResponse** ▪ **CRUKSCheckTransactionResponse** ▪ **CCBRCheckTransactionResponse** ▪ **RefundTransactionResponse** ▪ **AddressLookupTransactionResponse** ▪ **AMLComplianceTransactionResponse** ▪ **CIRCheckTransactionResponse** ▪ **PaymentStatusUpdate** ▪ **EMandateStatusUpdate** ▪ **IDentityStatusUpdate**
HTTP 400 NOK	XML message with a description of the error - **PaymentErrorResponse** or **EMandateErrorResponse, IDentityErrorResponse** or **IBANCheckErrorResponse** or **CRUKSCheckErrorResponse** or **CCBRCheckErrorResponse or RefundErrorResponse or AddressLookupErrorResponse or AMLComplianceErrorResponse or CIRCheckErrorResponse**
HTTP 401 Unauthorized	Requestor authentication has failed
HTTP 500 Internal Server Error	An unrecoverable error at the server side occurred while processing the request

© 2025 Bluem b.v. - All rights reserved.

6 Important notes

- Before the requestor starts to use the service they MUST be registered within Bluem environment with a senderID.
- Bluem will provide an access token (see Paragraph 3.3) above
- Line separators ARE NOT ALLOWED in HTTP header values. Requests that violate this requirement will be rejected by the Apache Http Server with 400 Bad Request.

  OK:

  x-ttrs-date: Mon, 30 Sep 2013 09:33:06 GMT

  NOT OK:

  x-ttrs-date:

  Mon, 30 Sep 2013 09:33:06 GMT
- Escape the ampersand in the URL for MerchantReturnURL / DebtorReturnURL in the xml file, for example:

  https://returnURL.eu/Update?mandateId=20170105100006&entranceCode=HIO100OIH20170104310246

© 2025 Bluem b.v. - All rights reserved.

7 Examples

Note: Below are examples for eMandates. The examples for payments differ only in the web service URL. **../mr/.. is replaced with ../pr/..** Likewise, for iDIN (Identity) **../mr/.. is replaced with ../ir/..** Likewise, for IBANCheck **../mr/.. is replaced with ../icr/..** Likewise, for CRUKSCheck **../mr/.. is replaced with ../ccr/..** Likewise, for CCBRCheck **../mr/.. is replaced with ../cbr/.. Likewise, for Refund ../mr/.. is replaced with ../rr/… Likewise, for AddressLookup ../mr/.. is replaced with ../ar/… Likewise, for AMLCompliance ../mr/.. is replaced with ../acr/… Likewise, for CIRCheck ../mr/.. is replaced with ../cir/…**

Next the filename starts differently – different interfaceID, for example *TRX* for mandate transaction request is replaced with *PTX* in payment transaction request, with an *ITX* in an Identity transaction, and with an *INX* in an IBANCheck transaction, and with CTX in a CRUKSCheck transaction, and with CBX in a CCBRCheck transaction, and with RTX in a Refund transaction, and with ATX in an AddressLookup transaction, with ACX in a AMLCompliance transaction, and with CIX in a CIRCheck transaction.

7.1 Create transaction request

POST request (EMandate example):

POST /mr/createTransactionWithToken?token=<yourToken> HTTP/1.1
x-ttrs-date: Tue, 11 Apr 2017 19:32:05 GMT
x-ttrs-files-count: 1
x-ttrs-filename: TRX-S441-BSP1- 20170116100000000.xml
Content-Length: 1727
Content-Type: application/xml;type=TRX;charset=UTF-8
Host: viamijnbank.net

NOTE: LOOK AT THOSE REQUEST HEADER EXAMPLE FOR MANDATES!! We need them exactly in this format, all is case sensitive. So chopping Content-Type in 3 lines is not allowed!! Bluem is very strict in checking the Request Header. Of course if you do Payments, or Identity or any other service than Mandates, TRX will be replaced by the appropriated Type. Same counts for SenderID, here your SenderID needs to be.

7.2 Transaction status request

POST request (EMandate example):

*POST /*mr/requestTransactionStatusWithToken*?token=2AF0DDBE-1C14-41B2-1234-0C39671389BA-12345-00016D6BFE88EA5 HTTP/1.1*
x-ttrs-date: Tue, 11 Apr 2017 19:32:05 GMT
x-ttrs-files-count: 1
x-ttrs-filename: SRX-S441-BSP1- 20170116100000000.xml
Content-Length: 1727
Content-Type: application/xml;type=SRX;charset=UTF-8
Host: viamijnbank.net

© 2025 Bluem b.v. - All rights reserved.