

## Lab 9 - Due 3/20

It is rarely the case that a dataset will have a single predictor variable. It is also rarely the case that a response variable will only depend on a single variable. So in this lab, we will extend our current linear model to allow a response to depend on *multiple* predictors. For this Lab we will discuss a dataset with information about cars. This dataset, which can be found at the UCI Machine Learning Repository contains a response variable `mpg` which stores the city fuel efficiency of cars, as well as several predictor variables for the attributes of the vehicles.

```
# read the data from the web
autompg = read.table(
  "http://archive.ics.uci.edu/ml/machine-learning-databases/auto-mpg/auto-mpg.data",
  quote = "\"",
  comment.char = "",
  stringsAsFactors = FALSE)
# give the dataframe headers
colnames(autompg) = c("mpg", "cyl", "disp", "hp", "wt", "acc", "year", "origin", "name")
# remove missing data, which is stored as "?"
autompg = subset(autompg, autompg$hp != "?")
# remove the plymouth reliant, as it causes some issues
autompg = subset(autompg, autompg$name != "plymouth reliant")
# give the dataset row names, based on the engine, year and name
rownames(autompg) = paste(autompg$cyl, "cylinder", autompg$year, autompg$name)
# remove the variable for name, as well as origin
autompg = subset(autompg, select = c("mpg", "cyl", "disp", "hp", "wt", "acc", "year"))
# change horsepower from character to numeric
autompg$hp = as.numeric(autompg$hp)
# check final structure of data
str(autompg)
```

```
## 'data.frame':   390 obs. of  7 variables:
##  $ mpg : num  18 15 18 16 17 15 14 14 14 15 ...
##  $ cyl : int   8  8  8  8  8  8  8  8  8  8 ...
##  $ disp: num  307 350 318 304 302 429 454 440 455 390 ...
##  $ hp  : num  130 165 150 150 140 198 220 215 225 190 ...
##  $ wt  : num  3504 3693 3436 3433 3449 ...
##  $ acc : num   12 11.5 11 12 10.5 10 9 8.5 10 8.5 ...
##  $ year: int   70  70  70  70  70  70  70  70  70  70 ...
```

We will focus on using two variables, `wt` and `year`, as predictor variables. That is, we would like to model the fuel efficiency (`mpg`) of a car as a function of its weight (`wt`) and model year (`year`). To do so, we will define the following linear model,

$$Y_i = \beta_0 + \beta_1 X_{i1} + \beta_2 X_{i2} + \epsilon_i, \quad i = 1, 2, \dots, n$$

where  $\epsilon_i \sim N(0, \sigma^2)$ . In this notation we will define:

- $X_{i1}$  as the weight (`wt`) of the  $i$ th car.
- $X_{i2}$  as the model year (`year`) of the  $i$ th car.

The picture below will visualize what we would like to accomplish. The data points  $(X_{i1}, X_{i2}, Y_i)$  now exist in 3-dimensional space, so instead of fitting a line to the data, we will fit a plane.

```
library("plot3D")

x = autmpg$wt
y = autmpg$year
z = autmpg$mpg

fit <- lm(z ~ x + y)

grid.lines = 25
x.pred = seq(min(x), max(x), length.out = grid.lines)
y.pred = seq(min(y), max(y), length.out = grid.lines)
xy = expand.grid(x = x.pred, y = y.pred)

z.pred = matrix(predict(fit, newdata = xy),
                 nrow = grid.lines, ncol = grid.lines)

fitpoints = predict(fit)

scatter3D(x, y, z, pch = 19, cex = 2, col = gg.col(1000), lighting = TRUE,
          theta = 25, phi = 45, ticktype = "detailed",
          xlab = "wt", ylab = "year", zlab = "mpg", zlim = c(0, 40), clim = c(0, 40),
          surf = list(x = x.pred, y = y.pred, z = z.pred,
                      facets = NA, fit = fitpoints), main = "")
```

