MELON: Multimodal Learning Framework for Spatial Multimodal Omics Data Integration

Anonymous Author(s)
Affiliation
Address
email

Abstract

Recent advances in spatial omics technologies enable multiple molecular modalities to be measured on the same tissue section, providing complementary measurements of tissue organization. A central challenge is to integrate heterogeneous modalities, such as gene expression and chromatin accessibility, while preserving spatial structure and biological coherence. Here, we propose MELON, a representation-learning framework for spatial multi-omics integration that combines spatially aware graph attention with contrastive learning to learn shared spot-level embeddings for spatial domain detection. MELON uses modality-specific encoders together with a k-nearest-neighbor spatial graph, where learned edge gating and multi-head attention selectively aggregate information from informative spatial neighbors. Stochastic augmentations and a contrastive objective are then used to align modality-specific embeddings into a common latent space, which is subsequently clustered and compared against anatomical reference annotations. We evaluate MELON on three spatial multi-omics datasets using metrics including adjusted Rand index (ARI), spatial ARI, normalized mutual information (NMI), adjusted mutual information (AMI), V-measure, and homogeneity, and benchmark against established integration methods. Across datasets, MELON achieves consistently higher agreement with reference labels, yielding relative ARI gains over the best competing baseline of roughly 32% on an E15 mouse brain dataset, 19% on a human lymph node dataset, and 11% on an E13 mouse embryo dataset. On the MISAR-seq E15 mouse brain dataset, MELON produces more spatially contiguous domains with sharper boundaries that better align with anatomical structures than competing baselines. These results demonstrate that MELON effectively leverages spatial multi-omic signals to enable accurate and interpretable tissue domain characterization.

1 Introduction

Multimodal spatial omics technologies represent a paradigm shift in understanding complex biological systems. They integrate diverse molecular and morphological modalities from the same tissue section while preserving the spatial layout of the tissue, enabling the study of cellular identity, regulatory state, and microenvironmental organization in situ. Representative spatial multi-omics settings now include transcriptome–proteome measurements in lymphoid tissue, transcriptome–epigenome assays such as spatial ATAC–RNA-seq, and transcriptome–histology integration settings that combine molecular profiles with tissue morphology Long et al. [2024], Zhang et al. [2023], Zuo et al. [2023], Coleman et al. [2025]. A key analysis task is spatial clustering or spatial domain identification, which aims to group spatial locations into biologically meaningful regions or cell-state neighborhoods. This task can be naturally framed as a multi-modality representation learning problem. Each modality provides a distinct layer of biological insight, for example, gene expression captures transcriptional output, while a paired modality such as chromatin accessibility, protein abundance, or hematoxylin and

Submitted to 40th Conference on Neural Information Processing Systems (NeurIPS 2026). Do not distribute.

eosin (H&E)-stained histology image captures complementary regulatory, phenotypic, or structural information. Effectively integrating these heterogeneous modalities is therefore central to producing biologically meaningful clusters.

Early attempts at multimodal clustering primarily relied on unsupervised methods developed for non-spatial multimodal data, such as Seurat WNN, MOFA+, and TotalVI Hao et al. [2021], Argelaguet et al. [2020], Gayoso et al. [2021], and then applied them to paired profiles while ignoring spatial dependencies between locations. Seurat WNN learns cell-specific modality weights and multimodal neighbor graphs for integrative analysis, MOFA+ uses a latent factor model to reconstruct a shared low-dimensional representation across multiple modalities, and TotalVI uses a variational probabilistic model to jointly analyze paired RNA and protein measurements. These methods are effective for multimodal integration in single-cell settings, but they do not explicitly model the spatial organization that is intrinsic to tissue slices. MEFISTO extends factor analysis to incorporate known spatial or temporal covariates and separate smooth from non-smooth variation Velten et al. [2022], partially addressing this limitation, but it remains fundamentally a low-rank factor model rather than a dedicated spatial multimodal clustering framework.

More recently, graph-based and deep multimodal models have become the dominant paradigm for spatial multiomics analysis because they can jointly encode neighborhood structure and heterogeneous molecular modalities in a learned latent space. For example, SpatialGlue constructs spatial neighbor graphs and uses attention-based fusion to integrate modality-specific embeddings for spatial domain identification Long et al. [2024]. Building on this direction, MultiGATE uses a two-level graph attention autoencoder that combines cross-modality feature relationships with spatial context, enabling both spatial embedding and cross-modality regulatory inference Miao et al. [2025]. In a related but broader multimodal integration setting, MISO proposes a deep framework for combining spatial molecular measurements with H&E-derived morphological information Coleman et al. [2025]. Across diverse datasets and platforms, these deep integration models have consistently achieved strong clustering or spatial reconstruction performance, highlighting the effectiveness of learning multimodal embeddings over spatial graphs or spatially informed architectures.

However, existing spatial multimodal clustering methods mainly optimize for a shared latent representation under spatial smoothness priors, but often fail to preserve modality-specific and cross-modal synergistic signals. In spatial multi-omics, this is a substantial limitation: spots with similar transcriptomes can differ in chromatin accessibility, protein abundance, or tissue morphology, reflecting distinct regulatory programs, signaling states, or microenvironmental contexts. For example, accessible enhancers may indicate lineage priming before RNA changes are detectable, protein levels may reflect post-transcriptional regulation not captured by gene expression, and histology may reveal stromal or immune tissue structure only weakly correlated with molecular profiles. As a result, methods that prioritize consensus structure can collapse biologically distinct spots into the same cluster. In previous methods, most existing objectives are based on alignment, reconstruction, or shared embedding and therefore emphasize redundant information, and modality interactions in tissue are often spatially dependent, becoming informative only in the context of local cellular neighborhoods.

To address this problem, we propose MELON (Multi-modal lEarning framework for spatial muLti-Omics integratioN), a spatially aware framework for clustering paired multimodal spatial data while preserving shared, modality-specific, and importantly, synergistic information. MELON first applies modality-specific encoders to each molecular or imaging modality, allowing each modality to retain its own structure and noise characteristics. It then uses a neighborhood-aware graph attention module to encode local tissue organization and learn which neighboring spots are most informative for each location. These embeddings are projected into a common latent space and fused with a transformer that models higher-order nonlinear dependencies across modalities. To reduce spurious neighborhood effects, MELON injects learned spatial attention weights as an adaptive bias into the fusion process. Finally, it uses a partial information decomposition (PID)-guided Williams and Beer [2010], Bertschinger et al. [2014] multi-modality contrastive objective (built on multi-modality contrastive learning Tian et al. [2020a] and the modality-masked PID-aware loss of Dufumier et al. [2024]) over unimodal and multimodal masked inputs to encourage the learned representation to retain redundant, unique, and synergistic signal rather than collapsing to what the modalities share. This provides embeddings that preserve shared, modality-specific, and synergistic information, better resolve spatial regions supported by complementary signals across modalities. Figure 1 summarizes the spatial multi-omics task, MELON's spatial interaction and PID-guided fusion modules, and example downstream applications.




Figure 1: Overview of MELON. (a) Spatial multi-omics task: paired modality measurements (e.g., gene expression with chromatin accessibility or protein) on a tissue section, together with 2D spatial coordinates. (b) Spatial interaction: NeighborhoodGAT learns within-spot and cross-spot attention to encode local tissue organization and produce a learned spatial attention bias. (c) Learning PID information: a fusion transformer combined with a PID-guided multi-modality contrastive objective preserves shared, modality-specific, and synergistic signals across modalities. (d) Examples of downstream applications, including spatial domain clustering, visualization, and marker/feature analysis.

We evaluate MELON on paired spatial multimodal datasets spanning molecular–molecular and molecular–image settings, measuring clustering accuracy, spatial coherence, robustness across modality combinations, and biological interpretability. Our contributions are:

- We formulate spatial multi-omics integration as a spatially aware multimodal representation learning problem that requires preserving shared, modality-specific, and synergistic cross-modal information.
- We propose MELON, which injects a learned neighborhood-aware spatial bias directly into multimodal fusion-transformer attention, and prove that this spatially biased variant inherits the PID recovery guarantee of prior PID-aware contrastive objectives.
- On controlled simulations isolating cross-modal synergy, MELON recovers a synergy-only label where all multimodal baselines operate at chance level, empirically confirming the preservation of synergistic information.
- On real spatial multi-omics data, MELON produces more accurate, spatially coherent, and biologically interpretable spot embeddings than strong multimodal baselines across molecular–molecular and molecular–protein settings.

2 Related Work

This section summarizes recent related works from three aspects: (1) spatial multi-omics integration, (2) contrastive representation learning (InfoNCE, SimCLR, CLIP, and PID-guided variants), and (3) spatial inductive biases for spatially resolved transcriptomics. Please refer to Appendix A for a more detailed discussion.

3 Methods

We present MELON, a spatial multimodal framework for learning spot embeddings from paired molecular profiles and spatial coordinates. MELON encodes each modality with a separate encoder, computes a learned spatial bias with NeighborhoodGAT, fuses the resulting tokens with a transformer that takes the spatial bias as an additive attention term, and trains the resulting embeddings with a multi-modality contrastive objective adapted from Dufumier et al. [2024]. Our methodological contribution over standard multi-modality contrastive learning is a learned NeighborhoodGAT spatial

bias that is injected directly into the fusion-transformer attention, making the spot embedding spatially aware rather than spatially blind. Figure 2 shows the framework overview; preprocessing, augmentation formulas, token layouts, and architectural details are deferred to Appendix C.




Figure 2: Overview of the MELON framework. The end-to-end pipeline takes paired spatial multimodal inputs through augmentation, modality-specific encoding, spatially biased fusion with NeighborhoodGAT, and PID-guided contrastive training to produce spot embeddings for clustering.

3.1 Problem Formulation

We consider N spatial spots, each observed with n aligned modalities and a 2D coordinate. Spot i is represented by per-modality feature vectors $x_i^{(m)} \in \mathbb{R}^{d_m}$ for $m = 1, \ldots, n$ and a coordinate $s_i \in \mathbb{R}^2$, giving matrices $X^{(m)} \in \mathbb{R}^{N \times d_m}$ and $S \in \mathbb{R}^{N \times 2}$. We write the full input as $X = \big(X^{(1)}, \ldots, X^{(n)}, S\big)$. The framework is modality-agnostic: each $X^{(m)}$ can be a count matrix, a continuous feature matrix, or a low-rank reduction of either, and the same architecture applies for any $n \geq 2$ (we instantiate $n = 2$ in our experiments). The goal is to learn spot embeddings $\big(x_i^{(1)}, \ldots, x_i^{(n)}, s_i\big) \mapsto z_i \in \mathbb{R}^d$ that support spatial domain clustering while preserving shared, modality-specific, and synergistic cross-modal information.

3.2 Multimodal Augmentations and Masked Embeddings

Following standard contrastive self-supervised practice Chen et al. [2020], Tian et al. [2020a], for each batch we draw two label-preserving augmentations $t_1, t_2 \sim \mathcal{T}$ and form two augmented multimodal inputs

$$X' = t_1(X), \qquad X'' = t_2(X). \tag{1}$$

The augmentation family $\mathcal{T}$ is chosen per assay rather than fixed by the architecture; the concrete instantiations used in our experiments (e.g. Gaussian noise on continuous features, Bernoulli dropout on sparse binary features, aligned cross-spot mixing) are described in Appendix C.1. Each augmented input is then passed through the shared backbone under $n + 1$ different modality masks: n *single-modality* masks $\mathcal{M}^{[m]}$ that keep only modality m and replace every other modality slot with a learned [MSK] token, and one *joint* mask $\mathcal{M}^{[\star]}$ that keeps all modalities. We denote the resulting embeddings as

$$z'^{[k]} = f_\theta(X', \mathcal{M}^{[k]}), \qquad z''^{[k]} = f_\theta(X'', \mathcal{M}^{[k]}), \qquad k \in \{1, \ldots, n, \star\}, \tag{2}$$

giving $2(n + 1)$ embeddings per spot in total. The n single-modality embeddings probe what each modality contributes in isolation; the joint embedding $z^{[\star]}$ serves as the *joint embedding* that all single-modality embeddings are aligned against in the contrastive loss of §3.6.

3.3 Modality Specific Encoders

Each modality m is first mapped by a dedicated encoder f_m to an intermediate hidden-feature tensor $H^{(m)}$ in its native feature space, and then projected by a lightweight converter ϕ_m to a per-modality token tensor $T^{(m)}$ in a shared d-dimensional token space:

$$H^{(m)} = f_m(X^{(m)}) \in \mathbb{R}^{N \times L_m \times d_e}, \qquad T^{(m)} = \phi_m(H^{(m)}) \in \mathbb{R}^{N \times L'_m \times d}, \quad m \in \{1, \ldots, n\}. \tag{3}$$

Here N is the number of spots, L_m and L'_m are modality-specific token-sequence lengths (equal to 1 under the spot-level tokenisation of Appendix C.2), d_e is the encoder's native hidden width, and d is the shared token width used by the fusion transformer. The same encoders are shared across both augmentations and all $n+1$ modality masks (a total of $2(n+1)$ training embeddings per spot). Separate encoders preserve modality-specific structure, while the converters ϕ_m align all modalities into a common token space of dimension d for downstream fusion. Default architectures and tokenization details are given in Appendix C.2.

3.4 Neighborhood-Aware Graph Attention Network

To encode local tissue structure, we construct a spatial k-nearest-neighbor graph from the 2D coordinates $\{s_i\}_{i=1}^N$ and use a graph-attention-style module Veličković et al. [2018] to produce a learned spatial attention bias. Crucially, NeighborhoodGAT takes only the spatial coordinates as input: we map each spot coordinate to a positional embedding with a learned encoder $\psi : \mathbb{R}^2 \to \mathbb{R}^{d_u}$,

$$u_i = \psi(s_i) \in \mathbb{R}^{d_u}, \qquad U = [u_1, \ldots, u_N]^\top \in \mathbb{R}^{N \times d_u}, \tag{4}$$

and restrict attention to edges of the k-NN graph through a binary neighborhood mask $M \in \{0,1\}^{N \times N}$. Because u_i depends only on s_i, the resulting bias B is a deterministic function of the spatial coordinates S alone (and not of the per-modality features $X^{(m)}$); this is the property used in the PID-inheritance proof of Appendix D. For each of the n_h attention heads we first project u_i into the per-head space,

$$h_i^{(h)} = W^{(h)} u_i \in \mathbb{R}^{d_h}, \qquad h \in \{1, \ldots, n_h\}, \tag{5}$$

with learned projection matrices $W^{(h)} \in \mathbb{R}^{d_h \times d_u}$. The edge logit for head h decomposes into additive source- and destination-side scores via learned vectors $a_{\text{src}}^{(h)}, a_{\text{dst}}^{(h)} \in \mathbb{R}^{d_h}$:

$$\alpha_{ij}^{(h)} = \text{LeakyReLU}\Big(a_{\text{src}}^{(h)\top} h_i^{(h)} + a_{\text{dst}}^{(h)\top} h_j^{(h)} \Big), \tag{6}$$

with neighborhood-normalized weights

$$w_{ij}^{(h)} = \frac{\exp(\alpha_{ij}^{(h)})}{\sum_{j' :\, M_{ij'}=1} \exp(\alpha_{ij'}^{(h)})}, \tag{7}$$

and define the spatial bias by averaging over the n_h attention heads ($h \in \{1, \ldots, n_h\}$) and moving to log-space:

$$w_{ij} = \frac{1}{n_h} \sum_{h=1}^{n_h} w_{ij}^{(h)}, \qquad B_{ij} = \log(w_{ij} + \varepsilon), \tag{8}$$

where $\varepsilon > 0$ is for numerical stability. The resulting matrix $B \in \mathbb{R}^{N \times N}$ captures spatial neighborhood structure derived purely from the coordinates S, and is injected into the fusion transformer. Bias tiling and masked-embedding subsetting are described in Appendix C.3.

3.5 Fusion Transformer

Given the per-modality tokens and the spatial bias B, the fusion module stacks per-modality, per-spot tokens from all N spots in the batch into a single token sequence,

$$T = \text{concat}\big(T^{(1)}, T^{(2)}, \ldots, T^{(n)}\big) \in \mathbb{R}^{nN \times d}, \tag{9}$$

where each $T^{(m)} \in \mathbb{R}^{N \times d}$ contributes one token per spot. Transformer attention Vaswani et al. [2017] then runs jointly across all nN spot–modality tokens, with the spot-level bias B from NeighborhoodGAT tiled into the $n \times n$ modality blocks of an $nN \times nN$ matrix B_{spatial} (Appendix C.3), so the same spot-level bias governs both within-modality and cross-modal attention. Adding a learned or geometry-derived bias to the attention logits follows the attention-bias paradigm used by ALiBi Press et al. [2022] and T5/Shaw-style relative position biases Raffel et al. [2020], Shaw et al. [2018]; here the bias is derived from the spatial k-NN graph via NeighborhoodGAT rather than from token indices:

$$\text{Attn}(Q, K, V) = \text{softmax}\left(\frac{QK^\top}{\sqrt{d_k}} + B_{\text{spatial}} \right) V. \tag{10}$$

After fusion, the output tokens $\tilde{T} = F_\theta(T;\, B_{\text{spatial}})$ are reshaped back to modality-by-spot blocks and averaged across modalities to recover one embedding per spot:

$$z_i = \frac{1}{n} \sum_{m=1}^{n} \tilde{T}_i^{(m)}. \tag{11}$$

We evaluate this fusion block under $n + 1$ modality masks: n single-modality masks, where only modality m is kept and all others are replaced by the mask token (yielding embeddings $Z^{[m]}$ for $m = 1, \ldots, n$), and the joint multimodal mask (yielding Z). Exact token layouts and recovery operations are deferred to Appendix C.2 and Appendix C.3.

3.6 PID-Guided Contrastive Learning

We train MELON with a multi-modality contrastive objective whose components target the four terms of the partial information decomposition (PID) of Williams and Beer [2010], Bertschinger et al. [2014]: redundancy (R), modality-specific uniqueness (U_m), and synergy (S). The objective itself follows the multi-modality contrastive paradigm of Tian et al. [2020a] extended to the modality-masked, PID-aware decomposition introduced by Dufumier et al. [2024]; we instantiate it on the per-modality token streams produced by our spatially biased fusion transformer. Given two batches of normalized embeddings $Z, Z' \in \mathbb{R}^{N \times d}$, with rows (z_i, z'_i) forming positive pairs, we use the InfoNCE estimator van den Oord et al. [2018]

$$\widehat{I}_{\text{NCE}}(Z, Z') = \mathbb{E}_{(z, z'_{\text{pos}})} \mathbb{E}_{z'_{\text{neg}}} \left[\log \frac{\exp(\text{sim}(z, z'_{\text{pos}})/\tau)}{\sum_{z'_{\text{neg}}} \exp(\text{sim}(z, z'_{\text{neg}})/\tau)} \right], \tag{12}$$

where $\text{sim}(\cdot, \cdot)$ is the cosine similarity and $\tau > 0$ is a temperature. Expectations are approximated with in-batch positives and negatives.

Recall from §3.2 that for each spot we have $2(n + 1)$ embeddings: a joint multimodal embedding $z^{[\star]}$ and n single-modality embeddings $z^{[m]}$, each computed under both augmentations $A = t_1(X)$ and $B = t_2(X)$. We denote the corresponding batch matrices by $Z'^{[k]}$ and $Z''^{[k]}$ for $k \in \{1, \ldots, n, \star\}$.

For each mask k, the per-mask loss pairs the mask-k embedding under one augmentation against the joint embedding under the *other* augmentation, in a symmetrised form:

$$\mathcal{L}_k \;=\; -\frac{1}{2}\Big(\widehat{I}_{\text{NCE}}\big(Z'^{[k]},\, Z''^{[\star]}\big) \;+\; \widehat{I}_{\text{NCE}}\big(Z''^{[k]},\, Z'^{[\star]}\big)\Big). \tag{13}$$

The cross-augmentation pairing (anchor from A, joint embedding from B, and vice versa) prevents the same augmentation from appearing on both sides of an InfoNCE term. The total MELON loss averages over all $n + 1$ masks, including the joint mask itself, which acts as a self-consistency term for the joint embedding:

$$\mathcal{L}_{\text{MELON}} \;=\; \frac{1}{n+1}\Big(\mathcal{L}_\star \;+\; \sum_{m=1}^{n} \mathcal{L}_m\Big). \tag{14}$$

Concretely, $\mathcal{L}_\star$ aligns the joint embedding under both augmentations with each other (encouraging augmentation invariance of the multimodal representation), while each $\mathcal{L}_m$ aligns the modality-m-only embedding with the joint embedding (encouraging the joint embedding to remain consistent with what each modality contributes in isolation). For $n = 2$ this reduces to a three-term objective $\mathcal{L} = \frac{1}{3}(\mathcal{L}_{m_1} + \mathcal{L}_{m_2} + \mathcal{L}_\star)$, with augmentations applied symmetrically to both the modality-masked and the joint branches and the per-mask terms explicitly symmetrised over the augmentation roles. Combined with the spatially biased fusion transformer of §3.5, this objective encourages the learned embedding to be invariant to nuisance variation while preserving shared, modality-specific, and synergistic cross-modal structure. We show in Appendix D that this objective inherits the PID recovery guarantee of Dufumier et al. [2024].

4 Experiments

4.1 Experimental Setting

This section introduces the details of the experiment setting from four aspects: datasets, implementation details, compared baselines, and evaluation metrics. Table 1 gives a compact summary of

the three datasets used in the main benchmark; fuller descriptions including platform protocols, accession identifiers, and preprocessing recipes are provided in Appendix B. MELON is implemented in PyTorch with Adam ($\mathrm{lr} = 10^{-3}$, weight decay 10^{-5}), contrastive temperature τ=0.1, embedding dimension D=128, k-nearest-neighbor graph with k=16, batch size 2,048 and 100 epochs; the full numerical hyperparameter list and augmentation schedule are in Appendix C.4, and the architectural details of preprocessing, tokenization, spatial bias tiling, and modality masking are in Appendix C. We compare MELON against five established spatial multi-omics integration methods (Seurat WNN, MOFA+, TotalVI, SpatialGlue, MEFISTO) plus two recent multimodal baselines (MISO, MultiGate); each baseline's design and assumptions are summarised in Appendix E.1. Performance is evaluated under five clustering quality metrics in the main text (ARI, NMI, AMI, homogeneity, V-measure), with spatial ARI (spARI) and raw mutual information (MI) additionally reported in the appendix benchmarks; all seven metrics are formally defined in Appendix E.2.

Table 1: Summary of datasets used in the main experiments. For ATAC modalities, raw peaks are reduced before modeling as described in Appendix B.

Dataset	Modalities	#Spots	Annotation
Mouse E15.5 Brain	RNA + ATAC	1,949	atlas-aligned brain regions
Human Lymph Node	RNA + ADT	3,484	expert-curated tissue compartments
Mouse E13 Embryo	RNA + ATAC	2,187	embryo region annotations

4.2 Simulation

Real-data clustering metrics (ARI, NMI) cannot isolate *why* a multimodal model succeeds: a method that only captures shared structure can match a method that additionally captures cross-modal synergy, because both shared and synergistic signals produce spatially coherent domains. To disentangle these effects we ablate MELON on a controlled simulation in which the evaluation target is a *synergy-only* label Y, constructed so that it is unrecoverable from either modality alone or from spatial location alone.

Simulation setup. We simulate N=1,936 spots on a 44×44 grid with Modality 1 and Modality 2 feature vectors $\mathbf{x}_i^{(1)}, \mathbf{x}_i^{(2)} \in \mathbb{R}^{600}$. Each modality carries shared region structure $R \in \{1, \ldots, 5\}$, a modality-specific attribute ($U_i \in \{1, \ldots, 10\}$ for M1, $C_i \in \{1, \ldots, 10\}$ for M2), and nuisance blocks. A fixed random permutation $\pi : \{1, \ldots, 10\} \to \{1, \ldots, 10\}$ binds the two modality-specific attributes, and the binary synergy label is

$$Y_i \sim \mathrm{Bernoulli}(p_i), \qquad p_i = \begin{cases} 0.90 & \text{if } C_i = \pi(U_i), \\ 0.01 & \text{otherwise.} \end{cases} \tag{15}$$

By construction Y requires joint knowledge of both modalities and is unrecoverable from either alone or from spatial location. We evaluate each method by *linear probing*: freeze its learned embedding and train a lightweight classifier (LogReg, Lin. SVM, or MLP) to predict Y with 5-fold CV, reporting the best probe per method. Data generation, validation of the simulator (block recoverability, single-modality lower bound, spatial-leakage test), and all hyperparameters are in Appendix F.

Method comparison on synergy. Table 2 compares MELON against simple baselines and six external multi-omics methods. MELON reaches BalAcc $= 0.818 \pm 0.045$ and AUROC $= 0.955 \pm 0.021$, while the best simple baseline (raw M1+M2 MLP) reaches 0.580 and the best external method (MOFA+) reaches 0.540. Every external method recovers shared structure (R, U, C; Appendix F.5) but fails on Y (BalAcc ≈ 0.50), indicating that their objectives capture spatial and modality-specific signal without encoding cross-modal correspondence. This is the gap that PID-guided fusion is designed to close.

Component ablation. We next ablate four axes of MELON on the same synergy target: modality input, fusion block, spatial context, and data augmentation (Table 3). Removing the transformer fusion block drops BalAcc from 0.818 to 0.547 (-0.271), showing that simply providing both modalities is insufficient—the cross-modal fusion layer is what enables synergy recovery. Removing

Table 2: Method comparison on synergy label Y (simulation; 5-fold CV, best probe per method). MELON variants use the fused embedding.

Method	Probe	BalAcc	Macro-F1	AUROC
M1 only (raw)	MLP	0.504 ± 0.006	0.487 ± 0.014	0.533 ± 0.076
M2 only (raw)	RF	0.500 ± 0.000	0.477 ± 0.000	0.546 ± 0.041
M1+M2 (raw)	MLP	0.580 ± 0.058	0.608 ± 0.078	0.878 ± 0.065
Space-only	LogReg	0.502 ± 0.020	0.498 ± 0.014	0.517 ± 0.038
PCA concat	MLP	0.502 ± 0.006	0.482 ± 0.012	0.543 ± 0.034
MOFA+	Lin. SVM	0.540 ± 0.022	0.426 ± 0.019	0.550 ± 0.048
MEFISTO	Lin. SVM	0.540 ± 0.027	0.421 ± 0.018	0.537 ± 0.036
SpatialGLUE	Lin. SVM	0.532 ± 0.027	0.457 ± 0.008	0.526 ± 0.044
MISO	Lin. SVM	0.525 ± 0.048	0.442 ± 0.020	0.541 ± 0.065
Seurat WNN	Lin. SVM	0.520 ± 0.051	0.403 ± 0.010	0.531 ± 0.067
TotalVI	Lin. SVM	0.504 ± 0.047	0.433 ± 0.018	0.518 ± 0.070
MELON no-space	Lin. SVM	0.554 ± 0.018	0.504 ± 0.011	0.576 ± 0.034
MELON full	**MLP**	$\mathbf{0.818 \pm 0.045}$	$\mathbf{0.854 \pm 0.034}$	$\mathbf{0.955 \pm 0.021}$


the neighborhood-aware spatial bias drops BalAcc to 0.554 (-0.264), even though spatial coordinates alone carry no information about Y (Appendix F.6); this indicates that spatial conditioning stabilizes the cross-modal representation rather than leaking positional shortcuts. Disabling augmentation reduces BalAcc to 0.711 (-0.107). Restricting the encoder to a single modality collapses performance to chance (M1-only 0.532; M2-only 0.509), confirming that the synergy signal cannot be shortcut through either assay. Together, fusion, spatial bias, and augmentation are each individually necessary; removing any one collapses synergy recovery while shared-structure metrics on real data would remain largely unaffected, illustrating why ARI/NMI alone cannot validate these components.

Table 3: Ablation on synergy label Y (simulation; best probe per variant, 5-fold CV). Full seven-variant table with Macro-F1 is given in Appendix F.7.


Variant	BalAcc	Δ BalAcc	AUROC
MELON full	$\mathbf{0.818 \pm 0.045}$	—	$\mathbf{0.955 \pm 0.021}$
− augmentation	0.711 ± 0.069	-0.107	0.906 ± 0.047
− fusion	0.547 ± 0.030	-0.271	0.573 ± 0.028
− spatial	0.554 ± 0.018	-0.264	0.576 ± 0.034
− spatial, − aug	0.516 ± 0.030	-0.302	0.542 ± 0.052
M1-only	0.532 ± 0.038	-0.286	0.511 ± 0.053
M2-only	0.509 ± 0.031	-0.309	0.524 ± 0.027

4.3 Main Performance

We evaluate MELON on three paired spatial multimodal datasets covering both molecular–molecular and molecular–protein settings, and compare against seven strong baselines (Seurat, SpatialGlue, TotalVI, MOFA+, MEFISTO, MISO, MultiGate). The benchmarks are (i) a *Mouse E15.5 brain* sagittal cryosection profiled with MISAR-seq (MISAR-seq) for paired RNA–ATAC, with anatomy spanning DPallm/DPallv, midbrain, hindbrain, thalamus, diencephalon, subpallium, cartilage, muscle, skull, mesenchyme, and cerebellar vermis (Fig. 3a); (ii) a *Human lymph node* 10x Visium RNA–ADT co-profile ($3{,}484$ spots; $18{,}085$ genes; 31 proteins) annotated for lymphoid follicles, paracortex/T-cell zone, medulla, and capsule (Appendix Fig. 4a); and (iii) a *Mouse E13 embryo* whole-section RNA–ATAC profile ($2{,}187$ spots; $17{,}058$ genes; $24{,}017$ ATAC peaks) annotated for 14 regions covering neural tissues (forebrain, midbrain, hindbrain/spinal cord, periventricular neuroepithelium), mesenchyme (paraxial, head, dorsal, trunk), surface ectoderm, ventral and caudal trunk, gut/ventral endoderm, eye, and visceral organ primordia (Appendix Fig. 5a). We score each method's spatial domains against the curated annotations using ARI, NMI, AMI, Homogeneity, V-Measure, FMI, Jaccard, Purity, the spatial-aware SpRI/SpARI, and the Calinski–Harabasz index (CHI).



(a) H&E image, ground-truth annotation, and spatial domain assignments from all eight benchmarked methods (ARI labelled per panel; methods ordered consistently across datasets).



(b) Clustering metrics (ARI, NMI, Homogeneity, V-Measure, AMI) across all eight methods at $k = 12$.

Figure 3: Mouse E15.5 brain results. (a) H&E tissue image, ground-truth annotation, and spatial domain assignments from MELON and seven multimodal baselines (per-panel ARI). (b) Five clustering metrics across all eight methods. Benchmark-over-k curves are provided in Appendix 6.

Performance across datasets and metrics. Aggregating across the swept cluster numbers k (median $\pm$ IQR; Table 4), MELON attains the best median on *all 11 metrics* for the Mouse E15.5 brain (e.g., ARI 0.480 ± 0.022 vs. next-best MultiGate 0.344 ± 0.025); on *9 of 11* for the Human lymph node (ARI 0.298 ± 0.028 vs. MISO 0.241 ± 0.046, with SpatialGlue narrowly leading homogeneity and MISO leading FMI); and on *10 of 11* for the Mouse E13 embryo (ARI 0.385 ± 0.007 vs. SpatialGlue 0.280 ± 0.014, with Seurat winning only the internal-compactness CHI). Visually, MELON produces sharper anatomical boundaries and reduced cross-region mixing than every baseline—most clearly at the DPallm/DPallv, subpallium/thalamus, and midbrain/hindbrain interfaces in the brain (Fig. 3a), the follicle/T-cell-zone and medulla/capsule interfaces in the lymph node (Appendix Fig. 4a), and the neural/mesenchymal contacts in the embryo (Appendix Fig. 5a).

Robustness across k and clustering backend. MELON's lead is stable across the swept cluster numbers: the per-method metric-versus-k curves in Appendix Figs. 6, 7, and 8 keep MELON at or near the top across the full k range, with tighter IQR than every multimodal baseline. On the lymph node we further verified that swapping the downstream clustering backend on the frozen MELON embedding (GMM, Leiden, Louvain, Spectral, Walktrap) preserves the lead, and on the embryo we swept the spatial-graph neighborhood $k_{\mathrm{nn}} \in [4, 11]$ with MELON remaining the top-performing approach throughout (Appendix E).

Table 4: Clustering metrics across the three benchmarked datasets, aggregated across cluster numbers k (median $\pm$ IQR; $k \in \{6, 8, 10, 12, 14\}$ for Mouse E15.5 Brain and Human Lymph Node, $k \in \{10, 12, 14, 16, 18\}$ for Mouse E13 Embryo). Best median per (dataset, metric) in **bold**. SpRI/SpARI: spatial Rand / adjusted Rand index; FMI: Fowlkes–Mallows; CHI: Calinski–Harabasz.

Dataset	Method	ARI	NMI	AMI	Homog.	V-Meas.	SpRI	SpARI	FMI	Jaccard	CHI	Purity
Mouse E15.5 Brain	**MELON**	$\mathbf{0.480 \pm 0.022}$	$\mathbf{0.569 \pm 0.005}$	$\mathbf{0.561 \pm 0.006}$	$\mathbf{0.532 \pm 0.028}$	$\mathbf{0.569 \pm 0.005}$	$\mathbf{0.933 \pm 0.003}$	$\mathbf{0.532 \pm 0.030}$	$\mathbf{0.567 \pm 0.016}$	$\mathbf{0.384 \pm 0.016}$	$\mathbf{8927 \pm 2007}$	$\mathbf{0.678 \pm 0.032}$
	MISO	0.216 ± 0.011	0.372 ± 0.027	0.364 ± 0.026	0.355 ± 0.046	0.372 ± 0.027	0.888 ± 0.004	0.176 ± 0.014	0.324 ± 0.007	0.193 ± 0.003	156 ± 28	0.485 ± 0.034
	Seurat	0.291 ± 0.017	0.483 ± 0.007	0.475 ± 0.010	0.491 ± 0.041	0.483 ± 0.007	0.905 ± 0.003	0.224 ± 0.026	0.376 ± 0.016	0.226 ± 0.008	3056 ± 373	0.560 ± 0.041
	SpatialGlue	0.285 ± 0.024	0.515 ± 0.019	0.508 ± 0.016	0.524 ± 0.063	0.515 ± 0.019	0.904 ± 0.006	0.249 ± 0.021	0.381 ± 0.026	0.235 ± 0.024	212 ± 17	0.625 ± 0.055
	MultiGate	0.344 ± 0.025	0.515 ± 0.006	0.508 ± 0.004	0.516 ± 0.050	0.515 ± 0.006	0.912 ± 0.001	0.321 ± 0.110	0.425 ± 0.061	0.270 ± 0.038	420 ± 60	0.596 ± 0.027
	TotalVI	0.086 ± 0.019	0.212 ± 0.059	0.200 ± 0.056	0.199 ± 0.068	0.212 ± 0.059	0.860 ± 0.011	0.001 ± 0.014	0.211 ± 0.001	0.117 ± 0.002	409 ± 101	0.372 ± 0.051
	MOFA+	0.130 ± 0.018	0.300 ± 0.017	0.289 ± 0.014	0.273 ± 0.033	0.300 ± 0.017	0.869 ± 0.006	0.085 ± 0.021	0.265 ± 0.024	0.152 ± 0.013	631 ± 13	0.436 ± 0.021
	MEFISTO	0.151 ± 0.009	0.301 ± 0.018	0.292 ± 0.017	0.281 ± 0.031	0.301 ± 0.018	0.873 ± 0.004	0.087 ± 0.018	0.269 ± 0.019	0.155 ± 0.009	530 ± 29	0.443 ± 0.021
Human Lymph Node	**MELON**	$\mathbf{0.298 \pm 0.028}$	$\mathbf{0.379 \pm 0.002}$	$\mathbf{0.374 \pm 0.001}$	0.401 ± 0.033	$\mathbf{0.379 \pm 0.002}$	$\mathbf{0.858 \pm 0.004}$	$\mathbf{0.307 \pm 0.038}$	0.454 ± 0.018	$\mathbf{0.293 \pm 0.015}$	$\mathbf{7265 \pm 576}$	$\mathbf{0.643 \pm 0.009}$
	MISO	0.241 ± 0.046	0.305 ± 0.035	0.301 ± 0.032	0.263 ± 0.071	0.305 ± 0.035	0.839 ± 0.012	0.281 ± 0.017	$\mathbf{0.455 \pm 0.003}$	0.285 ± 0.010	241 ± 47	0.576 ± 0.065
	Seurat	0.182 ± 0.000	0.260 ± 0.006	0.256 ± 0.005	0.236 ± 0.017	0.260 ± 0.006	0.824 ± 0.000	0.185 ± 0.014	0.389 ± 0.018	0.240 ± 0.012	597 ± 126	0.529 ± 0.004
	SpatialGlue	0.227 ± 0.049	0.375 ± 0.023	0.371 ± 0.024	$\mathbf{0.423 \pm 0.023}$	0.375 ± 0.023	0.837 ± 0.012	0.195 ± 0.084	0.371 ± 0.065	0.220 ± 0.061	375 ± 51	0.624 ± 0.008
	MultiGate	0.148 ± 0.011	0.203 ± 0.013	0.199 ± 0.012	0.221 ± 0.038	0.203 ± 0.013	0.823 ± 0.002	0.147 ± 0.017	0.325 ± 0.022	0.192 ± 0.019	1289 ± 133	0.484 ± 0.001
	TotalVI	0.181 ± 0.006	0.258 ± 0.001	0.253 ± 0.000	0.232 ± 0.001	0.258 ± 0.001	0.823 ± 0.001	0.187 ± 0.011	0.393 ± 0.010	0.242 ± 0.007	418 ± 105	0.525 ± 0.004
	MOFA+	0.212 ± 0.032	0.321 ± 0.033	0.318 ± 0.031	0.306 ± 0.103	0.321 ± 0.033	0.834 ± 0.009	0.229 ± 0.025	0.415 ± 0.036	0.261 ± 0.020	1042 ± 81	0.589 ± 0.073
	MEFISTO	0.200 ± 0.011	0.307 ± 0.007	0.302 ± 0.005	0.310 ± 0.045	0.307 ± 0.007	0.832 ± 0.002	0.221 ± 0.050	0.400 ± 0.044	0.249 ± 0.036	854 ± 82	0.594 ± 0.046
Mouse E13 Embryo	**MELON**	$\mathbf{0.385 \pm 0.007}$	$\mathbf{0.528 \pm 0.010}$	$\mathbf{0.519 \pm 0.007}$	$\mathbf{0.546 \pm 0.039}$	$\mathbf{0.528 \pm 0.010}$	$\mathbf{0.925 \pm 0.001}$	$\mathbf{0.362 \pm 0.026}$	$\mathbf{0.452 \pm 0.022}$	$\mathbf{0.290 \pm 0.023}$	191 ± 40	$\mathbf{0.655 \pm 0.008}$
	MISO	0.227 ± 0.014	0.441 ± 0.031	0.431 ± 0.028	0.417 ± 0.046	0.441 ± 0.031	0.899 ± 0.004	0.251 ± 0.005	0.337 ± 0.002	0.197 ± 0.002	204 ± 29	0.521 ± 0.053
	Seurat	0.266 ± 0.043	0.454 ± 0.017	0.443 ± 0.020	0.487 ± 0.017	0.454 ± 0.017	0.910 ± 0.002	0.223 ± 0.073	0.341 ± 0.047	0.201 ± 0.041	$\mathbf{5180 \pm 318}$	0.571 ± 0.005
	SpatialGlue	0.280 ± 0.014	0.460 ± 0.022	0.451 ± 0.018	0.472 ± 0.063	0.460 ± 0.022	0.910 ± 0.001	0.238 ± 0.043	0.355 ± 0.018	0.215 ± 0.016	306 ± 35	0.600 ± 0.061
	MultiGate	0.170 ± 0.016	0.380 ± 0.008	0.369 ± 0.007	0.392 ± 0.031	0.380 ± 0.008	0.899 ± 0.003	0.168 ± 0.056	0.263 ± 0.036	0.151 ± 0.025	1342 ± 133	0.438 ± 0.021
	TotalVI	0.092 ± 0.003	0.224 ± 0.033	0.212 ± 0.029	0.164 ± 0.030	0.224 ± 0.033	0.819 ± 0.002	0.140 ± 0.005	0.321 ± 0.000	0.149 ± 0.000	195 ± 22	0.307 ± 0.006
	MOFA+	0.201 ± 0.012	0.389 ± 0.012	0.377 ± 0.009	0.383 ± 0.040	0.389 ± 0.012	0.897 ± 0.008	0.199 ± 0.033	0.295 ± 0.017	0.173 ± 0.010	1203 ± 49	0.491 ± 0.030
	MEFISTO	0.207 ± 0.015	0.391 ± 0.003	0.381 ± 0.007	0.392 ± 0.018	0.391 ± 0.003	0.900 ± 0.003	0.189 ± 0.050	0.302 ± 0.032	0.178 ± 0.021	767 ± 29	0.496 ± 0.017

4.3.1 Interpretability via a Joint Pair Decoder

To probe whether MELON's frozen embedding admits a biologically meaningful joint factorisation Doshi-Velez and Kim [2017], Rudin [2019], we train a small *pair decoder* on top of the frozen fused embedding $\mathbf{z}_i$ for each of the three datasets. This follows the post-hoc probing paradigm for interpreting frozen representations Alain and Bengio [2017], instantiated as a post-hoc concept-bottleneck decoder Koh et al. [2020], Yuksekgonul et al. [2023], Svensson et al. [2020] in which each latent factor is directly read out as a gene/peak program. The decoder is a two-headed MLP with a non-negative factor bottleneck $\mathbf{u}_i = \mathrm{softplus}(\phi(\mathbf{z}_i)) \in \mathbb{R}^K_{\geq 0}$ (non-negativity promotes parts-based, additive programs as in NMF Lee and Seung [1999]) (K=24 for the two RNA–ATAC datasets, K=16 for the RNA–ADT lymph node) and two linear heads that simultaneously reconstruct the two modalities under a coupled loss

$$\mathcal{L}_{\text{dec}} \;=\; \tfrac{1}{N} \sum_{i=1}^{N} \Big[\big\| \mathbf{x}_i^R - \mathbf{W}^R \mathbf{u}_i \big\|_2^2 \;+\; \mathrm{BCE}\big(\mathbf{x}_i^A,\, \sigma(\mathbf{W}^A \mathbf{u}_i)\big) \Big], \tag{16}$$

where $\mathbf{W}^R$ and $\mathbf{W}^A$ are the gene and peak/protein loading matrices and σ is the elementwise sigmoid; only the decoder is trained, MELON itself is frozen. Each latent factor k is then summarised by its spatial usage $\{u_{i,k}\}_i$ together with its top gene–peak pair $(g_k^\dagger, p_k^\dagger) = \arg\max_{g,p}\, W^R_{g,k} W^A_{p,k}$ (full derivation in Appendix E.6). Across datasets, factor usage is spatially compartmentalised and the top-ranked features include known developmental and immune markers (Cdh19 Simões-Costa and Bronner [2015], Pou3f1 Zhu et al. [2014], Prdm8 Ross et al. [2012], Uncx Mansouri et al. [1997], Ednrb Baynash et al. [1994], FCGR3A/CD16 Bruhns [2012], CD274/PD-L1 Dong et al. [1999], SDC1/CD138 Wijdenes et al. [1996], PAX5 Nutt et al. [1999]), indicating that the embedding preserves localised cross-modal programs beyond what clustering alone reveals. Per-dataset factor usage maps and curated top gene–peak spatial maps are reported in Appendix E.6.

Additional sensitivity analyses, interpretability results, and qualitative case studies are deferred to Appendix E to keep the main paper within the NeurIPS page limit.

5 Conclusion

We presented MELON, a spatial multimodal representation-learning framework that combines modality-specific encoding, neighborhood-aware spatial attention, transformer-based fusion, and a PID-guided contrastive objective. Across paired RNA–ATAC and RNA–ADT datasets, MELON produced spatially coherent domains and improved agreement with anatomical annotations relative to strong multimodal baselines. These results suggest that preserving shared, modality-specific, and synergistic information is important for accurate spatial multi-omics integration and domain identification. More broadly, the results support a perspective on spatial multi-omics integration in which complementary structure across assays should be modeled explicitly rather than compressed into a purely shared latent space. A practical next step is to extend MELON to additional modality

combinations and larger tissue collections, where richer cross-modal interactions may further improve domain discovery and biological interpretation.

6 Acknowledgments

Acknowledgments are omitted for anonymous review.

References

Joshua Ainslie, James Lee-Thorp, Michiel de Jong, Yury Zemlyanskiy, Federico Lebrón, and Sumit Sanghai. GQA: Training generalized multi-query transformer models from multi-head checkpoints. *arXiv preprint arXiv:2305.13245*, 2023.

Guillaume Alain and Yoshua Bengio. Understanding intermediate layers using linear classifier probes. In *International Conference on Learning Representations (ICLR) Workshop*, 2017.

Ricard Argelaguet, Damien Arnol, Danila Ber, Yonatan Bilu, John C Marioni, and Oliver Stegle. MOFA+: a statistical framework for comprehensive integration of multi-modal single-cell data. *Genome Biology*, 21(1):111, 2020.

Tal Ashuach, Mariano I Gabitto, Rohan V Koodli, Giuseppe-Antonio Saldi, Michael I Jordan, and Nir Yosef. MultiVI: deep generative model for the integration of multimodal data. *Nature Methods*, 20(8):1222–1231, 2023.

Alisa G Baynash, Kiyoshi Hosoda, Adel Giaid, James A Richardson, Noriaki Emoto, Robert E Hammer, and Masashi Yanagisawa. Interaction of endothelin-3 with endothelin-B receptor is essential for development of epidermal melanocytes and enteric neurons. *Cell*, 79(7):1277–1285, 1994.

Nils Bertschinger, Johannes Rauh, Eckehard Olbrich, Jürgen Jost, and Nihat Ay. Quantifying unique information. *Entropy*, 16(4):2161–2183, 2014.

Pierre Bruhns. Properties of mouse and human IgG receptors and their contribution to disease models. *Blood*, 119(24):5640–5649, 2012.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International Conference on Machine Learning (ICML)*, pages 1597–1607. PMLR, 2020.

Kyle Coleman, Amelia Schroeder, Melanie Loth, Daiwei Zhang, Jeong Hwan Park, Ji-Youn Sung, Niklas Blank, Alexis J. Cowan, Xuyu Qian, Jianfeng Chen, Jiahui Jiang, Hanying Yan, Laith Z. Samarah, Jean R. Clemenceau, Inyeop Jang, Minji Kim, Isabel Barnfather, Joshua D. Rabinowitz, Yanxiang Deng, Edward B. Lee, Alexander Lazar, Jianjun Gao, Emma E. Furth, Tae Hyun Hwang, Linghua Wang, Christoph Thaiss, Jian Hu, and Mingyao Li. Resolving tissue complexity by multimodal spatial omics modeling with MISO. *Nature Methods*, 22:530–538, 2025. doi: 10.1038/s41592-024-02574-2.

Zhiyuan Cui et al. Spatial-aware adjusted Rand index for benchmarking spatial domain detection. *Bioinformatics*, 2024.

Haidong Dong, Gefeng Zhu, Koji Tamada, and Lieping Chen. B7-H1, a third member of the B7 family, co-stimulates T-cell proliferation and interleukin-10 secretion. *Nature Medicine*, 5(12): 1365–1369, 1999.

Kangning Dong and Shihua Zhang. Deciphering spatial domains from spatially resolved transcriptomics with an adaptive graph attention auto-encoder. *Nature Communications*, 13(1):1739, 2022.

Finale Doshi-Velez and Been Kim. Towards a rigorous science of interpretable machine learning. *arXiv preprint arXiv:1702.08608*, 2017.

Benoit Dufumier, Javiera Castillo-Navarro, Devis Tuia, and Jean-Philippe Thiran. What to align in multimodal contrastive learning? *arXiv preprint arXiv:2409.07402*, 2024.

Adam Gayoso, Zoë Steier, Romain Lopez, Jeffrey Regier, Kristopher L Nazor, Aaron Streets, and Nir Yosef. Joint probabilistic modeling of single-cell multi-omic data with totalVI. *Nature Methods*, 18(3):272–282, 2021.

Yuhan Hao, Stephanie Hao, Erica Andersen-Nissen, William M Mauck III, Shiwei Zheng, Andrew Butler, et al. Integrated analysis of multimodal single-cell data. *Cell*, 184(13):3573–3587, 2021.

Lawrence Hubert and Phipps Arabie. Comparing partitions. *Journal of Classification*, 2(1):193–218, 1985.

Pang Wei Koh, Thao Nguyen, Yew Siang Tang, Stephen Mussmann, Emma Pierson, Been Kim, and Percy Liang. Concept bottleneck models. In *International Conference on Machine Learning (ICML)*, pages 5338–5348, 2020.

Daniel D Lee and H Sebastian Seung. Learning the parts of objects by non-negative matrix factorization. *Nature*, 401(6755):788–791, 1999.

Yahui Long, Kok Siong Ang, Mengwei Li, Kian Long Kelvin Chong, Raman Sethi, Chengwei Zhong, Hang Xu, Zhiwei Ong, Karishma Sachaphibulkij, Ao Chen, et al. Spatially informed clustering, integration, and deconvolution of spatial transcriptomics with GraphST. *Nature Communications*, 14(1):1155, 2023.

Yahui Long, Kok Siong Ang, Mengwei Li, Kian Long Kelvin Chong, Raman Sethi, Zhiqiang Zhong, et al. Deciphering spatial domains from spatially resolved multi-omics with SpatialGLUE. *Nature Methods*, 21(9):1658–1667, 2024.

Ahmed Mansouri, Yoshifumi Yokota, Reinhard Wehr, Neal G Copeland, Nancy A Jenkins, and Peter Gruss. Paired-related murine homeobox gene expressed in the developing sclerotome, kidney, and nervous system. *Developmental Dynamics*, 210(1):53–65, 1997.

Jishuai Miao, Jinzhao Li, Jingxue Xin, Jiajuan Tu, Muyang Ge, Ji Qi, Xiaocheng Zhou, Ying Zhu, Can Yang, and Zhixiang Lin. Multigate: integrative analysis and regulatory inference in spatial multi-omics data via graph representation learning. *Nature Communications*, 16:9403, 2025.

Stephen L Nutt, Barry Heavey, Antonius G Rolink, and Meinrad Busslinger. Commitment to the B-lymphoid lineage depends on the transcription factor Pax5. *Nature*, 401(6753):556–562, 1999.

Ofir Press, Noah A Smith, and Mike Lewis. Train short, test long: Attention with linear biases enables input length generalization. In *International Conference on Learning Representations (ICLR)*, 2022.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning (ICML)*, pages 8748–8763. PMLR, 2021.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21(140):1–67, 2020.

Honglei Ren, Benjamin L Walker, Zixuan Cang, and Qing Nie. SpaceFlow: identifying multicellular spatiotemporal organization of cells using the spatial transcriptome. *Nature Communications*, 13 (1):4076, 2022.

Andrew Rosenberg and Julia Hirschberg. V-Measure: A conditional entropy-based external cluster evaluation measure. In *Proceedings of the 2007 Joint Conference on Empirical Methods in Natural Language Processing and Computational Natural Language Learning (EMNLP-CoNLL)*, pages 410–420, 2007.

Sarah E Ross, Alexander E McCord, Cynthia Jung, Denize Atan, Shan I Mok, Martin Hemberg, Tae-Kyung Kim, Brenda L Bloodgood, Sinisa Hrvatin, and Michael E Greenberg. Bhlhb5 and Prdm8 form a repressor complex involved in neuronal circuit assembly. *Neuron*, 73(2):292–303, 2012.

Cynthia Rudin. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature Machine Intelligence*, 1(5):206–215, 2019.

Peter Shaw, Jakob Uszkoreit, and Ashish Vaswani. Self-attention with relative position representations. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT)*, pages 464–468, 2018.

Marcos Simões-Costa and Marianne E Bronner. Establishing neural crest identity: a gene regulatory recipe. *Development*, 142(2):242–257, 2015.

Alexander Strehl and Joydeep Ghosh. Cluster ensembles—a knowledge reuse framework for combining multiple partitions. In *Journal of Machine Learning Research*, volume 3, pages 583–617, 2002.

Valentine Svensson, Adam Gayoso, Nir Yosef, and Lior Pachter. Interpretable factor models of single-cell RNA-seq via variational autoencoders. *Bioinformatics*, 36(11):3418–3421, 2020.

Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive multiview coding. In *European Conference on Computer Vision (ECCV)*, 2020a.

Yonglong Tian, Chen Sun, Ben Poole, Dilip Krishnan, Cordelia Schmid, and Phillip Isola. What makes for good views for contrastive learning? In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020b.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. In *International Conference on Learning Representations*, 2018.

Britta Velten, Jana M Braunger, Ricard Argelaguet, Damien Arnol, Jakob Wirbel, Danila Ber, and Oliver Stegle. Identifying temporal and spatial patterns of variation from multimodal data using MEFISTO. *Nature Methods*, 19(2):179–186, 2022.

Nguyen Xuan Vinh, Julien Epps, and James Bailey. Information theoretic measures for clusterings comparison: Variants, properties, normalization and correction for chance. *Journal of Machine Learning Research*, 11:2837–2854, 2010.

J Wijdenes, W C Vooijs, C Clément, J Post, F Morard, N Vita, P Laurent, R X Sun, B Klein, and J M Dore. A plasmocyte selective monoclonal antibody (B-B4) recognizes syndecan-1. *British Journal of Haematology*, 94(2):318–323, 1996.

Paul L Williams and Randall D Beer. Nonnegative decomposition of multivariate information. *arXiv preprint arXiv:1004.2515*, 2010.

Mert Yuksekgonul, Maggie Wang, and James Zou. Post-hoc concept bottleneck models. In *International Conference on Learning Representations (ICLR)*, 2023.

Di Zhang, Yanxiang Deng, Petra Kukanja, Eneritz Agirre, Marek Bartosovic, Mingze Dong, Cong Ma, Sai Ma, Graham Su, Shuozhen Bao, Yang Liu, Yang Xiao, Gorazd B Rosoklija, Andrew J Dwork, J John Mann, Kam W Leong, Maura Boldrini, Liya Wang, Maximilian Haeussler, Benjamin J Raphael, Yuval Kluger, Gonçalo Castelo-Branco, and Rong Fan. Spatial epigenome–transcriptome co-profiling of mammalian tissues. *Nature*, 616(7955):113–122, 2023.

Qingqing Zhu, Lu Song, Guangdun Peng, Na Sun, Jun Chen, Ting Zhang, Nengyin Sheng, Wei Tang, Cheng Qian, Yunbo Qiao, Ke Tang, Jing-Dong Jackie Han, Jinsong Li, and Naihe Jing. The transcription factor Pou3f1 promotes neural fate commitment via activation of neural lineage genes and inhibition of external signaling pathways. *eLife*, 3:e02224, 2014.

Changhao Zuo, Zhiliang Zhang, et al. Simultaneous profiling of spatial gene expression and chromatin accessibility during mouse brain development. *Nature Methods*, 20(7):1048–1057, 2023.

A Related Work

This section expands the brief related-work summary in the main text into a fuller discussion organized by sub-topic.

Spatial Multi-Omics Integration. A central challenge in spatial multi-omics is learning a unified embedding from heterogeneous modalities (e.g., RNA expression and chromatin accessibility) while preserving the spatial organization of tissue. Early approaches adapted single-cell integration tools to the spatial setting. Seurat Hao et al. [2021] performs anchor-based canonical correlation analysis followed by graph-based clustering, but treats spots as independent observations and discards spatial coordinates. MOFA+ Argelaguet et al. [2020] extends multi-omics factor analysis with group and modality structure, yet the underlying linear factor model cannot capture non-linear cross-modal interactions and has no mechanism to incorporate spatial information. TotalVI Gayoso et al. [2021] jointly models RNA and protein (CITE-seq) counts via a variational autoencoder (VAE), but likewise assumes i.i.d. cells and does not exploit spatial neighborhoods. MultiVI Ashuach et al. [2023] extends the VAE paradigm to handle partially observed modalities; however, it still lacks spatial awareness and relies on largely linear/Gaussian priors. MEFISTO Velten et al. [2022] introduces Gaussian-process priors over a spatial or temporal axis to encourage smooth latent factors, effectively capturing spatially coherent variation, but its reconstruction-based objective emphasizes shared (redundant) variation and can over-smooth domain boundaries. SpatialGlue Long et al. [2024] couples graph convolutional networks with a VAE, building a spatial neighbor graph per modality and fusing representations via cross-attention. While SpatialGlue explicitly models spatial structure, its reconstruction loss still primarily captures redundancy and can average away sharp boundaries. In contrast, MELON uses a contrastive objective that captures not only shared (redundant) information but also unique and synergistic cross-modal signals, combined with a learned spatial attention bias that preserves tissue boundaries.

Contrastive Representation Learning. Contrastive self-supervised methods learn representations by pulling positive pairs together and pushing negative pairs apart in an embedding space. The InfoNCE estimator was introduced by van den Oord et al. [2018] and popularised for image self-supervised learning by SimCLR Chen et al. [2020], which showed that data-augmentation-based positive pairs, a projection head, and large batch sizes are critical for performance. Tian et al. [2020a] (Contrastive Multiview Coding, CMC) extended InfoNCE to multiple augmentations of the same scene, providing the multi-modality contrastive paradigm that subsequent multimodal methods build on. CLIP Radford et al. [2021] applied a two-modality symmetric cross-modal InfoNCE loss to image–text pairs at scale. The theoretical foundations of which information these losses recover trace back to *partial information decomposition* (PID, Williams and Beer [2010], Bertschinger et al. [2014]), which decomposes the joint mutual information $I(X_1, X_2; Y)$ into redundancy (R), modality-specific uniqueness (U_1, U_2), and synergy (S). Building on these two threads, the CoMM framework Dufumier et al. [2024] showed that standard CLIP-style two-modality objectives capture only R, and proposed a modality-masking InfoNCE loss whose terms provably (Lemmas 2 and 3) align with all four PID components, including S. MELON directly builds on this framework: it generates modality-masked and joint embeddings and contrasts each modality-masked embedding against the joint embedding, ensuring that the learned embedding captures all four information components.

Spatial Inductive Biases for Transcriptomics. Incorporating spatial structure into representation learning for spatially resolved data is a well-studied problem with two broad families of approaches: graph neural networks that perform explicit message passing, and attention-bias methods that modulate Transformer attention with positional priors.

On the GNN side, Graph Attention Networks (GAT) Veličković et al. [2018] learn adaptive edge weights via $\mathrm{LeakyReLU}(\mathbf{a}^\top [W\mathbf{h}_i \,\|\, W\mathbf{h}_j])$ and *aggregate* neighbour features through a weighted sum, producing new node embeddings at each layer. In spatial transcriptomics, STAGATE Dong and Zhang [2022] applies a graph attention autoencoder over a spatial neighbor graph for spatial domain identification, and GraphST Long et al. [2023] combines graph contrastive learning with spatial neighbor aggregation. SpaceFlow Ren et al. [2022] uses a spatially regularised deep graph network to learn pseudo-spatiotemporal embeddings. These methods perform true message passing—each

node's representation is updated by aggregating information from its neighbours—but are designed for a single modality (gene expression).

On the attention-bias side, recent work in NLP and vision has shown that injecting learned or fixed positional biases directly into Transformer attention scores is an effective alternative to explicit positional encodings. ALiBi Press et al. [2022] adds a linear distance penalty to attention logits, and relative position biases Raffel et al. [2020], Shaw et al. [2018] parameterise position-dependent offsets in the attention matrix.

MELON's spatial module (internally called *NeighborhoodGAT*) falls squarely in the second category: it is **not** a standard GAT despite the name. It computes a learned attention bias over a k-nearest-neighbour graph from positional embeddings of the spot coordinates $u_i = \psi(s_i)$, using an additive GAT-style edge logit $\mathrm{LeakyReLU}(a_{\mathrm{src}}^{(h)\top} h_i^{(h)} + a_{\mathrm{dst}}^{(h)\top} h_j^{(h)})$ with per-head learned vectors $a_{\mathrm{src}}^{(h)}, a_{\mathrm{dst}}^{(h)}$ and projections $h_i^{(h)} = W^{(h)} u_i$ (Methods §3.4), but critically performs **no message passing and no neighbour-feature aggregation**. Instead, the module outputs a log-space bias matrix $B \in \mathbb{R}^{N\times N}$ that is injected additively into the Transformer's scaled dot-product attention: $\mathrm{softmax}(QK^\top/\sqrt{d_k} + B)V$. Because the bias is additive in log-space, it is equivalent to *multiplicatively gating* content-based attention by learned spatial proximity weights, with non-neighbour entries receiving $\log \epsilon \approx -13.8$ and therefore effectively zero attention. This design is modality-invariant—the same spatial bias is block-tiled and applied regardless of which modality combination is active under the masking strategy (Appendix C.3)—and integrates seamlessly with the Transformer's Grouped Query Attention (GQA) Ainslie et al. [2023].

B Datasets and Preprocessing

We evaluate MELON on three paired spatial multimodal datasets that span embryonic brain, embryonic whole-embryo, and human lymphoid tissue settings. Together they cover both RNA–ATAC and RNA–protein integration, different tissue architectures, and a range of spatial domain granularities.

Table 5: Dataset statistics used in experiments. For ATAC modalities, the raw peak matrices are reduced to 50 components via TF–IDF + LSI before modeling (Appendix C.1).

Dataset	#Spots	Modality 1	Modality 2	#Domains
Mouse E15.5 Brain	1,949	2,144 genes	47,287 peaks	12
Mouse E13 Embryo	2,187	17,058 genes	24,017 peaks	14
Human Lymph Node	3,484	18,085 genes	31 proteins	10

Mouse E15.5 Brain (MISAR-seq). This dataset profiles an embryonic day 15.5 mouse brain sagittal section using MISAR-seq (Microfluidic Indexing-based Spatial ATAC and RNA-seq), which simultaneously measures chromatin accessibility and gene expression at 50 μm grid resolution ($\sim$15–30 cells per spot) Zuo et al. [2023]. The dataset contains 1,949 spots with 2,144 RNA features and 47,287 ATAC peaks. Ground-truth labels comprise 12 manually annotated neuroanatomical regions (diencephalon, cartilage, hindbrain, dorsal pallium medial/ventral, mesenchyme, midbrain, skull, subpallium, muscle, cerebellar vermis, thalamus), validated against the Allen Mouse Brain Atlas. RNA counts are normalized with `normalize_total` (target sum 10^4) followed by $\log(1+x)$. ATAC peaks are transformed via TF–IDF weighting followed by Latent Semantic Indexing (truncated SVD with 50 components), yielding a 50-dimensional input per spot. Data are publicly available at GEO accession `GSE213264`.

Human Lymph Node (Visium RNA–ADT). This dataset profiles two sequential 5 μm FFPE sections of a human lymph node using the 10x Genomics Visium CytAssist platform Long et al. [2024]. Sections were stained with H&E following the CytAssist FFPE protocol (CG000658, 10x Genomics) including deparaffinization, staining, imaging, and decrosslinking, with imaging on an EVOS M7000 microscope ($\times$20 objective). Spatial gene expression libraries were prepared with the Visium Human Transcriptome Probe Set v2.0 and spatial protein expression libraries with the Human FFPE Immune Profiling Panel (31 antibody targets + 4 isotype controls = 35-plex; antibodies from BioLegend and Abcam, signals normalized to isotype controls). Libraries were sequenced on an Illumina NovaSeq S2 PE50 ($\sim$2,000 M reads per lane) and processed with Space Ranger v2.1.0

against GRCh38 (GENCODE v32 / Ensembl 98). The dataset contains 3,484 spots with 18,085 genes and 31 proteins. Reference labels comprise 10 manually annotated lymphoid compartments (medulla cords, medulla sinuses, cortex, pericapsular adipose tissue, capsule, subcapsular sinus, follicle, medulla vessels, hilum, trabeculae) curated from H&E images in Loupe Browser. RNA counts are $\log(1+x)$-normalized; ADT counts are transformed via centered log-ratio (CLR) normalization. Data are available at `https://zenodo.org/records/10362607`.

Mouse E13 Embryo (spatial-ATAC–RNA-seq). This dataset profiles a whole embryonic day 13 mouse section with paired RNA and ATAC (H3K27ac active chromatin marks) using spatial-ATAC–RNA-seq, which co-profiles the epigenome and transcriptome at 50 μm pixel resolution via deterministic barcoding in tissue (DBiT-seq) Zhang et al. [2023]. It contains 2,187 spatial locations, 17,058 genes, and 24,017 ATAC peaks. Ground-truth annotations comprise 14 embryonic regions (ventral trunk, surface ectoderm, forebrain, paraxial mesoderm, dorsal head/body-wall mesenchyme, periventricular neuroepithelium, spinal cord, head mesenchyme, caudal ventral trunk, gut/ventral endoderm, hindbrain–cervical transition, trunk mesenchyme, eye, visceral organ primordia). Preprocessing follows the same recipe as the E15.5 dataset: $\log(1+x)$ for RNA and TF–IDF + LSI (50 components) for ATAC. This benchmark complements the E15.5 brain dataset by testing MELON on a larger developmental system with broader anatomical diversity.

C Implementation Details

C.1 Preprocessing and Augmentations

MELON operates on modality-specific input matrices after standard preprocessing for each assay. The framework is agnostic to the choice of preprocessing – continuous, normalized, or low-rank-reduced features all work as drop-in inputs to the per-modality encoder f_m – and the concrete recipes used for the assays in our experiments (RNA, ATAC, ADT) are described in Appendix B. During training, augmentations are applied before the encoder so that the model never observes a clean batch in the contrastive forward pass.

For each batch, MELON samples two independent augmented multimodal inputs by independently applying three stochastic transformations: Gaussian noise, feature dropout, and aligned cross-spot mixing (the latter shares its permutation and mixing coefficient across all modalities of the same spot so that cross-modal correspondences are preserved). The functional form of each augmentation and the exact hyperparameters used in our experiments (σ, dropout fraction, mixing distribution, and activation probability) are listed in Appendix C.4.

C.2 Spot Tokenization and Token Recovery

Let N denote the batch size and n the number of modalities ($n = 2$ in all of our experiments). After the modality-specific encoders and token-space projection, MELON has one embedding per spot and per modality. With spot tokenization enabled, the batch dimension is reinterpreted as the token dimension, so that each modality contributes a length-N token sequence:

$$T^{(m)} \in \mathbb{R}^{1\times N\times d}, \qquad m \in \{1,\dots,n\}. \tag{17}$$

Concatenating modalities yields a single token sequence

$$T = \operatorname{concat}\big(T^{(1)},\dots,T^{(n)}\big) \in \mathbb{R}^{1\times (nN)\times d}. \tag{18}$$

Thus, token i corresponds to spot i in modality 1, token $N+i$ to the same spot in modality 2, and so on. The transformer therefore attends jointly across all spot–modality pairs in the batch.

After the fusion transformer outputs all active tokens, the resulting tensor is reshaped back into modality-by-spot blocks and pooled across modalities to recover one fused embedding per spot:

$$\tilde{T} \in \mathbb{R}^{1\times (nN)\times d} \to \mathbb{R}^{n\times N\times d}, \qquad z_i = \frac{1}{n}\sum_{m=1}^{n} \tilde{t}_i^{(m)}. \tag{19}$$

This tokenization scheme is the default because it allows the transformer to model both cross-modal and cross-spot interactions within a single attention layer.

C.3 Spatial Bias Tiling and Modality Masking

NeighborhoodGAT produces a spot-level spatial bias matrix $B \in \mathbb{R}^{N \times N}$, where N is the batch size as defined in Appendix C.2. Under spot tokenization, however, the transformer sees nN tokens rather than N spots. To align the spatial prior with the token layout, we tile the spot-level bias across modality blocks into the matrix B_{spatial} used in the fusion-transformer attention (§3.5). For n modalities, B_{spatial} is an $n \times n$ block matrix in which every block equals B; we write the $n = 2$ case explicitly here for concreteness:

$$B_{\text{spatial}} = \begin{bmatrix} B & B \\ B & B \end{bmatrix} \in \mathbb{R}^{2N \times 2N}. \tag{20}$$

This tiling enforces that the spatial relationship between spot i and spot j is modality-invariant: the same bias is used whether attention connects within-modality token pairs (modality m to modality m) or cross-modal token pairs (modality m to modality m') for those two spots. For n modalities the construction generalises by replacing the 2×2 block matrix above with an $n \times n$ block matrix whose every block is B.

MELON then evaluates the fusion module under $n + 1$ modality masks: n single-modality passes and one joint multimodal pass. When only modality m is active, the token sequence is physically subsetted and the tiled bias is sliced to the diagonal block corresponding to m, which by construction equals the underlying spot-level bias B. For the multimodal pass, the full tiled matrix is used. This design guarantees that single-modality and multimodal forward passes share the same underlying spot-level spatial bias.

C.4 Hyperparameters

MELON is implemented in PyTorch with PyTorch Lightning. All defaults used in this paper are listed in Table 6 and were not tuned per dataset. Augmentation functional forms are described in §3.2; the values in the table refer to the parameters of those functions. After training, the joint embedding is clustered with Leiden clustering; the implementation also supports Louvain, Walktrap, spectral, and GMM for downstream exploration.

Table 6: MELON default hyperparameters. All values were used as-is across the three benchmarked datasets without per-dataset tuning.

Group	Hyperparameter	Value
Encoder	Per-modality encoder	2-layer MLP, $d_m \to 128 \to 128$, ReLU
	Embedding dimension	128
	Projection head	3-layer MLP, $128 \to 256 \to 256 \to 128$, SyncBatchNorm
	Output normalisation	L2
Fusion transformer	Layers	1
	Attention	Grouped Query Attention, 8 heads
	MLP expansion / activation	$4\times$ / QuickGELU
	Spatial bias	additive (NeighborhoodGAT, see below)
NeighborhoodGAT	Layers / heads	1 / 8
	Hidden dim per head	64
	Attention dropout	0.1
	LeakyReLU slope	0.2
	Spatial k-NN graph	$k = 16$, self-loops included
Optimisation	Optimiser	Adam, $(\beta_1, \beta_2) = (0.9, 0.999)$
	Learning rate	1×10^{-3}
	Weight decay	1×10^{-5}
	Schedule	none
	Epochs	100
	Batch size	2,048
Loss	Temperature τ	0.1
	Per-mask weighting	equal across $n+1$ masks (Eq. 14)
Augmentations	Activation probability	$p = 0.8$ per augmentation
	Gaussian noise	$\sigma = 0.05$
	Feature dropout	fraction 0.2
	Neighbour mix	$\lambda \sim \mathrm{Beta}(0.3, 0.3)$, shared π, λ across modalities
Reproducibility	Random seed	42 (PyTorch, NumPy, Python `random`)
	Hardware	CPU (Apple Silicon / MPS) or single CUDA GPU
	Framework	PyTorch + PyTorch Lightning

D Proof of Proposition 1

Proposition 1 (PID inheritance under spatial bias)**.** *Let f_θ be an encoder satisfying the standard expressivity assumption (Assumption 1), and let B be any spatial-bias matrix injected as an additive term in f_θ's attention scores (§3.4–§3.5). Suppose the augmentation family $\mathcal{T}$ used to draw the two augmented inputs X', X'' is label-preserving with respect to the latent spatial-domain identity Y (Eq. 21). Then at the supremum $\mathcal{L}_{\mathrm{MELON}}$ decomposes across the four PID quantities $\{R, S, U_1, \ldots, U_n\}$ through its joint and modality-masked terms: the joint term $\mathcal{L}_\star$ aligns the joint embedding with $R + S + \sum_{m=1}^{n} U_m$, each modality-masked term $\mathcal{L}_m$ aligns the modality-m embedding with $R + U_m$, and each individual PID component is therefore identifiable from linear combinations of these loss-term optima.*

Setup. Let $X = (X^{(1)}, \ldots, X^{(n)})$ be a multimodal input, Y a latent task variable, and $f_\theta : \mathcal{X} \to \mathcal{Z}$ an encoder. Let $\mathcal{T}^\star$ be a label-preserving augmentation family in the sense of Tian et al. [2020b]: two independent views $t'(X), t''(X)$ drawn from $\mathcal{T}^\star$ are jointly sufficient and minimal for Y, equivalently

$$\forall\, t', t'' \in \mathcal{T}^\star, \qquad I\big(t'(X),\, t''(X)\big) \;=\; I(X,\, Y). \tag{21}$$

For $t', t'' \sim \mathcal{T}^\star$, write $X' = t'(X)$, $X'' = t''(X)$, and let

$$Z'_\theta \;=\; f_\theta(X'), \qquad Z''_\theta \;=\; f_\theta(X''), \qquad Z_\theta^{[m]} \;=\; f_\theta\big(X^{[m]}\big), \tag{22}$$

where $X^{[m]} = ([\mathrm{MSK}], \ldots, X^{(m)}, \ldots, [\mathrm{MSK}])$ is the modality-m-only masked input. The partial information decomposition [Williams and Beer, 2010, Bertschinger et al., 2014] writes

$$I\big(X^{(1)}, \ldots, X^{(n)};\, Y\big) \;=\; R + S + \sum_{m=1}^{n} U_m, \tag{23}$$

and the chain rule of mutual information gives the consistency relations [Bertschinger et al., 2014]

$$I\big(X^{(m)};Y\big) \;=\; R + U_m, \qquad m = 1,\dots,n. \tag{24}$$

Assumption 1 (Expressivity of f_θ)**.** The encoder family $\{f_\theta\}_\theta$ is sufficiently rich that $\sup_\theta I(f_\theta(V);W) = I(V;W)$ for every pair of random variables (V,W) appearing in the proof; equivalently, the supremum is attained by an f_θ that is a sufficient statistic of V for W. (We use V, W as generic placeholders to avoid clash with the spatial-bias matrix B.) This is the standard expressivity hypothesis used in neural mutual-information estimation [van den Oord et al., 2018, Tian et al., 2020a].

Proof. Recall the MELON loss from Eq. 14,

$$\mathcal{L}_{\mathrm{MELON}} \;=\; \frac{1}{n+1}\Big(\mathcal{L}_\star \;+\; \sum_{m=1}^{n} \mathcal{L}_m\Big), \tag{25}$$

with the joint and modality-masked per-mask terms (Eq. 13)

$$\mathcal{L}_\star \;=\; -\tfrac{1}{2}\Big(\widehat{I}_{\mathrm{NCE}}\big(Z_\theta'^{[\star]},\, Z_\theta''^{[\star]}\big) + \widehat{I}_{\mathrm{NCE}}\big(Z_\theta''^{[\star]},\, Z_\theta'^{[\star]}\big)\Big), \tag{26}$$

$$\mathcal{L}_m \;=\; -\tfrac{1}{2}\Big(\widehat{I}_{\mathrm{NCE}}\big(Z_\theta'^{[m]},\, Z_\theta''^{[\star]}\big) + \widehat{I}_{\mathrm{NCE}}\big(Z_\theta''^{[m]},\, Z_\theta'^{[\star]}\big)\Big), \tag{27}$$

where $Z_\theta'^{[\star]} = Z_\theta'$ and $Z_\theta''^{[\star]} = Z_\theta''$ denote the joint-mask embeddings.

Step 1: $\mathcal{L}_\star$ recovers $R + S + \sum_m U_m$. Consider the Markov chains $X \to X' \to Z_\theta'$ and $X \to X'' \to Z_\theta''$, with X' and X'' conditionally independent given X. Then

$$\begin{aligned}
\sup_\theta\big(-\mathcal{L}_\star\big) \;&=\; \sup_\theta\, \widehat{I}_{\mathrm{NCE}}\big(Z_\theta',\, Z_\theta''\big) && \text{[Eq. (26), symmetrisation]}\\
&=\; \sup_\theta\, I\big(Z_\theta',\, Z_\theta''\big) && \text{[van den Oord et al., 2018, Assumption 1]}\\
&=\; I(X', X'') && \text{[data processing inequality, Assumption 1]}\\
&=\; I(X, Y) && \text{[label-preservation, Eq. (21)]}\\
&=\; R + S + \sum_{m=1}^{n} U_m && \text{[PID, Eq. (23)].}
\end{aligned} \tag{28}$$

This follows the standard InfoNCE–mutual-information equivalence [van den Oord et al., 2018] combined with the PID decomposition (23).

Step 2: $\mathcal{L}_m$ recovers $R+U_m$ for each m. Consider the Markov chain $Y \to X^{(m)} \to X^{[m]} \to Z_\theta^{[m]}$, since the masked input $X^{[m]} = ([\mathrm{MSK}],\dots,X^{(m)},\dots,[\mathrm{MSK}])$ depends on $X^{(m)}$ alone. Then

$$\begin{aligned}
\sup_\theta\big(-\mathcal{L}_m\big) \;&=\; \sup_\theta\, \widehat{I}_{\mathrm{NCE}}\big(Z_\theta^{[m]},\, Z_\theta\big) && \text{[Eq. (27), symmetrisation]}\\
&=\; \sup_\theta\, I\big(Z_\theta^{[m]};\, Z_\theta\big) && \text{[van den Oord et al., 2018, Assumption 1]}\\
&=\; \sup_\theta\, I\big(Z_\theta^{[m]};\, Y\big) && \text{[Step 1: at the supremum } Z_\theta \text{ is a sufficient statistic of } Y]\\
&=\; I\big(X^{(m)};\, Y\big) && \text{[data processing inequality, Assumption 1]}\\
&=\; R + U_m && \text{[PID consistency, Eq. (24)].}
\end{aligned} \tag{29}$$

Note that this chain does not invoke the label-preservation hypothesis (21); the symmetric augmentation in MELON ($Z_\theta'^{[m]}, Z_\theta''^{[m]}$ both deterministic functions of $X^{(m)}$ via $t \in \mathcal{T}^\star$) leaves it unaffected, since the masked input depends on modality m alone regardless of the augmentation applied.

Step 3: the spatial bias preserves both chains. The bias B enters f_θ only as an additive term in the attention logits, $\mathrm{Attn}(Q,K,V) = \mathrm{softmax}\big(QK^\top/\sqrt{d_k} + B\big)V$, and B is computed solely from the spatial coordinates S via NeighborhoodGAT (§3.4), independently of the per-modality features $X^{(1)},\dots,X^{(n)}$. Conditioned on S, the bias B is therefore a fixed observed covariate and $f_\theta(\,\cdot\,;\,B)$

is a deterministic function of X. The Markov chains of Steps 1 and 2 hold conditionally on S, so the chains (28) and (29) carry through under $f_\theta \mapsto f_\theta(\,\cdot\,;\, B)$.

Conclusion. Substituting Steps 1 and 2 into Eq. (25),

$$\sup_\theta\big(-\mathcal{L}_{\mathrm{MELON}}\big) \;=\; \frac{1}{n+1}\Bigg[\underbrace{\Big(R+S+\sum_{m=1}^{n} U_m\Big)}_{\text{Step 1: } \mathcal{L}_\star} \;+\; \sum_{m=1}^{n}\underbrace{\big(R+U_m\big)}_{\text{Step 2: } \mathcal{L}_m}\Bigg]. \tag{30}$$

Each of the four PID components R, S, $U_1, \ldots, U_n$ appears as the optimum of a distinct term of $\mathcal{L}_{\mathrm{MELON}}$. □

Where the assumptions can fail in practice. Two assumptions of Proposition 1 can be violated in real spatial multi-omics data.

(i) Expressivity of f_θ. Assumption 1 requires the supremum of the InfoNCE bound (12) to be attained, i.e. f_θ is expressive enough to saturate the InfoNCE bound. In practice, MELON uses a single fusion-transformer layer with embedding width 128, so the supremum is replaced by a stationary point of finite-capacity neural optimisation. The recovered information is therefore a lower bound on the four PID components rather than an exact match. This caveat is shared by every neural mutual-information estimator [van den Oord et al., 2018, Tian et al., 2020a].

(ii) Approximate label-preservation of $\mathcal{T}$. The strict equality (21) is unlikely to hold for any finite augmentation family. The augmentations used in MELON (Gaussian noise, Bernoulli dropout, aligned cross-spot mixing) are only *approximately* label-preserving with respect to the latent spatial-domain identity Y. We expect $I(X, t(X)) \approx I(X, Y)$ in this setting because (a) Gaussian noise and feature dropout are weak perturbations that rarely cross spatial-domain boundaries, and (b) cross-spot mixing is modulated by a small $\lambda \sim \mathrm{Beta}(0.3, 0.3)$, so the perturbed input is still dominated by the original spot's signal. The conclusion (30) should therefore be read as "approximately recovers the four PID components, with the approximation tightening as the augmentation family becomes more strictly label-preserving." We examine this empirically in the simulation study of §4.2, where MELON recovers a synergy-only label Y at $\mathrm{BalAcc} = 0.818$ while every external multi-omics method collapses to chance, confirming that the synergy term of $\mathcal{L}_{\mathrm{MELON}}$ is empirically active under our augmentation choices.

E Additional Real-Data Experiments

E.1 Compared Baselines

We compare MELON against five established spatial multi-omics integration methods. For each baseline we report the joint embedding produced by the published implementation under default settings, then evaluate it under the same downstream clustering and metric protocol described in Appendix E.2.

- **Seurat v4** Hao et al. [2021]: performs weighted nearest-neighbor (WNN) integration of multiple modalities via anchor-based canonical correlation analysis, followed by graph-based Louvain clustering. Spatial coordinates are not used.
- **MOFA+** Argelaguet et al. [2020]: multi-omics factor analysis with group and modality structure. Learns linear shared and private latent factors via variational inference. No spatial information.
- **TotalVI** Gayoso et al. [2021]: a deep generative variational autoencoder (VAE) for joint modeling of RNA and protein (CITE-seq) counts. Assumes i.i.d. cells and does not exploit spatial neighborhoods.
- **SpatialGlue** Long et al. [2024]: a graph neural network with a dual-attention mechanism that builds per-modality spatial neighbor graphs and fuses representations via cross-attention within a VAE framework. Explicitly uses spatial coordinates.
- **MEFISTO** Velten et al. [2022]: extends MOFA+ with Gaussian-process priors over spatial (or temporal) covariates to encourage smooth latent factors, partially capturing spatial structure but at the cost of over-smoothing domain boundaries.

In addition we evaluate **MISO** Coleman et al. [2025] and **MultiGate** as recent multimodal integration methods, run under the same protocol. For downstream clustering of all learned embeddings (MELON and baselines) we apply Leiden clustering. All methods are evaluated at matching numbers of clusters k.

E.2 Evaluation Metrics

We evaluate spatial domain identification using seven clustering quality metrics that together capture cluster purity, mutual dependence, and spatial coherence.

Adjusted Rand Index (ARI) Hubert and Arabie [1985] measures the similarity between predicted and ground-truth cluster assignments, adjusted for chance:

$$\mathrm{ARI} \;=\; \frac{\mathrm{RI}_{\text{obs}} - \mathrm{RI}_{\text{rand}}}{\max(\mathrm{RI}) - \mathrm{RI}_{\text{rand}}}, \tag{31}$$

where RI is the Rand index and $\mathrm{RI}_{\text{rand}}$ is its expectation under random labelings.

Normalized Mutual Information (NMI) Strehl and Ghosh [2002] quantifies the mutual dependence between true and predicted clusters, normalized by the arithmetic mean of their entropies: $\mathrm{NMI} = 2\,I(Y;\hat{Y})/(H(Y) + H(\hat{Y}))$, where $I(Y;\hat{Y})$ is the mutual information and $H(\cdot)$ is the Shannon entropy. **Adjusted Mutual Information (AMI)** Vinh et al. [2010] corrects mutual information for chance agreement, analogous to ARI's adjustment. **Homogeneity** Rosenberg and Hirschberg [2007] measures whether each predicted cluster contains only members of a single ground-truth class. **V-measure** Rosenberg and Hirschberg [2007] is the harmonic mean of homogeneity and completeness, providing a balanced assessment of clustering quality. **Mutual Information (MI)** reports the raw mutual information $I(Y;\hat{Y})$ between true and predicted labels, without normalization or chance correction. **Spatial ARI (spARI)** Cui et al. [2024] extends ARI by incorporating spatial proximity, penalizing misassignments that are spatially incoherent. This metric is the only one in our suite that explicitly rewards spatially contiguous predictions.

E.3 Additional Dataset Results


E.4 Benchmarking Metrics Across Methods

E.5 Sensitivity Analysis


We evaluate the sensitivity of MELON to its main hyperparameters, including the (1) number of spatial neighbors k, (2) latent dimension, (3) number of fusion layers, and (4) contrastive temperature. The results show that MELON is stable over a broad range of settings, with only moderate degradation under substantial perturbations.

Number of spatial neighbors. We sweep the spatial graph size $k \in \{1, 2, 4, 8, 16, 32\}$ on the simulation benchmark and probe the frozen embedding for the four latent factors (shared Y, modality-specific R and U, and common signal C). As shown in Figure 9, the modality-specific and common factors (R, U, C) are recovered essentially perfectly across the entire range, while balanced accuracy on the shared label Y stays within a narrow 0.78–0.84 band, with overlapping error bars across all k. Performance is therefore robust to reasonable changes in neighborhood size, indicating that MELON does not rely on carefully tuned local graph construction. Very small (k=1) and very large (k=32) neighborhoods behave comparably to the default k=8, suggesting that the spatial bias injected by NeighborhoodGAT degrades gracefully rather than collapsing when the graph is mis-specified.

Other hyperparameters. Varying the latent dimension or transformer depth produces relatively small fluctuations compared with the gap to baselines, indicating that MELON's gains are architectural rather than incidental. We also test sensitivity to the relative weighting of the multimodal and unimodal contrastive terms and find that the model is most stable when both are retained, which is consistent with the goal of preserving both shared and modality-specific signal. These results suggest that MELON is not only accurate but also practically robust across datasets with different modality characteristics and spatial resolutions.



(a) H&E image, ground-truth annotation, and spatial domain assignments from all eight benchmarked methods (ARI labelled per panel; methods ordered consistently across datasets).



(b) Clustering metrics (ARI, NMI, Homogeneity, V-Measure, AMI) across all eight methods at $k = 10$.

Figure 4: Human lymph node results. (a) H&E tissue image, ground-truth annotation, and spatial domain assignments from MELON and seven multimodal baselines (per-panel ARI). (b) Five clustering metrics across all eight methods. Benchmark-over-k curves are provided in Appendix 7.

E.6 Interpretability

We probe MELON's frozen embedding with a joint pair-decoder and ask whether the resulting factors recover biologically meaningful, spatially organized RNA–ATAC (or RNA–protein) programs.

Decoder formulation. Let $\mathbf{z}_i \in \mathbb{R}^d$ denote the frozen MELON fused embedding of spot i, and let $\mathbf{x}_i^R \in \mathbb{R}^G$ and $\mathbf{x}_i^A \in \{0,1\}^P$ be its observed RNA expression and binarised ATAC (or protein) profile, where G and P are the number of genes and peaks respectively. We map each embedding through a small MLP ϕ with a low-rank bottleneck of width K (we use $K{=}24$ for the two RNA–ATAC datasets and $K{=}16$ for the lymph node):

$$\mathbf{u}_i \;=\; \mathrm{softplus}\big(\phi(\mathbf{z}_i)\big) \;\in\; \mathbb{R}^K_{\geq 0}, \tag{32}$$


so that $u_{i,k}$ is the non-negative usage of factor k at spot i. Two linear heads decode this bottleneck back into the two modalities,

$$\widehat{\mathbf{x}}_i^R \;=\; \mathbf{W}^R\,\mathbf{u}_i \;+\; \mathbf{b}^R, \qquad \widehat{\mathbf{x}}_i^A \;=\; \sigma\big(\mathbf{W}^A\,\mathbf{u}_i \;+\; \mathbf{b}^A\big), \tag{33}$$


with $\mathbf{W}^R \in \mathbb{R}^{G\times K}$, $\mathbf{W}^A \in \mathbb{R}^{P\times K}$ and σ the elementwise sigmoid. The two-headed reconstruction loss couples both modalities through the same factor activations,

$$\mathcal{L}_{\text{dec}} \;=\; \frac{1}{N}\sum_{i=1}^{N}\Big[\big\|\mathbf{x}_i^R - \widehat{\mathbf{x}}_i^R\big\|_2^2 \;+\; \lambda\,\mathrm{BCE}\big(\mathbf{x}_i^A,\,\widehat{\mathbf{x}}_i^A\big)\Big], \tag{34}$$

where $\mathrm{BCE}(\cdot,\cdot)$ is the elementwise binary cross-entropy averaged over peaks/proteins and λ balances the two heads (we use $\lambda{=}1$). Only the decoder parameters $\{\phi, \mathbf{W}^R, \mathbf{b}^R, \mathbf{W}^A, \mathbf{b}^A\}$ are trained; MELON is frozen. We optimise with Adam for 20 epochs on a 90/10 train–validation split.



(a) H&E image, ground-truth annotation, and spatial domain assignments from all eight benchmarked methods (ARI labelled per panel; methods ordered consistently across datasets).



(b) Clustering metrics (ARI, NMI, Homogeneity, V-Measure, AMI) across all eight methods at $k = 14$.

Figure 5: Mouse E13 embryo results. (a) H&E tissue image, ground-truth annotation, and spatial domain assignments from MELON and seven multimodal baselines (per-panel ARI). (b) Five clustering metrics across all eight methods. Benchmark-over-k curves are provided in Appendix 8.

Per-factor feature ranking. After training, factor k is summarised by three quantities: (i) its *spatial usage* $\{u_{i,k}\}_{i=1}^{N}$, plotted on tissue coordinates; (ii) its *top gene* and *top peak/protein*, defined as the columns of $\mathbf{W}^R$ and $\mathbf{W}^A$ with the largest loading on factor k,

$$g_k^\star \;=\; \arg\max_{g\in[G]} W^R_{g,k}, \qquad p_k^\star \;=\; \arg\max_{p\in[P]} W^A_{p,k}; \tag{35}$$

and (iii) its *top gene–peak pair score*, defined as the product of the two loadings,

$$s_{g,p,k} \;=\; W^R_{g,k} \cdot W^A_{p,k}, \qquad (g_k^\dagger, p_k^\dagger) \;=\; \arg\max_{(g,p)} s_{g,p,k}. \tag{36}$$

This product score promotes pairs in which the gene and the peak load on the *same* factor with high magnitude, so that a high score identifies cross-modal feature pairs jointly explained by a shared latent program. We rank all $G \times P$ pairs per factor by (36) and report the top entries in the supplementary CSVs.

Decoder factor program maps. For each dataset we show four high-variance factors with their top gene and top peak (or protein) label as Figures 10, 11, and 12. The mouse E13 embryo factors (0, 14, 8, 19) have biologically named top pairs including *Cdh19–Pmpcb* (factor 0; *Cdh19* is a cadherin involved in neural crest development) and *Mak–Pou3f1* (factor 14; *Pou3f1* marks early neural progenitors). The mouse E15.5 brain factors carry chromosomal-coordinate ATAC peaks that we abbreviate to `chrN:Mb` for display. The human lymph node decoder collapses every factor's top protein loading to the dominant cytokeratin marker KRT5 (which has prevalence ≈ 0.76 across the section), but the per-spot factor usage still clearly separates follicular and cortical-medullary territories. The remaining factors and full feature loadings are reported in the supplementary CSVs (`factor_top_genes.csv`, `factor_top_peaks.csv`, `factor_top_pairs.csv`) for each decoder.




Figure 6: Appendix benchmark-over-k metrics for the Mouse E15.5 brain dataset.




Figure 7: Appendix benchmark-over-k metrics for the Human lymph node dataset.

High-support gene–peak pair maps. As an additional perspective we select six gene–peak pairs per dataset from the global top-pair list whose joint score exceeds a coverage threshold, and visualize each pair's RNA expression, ATAC accessibility (or protein abundance for the lymph node), and decoder pair-activity on the tissue coordinates side by side (Figures 13, 14, and 15). Several of these pairs show concentrated activity patterns that are not explained by either modality in isolation – the per-spot pair activity has a sharper boundary than the marginal RNA or ATAC channel alone – consistent with the claim that MELON's embedding preserves cross-modal correspondence rather than collapsing to a shared consensus. We caution that the global top-pair list is dominated by ubiquitous peaks for the embryo and lymph node decoders (peak/protein prevalence approaching 1.0




Figure 8: Appendix benchmark-over-k metrics for the Mouse E13 embryo dataset.




Figure 9: Sensitivity of MELON to the number of spatial neighbors k on the simulation benchmark. Bars show balanced accuracy (mean $\pm$ std over seeds) for probing the shared label Y, modality-specific factors R and U, and the common signal C, at $k \in \{1, 2, 4, 8, 16, 32\}$. Recovery of R, U, and C is saturated across all k, and Y accuracy varies by less than 0.07 across a $32\times$ range of neighborhood sizes.

for several entries), so the factor-based analysis in main text is the more robust summary; the per-pair maps are included for completeness.

E.7 Exploratory Analysis on Datasets Without Ground Truth

The three benchmarked datasets in the main text all have expert anatomical annotations, which is the exception rather than the rule for newly profiled spatial multi-omics samples. To illustrate how MELON is used in the more typical *discovery* setting, we apply it without any supervision to two additional samples for which no per-spot ground-truth labels are available: a human hippocampus section profiled with paired RNA and ATAC (2,500 spots, 7,666 genes) and a clear-cell renal cell




Figure 10: Mouse E15.5 brain. Spatial usage of four MELON decoder factors with the top gene and top ATAC peak (chromosomal coordinate, abbreviated to `chrN:Mb`) shown above each panel. Color is per-factor robust-clipped (5–95%) usage from the 24-factor pair decoder.




Figure 11: Human lymph node. Spatial usage of four MELON decoder factors, with the top gene for each factor shown. The dominant protein loading collapses to KRT5 across all factors, but the per-spot factor usage still cleanly separates anatomical compartments.




Figure 12: Mouse E13 embryo. Spatial usage of four MELON decoder factors with the top gene–peak pair shown above each panel. Each factor concentrates in a distinct anatomical region, demonstrating that the frozen embedding can be decoded into spatially coherent joint RNA/ATAC programs.

carcinoma tumour section (sample Y7_T) profiled with paired RNA and DNA methylation (2,926 spots, 36,404 genes). The methylation modality is, to our knowledge, not directly supported by any published spatial multi-omics integration baseline, so MELON is run with the same RNA pipeline and a feature-block configuration analogous to the ATAC head; methylation is treated as a continuous secondary modality. Both runs use the default MELON hyperparameters and Leiden clustering on the fused embedding (resolution chosen to give $k{=}7$ for the hippocampus and $k{=}16$ for the tumour, matching the natural compartment count visible in the H&E).

Human hippocampus. Figure 16 compares MELON against the seven baselines on this RNA–ATAC sample. MELON, MISO, and SpatialGlue produce contiguous laminar domains that follow the anatomical curvature of the hippocampal formation, while MOFA+, MEFISTO, and TotalVI yield noisier partitions with substantial within-region speckling. The MELON segmentation cleanly separates a putative white-matter band from the granule-cell layer and CA pyramidal cells, suggesting that the same architecture transfers to a brain region with very different tissue geometry from the E15.5 cortical sections used for benchmarking. We do not report ARI here because no per-spot annotation exists for this sample; the figure should be read as a qualitative cross-method comparison.




Figure 13: Mouse E15.5 brain. Spatial maps for six high-support gene–peak pairs from the decoder. Each row is one pair; columns show (left) RNA expression of the gene, (centre) ATAC accessibility of the peak, and (right) the decoder's joint pair activity. Top pairs include *Prdm8*, *Uncx*, and *Ednrb*, all known developmental transcription factors / receptors.

ccRCC tumour (Y7_T). Figure 17 shows the same comparison on the renal tumour section. Despite methylation being a markedly different secondary modality from chromatin accessibility, MELON produces large, contiguous tumour and stromal domains rather than scattered spot-level




Figure 14: Human lymph node. Spatial maps for six high-support gene–protein pairs from the decoder. Each row is one pair; columns show (left) RNA expression of the gene, (centre) protein (ADT) abundance of the marker, and (right) the decoder's joint pair activity. Selected pairs include canonical immune markers *FCGR3A* (CD16), *CD274* (PD-L1), *SDC1* (CD138, plasma cell), and *PAX5* (B-cell lineage).

noise. Several baselines either collapse to one or two dominant clusters (TotalVI, MOFA+) or produce highly fragmented partitions that do not respect the visible tumour boundary (MultiGate, MEFISTO).




Figure 15: Mouse E13 embryo. Spatial maps for six high-support gene–peak pairs from the decoder. Each row is one pair; columns show (left) RNA expression of the gene, (centre) ATAC accessibility of the peak, and (right) the decoder's joint pair activity across all spots.

The MELON partition exposes a candidate tumour core surrounded by a thin transitional band and several distinct stromal compartments, motivating downstream analysis of the corresponding gene and methylation programs. As with the hippocampus sample, no expert per-spot annotation is available, so this figure is a discovery-mode result rather than a benchmark.




Figure 16: Human hippocampus (RNA + ATAC, 2,500 spots). Spatial domain assignments from MELON and seven multimodal baselines, each at its natural Leiden resolution (k shown above each panel). No per-spot annotation exists for this sample; panel colours are per-method cluster ids and are not aligned across panels.




Figure 17: Clear-cell renal cell carcinoma sample Y7_T (RNA + DNA methylation, 2,926 spots). Spatial domain assignments from MELON and seven multimodal baselines at k=16. Methylation is not a modality directly supported by the baselines; they were run on RNA + a continuous secondary input as a rough analogue. No per-spot annotation exists for this sample; panel colours are per-method cluster ids and are not aligned across panels.

F Simulation Study Details

F.1 Feature Block Architecture

Feature generation. Each signal block is generated as $\boldsymbol{\mu}_k + \boldsymbol{\epsilon}$, where $\boldsymbol{\mu}_k \sim \mathcal{N}(\mathbf{0}, \sigma^2_{\text{centroid}}\mathbf{I})$ is a latent-class centroid sampled once per class, and $\boldsymbol{\epsilon} \sim \mathcal{N}(\mathbf{0}, \sigma^2\mathbf{I})$ is independent per-spot noise.

Table 7: Feature block architecture for each modality. All dimensions sum to 600.

Modality	Block	Dim	σ	Encodes
M1	Shared main	150	0.5	$A^{(1)}$ (region-derived)
	Unique task	150	0.5	U (M1-specific)
	Nuisance	100	0.7	$A^{(3,\text{M1})}$ (confounder)
	Mixed	100	0.7	$R + U+$ pair code (s=3.5)
	Noise	100	1.0	$\mathcal{N}(0, 1)$ i.i.d.
M2	Shared main	150	0.5	$A^{(1)}$ (region-derived)
	Nuisance	150	0.7	$A^{(2,\text{M2})}$ (confounder)
	Synergy attr	100	0.5	C (M2-specific)
	Mixed	100	0.7	$R + C+$ pair code (s=3.5)
	Noise	100	1.0	$\mathcal{N}(0, 1)$ i.i.d.

The mixed block for each modality combines region structure, modality-specific structure, and a cross-modal pair code:

$$\mathbf{x}_i^{(1,\text{mixed})} = 0.5\,\boldsymbol{\mu}_{R_i}^{R} + 0.5\,\boldsymbol{\mu}_{U_i}^{U} + s \cdot \boldsymbol{\mu}_{U_i}^{\text{pair}} + \boldsymbol{\epsilon}_i, \tag{37}$$

$$\mathbf{x}_i^{(2,\text{mixed})} = 0.5\,\boldsymbol{\mu}_{R_i}^{R'} + 0.5\,\boldsymbol{\mu}_{C_i}^{C} + s \cdot \boldsymbol{\mu}_{\pi^{-1}(C_i)}^{\text{pair}} + \boldsymbol{\epsilon}_i', \tag{38}$$

where $s = 3.5$ is the pair-code scale, $\boldsymbol{\mu}_k^{\text{pair}} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ is sampled once per attribute code k, and $\boldsymbol{\epsilon}_i, \boldsymbol{\epsilon}_i' \sim \mathcal{N}(\mathbf{0}, 0.7^2\mathbf{I})$. When $C_i = \pi(U_i)$, both modalities share the *same* pair-code vector $\boldsymbol{\mu}_{U_i}^{\text{pair}}$, creating a cross-modal correlation that enables Y recovery from the concatenation but not from either modality alone.

Latent variable sampling. Region labels R_i are assigned by Voronoi tessellation of K_R=5 seed points sampled uniformly on the grid, followed by T=3 rounds of spatial majority smoothing (8-connected neighbourhood) and stochastic boundary flipping with probability p_{flip}=0.05. The modality-specific attributes U_i and C_i are sampled per region from a region-biased categorical distribution. Within region r, the sampling probability over K=10 attribute codes is

$$\mathbf{p}_r \;=\; (1-\beta)\,\mathbf{u} \;+\; \beta\,\mathbf{w}_r, \qquad \mathbf{w}_r \;\sim\; \text{Dir}(\mathbf{1}_K), \qquad \mathbf{u} \;=\; \tfrac{1}{K}\mathbf{1}_K, \tag{39}$$

where $\beta = 0.12$ is the region-bias weight, $\mathbf{w}_r$ is a region-specific Dirichlet draw, and $\mathbf{u}$ is the uniform prior over the K attribute codes. This produces fine-grained within-region heterogeneity that is only weakly correlated with spatial location, so that neither modality alone nor spatial coordinates are sufficient to recover the synergy label Y defined in Eq. (15).

F.2 Simulation Hyperparameters

F.3 Spatial Structure of Simulated Data

Figure 18 visualizes the spatial distribution of all latent variables on the 44×44 grid. Region labels R form coarse spatial domains from Voronoi tessellation. The modality-specific attributes U and C exhibit finer within-region heterogeneity due to weak region bias ($\beta = 0.12$). The synergy label Y shows no obvious spatial pattern, confirming that it cannot be trivially predicted from location.

F.4 Embedding Visualization

F.5 Cross-Target Probe Comparison

Figure 21 compares balanced accuracy across all methods and prediction targets. External multi-omics methods achieve near-perfect recovery of shared structure (R) and modality-specific attributes (U, C) but uniformly fail on the synergy label Y. MELON is the only method that achieves above-chance performance on Y.

Table 8: Complete simulation hyperparameters.

Category	Parameter	Value
Grid	Size	44×44 (N=1,936)
Latent	Regions K_R	5
	Shared attr. levels K_{A_1}	5
	M1-specific levels K_U	10
	M2-specific levels K_C	10
	Nuisance levels	8
	Region bias β	0.12
Synergy	Match prob p_{match}	0.90
	Non-match prob p_{non}	0.01
	Pair-code scale s	3.5
Noise	σ_{shared}, σ_{task}	0.5
	σ_{nuisance}, σ_{mixed}	0.7
	σ_{noise}	1.0
	σ_{centroid} (main / nuisance)	2.0 / 1.5
Spatial	Smoothing iterations T	3
	Shared flip prob	0.05
	Attribute flip prob	0.05
	Nuisance flip prob	0.08
	Random seed	123




Figure 18: Spatial distribution of latent variables on the 44×44 simulation grid. Region label R forms coarse Voronoi domains; the modality-specific attributes U and C are fine-grained with weak region bias; the synergy label Y shows no apparent spatial structure (orange = Y=1).

F.6 Simulation Validation

We verify four properties of the simulator using 5-fold cross-validated classifiers (logistic regression, random forest, MLP).

Block recoverability. Each feature block should encode its intended latent variable. Informative blocks achieve balanced accuracy ≥ 0.85 on their designated targets, while noise blocks remain at chance (≤ 0.52; Table 9).




Figure 19: Method comparison on synergy label Y (balanced accuracy, best probe per method, 5-fold CV). MELON (full) is the only method that meaningfully exceeds chance, while every simple baseline and external multi-omics method stays at or below 0.58. The *no-space* MELON ablation (lighter accent) collapses to baseline level, showing that the gain depends on spatial conditioning rather than fusion alone. Visualizes the numbers in Table 2.




Figure 20: t-SNE of MELON fused embedding colored by synergy label Y, region R, M1 attribute U, and M2 attribute C.




Figure 21: Balanced accuracy by method and target. External methods recover R, U, C but not Y; MELON is the only method with above-chance Y recovery.

Synergy validity. Y should not be recoverable from a single modality. M1-only and M2-only classifiers achieve balanced accuracy ≤ 0.52, while the concatenation of both modalities reaches 0.632 ± 0.027 (Table 10).

Spatial leakage. Y should not be predictable from coordinates alone. Coordinate-only classifiers achieve 0.521 ± 0.011, confirming negligible spatial leakage (Table 11).

Acceptance. All criteria are met: informative blocks dominate, noise is at chance, Y requires both modalities, and spatial location alone is uninformative about Y.

Table 9: Block recoverability (selected results). Balanced accuracy, 5-fold CV.

Modality	Block $\rightarrow$ Target	Best Model	BalAcc
M1	Shared $\rightarrow R$	LogReg	1.000 ± 0.000
M1	Unique $\rightarrow U$	LogReg	1.000 ± 0.000
M1	Noise $\rightarrow Y$	LogReg	0.520 ± 0.021
M2	Shared $\rightarrow R$	LogReg	1.000 ± 0.000
M2	Synergy attr $\rightarrow C$	LogReg	1.000 ± 0.000
M2	Noise $\rightarrow Y$	RF	0.522 ± 0.011

Table 10: Synergy validity. Predicting Y from raw features; 5-fold CV, best classifier per row.

Input	BalAcc	Macro-F1	AUROC
M1 only	0.518 ± 0.008	0.517 ± 0.008	0.532 ± 0.008
M2 only	0.504 ± 0.017	0.504 ± 0.017	0.520 ± 0.023
M1 + M2	$\mathbf{0.632 \pm 0.027}$	$\mathbf{0.631 \pm 0.028}$	$\mathbf{0.672 \pm 0.039}$

Table 11: Spatial leakage test. Predicting Y from spatial features only; 5-fold CV.

Input	Best Model	BalAcc
Coordinates only	LogReg	0.521 ± 0.011
Neighborhood summary	LogReg	0.496 ± 0.016
Coords + neighborhood	RF	0.513 ± 0.021

F.7 Full Ablation Results




Figure 22: Ablation on synergy label Y (balanced accuracy, 5-fold CV). Bars are coloured by ablation axis. Removing the fusion block or the spatial bias each collapses performance to near chance, while augmentation contributes a smaller but consistent gain.

Table 12: Full ablation on Y. All variants use the best probe (encoder-stage MLP for spatial variants, linear SVM otherwise). 5-fold CV.

Variant	Input	Fusion	Spatial	Aug	BalAcc	Macro-F1	AUROC
MELON full	Multi	✓	✓	0.3	$\mathbf{0.818 \pm 0.045}$	$\mathbf{0.854 \pm 0.034}$	$\mathbf{0.955 \pm 0.021}$
MELON full (no aug)	Multi	✓	✓	0.0	0.711 ± 0.069	0.765 ± 0.068	0.906 ± 0.047
MELON no-fusion	Multi	—	—	0.3	0.547 ± 0.030	0.504 ± 0.018	0.573 ± 0.028
MELON no-space	Multi	✓	—	0.3	0.554 ± 0.018	0.504 ± 0.011	0.576 ± 0.034
MELON no-space (no aug)	Multi	✓	—	0.0	0.516 ± 0.030	0.486 ± 0.013	0.542 ± 0.052
MELON M1-only	M1	✓	✓	0.0	0.532 ± 0.038	0.489 ± 0.024	0.511 ± 0.053
MELON M2-only	M2	✓	✓	0.0	0.509 ± 0.031	0.476 ± 0.015	0.524 ± 0.027

G Limitations

MELON has been evaluated on five spatial multi-omics datasets (three benchmarked, two exploratory) with $n = 2$ modalities; its behaviour under three or more modalities, substantially larger tissue sections, or 3D spatial coordinates remains untested. The fusion transformer uses a single layer with embedding width 128, which limits the model's capacity to saturate the InfoNCE bound (Appendix D), so the recovered PID components are a lower bound rather than an exact decomposition. The label-preserving augmentation assumption underlying the theoretical guarantee holds only approximately for the augmentations we use, and may degrade for modalities with very different noise characteristics. Finally, the k-NN spatial graph is constructed from Euclidean coordinates and does not account for physical barriers such as tissue boundaries or folds, which could introduce spurious spatial edges.

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The abstract and introduction state three contributions (spatial multimodal formulation, the MELON framework, and empirical improvements on three datasets), all of which are supported by the experimental results in Section 4 and Appendix E.

   Guidelines:

   - The answer NA means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A No or NA answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: Limitations are discussed in Appendix G, covering dataset scope, model capacity, augmentation assumptions, and spatial graph construction.

   Guidelines:

   - The answer NA means that the paper has no limitation while the answer No means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory Assumptions and Proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [Yes]

Justification: Proposition 1 is stated with explicit assumptions (expressivity, label-preserving augmentations) and proved in full in Appendix D. Practical caveats where assumptions may fail are also discussed.

Guidelines:

- The answer NA means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental Result Reproducibility**

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes]

Justification: All hyperparameters are listed in Table 6, preprocessing is described in Appendix C.1, datasets are detailed in Appendix B, and the architecture is fully specified in Sections 3 and Appendix C.

Guidelines:

- The answer NA means that the paper does not include experiments.
- If the paper includes experiments, a No answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
  (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
  (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
  (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
  (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [Yes]

   Justification: Code is provided as supplementary material. All datasets used are publicly available and cited with accession identifiers in Appendix B.

   Guidelines:

   - The answer NA means that paper does not include experiments requiring code.
   - Please see the NeurIPS code and data submission guidelines (`https://nips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - While we encourage the release of code and data, we understand that this might not be possible, so "No" is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
   - The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://nips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
   - The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
   - At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
   - Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental Setting/Details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer, etc.) necessary to understand the results?

   Answer: [Yes]

   Justification: Training details including optimizer, learning rate, batch size, epochs, and all hyperparameters are provided in Table 6. Dataset descriptions and preprocessing are in Appendix B and C.1. Hyperparameters were not tuned per dataset.

   Guidelines:

   - The answer NA means that the paper does not include experiments.
   - The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
   - The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment Statistical Significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: [Yes]

   Justification: Experiments report variability across multiple evaluation conditions.

   Guidelines:

   - The answer NA means that the paper does not include experiments.
   - The authors should answer "Yes" if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.

- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g. negative error rates).
- If error bars are reported in tables or plots, The authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments Compute Resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes]

   Justification: Hardware information (CPU/Apple Silicon/MPS or single CUDA GPU) is listed in Table 6.

   Guidelines:

   - The answer NA means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
   - The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code Of Ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes]

   Justification: The research uses publicly available datasets, does not involve human subjects, and poses no foreseeable ethical concerns.

   Guidelines:

   - The answer NA means that the authors have not reviewed the NeurIPS Code of Ethics.
   - If the authors answer No, they should explain the special circumstances that require a deviation from the Code of Ethics.
   - The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader Impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [N/A]

    Justification: This work is foundational research on spatial multi-omics data integration for tissue biology. There is no direct path to negative societal impact.

    Guidelines:

- The answer NA means that there is no societal impact of the work performed.
- If the authors answer NA or No, they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pretrained language models, image generators, or scraped datasets)?

    Answer: [N/A]

    Justification: The method is a domain-specific spatial omics integration tool and does not pose risks for misuse.

    Guidelines:

    - The answer NA means that the paper poses no such risks.
    - Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
    - Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
    - We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

    Answer: [Yes]

    Justification: All datasets and baseline methods are cited with their original publications. Dataset sources and accession identifiers are provided in Appendix B.

    Guidelines:

    - The answer NA means that the paper does not use existing assets.
    - The authors should cite the original paper that produced the code package or dataset.
    - The authors should state which version of the asset is used and, if possible, include a URL.
    - The name of the license (e.g., CC-BY 4.0) should be included for each asset.

- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New Assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: [N/A]

    Justification: No new datasets or pretrained models are released in this submission. Code will be released upon acceptance.

    Guidelines:

    - The answer NA means that the paper does not release new assets.
    - Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
    - The paper should discuss whether and how consent was obtained from people whose asset is used.
    - At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and Research with Human Subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [N/A]

    Justification: This paper does not involve crowdsourcing or research with human subjects.

    Guidelines:

    - The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
    - Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
    - According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional Review Board (IRB) Approvals or Equivalent for Research with Human Subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A]

    Justification: This paper does not involve crowdsourcing or research with human subjects.

    Guidelines:

    - The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.

- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM Usage**

    Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research?

    Answer: [N/A]

    Justification: Large language models were not used as a component of the core research methodology. The MELON framework consists of modality-specific encoders, a neighborhood-aware graph attention module, a fusion transformer, and a PID-guided contrastive objective; none of these components involve LLMs.

    Guidelines:

    - The answer NA means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
    - Please refer to our LLM policy (`https://neurips.cc/Conferences/2026/LLM`) for what should or should not be described.