

# 2017年10月 技术分享会

2017年10月11月27日

# Agenda

- ▶ 《利用npm+gulp构建Bootstrap4 前台项目》  
-- Xiaojun Pan
- ▶ 《Vue.js帮你拿到40万年薪不是梦》  
-- Lingjia Gong & Weizhong Han
- ▶ 《ASP.NET MVC5的那些事》  
-- Vivian Tang & Nancy Zhuang


# 利用npm+gulp构建 Bootstrap4 前台项目

XIAOJUN PAN

2017年10月 技术分享会

# 工具篇

## ► Node.js



npm config set registry http://registry.npm.taobao.org/

# 工具篇

## ► npm

Node.js command prompt

```
C:\Users\xiaojunp>node --version  
v6.11.3
```

```
C:\Users\xiaojunp>npm --version  
3.10.10
```

```
C:\Users\xiaojunp>_
```

## 将 Npm 的源替换成淘宝的源

在墙内久了，难免会碰到撞墙的时候，所幸国内也有众多 NPM 镜像可供选择，在大多数情况下我们可以使用国内的源（比如 [淘宝 NPM 镜像](#)）去替换官方的源以加快下载包的速度。

不过呢，我们在发布自己的包的时候却需要将源修改回官方的 <https://registry.npmjs.org/> 源。

## 修改源地址为淘宝 NPM 镜像

```
npm config set registry http://registry.npm.taobao.org/
```

## 修改源地址为官方源

```
npm config set registry https://registry.npmjs.org/
```


# 工具篇

## ► gulp

```
Node.js command prompt
C:\Users\xiaojun>npm install --global gulp gulp-cli
npm WARN deprecated minimatch@2.0.10: Please update to minimatch 3.0.2 or higher to avoid a RegExp DoS issue
npm WARN deprecated minimatch@0.2.14: Please update to minimatch 3.0.2 or higher to avoid a RegExp DoS issue
npm WARN deprecated graceful-fs@1.2.3: graceful-fs v3.0.0 and before will fail on node releases >= v7.0. Please update to
o graceful-fs@^4.0.0 as soon as possible. Use 'npm ls graceful-fs' to find it in the tree.
D:\nodejs\node_global\gulp -> D:\nodejs\node_global\node_modules\gulp\bin\gulp.js
D:\nodejs\node_global\gulp -> D:\nodejs\node_global\node_modules\gulp-cli\bin\gulp.js
D:\nodejs\node_global
+-- gulp@3.9.1
|   -- liftoff@2.3.0
|   +-- findup-sync@0.4.3
|   |   -- micromatch@2.3.11
|   |   -- kind-of@3.2.2
|   |   -- is-buffer@1.1.6
|   -- resolve@1.5.0
-- gulp-cli@1.4.0
+-- liftoff@2.3.0
|   -- resolve@1.5.0
-- matchdep@1.0.1
  -- micromatch@2.3.11
  -- kind-of@3.2.2
  -- is-buffer@1.1.6
```

# 工具篇

## ► Sumlime Text 3



# 创建项目

## ► npm init


```
选择Node.js command prompt
D:\pxj\Web\bootstrap4\test>npm init
This utility will walk you through creating a package.json file.
It only covers the most common items, and tries to guess sensible defaults.

See `npm help json` for definitive documentation on these fields
and exactly what they do.

Use `npm install <pkg> --save` afterwards to install a package and
save it as a dependency in the package.json file.

Press ^C at any time to quit.
name: (test)
version: (1.0.0)
description:
entry point: (index.js)
test command:
git repository:
keywords:
author: xiaojun pan
license: (ISC) MIT
About to write to D:\pxj\Web\bootstrap4\test\package.json:
{
  "name": "test",
  "version": "1.0.0",
  "description": "",
  "main": "index.js",
  "scripts": {
    "test": "echo \"Error: no test specified\" && exit 1"
  },
  "author": "xiaojun pan",
  "license": "MIT"
}

Is this ok? (yes) yes
```

| 此电脑 > Data (D:) > pxj > Web > bootstrap4 > test  |                  |           |      |
|--|------------------|-----------|------|
| 名称   | 修改日期             | 类型        | 大小   |
|  package.json | 2017/10/27 11:18 | JSON File | 1 KB |

```
package.json
1 {
2   "name": "test",
3   "version": "1.0.0",
4   "description": "",
5   "main": "index.js",
6   "scripts": {
7     "test": "echo \"Error: no test specified\" && exit 1"
8   },
9   "author": "xiaojun pan",
10  "license": "MIT"
11 }
12
```



# 创建项目

## ► npm install bootstrap

### Package managers

Pull in Bootstrap's **source files** into nearly any project with some of the most popular package managers. No matter the package manager, Bootstrap will **require a Sass compiler, Autoprefixer, and postcss-flexbugs-fixes** for a setup that matches our official compiled versions.

### npm

Install Bootstrap in your Node powered apps with [the npm package](#):

```
$ npm install bootstrap@4.0.0-alpha.6
```

Copy

`require('bootstrap')` will load all of Bootstrap's jQuery plugins onto the jQuery object. The `bootstrap` module itself does not export anything. You can manually load Bootstrap's jQuery plugins individually by loading the `/js/*.js` files under the package's top-level directory.

Bootstrap's `package.json` contains some additional metadata under the following keys:

- `sass` - path to Bootstrap's main [Sass](#) source file
- `style` - path to Bootstrap's non-minified CSS that's been precompiled using the default settings (no customization)

### Node.js command prompt

```
D:\pxj\Web\bootstrap4\test>npm install bootstrap@4.0.0-alpha.6 --save
test@1.0.0 D:\pxj\Web\bootstrap4\test
-- bootstrap@4.0.0-alpha.6
+-- jquery@3.2.1
   -- tether@1.4.0

npm WARN test@1.0.0 No description
npm WARN test@1.0.0 No repository field.
```

### D:\pxj\Web\bootstrap4\test\package.json (blogen, test) - Sublime Text (UNREGISTERED)

File Edit Selection Find View Goto Tools Project Preferences Help

#### FOLDERS

- ▶ blogen
- ▼ test
  - ▶ node\_modules
    - ▶ bootstrap
    - ▶ jquery
    - ▶ tether
  - /\* package.json

```
1 {
2   "name": "test",
3   "version": "1.0.0",
4   "description": "",
5   "main": "index.js",
6   "scripts": {
7     "test": "echo \"Error: no test specified\" && exit 1"
8   },
9   "author": "xiaojun pan",
10  "license": "MIT",
11  "dependencies": {
12    "bootstrap": "^4.0.0-alpha.6"
13  }
14 }
15
```

# 创建项目

## ► npm install jquery font-awesome

```
Node.js command prompt

D:\pxj\Web\bootstrap4\test>npm install jquery font-awesome --save
test@1.0.0 D:\pxj\Web\bootstrap4\test
+-- font-awesome@4.7.0
+-- jquery@3.2.1

npm WARN test@1.0.0 No description
npm WARN test@1.0.0 No repository field.
```

```
D:\pxj\Web\bootstrap4\test\package.json (blogen, test) - Sublime Text (UNREGISTERED)
File Edit Selection Find View Goto Tools Project Preferences Help

FOLDERS
  ► blogen
  ▼ test
    ► node_modules
      ► bootstrap
      ► font-awesome
      ► jquery
      ► tether
    /* package.json


package.json
1 {
2   "name": "test",
3   "version": "1.0.0",
4   "description": "",
5   "main": "index.js",
6   "scripts": {
7     "test": "echo \"Error: no test specified\" && exit 1"
8   },
9   "author": "xiaojun pan",
10  "license": "MIT",
11  "dependencies": {
12    "bootstrap": "^4.0.0-alpha.6",
13    "font-awesome": "^4.7.0",
14    "jquery": "^3.2.1"
15  }
16 }
17
```

# 创建项目

## ► npm install jquery font-awesome

# 创建项目

## ► gulp



# 创建项目

## ► gulp

```
1  const gulp = require('gulp');
2  const browserSync = require('browser-sync').create();
3  const sass = require('gulp-sass');
4
```

```
5  // Compile Sass & Inject Into browser
6  gulp.task('sass',function(){
7    return gulp.src(['node_modules/bootstrap/scss/bootstrap.scss', 'src/scss/*.scss'])
8      .pipe(sass())
9      .pipe(gulp.dest("src/css"))
10     .pipe(browserSync.stream());
11  });
12
13  // Move JS Files to src/js
14  gulp.task('js',function(){
15    return gulp.src(['node_modules/bootstrap/dist/js/bootstrap.min.js','node_modules/jquery/dist/jquery.min.js','node_modules/po
16      .pipe(gulp.dest("src/js"))
17      .pipe(browserSync.stream());
18  });
19
```

# 创建项目

## ► gulp


```
32 // Move Fonts Folder to src/fonts
33 gulp.task('fonts', function(){
34     return gulp.src('node_modules/font-awesome/fonts/*')
35         .pipe(gulp.dest("src/fonts"));
36 });
37
38 // Move Fonts Awesome CSS to src/css
39 gulp.task('fa', function(){
40     return gulp.src('node_modules/font-awesome/css/font-awesome.min.css')
41         .pipe(gulp.dest("src/css"));
42 });
```

```
23 // Watch Sass & Server
24 gulp.task('server', ['sass'], function(){
25     browserSync.init({
26         server: "./src"
27     });
28     gulp.watch(['node_modules/bootstrap/scss/bootstrap.scss', 'src/scss/*.scss'], ['sass']);
29     gulp.watch("src/*.html").on('change', browserSync.reload);
30 });
```

```
51
52 gulp.task('default', ['js', 'server', 'fa', 'fonts', 'ckeditor']);
53
```

# 创建项目

## ► gulp



```
1 {
2   "name": "test",
3   "version": "1.0.0",
4   "description": "",
5   "main": "index.js",
6   "scripts": {
7     "start": "gulp"
8   },
9   "author": "xiaojun pan",
10  "license": "MIT",
11  "dependencies": {
12    "bootstrap": "4.0.0-alpha.6",
13    "font-awesome": "^4.7.0",
14    "jquery": "^3.2.1"
15  },
16  "devDependencies": {
17    "browser-sync": "^2.18.13",
18    "gulp": "^3.9.1",
19    "gulp-sass": "^3.1.0"
20  }
21 }
```

## ► HTML

```
18 <script src= js/bootstrap.min.js ></script>
19 </body>
20 </html>
```



# 创建项目

## ► npm start

```
D:\pxj\Web\bootstrap4\test>
D:\pxj\Web\bootstrap4\test>
D:\pxj\Web\bootstrap4\test>npm start

> test@1.0.0 start D:\pxj\Web\bootstrap4\test
> gulp

[13:25:26] Using gulpfile D:\pxj\Web\bootstrap4\test\gulpfile.js
[13:25:26] Starting 'js'...
[13:25:26] Starting 'sass'...
[13:25:26] Starting 'fa'...
[13:25:26] Starting 'fonts'...
[13:25:26] Starting 'ckeditor'...
[13:25:26] Finished 'ckeditor' after 16 ms
[13:25:26] Finished 'js' after 141 ms
[13:25:27] Finished 'fa' after 161 ms
[13:25:27] Finished 'fonts' after 217 ms
[13:25:27] Finished 'sass' after 288 ms
[13:25:27] Starting 'server'...
[13:25:27] Finished 'server' after 33 ms
[13:25:27] Starting 'default'...
[13:25:27] Finished 'default' after 6.95 μs
[Browsersync] Access URLs:
-----
    Local: http://localhost:3000
  External: http://172.18.130.49:3000
-----
    UI: http://localhost:3001
  UI External: http://172.18.130.49:3001
-----
[Browsersync] Serving files from: ./src
```

# 创建项目

## ► Reference


<https://www.w3cschool.cn/>



# Bootstrap4 sample

► Github

<https://github.com/tydaniel/bootstrap4>



The screenshot shows the GitHub repository page for 'tydaniel / bootstrap4'. The repository has 2 commits, 1 branch, 0 releases, and 1 contributor. It includes a table of files: 'blogen', 'bs4starter', 'looplab', and 'mizuxe', all with the description 'bootstrap4 sample project' and a commit time of '4 hours ago'. A blue banner at the bottom encourages adding a README.

tydaniel / bootstrap4

Unwatch 1 Unstar 1 Fork 0

Code Issues 0 Pull requests 0 Projects 0 Wiki Insights Settings

No description, website, or topics provided. [Add topics](#) [Edit](#)

2 commits 1 branch 0 releases 1 contributor

Branch: master New pull request Create new file Upload files Find file Clone or download

| tydaniel bootstrap4 sample project |                           | Latest commit 9e67fb6 4 hours ago |
|------------------------------------|---------------------------|-----------------------------------|
| blogen                             | bootstrap4 sample project | 4 hours ago                       |
| bs4starter                         | bootstrap4 sample project | 4 hours ago                       |
| looplab                            | bootstrap4 sample project | 4 hours ago                       |
| mizuxe                             | bootstrap4 sample project | 4 hours ago                       |

Help people interested in this repository understand your project by adding a README. [Add a README](#)

© 2017 GitHub, Inc. [Terms](#) [Privacy](#) [Security](#) [Status](#) [Help](#) [Contact GitHub](#) [API](#) [Training](#) [Shop](#) [Blog](#) [About](#)

Thanks

感謝いたします！

谢谢侬！