

# Package ‘GeneticMediation’

May 7, 2020

**Type** Package

**Title** An R Package for Causal Mediation Analysis of ROSMAP Data

**Version** 1.1.0.9000

**License** GPL-3

**URL** <https://github.com/tydarnell/GeneticMediation>,  
<https://tydarnell.github.io/GeneticMediation>

**Author** Ty Darnell [aut, cre]

**Maintainer** Ty Darnell <tydarnell@gmail.com>

**Description** Provides methods for cleaning and processing data from the ROSMAP study  
and preparing it for causal mediation analysis

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.1.0

**Depends** R (>= 3.6.0)

**biocViews**

**Imports** data.table,  
IRanges,  
mediation,  
purrr,  
readr,  
stats,  
utils

**Suggests** dplyr,  
knitr,  
magrittr,  
rmarkdown,  
testthat,  
tibble,  
tidyselect

**VignetteBuilder** knitr

## R topics documented:

check_data . . . . .	2
chr_numeric . . . . .	3
clean_data . . . . .	3
combine_data_spc . . . . .	3
combine_data_spg . . . . .	4
last_to_first . . . . .	4
lenu . . . . .	4
make_folder . . . . .	5
match_all . . . . .	5
match_snp_peak . . . . .	5
med.res_spc . . . . .	6
med.res_spg . . . . .	6
mediation_spg . . . . .	6
med_all_spc . . . . .	7
med_chr_spc . . . . .	7
med_chr_spg . . . . .	8
med_table_spc . . . . .	8
med_table_spg . . . . .	9
merge_csv . . . . .	9
setup_folders . . . . .	9
sig_chr_spg . . . . .	10
snp_peak_bychr . . . . .	10
sum_zero . . . . .	10
transpose_readcount . . . . .	11
<b>Index</b>	<b>12</b>

---

check_data	<i>Check Data</i>
------------	-------------------

---

### Description

Checks if the data is in the data folder

### Usage

check\_data()

---

chr_numeric	<i>Chromosome Numeric</i>
-------------	---------------------------

---

**Description**

Convert chromosome names from character to numeric. Useful when sorting a dataframe by chromosome number.

**Usage**

```
chr_numeric(Chr)
```

**Arguments**

Chr	a character column or vector of chromosome names
-----	--

---

clean_data	<i>Clean Data</i>
------------	-------------------

---

**Description**

Clean snp.info, peak.info data and save as data/chipseq.RData

**Usage**

```
clean_data(snp.path, peak.path)
```

**Arguments**

snp.path	path to SNP information dataframe
peak.path	path to Peak annotation dataframe

---

combine_data_spc	<i>Combine Data SNP-Peak-Clinical</i>
------------------	---------------------------------------

---

**Description**

SNP-Peak-Clinical data: combine projid, SNPs, PCs, membership, age, gender, peaks, and outcome data for a chromosome

**Usage**

```
combine_data_spc(chr)
```

**Arguments**

chr	chromosome name
-----	-----------------

---

combine_data_spg	<i>Combine Data SNP-Peak-Gene</i>
------------------	-----------------------------------

---

**Description**

SNP-Peak-Gene Data: combine projid, SNPs, PCs, membership, age, gender, peaks, gene and outcome data for a chromosome.

**Usage**

```
combine_data_spg(chr)
```

**Arguments**

chr	chromosome name
-----	-----------------

---

last_to_first	<i>Last to First</i>
---------------	----------------------

---

**Description**

Make the last column the first column in a dataframe

**Usage**

```
last_to_first(df)
```

**Arguments**

df	dataframe
----	-----------

---

lenu	<i>Length Unique</i>
------	----------------------

---

**Description**

Get the length of unique values in a vector

**Usage**

```
lenu(x)
```

**Arguments**

x	vector
---	--------

---

make_folder	<i>Make Folder</i>
-------------	--------------------

---

**Description**

Make a folder only if the folder does not already exist

**Usage**

```
make_folder(path)
```

**Arguments**

path	folder path
------	-------------

---

match_all	<i>Match SNPs Peaks All Chromosomes</i>
-----------	---

---

**Description**

Match SNPs and Peaks in all chromosomes and return dataframe of matches

**Usage**

```
match_all(snp.info, peak.info, chrs)
```

**Arguments**

snp.info	SNP information
peak.info	Peak information
chrs	character vector of chromosome names

---

match_snp_peak	<i>Match SNPs and Peaks</i>
----------------	-----------------------------

---

**Description**

Match SNPs and Peaks in a chromosome

**Usage**

```
match_snp_peak(snp.info, peak.info)
```

**Arguments**

snp.info	SNP information for chr
peak.info	Peak information chr

---

med.res_spc	<i>SNP-Peak-Clinical Mediation Data Prep</i>
-------------	--

---

**Description**

Prepare a chromosome of SNP-Peak-Clinical data for mediation analysis and save as "data/spc.res/res\_chr.RData"

**Usage**

```
med.res_spc(chr, all_matches)
```

**Arguments**

chr	chromosome name
all_matches	dataframe of SNP-Peak matches for all chromosomes

---

med.res_spg	<i>SNP-Peak-Gene Mediation Data Prep</i>
-------------	--

---

**Description**

Prepare a chromosome SNP-Peak-Gene data for mediation analysis data and save as "data/spg.res/res\_chr.RData"

**Usage**

```
med.res_spg(chr, med.data, matches)
```

**Arguments**

chr	chromosome name
med.data	gene mediation data
matches	SNP-Peak-Gene matches dataframe

---

mediation_spg	<i>Mediation SNP-Peak-Gene</i>
---------------	--------------------------------

---

**Description**

Mediation analysis one SNP-Peak-Gene match

**Usage**

```
mediation_spg(med.res.data, match_row, simulations = 1000)
```

**Arguments**

med.res.data	gene mediation data
match_row	row in match dataframe: col1 SNP, col2 Peak, col3 Gene
simulations	number of simulations, 1000 by default

---

med_all_spc	<i>SNP-Peak-Clinical Mediation Table</i>
-------------	--

---

**Description**

Create a table of SNP-Peak-Clinical mediation results for all chromosomes

**Usage**

```
med_all_spc(chrs, covar, simulations)
```

**Arguments**

chrs	character vector of chromosome names
covar	covariates string, each covariate separated by +
simulations	number of simulations to run

---

med_chr_spc	<i>SNP-Peak-Clinical Mediation Table Chromosome</i>
-------------	---

---

**Description**

Create SNP-Peak-Clinical mediation table for SNP-Peak matches in a chromosome

**Usage**

```
med_chr_spc(matches, med.res.data, covar, simulations)
```

**Arguments**

matches	SNP-Peak matches dataframe for a chromosome
med.res.data	mediation data
covar	covariates string, separate covariates with +
simulations	number of simulations to run

---

med_chr_spg	<i>SNP-Peak-Gene Mediation Table Chromosome</i>
-------------	---

---

### Description

Create a SNP-Peak-Gene mediation table for a chromosome

### Usage

```
med_chr_spg(chr, gene_matches, covar, simulations)
```

### Arguments

chr	chromosome name
gene_matches	list of peak-SNP matches for each gene
covar	covariates string, separate covariates with +
simulations	number of simulations to run

---

med_table_spc	<i>SNP-Peak-Clinical Mediation Table</i>
---------------	--

---

### Description

Create SNP-Peak-Clinical mediation table for a SNP-Peak match

### Usage

```
med_table_spc(med.res.data, match_row, covar, simulations)
```

### Arguments

med.res.data	mediation data
match_row	row in match dataframe, should have 2 columns
covar	covariates character variable, separate covariates with +
simulations	number of simulations to run



---

med_table_spg	<i>SNP-Peak-Gene Mediation Table</i>
---------------	--------------------------------------

---

**Description**

Create a mediation table for one SNP-Peak-Gene match

**Usage**

```
med_table_spg(med.res.data, match_row, covar, simulations)
```

**Arguments**

med.res.data	gene mediation data
match_row	row in match dataframe: col1 SNP, col2 Peak, col3 Gene
covar	covariates character variable, separate covariates with +
simulations	number of simulations to run

---

merge_csv	<i>Merge CSV</i>
-----------	------------------

---

**Description**

merge multiple csv files into a single dataframe

**Usage**

```
merge_csv(path)
```

**Arguments**

path	path to folder containing csv files
------	-------------------------------------

---

setup_folders	<i>Setup Folders</i>
---------------	----------------------

---

**Description**

Creates data, data/mediator, results folders

**Usage**

```
setup_folders()
```

---

sig_chr_spg	<i>Significant SNP-Peak-Gene</i>
-------------	----------------------------------

---

**Description**

Returns summary of mediation results for a chr with significant results

**Usage**

```
sig_chr_spg(chr)
```

**Arguments**

chr	chromosome name
-----	-----------------

---

snp_peak_bychr	<i>SNPs and Peaks by Chromosome</i>
----------------	-------------------------------------

---

**Description**

save snp.info, peak.info for each chromosome as "data/chipseq/chipseq\_chr.RData"

**Usage**

```
snp_peak_bychr(chrs, snps, peaks)
```

**Arguments**

chrs	Character vector of chromosomes names
snps	SNP information dataframe
peaks	Peak information dataframe

---

sum_zero	<i>Sum Zero</i>
----------	-----------------

---

**Description**

Get names of columns that have a sum of zero

**Usage**

```
sum_zero(df)
```

**Arguments**

df	dataframe
----	-----------

---

transpose_readcount	<i>Transpose Readcount</i>
---------------------	----------------------------

---

**Description**

Read in and transpose ChIP-seq Readcount dataframe and match project id

**Usage**

```
transpose_readcount(readcount.path)
```

**Arguments**

readcount.path ChIP-seq readcount dataframe file path

# Index

## \*Topic **dataprep**

- [clean\\_data](#), [3](#)
- [combine\\_data\\_spc](#), [3](#)
- [combine\\_data\\_spg](#), [4](#)
- [med.res\\_spc](#), [6](#)
- [med.res\\_spg](#), [6](#)
- [snp\\_peak\\_bychr](#), [10](#)
- [transpose\\_readcount](#), [11](#)

## \*Topic **helper**

- [chr\\_numeric](#), [3](#)
- [last\\_to\\_first](#), [4](#)
- [lenu](#), [4](#)
- [make\\_folder](#), [5](#)
- [merge\\_csv](#), [9](#)
- [sum\\_zero](#), [10](#)

## \*Topic **match**

- [match\\_all](#), [5](#)
- [match\\_snp\\_peak](#), [5](#)

## \*Topic **mediation**

- [med\\_all\\_spc](#), [7](#)
- [med\\_chr\\_spc](#), [7](#)
- [med\\_chr\\_spg](#), [8](#)
- [med\\_table\\_spc](#), [8](#)
- [med\\_table\\_spg](#), [9](#)
- [mediation\\_spg](#), [6](#)
- [sig\\_chr\\_spg](#), [10](#)

## \*Topic **setup**

- [check\\_data](#), [2](#)
- [setup\\_folders](#), [9](#)

## \*Topic **spc**

- [clean\\_data](#), [3](#)
- [combine\\_data\\_spc](#), [3](#)
- [med.res\\_spc](#), [6](#)
- [med\\_all\\_spc](#), [7](#)
- [med\\_chr\\_spc](#), [7](#)
- [med\\_table\\_spc](#), [8](#)

## \*Topic **spg**

- [combine\\_data\\_spg](#), [4](#)
- [med.res\\_spg](#), [6](#)
- [med\\_chr\\_spg](#), [8](#)
- [med\\_table\\_spg](#), [9](#)
- [mediation\\_spg](#), [6](#)
- [sig\\_chr\\_spg](#), [10](#)

- [check\\_data](#), [2](#)
- [chr\\_numeric](#), [3](#)
- [clean\\_data](#), [3](#)
- [combine\\_data\\_spc](#), [3](#)
- [combine\\_data\\_spg](#), [4](#)

- [last\\_to\\_first](#), [4](#)
- [lenu](#), [4](#)

- [make\\_folder](#), [5](#)
- [match\\_all](#), [5](#)
- [match\\_snp\\_peak](#), [5](#)
- [med.res\\_spc](#), [6](#)
- [med.res\\_spg](#), [6](#)
- [med\\_all\\_spc](#), [7](#)
- [med\\_chr\\_spc](#), [7](#)
- [med\\_chr\\_spg](#), [8](#)
- [med\\_table\\_spc](#), [8](#)
- [med\\_table\\_spg](#), [9](#)
- [mediation\\_spg](#), [6](#)
- [merge\\_csv](#), [9](#)

- [setup\\_folders](#), [9](#)
- [sig\\_chr\\_spg](#), [10](#)
- [snp\\_peak\\_bychr](#), [10](#)
- [sum\\_zero](#), [10](#)

- [transpose\\_readcount](#), [11](#)