

BATTERY PASSPORT - RESEARCH PROTOTYPE

Not a certified battery passport. Fields are oriented on Regulation (EU) 2023/1542, Annex XIII.

Generated (UTC): 2026-09-30T16:31:37Z

1. Battery and data-source provenance

Battery ID: B0005

Data source: NASA

Provenance: NASA public dataset, processed by this project

Model: base XGBoost-fusion model (validated routing) (encoder: old_v1)

2. State of health

State of health: 71.7 %

90% interval: 66.8 - 76.6 %

90% conformal interval calibrated on known sources

3. Expected remaining life

Expected remaining life: 2 cycles (to 80% SOH)

90% interval: 0 - 484 cycles

4. Cycle count

Cycles available for this battery in this app: 168 Assessed cycle: 168

5. Trust status of this assessment

No distribution shift detected (this is not a guarantee)

Nearest known source: NASA score nll_min = -16.46 (flagged if ≥ -5.52)

Stated detection rate: the check flagged 81.9% of batteries from a source it had never seen and wrongly flagged 11.0% of batteries from known sources (leave-one-source-out over 16 sources). It is weakest for mich, NASA, snl. About 1 in 5 unfamiliar batteries are not detected; check against a measured capacity when possible.

Typical SOH error (MAE, points): 3.2 for the nearest known source vs about 5.9 on an unseen source

Guarantee: none - this is a screening check.

6. Disclaimer

RESEARCH PROTOTYPE - NOT A CERTIFIED BATTERY PASSPORT. This document is generated by a university research project (CellSense). It is not issued under, and makes no claim of compliance with, Regulation (EU) 2023/1542. The numbers are model estimates with the stated uncertainty and limits; they are not measurements and must not be used for safety-critical, commercial or legal decisions without an independent measured capacity test.

Routing was selected on held-out data, so it is a deployment choice, not an unbiased test result.