CPE301 – SPRING 2019

Design Assignment 4A

Student Name: Tyler Gardenhire

Student #: 8000450294

Student Email: gardenhi@unlv.nevada.edu

Primary Github address: gardenhi@unlv.nevada.edu

Directory: https://github.com/tylergardenhire/submission_projects.git

Submit the following for all Labs:

1. In the document, for each task submit the modified or included code (only) with highlights and justifications of the modifications. Also, include the comments.

- Use the previously create a Github repository with a random name (no CPE/301, Lastname, Firstname). Place all labs under the root folder ESD301/DA, sub-folder named LABXX, with one document and one video link file for each lab, place modified asm/c files named as LabXX-TYY.asm/c.
- 3. If multiple asm/c files or other libraries are used, create a folder LabXX-TYY and place these files inside the folder.
- 4. The folder should have a) Word document (see template), b) source code file(s) and other include files, c) text file with youtube video links (see template).

1. COMPONENTS LIST AND CONNECTION BLOCK DIAGRAM w/ PINS

Atmel Studio 7 w/ AVR assembly and simulator, Atmega328p board, DC motor, and potentiometer used.





Fig. 1. DC Motor



2. INITIAL/MODIFIED/DEVELOPED CODE OF TASK 1/A

```
Task 1 C code:
```


```
#define F_CPU 8000000UL
#include <avr/io.h>
#include <util/delay.h>
#define ENABLE 6
#define MTR 1 1
#define MTR 2 2
#define SW (PINC&(1<<1))</pre>
int main()
{
       PORTC |= (1<<1);
                                                  //Enable pull-up
       DDRB |= 0b00000111;
                                                  //PB0, PB1, and PB2 as outputs
       PORTD &= ~(1<<ENABLE);
                                                  //Enable = 0
       PORTB &= ~(1<<MTR_1);
                                                  //MTR_1 = 0
       PORTB &= \sim(1<<MTR_2);
                                                  //MTR_2 = 0
       DDRD |= (1<<6);
                                                         //OCOA as output
```

```
OCR0A = 50;
                                                                 //Fast PWM, non-inverted
       TCCR0A = (1<<COM0A1) | (1<<WGM01) | (1<<WGM00);
       TCCR0B = 0x02;
                                                          //N = 8
       while(1)
       {
              PORTD |= (1<<ENABLE);
                                                //Enable = 1
              if(SW != 0)
                                                          //if PD7 is high
              {
                                                                 //Clockwise Rotation
                     _delay_ms(20);
PORTB |= (1<<MTR_1); //MTR_1 = 1
                      PORTB &= (\sim(1<<MTR_2)); //MTR_2 = 0
              }
              else
              {
                                                                 //0ff
                      _delay_ms(20);
                                               //MTR_1 = 0
//MTR_2 = 0
                      PORTB &= (~(1<<MTR_1));
                      PORTB &= (~(1<<MTR_2));
              _delay_ms(1000);
              if (OCR0A > 250)
                     OCR0A = 50;
              else
                     OCR0A = OCR0A + 25;
       }
}
```

3. DEVELOPED MODIFIED CODE OF TASK 2/A from TASK 1/A

N/A


4. SCHEMATICS



5. SCREENSHOTS OF EACH TASK OUTPUT (ATMEL STUDIO OUTPUT)

N/A

6. SCREENSHOT OF EACH DEMO (BOARD SETUP)



7. VIDEO LINKS OF EACH DEMO

https://youtu.be/gByFVQdgRBs

8. GITHUB LINK OF THIS DA

https://github.com/tylergardenhire/submission_projects.git

Student Academic Misconduct Policy

http://studentconduct.unlv.edu/misconduct/policy.html

"This assignment submission is my own, original work".

TYLER GARDENHIRE