

[301] Tabular Data

Tyler Caraza-Harter

Learning Objectives Today

CSV format

- purpose
- syntax
- comparison to spreadsheet

Chapter 14 of Sweigart,
to (and including) “Reading Data
from Reader Objects in a for Loop”

Reading CSV files

- without header
- with header
- type casting

Today's Outline

Spreadsheets


CSVs

Reading a CSV to a list of lists

Coding examples

Spreadsheets (e.g., Excel)

Spreadsheets are tables of cells, organized by rows and columns




A screenshot of a Microsoft Excel spreadsheet titled "Search Sheet". The ribbon menu is visible at the top, showing "Home" as the active tab. The main area displays a table with 13 rows and 6 columns. The columns are labeled "name", "year", "mph", "damage", and "deaths". The first row contains the column headers. The data includes entries for Baker (1950, 120 mph, 2550000 damage, 38 deaths), Camille (1969, 175 mph, 1.43B damage, 259 deaths), Eloise (1975, 125 mph, 560M damage, 80 deaths), Frederic (1979, 130 mph, 1770000000 damage, 12 deaths), Elena (1985, 125 mph, 1300000000 damage, 9 deaths), Danny (1997, 80 mph, 100000000 damage, 4 deaths), Ivan (2004, 165 mph, 26100000000 damage, 92 deaths), Dennis (2005, 150 mph, 3980000000 damage, 76 deaths), Katrina (2005, 175 mph, 125B damage, 1836 deaths), Michael (2018, 155 mph, 25100000000 damage, 72 deaths), Carol (1954, 115 mph, 462000000 damage, 72 deaths), and Donna (1960, 145 mph, 980000000 damage, 439 deaths). The bottom of the screen shows the status bar with "Ready" and zoom controls.

	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Elena	1985	125	1300000000	9	
7	Danny	1997	80	100000000	4	
8	Ivan	2004	165	26100000000	92	
9	Dennis	2005	150	3980000000	76	
10	Katrina	2005	175	125B	1836	
11	Michael	2018	155	25100000000	72	
12	Carol	1954	115	462000000	72	
13	Donna	1960	145	980000000	439	

Spreadsheets (e.g., Excel)

Spreadsheets are tables of cells, organized by rows and columns

cells




A screenshot of a Microsoft Excel spreadsheet titled "hurricanes". The table has 13 rows and 6 columns. The columns are labeled "name", "year", "mph", "damage", "deaths", and an empty column F. The "name" column is bolded. Row 1 contains the header labels. Rows 2 through 13 contain data for various hurricanes. The "name" column for row 4 (Eloise) is highlighted with a red box. The "damage" column for row 3 (Camille) is highlighted with a red box. The "year" column for row 7 (Danny) is highlighted with a red box. The "deaths" column for row 10 (Katrina) is highlighted with a red box. The "name" column for row 13 (Donna) is highlighted with a green box. The "damage" column for row 13 (Donna) is also highlighted with a green box. The "name" column for row 1 (Baker) is also highlighted with a green box.

	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Elena	1985	125	1300000000	9	
7	Danny	1997	80	100000000	4	
8	Ivan	2004	165	26100000000	92	
9	Dennis	2005	150	3980000000	76	
10	Katrina	2005	175	125B	1836	
11	Michael	2018	155	25100000000	72	
12	Carol	1954	115	462000000	72	
13	Donna	1960	145	980000000	439	

Spreadsheets (e.g., Excel)

Spreadsheets are tables of cells, organized by rows and columns

columns




The screenshot shows a Microsoft Excel spreadsheet titled "Search Sheet". The ribbon menu is visible at the top, with "Home" selected. The table consists of 13 rows and 6 columns, labeled A through F. The columns are: name, year, mph, damage, and deaths. The first row contains column headers. The "name" column is highlighted with a green border, while the other four columns are highlighted with red borders. The data in the columns is as follows:

	name	year	mph	damage	deaths
1	Baker	1950	120	2550000	38
2	Camille	1969	175	1.43B	259
3	Eloise	1975	125	560M	80
4	Frederic	1979	130	1770000000	12
5	Elena	1985	125	1300000000	9
6	Danny	1997	80	100000000	4
7	Ivan	2004	165	26100000000	92
8	Dennis	2005	150	3980000000	76
9	Katrina	2005	175	125B	1836
10	Michael	2018	155	25100000000	72
11	Carol	1954	115	462000000	72
12	Donna	1960	145	980000000	439

Spreadsheets (e.g., Excel)

Spreadsheets are tables of cells, organized by rows and columns

rows




A screenshot of a Microsoft Excel spreadsheet titled "Search Sheet". The ribbon menu is visible at the top, showing "Home" as the active tab. The formula bar shows "A1" and "name". The main area contains a table of data with the following columns: name, year, mph, damage, and deaths. The first row is a header, and the subsequent 13 rows are data entries. The rows are highlighted with red boxes. The table has a green border. The bottom of the screen shows the status bar with "Ready" and various icons.

	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Elena	1985	125	1300000000	9	
7	Danny	1997	80	100000000	4	
8	Ivan	2004	165	26100000000	92	
9	Dennis	2005	150	3980000000	76	
10	Katrina	2005	175	125B	1836	
11	Michael	2018	155	25100000000	72	
12	Carol	1954	115	462000000	72	
13	Donna	1960	145	980000000	439	

Spreadsheets (e.g., Excel)

Spreadsheets are tables of cells, organized by rows and columns



A screenshot of a Microsoft Excel spreadsheet titled "Search Sheet". The ribbon menu is visible at the top, showing tabs for Home, Insert, Draw, and Page Layout. The Home tab is selected. The formula bar shows the cell A1 and the text "name". The main area contains a table of data. The first row is highlighted with a red border and labeled "header" in red text to its left. The table has columns for index (1), name, year, mph, damage, and deaths. The data shows various hurricanes from 1950 to 2018, with values ranging from 38 to 1836 deaths.

1	name	year	mph	damage	deaths
2	Baker	1950	120	2550000	38
3	Camille	1969	175	1.43B	259
4	Eloise	1975	125	560M	80
5	Frederic	1979	130	1770000000	12
6	Elena	1985	125	1300000000	9
7	Danny	1997	80	100000000	4
8	Ivan	2004	165	26100000000	92
9	Dennis	2005	150	3980000000	76
10	Katrina	2005	175	125B	1836
11	Michael	2018	155	25100000000	72
12	Carol	1954	115	462000000	72
13	Donna	1960	145	980000000	439

Spreadsheets (e.g., Excel)


Spreadsheets often allow different **data types**

text numbers

	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Elena	1985	125	1300000000	9	
7	Danny	1997	80	100000000	4	
8	Ivan	2004	165	26100000000	92	
9	Dennis	2005	150	3980000000	76	
10	Katrina	2005	175	125B	1836	
11	Michael	2018	155	25100000000	72	
12	Carol	1954	115	462000000	72	
13	Donna	1960	145	980000000	439	

Spreadsheets (e.g., Excel)

Spreadsheets often allow different **fonts**



The screenshot shows a Microsoft Excel spreadsheet titled "Search Sheet". The ribbon menu is visible at the top, with "Home" selected. The font dropdown on the ribbon is set to bold. The table below contains 13 rows of data about hurricanes. The first row, labeled "name", is bolded, while the second row, "Baker", is in regular font. The columns are labeled "name", "year", "mph", "damage", and "deaths". The "damage" column contains large numerical values, some with commas and some with underscores.

	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Elena	1985	125	1300000000	9	
7	Danny	1997	80	100000000	4	
8	Ivan	2004	165	26100000000	92	
9	Dennis	2005	150	3980000000	76	
10	Katrina	2005	175	125B	1836	
11	Michael	2018	155	25100000000	72	
12	Carol	1954	115	462000000	72	
13	Donna	1960	145	980000000	439	

Spreadsheets (e.g., Excel)

Spreadsheets often support **multiple sheets**

The screenshot shows a Microsoft Excel spreadsheet titled "Search Sheet". The ribbon menu is visible at the top, with "Home" selected. The main area displays a table with 13 rows of data. The columns are labeled "name", "year", "mph", "damage", and "deaths". The first row contains the column headers. The data includes entries for Baker (1950), Camille (1969), Eloise (1975), Frederic (1979), Elena (1985), Danny (1997), Ivan (2004), Dennis (2005), Katrina (2005), Michael (2018), Carol (1954), and Donna (1960). The "damage" column contains large values like "2550000" and "1770000000". The "deaths" column contains values like "38", "259", "80", "12", "9", "4", "92", "76", "1836", "72", "72", and "439". The bottom of the screen shows the standard Windows taskbar with icons for Start, Task View, File Explorer, Edge, and Settings. The status bar at the bottom right shows "100%".

1	name	year	mph	damage	deaths
2	Baker	1950	120	2550000	38
3	Camille	1969	175	1.43B	259
4	Eloise	1975	125	560M	80
5	Frederic	1979	130	1770000000	12
6	Elena	1985	125	1300000000	9
7	Danny	1997	80	100000000	4
8	Ivan	2004	165	26100000000	92
9	Dennis	2005	150	3980000000	76
10	Katrina	2005	175	125B	1836
11	Michael	2018	155	25100000000	72
12	Carol	1954	115	462000000	72
13	Donna	1960	145	980000000	439

more tables of data

Excel Files


Extension: .xlsx

Format: binary

Excel Files

Extension: .xlsx

Format: **binary** ➤ just 0's and 1's, not human-readable characters.
Need special software...




```
ty-mac:lec-15$ cat hurricanes.xlsx
P!b?h^[Content_Types].xml ?(????N?0E?H?C?-J5??*Q>?é]c[?ii????B?j7??
?{2??h?nm???R
????U^/????%??rZY?1__?f??q??R4D?AJ?h>????V?ξ
?Z?9????NV
?8ñ????ji){^??-I?"{?v^?P!XS)bR?r??K?s(?3?`c?0?????????M4?????ZEk+?|
\|z?(??P??6h_-[@?!???Pk???2n?}??L??? ??%??????dN"m,?ÅD097*?~??Φ
8?0?c|n???E??????B??!$}?????;{???[????2???P!?U0#?L

_rels/.rels ?(???M0?0
??9L?3?sbg_!|?l!??USh9i?b?r:"y_dl??D???|-N??R"4?2?G?%??Z?4?"y?7  é??
??????P!?>???xl/_rels/workbook.xml.rels ?(???RMK?0?T~?I?????$JT?G?~??
??<???!??4??;#?w????qu*&r?Fq???v?????GJy(v??*????K??#F??D???.W      ?
?=??Z?MY?b???BS??????ç? ???
??0w?v?t/"?UN)?&!
3~??]X?K/o?y???v?5???+??zl?;o??b???G?????
?S?>??,?8??(%???"D??4j?0u2j
s??MY?~??S葵 ??? ?)f???C????y?? Iy??!!+??E??fMy?k???
??K?5=|?t ??G)?s墙 ?U??tB??)???,???f????????P!u???
```

Excel Files

Extension: .xlsx

Format: **binary** ➤ just 0's and 1's, not human-readable characters.
Need special software...



```
ty-mac:lec-15$ cat hurricanes.xlsx
P!b?h^[Content_Types].xml ?(????N?0E?H?C?-J5??*Q>?é]c[?ii????B?j7??
?{2??h?nm???R
????U^/????%??rZY?1__?f??q??R4D?AJ?h>????V? 
?Z?9????NV
?8?j????ji){^??-I?"{?v^?P!XS)bR?r??K?s(?3?`c?0?????????M4?????Z?k+?|_
\|z?(??P??6h_-[@?!???Pk???2n?}??L??? ??%??????dN"m,?ÅD097*?~?? 
8?0?c|n???E??????B??!$}?????;{???[?????2???P!?U0#?L
_rels/.rels ?(???M0?0
??9L?3?sbg_!|?l!??USh9i?b?r:"y_dl?D???|-N??R"4?2?G?%??Z?4?"y?7  ??
??????P!?>???xl/_rels/workbook.xml.rels ?(???RMK?0?T~?I?????$ T?G?~??
??<???!??4??;#?w????qu*&r?Fq???v?????GJy(v??*????K??#F??D???.W      ?
?=??Z?MY?b???BS??????ct ???
??0w?v?t/"?UN)?&
3~??]X?K/o?y???v?5???+??zl?;o??b???G?????
?s?>??,?8??(%???"D??4j?0u2j
s??MY?、??S葵 ??? ?)f???C????y?? Iy??!+??E??fMy?k???
??K?5=|?t ??G)?s墙 ?U??tB??)???,??f???????P!u???
```

Writing code to read data from Excel files is tricky, unless you use special modules

Today's Outline

Spreadsheets

CSVs

Reading a CSV to a list of lists

Coding examples

CSVs

CSV is a simple data format that stands for
Comma-Separated Values


CSVs are like simple spreadsheets

- organize cells of data into rows and columns
 - only one sheet per file
 - only holds strings
 - no way to specify font, borders, cell size, etc
- you'll do lots of type casting/conversion!**
- 

CSV Files

Extension: .csv

Format: plain text ➤ just open in any editor (notepad, textedit, idle, etc) and you'll be able to read it



A screenshot of a Mac OS X terminal window titled "lec-16 — bash — 46x21". The window shows the command "ls" followed by two files: "h10.csv" and "h10.xlsx". Below this, the command "cat h10.csv" is run, and its output is displayed. The output is a CSV file containing data about hurricanes. The columns are labeled "name", "year", "mph", "damage", and "deaths". The data rows are: Baker, 1950, 120, 2550000, 38; Camille, 1969, 175, 1.43B, 259; Eloise, 1975, 125, 560M, 80; Frederic, 1979, 130, 1770000000, 12; Elena, 1985, 125, 1300000000, 9; Danny, 1997, 80, 100000000, 4; Ivan, 2004, 165, 2610000000, 92; Dennis, 2005, 150, 3980000000, 76; Katrina, 2005, 175, 125B, 1836.

```
ty-mac:lec-16$ ls
h10.csv      h10.xlsx
ty-mac:lec-16$ cat h10.csv
name,year,mph,damage,deaths
Baker,1950,120,2550000,38
Camille,1969,175,1.43B,259
Eloise,1975,125,560M,80
Frederic,1979,130,1770000000,12
Elena,1985,125,1300000000,9
Danny,1997,80,100000000,4
Ivan,2004,165,2610000000,92
Dennis,2005,150,3980000000,76
Katrina,2005,175,125B,1836
ty-mac:lec-16$
```

Writing code that understands CSV files is easy

Basic Syntax

Table

Name	Date	Time	Status	Latitude	Longitude	WindSpeed	Ocean
HEIDI	19671019	1200	TD	20.5N	54.0W	25	Atlantic
OLAF	19850822	0	TD	12.9N	102.2W	25	Pacific
TINA	19920917	1200	TD	10.4N	98.5W	25	Pacific
EMMY	19760820	1200	TD	14.0N	48.0W	20	Atlantic

Corresponding CSV

Name,Date,Time,Status,Latitude,Longitude,WindSpeed,Ocean
HEIDI,19671019,1200, TD,20.5N,54.0W,25,Atlantic
OLAF,19850822,0, TD,12.9N,102.2W,25,Pacific
TINA,19920917,1200, TD,10.4N,98.5W,25,Pacific
EMMY,19760820,1200, TD,14.0N,48.0W,20,Atlantic

Basic Syntax

Table

Name	Date	Time	Status	Latitude	Longitude	WindSpeed	Ocean
HEIDI	19671019	1200	TD	20.5N	54.0W	25	Atlantic
OLAF	19850822	0	TD	12.9N	102.2W	25	Pacific
TINA	19920917	1200	TD	10.4N	98.5W	25	Pacific
EMMY	19760820	1200	TD	14.0N	48.0W	20	Atlantic

Corresponding CSV

Name,Date,Time,Status,Latitude,Longitude,WindSpeed,Ocean
HEIDI,19671019,1200, TD,20.5N,54.0W,25,Atlantic
OLAF,19850822,0, TD,12.9N,102.2W,25,Pacific
TINA,19920917,1200, TD,10.4N,98.5W,25,Pacific
EMMY,19760820,1200, TD,14.0N,48.0W,20,Atlantic

Each row is a line of the file

Basic Syntax

Table

Name	Date	Time	Status	Latitude	Longitude	WindSpeed	Ocean
HEIDI	19671019	1200	TD	20.5N	54.0W	25	Atlantic
OLAF	19850822	0	TD	12.9N	102.2W	25	Pacific
TINA	19920917	1200	TD	10.4N	98.5W	25	Pacific
EMMY	19760820	1200	TD	14.0N	48.0W	20	Atlantic

Corresponding CSV

Name,Date,Time,Status,Latitude,Longitude,WindSpeed,Ocean
HEIDI,19671019,1200, TD,20.5N,54.0W,25,Atlantic
OLAF,19850822,0, TD,12.9N,102.2W,25,Pacific
TINA,19920917,1200, TD,10.4N,98.5W,25,Pacific
EMMY,19760820,1200, TD,14.0N,48.0W,20,Atlantic

Each row is a line of the file

Basic Syntax

Table

Name	Date	Time	Status	Latitude	Longitude	WindSpeed	Ocean
HEIDI	19671019	1200	TD	20.5N	54.0W	25	Atlantic
OLAF	19850822	0	TD	12.9N	102.2W	25	Pacific
TINA	19920917	1200	TD	10.4N	98.5W	25	Pacific
EMMY	19760820	1200	TD	14.0N	48.0W	20	Atlantic

Corresponding CSV

Name,Date,Time,Status,Latitude,Longitude,WindSpeed,Ocean
HEIDI,19671019,1200,TD,20.5N,54.0W,25,Atlantic
OLAF,19850822,0,TD,12.9N,102.2W,25,Pacific
TINA,19920917,1200,TD,10.4N,98.5W,25,Pacific
EMMY,19760820,1200,TD,14.0N,48.0W,20,Atlantic

Cells...

Basic Syntax

Table

Name	Date	Time	Status	Latitude	Longitude	WindSpeed	Ocean
HEIDI	19671019	1200	TD	20.5N	54.0W	25	Atlantic
OLAF	19850822	0	TD	12.9N	102.2W	25	Pacific
TINA	19920917	1200	TD	10.4N	98.5W	25	Pacific
EMMY	19760820	1200	TD	14.0N	48.0W	20	Atlantic

Corresponding CSV

Name,Date,Time,Status,Latitude,Longitude,WindSpeed,Ocean
HEIDI,19671019,1200,TD,20.5N,54.0W,25,Atlantic
OLAF,19850822,0,TD,12.9N,102.2W,25,Pacific
TINA,19920917,1200,TD,10.4N,98.5W,25,Pacific
EMMY,19760820,1200,TD,14.0N,48.0W,20,Atlantic

... are separated by commas

Basic Syntax

Table

Name	Date	Time	Status	Latitude	Longitude	WindSpeed	Ocean
HEIDI	19671019	1200	TD	20.5N	54.0W	25	Atlantic
OLAF	19850822	0	TD	12.9N	102.2W	25	Pacific
TINA	19920917	1200	TD	10.4N	98.5W	25	Pacific
EMMY	19760820	1200	TD	14.0N	48.0W	20	Atlantic

We call characters that act as separators “**delimiters**”

Newlines delimit rows

The comma is a delimiter between cells in a row

EMMY,19760820,1200, TD,14.0N,48.0W,20,Atlantic

... are separated by commas

Advanced Syntax

We won't go into details here, but there are some complexities

Motivation for more complicated syntax

- what if a cell contains a newline?
- what if we want a comma inside a cell?
- what if a cell contains a quote?
- what if we want to use different delimiters between rows/cells?

usually better to use a general CSV module than roll your own

Today's Outline

Spreadsheets


CSVs

Reading a CSV to a list of lists

Coding examples

Data Management

1. spreadsheet in Excel



A screenshot of the Microsoft Excel application interface. The ribbon at the top shows tabs for Home, Insert, Draw, Page Layout, Share, and Comments. The Home tab is selected. Below the ribbon, there are toolbars for Clipboard, Font, Alignment, and Number. The main area shows a table with data in rows 1 through 6. Row 1 contains column headers: 'name' (A1), 'year' (B1), 'mph' (C1), 'damage' (D1), and 'deaths' (E1). Rows 2 through 5 contain data for Hurricane Baker, Camille, Eloise, and Frederic respectively. Row 6 contains data for Hurricane Elena. The 'damage' column for Elena has a value of 13000000000, which is displayed with commas as thousands separators.

	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	17700000000	12	
6	Elena	1985	125	13000000000	9	

Data Management

1. spreadsheet in Excel

	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Elena	1985	125	1300000000	9	

Save As
.CSV

2. CSV file saved somewhere

```
name,year,mph,damage,deaths
Baker,1950,120,2550000,38
Camille,1969,175,1.43B,259
Eloise,1975,125,560M,80
Frederic,1979,130,1770000000,12
```

Data Management

3. Python Program

1. spreadsheet in Excel

	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Elena	1985	125	1300000000	9	

Save As
.CSV


2. CSV file saved somewhere

```
name,year,mph,damage,deaths
Baker,1950,120,2550000,38
Camille,1969,175,1.43B,259
Eloise,1975,125,560M,80
Frederic,1979,130,1770000000,12
```

Data Management

3. Python Program

1. spreadsheet in Excel



	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Elena	1985	125	1300000000	9	

Save As
.CSV

2. CSV file saved somewhere

```
name,year,mph,damage,deaths
Baker,1950,120,2550000,38
Camille,1969,175,1.43B,259
Eloise,1975,125,560M,80
Frederic,1979,130,1770000000,12
```

list of lists

[

```
[ "name", "year", ... ],  
[ "Baker", "1950", ... ],
```

...


]

Parsing Code

we'll come
back to this

Data Management

1. spreadsheet in Excel



	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Frena	1985	125	1300000000	9	

Save As
.CSV

2. CSV file saved somewhere

```
name,year,mph,damage,deaths
Baker,1950,120,2550000,38
Camille,1969,175,1.43B,259
Eloise,1975,125,560M,80
Frederic,1979,130,1770000000,12
```

3. Python Program

Analysis Code

`rows[1][0] → ???`

[]

["name", "year", ...],
["Baker", "1950", ...],

...

Parsing Code

Data Management

1. spreadsheet in Excel

	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Elena	1985	125	1300000000	9	

Save As
.CSV

2. CSV file saved somewhere

```
name,year,mph,damage,deaths
Baker,1950,120,2550000,38
Camille,1969,175,1.43B,259
Eloise,1975,125,560M,80
Frederic,1979,130,1770000000,12
```

3. Python Program

Analysis Code

```
rows[1][0] → "Baker"
```

list of lists

[

```
[ "name", "year", ... ],  
[ "Baker", "1950", ... ],
```

...

]

Parsing Code

Data Management

1. spreadsheet in Excel

	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Elena	1985	125	1300000000	9	

Save As
.CSV

2. CSV file saved somewhere

```
name,year,mph,damage,deaths
Baker,1950,120,2550000,38
Camille,1969,175,1.43B,259
Eloise,1975,125,560M,80
Frederic,1979,130,1770000000,12
```

3. Python Program

Analysis Code

rows[3][1] → ????

[

["name", "year", ...],
["Baker", "1950", ...],

...

]

Parsing Code

Data Management

1. spreadsheet in Excel

	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Elena	1985	125	1300000000	9	

Save As
.CSV

2. CSV file saved somewhere

```
name,year,mph,damage,deaths
Baker,1950,120,2550000,38
Camille,1969,175,1.43B,259
Eloise,1975,125,560M,80
Frederic,1979,130,1770000000,12
```

3. Python Program

Analysis Code

```
rows[3][1] → "1975"
```

list of lists

[...]


```
[ "name", "year", ... ],  
[ "Baker", "1950", ... ],
```

...

Parsing Code

Data Management

1. spreadsheet in Excel



	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Elena	1985	125	1300000000	9	

Save As
.CSV

2. CSV file saved somewhere

```
name,year,mph,damage,deaths
Baker,1950,120,2550000,38
Camille,1969,175,1.43B,259
Eloise,1975,125,560M,80
Frederic,1979,130,1770000000,12
```

3. Python Program

Analysis Code

`rows[1][-1] → ???`

list of lists

[

`["name", "year", ...],
["Baker", "1950", ...],`


...

]

Parsing Code

Data Management

1. spreadsheet in Excel



	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Frena	1985	125	1300000000	9	

Save As
.CSV

2. CSV file saved somewhere

```
name,year,mph,damage,deaths
Baker,1950,120,2550000,38
Camille,1969,175,1.43B,259
Eloise,1975,125,560M,80
Frederic,1979,130,1770000000,12
```

3. Python Program

Analysis Code

`rows[1][-1] → "38"`

list of lists

[

`["name", "year", ...],
["Baker", "1950", ...],`


...

]

Parsing Code

Data Management

1. spreadsheet in Excel



	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Frena	1985	125	1300000000	9	

Save As
.CSV

2. CSV file saved somewhere

```
name,year,mph,damage,deaths
Baker,1950,120,2550000,38
Camille,1969,175,1.43B,259
Eloise,1975,125,560M,80
Frederic,1979,130,1770000000,12
```

3. Python Program

Analysis Code

`rows[0][-2] → ???`

list of lists

[

`["name", "year", ...],
["Baker", "1950", ...],`


...

]

Parsing Code

Data Management

1. spreadsheet in Excel



	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Elena	1985	125	1300000000	9	

Save As
.CSV

2. CSV file saved somewhere

```
name,year,mph,damage,deaths
Baker,1950,120,2550000,38
Camille,1969,175,1.43B,259
Eloise,1975,125,560M,80
Frederic,1979,130,1770000000,12
```

3. Python Program

Analysis Code

`rows[0][-2] → "damage"`

list of lists

[

`["name", "year", ...],`
`["Baker", "1950", ...],`

...

]

Parsing Code

Data Management

1. spreadsheet in Excel

	A	B	C	D	E	F
1	name	year	mph	damage	deaths	
2	Baker	1950	120	2550000	38	
3	Camille	1969	175	1.43B	259	
4	Eloise	1975	125	560M	80	
5	Frederic	1979	130	1770000000	12	
6	Flora	1985	125	1300000000	9	

Save As
.CSV

2. CSV file saved somewhere

```
name,year,mph,damage,deaths
Baker,1950,120,2550000,38
Camille,1969,175,1.43B,259
Eloise,1975,125,560M,80
Frederic,1979,130,1770000000,12
```

3. Python Program

Analysis Code

`rows[0][-2] → "damage"`

list of lists

```
[ ["name", "year", ...],  
  ["Baker", "1950", ...],  
  ... ]
```

Parsing Code

What does this look like?

Example Copied From Sweigart Ch 14

Code

```
import csv
exampleFile = open('example.csv')
exampleReader = csv.reader(exampleFile)
exampleData = list(exampleReader)
```


example.csv

4/5/2015 13:34,Apples,73
4/5/2015 3:41,Cherries,85
4/6/2015 12:46,Pears,14
4/8/2015 8:59,Oranges,52
4/10/2015 2:07,Apples,152
4/10/2015 18:10,Bananas,23
4/10/2015 2:40,Strawberries,98

Example Copied From Sweigart Ch 14

Code

```
import csv  
exampleFile = open('example.csv')  
exampleReader = csv.reader(exampleFile)  
exampleData = list(exampleReader)  
exampleData
```



list of
lists

```
[['4/5/2015 13:34', 'Apples', '73'], ['4/5/2015 3:41', 'Cherries', '85'],  
 ['4/6/2015 12:46', 'Pears', '14'], ['4/8/2015 8:59', 'Oranges', '52'],  
 ['4/10/2015 2:07', 'Apples', '152'], ['4/10/2015 18:10', 'Bananas', '23'],  
 ['4/10/2015 2:40', 'Strawberries', '98']]
```

Example Copied From Sweigart Ch 14

```
import csv
exampleFile = open('example.csv')
exampleReader = csv.reader(exampleFile)
exampleData = list(exampleReader)
exampleData
```

let's generalize this to a function
(don't need to know exactly how the code
works, though we will eventually)

Example Copied From Sweigart Ch 14

```
import csv  
exampleFile = open('example.csv')  
exampleReader = csv.reader(exampleFile)  
exampleData = list(exampleReader)  
exampleData
```

output

let's generalize this to a function
(don't need to know exactly how the code
works, though we will eventually)

Example Copied From Sweigart Ch 14

```
def process_csv():
    import csv
    exampleFile = open('example.csv')
    exampleReader = csv.reader(exampleFile)
    exampleData = list(exampleReader)
    exampleData
```

1. move code to a function

Example Copied From Sweigart Ch 14

```
import csv

def process_csv():
    import csv
    exampleFile = open('example.csv')
    exampleReader = csv.reader(exampleFile)
    exampleData = list(exampleReader)
    exampleData
```

2. move out imports

Example Copied From Sweigart Ch 14

```
import csv

def process_csv():
    import csv
    exampleFile = open('example.csv')
    exampleReader = csv.reader(exampleFile)
    exampleData = list(exampleReader)
    return exampleData
```

3. return data to get it out of the function

Example Copied From Sweigart Ch 14

```
import csv

def process_csv():
    import csv
    exampleFile = open('example.csv')
    exampleReader = csv.reader(exampleFile)
    exampleData = list(exampleReader)
    return exampleData
```

4. generalize input

Example Copied From Sweigart Ch 14

```
import csv

def process_csv(filename):
    import csv
    exampleFile = open(filename)
    exampleReader = csv.reader(exampleFile)
    exampleData = list(exampleReader)
    return exampleData
```

4. generalize input

Example Copied From Sweigart Ch 14

```
import csv  
  
# copied from https://automatetheboringstuff.com/chapter14/  
def process_csv(filename):  
    import csv  
    exampleFile = open(filename)  
    exampleReader = csv.reader(exampleFile)  
    exampleData = list(exampleReader)  
    return exampleData
```

Reminder!
cite code
copied online

5. cite the code

Example Copied From Sweigart Ch 14

```
import csv

# copied from https://automatetheboringstuff.com/chapter14/
def process_csv(filename):
    exampleFile = open(filename, encoding="utf-8")
    exampleReader = csv.reader(exampleFile)
    exampleData = list(exampleReader)
    return exampleData
```

keep this handy for copy/paste

Today's Outline

Spreadsheets

CSVs

Reading a CSV to a list of lists

Coding examples

Demo 1: Restaurant Location Lookup


Goal: given a restaurant name, give x,y coordinates for it

Input:

- Restaurant name (and a CSV file)

Output:

- X, Y coordinates



Example:

```
prompt> python rlookup.py subway
```

```
x=1, y=0
```

```
prompt> python rlookup.py mcdonalds
```

```
x=4, y=-3
```

Demo 2: Nearest Restaurant Search


Goal: given a location, find the nearest restaurant

Input:

- X, Y coordinates (and a CSV file)

Output:

- nearest restaurant



Example:

```
prompt> python nearest.py 4,-4
```

McDonalds

```
prompt> python nearest.py -2,0
```


The Sett

Demo 3: Hurricane Column Dump

Goal: column name, print that data for all hurricanes

Input:

- column name (and a CSV file)



Output:

- data in given column, associated with name

Example:

```
prompt> python dump.py hurricanes.csv year
```

Baker: 1950

Camille: 1969

Eloise: 1975


...

Demo 4: Hurricanes per Year

Goal: column name, print that data for all hurricanes

Input:

- none typed (only a CSV file)



Output:

- the number of hurricanes in each year

Example:

```
prompt> python yearly.py
```

```
1967: 23
```

```
1968: 29
```

```
2969: 15
```

```
...
```

Demo 5: Hurricane Names and Stereotypes



CrossMark
click for updates

Female hurricanes are deadlier than male hurricanes

Kiju Jung^{a,1}, Sharon Shavitt^{a,b,1}, Madhu Viswanathan^{a,c}, and Joseph M. Hilbe^d

^aDepartment of Business Administration and ^bDepartment of Psychology, Institute of Communications Research, and Survey Research Laboratory, and ^cWomen and Gender in Global Perspectives, University of Illinois at Urbana-Champaign, Champaign, IL 61820; and ^dDepartment of Statistics, T. Denny Sanford School of Social and Family Dynamics, Arizona State University, Tempe, AZ 85287-3701

Edited* by Susan T. Fiske, Princeton University, Princeton, NJ, and approved May 14, 2014 (received for review February 13, 2014)

Do people judge hurricane risks in the context of gender-based expectations? We use more than six decades of death rates from US hurricanes to show that feminine-named hurricanes cause significantly more deaths than do masculine-named hurricanes. Laboratory experiments indicate that this is because hurricane names lead to gender-based expectations about severity and this, in turn, guides respondents' preparedness to take protective action. This finding indicates an unfortunate and unintended consequence of the gendered naming of hurricanes, with important implications for policymakers, media practitioners, and the general public concerning hurricane communication and preparedness.

gender stereotypes | implicit bias | risk perception | natural hazard communication | bounded rationality

violence and destruction (23, 24). We extend these findings to hypothesize that the anticipated severity of a hurricane with a masculine name (Victor) will be greater than that of a hurricane with a feminine name (Victoria). This expectation, in turn, will affect the protective actions that people take. As a result, a hurricane with a feminine vs. masculine name will lead to less protective action and more fatalities.

Archival Study

To test this hypothesis, we used archival data on actual fatalities caused by hurricanes in the United States (1950–2012). Ninety-four Atlantic hurricanes made landfall in the United States during this period (25). Nine independent coders who were blind to the hypothesis rated the masculinity vs. femininity of historical hurricane names on two items (1 = very masculine, 11 = very

what would it take to try to replicate this study?