

# SEACAR Discrete Water Quality Analysis: Field Surface Salinity

Last compiled on 30 May, 2022

## Contents

<b>Libraries</b>	<b>1</b>
<b>File Import</b>	<b>2</b>
<b>Data Filtering and Data Impacted by Specific Value Qualifiers</b>	<b>2</b>
<b>Managed Area Statistics</b>	<b>5</b>
<b>Monitoring Location Statistics</b>	<b>7</b>
<b>Seasonal Kendall Tau Analysis</b>	<b>8</b>
<b>Appendix I: Scatter Plot of Entire Dataset</b>	<b>11</b>
<b>Appendix II: Dataset Summary Box Plots</b>	<b>13</b>
<b>Appendix III: Excluded Managed Areas</b>	<b>19</b>
<b>Appendix IV: Managed Area Trendlines</b>	<b>21</b>
<b>Appendix V: Managed Area Summary Box Plots</b>	<b>45</b>

## Libraries

Loads libraries used in the script. The inclusion of `scipen` option limits how frequently R defaults to scientific notation.

```
library(knitr)
library(data.table)
library(dplyr)
library(lubridate)
library(ggplot2)
library(ggpubr)
library(scales)
library(EnvStats)
library(tidyr)
options(scipen=999)
opts_chunk$set(warning=FALSE, message=FALSE)
```

## File Import

Imports file that is determined in the WC\_Discrete\_parameter\_ReportCompile.R script.

The command `fread` is used because of its improved speed while handling large data files. Only columns that are used by the script are imported from the file, and are designated in the `select` input.

The script then gets the name of the parameter as it appears in the data file, units of the parameter, sets the `SampleDate` as a date object, and creates various scales of the date to be used by plotting functions.

```
data <- fread(file_in, sep="|", header=TRUE, stringsAsFactors=FALSE,
               select=c("ManagedAreaName", "ProgramID", "ProgramName",
                       "ProgramLocationID", "SampleDate", "Year", "Month",
                       "RelativeDepth", "ActivityType", "ParameterName",
                       "ResultValue", "ParameterUnits", "ValueQualifier",
                       "SEACAR_QAQCFlagCode", "Include"), na.strings="")  
  
parameter <- unique(data$ParameterName)  
unit <- unique(data$ParameterUnits)  
data$SampleDate <- as.Date(data$SampleDate)  
data$YearMonth <- paste0(data$Month, "-", data$Year)  
data$YearMonthDec <- data$Year + ((data$Month-0.5) / 12)  
data$DecDate <- decimal_date(data$SampleDate)
```

## Data Filtering and Data Impacted by Specific Value Qualifiers

Most data filtering is performed on export from the database, and is indicated by the `Include` variable. `Include` values of 1 indicate the data should be used for analysis, values of 0 indicate the data should not be used for analysis. Documentation on the database filtering is provided here: SEACAR Documentation-Analysis Filters and Calculations.docx

The filtering that is performed by the script at this point removes rows that are missing values for `ResultValue`, and only keeps data that is measured at the relative depth (surface, bottom, etc.) and activity type (field or sample) of interest. This is partly handled on export with the `RelativeDepth` variable, but there are some measurements that are considered both surface and bottom based on measurement depth and total depth. By default, these are marked as `Surface` for `RelativeDepth` and receive a `SEACAR_QAQCFlag` indicator of 12Q. Data passes the filtering process if it is from the correct depth and has an `Include` value of 1. The script also only looks at data of the desired `ActivityType` which indicates whether it was measured in the field (`Field`) or in the lab (`Sample`).

After the initial filtering, a second filter variable is created to determine whether enough time is represented in the managed area, which is that each managed area has 10 year or more of unique year entries for observation that pass the initial filter. If data passes the first set of filtering criteria and the time criteria, they are used in the analysis.

After filtering, the amount of data impacted by the H (for dissolved oxygen & pH in program 476), I, Q, S (for Secchi depth), and U value qualifiers. A variable is also created that determines if scatter plot points should be a different color based on value qualifiers of interest.

```
if(depth=="Bottom"){  
  data$RelativeDepth[grep("12Q", data$SEACAR_QAQCFlagCode[  
    data$RelativeDepth=="Surface"])] <- "Bottom"  
}
```

```

data$Include <- as.logical(data$Include)
data$Include[grep("H", data$ValueQualifier[data$ProgramID==476])] <- TRUE
data <- data[!is.na(data$ResultValue),]

if(param_name!="Secchi_Depth"){
  data <- data[!is.na(data$RelativeDepth),]
  data <- data[data$RelativeDepth==depth,]
}

if(length(grep("Blank", data$ActivityType))>0){
  data <- data[-grep("Blank", data$ActivityType),]
}

if(param_name=="Chlorophyll_a_uncorrected_for_pheophytin" |
  param_name=="Salinity" | param_name=="Turbidity"){
  data <- data[grep(activity, data$ActivityType[!is.na(data$ActivityType)]),]
}

if(param_name=="Water_Temperature"){
  data <- data[data$ResultValue>=-2,]
} else{
  data <- data[data$ResultValue>=0,]
}

data <- merge.data.frame(MA_All[,c("AreaID", "ManagedAreaName")],
                         data, by="ManagedAreaName", all=TRUE)

MA_Summ <- data %>%
  group_by(AreaID, ManagedAreaName) %>%
  summarize(ParameterName=parameter,
            RelativeDepth=depth,
            ActivityType=activity,
            N_Data=length(ResultValue[Include==TRUE & !is.na(ResultValue)]),
            N_Years=length(unique(Year[Include==TRUE & !is.na(Year)])),
            EarliestYear=min(Year[Include==TRUE]),
            LatestYear=max(Year[Include==TRUE]),
            SufficientData=ifelse(N_Data>0 & N_Years>=10, TRUE, FALSE))

data <- merge.data.frame(data, MA_Summ[,c("ManagedAreaName", "SufficientData")],
                         by="ManagedAreaName")

data$Use_In_Analysis <- ifelse(data$Include==TRUE & data$SufficientData==TRUE,
                                 TRUE, FALSE)

MA_Summ <- MA_Summ %>%
  select(AreaID, ManagedAreaName, ParameterName, RelativeDepth, ActivityType,
         SufficientData, everything())
MA_Summ <- as.data.frame(MA_Summ[order(MA_Summ$ManagedAreaName), ])

total <- length(data$Include)
pass_filter <- length(data$Include[data$Include==TRUE])

```

```

count_H <- length(grep("H", data$ValueQualifier[data$ProgramID==476]))
perc_H <- 100*count_H/length(data$ValueQualifier)

count_I <- length(grep("I", data$ValueQualifier))
perc_I <- 100*count_I/length(data$ValueQualifier)

count_Q <- length(grep("Q", data$ValueQualifier))
perc_Q <- 100*count_Q/length(data$ValueQualifier)

count_S <- length(grep("S", data$ValueQualifier))
perc_S <- 100*count_S/length(data$ValueQualifier)

count_U <- length(grep("U", data$ValueQualifier))
perc_U <- 100*count_U/length(data$ValueQualifier)

data$VQ_Plot <- data$ValueQualifier

inc_H <- ifelse(param_name=="pH" | param_name=="Dissolved_Oxygen" |
                 param_name=="Dissolved_Oxygen_Saturation", TRUE, FALSE)

if (inc_H==TRUE){
  data$VQ_Plot <- gsub("[^HU]+", "", data$VQ_Plot)
  data$VQ_Plot <- gsub("UH", "HU", data$VQ_Plot)
  data$VQ_Plot[na.omit(data$ProgramID!=476)] <- gsub("[^U]+", "", data$VQ_Plot[na.omit(data$ProgramID!=476)])
  data$VQ_Plot[data$VQ_Plot==""] <- NA

  cat(paste0("Number of Measurements: ", total,
             ", Number Passed Filter: ", pass_filter, "\n",
             "Program 476 H Codes: ", count_H, " (", round(perc_H, 6), "%)\n",
             "I Codes: ", count_I, " (", round(perc_I, 6), "%)\n",
             "Q Codes: ", count_Q, " (", round(perc_Q, 6), "%)\n",
             "U Codes: ", count_U, " (", round(perc_U, 6), "%)"))

} else if (param_name=="Secchi_Depth") {
  count_S <- length(grep("S", data$ValueQualifier))
  perc_S <- 100*count_S/length(data$ValueQualifier)
  data$VQ_Plot <- gsub("[^SU]+", "", data$VQ_Plot)
  data$VQ_Plot <- gsub("US", "SU", data$VQ_Plot)
  data$VQ_Plot[data$VQ_Plot==""] <- NA
  cat(paste0("Number of Measurements: ", total,
             ", Number Passed Filter: ", pass_filter, "\n",
             "I Codes: ", count_I, " (", round(perc_I, 6), "%)\n",
             "Q Codes: ", count_Q, " (", round(perc_Q, 6), "%)\n",
             "S Codes: ", count_S, " (", round(perc_S, 6), "%)\n",
             "U Codes: ", count_U, " (", round(perc_U, 6), "%)"))

} else{
  data$VQ_Plot <- gsub("[^U]+", "", data$VQ_Plot)
  data$VQ_Plot[data$VQ_Plot==""] <- NA
  cat(paste0("Number of Measurements: ", total,
             ", Number Passed Filter: ", pass_filter, "\n",
             "I Codes: ", count_I, " (", round(perc_I, 6), "%)\n",
             "Q Codes: ", count_Q, " (", round(perc_Q, 6), "%)\n",
             "S Codes: ", count_S, " (", round(perc_S, 6), "%)\n",
             "U Codes: ", count_U, " (", round(perc_U, 6), "%)"))
}

```

```

    "Q Codes: ", count_Q, " (", round(perc_Q, 6), "%)\n",
    "U Codes: ", count_U, " (", round(perc_U, 6), "%))"
}

## Number of Measurements: 566820, Number Passed Filter: 566291
## I Codes: 0 (0%)
## Q Codes: 0 (0%)
## U Codes: 0 (0%)

data_summ <- data %>%
  group_by(AreaID, ManagedAreaName) %>%
  summarize(ParameterName=parameter,
            RelativeDepth=depth,
            ActivityType=activity,
            N_Total=length(ResultValue),
            N_AnalysisUse=length(ResultValue[SufficientData==TRUE]),
            N_H=length(grep("H", data$ValueQualifier[data$ProgramID==476])),
            perc_H=100*N_H/length(data$ValueQualifier),
            N_I=length(grep("I", data$ValueQualifier)),
            perc_I=100*N_I/length(data$ValueQualifier),
            N_Q=length(grep("Q", data$ValueQualifier)),
            perc_Q=100*N_Q/length(data$ValueQualifier),
            N_S=length(grep("S", data$ValueQualifier)),
            perc_S=100*N_S/length(data$ValueQualifier),
            N_U=length(grep("U", data$ValueQualifier)),
            perc_U=100*N_U/length(data$ValueQualifier))

data_summ <- as.data.table(data_summ[order(data_summ$ManagedAreaName), ])
fwrite(data_summ, paste0(out_dir, "/", param_name, "_", activity, "_", depth,
                        "_DataSummary.csv"), sep=",")

rm(data_summ)
MA_Include <- MA_Summ$ManagedAreaName [MA_Summ$SufficientData==TRUE &
                                         MA_Summ$N_Data<2000000]
n <- length(MA_Include)
MA_Exclude <- MA_Summ [MA_Summ$N_Years<10 & MA_Summ$N_Years>0,]
MA_Exclude <- MA_Exclude[,c("ManagedAreaName", "N_Years")]
z <- nrow(MA_Exclude)

```

## Managed Area Statistics

Gets summary statistics for each managed area. Excluded managed areas are not included into whether the data should be used or not. Uses piping from dplyr package to feed into subsequent steps. The following steps are performed:

1. Take the `data` variable and only include rows that have a `SufficientData` value of TRUE
2. Group data that have the same `ManagedAreaName`, `Year`, and `Month`.
  - Second summary statistics do not use the `Month` grouping and are only for `ManagedAreaName` and `Year`.
  - Third summary statistics do not use `Year` grouping and are only for `ManagedAreaName` and `Month`

3. For each group, provide the following information: Number of Entries (N), Lowest Value (Min), Largest Value (Max), Median, Mean, Standard Deviation, and a list of all Program IDs included in these measurements.
4. Sort the data in ascending (A to Z and 0 to 9) order based on ManagedAreaName then Year then Month
5. Write summary stats to a pipe-delimited .txt file in the output directory
  - Click this text to open Git directory with output files

```

MA_YM_Stats <- data[data$Use_In_Analysis==TRUE, ] %>%
  group_by(AreaID, ManagedAreaName, Year, Month) %>%
  summarize(ParameterName=parameter,
            RelativeDepth=depth,
            ActivityType=activity,
            N_Data=length(ResultValue),
            Min=min(ResultValue),
            Max=max(ResultValue),
            Median=median(ResultValue),
            Mean=mean(ResultValue),
            StandardDeviation=sd(ResultValue),
            ProgramIDs=paste(sort(unique(ProgramID), decreasing=FALSE),
                            collapse=', '))
MA_YM_Stats <- as.data.table(MA_YM_Stats[order(MA_YM_Stats$ManagedAreaName,
                                                MA_YM_Stats$Year,
                                                MA_YM_Stats$Month), ])
fwrite(MA_YM_Stats, paste0(out_dir, "/", param_name, "_", activity, "_", depth,
                           "_ManagedArea_YearMonth_Stats.txt"), sep="|")
rm(MA_YM_Stats)

MA_Y_Stats <- data[data$Use_In_Analysis==TRUE, ] %>%
  group_by(AreaID, ManagedAreaName, Year) %>%
  summarize(ParameterName=parameter,
            RelativeDepth=depth,
            ActivityType=activity,
            N=length(ResultValue),
            Min=min(ResultValue),
            Max=max(ResultValue),
            Median=median(ResultValue),
            Mean=mean(ResultValue),
            StandardDeviation=sd(ResultValue),
            ProgramIDs=paste(sort(unique(ProgramID), decreasing=FALSE),
                            collapse=', '))
MA_Y_Stats <- as.data.table(MA_Y_Stats[order(MA_Y_Stats$ManagedAreaName,
                                              MA_Y_Stats$Year), ])
fwrite(MA_Y_Stats, paste0(out_dir, "/", param_name, "_", activity, "_", depth,
                           "_ManagedArea_Year_Stats.txt"), sep="|")
rm(MA_Y_Stats)

MA_M_Stats <- data[data$Use_In_Analysis==TRUE, ] %>%
  group_by(AreaID, ManagedAreaName, Month) %>%
  summarize(ParameterName=parameter,
            RelativeDepth=depth,
            ActivityType=activity,
            N=length(ResultValue),
            Min=min(ResultValue),

```

```

Max=max(ResultValue),
Median=median(ResultValue),
Mean=mean(ResultValue),
StandardDeviation=sd(ResultValue),
ProgramIDs=paste(sort(unique(ProgramID), decreasing=FALSE),
                  collapse=', '))
MA_M_Stats <- as.data.table(MA_M_Stats[order(MA_M_Stats$ManagedAreaName,
                                              MA_M_Stats$Month), ])
fwrite(MA_M_Stats, paste0(out_dir, "/", param_name, "_", activity, "_",
                        "_ManagedArea_Month_Stats.txt"), sep="|")
rm(MA_M_Stats)

```

## Monitoring Location Statistics

Gets monitoring location statistics, which is defined as a unique combination of `ManagedAreaName`, `ProgramID`, `ProgramAreaName`, and `ProgramLocationID`, using piping from `dplyr` package. The following steps are performed:

1. Take the `data` variable and only include rows that have a `SufficientData` value of TRUE
2. Group data that have the same `ManagedAreaName`, `ProgramID`, `ProgramName`, and `ProgramLocationID`.
3. For each group, provide the following information: Earliest Sample Date (`EarliestSampleDate`), Latest Sample Date (`LastSampleDate`), Number of Entries (N), Lowest Value (Min), Largest Value (Max), Median, Mean, and Standard Deviation.
4. Sort the data in ascending (A to Z and 0 to 9) order based on `ManagedAreaName` then `ProgramName` then `ProgramID` then `ProgramLocationID`
5. Write summary stats to a pipe-delimited .txt file in the output directory
  - Click this text to open Git directory with output files

```

Mon_Stats <- data[data$Use_In_Analysis==TRUE, ] %>%
  group_by(AreaID, ManagedAreaName, ProgramID, ProgramName, ProgramLocationID) %>%
  summarize(ParameterName=parameter,
            RelativeDepth=depth,
            ActivityType=activity,
            EarliestSampleDate=min(SampleDate),
            LastSampleDate=max(SampleDate),
            N=length(ResultValue),
            Min=min(ResultValue),
            Max=max(ResultValue),
            Median=median(ResultValue),
            Mean=mean(ResultValue),
            StandardDeviation=sd(ResultValue))

Mon_Stats <- as.data.table(Mon_Stats[order(Mon_Stats$ManagedAreaName,
                                             Mon_Stats$ProgramName,
                                             Mon_Stats$ProgramID,
                                             Mon_Stats$ProgramLocationID), ])
fwrite(Mon_Stats, paste0(out_dir, "/", param_name, "_", activity, "_",
                        "_MonitoringLoc_Stats.txt"), sep="|")
rm(Mon_Stats)

```

## Seasonal Kendall Tau Analysis

Gets seasonal Kendall Tau statistics using the `kendallSeasonalTrendTest` from the `EnvStats` package. The `Trend` parameter is determined from a user-defined function based on the median, Senn slope, and p values from the data. Analysis modified from code created by Jason Scolaro that performed at The Water Atlas: <https://sarasota.wateratlas.usf.edu/water-quality-trends/#analysis-overview>

The following steps are performed:

1. Define the functions used in the analysis
2. Check to see if there are any groups to run analysis on.
3. Take the `data` variable and only include rows that have a `SufficientData` value of TRUE
4. Group data that have the same `ManagedAreaName`.
5. For each group, provides the following information: Earliest Sample Date (`EarliestSampleDate`), Latest Sample Date (`LastSampleDate`), Number of Entries (N), Lowest Value (Min), Largest Value (Max), Median, Mean, Standard Deviation, tau, Senn Slope (`SennSlope`), Senn Intercept (`SennIntercept`), and p.
  - The analysis is run with the `kendallSeasonalTrendTest` function using the `Year` values for year, and `Month` as the seasonal qualifier, and `Trend`.
  - An `independent.obs` value of TRUE indicates that the data should be treated as not being serially auto-correlated. An `independent.obs` value of FALSE indicates that it is treated as being serially auto-correlated, but also requires one observation per season per year for the full time of observation.
6. Reformat columns in the data frame from export.
7. Write summary stats to a pipe-delimited .txt file in the output directory
  - Click this text to open Git directory with output files

```
tauSeasonal <- function(data, independent, stats.median, stats.minYear,
                         stats.maxYear) {
  tau <- NULL
  tryCatch({ken <- kendallSeasonalTrendTest(
    y = data$resultValue,
    season = data$Month,
    year = data$Year,
    independent.obs = independent)

  tau <- ken$estimate[1]
  p <- ken$p.value[2]
  slope <- ken$estimate[2]
  intercept <- ken$estimate[3]
  trend <- trend_calculator(slope, stats.median, p)
  rm(ken)
  }, warning = function(w) {
    print(w)
  }, error = function(e) {
    print(e)
  }, finally = {
    if (!exists("tau")) {
      tau <- NA
    }
    if (!exists("p")) {
      p <- NA
    }
  }
}
```

```

    }
    if (!exists("slope")) {
      slope <- NA
    }
    if (!exists("intercept")) {
      intercept <- NA
    }
    if (!exists("trend")) {
      trend <- NA
    }
  })
KT <-c(unique(data$AreaID),
       unique(data$ManagedAreaName),
       stats.median,
       independent,
       tau,
       p,
       slope,
       intercept,
       trend)
return(KT)
}
runStats <- function(data) {
  data$Index <- as.Date(data$SampleDate) # , "%Y-%m-%d")
  data$resultValue <- as.numeric(data$resultValue)
  # Calculate basic stats
  stats.median <- median(data$resultValue, na.rm = TRUE)
  stats.minYear <- min(data$Year, na.rm = TRUE)
  stats.maxYear <- max(data$Year, na.rm = TRUE)
  # Calculate Kendall Tau and Slope stats, then update appropriate columns and table
  KT <- tauSeasonal(data, TRUE, stats.median,
                     stats.minYear, stats.maxYear)
  if (is.null(KT[9])) {
    KT <- tauSeasonal(data, FALSE, stats.median,
                      stats.minYear, stats.maxYear)
  }
  if (is.null(KT$Stats) == TRUE) {
    KT$Stats <- KT
  } else{
    KT$Stats <- rbind(KT$Stats, KT)
  }
  return(KT$Stats)
}
trend_calculator <- function(slope, median_value, p) {
  trend <-
    if (p < .05 & abs(slope) > abs(median_value) / 10.) {
      if (slope > 0) {
        2
      }
      else {
        -2
      }
    }
}

```

```

    else if (p < .05 & abs(slope) < abs(median_value) / 10.) {
      if (slope > 0) {
        1
      }
      else {
        -1
      }
    }
    else
      0
  return(trend)
}
KT.Stats <- NULL
# Loop that goes through each managed area.
# List of managed areas stored in MA_Years$ManagedAreaName
c_names <- c("AreaID", "ManagedAreaName", "Median", "Independent",
            "tau", "p", "SennSlope", "SennIntercept", "Trend")
if(n==0){
  KT.Stats <- data.frame(matrix(ncol=length(c_names),
                                nrow=length(MA_Summ$ManagedAreaName)))
  colnames(KT.Stats) <- c_names
  KT.Stats[, c("AreaID", "ManagedAreaName")] <-
    MA_Summ[, c("AreaID", "ManagedAreaName")]
} else{
  for (i in 1:n) {
    x <- nrow(data[data$Use_In_Analysis == TRUE &
                    data$ManagedAreaName == MA_Include[i], ])
    if (x>0) {
      KT.Stats <- runStats(data[data$Use_In_Analysis == TRUE &
                                    data$ManagedAreaName ==
                                    MA_Include[i], ])
    }
  }
  KT.Stats <- as.data.frame(KT.Stats)
  c_names <- c("AreaID", "ManagedAreaName", "Median", "Independent",
              "tau", "p", "SennSlope", "SennIntercept", "Trend")
  if(dim(KT.Stats)[2]==1){
    KT.Stats <- as.data.frame(t(KT.Stats))
  }
  colnames(KT.Stats) <- c_names
  rownames(KT.Stats) <- seq(1:nrow(KT.Stats))
  KT.Stats$tau <- round(as.numeric(KT.Stats$tau), digits=4)
  KT.Stats$p <- round(as.numeric(KT.Stats$p), digits=4)
  KT.Stats$SennSlope <- as.numeric(KT.Stats$SennSlope)
  KT.Stats$SennIntercept <- as.numeric(KT.Stats$SennIntercept)
  KT.Stats$Trend <- as.integer(KT.Stats$Trend)
}

KT.Stats <- merge.data.frame(MA_Summ, KT.Stats,
                             by=c("AreaID", "ManagedAreaName"), all=TRUE)

KT.Stats <- as.data.table(KT.Stats[order(KT.Stats$ManagedAreaName), ])

```

```

fwrite(KT.Stats, paste0(out_dir, "/", param_name, "_", activity, "_", depth,
                      "_KendallTau_Stats.txt"), sep="|")
data <- data[!is.na(data$ResultValue),]

```

## Appendix I: Scatter Plot of Entire Dataset

This part will create a scatter plot of the all data that passed initial filtering criteria with points colored based on specific value qualifiers. The values determined at the beginning (`year_lower`, `year_upper`, `min_RV`, `mn_RV`, `x_scale`, and `y_scale`) are solely for use by the plotting functions and are not output as part of the computed statistics.

```

plot_theme <- theme_bw() + theme(text=element_text(family="Segoe UI"),
                                 title=element_text(face="bold"),
                                 plot.title=element_text(hjust=0.5, size=14, color="#314963"),
                                 plot.subtitle=element_text(hjust=0.5, size=10, color="#314963"),
                                 axis.text.x=element_text(face="bold"),
                                 axis.text.y=element_text(face="bold"))

year_lower <- min(data$Year)
year_upper <- max(data$Year)
min_RV <- min(data$ResultValue)
mn_RV <- mean(data$ResultValue[data$ResultValue <
                                quantile(data$ResultValue, 0.98)])
sd_RV <- sd(data$ResultValue[data$ResultValue <
                                quantile(data$ResultValue, 0.98)])
x_scale <- ifelse(year_upper - year_lower > 30, 10, 5)
y_scale <- mn_RV + 4 * sd_RV

p1 <- ggplot(data=data[data$Include==TRUE],
              aes(x=SampleDate, y=ResultValue, fill=VQ_Plot)) +
  geom_point(shape=21, size=3, color="#333333", alpha=0.75) +
  labs(subtitle="Autoscale",
       x="Year", y=paste0("Values (", unit, ")"),
       fill="Value Qualifier") +
  plot_theme +
  theme(legend.position="top", legend.box="horizontal",
        legend.justification="right") +
  scale_x_date(labels=date_format("%Y")) +
  {if(inc_H==TRUE){
    scale_fill_manual(values=c("H"= "#F8766D", "U"= "#00BFC4",
                              "HU"="#7CAE00"), na.value="#cccccc")
  } else if(param_name=="Secchi_Depth"){
    scale_fill_manual(values=c("S"= "#F8766D", "U"= "#00BFC4",
                              "SU"="#7CAE00"), na.value="#cccccc")
  } else {
    scale_fill_manual(values=c("U"= "#00BFC4"), na.value="#cccccc")
  }}
}

p2 <- ggplot(data=data[data$Include==TRUE],
              aes(x=SampleDate, y=ResultValue, fill=VQ_Plot)) +

```

```

geom_point(shape=21, size=3, color="#333333", alpha=0.75) +
ylim(min_RV, y_scale) +
labs(subtitle="Scaled to 4x Standard Deviation",
x="Year", y=paste0("Values (", unit, ")")) +
plot_theme +
theme(legend.position="none") +
scale_x_date(labels=date_format("%Y")) +
{if(inc_H==TRUE){
  scale_fill_manual(values=c("H"= "#F8766D", "U"= "#00BFC4",
                            "HU"="#7CAE00"), na.value="#cccccc")
} else if(param_name=="Secchi_Depth"){
  scale_fill_manual(values=c("S"= "#F8766D", "U"= "#00BFC4",
                            "SU"="#7CAE00"), na.value="#cccccc")
} else {
  scale_fill_manual(values=c("U"= "#00BFC4"), na.value="#cccccc")
} }


leg <- get_legend(p1)
pset <- ggarrange(leg, p1 + theme(legend.position="none"), p2,
                  ncol=1, heights=c(0.1, 1, 1))

p0 <- ggplot() + labs(title="Scatter Plot for Entire Dataset") +
  plot_theme + theme(panel.border=element_blank(),
                     panel.grid.major=element_blank(),
                     panel.grid.minor=element_blank(),
                     axis.line=element_blank())

ggarrange(p0, pset, ncol=1, heights=c(0.1, 1))

```

### Scatter Plot for Entire Dataset



### Appendix II: Dataset Summary Box Plots

Box plots are created by using the entire data set and excludes any data that has been previously filtered out. The scripts that create plots follow this format

1. Use the data set that only has `SufficientData` of TRUE
2. Set what values are to be used for the x-axis, y-axis, and the variable that should determine groups for the box plots
3. Set the plot type as a box plot with the size of the outlier points
4. Create the title, x-axis, y-axis, and color fill labels
5. Set the y and x limits
6. Make the axis labels bold
7. Plot the arrangement as a set of panels

This set of box plots are grouped by year.

```

min_RV <- min(data$ResultValue[data$Include==TRUE])
mn_RV <- mean(data$ResultValue[data$Include==TRUE &
                                data$ResultValue <
                                quantile(data$ResultValue, 0.98)])
sd_RV <- sd(data$ResultValue[data$Include==TRUE &
                                data$ResultValue <
                                quantile(data$ResultValue, 0.98)])
y_scale <- mn_RV + 4 * sd_RV

p1 <- ggplot(data=data[data$Include==TRUE, ],
              aes(x=Year, y=ResultValue, group=Year)) +
  geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
               outlier.size=3, outlier.color="#333333",
               outlier.fill="#cccccc", outlier.alpha=0.75) +
  labs(subtitle="Autoscale", x="Year",
       y=paste0("Values (", unit, ")")) +
  plot_theme

p2 <- ggplot(data=data[data$Include==TRUE, ],
              aes(x=Year, y=ResultValue, group=Year)) +
  geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
               outlier.size=3, outlier.color="#333333",
               outlier.fill="#cccccc", outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation", x="Year",
       y=paste0("Values (", unit, ")")) +
  ylim(min_RV, y_scale) +
  plot_theme

p3 <- ggplot(data=data[data$Include==TRUE, ],
              aes(x=as.integer(Year), y=ResultValue, group=Year)) +
  geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
               outlier.size=3, outlier.color="#333333",
               outlier.fill="#cccccc", outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation, Last 10 Years",
       x="Year", y=paste0("Values (", unit, ")")) +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits=c(max(data$Year) - 10.5, max(data$Year)+1),
                     breaks=seq(max(data$Year) - 10, max(data$Year), 2)) +
  plot_theme

set <- ggarrange(p1, p2, p3, ncol=1)

p0 <- ggplot() + labs(title="Summary Box Plots for Entire Data",

```

```

        subtitle="By Year") + plot_theme +
theme(panel.border=element_blank(), panel.grid.major=element_blank(),
      panel.grid.minor=element_blank(), axis.line=element_blank())

Yset <- ggarrange(p0, set, ncol=1, heights=c(0.07, 1))

```

This set of box plots are grouped by year and month with the color being related to the month.

```

p1 <- ggplot(data=data[data$Include==TRUE, ],
              aes(x=YearMonthDec, y=ResultValue,
                  group=YearMonth, color=as.factor(Month))) +
  geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
  labs(subtitle="Autoscale", x="Year",
       y=paste0("Values (", unit, ")"), color="Month") +
  plot_theme +
  theme(legend.position="top", legend.box="horizontal") +
  guides(color=guide_legend(nrow=1))

p2 <- ggplot(data=data[data$Include==TRUE, ],
              aes(x=YearMonthDec, y=ResultValue,
                  group=YearMonth, color=as.factor(Month))) +
  geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation",
       x="Year", y=paste0("Values (", unit, ")")) +
  ylim(min_RV, y_scale) +
  plot_theme +
  theme(legend.position="none", axis.text.x=element_text(face="bold"),
        axis.text.y=element_text(face="bold"))

p3 <- ggplot(data=data[data$Include==TRUE, ],
              aes(x=YearMonthDec, y=ResultValue,
                  group=YearMonth, color=as.factor(Month))) +
  geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation, Last 10 Years",
       x="Year", y=paste0("Values (", unit, ")")) +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits=c(max(data$Year) - 10.5, max(data$Year)+1),
                     breaks=seq(max(data$Year) - 10, max(data$Year), 2)) +
  plot_theme +
  theme(legend.position="none")

leg <- get_legend(p1)
set <- ggarrange(leg, p1 + theme(legend.position="none"), p2, p3, ncol=1,
                 heights=c(0.1, 1, 1, 1))

p0 <- ggplot() + labs(title="Summary Box Plots for Entire Data",
                       subtitle="By Year & Month") + plot_theme +
  theme(panel.border=element_blank(), panel.grid.major=element_blank(),
        panel.grid.minor=element_blank(), axis.line=element_blank())

Yset <- ggarrange(p0, set, ncol=1, heights=c(0.07, 1))

```

The following box plots are grouped by month with fill color being related to the month. This is designed to view potential seasonal trends.

```

p1 <- ggplot(data=data[data$Include==TRUE, ],
              aes(x=Month, y=ResultValue,
                  group=Month, fill=as.factor(Month))) +
  geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
               outlier.color="#333333", outlier.alpha=0.75) +
  labs(subtitle="Autoscale", x="Month",
       y=paste0("Values (", unit, ")"), fill="Month") +
  scale_x_continuous(limits=c(0, 13), breaks=seq(3, 12, 3)) +
  plot_theme +
  theme(legend.position="top", legend.box="horizontal") +
  guides(fill=guide_legend(nrow=1))

p2 <- ggplot(data=data[data$Include==TRUE, ],
              aes(x=Month, y=ResultValue,
                  group=Month, fill=as.factor(Month))) +
  geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
               outlier.color="#333333", outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation",
       x="Month", y=paste0("Values (", unit, ")")) +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits=c(0, 13), breaks=seq(3, 12, 3)) +
  plot_theme +
  theme(legend.position="none")

p3 <- ggplot(data=data[data$Include==TRUE &
                           data$Year >= max(data$Year) - 10, ],
              aes(x=Month, y=ResultValue,
                  group=Month, fill=as.factor(Month))) +
  geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
               outlier.color="#333333", outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation, Last 10 Years",
       x="Month", y=paste0("Values (", unit, ")")) +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits=c(0, 13), breaks=seq(3, 12, 3)) +
  plot_theme +
  theme(legend.position="none")




leg <- get_legend(p1)
set <- ggarrange(leg, p1 + theme(legend.position="none"), p2, p3, ncol=1,
                 heights=c(0.1, 1, 1, 1))

p0 <- ggplot() + labs(title="Summary Box Plots for Entire Data",
                       subtitle="By Month") + plot_theme +
  theme(panel.border=element_blank(), panel.grid.major=element_blank(),
        panel.grid.minor=element_blank(), axis.line=element_blank())


Mset <- ggarrange(p0, set, ncol=1, heights=c(0.07, 1))

```


**Summary Box Plots for Entire Data**  
By Year



**Summary Box Plots for Entire Data**  
By Year & Month



**Summary Box Plots for Entire Data**  
By Month




### Appendix III: Excluded Managed Areas

Scatter plots of data values are created for managed areas that have fewer than 10 separate years of data entries. Data points are colored based on specific value qualifiers of interest.

```

if(z==0){
  print("There are no managed areas that qualify.")
} else {
  for(i in 1:z){
    p1<-ggplot(data=data[data$ManagedAreaName==MA_Exclude$ManagedAreaName[i]&
      data$Include==TRUE, ],
      aes(x=SampleDate, y=ResultValue, fill=VQ_Plot)) +
      geom_point(shape=21, size=3, color="#333333", alpha=0.75) +
      labs(title=paste0("Scatter Plot of Excluded Managed Area\n",
        MA_Exclude$ManagedAreaName[i], " (",
        MA_Exclude$N_Years[i], " Unique Years)"),
        subtitle="Autoscale", x="Year",
        y=paste0("Values (", unit, ")"), fill="Value Qualifier") +
      plot_theme +
      theme(legend.position="top", legend.box="horizontal",
        legend.justification="right") +
      scale_x_date(labels=date_format("%m-%Y")) +
      {if(inc_H==TRUE){
        scale_fill_manual(values=c("H"= "#F8766D", "U"= "#00BFC4",
          "HU"="#7CAE00"), na.value="#cccccc")
      } else if(param_name=="Secchi_Depth"){
        scale_fill_manual(values=c("S"= "#F8766D", "U"= "#00BFC4",
          "SU"="#7CAE00"), na.value="#cccccc")
      } else {
        scale_fill_manual(values=c("U"= "#00BFC4"), na.value="#cccccc")
      }}
      print(p1)
    }
}

```



## Appendix IV: Managed Area Trendlines

The plots created in this section are designed to show the general trend of the data. Data is taken and grouped by `ManagedAreaName`. The trendlines on the plots are created using the Senn slope and intercept from the seasonal Kendall Tau analysis. The scripts that create plots follow this format

1. Use the data set that only has `SufficientData` of TRUE for the desired managed area
2. Determine the earliest and latest year of the data to create x-axis scale and intervals
3. Determine the minimum, mean, and standard deviation for the data to be used for y-axis scales
  - Excludes the top 2% of values to reduce the impact of extreme outliers on the y-axis scale
4. Set what values are to be used for the x-axis, y-axis, and the variable that should determine groups for the plots
5. Set the plot type as a point plot with the size of the points
6. Add the linear trend
7. Create the title, x-axis, y-axis, and color fill labels
8. Set the y and x limits
9. Make the axis labels bold
10. Plot the arrangement as a set of panels

```
if(n==0){  
  print("There are no managed areas that qualify.")  
} else {  
  for (i in 1:n) {  
    plot_data <- data[data$SufficientData==TRUE &  
                      data$ManagedAreaName==MA_Include[i],]  
    year_lower <- min(plot_data$Year)  
    year_upper <- max(plot_data$Year)  
    min_RV <- min(plot_data$ResultValue)  
    mn_RV <- mean(plot_data$ResultValue[plot_data$ResultValue <  
                                         quantile(data$ResultValue, 0.98)])  
    sd_RV <- sd(plot_data$ResultValue[plot_data$ResultValue <  
                                         quantile(data$ResultValue, 0.98)])  
    x_scale <- ifelse(year_upper - year_lower > 30, 10, 5)  
    y_scale <- mn_RV + 4 * sd_RV  
  
    tau <- KT.Stats$tau[KT.Stats$ManagedAreaName==MA_Include[i]]  
    s_slope <- KT.Stats$SennSlope[KT.Stats$ManagedAreaName==MA_Include[i]]  
    s_int <- KT.Stats$SennIntercept[KT.Stats$ManagedAreaName==MA_Include[i]]  
    trend <- KT.Stats$Trend[KT.Stats$ManagedAreaName==MA_Include[i]]  
    p <- KT.Stats$p[KT.Stats$ManagedAreaName==MA_Include[i]]  
  
    model <- lm(ResultValue ~ DecDate,  
                 data=plot_data)  
    m_int <- coef(model)[[1]]  
    m_slope <- coef(model)[[2]]  
    rm(model)  
    p1 <- ggplot(data=plot_data,  
                  aes(x=DecDate, y=ResultValue, fill=VQ_Plot)) +  
      geom_point(shape=21, size=3, color="#333333", alpha=0.75) +  
      geom_abline(aes(slope=s_slope, intercept=s_int),  
                  color="blue", size=1.2) +  
      labs(subtitle="Autoscale",
```

```

        x="Year", y=paste0("Values (", unit, ")"),
        fill="Value Qualifier") +
plot_theme +
theme(legend.position="top", legend.box="horizontal",
      legend.justification="right") +
{if(inc_H==TRUE){
  scale_fill_manual(values=c("H"= "#F8766D", "U"= "#00BFC4",
                            "HU"= "#7CAE00"), na.value="#cccccc")
} else if(param_name=="Secchi_Depth"){
  scale_fill_manual(values=c("S"= "#F8766D", "U"= "#00BFC4",
                            "SU"= "#7CAE00"), na.value="#cccccc")
} else {
  scale_fill_manual(values=c("U"= "#00BFC4"), na.value="#cccccc")
} }

p2 <- ggplot(data=plot_data,
              aes(x=DecDate, y=ResultValue, fill=VQ_Plot)) +
  geom_point(shape=21, size=3, color="#333333", alpha=0.75) +
  geom_abline(aes(slope=s_slope, intercept=s_int),
              color="blue", size=1.2) +
  ylim(min_RV, y_scale) +
  labs(subtitle="Scaled to 4x Standard Deviation",
       x="Year", y=paste0("Values (", unit, ")")) +
plot_theme +
theme(legend.position="none") +
{if(inc_H==TRUE){
  scale_fill_manual(values=c("H"= "#F8766D", "U"= "#00BFC4",
                            "HU"= "#7CAE00"), na.value="#cccccc")
} else if(param_name=="Secchi_Depth"){
  scale_fill_manual(values=c("S"= "#F8766D", "U"= "#00BFC4",
                            "SU"= "#7CAE00"), na.value="#cccccc")
} else {
  scale_fill_manual(values=c("U"= "#00BFC4"), na.value="#cccccc")
} }

leg <- get_legend(p1)
KTset <- ggarrange(leg, p1 + theme(legend.position="none"), p2,
                    ncol=1, heights=c(0.1, 1, 1))

p0 <- ggplot() + labs(title=paste0("Data Points with Trendlines for ",
                                      MA_Include[i]),
                        subtitle =paste0("Senn Slope=", s_slope,
                                      ", Senn Intercept=", s_int,
                                      "\nTrend=", trend,
                                      ", tau=", tau,
                                      ", p=", p,
                                      "\nLinear Trendline: ",
                                      "y=", m_slope,"x + ",m_int)) +
plot_theme + theme(panel.border=element_blank(),
                   panel.grid.major=element_blank(),
                   panel.grid.minor=element_blank(),
                   axis.line=element_blank())

print(ggarrange(p0, KTset, ncol=1, heights=c(0.15, 1)))

```


```

    rm(plot_data)
    rm(KTset, leg)
  }
}

```


### Data Points with Trendlines for Alligator Harbor Aquatic Preserve

Senn Slope=-0.0400000000000001, Senn Intercept=111.171375  
 Trend=-1, tau=-0.0586, p=0  
 Linear Trendline:  $y = -0.0363912751425216x + 103.925259399584$




### Data Points with Trendlines for Apalachicola Bay Aquatic Preserve

Senn Slope=0, Senn Intercept=-8.42500000000005  
 Trend=0, tau=-0.0029, p=0.8525  
 Linear Trendline:  $y=0.0443969561183827x + -74.769963325663$




### Data Points with Trendlines for Apalachicola National Estuarine Research Reserve

Senn Slope=-0.025, Senn Intercept=75.0821637426903  
 Trend=-1, tau=-0.0275, p=0  
 Linear Trendline:  $y=-0.00388383504818269x + 22.7858584290594$




### Data Points with Trendlines for Banana River Aquatic Preserve

Senn Slope=0.5, Senn Intercept=-936.933991228071  
 Trend=1, tau=0.3486, p=0  
 Linear Trendline:  $y=0.314654150593402x + -610.192518833575$




### Data Points with Trendlines for Big Bend Seagrasses Aquatic Preserve

Senn Slope=0.0499999999999999, Senn Intercept=-91.47500000000001  
 Trend=1, tau=0.0322, p=0  
 Linear Trendline:  $y=0.0204910119932903x + -20.5350534922381$




### Data Points with Trendlines for Biscayne Bay-Cape Florida to Monroe County Line Aquatic Preserve

Senn Slope=0.0300000000000011, Senn Intercept=-43.2470781250012  
 Trend=0, tau=0.136, p=0.6318  
 Linear Trendline:  $y=0.064957052661303x + -94.4651048675445$




### Data Points with Trendlines for Biscayne Bay Aquatic Preserve

Senn Slope=-0.0517333333333333, Senn Intercept=190.704871794872  
 Trend=-1, tau=-0.0634, p=0  
 Linear Trendline:  $y=-0.126553858267903x + 283.881855239494$




### Data Points with Trendlines for Boca Ciega Bay Aquatic Preserve

Senn Slope=0.0060000000000023, Senn Intercept=7.54600000000028  
 Trend=1, tau=0.0271, p=0.0006  
 Linear Trendline:  $y=-0.0144341488264489x + 61.5429014307087$




### Data Points with Trendlines for Cape Haze Aquatic Preserve

Senn Slope=-0.02, Senn Intercept=72.4833333333336  
 Trend=-1, tau=-0.0137, p=0.0231  
 Linear Trendline:  $y=-0.014178080680021x + 57.255313556171$




### Data Points with Trendlines for Cape Romano-Ten Thousand Islands Aquatic Preserve

Senn Slope=0.0611111111111111, Senn Intercept=-98.9625  
 Trend=1, tau=0.0604, p=0  
 Linear Trendline:  $y=-0.0658687002783872x + 162.117299376915$




### Data Points with Trendlines for Cockroach Bay Aquatic Preserve

Senn Slope=-0.173684210526316, Senn Intercept=507.181176470588  
 Trend=-1, tau=-0.1057, p=0  
 Linear Trendline:  $y=-0.166212567315577x + 347.45588931986$




### Data Points with Trendlines for Coupon Bight Aquatic Preserve

Senn Slope=0.018965, Senn Intercept=-14.3568223958336  
 Trend=0, tau=0.0615, p=0.3186  
 Linear Trendline:  $y = -0.00489143323808193x + 46.0799731223233$




### Data Points with Trendlines for Estero Bay Aquatic Preserve

Senn Slope=0.0925, Senn Intercept=-165.516331168832  
 Trend=1, tau=0.056, p=0  
 Linear Trendline:  $y = 0.0191276703461966x + -10.8207820239572$




### Data Points with Trendlines for Florida Keys National Marine Sanctuary

Senn Slope=0.00847619047619068, Senn Intercept=15.3355923809522  
 Trend=1, tau=0.0475, p=0  
 Linear Trendline:  $y=0.00234066890807407x + 30.5058994213069$




### Data Points with Trendlines for Fort Clinch State Park Aquatic Preserve

Senn Slope=-0.0300000000000002, Senn Intercept=90.8016666666667  
 Trend=-1, tau=-0.0503, p=0.0217  
 Linear Trendline:  $y=-0.0636358228450696x + 160.677812392399$




### Data Points with Trendlines for Fort Pickens State Park Aquatic Preserve

Senn Slope=-0.1605, Senn Intercept=238.533848351648  
 Trend=-1, tau=-0.0902, p=0  
 Linear Trendline:  $y=-0.124241411250053x + 273.915367660349$




### Data Points with Trendlines for Gasparilla Sound-Charlotte Harbor Aquatic Preserve

Senn Slope=-0.066999999999998, Senn Intercept=166.8463333333333  
 Trend=-1, tau=-0.0458, p=0  
 Linear Trendline:  $y=-0.0487767917523279x + 123.606838552617$




### Data Points with Trendlines for Guana River Marsh Aquatic Preserve

Senn Slope=-0.15, Senn Intercept=278.628409090909  
 Trend=-1, tau=-0.1154, p=0  
 Linear Trendline:  $y = -0.52751808500712x + 1085.07066886787$




### Data Points with Trendlines for Guana Tolomato Matanzas National Estuarine Research Reserve

Senn Slope=-0.0899999999999999, Senn Intercept=211.224318181819  
 Trend=-1, tau=-0.1016, p=0  
 Linear Trendline:  $y = -0.417917689420175x + 867.426627605719$




### Data Points with Trendlines for Indian River-Malabar to Vero Beach Aquatic Preserve

Senn Slope=-0.0159999999999997, Senn Intercept=26.1302521008404  
 Trend=-1, tau=-0.0079, p=0.0085  
 Linear Trendline:  $y=-0.150026429669652x + 323.884495786274$




### Data Points with Trendlines for Indian River-Vero Beach to Ft. Pierce Aquatic Preserve

Senn Slope=0, Senn Intercept=-11.9484926470588  
 Trend=0, tau=0.0002, p=0.8378  
 Linear Trendline:  $y=-0.142344691824049x + 313.122503286175$




### Data Points with Trendlines for Jensen Beach to Jupiter Inlet Aquatic Preserve

Senn Slope=0.0999999999999998, Senn Intercept=-131.605  
 Trend=1, tau=0.1123, p=0  
 Linear Trendline:  $y=0.106978122533308x + -183.541103073579$




### Data Points with Trendlines for Lemon Bay Aquatic Preserve

Senn Slope=0, Senn Intercept=22.0612179487176  
 Trend=0, tau=0.0083, p=0.7761  
 Linear Trendline:  $y=-0.0210858378160797x + 75.2765385036685$




### Data Points with Trendlines for Lignumvitae Key Aquatic Preserve

Senn Slope=0.0356521739130435, Senn Intercept=21.2695652173914  
 Trend=0, tau=0.0526, p=0.2039  
 Linear Trendline:  $y=0.00986452932358945x + 15.8681680145878$




### Data Points with Trendlines for Loxahatchee River-Lake Worth Creek Aquatic Preserve

Senn Slope=0.06666666666666668, Senn Intercept=-67.8530303030304  
 Trend=1, tau=0.0306, p=0  
 Linear Trendline:  $y=0.0453840500083511x - 69.2629755896759$




### Data Points with Trendlines for Matlacha Pass Aquatic Preserve

Senn Slope=-0.0125000000000002, Senn Intercept=82.35833333333331  
 Trend=0, tau=-0.0065, p=0.2176  
 Linear Trendline:  $y=-0.0256540546354286x + 76.4902615265813$




### Data Points with Trendlines for Mosquito Lagoon Aquatic Preserve

Senn Slope=0.0999999999999996, Senn Intercept=-138.403125  
 Trend=1, tau=0.1005, p=0  
 Linear Trendline:  $y=-0.0162096062159285x + 64.0182188897898$




### Data Points with Trendlines for Nassau River-St. Johns River Marshes Aquatic Preserve

Senn Slope=0.02499999999986, Senn Intercept=-19.3000000000007  
 Trend=1, tau=0.0152, p=0.0259  
 Linear Trendline:  $y=0.0902133729245138x + -153.208275589103$




### Data Points with Trendlines for Nature Coast Aquatic Preserve

Senn Slope=0.0727272727272728, Senn Intercept=-153.858125  
 Trend=1, tau=0.0432, p=0  
 Linear Trendline:  $y=0.065887487944461x + -108.475577133249$




### Data Points with Trendlines for North Fork St. Lucie Aquatic Preserve

Senn Slope=-0.0384615384615385, Senn Intercept=154.881  
 Trend=-1, tau=-0.0737, p=0  
 Linear Trendline:  $y = -0.204938285469632x + 418.918227306432$




### Data Points with Trendlines for Pellicer Creek Aquatic Preserve

Senn Slope=-0.5, Senn Intercept=570.648214285715  
 Trend=-1, tau=-0.1133, p=0.0097  
 Linear Trendline:  $y = -0.127580022338208x + 269.465142963627$




### Data Points with Trendlines for Pine Island Sound Aquatic Preserve

Senn Slope=0.0055555555555563, Senn Intercept=25.3749999999999  
 Trend=1, tau=0.0117, p=0.0141  
 Linear Trendline:  $y=-0.000756929749784737x + 33.6161060571487$




### Data Points with Trendlines for Pinellas County Aquatic Preserve

Senn Slope=-0.0625, Senn Intercept=177.461944444445  
 Trend=-1, tau=-0.0743, p=0  
 Linear Trendline:  $y=-0.113537350503486x + 254.733547621325$




### Data Points with Trendlines for Rocky Bayou State Park Aquatic Preserve

Senn Slope=-0.129473684210526, Senn Intercept=533.0037500000001  
 Trend=0, tau=-0.0693, p=0.0923  
 Linear Trendline:  $y = -0.0500567001373941x + 114.502894911245$




### Data Points with Trendlines for Rookery Bay Aquatic Preserve

Senn Slope=0.005499999999997, Senn Intercept=27.46999999999999  
 Trend=0, tau=0.0162, p=0.1451  
 Linear Trendline:  $y = -0.0227360620549928x + 77.9438347760232$




### Data Points with Trendlines for Rookery Bay National Estuarine Research Reserve

Senn Slope=0.0463636363636363, Senn Intercept=-55.5758181818176  
 Trend=1, tau=0.0595, p=0  
 Linear Trendline:  $y=0.0374240096847303x + 105.345299499772$




### Data Points with Trendlines for Southeast Florida Coral Reef Ecosystem Conservation Area

Senn Slope=0.0037724358974359, Senn Intercept=-39.8962967741934  
 Trend=0, tau=0.0586, p=0.5034  
 Linear Trendline:  $y=0.00916177290503306x + 15.5629192795011$




### Data Points with Trendlines for St. Andrews State Park Aquatic Preserve

Senn Slope=-0.177332015810277, Senn Intercept=513.251428571428  
 Trend=-1, tau=-0.212, p=0  
 Linear Trendline:  $y=-0.140379826518219x + 312.683838101793$




### Data Points with Trendlines for St. Joseph Bay Aquatic Preserve

Senn Slope=-0.0414285714285713, Senn Intercept=103.26875  
 Trend=-1, tau=-0.0665, p=0  
 Linear Trendline:  $y=-0.0533867971926461x + 139.047883690827$




### Data Points with Trendlines for St. Martins Marsh Aquatic Preserve

Senn Slope=0.185714285714286, Senn Intercept=-373.481818181818  
 Trend=1, tau=0.1561, p=0  
 Linear Trendline:  $y=0.156815763910326x + -296.514868130943$




### Data Points with Trendlines for Terra Ceia Aquatic Preserve

Senn Slope=0.0162162162162, Senn Intercept=-36.6982105263159  
 Trend=1, tau=0.0353, p=0  
 Linear Trendline:  $y=-0.00213634846960425x + 33.9342925478725$




### Data Points with Trendlines for Tomoka Marsh Aquatic Preserve

Senn Slope=0.16875, Senn Intercept=-362.688333333333  
 Trend=0, tau=0.0776, p=0.0724  
 Linear Trendline:  $y=0.191058853774667x + -368.835694846211$



### Data Points with Trendlines for Yellow River Marsh Aquatic Preserve

Senn Slope=-0.109090909090909, Senn Intercept=380.865769230769  
 Trend=-1, tau=-0.0852, p=0.0139  
 Linear Trendline:  $y=-0.18471724013944x + 380.747250771181$



## Appendix V: Managed Area Summary Box Plots

Data is taken and grouped by `ManagedAreaName`. The scripts that create plots follow this format

1. Use the data set that only has `SufficientData` of `TRUE` for the desired managed area
2. Determine the earliest and latest year of the data to create x-axis scale and intervals
3. Determine the minimum, mean, and standard deviation for the data to be used for y-axis scales
  - Excludes the top 2% of values to reduce the impact of extreme outliers on the y-axis scale
4. Set what values are to be used for the x-axis, y-axis, and the variable that should determine groups for the box plots
5. Set the plot type as a box plot with the size of the outlier points
6. Create the title, x-axis, y-axis, and color fill labels
7. Set the y and x limits
8. Make the axis labels bold
9. Plot the arrangement as a set of panels

The following plots are arranged by `ManagedAreaName` with data grouped by `Year`, then `Year` and `Month`, then finally `Month` only. Each managed area will have 3 sets of plots, each with 3 panels in them. Each panel goes as follows:

1. Y-axis autoscaled
2. Y-axis set to be mean + 4 times the standard deviation
3. Y-axis set to be mean + 4 times the standard deviation for most recent 10 years of data

```
if(n==0){  
  print("There are no managed areas that qualify.")  
} else {  
  for (i in 1:n) {  
    plot_data <- data[data$SufficientData==TRUE &  
                      data$ManagedAreaName==MA_Include[i],]  
    year_lower <- min(plot_data$Year)  
    year_upper <- max(plot_data$Year)  
    mn_RV <- min(plot_data$ResultValue)  
    mn_RV <- mean(plot_data$ResultValue[plot_data$ResultValue <  
                                         quantile(data$ResultValue, 0.98)])  
    sd_RV <- sd(plot_data$ResultValue[plot_data$ResultValue <  
                                         quantile(data$ResultValue, 0.98)])  
    x_scale <- ifelse(year_upper - year_lower > 30, 10, 5)  
    y_scale <- mn_RV + 4 * sd_RV  
  
    ##Year plots  
    p1 <- ggplot(data=plot_data,  
                  aes(x=Year, y=ResultValue, group=Year)) +  
      geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,  
                   outlier.size=3, outlier.color="#333333",  
                   outlier.fill="#cccccc", outlier.alpha=0.75) +  
      labs(subtitle="Autoscale",  
            x="Year", y=paste0("Values (", unit, ")")) +  
      scale_x_continuous(limits=c(year_lower - 1, year_upper + 1),  
                         breaks=rev(seq(year_upper,  
                                      year_lower, -x_scale))) +  
      plot_theme
```

```

p2 <- ggplot(data=plot_data,
             aes(x=Year, y=ResultValue, group=Year)) +
  geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
               outlier.size=3, outlier.color="#333333",
               outlier.fill="#cccccc", outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation",
       x="Year", y=paste0("Values (", unit, ")")) +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits=c(year_lower - 1, year_upper + 1),
                     breaks=rev(seq(year_upper,
                                   year_lower, -x_scale))) +
  plot_theme

p3 <- ggplot(data=plot_data[plot_data$Year >= year_upper - 10, ],
             aes(x=Year, y=ResultValue, group=Year)) +
  geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
               outlier.size=3, outlier.color="#333333",
               outlier.fill="#cccccc", outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation, Last 10 Years",
       x="Year", y=paste0("Values (", unit, ")")) +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits=c(year_upper - 10.5, year_upper + 1),
                     breaks=rev(seq(year_upper, year_upper - 10,-2))) +
  plot_theme

Yset <- ggarrange(p1, p2, p3, ncol=1)

p0 <- ggplot() + labs(title=paste0("Summary Box Plots for ",
                                     MA_Include[i]),
                       subtitle="By Year") +
  plot_theme + theme(panel.border=element_blank(),
                     panel.grid.major=element_blank(),
                     panel.grid.minor=element_blank(),
                     axis.line=element_blank())

## Year & Month Plots
p4 <- ggplot(data=plot_data,
             aes(x=YearMonthDec, y=ResultValue,
                 group=YearMonth, color=as.factor(Month))) +
  geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
  labs(subtitle="Autoscale",
       x="Year", y=paste0("Values (", unit, ")"), color="Month") +
  scale_x_continuous(limits=c(year_lower - 1, year_upper + 1),
                     breaks=rev(seq(year_upper,
                                   year_lower, -x_scale))) +
  plot_theme +
  theme(legend.position="none")

p5 <- ggplot(data=plot_data,
             aes(x=YearMonthDec, y=ResultValue,
                 group=YearMonth, color=as.factor(Month))) +
  geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +

```

```

    labs(subtitle="Scaled to 4x Standard Deviation",
         x="Year", y=paste0("Values (", unit, ")"), color="Month") +
    ylim(min_RV, y_scale) +
    scale_x_continuous(limits=c(year_lower - 1, year_upper + 1),
                       breaks=rev(seq(year_upper,
                                      year_lower, -x_scale))) +
  plot_theme +
  theme(legend.position="top", legend.box="horizontal") +
  guides(color=guide_legend(nrow=1))

p6 <- ggplot(data=plot_data[plot_data$Year >= year_upper - 10, ],
              aes(x=YearMonthDec, y=ResultValue,
                  group=YearMonth, color=as.factor(Month))) +
  geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation, Last 10 Years",
       x="Year", y=paste0("Values (", unit, ")"), color="Month") +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits=c(year_upper - 10.5, year_upper + 1),
                     breaks=rev(seq(year_upper, year_upper - 10,-2))) +
  plot_theme +
  theme(legend.position="none")

leg1 <- get_legend(p5)
YMset <- ggarrange(leg1, p4, p5 + theme(legend.position="none"), p6,
                    ncol=1, heights=c(0.1, 1, 1, 1))

p00 <- ggplot() + labs(title=paste0("Summary Box Plots for ",
                                       MA_Include[i]),
                           subtitle="By Year & Month") + plot_theme +
  theme(panel.border=element_blank(),
        panel.grid.major=element_blank(),
        panel.grid.minor=element_blank(), axis.line=element_blank())

## Month Plots
p7 <- ggplot(data=plot_data,
              aes(x=Month, y=ResultValue,
                  group=Month, fill=as.factor(Month))) +
  geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
               outlier.color="#333333", outlier.alpha=0.75) +
  labs(subtitle="Autoscale",
       x="Month", y=paste0("Values (", unit, ")"), fill="Month") +
  scale_x_continuous(limits=c(0, 13), breaks=seq(3, 12, 3)) +
  plot_theme +
  theme(legend.position="none")

p8 <- ggplot(data=plot_data,
              aes(x=Month, y=ResultValue,
                  group=Month, fill=as.factor(Month))) +
  geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
               outlier.color="#333333", outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation",
       x="Month", y=paste0("Values (", unit, ")"), fill="Month") +
  ylim(min_RV, y_scale) +

```

```

scale_x_continuous(limits=c(0, 13), breaks=seq(3, 12, 3)) +
plot_theme +
theme(legend.position="top", legend.box="horizontal") +
guides(fill=guide_legend(nrow=1))

p9 <- ggplot(data=plot_data[plot_data$Year >= year_upper - 10, ],
              aes(x=Month, y=ResultValue,
                  group=Month, fill=as.factor(Month))) +
  geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
               outlier.color="#333333", outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation, Last 10 Years",
       x="Month", y=paste0("Values (", unit, ")"), fill="Month") +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits=c(0, 13), breaks=seq(3, 12, 3)) +
  plot_theme +
  theme(legend.position="none")

leg2 <- get_legend(p8)
Mset <- ggarrange(leg2, p7, p8 + theme(legend.position="none"), p9,
                  ncol=1, heights=c(0.1, 1, 1, 1))


p000 <- ggplot() + labs(title=paste0("Summary Box Plots for ",
                                         MA_Include[i]),
                           subtitle="By Month") + plot_theme +
  theme(panel.border=element_blank(),
        panel.grid.major=element_blank(),
        panel.grid.minor=element_blank(), axis.line=element_blank())

print(ggarrange(p0, Yset, ncol=1, heights=c(0.07, 1)))
print(ggarrange(p00, YMset, ncol=1, heights=c(0.07, 1)))
print(ggarrange(p000, Mset, ncol=1, heights=c(0.07, 1, 0.7)))


rm(plot_data)
rm(p1, p2, p3, p4, p5, p6, p7, p8, p9, p0, p00, p000, leg1, leg2,
    Yset, YMset, Mset)
}
}

```


**Summary Box Plots for Alligator Harbor Aquatic Preserve**  
By Year






**Summary Box Plots for Alligator Harbor Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Alligator Harbor Aquatic Preserve**  
By Month




**Summary Box Plots for Apalachicola Bay Aquatic Preserve**  
By Year




**Summary Box Plots for Apalachicola Bay Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Apalachicola Bay Aquatic Preserve**  
By Month




**Summary Box Plots for Apalachicola National Estuarine Research Reserve**  
By Year




**Summary Box Plots for Apalachicola National Estuarine Research Reserve**  
By Year & Month




**Summary Box Plots for Apalachicola National Estuarine Research Reserve**  
By Month




**Summary Box Plots for Banana River Aquatic Preserve**  
By Year




**Summary Box Plots for Banana River Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Banana River Aquatic Preserve**  
By Month




**Summary Box Plots for Big Bend Seagrasses Aquatic Preserve**  
By Year




**Summary Box Plots for Big Bend Seagrasses Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Big Bend Seagrasses Aquatic Preserve**  
By Month




**Summary Box Plots for Biscayne Bay-Cape Florida to Monroe County Line Aquatic Preserve**  
By Year




**Summary Box Plots for Biscayne Bay-Cape Florida to Monroe County Line Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Biscayne Bay-Cape Florida to Monroe County Line Aquatic Preserve**  
 By Month




**Summary Box Plots for Biscayne Bay Aquatic Preserve**  
By Year




**Summary Box Plots for Biscayne Bay Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Biscayne Bay Aquatic Preserve**  
By Month




**Summary Box Plots for Boca Ciega Bay Aquatic Preserve**  
By Year




**Summary Box Plots for Boca Ciega Bay Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Boca Ciega Bay Aquatic Preserve**  
By Month




**Summary Box Plots for Cape Haze Aquatic Preserve**  
By Year




**Summary Box Plots for Cape Haze Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Cape Haze Aquatic Preserve**  
By Month




**Summary Box Plots for Cape Romano-Ten Thousand Islands Aquatic Preserve**  
By Year




**Summary Box Plots for Cape Romano-Ten Thousand Islands Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Cape Romano-Ten Thousand Islands Aquatic Preserve**  
By Month




**Summary Box Plots for Cockroach Bay Aquatic Preserve**  
By Year




**Summary Box Plots for Cockroach Bay Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Cockroach Bay Aquatic Preserve**  
By Month




**Summary Box Plots for Coupon Bright Aquatic Preserve**  
By Year




**Summary Box Plots for Coupon Eight Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Coupon Bright Aquatic Preserve**  
By Month




**Summary Box Plots for Estero Bay Aquatic Preserve**  
By Year




**Summary Box Plots for Estero Bay Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Estero Bay Aquatic Preserve**  
By Month




**Summary Box Plots for Florida Keys National Marine Sanctuary**  
By Year




**Summary Box Plots for Florida Keys National Marine Sanctuary**  
By Year & Month




**Summary Box Plots for Florida Keys National Marine Sanctuary**  
By Month




**Summary Box Plots for Fort Clinch State Park Aquatic Preserve**  
By Year




**Summary Box Plots for Fort Clinch State Park Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Fort Clinch State Park Aquatic Preserve**  
By Month




**Summary Box Plots for Fort Pickens State Park Aquatic Preserve**  
By Year




**Summary Box Plots for Fort Pickens State Park Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Fort Pickens State Park Aquatic Preserve**  
By Month




**Summary Box Plots for Gasparilla Sound-Charlotte Harbor Aquatic Preserve**  
By Year




**Summary Box Plots for Gasparilla Sound-Charlotte Harbor Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Gasparilla Sound-Charlotte Harbor Aquatic Preserve**  
By Month




**Summary Box Plots for Guana River Marsh Aquatic Preserve**  
By Year




**Summary Box Plots for Guana River Marsh Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Guana River Marsh Aquatic Preserve**  
By Month




**Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve**  
By Year




**Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve**  
By Year & Month




**Summary Box Plots for Guana Tolomato Matanzas National Estuarine Research Reserve**  
 By Month




**Summary Box Plots for Indian River-Malabar to Vero Beach Aquatic Preserve**  
By Year






**Summary Box Plots for Indian River-Malabar to Vero Beach Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Indian River-Malabar to Vero Beach Aquatic Preserve**  
By Month




**Summary Box Plots for Indian River-Vero Beach to Ft. Pierce Aquatic Preserve**  
By Year






**Summary Box Plots for Indian River-Vero Beach to Ft. Pierce Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Indian River-Vero Beach to Ft. Pierce Aquatic Preserve**  
By Month




**Summary Box Plots for Jensen Beach to Jupiter Inlet Aquatic Preserve**  
By Year




**Summary Box Plots for Jensen Beach to Jupiter Inlet Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Jensen Beach to Jupiter Inlet Aquatic Preserve**  
By Month




**Summary Box Plots for Lemon Bay Aquatic Preserve**  
By Year




**Summary Box Plots for Lemon Bay Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Lemon Bay Aquatic Preserve**  
By Month




**Summary Box Plots for Lignumvitae Key Aquatic Preserve**  
By Year




**Summary Box Plots for Lignumvitae Key Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Lignumvitae Key Aquatic Preserve**  
By Month




**Summary Box Plots for Loxahatchee River-Lake Worth Creek Aquatic Preserve**  
By Year




**Summary Box Plots for Loxahatchee River-Lake Worth Creek Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Loxahatchee River-Lake Worth Creek Aquatic Preserve**  
By Month




**Summary Box Plots for Matlacha Pass Aquatic Preserve**  
By Year




**Summary Box Plots for Matlacha Pass Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Matlacha Pass Aquatic Preserve**  
By Month




**Summary Box Plots for Mosquito Lagoon Aquatic Preserve**  
By Year




**Summary Box Plots for Mosquito Lagoon Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Mosquito Lagoon Aquatic Preserve**  
By Month




**Summary Box Plots for Nassau River-St. Johns River Marshes Aquatic Preserve**  
By Year




**Summary Box Plots for Nassau River-St. Johns River Marshes Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Nassau River-St. Johns River Marshes Aquatic Preserve**  
By Month




**Summary Box Plots for Nature Coast Aquatic Preserve**  
By Year




**Summary Box Plots for Nature Coast Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Nature Coast Aquatic Preserve**  
By Month




**Summary Box Plots for North Fork St. Lucie Aquatic Preserve**  
By Year




**Summary Box Plots for North Fork St. Lucie Aquatic Preserve**  
By Year & Month




**Summary Box Plots for North Fork St. Lucie Aquatic Preserve**  
By Month




**Summary Box Plots for Pellicer Creek Aquatic Preserve**  
By Year




**Summary Box Plots for Pellicer Creek Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Pellicer Creek Aquatic Preserve**  
By Month




**Summary Box Plots for Pine Island Sound Aquatic Preserve**  
By Year




**Summary Box Plots for Pine Island Sound Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Pine Island Sound Aquatic Preserve**  
By Month




**Summary Box Plots for Pinellas County Aquatic Preserve**  
By Year




**Summary Box Plots for Pinellas County Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Pinellas County Aquatic Preserve**  
By Month




**Summary Box Plots for Rocky Bayou State Park Aquatic Preserve**  
By Year






**Summary Box Plots for Rocky Bayou State Park Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Rocky Bayou State Park Aquatic Preserve**  
By Month




**Summary Box Plots for Rookery Bay Aquatic Preserve**  
By Year




**Summary Box Plots for Rookery Bay Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Rookery Bay Aquatic Preserve**  
By Month




**Summary Box Plots for Rookery Bay National Estuarine Research Reserve**  
By Year




**Summary Box Plots for Rookery Bay National Estuarine Research Reserve**  
By Year & Month




**Summary Box Plots for Rookery Bay National Estuarine Research Reserve**  
By Month




**Summary Box Plots for Southeast Florida Coral Reef Ecosystem Conservation Area**  
By Year




**Summary Box Plots for Southeast Florida Coral Reef Ecosystem Conservation Area**  
By Year & Month




**Summary Box Plots for Southeast Florida Coral Reef Ecosystem Conservation Area**  
By Month




**Summary Box Plots for St. Andrews State Park Aquatic Preserve**  
By Year




**Summary Box Plots for St. Andrews State Park Aquatic Preserve**  
By Year & Month




**Summary Box Plots for St. Andrews State Park Aquatic Preserve**  
By Month




**Summary Box Plots for St. Joseph Bay Aquatic Preserve**  
By Year




**Summary Box Plots for St. Joseph Bay Aquatic Preserve**  
By Year & Month




**Summary Box Plots for St. Joseph Bay Aquatic Preserve**  
By Month




**Summary Box Plots for St. Martins Marsh Aquatic Preserve**  
By Year




**Summary Box Plots for St. Martins Marsh Aquatic Preserve**  
By Year & Month




**Summary Box Plots for St. Martins Marsh Aquatic Preserve**  
By Month




**Summary Box Plots for Terra Ceia Aquatic Preserve**  
By Year




**Summary Box Plots for Terra Ceia Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Terra Ceia Aquatic Preserve**  
By Month




**Summary Box Plots for Tomoka Marsh Aquatic Preserve**  
By Year




**Summary Box Plots for Tomoka Marsh Aquatic Preserve**  
By Year & Month




**Summary Box Plots for Tomoka Marsh Aquatic Preserve**  
By Month



**Summary Box Plots for Yellow River Marsh Aquatic Preserve**  
By Year



**Summary Box Plots for Yellow River Marsh Aquatic Preserve**  
By Year & Month



**Summary Box Plots for Yellow River Marsh Aquatic Preserve**  
By Month

