

SEACAR Discrete Water Quality Analysis: All Surface Salinity

Last compiled on 16 July, 2023

Contents

Important Notes	1
Libraries and Settings	2
File Import	2
Data Filtering	3
Data Impacted by Specific Value Qualifiers	7
Managed Area Statistics	9
Monitoring Location Statistics	11
Seasonal Kendall Tau Analysis	12
Appendix I: Scatter Plot of Entire Dataset	15
Appendix II: Dataset Summary Box Plots	17
Appendix III: Managed Area Trendlines	23
Appendix IV: Managed Area Summary Box Plots	67
Appendix V: Excluded Managed Areas	197

Important Notes

The purpose of this script is to create managed area statistics, perform seasonal Kendall Tau analysis, generate summary plots, and create reports in pdf and Word document form for each parameter in Wc Discrete.

These scripts were created by [J.E. Panzik](mailto:jepanzik@usf.edu) (jepanzik@usf.edu) for SEACAR.

All scripts and outputs can be found on the SEACAR GitHub repository:

https://github.com/FloridaSEACAR/SEACAR_Trend_Analyses

This markdown file is designed to be compiled by [WC_Discrete_ReportRender.R](https://github.com/FloridaSEACAR/SEACAR_Trend_Analyses/blob/main/WC_Discrete/WC_Discrete_ReportRender.R) (https://github.com/FloridaSEACAR/SEACAR_Trend_Analyses/blob/main/WC_Discrete/WC_Discrete_ReportRender.R).

Note: The top 2% of data is excluded when computing mean and standard deviations in plotting sections solely for the purpose of getting y-axis scales. The exclusion of the top 2% is not used in any statistics that are exported.

Libraries and Settings

Loads libraries used in the script. The inclusion of `scipen` option limits how frequently R defaults to scientific notation. Sets default settings for displaying warning and messages in created document, and sets figure dpi.

```
library(knitr)
library(data.table)
library(dplyr)
library(lubridate)
library(ggplot2)
library(ggpubr)
library(scales)
library(EnvStats)
library(tidyverse)
library(kableExtra)
options(scipen=999)
knitr:::opts_chunk$set(
  warning=FALSE,
  message=FALSE,
  dpi=200
)
```

File Import

Imports file that is determined in the WC_Discrete_ReportRender.R script.

The command `fread` is used because of its improved speed while handling large data files. Only columns that are used by the script are imported from the file, and are designated in the `select` input.

The script then gets the name of the parameter as it appears in the data file and units of the parameter.

The latest version of WC Discrete data is available at: <https://usf.box.com/s/fbimxw4hrmazfn5b1d4jbn0addmcsl8>

The file being used for the analysis is: **Combined_WQ_WC_NUT_Salinity-2023-Jun-01.txt**

```
data <- fread(file_in, sep="|", header=TRUE, stringsAsFactors=FALSE,
  select=c("ManagedAreaName", "ProgramID", "ProgramName",
  "ProgramLocationID", "SampleDate", "Year", "Month",
  "RelativeDepth", "ActivityType", "ParameterName",
  "ParameterValue", "ParameterUnits", "ValueQualifier",
  "SEACAR_QAQCFlagCode", "Include"),
  na.strings=c("NULL","","NA"))

parameter <- unique(data$ParameterName)
unit <- unique(data$ParameterUnits)
cat(paste("The data file(s) used:", file_short, sep="\n"))
```

```
## The data file(s) used:  
## Combined_WQ_WC_NUT_Salinity-2023-Jun-01.txt
```

Data Filtering

Most data filtering is performed on export from the database, and is indicated by the `Include` variable. `Include` values of 1 indicate the data should be used for analysis, values of 0 indicate the data should not be used for analysis. Documentation on the database filtering is provided here: [SEACAR Documentation - Analysis Filters and Calculations.pdf](#)

The filtering that is performed by the script at this point removes rows that are missing values for `ResultValue`, and only keeps data that is measured at the relative depth (surface, bottom, etc.) and activity type (field or sample) of interest. This is partly handled on export with the `RelativeDepth` variable, but there are some measurements that are considered both surface and bottom based on measurement depth and total depth. By default, these are marked as `Surface` for `RelativeDepth` and receive a `SEACAR_QAQCFlag` indicator of 12Q. Data passes the filtering process if it is from the correct depth and has an `Include` value of 1. The script also only looks at data of the desired `ActivityType` which indicates whether it was measured in the field (`Field`) or in the lab (`Sample`).

After the initial filtering, a second filter variable is created to determine whether enough time is represented in the monitoring location, which is that each monitoring location has 10 year or more of unique year entries and have at least 2 consecutive years of observations with at least 2 repeating months for observations that pass the initial filter. If data passes the first set of filtering criteria and the time criteria, they are used in the analysis.

The function that determines whether a managed area has at least 2 consecutive years of observations with at least 2 repeating months takes the data, creates a list of the managed areas and cycles through each managed area. For each managed area cycle:

1. List the unique years and put them in ascending order
2. If there are fewer than 2 unique years, skip to the next area
3. If there are 2 or more unique years, start a loop that compares adjacent year entries for the area
 - Start with the first two year entries
4. See if the year entries are subsequent years (1 year apart)
 - If not, skip to next pair of years
5. For the two years being compared, get the list of months for each
6. Compare the two lists of months to see what months are the same
 - If there are two or more months that are the same, the managed area passes the criteria and is stored in a variable
7. The list of managed areas that pass the 2 consecutive years with at least 2 repeating months is returned and used to determine if there is sufficient data for analysis.

A data frame is created that stores summary information for each managed area. This information is stored and combined with the results of the Seasonal Kendall Tau analysis and export to a data file once combined.

The sufficient data qualifier is merged with the original data, and a variable `Use_In_Analysis` is created to indicate what data should be used.

```

# Removes data rows with missing ResultValue
data <- data[!is.na(data$ResultValue),]
# Changes "Sample" to "Lab" for ActivityType
data$ActivityType <- gsub("Sample", "Lab", data$ActivityType)

# Gets data for the specific activity type for Chlorophyll, salinity, TSS,
# and Turbidity
if((param_name=="Chlorophyll_a_uncorrected_for_pheophytin" |
    param_name=="Salinity" | param_name=="Total_Suspended_Solids_TSS" |
    param_name=="Turbidity") & activity!="All"){
  data <- data[grep(activity, data$ActivityType[!is.na(data$ActivityType)]),]
}

# Changes RelativeDepth to Bottom for the QAQC flag 12Q that indicates
# measurements are both surface and bottom if the relative depth is bottom
if(depth=="Bottom"){
  data$RelativeDepth[grep("12Q", data$SEACAR_QAQCFlagCode[
    data$RelativeDepth=="Surface"])] <- "Bottom"
}
# Removes missing RelativeDepth data and data for RelativeDepth not of interest
# from all parameters except Secchi_Depth
if(param_name!="Secchi_Depth" & depth!="All"){
  data <- data[!is.na(data$RelativeDepth),]
  data <- data[data$RelativeDepth==depth,]
}

# Removes data rows that have "Blank" as an ActivityType
if(length(grep("Blank", data$ActivityType))>0){
  data <- data[-grep("Blank", data$ActivityType),]
}

# Removes data rows with ResultValue below 0, or -2 for Water_Temperature
if(param_name=="Water_Temperature"){
  data <- data[data$ResultValue>=-2,]
} else{
  data <- data[data$ResultValue>=0,]
}

# Changes Include to be either TRUE or FALSE
data$Include <- as.logical(data$Include)
# Changes Include to be TRUE for ProgramID 476 if it had the H value qualifier
data$Include[grep("H", data$ValueQualifier[data$ProgramID==476])] <- TRUE
# Change Include to be FALSE for Secchi_Depth with U value qualifier
if(param_name=="Secchi_Depth"){
  data$Include[grep("U", data$ValueQualifier)] <- FALSE
}

# Gets AreaID for data by merging data with the managed area list
data <- merge.data.frame(MA_All[,c("AreaID", "ManagedAreaName")],
                         data, by="ManagedAreaName", all=TRUE)
# Creates function to checks managed area for at least 2 years of
# continuous consecutive data
DiscreteConsecutiveCheck <- function(con_data){
  # Gets AreaIDs
  IDs <- unique(con_data$AreaID[con_data$Include==TRUE &

```

```

        !is.na(con_data$Include]))
# Loops through each AreaID
for(i in 1:length(IDs)) {
  # Gets list of Years for AreaID
  Years <- unique(con_data$Year[con_data$AreaID==IDs[i] &
    con_data$Include==TRUE &
    !is.na(con_data$Include)])
  # Puts Years in order
  Years <- Years[order(Years)]
  # If there are fewer than 2 years, skip to next AreaID
  if(length(Years)<2) {
    next
  }
  # Starts loop to make sure there are at least 2 consecutive years
  # with consecutive months of data
  for(j in 2:length(Years)) {
    # If adjacent year entries are not 1 year apart, skip to the
    # next set of year entries
    if(Years[j]-Years[j-1] !=1) {
      next
    }
    # Gets the list of months from the first year
    Months1 <- unique(con_data$Month[
      con_data$AreaID==IDs[i] &
      con_data$Year==Years[j-1] &
      con_data$Include==TRUE &
      !is.na(con_data$Include)])
    # Gets list of months for the second year
    Months2 <- unique(con_data$Month[
      con_data$AreaID==IDs[i] &
      con_data$Year==Years[j] &
      con_data$Include==TRUE &
      !is.na(con_data$Include)])
    # If there are more than 2 months shared between the two
    # years, the AreaID passes the check and is stored
    if(length(intersect(Months1, Months2))>=2) {
      # Creates variable for stored AreaID if it
      # doesn't exist
      if(exists("consecutive")==FALSE){
        consecutive <- IDs[i]
        break
      } else{
        consecutive <- append(consecutive, IDs[i])
        break
      }
    }
  }
}
# After going through all AreaID, return variable with list of all
# that pass
return(consecutive)
}

```

```

# Stores the AreaID that pass the consecutive year check
consMonthIDs <- DiscreteConsecutiveCheck(data)

# Creates data frame with summary for each managed area
MA_Summ <- data %>%
  group_by(AreaID, ManagedAreaName) %>%
  summarize(ParameterName=parameter,
            RelativeDepth=depth,
            ActivityType=activity,
            N_Data=length(ResultValue[Include==TRUE & !is.na(ResultValue)]),
            N_Years=length(unique(Year[Include==TRUE & !is.na(Year)])),
            EarliestYear=min(Year[Include==TRUE & N_Data!=0]),
            LatestYear=max(Year[Include==TRUE & N_Data!=0]),
            EarliestSampleDate=min(SampleDate[Include==TRUE]),
            LastSampleDate=max(SampleDate[Include==TRUE]),
            ConsecutiveMonths=ifelse(unique(AreaID) %in%
                                      consMonthIDs==TRUE, TRUE, FALSE),
            # Determines if monitoring location is sufficient for analysis
            # based on having more than 0 data entries, more than the
            # sufficient number of year, and the consecutive month criteria
            SufficientData=ifelse(N_Data>0 & N_Years>=suff_years &
                                  ConsecutiveMonths==TRUE, TRUE, FALSE),
            Median=median(ResultValue[Include==TRUE & N_Data!=0], na.rm=TRUE))

MA_Summ$ConsecutiveMonths <- NULL
# Creates column in data that determines how many years from the start for each
# managed area
data <- data %>%
  group_by(AreaID, ManagedAreaName) %>%
  mutate(YearFromStart=Year-min(Year))
# Adds SufficientData column to data table based on managed area
data <- merge.data.frame(data, MA_Summ[,c("ManagedAreaName", "SufficientData")],
                         by="ManagedAreaName")
# Creates Use_In_Analysis column for data that is determined if the row has
# Include value of TRUE and SufficientData value of TRUE
data$Use_In_Analysis <- ifelse(data$Include==TRUE & data$SufficientData==TRUE,
                                 TRUE, FALSE)
# Rearranges the summary data frame columns to be AreaID, ManagedAreaName,
# ParameterName RelativeDepth, ActivityType, SufficientData, everything else
MA_Summ <- MA_Summ %>%
  select(AreaID, ManagedAreaName, ParameterName, RelativeDepth, ActivityType,
         SufficientData, everything())
# Puts summary data in order based on managed area
MA_Summ <- as.data.frame(MA_Summ[order(MA_Summ$ManagedAreaName), ])
# Put SampleDate as date object
data$SampleDate <- as.Date(data$SampleDate)
# Creates character object for Month and Year
data$YearMonth <- paste0(data$Month, "-", data$Year)
# Creates variable that puts year and month into a decimal year format
data$YearMonthDec <- data$Year + ((data$Month-0.5) / 12)
# Converts ampleDate to a decimal date
data$DecDate <- decimal_date(data$SampleDate)

```

```

# Get list of and number of managed areas that are to be used in analysis
MA_Include <- MA_Summ$ManagedAreaName[MA_Summ$SufficientData==TRUE]
n <- length(MA_Include)
# Get list of and number of managed areas that are excluded from analysis
MA_Exclude <- MA_Summ[MA_Summ$N_Years<10 & MA_Summ$N_Years>0,]
MA_Exclude <- MA_Exclude[,c("ManagedAreaName", "N_Years")]
z <- nrow(MA_Exclude)

```

Data Impacted by Specific Value Qualifiers

Reports the amount of data impacted by the H (for dissolved oxygen & pH in program 476), I, Q, S (for Secchi depth), and U value qualifiers. It determines how much of the data for the given `ParametetrName`, `RelativeDepth`, and `ActivityType` is impacted by each value qualifier. Percentages are determined using $100 * (\# \text{ of value qualifier}) / (\# \text{ of total data})$

A variable is also created that determines if scatter plot points should be a different color based on value qualifiers of interest.

A summary data frame is created that determines the amount of data and percentage of data impacted by the value qualifiers for each managed area by year and is written to a csv file in the output directory. Columns with N are the number impacted by the value qualifier, and those with perc are the percent of the data for that managed area and year impacted by the value qualifier. + [WC Discrete Output Files in SEACAR GitHub](#) (https://github.com/FloridaSEACAR/SEACAR_Trend_Analyses/tree/main/WQ_Discrete/output)

```

# Find out how much total data exists and how much passed the initial filters
total <- length(data$Include)
pass_filter <- length(data$Include[data$Include==TRUE])
# Get the number and percentage of data entries impacted by value qualifier H
count_H <- length(grep("H", data$ValueQualifier[data$ProgramID==476]))
perc_H <- 100*count_H/length(data$ValueQualifier)
# Get the number and percentage of data entries impacted by value qualifier I
count_I <- length(grep("I", data$ValueQualifier))
perc_I <- 100*count_I/length(data$ValueQualifier)
# Get the number and percentage of data entries impacted by value qualifier Q
count_Q <- length(grep("Q", data$ValueQualifier))
perc_Q <- 100*count_Q/length(data$ValueQualifier)
# Get the number and percentage of data entries impacted by value qualifier S
count_S <- length(grep("S", data$ValueQualifier))
perc_S <- 100*count_S/length(data$ValueQualifier)
# Get the number and percentage of data entries impacted by value qualifier U
count_U <- length(grep("U", data$ValueQualifier))
perc_U <- 100*count_U/length(data$ValueQualifier)
# Copy ValueQualifier to a new VQ_Plot to create codes for plots
data$VQ_Plot <- data$ValueQualifier
# Determine if data with value qualifier H should be included for plots based
# on the parameter being observed
inc_H <- ifelse(param_name=="pH" | param_name=="Dissolved_Oxygen" |
                  param_name=="Dissolved_Oxygen_Saturation", TRUE, FALSE)
# Loops through conditions to determine what indicators to include in plots.
# If H should be included
if (inc_H==TRUE){
    # Remove any Value qualifiers that aren't H or U
    data$VQ_Plot <- gsub("[^HU]+", "", data$VQ_Plot)
}

```

```

# Standardize order of qualifiers. Puts UH as HU
data$VQ_Plot <- gsub("UH", "HU", data$VQ_Plot)
# Remove anything from ValueQualifier that isn't U from programs and that
# aren't ProgramID 476
data$VQ_Plot[na.omit(data$ProgramID!=476)] <-
  gsub("[^U]+", "", data$VQ_Plot[na.omit(data$ProgramID!=476)])
# Changes blank character strings to NA
data$VQ_Plot[data$VQ_Plot==""] <- NA
# Prints the number and percentage of H, I, Q, U value qualifiers
cat(paste0("Number of Measurements: ", total,
           ", Number Passed Filter: ", pass_filter, "\n",
           "Program 476 H Codes: ", count_H, " (", round(perc_H, 6), "%)\n",
           "I Codes: ", count_I, " (", round(perc_I, 6), "%)\n",
           "Q Codes: ", count_Q, " (", round(perc_Q, 6), "%)\n",
           "U Codes: ", count_U, " (", round(perc_U, 6), "%))")
# If Parameter is Secchi_Depth
} else if (param_name=="Secchi_Depth") {
  # Count the number of S ValueQualifier
  count_S <- length(grep("S", data$ValueQualifier))
  # Get percentage of S ValueQualifier
  perc_S <- 100*count_S/length(data$ValueQualifier)
  # Remove anything from ValueQualifier that isn't S or U
  data$VQ_Plot <- gsub("[^SU]+", "", data$VQ_Plot)
  # Change all ValueQualifier that are US to be US, standardizes codes
  data$VQ_Plot <- gsub("US", "SU", data$VQ_Plot)
  # Sets any blank character ValueQualifier to be NA
  data$VQ_Plot[data$VQ_Plot==""] <- NA
  # Prints the number and percentage of I, Q, S, U
  cat(paste0("Number of Measurements: ", total,
             ", Number Passed Filter: ", pass_filter, "\n",
             "I Codes: ", count_I, " (", round(perc_I, 6), "%)\n",
             "Q Codes: ", count_Q, " (", round(perc_Q, 6), "%)\n",
             "S Codes: ", count_S, " (", round(perc_S, 6), "%)\n",
             "U Codes: ", count_U, " (", round(perc_U, 6), "%))")
# For all other scenarios
} else{
  # Remove all ValueQualifier except U
  data$VQ_Plot <- gsub("[^U]+", "", data$VQ_Plot)
  # Sets any blank character ValueQualifier to be NA
  data$VQ_Plot[data$VQ_Plot==""] <- NA
  # Prints the number and percentage of I, Q, U
  cat(paste0("Number of Measurements: ", total,
             ", Number Passed Filter: ", pass_filter, "\n",
             "I Codes: ", count_I, " (", round(perc_I, 6), "%)\n",
             "Q Codes: ", count_Q, " (", round(perc_Q, 6), "%)\n",
             "U Codes: ", count_U, " (", round(perc_U, 6), "%))"))
}

## Number of Measurements: 581338, Number Passed Filter: 580667
## I Codes: 0 (0%)
## Q Codes: 0 (0%)
## U Codes: 0 (0%)

```

```

# Creates a data table that summarizes the number and percentage of
# ValueQualifier H, I, Q, S, and U for each managed area each year
data_summ <- data %>%
  group_by(AreaID, ManagedAreaName, Year) %>%
  summarize(ParameterName=parameter,
            RelativeDepth=depth,
            ActivityType=activity,
            N_Total=length(ResultValue),
            N_AnalysisUse=length(ResultValue[Use_In_Analysis==TRUE]),
            N_H=length(grep("H", ValueQualifier[ProgramID==476])),
            perc_H=100*N_H/length(ValueQualifier),
            N_I=length(grep("I", ValueQualifier)),
            perc_I=100*N_I/length(ValueQualifier),
            N_Q=length(grep("Q", ValueQualifier)),
            perc_Q=100*N_Q/length(ValueQualifier),
            N_S=length(grep("S", ValueQualifier)),
            perc_S=100*N_S/length(ValueQualifier),
            N_U=length(grep("U", ValueQualifier)),
            perc_U=100*N_U/length(ValueQualifier))
# Orders the data table rows based on managed area name
data_summ <- as.data.table(data_summ[order(data_summ$ManagedAreaName,
                                             data_summ$Year), ])
# Writes the ValueQualifier summary to a csv file
fwrite(data_summ, paste0(out_dir_param,"/WC_Discrete_", param_abrev, "_",
                        activity, "_", depth, "_VQSummary.csv"), sep=",")
rm(data_summ)

```

Managed Area Statistics

Gets summary statistics for each managed area. Excluded managed areas are not included into whether the data should be used or not. Uses piping from dplyr package to feed into subsequent steps. The following steps are performed:

1. Take the `data` variable and only include rows that have a `SufficientData` value of TRUE
2. Group data that have the same `ManagedAreaName`, `Year`, and `Month`.
 - Second summary statistics do not use the `Month` grouping and are only for `ManagedAreaName` and `Year`.
 - Third summary statistics do not use `Year` grouping and are only for `ManagedAreaName` and `Month`
3. For each group, provide the following information: Number of Entries (N), Lowest Value (Min), Largest Value (Max), Median, Mean, Standard Deviation, and a list of all Program IDs included in these measurements.
4. Sort the data in ascending (A to Z and 0 to 9) order based on `ManagedAreaName` then `Year` then `Month`
5. Write summary stats to a pipe-delimited .txt file in the output directory
 - WC Discrete Output Files in SEACAR GitHub (https://github.com/FloridaSEACAR/SEACAR_Trend_Analyses/tree/main/WQ_Discrete/output)

```

# Create summary statistics for each managed area based on Year and Month
# intervals.
MA_YM_Stats <- data[data$Use_In_Analysis==TRUE, ] %>%
  group_by(AreaID, ManagedAreaName, Year, Month) %>%

```

```

summarize(ParameterName=parameter,
          RelativeDepth=depth,
          ActivityType=activity,
          N_Data=length(ResultValue),
          Min=min(ResultValue),
          Max=max(ResultValue),
          Median=median(ResultValue),
          Mean=mean(ResultValue),
          StandardDeviation=sd(ResultValue),
          Programs=paste(sort(unique(ProgramName), decreasing=FALSE),
                         collapse=' ', ''),
          ProgramIDs=paste(sort(unique(ProgramID), decreasing=FALSE),
                            collapse=' ', ''))
# Puts the data in order based on ManagedAreaName, Year, then Month
MA_YM_Stats <- as.data.table(MA_YM_Stats[order(MA_YM_Stats$ManagedAreaName,
                                                MA_YM_Stats$Year,
                                                MA_YM_Stats$Month), ])
# Writes summary statistics to file
fwrite(MA_YM_Stats, paste0(out_dir_param, "/WC_Discrete_", param_abrev, "_",
                           activity, "_", depth, "_MA_MMYY_Stats.txt"), sep="|")
# Get year from start for each managed area to be used in SKT analysis
MA_YM_Stats <- MA_YM_Stats %>%
  group_by(AreaID, ManagedAreaName) %>%
  mutate(YearFromStart=Year-min(Year))
# Create decimal value of year and month values
MA_YM_Stats$YearMonthDec <- MA_YM_Stats$Year + ((MA_YM_Stats$Month-0.5) / 12)
# Create summary statistics for each managed area based on Year intervals.
MA_Y_Stats <- data[data$Use_In_Analysis==TRUE, ] %>%
  group_by(AreaID, ManagedAreaName, Year) %>%
  summarize(ParameterName=parameter,
            RelativeDepth=depth,
            ActivityType=activity,
            N_Data=length(ResultValue),
            Min=min(ResultValue),
            Max=max(ResultValue),
            Median=median(ResultValue),
            Mean=mean(ResultValue),
            StandardDeviation=sd(ResultValue),
            Programs=paste(sort(unique(ProgramName), decreasing=FALSE),
                           collapse=' ', ''),
            ProgramIDs=paste(sort(unique(ProgramID), decreasing=FALSE),
                              collapse=' ', ''))
# Puts the data in order based on ManagedAreaName then Year
MA_Y_Stats <- as.data.table(MA_Y_Stats[order(MA_Y_Stats$ManagedAreaName,
                                              MA_Y_Stats$Year), ])
# Writes summary statistics to file
fwrite(MA_Y_Stats, paste0(out_dir_param, "/WC_Discrete_", param_abrev, "_",
                           activity, "_", depth, "_MA_Yr_Stats.txt"), sep="|")
rm(MA_Y_Stats)
# Create summary statistics for each managed area based on Month intervals.
MA_M_Stats <- data[data$Use_In_Analysis==TRUE, ] %>%
  group_by(AreaID, ManagedAreaName, Month) %>%
  summarize(ParameterName=parameter,

```

```

RelativeDepth=depth,
ActivityType=activity,
N_Data=length(ResultValue),
Min=min(ResultValue),
Max=max(ResultValue),
Median=median(ResultValue),
Mean=mean(ResultValue),
StandardDeviation=sd(ResultValue),
Programs=paste(sort(unique(ProgramName), decreasing=FALSE),
               collapse=', '),
ProgramIDs=paste(sort(unique(ProgramID), decreasing=FALSE),
                  collapse=', '))
# Puts the data in order based on ManagedAreaName then Month
MA_M_Stats <- as.data.table(MA_M_Stats[order(MA_M_Stats$ManagedAreaName,
                                              MA_M_Stats$Month), ])
# Writes summary statistics to file
fwrite(MA_M_Stats, paste0(out_dir_param,"/WC_Discrete_", param_abrev, "_",
                         activity, "_", depth, "_MA_Mo_Stats.txt"), sep="|")
rm(MA_M_Stats)

```

Monitoring Location Statistics

Gets monitoring location statistics, which is defined as a unique combination of `ManagedAreaName`, `ProgramID`, `ProgramAreaName`, and `ProgramLocationID`, using piping from `dplyr` package. The following steps are performed:

1. Take the `data` variable and only include rows that have a `SufficientData` value of TRUE
2. Group data that have the same `ManagedAreaName`, `ProgramID`, `ProgramName`, and `ProgramLocationID`.
3. For each group, provide the following information: Earliest Sample Date (`EarliestSampleDate`), Latest Sample Date (`LastSampleDate`), Number of Entries (N), Lowest Value (Min), Largest Value (Max), Median, Mean, and Standard Deviation.
4. Sort the data in ascending (A to Z and 0 to 9) order based on `ManagedAreaName` then `ProgramName` then `ProgramID` then `ProgramLocationID`
5. Write summary stats to a pipe-delimited .txt file in the output directory
 - WC Discrete Output Files in SEACAR GitHub (https://github.com/FloridaSEACAR/SEACAR_Trend_Analyses/tree/main/WQ_Discrete/output)

```

# Gets summary statistics for monitoring locations, which are defined as unique
# combinations of ManagedAreaName, ProgramID, And ProgramLocationID
Mon_Stats <- data[data$Use_In_Analysis==TRUE, ] %>%
  group_by(AreaID, ManagedAreaName, ProgramID, ProgramName,
           ProgramLocationID) %>%
  summarize(ParameterName=parameter,
            RelativeDepth=depth,
            ActivityType=activity,
            EarliestSampleDate=min(SampleDate),
            LastSampleDate=max(SampleDate),
            N_Data=length(ResultValue),
            Min=min(ResultValue),
            Max=max(ResultValue),
            Median=median(ResultValue),

```

```

    Mean=mean(ResultValue),
    StandardDeviation=sd(ResultValue))
# Order data rows by ManagedAreaName, ProgramName, ProgramID, then
# ProgramLocationID
Mon_Stats <- as.data.table(Mon_Stats[order(Mon_Stats$ManagedAreaName,
                                             Mon_Stats$ProgramName,
                                             Mon_Stats$ProgramID,
                                             Mon_Stats$ProgramLocationID), ])
# Write summary statistics to file
fwrite(Mon_Stats, paste0(out_dir_param,"/WC_Discrete_", param_abrev, "_",
                        activity, "_", depth, "_MonLoc_Stats.txt"), sep="|")
rm(Mon_Stats)

```

Seasonal Kendall Tau Analysis

Gets seasonal Kendall Tau statistics using the `kendallSeasonalTrendTest` from the `EnvStats` package. The Trend parameter is determined from a user-defined function based on the median, Senn slope, and p values from the data. Analysis modified from code created by Jason Scolaro that performed at The Water Atlas: <https://sarasota.wateratlas.usf.edu/water-quality-trends/#analysis-overview>

The following steps are performed:

1. Set the column names for the variable holding the SKT stat values
2. Create a data frame with the same number of columns as column names, and the same number of rows as the number of managed areas being analyzed.
3. Starts a loop that goes through each managed area
4. Gets data for that ManagedAreaName and the number of data rows.
5. Gets basic statistics for the ManagedAreaName from the MA_Summ variable.
6. Performs a seasonal Kendall Tau trend test with the assumption that data is not serially correlated (independent.obs=TRUE)
 - If analysis returns NULL, performs SKT assuming data is serially auto-correlated (independent.obs=FALSE)
7. Store the SKT result values in the skt_stats data frame created.
8. Determines the Trend of the slope based on the statistics and SKT parameters.
9. Merge data frames together to create a cumulative data frame with all statistics and round values to appropriate decimal points.
10. Write summary stats to a pipe-delimited .txt file in the output directory
 - WC Discrete Output Files in SEACAR GitHub (https://github.com/FloridaSEACAR/SEACAR_Trend_Analyses/tree/main/WQ_Discrete/output)

```

# List for column names
c_names <- c("AreaID", "ManagedAreaName", "Independent", "tau", "p",
            "SennSlope", "SennIntercept", "ChiSquared", "pChiSquared", "Trend")

skt_stats <- data.frame(matrix(ncol = length(c_names), nrow = n))

colnames(skt_stats) <- c_names
# Determines if there are any managed areas to analyze
if(n==0){

```

```

print("There are no managed areas that qualify.")
} else{
  # Starts cycling through managed areas to determine seasonal Kendall Tau
  for (i in 1:n) {
    # Gets the number of rows of data for the managed area
    data_SKT <- MA_YM_Stats[MA_YM_Stats$ManagedAreaName==MA_Include[i], ]
    x <- nrow(data_SKT)
    # Perform analysis if there is more than 1 row
    if (x>0) {
      # Store the managed area summary statistics to be used in
      # trend analysis
      SKT.med <- MA_Summ$Median[MA_Summ$ManagedAreaName==MA_Include[i]]
      SKT.minYr <- MA_Summ$EarliestYear[MA_Summ$ManagedAreaName==
                                         MA_Include[i]]
      SKT.maxYr <- MA_Summ$LatestYear[MA_Summ$ManagedAreaName==MA_Include[i]]
      SKT.ind <- TRUE
      SKT <- kendallSeasonalTrendTest(y=data_SKT$Mean,
                                       season=data_SKT$Month,
                                       year=data_SKT$YearFromStart,
                                       independent.obs=SKT.ind)
      if(is.na(SKT$estimate[1])==TRUE){
        SKT.ind <- FALSE
        SKT <- kendallSeasonalTrendTest(y=data_SKT$Mean,
                                         season=data_SKT$Month,
                                         year=data_SKT$YearFromStart,
                                         independent.obs=SKT.ind)
      }
      skt_stats$AreaID[i] <-
        MA_Summ$AreaID[MA_Summ$ManagedAreaName==MA_Include[i]]
      skt_stats$ManagedAreaName[i] <-
        MA_Summ$ManagedAreaName[MA_Summ$ManagedAreaName==MA_Include[i]]
      skt_stats$Independent[i] <- SKT.ind
      skt_stats$tau[i] <- SKT$estimate[1]
      skt_stats$p[i] <- SKT$p.value[2]
      skt_stats$SennSlope[i] <- SKT$estimate[2]
      skt_stats$SennIntercept[i] <- SKT$estimate[3]
      skt_stats$ChiSquared[i] <- SKT$statistic[1]
      skt_stats$pChiSquared[i] <- SKT$p.value[1]
      # If the p value is less than 5% and the slope is greater than 10% of the
      # median value, the trend is large (2).
      if (skt_stats$p[i] < .05 & abs(skt_stats$SennSlope[i]) >
          abs(SKT.med) / 10.) {
        skt_stats$Trend[i] <- 2
      }
      # If the p value is less than 5% and the slope is less than 10% of the
      # median value, there is a trend (1).
      }else if (skt_stats$p[i] < .05 & abs(skt_stats$SennSlope[i]) <
                 abs(SKT.med) / 10.) {
        skt_stats$Trend[i] <- 1
      }
      # Otherwise, there is no trend (0)
    }else {
      skt_stats$Trend[i] <- 0
    }
  }
}

```

```

        }
        # Sets the sign of the trend based on Senn Slope direction
        if (skt_stats$SennSlope[i] <= 0) {
            skt_stats$Trend[i] <- -skt_stats$Trend[i]
        }
    }

    # Stores as data frame
    skt_stats <- as.data.frame(skt_stats)

}

# Clears unused variables
rm(SKT, data_SKT, x, SKT.med, SKT.minYr, SKT.maxYr, SKT.ind)
# Combines the skt_stats with MA_Summ
skt_stats <- merge.data.frame(MA_Summ, skt_stats,
                               by=c("AreaID", "ManagedAreaName"), all=TRUE)

skt_stats <- as.data.table(skt_stats[order(skt_stats$ManagedAreaName), ])

# Sets variables to proper format and rounds values if necessary
skt_stats$tau <- round(as.numeric(skt_stats$tau), digits=4)
skt_stats$p <- format(round(as.numeric(skt_stats$p), digits=4),
                       scientific=FALSE)
skt_stats$SennSlope <- as.numeric(skt_stats$SennSlope)
skt_stats$SennIntercept <- as.numeric(skt_stats$SennIntercept)
skt_stats$ChiSquared <- round(as.numeric(skt_stats$ChiSquared), digits=4)
skt_stats$pChiSquared <- round(as.numeric(skt_stats$pChiSquared), digits=4)
skt_stats$Trend <- as.integer(skt_stats$Trend)

# Writes combined statistics to file
fwrite(select(skt_stats, -c(EarliestSampleDate)),
       paste0(out_dir_param, "/WC_Discrete_", param_abrev, "_",
              activity, "_", depth, "_KendallTau_Stats.txt"),
       sep="|")

# Removes data rows with no ResultValue (created by merging with MA_All)
data <- data[!is.na(data$ResultValue),]

# Gets x and y values for starting point for trendline
KT.Plot <- skt_stats %>%
    group_by(ManagedAreaName) %>%
    summarize(x=decimal_date(EarliestSampleDate),
              y=(x-EarliestYear)*SennSlope+SennIntercept)
# Gets x and y values for ending point for trendline
KT.Plot2 <- skt_stats %>%
    group_by(ManagedAreaName) %>%
    summarize(x=decimal_date(LastSampleDate),
              y=(x-EarliestYear)*SennSlope+SennIntercept)
# Combines the starting and endpoints for plotting the trendline
KT.Plot <- bind_rows(KT.Plot, KT.Plot2)
rm(KT.Plot2)
KT.Plot <- as.data.table(KT.Plot[order(KT.Plot$ManagedAreaName), ])

```

```
KT.Plot <- KT.Plot[!is.na(KT.Plot$y),]
```

Appendix I: Scatter Plot of Entire Dataset

This part will create a scatter plot of the all data that passed initial filtering criteria with points colored based on specific value qualifiers. The values determined at the beginning (`year_lower`, `year_upper`, `min_RV`, `mn_RV`, `x_scale`, and `y_scale`) are solely for use by the plotting functions and are not output as part of the computed statistics.

```
# Defines standard plot theme: black and white, no major or minor grid lines,
# Arial font. Title is centered, size 12, and blue (hex coded). Subtitle is
# centered, size 10, and blue (hex coded). Legend title is size 10 and the
# legend is left-justified. X-axis title is size 10 and the margins are padded
# at the top and bottom to give more space for angled axis labels. Y-axis title
# is size 10 and margins are padded on the right side to give more space for
# axis labels. Axis labels are size 10 and the x-axis labels are rotated -45
# degrees with a horizontal justification that aligns them with the tick mark
plot_theme <- theme_bw() +
  theme(panel.grid.major = element_blank(),
    panel.grid.minor = element_blank(),
    text=element_text(family="Arial"),
    plot.title=element_text(hjust=0.5, size=12, color="#314963"),
    plot.subtitle=element_text(hjust=0.5, size=10, color="#314963"),
    legend.title=element_text(size=10),
    legend.text.align = 0,
    axis.title.x = element_text(size=10, margin = margin(t = 5, r = 0,
      b = 10, l = 0)),
    axis.title.y = element_text(size=10, margin = margin(t = 0, r = 10,
      b = 0, l = 0)),
    axis.text=element_text(size=10),
    axis.text.x=element_text(angle = 60, hjust = 1))
# Gets first and most recent years from data set
year_lower <- min(data$Year)
year_upper <- max(data$Year)
# Gets minimum, mean, and standard deviation of ResultValue for setting y-axis
# scale
min_RV <- min(data$ResultValue)
mn_RV <- mean(data$ResultValue[data$ResultValue <
  quantile(data$ResultValue, 0.98)])
sd_RV <- sd(data$ResultValue[data$ResultValue <
  quantile(data$ResultValue, 0.98)])
x_scale <- ifelse(year_upper - year_lower > 30, 10, 5)
y_scale <- mn_RV + 4 * sd_RV


# Create plot object for auto-scaled y-axis plot
p1 <- ggplot(data=data[data$Include==TRUE,],
  aes(x=SampleDate, y=ResultValue, fill=VQ_Plot)) +
  geom_point(shape=21, size=3, color="#333333", alpha=0.75) +
  labs(subtitle="Autoscale",
    x="Year", y=paste0("Values (", unit, ")"),
    fill="Value Qualifier") +
  plot_theme +
```

```

theme(legend.position="top", legend.box="horizontal",
      legend.justification="right") +
scale_x_date(labels=date_format("%Y")) +
{if(inc_H==TRUE){
  scale_fill_manual(values=c("H"= "#F8766D", "U"= "#00BFC4",
                            "HU"="#7CAE00"), na.value="#cccccc")
} else if(param_name=="Secchi_Depth"){
  scale_fill_manual(values=c("S"= "#F8766D", "U"= "#00BFC4",
                            "SU"="#7CAE00"), na.value="#cccccc")
} else {
  scale_fill_manual(values=c("U"= "#00BFC4"), na.value="#cccccc")
}}
# Create plot object for y-axis scaled plot
p2 <- ggplot(data=data[data$Include==TRUE,],
              aes(x=SampleDate, y=ResultValue, fill=VQ_Plot)) +
  geom_point(shape=21, size=3, color="#333333", alpha=0.75) +
  ylim(min_RV, y_scale) +
  labs(subtitle="Scaled to 4x Standard Deviation",
       x="Year", y=paste0("Values (", unit, ")")) +
  plot_theme +
  theme(legend.position="none") +
  scale_x_date(labels=date_format("%Y")) +
{if(inc_H==TRUE){
  scale_fill_manual(values=c("H"= "#F8766D", "U"= "#00BFC4",
                            "HU"="#7CAE00"), na.value="#cccccc")
} else if(param_name=="Secchi_Depth"){
  scale_fill_manual(values=c("S"= "#F8766D", "U"= "#00BFC4",
                            "SU"="#7CAE00"), na.value="#cccccc")
} else {
  scale_fill_manual(values=c("U"= "#00BFC4"), na.value="#cccccc")
}}
# Create legend object
leg <- get_legend(p1)
# Arrange plots and legend
pset <- ggarrange(leg, p1 + theme(legend.position="none"), p2,
                  ncol=1, heights=c(0.1, 1, 1))
# Create title object
p0 <- ggplot() + labs(title="Scatter Plot for Entire Dataset") +
  plot_theme + theme(panel.border=element_blank(),
                     panel.grid.major=element_blank(),
                     panel.grid.minor=element_blank(),
                     axis.line=element_blank())
# Arrange and print title with plots
ggarrange(p0, pset, ncol=1, heights=c(0.1, 1))

```

Scatter Plot for Entire Dataset



Appendix II: Dataset Summary Box Plots

Box plots are created by using the entire data set and excludes any data that has been previously filtered out. The scripts that create plots follow this format

1. Use the data set that only has `SufficientData` of TRUE
2. Set what values are to be used for the x-axis, y-axis, and the variable that should determine groups for the box plots
3. Set the plot type as a box plot with the size of the outlier points
4. Create the title, x-axis, y-axis, and color fill labels
5. Set the y and x limits
6. Make the axis labels bold
7. Plot the arrangement as a set of panels

This set of box plots are grouped by year.

```
# Get minimum, mean, and standard deviation of the data
min_RV <- min(data$ResultValue[data$Include==TRUE])
mn_RV <- mean(data$ResultValue[data$Include==TRUE] &
                data$ResultValue <
                quantile(data$ResultValue, 0.98)))
sd_RV <- sd(data$ResultValue[data$Include==TRUE] &
                data$ResultValue <
                quantile(data$ResultValue, 0.98)))

# Sets y scale based on data
y_scale <- mn_RV + 4 * sd_RV

# Create plot object for auto-scaled y-axis plot
p1 <- ggplot(data=data[data$Include==TRUE], ),
  aes(x=Year, y=ResultValue, group=Year)) +
  geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
               outlier.size=3, outlier.color="#333333",
               outlier.fill="#cccccc", outlier.alpha=0.75) +
  labs(subtitle="Autoscale", x="Year",
       y=paste0("Values (", unit, ")")) +
  plot_theme

# Create plot object for y-axis scaled plot
p2 <- ggplot(data=data[data$Include==TRUE], ),
  aes(x=Year, y=ResultValue, group=Year)) +
  geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
               outlier.size=3, outlier.color="#333333",
               outlier.fill="#cccccc", outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation", x="Year",
       y=paste0("Values (", unit, ")")) +
  ylim(min_RV, y_scale) +
  plot_theme

# Create plot object for y-axis scaled plot for past 10 years
p3 <- ggplot(data=data[data$Include==TRUE], ),
  aes(x=as.integer(Year), y=ResultValue, group=Year)) +
  geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
               outlier.size=3, outlier.color="#333333",
               outlier.fill="#cccccc", outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation, Last 10 Years",
       x="Year", y=paste0("Values (", unit, ")")) +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits=c(max(data$Year) - 10.5, max(data$Year)+1),
                     breaks=seq(max(data$Year) - 10, max(data$Year), 2)) +
  plot_theme

# Arrange plot objects
set <- ggarrange(p1, p2, p3, ncol=1)
```

```

# Create title object for plots
p0 <- ggplot() + labs(title="Summary Box Plots for Entire Data",
                      subtitle="By Year") + plot_theme +
  theme(panel.border=element_blank(), panel.grid.major=element_blank(),
        panel.grid.minor=element_blank(), axis.line=element_blank())
# Arrange title on plots
Yset <- ggarrange(p0, set, ncol=1, heights=c(0.07, 1))

```

This set of box plots are grouped by year and month with the color being related to the month.

```

# Create plot object for auto-scaled y-axis plot
p1 <- ggplot(data=data[data$Include==TRUE, ],
              aes(x=YearMonthDec, y=ResultValue,
                  group=YearMonth, color=as.factor(Month))) +
  geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
  labs(subtitle="Autoscale", x="Year",
       y=paste0("Values (", unit, ")"), color="Month") +
  plot_theme +
  theme(legend.position="top", legend.box="horizontal") +
  guides(color=guide_legend(nrow=1))
# Create plot object for y-axis scaled plot
p2 <- ggplot(data=data[data$Include==TRUE, ],
              aes(x=YearMonthDec, y=ResultValue,
                  group=YearMonth, color=as.factor(Month))) +
  geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation",
       x="Year", y=paste0("Values (", unit, ")")) +
  ylim(min_RV, y_scale) +
  plot_theme +
  theme(legend.position="none", axis.text.x=element_text(face="bold"),
        axis.text.y=element_text(face="bold"))
# Create plot object for y-axis scaled plot for past 10 years
p3 <- ggplot(data=data[data$Include==TRUE, ],
              aes(x=YearMonthDec, y=ResultValue,
                  group=YearMonth, color=as.factor(Month))) +
  geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation, Last 10 Years",
       x="Year", y=paste0("Values (", unit, ")")) +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits=c(max(data$Year) - 10.5, max(data$Year)+1),
                     breaks=seq(max(data$Year) - 10, max(data$Year), 2)) +
  plot_theme +
  theme(legend.position="none")
# Create legend item
leg <- get_legend(p1)
# Arrange plots and legend
set <- ggarrange(leg, p1 + theme(legend.position="none"), p2, p3, ncol=1,
                 heights=c(0.1, 1, 1, 1))
# Create plot title object
p0 <- ggplot() + labs(title="Summary Box Plots for Entire Data",
                      subtitle="By Year & Month") + plot_theme +
  theme(panel.border=element_blank(), panel.grid.major=element_blank(),
        panel.grid.minor=element_blank(), axis.line=element_blank())


```

```
# Arrange plots and title
YMset <- ggarrange(p0, set, ncol=1, heights=c(0.07, 1))
```


The following box plots are grouped by month with fill color being related to the month. This is designed to view potential seasonal trends.


```
# Create plot object for auto-scaled y-axis plot
p1 <- ggplot(data=data[data$Include==TRUE, ],
    aes(x=Month, y=ResultValue,
        group=Month, fill=as.factor(Month))) +
    geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
        outlier.color="#333333", outlier.alpha=0.75) +
    labs(subtitle="Autoscale", x="Month",
        y=paste0("Values (", unit, ")"), fill="Month") +
    scale_x_continuous(limits=c(0, 13), breaks=seq(3, 12, 3)) +
    plot_theme +
    theme(legend.position="top", legend.box="horizontal") +
    guides(fill=guide_legend(nrow=1))
# Create plot object for y-axis scaled plot
p2 <- ggplot(data=data[data$Include==TRUE, ],
    aes(x=Month, y=ResultValue,
        group=Month, fill=as.factor(Month))) +
    geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
        outlier.color="#333333", outlier.alpha=0.75) +
    labs(subtitle="Scaled to 4x Standard Deviation",
        x="Month", y=paste0("Values (", unit, ")")) +
    ylim(min_RV, y_scale) +
    scale_x_continuous(limits=c(0, 13), breaks=seq(3, 12, 3)) +
    plot_theme +
    theme(legend.position="none")
# Create plot object for y-axis scaled plot for past 10 years
p3 <- ggplot(data=data[data$Include==TRUE &
    data$Year >= max(data$Year) - 10, ],
    aes(x=Month, y=ResultValue,
        group=Month, fill=as.factor(Month))) +
    geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
        outlier.color="#333333", outlier.alpha=0.75) +
    labs(subtitle="Scaled to 4x Standard Deviation, Last 10 Years",
        x="Month", y=paste0("Values (", unit, ")")) +
    ylim(min_RV, y_scale) +
    scale_x_continuous(limits=c(0, 13), breaks=seq(3, 12, 3)) +
    plot_theme +
    theme(legend.position="none")
# Create legend object
leg <- get_legend(p1)
# Arrange plots and legend
set <- ggarrange(leg, p1 + theme(legend.position="none"), p2, p3, ncol=1,
    heights=c(0.1, 1, 1, 1))
# Create title object for plots
p0 <- ggplot() + labs(title="Summary Box Plots for Entire Data",
    subtitle="By Month") + plot_theme +
    theme(panel.border=element_blank(), panel.grid.major=element_blank(),
        panel.grid.minor=element_blank(), axis.line=element_blank())
```

```
# Arrange plots and title
Mset <- ggarrange(p0, set, ncol=1, heights=c(0.07, 1))
```



Summary Box Plots for Entire Data
By Year & Month





Appendix III: Managed Area Trendlines

The plots created in this section are designed to show the general trend of the data. Data is taken and grouped by `ManagedAreaName`. The trendlines on the plots are created using the Senn slope and intercept

from the seasonal Kendall Tau analysis. The scripts that create plots follow this format

1. Use the data set that only has `SufficientData` of TRUE for the desired managed area
2. Determine the earliest and latest year of the data to create x-axis scale and intervals
3. Determine the minimum, mean, and standard deviation for the data to be used for y-axis scales
 - Excludes the top 2% of values to reduce the impact of extreme outliers on the y-axis scale
4. Set what values are to be used for the x-axis, y-axis, and the variable that should determine groups for the plots
5. Set the plot type as a point plot with the size of the points
6. Add the linear trend
7. Create the title, x-axis, y-axis, and color fill labels
8. Set the y and x limits
9. Make the axis labels bold
10. Plot the arrangement as a set of panels

```
# Determines whether analyzed managed areas exist. If they do, begins
# looping through them
if(n==0){
  print("There are no managed areas that qualify.")
} else {
  # Begins looping through each managed area
  for (i in 1:n) {
    # Gets data to be used in plot for managed area
    plot_data <- MA_YM_Stats[MA_YM_Stats$ManagedAreaName==MA_Include[i],]
    # Gets trendline data for managed area
    KT.plot_data <- KT.Plot[KT.Plot$ManagedAreaName==MA_Include[i],]
    #Determine max and min time (Year) for plot x-axis
    t_min <- min(plot_data$Year)
    t_max <- max(plot_data$YearMonthDec)
    t_max_brk <- as.integer(round(t_max, 0))
    t <- t_max-t_min
    min_RV <- min(plot_data$Mean)

    # Sets break intervals based on the number of years spanned by data
    if(t>=30){
      brk <- -10
    }else if(t<30 & t>=10){
      brk <- -5
    }else if(t<10 & t>=4){
      brk <- -2
    }else if(t<4){
      brk <- -1
    }


    # Create plot object with data and trendline
    p1 <- ggplot(data=plot_data,
                  aes(x=YearMonthDec, y=Mean)) +
      geom_line(size=0.75, color="#333333", alpha=0.6) +
      geom_point(shape=21, size=3, color="#333333", fill="#cccccc",
                 alpha=0.75) +
      geom_line(data=KT.plot_data, aes(x=x, y=y),
                color="#000099", size=1.2, alpha=0.7) +
      labs(title=paste0(MA_Include[i]),
```

```

    subtitle=parameter,
    x="Year", y=paste0("Values (", unit, ")"))
  scale_x_continuous(limits=c(t_min-0.25, t_max+0.25),
                     breaks=seq(t_max_brk, t_min, brk)) +
  plot_theme
# Creates ResultTable to display statistics below plot
ResultTable <- skt_stats[skt_stats$ManagedAreaName==MA_Include[i], ] %>%
  select(RelativeDepth, N_Data, N_Years, Median, Independent, tau, p,
         SennSlope, SennIntercept, ChiSquared, pChiSquared, Trend)
# Create table object
t1 <- ggtexttable(ResultTable, rows=NULL,
                   theme=ttheme(base_size=10)) %>%
  tab_add_footnote(text="p < 0.00005 appear as 0 due to rounding.\n
                        SennIntercept is intercept value at beginning of
                        record for monitoring location",
                   size=10, face="italic")
# Arrange and display plot and statistic table
print(ggarrange(p1, t1, ncol=1, heights=c(0.85, 0.15)))
# Add extra space at the end to prevent the next figure from being too
# close.
cat("\n \n \n")
rm(plot_data)
rm(KTset, leg)
rm(plot_data)
rm(KTset, leg)
}
}

```


Alligator Harbor Aquatic Preserve
Salinity



RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	6081	27	31	TRUE	-0.0942	0.0242	-0.04100183	31.7995	6.2736	0.8545	-1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	36009	34	13.5	TRUE	-0.0833	0.0381	-0.07281575	18.64137	11.1731	0.4289	-1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Apalachicola National Estuarine Research Reserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	53903	35	14.7	TRUE	-0.23	0.0000	-0.1969602	24.94785	9.8559	0.5434	-1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Banana River Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	23929	33	19.84	TRUE	0.0972	0.0074	0.08616568	19.68024	2.9431	0.9915	1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Big Bend Seagrasses Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	96183	39	22.6	TRUE	-0.1602	0.0000	-0.1045963	24.05822	8.1082	0.7036	-1

$p < 0.00005$ appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Biscayne Bay Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	9196	31	31.21	TRUE	-0.3176	0.0000	-0.2048448	33.38105	6.9265	0.805	-1

$p < 0.00005$ appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Boca Ciega Bay Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	16569	57	32.7	TRUE	-0.026	0.3923	-0.003768997	32.66882	3.7126	0.9776	0

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Cape Haze Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	7394	38	30	TRUE	0.0525	0.1652	0.02823636	27.64974	6.2482	0.8563	0

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location


Cape Romano-Ten Thousand Islands Aquatic Preserve
Salinity



RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	6232	42	32.1	TRUE	0.0686	0.0689	0.03910203	29.388	11.1852	0.4279	0

p < 0.00005 appear as 0 due to rounding.


SennIntercept is intercept value at beginning of record for monitoring location



RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	14970	39	13.3	TRUE	-0.2382	0.0000	-0.2438846	24.31074	7.9962	0.7136	-1

$p < 0.00005$ appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	110	21	36.60015	TRUE	0.2647	0.0005	0.04434167	36.373	20.1885	0.0428	1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Estero Bay Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	3650	31	31.8	TRUE	-0.3522	0.0000	-0.2181639	41.07904	6.2637	0.8552	-1

$p < 0.00005$ appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Florida Keys National Marine Sanctuary
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	27856	47	36.16395	TRUE	0.0889	0.0102	0.02159948	34.64405	4.5635	0.9505	1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Fort Clinch State Park Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	813	24	33.4	TRUE	0.0628	0.2147	0.03333333	32.58163	6.4825	0.8393	0

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Fort Pickens State Park Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	853	31	25.1874	TRUE	-0.0649	0.2012	-0.07256092	28.89513	7.168	0.7853	0

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Gasparilla Sound-Charlotte Harbor Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	35507	48	26.4	TRUE	-0.2405	0.0000	-0.1119048	32.65282	8.1248	0.7021	-1

$p < 0.00005$ appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Guana River Marsh Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	5616	29	30.7	TRUE	-0.1555	0.0001	-0.1702778	31.38431	4.3251	0.9594	-1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Guana Tolomato Matanzas National Estuarine Research Reserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	17431	30	31.6	TRUE	-0.3259	0.0000	-0.3074501	36.34259	4.547	0.9511	-1

$p < 0.00005$ appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Indian River-Malabar to Vero Beach Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	43167	36	25.2	TRUE	-0.2785	0.0000	-0.226597	30.71254	6.9369	0.8042	-1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Indian River-Vero Beach to Ft. Pierce Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	5933	32	28.9	TRUE	0.0119	0.7220	0.009381614	28.65525	5.9632	0.8758	0

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location


Jensen Beach to Jupiter Inlet Aquatic Preserve
Salinity



RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	7472	34	32.8	TRUE	0.1445	0.0001	0.07158508	30.20776	8.7141	0.6483	1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	6116	56	33.92	TRUE	-0.1002	0.0012	-0.02092593	35.04256	7.1518	0.7867	-1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Lignumvitae Key Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	156	13	36.23	TRUE	0.1897	0.0662	0.04041502	35.84284	15.1318	0.1765	0

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Loxahatchee River-Lake Worth Creek Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	6574	34	25.1	TRUE	0.1129	0.0032	0.09615385	17.78893	15.4067	0.1646	1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Matlacha Pass Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	6173	39	26.2	TRUE	-0.0631	0.0946	-0.04895147	28.98424	2.5242	0.9956	0

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Mosquito Lagoon Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	3988	29	32.4	TRUE	0.1592	0.0001	0.09509615	31.4162	8.8302	0.6376	1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Nassau River-St. Johns River Marshes Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	9319	28	30.4	TRUE	-0.004	0.9033	-0.005910973	29.54442	5.1863	0.9218	0

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Nature Coast Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	5548	38	24.3	TRUE	0.0519	0.2533	0.03505722	22.34158	9.2453	0.5993	0

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

North Fork St. Lucie Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	3056	28	4.4	TRUE	-0.1092	0.0070	-0.07528571	9.759105	3.5138	0.982	-1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Pellicer Creek Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	1968	21	17	TRUE	-0.0566	0.2880	-0.1174183	17.05351	7.955	0.7173	0

$p < 0.00005$ appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Pine Island Sound Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	19814	62	32.8	TRUE	-0.0658	0.0423	-0.01227936	33.18054	5.9513	0.8766	-1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Pinellas County Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	55159	63	29.17	TRUE	-0.4049	0.0000	-0.1139918	33.36866	10.5294	0.4835	-1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location


Rocky Bayou State Park Aquatic Preserve
Salinity



RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	313	24	14.2	TRUE	-0.0342	0.4294	-0.06794872	16.5135	10.3321	0.5008	0

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	3504	44	34	TRUE	0.0115	0.7078	0.003178295	33.94441	7.3688	0.7685	0

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Rookery Bay National Estuarine Research Reserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	10327	51	32.83	TRUE	-0.0696	0.0519	-0.02009524	33.24631	8.9351	0.6279	0

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Southeast Florida Coral Reef Ecosystem Conservation Area
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	568	34	35.57625	TRUE	0.2032	0.0011	0.06472222	32.74225	3.1227	0.989	1

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

St. Andrews State Park Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	1128	30	31.5	TRUE	-0.2322	0.0001	-0.1403226	37.86529	8.9804	0.6237	-1

$p < 0.00005$ appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

St. Joseph Bay Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	4084	30	32.04	TRUE	-0.0825	0.0586	-0.03100576	32.86978	8.0266	0.7109	0

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

St. Martins Marsh Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	5759	30	17.84	TRUE	0.0994	0.0207	0.07142857	16.61682	6.4593	0.841	1

$p < 0.00005$ appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Terra Ceia Aquatic Preserve
Salinity




RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	17260	47	30.6	TRUE	-0.1065	0.0016	-0.0296337	31.54071	9.0018	0.6217	-1

$p < 0.00005$ appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location


Tomoka Marsh Aquatic Preserve
Salinity



RelativeDepth	N_Data	N_Years	Median	Independent	tau	p	SennSlope	SennIntercept	ChiSquared	pChiSquared	Trend
Surface	357	23	15.97	TRUE	0.1217	0.0820	0.252	13.42793	8.9247	0.6288	0

p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location



p < 0.00005 appear as 0 due to rounding.

SennIntercept is intercept value at beginning of record for monitoring location

Appendix IV: Managed Area Summary Box Plots

Data is taken and grouped by `ManagedAreaName`. The scripts that create plots follow this format

1. Use the data set that only has `SufficientData` of TRUE for the desired managed area
2. Determine the earliest and latest year of the data to create x-axis scale and intervals
3. Determine the minimum, mean, and standard deviation for the data to be used for y-axis scales
 - Excludes the top 2% of values to reduce the impact of extreme outliers on the y-axis scale
4. Set what values are to be used for the x-axis, y-axis, and the variable that should determine groups for the box plots
5. Set the plot type as a box plot with the size of the outlier points
6. Create the title, x-axis, y-axis, and color fill labels
7. Set the y and x limits
8. Make the axis labels bold
9. Plot the arrangement as a set of panels

The following plots are arranged by ManagedAreaName with data grouped by Year, then Year and Month, then finally Month only. Each managed area will have 3 sets of plots, each with 3 panels in them. Each panel goes as follows:

1. Y-axis autoscaled
2. Y-axis set to be mean + 4 times the standard deviation
3. Y-axis set to be mean + 4 times the standard deviation for most recent 10 years of data

```
# Determines whether analyzed managed area exist. If they do, begins
# looping through them
if(n==0){
  print("There are no managed areas that qualify.")
} else {
  # Begin looping through managed area
  for (i in 1:n) {
    # Determine upper and lower bounds of time for x-axis
    plot_data <- data[data$SufficientData==TRUE &
      data$ManagedAreaName==MA_Include[i],]
    year_lower <- min(plot_data$Year)
    year_upper <- max(plot_data$Year)
    # Determine upper and lower bounds of ResultValue for y-axis
    min_RV <- min(plot_data$ResultValue)
    mn_RV <- mean(plot_data$ResultValue[plot_data$ResultValue <
      quantile(data$ResultValue, 0.98)])
    sd_RV <- sd(plot_data$ResultValue[plot_data$ResultValue <
      quantile(data$ResultValue, 0.98)])
    # Sets x- and y-axis scale
    x_scale <- ifelse(year_upper - year_lower > 30, 10, 5)
    y_scale <- mn_RV + 4 * sd_RV

    ##Year plots
    # Create plot object for auto-scaled y-axis plot
    p1 <- ggplot(data=plot_data,
      aes(x=Year, y=ResultValue, group=Year)) +
      geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
        outlier.size=3, outlier.color="#333333",
        outlier.fill="#cccccc", outlier.alpha=0.75) +
      labs(subtitle="Autoscale",
        x="Year", y=paste0("Values (", unit, ")")) +
      scale_x_continuous(limits=c(year_lower - 1, year_upper + 1),
        breaks=rev(seq(year_upper,
          year_lower, -x_scale))) +
      plot_theme
    # Create plot object for y-axis scaled plot
    p2 <- ggplot(data=plot_data,
      aes(x=Year, y=ResultValue, group=Year)) +
      geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
        outlier.size=3, outlier.color="#333333",
        outlier.fill="#cccccc", outlier.alpha=0.75) +
      labs(subtitle="Scaled to 4x Standard Deviation",
        x="Year", y=paste0("Values (", unit, ")")) +
      ylim(min_RV, y_scale) +
      scale_x_continuous(limits=c(year_lower - 1, year_upper + 1),
        breaks=rev(seq(year_upper,
```

```

                year_lower, -x_scale))) +
plot_theme
# Create plot object for y-axis scaled plot for past 10 years
p3 <- ggplot(data=plot_data[plot_data$Year >= year_upper - 10, ],
             aes(x=Year, y=ResultValue, group=Year)) +
geom_boxplot(color="#333333", fill="#cccccc", outlier.shape=21,
             outlier.size=3, outlier.color="#333333",
             outlier.fill="#cccccc", outlier.alpha=0.75) +
labs(subtitle="Scaled to 4x Standard Deviation, Last 10 Years",
     x="Year", y=paste0("Values (", unit, ")")) +
ylim(min_RV, y_scale) +
scale_x_continuous(limits=c(year_upper - 10.5, year_upper + 1),
                   breaks=rev(seq(year_upper, year_upper - 10,-2))) +
plot_theme
# Arrange plot objects
Yset <- ggarrange(p1, p2, p3, ncol=1)
# Create plot title object
p0 <- ggplot() + labs(title=paste0(MA_Include[i]),
                      subtitle="By Year") +
plot_theme + theme(panel.border=element_blank(),
                    panel.grid.major=element_blank(),
                    panel.grid.minor=element_blank(),
                    axis.line=element_blank())

## Year & Month Plots
# Create plot object for auto-scaled y-axis plot
p4 <- ggplot(data=plot_data,
             aes(x=YearMonthDec, y=ResultValue,
                 group=YearMonth, color=as.factor(Month))) +
geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
labs(subtitle="Autoscale",
     x="Year", y=paste0("Values (", unit, ")"), color="Month") +
scale_x_continuous(limits=c(year_lower - 1, year_upper + 1),
                   breaks=rev(seq(year_upper,
                                 year_lower, -x_scale))) +
plot_theme +
theme(legend.position="none")
# Create plot object for y-axis scaled plot
p5 <- ggplot(data=plot_data,
             aes(x=YearMonthDec, y=ResultValue,
                 group=YearMonth, color=as.factor(Month))) +
geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
labs(subtitle="Scaled to 4x Standard Deviation",
     x="Year", y=paste0("Values (", unit, ")"), color="Month") +
ylim(min_RV, y_scale) +
scale_x_continuous(limits=c(year_lower - 1, year_upper + 1),
                   breaks=rev(seq(year_upper,
                                 year_lower, -x_scale))) +
plot_theme +
theme(legend.position="top", legend.box="horizontal") +
guides(color=guide_legend(nrow=1))
# Create plot object for y-axis scaled plot for past 10 years

```

```

p6 <- ggplot(data=plot_data[plot_data$Year >= year_upper - 10, ],
              aes(x=YearMonthDec, y=ResultValue,
                  group=YearMonth, color=as.factor(Month))) +
  geom_boxplot(fill="#cccccc", outlier.size=1.5, outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation, Last 10 Years",
       x="Year", y=paste0("Values (", unit, ")"), color="Month") +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits=c(year_upper - 10.5, year_upper + 1),
                     breaks=rev(seq(year_upper, year_upper - 10,-2))) +
  plot_theme +
  theme(legend.position="none")
# Create legend object
leg1 <- get_legend(p5)
# Arrange plots and legend
YMset <- ggarrange(leg1, p4, p5 + theme(legend.position="none"), p6,
                   ncol=1, heights=c(0.1, 1, 1, 1))
# Create plot title object
p00 <- ggplot() + labs(title=paste0(MA_Include[i]),
                        subtitle="By Year & Month") + plot_theme +
  theme(panel.border=element_blank(),
        panel.grid.major=element_blank(),
        panel.grid.minor=element_blank(), axis.line=element_blank())

## Month Plots
# Create plot object for auto-scaled y-axis plot
p7 <- ggplot(data=plot_data,
              aes(x=Month, y=ResultValue,
                  group=Month, fill=as.factor(Month))) +
  geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
               outlier.color="#333333", outlier.alpha=0.75) +
  labs(subtitle="Autoscale",
       x="Month", y=paste0("Values (", unit, ")"), fill="Month") +
  scale_x_continuous(limits=c(0, 13), breaks=seq(3, 12, 3)) +
  plot_theme +
  theme(legend.position="none")
# Create plot object for y-axis scaled plot
p8 <- ggplot(data=plot_data,
              aes(x=Month, y=ResultValue,
                  group=Month, fill=as.factor(Month))) +
  geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,
               outlier.color="#333333", outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation",
       x="Month", y=paste0("Values (", unit, ")"), fill="Month") +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits=c(0, 13), breaks=seq(3, 12, 3)) +
  plot_theme +
  theme(legend.position="top", legend.box="horizontal") +
  guides(fill=guide_legend(nrow=1))
# Create plot object for y-axis scaled plot for past 10 years
p9 <- ggplot(data=plot_data[plot_data$Year >= year_upper - 10, ],
              aes(x=Month, y=ResultValue,
                  group=Month, fill=as.factor(Month))) +
  geom_boxplot(color="#333333", outlier.shape=21, outlier.size=3,

```


```

        outlier.color="#333333", outlier.alpha=0.75) +
  labs(subtitle="Scaled to 4x Standard Deviation, Last 10 Years",
    x="Month", y=paste0("Values (", unit, ")"), fill="Month") +
  ylim(min_RV, y_scale) +
  scale_x_continuous(limits=c(0, 13), breaks=seq(3, 12, 3)) +
  plot_theme +
  theme(legend.position="none")
# Create legend object
leg2 <- get_legend(p8)
# Arrange plots and legend
Mset <- ggarrange(leg2, p7, p8 + theme(legend.position="none"), p9,
  ncol=1, heights=c(0.1, 1, 1, 1))
# Create title object
p000 <- ggplot() + labs(title=MA_Include[i]),
  subtitle="By Month") + plot_theme +
  theme(panel.border=element_blank(),
    panel.grid.major=element_blank(),
    panel.grid.minor=element_blank(), axis.line=element_blank())
# Arrange and display plots with titles for all combinations
print(ggarrange(p0, Yset, ncol=1, heights=c(0.07, 1)))
print(ggarrange(p00, YMset, ncol=1, heights=c(0.07, 1)))
print(ggarrange(p000, Mset, ncol=1, heights=c(0.07, 1, 0.7)))


rm(plot_data)
rm(p1, p2, p3, p4, p5, p6, p7, p8, p9, p0, p00, p000, leg1, leg2,
  Yset, YMset, Mset)
}
}

```


Alligator Harbor Aquatic Preserve
By Year




Alligator Harbor Aquatic Preserve
By Year & Month




Alligator Harbor Aquatic Preserve
By Month




Apalachicola Bay Aquatic Preserve
By Year




Apalachicola Bay Aquatic Preserve
By Year & Month




Apalachicola Bay Aquatic Preserve
By Month




Apalachicola National Estuarine Research Reserve
By Year




Apalachicola National Estuarine Research Reserve
By Year & Month




Apalachicola National Estuarine Research Reserve
By Month




Banana River Aquatic Preserve
By Year




Banana River Aquatic Preserve
By Year & Month




Banana River Aquatic Preserve
By Month




Big Bend Seagrasses Aquatic Preserve
By Year




Big Bend Seagrasses Aquatic Preserve
By Year & Month




Big Bend Seagrasses Aquatic Preserve
By Month




Biscayne Bay Aquatic Preserve
By Year




Biscayne Bay Aquatic Preserve
By Year & Month




Biscayne Bay Aquatic Preserve
By Month




Boca Ciega Bay Aquatic Preserve
By Year




Boca Ciega Bay Aquatic Preserve
By Year & Month




Boca Ciega Bay Aquatic Preserve
By Month




Cape Haze Aquatic Preserve
By Year




Cape Haze Aquatic Preserve
By Year & Month




Cape Haze Aquatic Preserve
By Month




Cape Romano-Ten Thousand Islands Aquatic Preserve
By Year




Cape Romano-Ten Thousand Islands Aquatic Preserve
By Year & Month




Cape Romano-Ten Thousand Islands Aquatic Preserve
By Month




Cockroach Bay Aquatic Preserve
By Year




Cockroach Bay Aquatic Preserve
By Year & Month




Cockroach Bay Aquatic Preserve
By Month




Coupon Bight Aquatic Preserve
By Year




Coupon Bight Aquatic Preserve
By Year & Month




Coupon Bight Aquatic Preserve
By Month




Estero Bay Aquatic Preserve
By Year




Estero Bay Aquatic Preserve
By Year & Month




Estero Bay Aquatic Preserve
By Month




Florida Keys National Marine Sanctuary
By Year




Florida Keys National Marine Sanctuary
By Year & Month




Florida Keys National Marine Sanctuary
By Month




Fort Clinch State Park Aquatic Preserve
By Year




Fort Clinch State Park Aquatic Preserve
By Year & Month




Fort Clinch State Park Aquatic Preserve
By Month




Fort Pickens State Park Aquatic Preserve
By Year




Fort Pickens State Park Aquatic Preserve
By Year & Month




Fort Pickens State Park Aquatic Preserve
By Month




Gasparilla Sound-Charlotte Harbor Aquatic Preserve
By Year




Gasparilla Sound-Charlotte Harbor Aquatic Preserve
By Year & Month




Gasparilla Sound-Charlotte Harbor Aquatic Preserve
By Month




Guana River Marsh Aquatic Preserve
By Year




Guana River Marsh Aquatic Preserve
By Year & Month




Guana River Marsh Aquatic Preserve
By Month




Guana Tolomato Matanzas National Estuarine Research Reserve
By Year




Guana Tolomato Matanzas National Estuarine Research Reserve
By Year & Month




Guana Tolomato Matanzas National Estuarine Research Reserve
By Month




Indian River-Malabar to Vero Beach Aquatic Preserve
By Year




Indian River-Malabar to Vero Beach Aquatic Preserve
By Year & Month




Indian River-Malabar to Vero Beach Aquatic Preserve
By Month




Indian River-Vero Beach to Ft. Pierce Aquatic Preserve
By Year




Indian River-Vero Beach to Ft. Pierce Aquatic Preserve
By Year & Month




Indian River-Vero Beach to Ft. Pierce Aquatic Preserve
By Month




Jensen Beach to Jupiter Inlet Aquatic Preserve
By Year




Jensen Beach to Jupiter Inlet Aquatic Preserve
By Year & Month




Jensen Beach to Jupiter Inlet Aquatic Preserve
By Month




Lemon Bay Aquatic Preserve
By Year




Lemon Bay Aquatic Preserve
By Year & Month




Lemon Bay Aquatic Preserve
By Month




Lignumvitae Key Aquatic Preserve
By Year




Lignumvitae Key Aquatic Preserve
By Year & Month




Lignumvitae Key Aquatic Preserve
By Month




Loxahatchee River-Lake Worth Creek Aquatic Preserve
By Year




Loxahatchee River-Lake Worth Creek Aquatic Preserve
By Year & Month




Loxahatchee River-Lake Worth Creek Aquatic Preserve
By Month




Matlacha Pass Aquatic Preserve
By Year




Matlacha Pass Aquatic Preserve
By Year & Month




Matlacha Pass Aquatic Preserve
By Month




Mosquito Lagoon Aquatic Preserve
By Year




Mosquito Lagoon Aquatic Preserve
By Year & Month




Mosquito Lagoon Aquatic Preserve
By Month




Nassau River-St. Johns River Marshes Aquatic Preserve
By Year




Nassau River-St. Johns River Marshes Aquatic Preserve
By Year & Month




Nassau River-St. Johns River Marshes Aquatic Preserve
By Month




Nature Coast Aquatic Preserve
By Year




Nature Coast Aquatic Preserve
By Year & Month




Nature Coast Aquatic Preserve
By Month




North Fork St. Lucie Aquatic Preserve
By Year




North Fork St. Lucie Aquatic Preserve
By Year & Month




North Fork St. Lucie Aquatic Preserve
By Month




Pellicer Creek Aquatic Preserve
By Year






Pellicer Creek Aquatic Preserve
By Year & Month




Pellicer Creek Aquatic Preserve
By Month




Pine Island Sound Aquatic Preserve
By Year




Pine Island Sound Aquatic Preserve
By Year & Month




Pine Island Sound Aquatic Preserve
By Month




Pinellas County Aquatic Preserve
By Year




Pinellas County Aquatic Preserve
By Year & Month




Pinellas County Aquatic Preserve
By Month




Rocky Bayou State Park Aquatic Preserve
By Year




Rocky Bayou State Park Aquatic Preserve
By Year & Month




Rocky Bayou State Park Aquatic Preserve
By Month




Rookery Bay Aquatic Preserve
By Year




Rookery Bay Aquatic Preserve
By Year & Month




Rookery Bay Aquatic Preserve
By Month




Rookery Bay National Estuarine Research Reserve
By Year




Rookery Bay National Estuarine Research Reserve
By Year & Month




Rookery Bay National Estuarine Research Reserve
By Month




Southeast Florida Coral Reef Ecosystem Conservation Area
By Year




Southeast Florida Coral Reef Ecosystem Conservation Area
By Year & Month




Southeast Florida Coral Reef Ecosystem Conservation Area
By Month




St. Andrews State Park Aquatic Preserve
By Year




St. Andrews State Park Aquatic Preserve
By Year & Month




St. Andrews State Park Aquatic Preserve
By Month




St. Joseph Bay Aquatic Preserve
By Year




St. Joseph Bay Aquatic Preserve
By Year & Month




St. Joseph Bay Aquatic Preserve
By Month




St. Martins Marsh Aquatic Preserve
By Year




St. Martins Marsh Aquatic Preserve
By Year & Month




St. Martins Marsh Aquatic Preserve
By Month




Terra Ceia Aquatic Preserve
By Year




Terra Ceia Aquatic Preserve
By Year & Month




Terra Ceia Aquatic Preserve
By Month




Tomoka Marsh Aquatic Preserve
By Year




Tomoka Marsh Aquatic Preserve
By Year & Month




Tomoka Marsh Aquatic Preserve
By Month




Yellow River Marsh Aquatic Preserve
By Year



Yellow River Marsh Aquatic Preserve
By Year & Month



Yellow River Marsh Aquatic Preserve
By Month



Appendix V: Excluded Managed Areas

Scatter plots of data values are created for managed areas that have fewer than 10 separate years of data entries. Data points are colored based on specific value qualifiers of interest.

```

# Determines whether excluded managed areas exist. If they do, begins
# looping through them
if(z==0){
  print("There are no managed areas that qualify.")
} else {
  for(i in 1:z){
    # Create scatter plot with data
    p1<-ggplot(data=data[data$ManagedAreaName==MA_Exclude$ManagedAreaName[i] &
      data$Include==TRUE, ],
      aes(x=SampleDate, y=ResultValue, fill=VQ_Plot)) +
      geom_point(shape=21, size=3, color="#333333", alpha=0.75) +
      labs(title=paste0(MA_Exclude$ManagedAreaName[i], " (",
        MA_Exclude$N_Years[i], " Unique Years"),
        subtitle="Autoscale", x="Year",
        y=paste0("Values (", unit, ")"), fill="Value Qualifier") +
      plot_theme +
      theme(legend.position="top", legend.box="horizontal",
        legend.justification="right") +
      scale_x_date(labels=date_format("%m-%Y")) +
      {if(inc_H==TRUE){
        scale_fill_manual(values=c("H"= "#F8766D", "U"= "#00BFC4",
          "HU"="#7CAE00"), na.value="#cccccc")
      } else if(param_name=="Secchi_Depth"){
        scale_fill_manual(values=c("S"= "#F8766D", "U"= "#00BFC4",
          "SU"="#7CAE00"), na.value="#cccccc")
      } else {
        scale_fill_manual(values=c("U"= "#00BFC4"), na.value="#cccccc")
      }
      print(p1)
    }
  }
}

```

