

PART SPECIFICATION SHEET

Part Number: PN-7356 — Sensor Housing

Spec Ref: SPS-APX-7356 Rev A

1. GENERAL

This specification defines requirements for the Sensor Housing (PN-7356) used in the Model 400 environmental sensor assembly. The housing provides a sealed enclosure for the sensor element and must withstand continuous exposure to marine environments.

2. MATERIAL

Material shall be **316 Stainless Steel** per AMS 5648 or ASTM A276. Material certifications with full chemical analysis and mechanical test results are required for each heat lot.

3. DIMENSIONAL REQUIREMENTS

Feature	Nominal	Tolerance
Overall Length	4.000	±0.010mm
Overall Width	2.500	±0.010mm
Bore Diameter	1.0000	±0.001mm
Mounting Hole Dia (4x)	0.190	±0.005mm
Wall Thickness (min)	0.250	—

4. SURFACE TREATMENT

Passivate per ASTM A967 using citric acid method. Bore surface finish shall be 32 Ra maximum. All other surfaces 125 Ra maximum.

5. TESTING

Each housing shall be pressure tested to 300 PSI with dry nitrogen. Hold for 5 minutes. No leakage permitted. Test results shall be recorded and included in the quality data package.

Prepared by: A. Petrov, Design Engineering | Date: Feb 20, 2025