Linting

Migrating to v1.0 (ESLint 9)

Migrate an existing ESLint configuration to ESLint 9.

Version 1.0 is a major update that moves to ESLint 9's **flat config format** and unbundles third-party rules to give you more control over your linting setup. The flat config files don't allow nesting configuration files in subdirectories — instead, all nesting must be in one configuration file.

If you already have an ESLint configuration in your project, review the table below to see what's changed:

Before (v0.x)	After (v1.0)
ESLint 8	ESLint 9+ required
Legacy config (`.eslintrc.*`)	Flat config (`eslint.config.js`)
Bundled `eslint:recommended`	Install separately via `@eslint/js`
Bundled `eslint-plugin-react` recommended rules	Install and configure separately
Bundled `eslint-plugin-react-hooks`	Install and configure separately
Bundled `eslint-config-prettier`	Install and configure separately
CommonJS (`require()`)	ESM (`import`)

After reviewing the above changes, proceed with the steps below to migrate to the latest version.

Migrate your ESLint config

1. Review your current config

Before migrating, open your existing `.eslintrc.*` file and note:

HubSpot Developers

›

Any `env` or `globals` settings

You'll need to translate these to flat config format. Keep your old config file for reference until migration is complete.

2. Update dependencies

Upgrade to ESLint 9 and the new package version by running the following command:

```
npm i --save-dev eslint@^9 @hubspot/eslint-config-ui-extens
```

3. Set up ESM

ES modules is required for a flat configuration, so you'll need to ensure your `package.json` includes `"type": "module"` :

```
{
  "type": "module"
}
```

4. Create a new ESLint config file

Create an `eslint.config.js` file in your project root. Start with either the minimal or recommended setup below, then add your custom rules. Read more about each addition in the .

Minimal setup (HubSpot UI extensions rules only):

```
import { config } from '@hubspot/eslint-config-ui-extension

export default [
  ...config,
  // Add your custom rules here (see Step 5)
];
```

HubSpot Developers

HubSpot Developers

```
import reactHooks from 'eslint-plugin-react-hooks';
import unusedImports from 'eslint-plugin-unused-imports';
import prettier from 'eslint-config-prettier';
import { config as uiExtensionsConfig } from '@hubspot/eslint-config-ui-extensi

export default defineConfig([
  js.configs.recommended,
  tseslint.configs.recommended,
  tseslint.configs.stylistic,
  react.configs.flat.recommended,
  react.configs.flat['jsx-runtime'],
  {
    settings: {
      react: { version: 'detect' },
    },
  },
  ...uiExtensionsConfig,
  reactHooks.configs.flat['recommended-latest'],
  {
    plugins: {
      'unused-imports': unusedImports,
    },
    rules: {
      'no-unused-vars': 'off',
      '@typescript-eslint/no-unused-vars': 'off',
      'unused-imports/no-unused-imports': 'error',
      'unused-imports/no-unused-vars': [
        'warn',
        {
          vars: 'all',
          varsIgnorePattern: '^_',
          args: 'after-used',
          argsIgnorePattern: '^_',
        },
      ],
      'react/prop-types': 'off',
    },
  },
  prettier,
```

HubSpot Developers

›

3. Migrate your custom configuration

Refer to your old config file and translate your customizations to flat config format.

Custom rules:

```
// Before (.eslintrc.js)
module.exports = {
  rules: {
    'no-console': 'warn',
    'prefer-const': 'error',
  },
};

// After (eslint.config.js) - add to your config array
{
  rules: {
    'no-console': 'warn',
    'prefer-const': 'error',
  },
}
```

Overrides (file-specific rules):

HubSpot Developers

```
      files: ['*.test.js'],
      rules: {
        'no-console': 'off',
      },
    },
  ],
};

// After (eslint.config.js) - add to your config array
{
  files: ['**/*.test.js'],
  rules: {
    'no-console': 'off',
  },
}
```

Globals:

```
// Before (.eslintrc.js)
module.exports = {
  globals: {
    myGlobal: 'readonly',
  },
};

// After (eslint.config.js) - add to your config array
{
  languageOptions: {
    globals: {
      myGlobal: 'readonly',
    },
  },
}
```

Environments:

HubSpot Developers

```
  env: {
    browser: true,
    node: true,
  },
};

// After (eslint.config.js)
import globals from 'globals';

export default [
  {
    languageOptions: {
      globals: {
        ...globals.browser,
        ...globals.node,
      },
    },
  },
  // ... rest of config
];
```

For more details, see the .

6. Testing and cleanup

Run ESLint to verify your migration:

```
npm run lint
```

Once you've verified that everything works, you can delete your old `.eslintrc.*` file.

Troubleshooting

ESLint seems to ignore your new config

2. The file is correctly exporting an array (check for syntax errors).

Error: Cannot use require() to import an ES module

Your config file is being loaded as CommonJS. Make sure:

1. Your `package.json` has `"type": "module"` .
2. Your config file is named `eslint.config.js` (not `.cjs`).

Errors about missing plugins or rules

If you see errors like `Definition for rule 'react/prop-types' was not found` , you're using a rule from a plugin that was previously bundled but is now opt-in. Either:

1. Install the plugin and add it to your config (see **recommended setup**).
2. Remove the rule if you no longer need it.

Error: Invalid option 'extends'

Flat config uses a different structure than legacy config. You can't use `extends` , `env` , `plugins` (as an array), or `overrides` the same way. See **Step 5 above** for translation examples.

Last modified on February 27, 2026

Was this page helpful? Yes No

Linting for UI extensions
‹ Previous

HubSpot Developers

HubSpot Developers

Copyright © 2026 HubSpot, Inc

Privacy Policy

Security

Website Accessibility

Manage Cookies