Standard components

SearchInput | UI components

Learn about the SearchInput component for enabling search in UI extensions.

The `SearchInput` component renders an input field that enables users to search. The component doesn't provide search functionality out of the box, but includes props for managing input state and validation.



HubSpot Developers

```
const Extension = ({ sendAlert }) => {
  const [searchValue, setSearchValue] = useState("");

  const handleSubmit = formData => {
    const searchTerm = formData.targetValue.search;
    sendAlert({
      message: `You searched for: "${searchTerm}"`,
      type: "success",
    });
  };

  return (
    <Form onSubmit={handleSubmit}>
      <Flex direction="column" gap="md">
        <SearchInput
          name="search"
          label="Search"
          placeholder="Enter your search term"
          value={searchValue}
          onChange={value => setSearchValue(value)}
        />
        <Button type="submit">Search</Button>
        {searchValue && <Text>Current search: {searchValue}</Text>}
      </Flex>
    </Form>
  );
};
```

Props

Prop	Type	Description
`clearable`	Boolean	When set to `true`, shows a clear button to clear the input. Default is `true`.
`description`	String	Instructional message to help understand the purpose of the input.

e	`string | null`	validation message. Depending on the width and length of message, the message display may appear above or inline with the input.
`label`	String	The label text to display for the input.
`name`	String	The unique identifier for the input.
`onBlur`	`(value: string) => void`	A function that is called when the field loses focus.
`onChange`	`(value: string) => void`	A callback function that is invoked when the input value changes.
`onFocus`	`(value: string) => void`	A function that is called when the field gets focused.
`onInput`	`(value: string) => void`	A callback function that is invoked every time the field is edited by the user.
`placeholder`	String	Text that appears in the input when it has no value set.
`readOnly`	Boolean	When set to `true`, the field is not editable.
`required`	Boolean	When set to `true`, displays a required field indicator.
`tooltip`	String	Text that will appear in a tooltip on hover next to the input label.
`validationMessage`	String	The text to show under the input for error or success validations. Will appear below the input. Learn more about **validation messages**.
`value`	String	The value of the input.

Validation messages

Using the `validationMessage` and `getValidationMessage` props, you can implement validation into the search input. By default, `validationMessage` will render as a green success message. When the `error` prop is `true`, the message will render as red and the search input will include a red border.

HubSpot Developers

```
<>
  <SearchInput
    name="validation-message"
    placeholder="Validation message"
    validationMessage="This is a validation message"
  />
  <SearchInput
    name="validation-error"
    placeholder="Validation error"
    validationMessage="This is a validation error message"
    error
  />
</>;
```

Table search example

The example below creates a searchable table.

HubSpot Developers



HubSpot Developers

```
  Form,
  Heading,
  Table,
  TableHead,
  TableHeader,
  TableRow,
  TableBody,
  TableCell,
  Flex,
  SearchInput,
  hubspot,
} from "@hubspot/ui-extensions";

hubspot.extend(({ actions }) => <Extension sendAlert={actions.addAlert} />);

const Extension = ({ sendAlert }) => {
  const tableData = [
    { name: "Mark Scout", role: "Team Lead (MDR)" },
    { name: "Dylan George", role: "Macrodata Refiner" },
    { name: "Irving Bailiff", role: "Senior Refiner" },
    { name: "Helly Riggs", role: "New Hire" },
    { name: "Burt Goodman", role: "Department Head (O&D)" },
  ];

  const [filteredData, setFilteredData] = useState(tableData);

  const handleSubmit = e => {
    const searchTerm = e.targetValue.searchInput;
    sendAlert({ message: `You've searched for: ${searchTerm}` });
  };

  const searchTable = e => {
    const searchTerm = e.targetValue.searchInput;
    // Filter the table data based on search term
    const filtered = tableData.filter(
      item =>
        item.name.toLowerCase().includes(searchTerm.toLowerCase()) ||
        item.role.toLowerCase().includes(searchTerm.toLowerCase())
    );
```

HubSpot Developers

```
  };

  return (
    <>
      <Form onSubmit={searchTable}>
        <Flex direction="column" gap="sm">
          <Heading>Searchable table</Heading>
          <Flex direction="row" gap="sm" alignSelf="end" align="end" justify="e
            <SearchInput name="searchInput" placeholder="Search Table" />
            <Button type="submit">Search</Button>
          </Flex>
          <Table bordered={true} paginated={true} pageCount="5" limit={10}>
            <TableHead>
              <TableRow>
                <TableHeader width="min">Name</TableHeader>
                <TableHeader width="min">Role</TableHeader>
              </TableRow>
            </TableHead>
            <TableBody>
              {filteredData.map((item, index) => (
                <TableRow key={index}>
                  <TableCell width="min">{item.name}</TableCell>
                  <TableCell width="min">{item.role}</TableCell>
                </TableRow>
              ))}
            </TableBody>
          </Table>
        </Flex>
      </Form>
    </>
  );
};
```

Related components

Form

HubSpot Developers

Last modified on January 28, 2026

Was this page helpful? Yes No

ScoreCircle
Previous

Select
Next

HubSpot Developers
Copyright © 2026 HubSpot, Inc
Privacy Policy
Security
Website Accessibility
Manage Cookies