Standard components

Error state | UI components

Learn about the ErrorState component for use in UI extensions.

The `ErrorState` component sets the content of an erroring extension. Use this component to guide users through resolving errors that your extension might encounter.

1. **Illustration:** one of three error-themed illustrations.
2. **Title:** the main error message to explain the root cause if known.
3. **Additional text:** an additional `Text` **component** to provide further guidance. This does not come with the component by default. Error text should use the following formats:

   Known cause: [what failed] + [why it failed] + [next steps]. For example, *Failed to load extension due to outage, please wait a few minutes and try again.*

   Unknown cause: [what failed] + [next steps]. For example, *Couldn't load data, try refreshing the page or contacting IT.*
4. **Additional button:** an additional `Button` **component** to can help users take action. This does not come with the component by default.

```
    return (
     <ErrorState title="Trouble fetching properties.">
      <Text>
       Please try again in a few moments.
      </Text>
      <Button onClick={fetchData}>
       Try again
      </Button>
    </ErrorState>
    )
  }
   return (
    {data.map(...)}
   );
 }
```

Props

Prop	Type	Description
`title`	String	The text of the component header.
`type`	`'support'` | `'lock'` | `'error'` (default)	The type of image that will be displayed.

Variants

Using the `type` prop, you can set one of three illustrations.

HubSpot Developers

Trouble fetching properties.

```
const Extension = ({ data, error, fetchData }) => {
  if (error) {
   return (
    <ErrorState
     title="Trouble fetching properties."
     type="error"
    >
   </ErrorState>
   )
 }
  return (
   {data.map(...)}
  );
}
```

Something went wrong.

HubSpot Developers

```
      title="Something went wrong."
      type="support"
     >
    </ErrorState>
    )
  }
  return (
    {data.map(...)}
  );
}
```

You must log in to view this data.

HubSpot Developers

```
      title="You must log in to view this data."
      type="lock"
     >
    </ErrorState>
    )
  }
  return (
   {data.map(...)}
  );
}
```

Usage examples

Use the `default` error type when a card encounters an error when fetching data.

Use the `support` error type when the user should contact internal or external support to resolve an error.

Use the `lock` error type when the user needs to log in or doesn't have permission to access the card's data.

Guidelines

DO: use text that's clear, direct, brief, and helpful.

DON'T: use technical jargon.

DON'T: say "sorry" or use frivolous language such as "oops," "uh-oh," and "it's us, not you."

DON'T: use exclamation points.

Related components

HubSpot Developers

EmptyState | UI components
Previous

Flex
Next

HubSpot Developers
Copyright © 2026 HubSpot, Inc
Privacy Policy
Security
Website Accessibility
Manage Cookies