tylerwnevin / Project-PRG2782

Code Issues Pull requests Agents Actions Projects

Commit a348724

tylerwnevin authored last week Verified

Add files via upload

feature/add-animal

1 parent 15f8687 commit a348724

13 files changed +232

Top

Filter files...

- BaobabRidgeWildlifeRecords
  - BaobabRidgeWildlifeRecords.sln
  - BaobabRidgeWildlifeRecords
    - BaobabRidgeWildlifeRecords.csproj
    - Form1.cs
    - Program.cs
    - obj
      - Debug/net8.0-windows
        - BaobabRidgeWildlifeRecords.AssemblyInfo.cs
        - BaobabRidgeWildlifeRecords.AssemblyInfoInputs.cache
        - BaobabRidgeWildlifeRecords.GeneratedMSBuildEditorConfig.editorconfig
        - BaobabRidgeWildlifeRecords.GlobalUsings.g.cs
      - Release/net8.0-windows
        - BaobabRidgeWildlifeRecords.AssemblyInfo.cs

BaobabRidgeWildlifeRecords.AssemblyInfoInputs.cache

BaobabRidgeWildlifeRecords.GeneratedMSBuildEditorConfig.editorconfig

BaobabRidgeWildlifeRecords.GlobalUsings.g.cs

README.md

Search within code

...WildlifeRecords/BaobabRidgeWildlifeRecords.sln

```
@@ -0,0 +1,18 @@
+ Microsoft Visual Studio Solution File, Format Version 12.00
+ # Visual Studio Version 17
+ VisualStudioVersion = 17.0.31903.59
+ MinimumVisualStudioVersion = 10.0.40219.1
+ Project("{FAE04EC0-301F-11D3-BF4B-00C04F79EFBC}") = "BaobabRidgeWildlifeRecords", "BaobabRidgeWildlifeRecords\BaobabRidgeWildlifeRecords.csproj", "{A9B7C6D5-E4F3-4210-9876-123456789ABC}"
+ EndProject
+ Global
+     GlobalSection(SolutionConfigurationPlatforms) = preSolution
+         Debug|Any CPU = Debug|Any CPU
+         Release|Any CPU = Release|Any CPU
+     EndGlobalSection
+     GlobalSection(ProjectConfigurationPlatforms) = postSolution
+         {A9B7C6D5-E4F3-4210-9876-123456789ABC}.Debug|Any CPU.ActiveCfg = Debug|Any CPU
+         {A9B7C6D5-E4F3-4210-9876-123456789ABC}.Debug|Any CPU.Build.0 = Debug|Any CPU
+         {A9B7C6D5-E4F3-4210-9876-123456789ABC}.Release|Any CPU.ActiveCfg = Release|Any CPU
+         {A9B7C6D5-E4F3-4210-9876-123456789ABC}.Release|Any CPU.Build.0 = Release|Any CPU
+     EndGlobalSection
+ EndGlobal
```

...dlifeRecords/BaobabRidgeWildlifeRecords.csproj

```
@@ -0,0 +1,9 @@
+ <Project Sdk="Microsoft.NET.Sdk">
+   <PropertyGroup>
+     <OutputType>WinExe</OutputType>
```

```
4  +     <TargetFramework>net8.0-windows</TargetFramework>
5  +     <UseWindowsForms>true</UseWindowsForms>
6  +     <Nullable>enable</Nullable>
7  +     <ImplicitUsings>enable</ImplicitUsings>
8  +   </PropertyGroup>
9  + </Project>
```

…ifeRecords/BaobabRidgeWildlifeRecords/Form1.cs

```
@@ -0,0 +1,30 @@
1  + namespace BaobabRidgeWildlifeRecords;
2  +
3  + /// <summary>
4  + /// The initial blank main form for the wildlife records application.
5  + /// </summary>
6  + public partial class Form1 : Form
7  + {
8  +     /// <summary>
9  +     /// Creates the main form.
10 +     /// </summary>
11 +     public Form1()
12 +     {
13 +         InitializeComponent();
14 +     }
15 +
16 +     /// <summary>
17 +     /// Initializes the blank form's basic properties.
18 +     /// </summary>
19 +     private void InitializeComponent()
20 +     {
21 +         SuspendLayout();
22 +         AutoScaleDimensions = new SizeF(7F, 15F);
23 +         AutoScaleMode = AutoScaleMode.Font;
24 +         ClientSize = new Size(1000, 600);
25 +         Name = "Form1";
26 +         StartPosition = FormStartPosition.CenterScreen;
27 +         Text = "Baobab Ridge Wildlife Rehabilitation Records System";
28 +         ResumeLayout(false);
29 +     }
30 + }
```

...eRecords/BaobabRidgeWildlifeRecords/Program.cs

```
@@ -0,0 +1,17 @@
+ namespace BaobabRidgeWildlifeRecords;
+
+ /// <summary>
+ /// Starts the Windows Forms application.
+ /// </summary>
+ internal static class Program
+ {
+     /// <summary>
+     /// Configures Windows Forms and opens the main form.
+     /// </summary>
+     [STAThread]
+     static void Main()
+     {
+         ApplicationConfiguration.Initialize();
+         Application.Run(new Form1());
+     }
+ }
```

...ows/BaobabRidgeWildlifeRecords.AssemblyInfo.cs

```
@@ -0,0 +1,25 @@
+ //------------------------------------------------------------------------------
+ // <auto-generated>
+ //     This code was generated by a tool.
+ //     Runtime Version:4.0.30319.42000
+ //
+ //     Changes to this file may cause incorrect behavior and will be lost if
+ //     the code is regenerated.
+ // </auto-generated>
+ //------------------------------------------------------------------------------
+
+ using System;
+ using System.Reflection;
+
+ [assembly: System.Reflection.AssemblyCompanyAttribute("BaobabRidgeWildlifeRecords")]
+ [assembly: System.Reflection.AssemblyConfigurationAttribute("Debug")]
```

```
16  + [assembly: System.Reflection.AssemblyFileVersionAttribute("1.0.0.0")]
17  + [assembly: System.Reflection.AssemblyInformationalVersionAttribute("1.0.0")]
18  + [assembly: System.Reflection.AssemblyProductAttribute("BaobabRidgeWildlifeRecords")]
19  + [assembly: System.Reflection.AssemblyTitleAttribute("BaobabRidgeWildlifeRecords")]
20  + [assembly: System.Reflection.AssemblyVersionAttribute("1.0.0.0")]
21  + [assembly: System.Runtime.Versioning.TargetPlatformAttribute("Windows7.0")]
22  + [assembly: System.Runtime.Versioning.SupportedOSPlatformAttribute("Windows7.0")]
23  +
24  + // Generated by the MSBuild WriteCodeFragment class.
25  +
```

…bRidgeWildlifeRecords.AssemblyInfoInputs.cache

```
@@ -0,0 +1 @@
1  + a4d467e47bff21456093153506666e115cb65faa73b2921f53af21ed50356305
```

…ords.GeneratedMSBuildEditorConfig.editorconfig

```
@@ -0,0 +1,25 @@
1  + is_global = true
2  + build_property.ApplicationManifest =
3  + build_property.StartupObject =
4  + build_property.ApplicationDefaultFont =
5  + build_property.ApplicationHighDpiMode =
6  + build_property.ApplicationUseCompatibleTextRendering =
7  + build_property.ApplicationVisualStyles =
8  + build_property.TargetFramework = net8.0-windows
9  + build_property.TargetFrameworkIdentifier = .NETCoreApp
10 + build_property.TargetFrameworkVersion = v8.0
11 + build_property.TargetPlatformMinVersion = 7.0
12 + build_property.UsingMicrosoftNETSdkWeb =
13 + build_property.ProjectTypeGuids =
14 + build_property.InvariantGlobalization =
15 + build_property.PlatformNeutralAssembly =
16 + build_property.EnforceExtendedAnalyzerRules =
17 + build_property.EntryPointFilePath =
18 + build_property._SupportedPlatformList = Linux,macOS,Windows
19 + build_property.RootNamespace = BaobabRidgeWildlifeRecords
20 + build_property.ProjectDir = C:
   \Users\user\Desktop\BaobabRidgeWildlifeRecords\BaobabRidgeWildlifeRecords\
```

```
21  + build_property.EnableComHosting =
22  + build_property.EnableGeneratedComInterfaceComImportInterop =
23  + build_property.CsWinRTUseWindowsUIXamlProjections = false
24  + build_property.EffectiveAnalysisLevelStyle = 8.0
25  + build_property.EnableCodeStyleSeverity =
```

...s/BaobabRidgeWildlifeRecords.GlobalUsings.g.cs

```
    @@ -0,0 +1,10 @@
1   + // <auto-generated/>
2   + global using System;
3   + global using System.Collections.Generic;
4   + global using System.Drawing;
5   + global using System.IO;
6   + global using System.Linq;
7   + global using System.Net.Http;
8   + global using System.Threading;
9   + global using System.Threading.Tasks;
10  + global using System.Windows.Forms;
```

...ows/BaobabRidgeWildlifeRecords.AssemblyInfo.cs

```
    @@ -0,0 +1,25 @@
1   + //------------------------------------------------------------------------------
2   + // <auto-generated>
3   + //     This code was generated by a tool.
4   + //     Runtime Version:4.0.30319.42000
5   + //
6   + //     Changes to this file may cause incorrect behavior and will be lost if
7   + //     the code is regenerated.
8   + // </auto-generated>
9   + //------------------------------------------------------------------------------
10  +
11  + using System;
12  + using System.Reflection;
13  +
14  + [assembly: System.Reflection.AssemblyCompanyAttribute("BaobabRidgeWildlifeRecords")]
15  + [assembly: System.Reflection.AssemblyConfigurationAttribute("Release")]
16  + [assembly: System.Reflection.AssemblyFileVersionAttribute("1.0.0.0")]
17  + [assembly: System.Reflection.AssemblyInformationalVersionAttribute("1.0.0")]
```

```
18  + [assembly: System.Reflection.AssemblyProductAttribute("BaobabRidgeWildlifeRecords")]
19  + [assembly: System.Reflection.AssemblyTitleAttribute("BaobabRidgeWildlifeRecords")]
20  + [assembly: System.Reflection.AssemblyVersionAttribute("1.0.0.0")]
21  + [assembly: System.Runtime.Versioning.TargetPlatformAttribute("Windows7.0")]
22  + [assembly: System.Runtime.Versioning.SupportedOSPlatformAttribute("Windows7.0")]
23  +
24  + // Generated by the MSBuild WriteCodeFragment class.
25  +
```

…bRidgeWildlifeRecords.AssemblyInfoInputs.cache

```
••• @@ -0,0 +1 @@
1   + f25e8101bdadc9f2d31a36d89f86a3a2945019c4f40aa796c149281ab3355102
```

…ords.GeneratedMSBuildEditorConfig.editorconfig

```
••• @@ -0,0 +1,25 @@
1   + is_global = true
2   + build_property.ApplicationManifest =
3   + build_property.StartupObject =
4   + build_property.ApplicationDefaultFont =
5   + build_property.ApplicationHighDpiMode =
6   + build_property.ApplicationUseCompatibleTextRendering =
7   + build_property.ApplicationVisualStyles =
8   + build_property.TargetFramework = net8.0-windows
9   + build_property.TargetFrameworkIdentifier = .NETCoreApp
10  + build_property.TargetFrameworkVersion = v8.0
11  + build_property.TargetPlatformMinVersion = 7.0
12  + build_property.UsingMicrosoftNETSdkWeb =
13  + build_property.ProjectTypeGuids =
14  + build_property.InvariantGlobalization =
15  + build_property.PlatformNeutralAssembly =
16  + build_property.EnforceExtendedAnalyzerRules =
17  + build_property.EntryPointFilePath =
18  + build_property._SupportedPlatformList = Linux,macOS,Windows
19  + build_property.RootNamespace = BaobabRidgeWildlifeRecords
20  + build_property.ProjectDir = C:
      \Users\user\Desktop\BaobabRidgeWildlifeRecords\BaobabRidgeWildlifeRecords\
21  + build_property.EnableComHosting =
22  + build_property.EnableGeneratedComInterfaceComImportInterop =
```

```
23  + build_property.CsWinRTUseWindowsUIXamlProjections = false
24  + build_property.EffectiveAnalysisLevelStyle = 8.0
25  + build_property.EnableCodeStyleSeverity =
```

...s/BaobabRidgeWildlifeRecords.GlobalUsings.g.cs

```
@@ -0,0 +1,10 @@
1   + // <auto-generated/>
2   + global using System;
3   + global using System.Collections.Generic;
4   + global using System.Drawing;
5   + global using System.IO;
6   + global using System.Linq;
7   + global using System.Net.Http;
8   + global using System.Threading;
9   + global using System.Threading.Tasks;
10  + global using System.Windows.Forms;
```

BaobabRidgeWildlifeRecords/README.md

```
@@ -0,0 +1,36 @@
1   + # Baobab Ridge Wildlife Rehabilitation Records System
2   +
3   + ## Project overview
4   + A C# Windows Forms application for managing animal rehabilitation records at the
      fictional Baobab Ridge Wildlife Rehabilitation Centre.
5   +
6   + ## Team members
7   + - Person A: [Name] — [Student number]
8   + - Person B: [Name] — [Student number]
9   + - Person C: [Name] — [Student number]
10  + - Person D: [Name] — [Student number]
11  +
12  + ## Technologies
13  + - C#
14  + - Windows Forms
15  + - .NET 8.0 or newer
16  + - Git and GitHub
17  + - Plain text file storage
18  +
```

```
19  + ## Features
20  + - Add animal records
21  + - View all animal records
22  + - Update animal records
23  + - Delete animal records
24  + - Generate a summary report
25  +
26  + ## File formats
27  + - `animals.txt`: Animal records stored as pipe-separated fields.
28  + - `summary.txt`: Generated summary report.
29  +
30  + ## How to build and run
31  + 1. Open `BaobabRidgeWildlifeRecords.sln` in Visual Studio.
32  + 2. Build the solution.
33  + 3. Run the application.
34  +
35  + ## Known limitations
36  + This is the initial blank project scaffold. Application features have not yet been
      implemented.
```

Comments 0

Lock conversation

Comment

Subscribe You're not receiving notifications from this thread.