

Core Data

Jump to a Section

[What is Core Data?](#)

[Review of Relational Databases](#)

[Example - Employee Table](#)

[Implementing the database and tables in SQL:](#)

[Implementing the database and tables in Core Data](#)

[How does CoreData work?](#)

[Coding with Core Data](#)

[Add Core Data to the Project](#)

[Locating the CoreData SQLite file](#)

[Use the CoreData GUI to create an entity](#)

[Adding Attributes to your Employee Entity](#)

[Generating a Model Class for The Entity](#)

[Accessing the context variables](#)

[Insert data:](#)

[Searching fo Data Fetch data](#)

[Filtering the Search Results](#)

[Update Data](#)


[Delete data](#)

What is Core Data?

- There are situations when you may want to persist data to local device storage
- Local data persistence is provided by the **CoreData framework**
- The CoreData Framework persists data as an SQLite relational database
- The CoreData framework provides a library of functions to work with an SQLite database.


Review of Relational Databases

Databases can be modelled as a set of related entities:



Source: <https://www.guru99.com/er-diagram-tutorial-dbms.html>

Each entity contains attributes that describe the object's properties:



In a relational database:

- The entity represents your table
- The attributes represent the table columns
- An attribute marked with a * indicates the primary key column

An **instance of an entity** is a single occurrence of the entity:

Entity


IdNum	LName	FName	JobCode	Salary	Phone
1075	CHIN	JACK	IT1	42400	212/588-3034
1114	GREENWALD	JANICE	ME3	38000	212/588-1092
1556	PENNINGTON	MICHAEL	ME1	29860	718/383-5681
1354	PARKER	MARY	FA3	65800	914/455-2337
1130	WOOD	DEBORAH	PT2	36514	212/587-0011

Attributes

Instance of an Entity

Entities can have relationships with each other.

- These relationships are often modelled with an ER diagram



In IOS, you must use the Core Data framework to:

- Define your entities
- Specify the attributes of the entities
- Describe relationships between the entities
- Create occurrences of the entity (insert data)

Example - Employee Table

COMPANY DATABASE

EMPLOYEE

* id
name
date_hired

Implementing the database and tables in SQL:

```
CREATE DATABASE company_db;
```

```
-- Create the table
```

```
CREATE TABLE Employees (  
    id int NOT NULL PRIMARY KEY,  
    name varchar(255) NOT NULL,  
    date_hired varchar(255),  
);
```

```
-- Insert values into the table
```

```
INSERT INTO Employees (id, name, date_hired)  
VALUES (1, 'Peter', '2003-05-01');  
INSERT INTO Employees (id, name, date_hired)  
VALUES (2, 'Abigail', '2007-11-23');
```

Implementing the database and tables in Core Data

1. Define entities and their attributes

Generate the classes for each entity (model classes)

Obtain a reference to the **persistent container**


Obtain a reference to the **managed context**

Use the managed context to interact with your entities

How does CoreData work?

Every app has access to a SQLite database.

Core Data acts as an interface between your app and the SQLite database.



Source: Apple Developers

CoreData consists of two parts:

- The persistent container - directly interfaces with the database tables
- The managed object context - the interface your app interacts with




Diagram from Code with Chris

Coding with Core Data

In this example, we will create an Employee table and perform CRUD operations on it.

COMPANY DATABASE




Learning Objectives:

1. Modelling an entity and attributes
2. Inserting data
3. Updating data
4. Deleting data
5. Searching for data

Add Core Data to the Project

- When creating the project, ensure you check “Use Core Data”




The screenshot shows the Xcode project creation interface. The fields are filled as follows:

- Product Name: CoreDataExample
- Team: Add account...
- Organization Name: zebra
- Organization Identifier: com.test
- Bundle Identifier: com.test.CoreDataExample
- Language: Swift
- User Interface: Storyboard

At the bottom, the following checkboxes are visible:


- ☒ Use Core Data
- ☐ Use CloudKit
- ☐ Include Unit Tests
- ☐ Include UI Tests

Expected Result




Locating the CoreData SQLite file

Software: <https://sqlitebrowser.org/>



1. In your app's AppDelegate.swift file, look for this function:

- Add the code in yellow to the function



```
func application(_ application: UIApplication, didFinishLaunchingWithOptions
launchOptions: [UIApplication.LaunchOptionsKey: Any]?) -> Bool {
    // Override point for customization after application launch.
    let path = FileManager
        .default
        .urls(for: .applicationSupportDirectory, in: .userDomainMask)
        .last?
        .absoluteString
        .replacingOccurrences(of: "file://", with: "")
        .removingPercentEncoding

    print("Core Data DB Path :: \(path ?? "Not found")")
    return true
}
```

2. Run the app, look at terminal

The code from step 1 will cause your app to output the location of your app's writable document directory.


At the top of your terminal, you should see something like this:

```
Core Data DB Path ::  
/Users/zebra/Library/Developer/CoreSimulator/Devices/E39E77E9-3964-4C57-8EF1  
-5A374D5145BA/data/Containers/Data/Application/865CC101-055F-4CE9-B794-D2FB2  
A55E996/Library/Application Support/
```


Make a note of the path highlighted in yellow above.

You will need to open this directory on your computer.

3. Open Finder >Go > Go to Folder



3. Copy and paste the file path into the folder window:






4. Open the *Library > Application Support* folder.

Inside the folder, you will find an .sqlite file.

5. Open the SQLite file using the DBBrowser:

- Right click on .sqlite file
- Choose Open With > Other
- Choose DB Browser for SQLite





Use the CoreData GUI to create an entity


To create an entity and attributes, we use the CoreData modelling tool.

Suppose we want to create an Employee entity.


COMPANY DATABASE




1/ Click on the *.xcdatamodeld file




2/ In the interface, tap the +ADD ENTITY button






Expected result




3/ Rename your Entity to “Employee”



Adding Attributes to your Employee Entity

Tap the + button to add a new attribute




Generating a Model Class for The Entity

- To work with your entity in code, we need to represent the entity as a *class*.
- XCode can automatically generate the class definition for your entity.


1/ Select the Entity. In the Inspector, go to Class > Code Gen

- Select Manual/None




2/ Select Editor > Create NSManagedObject Subclass

- This will generate a Swift class that represents your Entity



After completing the wizard, you should get two new files:



Accessing the context variables

To perform CRUD operations, we need a reference to Core Data's managed context variable.

On the screens that need to access CoreData, add a context variable, as follows:

ViewController.swift

```
class ViewController: UIViewController {  
  
    // context variable  
    let context = (UIApplication.shared.delegate as!  
AppDelegate).persistentContainer.viewContext  
  
    // MARK: Outlets  
    override func viewDidLoad() {  
        super.viewDidLoad()  
        // Do any additional setup after loading the view.  
    }  
}
```

CRUD operations are performed through CoreData's managed context object.

Insert data:

1/ Using Swift, create an **instance** of the data you want to insert

2/ Set the data's properties to se

2/ Call save() on the context variable

- Saves can fail - so this function call must be marked with try wrapped in a do-catch

```
func addEmployee(name:String, dateHired:String) {
    // 1. Create an employee object
    let e1 = Employee(context: self.context)

    // 2. Set the properties of that object
    e1.date_hired = dateHired
    e1.name = name

    // 3. Use the context variable to save the Employee to the database table
    do {
        try self.context.save()
        print("Employee saved!")
    } catch {
        print("Saved failed.")
    }
}
```

Searching fo Data Fetch data

1/ Create a fetch request object using the entity's autogenerated fetchRequest() function

2/ Call the content variable's fetch() function:

- The fetch() function is the equivalent of running a SELECT * FROM EMPLOYEE
- The fetch() function returns an *array* of Employee objects
- The fetch() can fail, so the call must be wrapped in a do-catch

```
@IBAction func fetchAll(_ sender: Any) {
```

```
    // 1. Create a fetch request object using Employee's fetchRequest() function
```

```
    let request:NSFetchRequest<Employee> = Employee.fetchRequest()
```

```
    // 2. Initiate the fetch request
```

```
    do {
```

```
        let results:[Employee] = try self.context.fetch(request)
```

```
        print("Fetch succeeded")
```

```
        print("Number of results: \(results.count)")
```

```
        for employee in results {
```

```
            print("Name: \(employee.name ?? "N/A")")
```

```
            print("Date Hired: \(employee.date_hired ?? "N/A")")
```

```
            print("-----")
```

```
        }
```

```
    } catch {
```

```
        print("Error while fetching")
```

```
    }
```

```
}
```

2/ If fetch() was successful, then do something with the results

Filtering the Search Results

Search queries can be filtered by adding a *predicate* to the search request

* By default, the context.fetchRequest() function will always perform a SELECT * FROM _____

If you want to filter the results (eg: SELECT * FROM _____ WHERE _____), then you need to use something called an NSPredicate

```
@IBAction func fetchAll(_ sender: Any) {
    // 1. Create a fetch request object using Employee's fetchRequest() function
    let request:NSFetchRequest<Employee> = Employee.fetchRequest()

    // predicate (filters that you add to the search query to narrow down the results)
    // this predicate updates the query to be:
    //      SELECT * FROM employees where name == 'Carl'
    request.predicate = NSPredicate(format:"name == %@", "Carl")

    // 2. Initiate the fetch request
    do {
        let results:[Employee] = try self.context.fetch(request)

        print("Fetch succeeded")
        print("Number of results: \(results.count)")

        for employee in results {
            print("Name: \(employee.name ?? "N/A")")
            print("Date Hired: \(employee.date_hired ?? "N/A")")
            print("-----")
        }
    } catch {
        print("Error while fetching")
    }
}
```


Update Data

1/ Retrieve

2/ Use the data's class properties to update the data's values

3/ Call .save() on the context variable to persist the change

- Persisting the change can fail, so need to mark this call with a try and wrap it in do-catch

```
@IBAction func updatePressed(_ sender: Any) {
    // 1. Search for the employee you want to update (Abigail)
    let request:NSFetchRequest<Employee> = Employee.fetchRequest()
    request.predicate = NSPredicate(format:"name == %@", "Abigail")
    do {
        let results:[Employee] = try self.context.fetch(request)

        // retrieve the employee from the array
        let abigail = results.first!
        print(abigail.name)

        // 2. Update their data
        abigail.name = "Alex"
        abigail.date_hired = "2035-05-23"

        // 3. Save the results
        try self.context.save()

    } catch {
        print("Error while finding a matching employee OR during the update")
    }
}
```

Delete data

1/ Get a copy of the data you want to delete

2/ Call `.delete()` on the context variable. Pass in a reference to the data you want to delete
(From step #1)

- Does not require a try,do-catch

3/ Call `.save()` on the context variable. to persist your change

- Persisting the change can fail, so need to mark this call with a try and wrap it in do-catch

```
@IBAction func deletePressed(_ sender: Any) {
    // 1. Search for the employee you want to delete
    let request:NSFetchRequest<Employee> = Employee.fetchRequest()
    request.predicate = NSPredicate(format:"name == %@", "Alex")
    do {
        let results:[Employee] =
            try self.context.fetch(request)

        let alex = results.first!
        print(alex.name)

        // 2. Delete them
        self.context.delete(alex)

        // 3. Save the results
        try self.context.save()

        print("Delete success")
    } catch {
        print("Error while finding a matching employee OR deleting")
    }
}
```