

```

In [2]: # --- 1. Setup and Configuration ---
import warnings
warnings.filterwarnings("ignore")

import os
import sys
import pandas as pd
import numpy as np
from PIL import Image
from tqdm.auto import tqdm
import joblib

# PyTorch and Deep Learning Libraries
import torch
import torch.nn as nn
import torch.nn.functional as F
from torch.utils.data import TensorDataset, DataLoader
from transformers import AutoModel, AutoTokenizer
from efficientnet_pytorch import EfficientNet
from sklearn.metrics import classification_report, f1_score

# Set up paths and device
tqdm.pandas()

DATA_DIR = '../data/'
IMAGES_DIR = os.path.join(DATA_DIR, 'images')
RESULTS_DIR = '../results/'
MODELS_DIR = os.path.join(RESULTS_DIR, 'models')
os.makedirs(MODELS_DIR, exist_ok=True)

DEVICE = "cuda" if torch.cuda.is_available() else "cpu"
print(f"Using device: {DEVICE}")

# Feature dimensions
TEXT_DIM = 768 # DistilBERT CLS token
IMAGE_DIM = 1280 # EfficientNet-B0 final pooling
FUSION_DIM = TEXT_DIM + IMAGE_DIM # 2048
HIDDEN_DIM = 512
NUM_CLASSES = 1
BATCH_SIZE = 64
EPOCHS = 10
LEARNING_RATE = 1e-4

```

Using device: cpu

```

In [3]: # --- 2. Load DataFrames ---
# Assuming your data files (created in the setup notebook) are available
try:
    df_train = pd.read_csv(os.path.join(DATA_DIR, 'multimodal_train.tsv'), sep='
    df_val = pd.read_csv(os.path.join(DATA_DIR, 'multimodal_validate.tsv'), sep='
    df_test = pd.read_csv(os.path.join(DATA_DIR, 'multimodal_test_public.tsv'),

    print(f"Loaded datasets: Train={len(df_train)}, Val={len(df_val)}, Test={len

    # Filter to only keep rows where image was successfully downloaded
    def filter_downloaded(df):
        return df[df['id'].progress_apply(lambda x: os.path.exists(os.path.join(

    df_train_filtered = filter_downloaded(df_train)

```

```

df_val_filtered = filter_downloaded(df_val)
df_test_filtered = filter_downloaded(df_test)

print(f"Filtered datasets: Train={len(df_train_filtered)}, Val={len(df_val_f

except FileNotFoundError:
    print("ERROR: Data files not found. Please run the setup/download notebooks
    sys.exit()

```

Loaded datasets: Train=564000, Val=59342, Test=59319

```

100% |████████████████████████████████████████████████████████████████████████████████| 564
000/564000 [00:14<00:00, 38550.13it/s]
100% |████████████████████████████████████████████████████████████████████████████████| 5
9342/59342 [00:02<00:00, 24385.05it/s]
100% |████████████████████████████████████████████████████████████████████████████████| 5
9319/59319 [00:02<00:00, 25251.34it/s]

```

Filtered datasets: Train=27046, Val=28358, Test=28330

```

In [4]: # --- 3. Feature Extractor Initialization ---
def initialize_feature_extractors():
    # Text Model (DistilBERT)
    text_model = AutoModel.from_pretrained("distilbert-base-uncased").to(DEVICE)
    text_tokenizer = AutoTokenizer.from_pretrained("distilbert-base-uncased")
    text_model.eval()

    # Image Model (EfficientNet-B0)
    image_model = EfficientNet.from_pretrained('efficientnet-b0').to(DEVICE)
    image_model._fc = nn.Identity()
    image_model.eval()

    return text_model, text_tokenizer, image_model

TEXT_MODEL, TEXT_TOKENIZER, IMAGE_MODEL = initialize_feature_extractors()
print("Feature Extractors Initialized.")

```

Loaded pretrained weights for efficientnet-b0

Feature Extractors Initialized.

```

In [5]: # --- 4. Feature Extraction Helpers ---

def extract_text_feature(text: str) -> np.ndarray:
    inputs = TEXT_TOKENIZER(text, return_tensors="pt", truncation=True, padding=
    with torch.no_grad():
        outputs = TEXT_MODEL(**inputs)
        # Use CLS token feature
        feature = outputs.last_hidden_state[:, 0, :].cpu().numpy() # [1, 768]
    return feature

def extract_image_feature(image_path: str) -> np.ndarray:
    try:
        image = Image.open(image_path).convert("RGB").resize((224, 224))
    except:
        # Fallback for corrupted images, return array of NaNs or zeros
        return np.zeros((1, IMAGE_DIM), dtype=np.float32)

    image_tensor = torch.tensor(np.array(image)).permute(2, 0, 1).float() / 255.
    # Simple normalization
    image_tensor = (image_tensor - 0.5) / 0.5
    image_tensor = image_tensor.unsqueeze(0).to(DEVICE)

```



```

"""
Multi-Layer Perceptron (MLP) for classifying fused features.
"""
def __init__(self, input_dim=FUSION_DIM, hidden_dim=HIDDEN_DIM, output_dim=N):
    super(DeepFusionNetwork, self).__init__()

    # 1. Initial Projection Layer (Input: 2048 -> Hidden: 512)
    self.fc1 = nn.Linear(input_dim, hidden_dim)

    # 2. Regularization
    self.dropout = nn.Dropout(p=dropout_rate)

    # 3. Final Classification Layer (Hidden: 512 -> Output: 1)
    self.fc2 = nn.Linear(hidden_dim, output_dim)

    def forward(self, features):
        # features shape: (B, 2048)
        x = F.relu(self.fc1(features))
        x = self.dropout(x)
        # Output is raw logits, Binary Cross Entropy with Logits will handle the
        logits = self.fc2(x)
        return logits

# Convert NumPy arrays to PyTorch tensors
X_train_t = torch.tensor(X_train, dtype=torch.float32)
y_train_t = torch.tensor(y_train, dtype=torch.float32).unsqueeze(1)

X_val_t = torch.tensor(X_val, dtype=torch.float32)
y_val_t = torch.tensor(y_val, dtype=torch.float32).unsqueeze(1)

# Create DataLoaders
train_dataset = TensorDataset(X_train_t, y_train_t)
train_loader = DataLoader(train_dataset, batch_size=BATCH_SIZE, shuffle=True)

val_dataset = TensorDataset(X_val_t, y_val_t)
val_loader = DataLoader(val_dataset, batch_size=BATCH_SIZE, shuffle=False)

```

In [7]: # --- 6. PyTorch Training Loop ---

```

model = DeepFusionNetwork().to(DEVICE)
criterion = nn.BCEWithLogitsLoss() # Combines Sigmoid and Binary Cross Entropy
optimizer = torch.optim.Adam(model.parameters(), lr=LEARNING_RATE)

def evaluate(model, data_loader, criterion):
    model.eval()
    total_loss = 0
    all_preds = []
    all_labels = []
    with torch.no_grad():
        for X_batch, y_batch in data_loader:
            X_batch, y_batch = X_batch.to(DEVICE), y_batch.to(DEVICE)
            logits = model(X_batch)
            loss = criterion(logits, y_batch)
            total_loss += loss.item() * X_batch.size(0)

        # Convert logits to probabilities and then to predictions
        probs = torch.sigmoid(logits)
        preds = (probs > 0.5).int().cpu().numpy()
        all_preds.extend(preds)
        all_labels.extend(y_batch.int().cpu().numpy())

```



```

        preds = (probs > 0.5).int().cpu().numpy()
        all_preds.extend(preds)
        all_labels.extend(y_batch.int().cpu().numpy())

all_preds = np.array(all_preds).flatten()
all_labels = np.array(all_labels).flatten()

report = classification_report(all_labels, all_preds, target_names=['FAKE', 'REAL'])
print("\nClassification Report:\n")
print(report)

# Save the final report
report_path = os.path.join(RESULTS_DIR, 'deep_fusion_report.txt')
with open(report_path, 'w') as f:
    f.write(report)
print(f"\nFinal classification report saved to {report_path}")

```

--- Evaluating Best DFN Model on Test Set ---

Test Loss: 0.3461

Test Macro F1-Score: 0.8379

Classification Report:

	precision	recall	f1-score	support
FAKE	0.8703	0.8798	0.8750	17314
REAL	0.8078	0.7939	0.8008	11016
accuracy			0.8464	28330
macro avg	0.8391	0.8369	0.8379	28330
weighted avg	0.8460	0.8464	0.8462	28330

Final classification report saved to ../results/deep_fusion_report.txt