

AGENTS.md: instructions for AI coding agents working on Typographics Art This file tells AI agents (and humans) how to work in this repository.
Read it before changing anything. ## The project in one paragraph Typographics Art sets a given text, character for character and in order, so that only the typography
of each glyph (size, weight, colour; width is an optional axis, off by default) changes and the page forms a picture. The text must stay real, extractable text. The three rules in
`docs/technique.md` are the contract of the project; no change may break them. ## Layout - `src/`: the library. Pure modules (`layout.js`, `tone.js`, `color.js`, `render.js`,
`typeset.js`, `fonts.js`, `options.js`, `lorem.js`) run in Node and browsers. `browser.js` needs a DOM: font measurement, image reading, PNG output. - `index.html`:
the landing page. `app.html`: the generator (served at `/app.html`). `work.html`: the three views of a work (Art, Read, Machine). `gallery.html` `examples.ht `404.html`:
gallery, one-pager examples, error page. - `cli/`: command-line tools that drive headless Chrome over the DevTools protocol
(`core.mjs`, `render.html`), the renderer `tg-art.mjs`, the one-pager `onepage.m `tg-secret.mjs` or hidden messages, gallery and asset builders. - `api/`: the paid
one-pager API server (see `api/README.m . - `scripts/`: builders for the website, the samples, `about/`, and the measurement scripts behind `docs/`. - `gallery/`: the 15 works, their photos and
`works.conf .json`. - `examples/`: one-pagers (31) of laws, declarations and AI nstructions with their published source texts. - `samples/`: sample texts for the generator, generated by `scripts/build-samples.mjs`. -
`demo/moby- ck/`: the demonstrator (whole book as a poster) with its proof report. - `docs/`: measurements the definition of the technique and the rules of the project. - `about/`: the generated single-file
description for AI assistants (do not edit by hand; run `node scripts/build-about.mjs`). - `benchmark/`: the test document for `docs/ai-benefit.md`. - `assets/`: brand assets. - `test/`: Node's built-in test
runner, no dependencies ## Rules 1. **No runtime dependencies and no build step for the library.** Plain ES modules only. The website needs `node scripts/build-site.mjs`, which is only used to deploy it.
Pages load no third-party resources; vendored files are listed in `NOTICE.md` 2. **Fidelity is ested, not assumed.** Any change to layout, rendering or export must keep `isFaithful()`
true and the text extractable from HTML, SVG and PDF. Add or update a test in `test/` for every behaviour change. 3. **Pure logic stays pure.** New algorithms go into the pure modules with tests that run
under `node --test`. Only code that needs a DOM goes into `browser.js`, `cli/render.h ` or the pages. 4. **Measure before claiming.** Numbers in the documentation (fidelity, OCR rates, timings) must
come from a script or test in this repository. Update them when the code changes. 5. **Keep outputs honest.** Generated reports must state their method and limits. Never hide nstructions in tiny text: a one-pager always shows its
title, and its full text must be the declared document. 6. **English** for code, comments, commits and documentation German translations live in `README.de.m and the app's dictionary. ## Commands ```sh npm test # all tests, a few
seconds npm run dev # needs Python 3; landing page at http://localhost:8080, generator at /app.html node cli/tg-art.mjs img.jpg --text t.txt -o out.pdf node cli/onepage.m doc.pdf --title "Title" -o onepage.pdf npm run
gallery # re-render gallery (needs Chrome) node examples/bu # re-render examples (needs Chrome and MuPDF; qpdf optional, shrinks the PDFs) node scripts/build-a out.mjs #
regenerate about/typogr (and its PDF;

need Ch and MuPDF) `` ##
Tools - Node: library >= 20; CLI >= 22 (it needs the global `WebSocket` API >= 22. (`node:sq e`). - Chromi m or Chrom (`CHR ME PATH` if it is not found),
MuPDF (`mutool`), qpdf. - For specific scr pts pando and tesser t (`sc i-b efit.mj `); Py n 3 wi h pypdf, pymup and pd mi r.s x (`scr ts/extract eck.py` Py n
3 for `npm run dev`. ## Before you open a pull re es - `npm test` passes. - For visual cha es ren at least one gallery work or example and oo at it. - The changelog has
an entry if users will notice the chang - The pull re est says what changed and how you check it.