AGENTS.md: instructions for AI coding agents working on Typographics Art This file tells AI agents (and humans) how to work in this repository. Read it before changing anything. ## The project in one paragraph Art sets a given text, character for character and in order, so that only the typography (weight, width, size, colour) forms a picture. The text extractable. The three rules in project: no change `docs/technique.md` (`layout.js`, `tone.js`, `typeset.js`, `fonts.js`, `color.js`, `image.js`) must stay real, `browser.js` needs a headless Chrome over DOM: font may break them. ## `options.js` the web app and measurement, command-line tools that drive `demo/mobydick/`: the reading, PNG output. - `gallery.html` gallery for typographicart.org. - and asset builders. - `render.html` the DevTools protocol the renderer `tg-art.mjs`, the one-pager `onepage.mjs`, gallery Node's built-in demonstrator (whole report. - `examples/`: one-pagers of laws, declarations and AI instructions. - `test/`: test runner, no dependencies. ## and no build step.** Plain ES modules only. CDN scripts in pages must be pinned to an exact version with a Subresource Integrity hash. 2. **Fidelity is to layout, rendering or export must keep `isFaithful()` true and the text extractable from Add or behaviour change. 3. **Pure logic stays pure.** New algorithms go into the HTML, SVG and PDF. --test`. Only code that `cli/render.html` or the **Measure** before claiming.** Numbers in the pure modules with tests that come from a script or pages. 4. changes. 5. **Keep** outputs honest.** Generated documentation (fidelity, OCR run under `node test/` instructions in tiny text: Update them when the **Declared** document. 6. **English** for code, rates, timings) must German translations shows its title, and its Commands test # all tests, under a second reports must state their method and limits. Never hide live in `README.de.md` app's dictionary. ```sh npm run gallery # comments, and documentation; ## npm run dev # app at http://localhost:8000 node cli/tg-art.mjs img.jpg --text t.txt -o out.pdf node cli/render.mjs --title "Title" -o doc.pdf node cli/onepage.mjs --title "Title" -o onepage.pdf npm run gallery # re-render examples (needs Chrome and MuPDF) optional, shrinks the PDFs) ``` ## Before you open a pull request - `npm test` passes. - For visual changes, render at least one gallery work or example and look at it. - The change has an entry if users will notice the change. - The pull request says what changed and how you checked it.