he summary dro
and re-reads
rieved facts, too
r input, the result
eliability The orche
el chooses within a
resume. Persist the
arse form of this; a pe
d result wit an id, and s
cks. A tool o model that k
s. Bound th arallel calls t
ields its finished parts. Fail
el is a replaceable part. Cho
ger model for the one hard ste
human or a judge pick the bes
before you ommit. ### The mo
et, and by da hat may leav
Route by mea ate per task c

step **neede**d
h **turn. It survives**
m **for the answer. Measu**
ersible action. Recompute
s software. Make its contro
he graph dec between no
after every st tool call: wh
p **checkpoint**
what can be
ps failing is cu
ach model a
e mode: a str
e it to the ta
, a cheaper one for the routin
Different models have differ
router One component o
ur premises). Change
let a failed chec

e against a fixed template — g , done, pendin
ction and survives a resta
hat fills it on real runs; too
hat is cheap and may hav
tructure explicit in code a
s. "Where are we" always
h node, wha
minism and replay. The
ogged trace with the too
t retried forever, and a f
est. Fan-out without a l
ches the user before it es
he model. -
steps. Mixed-model pipel
nt strengths; trying a few
s the choice of model for
uting in one place; the pip
e. ### Escalation **Two** escala
on paths, bo

ions, blocke , open questions — never "summa e this". - Scrat
wn durabl memory; keep it small and structured. - C
the largest tem and the first to trim. - Peist or recomp
ent conten of a file, a listing, a status. A cached fact
verable. - A state machine or a graph. We the contro
ure mode: ontrol flow hidden in prompts (when you are
udget stop re the last chec
s far as the m pin the mod
how you deb . - Timeouts,
ed result, a fi e, a human. N
ming and part tream output
he final — an ommit, a sen
valuation. Ma ed only one c
ve (a design oice: compa
is best. - Me red capabilit
draft, reaso chooses by
ailure mode: a he cheaper on
a stronger m

ng-notes file
dget. **Allocate the w**
ersist what is expensive
ut **a changing world is a st**
w as named states and tran
ne, say DONE at no code c
point instead rting over. T
version and t mpling setti
verywhere. P
me the fallba
d persist par
. ## 9. Mod
el. - Escalat
s on the same task in isolat
uality, tokens, and calls ac
context, tool use, imag
e sends hard cases t
is its check or ir

on eq o
eps a d a de d- ett pa h fo
that spli s into sub oa s (ui
sh low; p ss bri return
c n tr s a

bo o s s
hat fails - Open-end
a f atur , un a cam
dence. - A chain of

n
wor with an u known path
ign): p n-based. A ead pla
ecialists (ntake, hen b lling,
it done. - ev al a id tes
dge

-ag
search qu
and ands
en techni
ion, ix a bu ,
, then hecks
hando f. ach
d si n ag
t (

wo g a
estigate a system): an au onomous gen loop he
d retrie ; gu rd its sin le poin o failure. - A l e j
ent picks who is next; guard against going i
ft dopy, opo p ns a alle f -o t e
f, ub

w en ed ue, it
ers, ac s, ve ifies, and peats u til d e, b un
pa able areas tha one ad can not : hie ar
y specialists build ng o e olving p ure (an i
prom ts t e a hu an j e c e t -
a s